

# FluidSynth Plugin

*Simple Wrappers Around the **FluidSynth** Library as  
DAW Plugin and Pedantic Command Line Processor*

**Author:** Dr. Thomas Tensi  
**Date:** 2023-01-09  
**Version:** 0.3  
**Platforms:** VST3 on Windows x64,  
VST3/AU on MacOSX (x86\_64)  
VST3 on Linux (x86\_64)

# Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Overview . . . . .	3
1.2	Acknowledgements . . . . .	4
<b>2</b>	<b>Installation of the FluidSynth-Plugins</b>	<b>6</b>
<b>3</b>	<b>Description of the FluidSynth-Plugins</b>	<b>7</b>
3.1	General Remarks . . . . .	7
3.2	Supported FluidSynth Settings . . . . .	8
3.3	Using the FluidSynthPlugin . . . . .	12
3.4	Using the PedanticFluidSynthConverter . . . . .	13
3.5	Restrictions . . . . .	17
<b>4</b>	<b>Regression Test</b>	<b>20</b>
<b>5</b>	<b>Notes on the Implementation</b>	<b>22</b>
5.1	Overview . . . . .	22
5.2	Building the Plugins . . . . .	22
5.3	Internal Documentation . . . . .	24
5.4	Available Build Targets . . . . .	25
5.5	Debugging . . . . .	25
	<b>Bibliography</b>	<b>27</b>

# Chapter 1

## Introduction

### 1.1 Overview

**FluidSynth** [FluidSynthDOC] is one of the most prominent open source MIDI players. It is reasonably flexible, delivers a good audio quality and is available for the typical platforms. A common scenario is to use it for either rendering live MIDI data on some audio device or converting MIDI files into audio files by command-line batch processing.

Basis of **FluidSynth** are the so-called *soundfonts*. Soundfonts contain sampled instruments together with envelope and modulation definitions and other descriptive settings. It is easy to find really usable ones in the internet and also several of those cover all general MIDI instruments (for example, the FluidR3\_GM.sf2).

So when using **FluidSynth** in a command-line driven context all is well. But when you want play around with settings for **FluidSynth** interactively in a DAW, you need some DAW plugin rendering audio from MIDI as close as possible to the original command-line `fluidsynth`.

So far there is no such thing to exactly emulate FluidSynth in a DAW context. There were some previous efforts like Alexey Zhelezov's FluidSynthVST [FluidSynthVST] or Birch Labs' JuicySFPlugin [JuicySFPlugin], but those are a bit tricky to use and support for them is unclear. But the main point is that even though they rely on the **FluidSynth** library, they **do not exactly reproduce an external fluidsynth rendition of some MIDI data**. Reasons for that will be explained below.

The reason for being picky about the exact rendering is as follows: my scenario is a command-line based rendering of notation videos for a band (the LilypondToBandVideoConverter [LTBVC]). Part of that chain is `fluidsynth`, but I want to experiment interactively with settings in a DAW to optimize the audio and then have a faithful reproduction of the external rendering

pipeline within the DAW.

So the first component of this package is a DAW plugin called “**FluidSynth-Plugin**”. It has a simplistic interface where you specify a soundfont, several fluidsynth settings and possibly a MIDI program to be selected by putting text data in a text field. Then you are able to convert an incoming MIDI stream in a DAW to audio using the **FluidSynth** library.

But when playing around with that plugin some inexplicable differences to the command-line **FluidSynth** occurred. Even when using innocent soundfonts (without chorus and other modulators), sample playback in the plugin and the command-line player were not absolutely identical. Analysis and contact with the **FluidSynth** team revealed that in that program MIDI events are quantized onto some processing raster in the millisecond range while the plugin quantizes them onto the smallest time unit: the sample raster itself.

So, for example, for a sample rate of 44.1kHz this 64 sample offset might lead to a time difference of more than 1ms between events in the DAW and in an external tool chain. You cannot hear this, but of course this leads to significant differences in the rendered audio (for example, when doing a spectrum analysis). In section 3.5 we will see that although the plugin feeds the events with sample raster precision to the **FluidSynth** library some inevitable internal rasterization happens there.

Another tool mitigates the rasterization by the player of **FluidSynth**. That second component of this package is a simplistic but pedantic command-line converter called “**PedanticFluidSynthConverter**”. It converts a MIDI file into a WAV file, is also based on the fluidsynth library and does the same sample-exact event feeding into that library as the plugin. Hence it should produce identical results when some circumstances are guaranteed (see section 3.5).

When using both components (command-line and DAW) on the same MIDI data they produce audio output with a difference of less than -200dBFS in a spectrum analysis.

Those components are available for the x86-64 architecture in Windows, MacOS and Linux with the plugin having either VST3 (Windows, Linux) or AU format (MacOS).

All the code is open-source; hence you can check and adapt it to your needs (see chapter 5).

## 1.2 Acknowledgements

This project is a derivative work based on the foundations laid by the **FluidSynth** community.

My thanks go to the FluidSynth team: Peter Hanappe, Conrad Berhörster, Antoine Schmitt, Pedro López-Cabanillas, Josh Green, David Henningsson and Tom Moebert. Without your effort this would not have been possible!

## Chapter 2

# Installation of the FluidSynth-Plugins

The installation is as follows:

1. Copy the plugins from the appropriate subdirectory for your platform of `_DISTRIBUTION/targetPlatforms` directory in [FluidSynthPlugin] into the directory for VST or AU plugins of your DAW.
2. If helpful, you can put this documentation pdf file contained in subdirectory `doc` and test files in subdirectory `test` (see section 4) somewhere.
3. When installing the plugins on MacOSX, note that those are **not signed**; so you have to explicitly remove the quarantine flag from them (e.g. by applying the command `sudo xattr -rd com.apple.quarantine «vstPath»`).
4. When installing the plugin and program on Windows, they require the so-called Microsoft Visual C++ Redistributable library `??`. Very often this is already installed on your system; if not, you have to install it from the Microsoft site.
5. Restart your DAW and rescan the plugins. You should now be able to select the `FluidSynthPlugin`.
6. The command-line version `PedanticFluidSynthConverter` can be put in an arbitrary location for executables. Ensure that the dynamic libraries in its directory are also placed appropriately.

Note that the plugin directory and the directory of the `PedanticFluidSynthConverter` contain a dynamically linked library version of `FluidSynth` as well as related libraries. You can easily exchange those libraries for more current versions.

# Chapter 3

## Description of the FluidSynth-Plugins

### 3.1 General Remarks

As mentioned in the introduction this package provides tools written in C++ for emulating FluidSynth bit-exactly: a plugin called “FluidSynthPlugin” and a very precise command-line clone of FluidSynth called “Pedantic-FluidSynthConverter”.

The term “bit-exactly” is a bit misleading: because the tools considered (including FluidSynth) have different execution environments (with some data conversions and roundings involved), absolute identical outputs are unreasonable. But what can be achieved is that they are identical to a degree that cannot be heard. If you analyze the spectrum of the difference signal and this difference lies below some assumed threshold, this will be good enough. The threshold here is -200dBFS which is about 100dB below the noise level of a CD.

So both tools render MIDI data similarly to FluidSynth and identical to each other. And when there is no difference in rasterization the difference between the audio from those tools is identical — up to that precision — to FluidSynth.

So why is there a difference between FluidSynthPlugin and FluidSynth in some cases? The differences come from the fact that FluidSynth shifts MIDI events onto some broader raster for audio samples while both programs presented here place an event onto a sample position. This means that there is a slight delay in audio in FluidSynth and original audio and emulated do not cancel out when subtracted.

Figure 1 shows the problem: when an event occurs the waveform is started in FluidSynthPlugin at the next sample position while it starts in FluidSynth




Figure 1: Rasterization Problem in FluidSynth

at the 64 sample raster. As can be easily seen, the difference is not zero, but some other complex waveform.

Note that this is not the complete truth as will be discussed in section 3.5: some shifting will still be done in the underlying `FluidSynth` library.

## 3.2 Supported FluidSynth Settings

Both programs support a subset of settings from `FluidSynth`. It is a subset, because, for example, all settings related to driver selection are omitted: those do not make any sense in the context of these programs.

The supported settings are shown in figures 2, 3 and 4 (with short explanations taken from from `[FluidSynthSettings]`).

Besides the standard settings from `FluidSynth` there are two special settings available: **soundfont** and **program**.

Note that the specified soundfont path must be an *absolute path*, because it is impossible for the plugin to find out the path of the enclosing project in the



Parameter	Description	Type
<code>synth.chorus.active</code>	tells whether chorus will be added to the output signal	boolean
<code>synth.chorus.depth</code>	specifies the modulation depth of the chorus	float
<code>synth.chorus.level</code>	specifies the output amplitude of the chorus signal	float
<code>synth.chorus.nr</code>	sets the voice count of the chorus	integer
<code>synth.chorus.speed</code>	sets the modulation speed in Hz	float
<code>synth.default-soundfont</code>	default soundfont file to use by the program	string
<code>synth.dynamic-sample-loading</code>	tells whether samples are loaded to and unloaded from memory whenever presets are being selected or unselected for a MIDI channel	boolean

Figure 2: Common Synthesizer Settings for `FluidSynthPlugin` and `PedanticFluidSynthConverter` (Part 1)

DAW and then use a relative path specification. Normally this should not be a problem — because soundfonts are often located in a specific directory in a system —, but it somewhat impedes portability of a DAW project containing this plugin.

But you can use environment variables in the path specification enclosed by `${` and `}`, for example `${soundFontDirectory}`.

### 3.2. SUPPORTED FLUIDSYNTH SETTINGS

---

Parameter	Description	Type
<code>synth.gain</code>	gain applied to the final or master output of the synthesizer	float
<code>synth.midi-bank-select</code>	defines how the synthesizer interprets bank select messages	string
<code>synth.min-note-length</code>		integer
<code>synth.overflow.age</code>	tells how event age is accounted for in a voice overflow situation	float
<code>synth.overflow.important</code>	another parameter for voice overflow handling	float
<code>synth.overflow.important-channels</code>	comma-separated list of MIDI channel numbers that should be treated as “important” by the overflow calculation	string
<code>synth.overflow.percussion</code>	overflow priority score to be added to voices on a percussion channel	float
<code>synth.overflow.released</code>	overflow priority score added to voices that have already received a note-off event	float
<code>synth.overflow.sustained</code>	overflow priority score added to currently sustained voices	float
<code>synth.overflow.volume</code>	overflow priority score added to voices based on their current volume	float

Figure 3: Common Synthesizer Settings for `FluidSynthPlugin` and `PedanticFluidSynthConverter` (Part 2)

Parameter	Description	Type
<code>synth.polyphony</code>	defines how many voices can be played in parallel	integer
<code>synth.reverb.active</code>	tells whether reverb will be added to the output signal	boolean
<code>synth.reverb.damp</code>	sets the amount of reverb damping	float
<code>synth.reverb.level</code>	sets the reverb output amplitude	float
<code>synth.reverb.room-size</code>	sets the room size (i.e. amount of wet) reverb	float
<code>synth.reverb.width</code>	sets the stereo spread of the reverb signal	float
<code>synth.sample-rate</code>	sample rate of the audio generated by the synthesizer	float
<code>synth.verbose</code>	tells whether synthesizer will print out information about the received MIDI events to stdout	boolean

Figure 4: Common Synthesizer Settings for `FluidSynthPlugin` and `PedanticFluidSynthConverter` (Part 3)

Parameter	Description	Type
soundfont	gives the path to the soundfont and may contain environment variables enclosed by <code>\${</code> and <code>}</code>	string
program	gives the program to use as the default; format is <code>bankNumber:programNumber</code> where counting for both numbers starts at zero	string

Figure 5: Additional Settings in `FluidSynthPlugin` and `PedanticFluidSynthConverter`




Figure 6: FluidSynthPlugin User Interface

## 3.3 Using the FluidSynthPlugin

The “FluidSynthPlugin” is a MIDI instrument in a DAW converting incoming MIDI input into an outgoing audio stream.

The configuration of the plugin is done via a very simplistic interface: a multiline edit field can be used for command entry.

In this multiline field the FluidSynth commands from figures 2 to 5 can be written. Figure 6 shows how the user interface of the plugin looks like.

Each line may contain a FluidSynth setting or a definition for **soundfont** or **program**. A setting consists of a key string (like e.g. **synth.reverb.active**), an equal sign and a value appropriate for the setting. Leading and trailing blanks are ignored; strings are given without quotes and float values must have a decimal point.

When data is entered in the multiline edit field, it changes its background from grey to white. This signifies that the data has not yet been registered by the plugin. To achieve this the **Confirm** button has to be pressed: the data is checked and then used by the underlying FluidSynth synthesizer.

When the check fails, an error message is given and the edit field is still in edit mode. Note that only the first error encountered is reported, so you have to incrementally correct the settings. For example, in figure 7 the soundfont path seems to be incorrect: this has to be corrected before any other error will be analyzed.

Note that also some error message is displayed, when the fluidsynth library cannot be found by the plugin. In that case please make sure that the



Figure 7: Error Message in FluidSynthPlugin

installation has been correctly done (the plugin expects its dynamic libraries in the directory of the plugin vst3 file).

For the VST3 plugin there is a problem caused by the VST3 API that has two consequences:

- Each program change in the MIDI event stream is converted into a preset change. Unfortunately those changes might not be correctly sequenced with the notes in the stream and hence notes immediately following that change (within a few milliseconds) might still use the previous sound.
- Even though the `FluidSynthPlugin` and its underlying library would support it, it is not possible to use multiple MIDI channels with different sounds within a single plugin instance. **Each plugin instance can only play a single preset at a time.**

### 3.4 Using the PedanticFluidSynthConverter

The `PedanticFluidSynthConverter` is merely a functionally reduced clone of `FluidSynth`, but with a special property: it places MIDI events onto the raster given by the sample rate.

Hence similarly to `FluidSynth`, the `PedanticFluidSynthConverter` is a command-line program. But the converter does not have to do real-time processing, so the list of its options is reduced. On top of that it only supports a conversion from a MIDI file into an audio WAVE file.

### 3.4. USING THE PEDANTICFLUIDSYNTHCONVERTER

---

The supported command line options are shown in figure 8 and 9. Any parameter not belonging to an option is interpreted as a file name. Files with their names ending in `.sf2` or `.sf3` are considered to be sound fonts, files with their names ending in `.mid` are considered to be MIDI files.

Hence the command line is

```
fluidSynthFileConverter [options] midifile soundfontfile  
                        -F wavefile
```

So, for example, the command line

```
fluidSynthFileConverter -g 1.0 -R 0 test.mid FluidR3\_GM.sf2  
                        -F test.wav
```

produces a wave file “test.wav” from MIDI file “test.mid” using sound font “FluidR3\_GM.sf2” with reverb turned off and gain set to unity.

Option	Description
-a --audio-driver=«name»	audio driver to use (IGNORED)
-C --chorus	turn the chorus on or off [0 1 yes no, default = on]
-c --audio-bufcount=«count»	number of audio buffers (IGNORED)
-d --dump	dump incoming and outgoing MIDI events to stdout (IGNORED)
-E --audio-file-endian	audio file endian (IGNORED: always little endian)
-f --load-config	load and execute a configuration file
-F --fast-render=«file»	name of target WAVE file (REQUIRED)
-G --audio-groups	define the number of LADSPA audio nodes (IGNORED)
-g --gain	set the master gain $0 < \text{gain} < 10$ , default = 0.2
-h --help	print out help summary
-i -no-shell	don't read commands from the shell (IGNORED)
-j -connect-jack-outputs	connect jack outputs to the physical ports (IGNORED)
-K -midi-channels=«num»	number of midi channels [default = 16] (IGNORED)
-L -audio-channels=«num»	number of stereo audio channels [default = 1] (IGNORED)
-l -disable-lash	don't connect to LASH server (IGNORED)
-m -midi-driver=«label»	name of the midi driver to use (IGNORED)

Figure 8: Command Line Options for PedanticFluidSynthConverter (Part 1)

Option	Description
<code>-n</code> <code>-no-midi-in</code>	don't create midi driver to read MIDI input events (IGNORED)
<code>-O</code> <code>-audio-file-format</code>	audio file format for fast rendering [double float s8 s16 s24 s32, default = s16]
<code>-o</code>	define a setting, -o name=value; see FluidSynth for details
<code>-p</code> <code>-portname=«label»</code>	set MIDI port name (IGNORED)
<code>-q</code> <code>-quiet</code>	do not print informational output
<code>-R</code> <code>-reverb</code>	turn reverb on or off [0 1 yes no, default = on]
<code>-r</code> <code>-sample-rate</code>	set the sample rate
<code>-s</code> <code>-server</code>	start FluidSynth as a server process (IGNORED)
<code>-T</code> <code>-audio-file-type</code>	audio file type for fast rendering (IGNORED: always WAV)
<code>-v</code> <code>-verbose</code>	print out verbose info about midi events (synth.verbose=1)
<code>-V</code> <code>-version</code>	show version of program
<code>-z</code> <code>-audio-bufsize=«size»</code>	size of each audio buffer (IGNORED)

Figure 9: Command Line Options for PedanticFluidSynthConverter (Part 2)



## 3.5 Restrictions

### No Timelocking Available

Often audio effects produce the same output for the same input, but sometimes effects behave differently in time, technically they are *time-variant*.

An example of the former is a filter: it does not care *when* a signal arrives, it always reacts in the same way. An example of the latter is a modulated effect like e.g. a tremolo: it produces a different sound for different event times because the modulation is normally in another phase.

Hence when looking at the behaviour at a specific point in time, those time-variant effects would behave differently when the effect start time is varied.

Of course, a sample player — like **FluidSynth** — very often is also time-variant. It is not, when only a sample playback is triggered, because the audio will be the same whenever you start its playback. But when there is some modulation happening (for example, caused by a chorus effect) the effect is time-variant: the audio output produced will not be the same for different playback start times unless the modulation is in some way synchronized.

So for some externally generated audio snippet with modulation at an arbitrary position in a DAW project, a modulation by a corresponding plugin would only be congruent by accident: typically it is out of phase. The reason for that is that plugins normally start their modulation when playback begins. This means technically the phase  $0^\circ$  of the modulation is on the time of playback start.

Figure 10 show that situation for an example. We assume that an amplitude modulation occurs in a soundfont and we have inserted an externally rendered audio snippet (e.g. generated by **FluidSynth**) into the DAW starting at time  $t_{\text{fragment}}$  into an audio track. Now the playback in the DAW is assumed to start at time  $t_{\text{play}}$ . As one can easily see, the modulation for the externally processed fragment (that just puts a modulation on the raw sample data) has its phase  $0^\circ$  exactly at time  $t_{\text{fragment}}$ . However, the internal effect in the DAW has its phase  $0^\circ$  at time  $t_{\text{play}}$  (see also the red dots on the respective tracks marking the phase  $0^\circ$  positions). This would lead to massive differences between externally and internally generated audio.

But it could be rectified by defining for the internal effect *at which point in time the modulation phase should be  $0^\circ$*  (so-called “time-locking”). If you set this time offset parameter to  $t_{\text{fragment}}$ , the modulations will be synchronous (as you can see when comparing the second with the lowest track). Of course, the effect starts at  $t_{\text{play}}$ , but its modulation phase is shifted such that it reaches phase  $0^\circ$  exactly at  $t_{\text{fragment}}$ .




Figure 10: Deviation in Modulation between External and Internal Generation and Timelocking

While this method would lead to perfect reproduction of the external rendering, it is not feasible for the `FluidSynthPlugin`. There is no direct way to set the modulators in the underlying `FluidSynth` library to a specific phase. As a workaround when  $t_{\text{fragment}} < t_{\text{play}}$  one could reset all modulators at playback start and first silently have the synthesizer process samples for a duration of  $t_{\text{play}} - t_{\text{fragment}}$  to bring its modulators to the correct phases before then putting out the “real” samples. But this is tedious, takes a lot of processing time and also does not solve the problem of having the playback starting before the fragment start time.

So there is no good solution for that.

When you need a bit-exact reproduction of externally rendered audio by the `FluidSynthPlugin`, some workaround has to be made as follows:

- The selected instrument(s) in the soundfont must not contain any (free-running) modulators.
- Chorus must be deactivated (e.g. by setting `synth.chorus.active` to “0”).

#### Forced Rasterization by FluidSynth

As mentioned in the introduction the important difference between using the standard `FluidSynth` from the command-line versus from a DAW is that there is a forced rasterization to 64 samples’ intervals.

Unfortunately this rasterization is not just done by `FluidSynth` when communicating with audio drivers or its file renderer, but also done internally by the `fluidsynth` synthesizer in the library. The length of the smallest unit for which `FluidSynth` can make state changes and does buffering is a constant called `FLUID_BUFSIZE` and this is fixed to the value 64.

So what can we do?

- We could recompile the `FluidSynth` library and set this value to 1. This would on the one hand lead to a performance penalty, but would on the other hand provide sample-exact processing.

I did not choose that option, because I wanted to use the *stock* `FluidSynth` library on all platforms.

- As an alternative we could do some intelligent buffering to adapt in the DAW to the 64-sample raster of the external rendering regardless of the start time. I played around with that, but it also did not work out well: for example, when looping in the DAW there is no way to flush the buffer within the `FluidSynth` library and to reset the synthesizer: this is just not a use-case typical for applications of `FluidSynth` and hence it has not been provided in its API.

So we are out of luck.

But there is a workaround that helps in many situations: when your DAW allows to change the loop interval and also the play head position via its API one can *nudge all those positions onto the 64-sample raster*.

Since this heavily depends on the scripting facilities of a DAW, I have only provided a simple Lua script for the Reaper DAW in the `misc` subdirectory of the distribution called `ForceToFluidSynthRaster.lua`. When executed, it shifts the selection boundaries and the play head position onto the required raster.

It is even possible to provide some integral shift offset (e.g. when the externally rendered audio files do not start at time 0 in the DAW). This is done by setting the variable `sampleOffset` in the project notes to some integer value, e.g. by writing the following text:

```
sampleOffset = 20
```

# Chapter 4

## Regression Test

To test that the `FluidSynthPlugin` is really bit-identical to the `PedanticFluidSynthConverter` (and at least similar to the output of `FluidSynth`), a little test suite has been set up for checking DAW versus the command-line.

The suite assumes that command-line `FluidSynth` is installed in the search path of your operating system.

If so, a simple batch script generates — externally via the command line — audio files from three MIDI files and some simple sound font both with `PedanticFluidSynthConverter` and also `FluidSynth`. The batch script can be found in the `test` subdirectory and is called `makeTestFiles.bat` (for Windows) or `makeTestFiles.sh` (for MacOS and Linux).

Since there are so many DAWs available, it is hard to provide a test project for each of those. The distribution just contains a Reaper project referencing those rendered audio files in autonomous tracks (see figure 11). Adaption to other DAWs should be straightforward.

Besides the six externally rendered tracks there are three other tracks containing the MIDI file data and having a single `FluidSynthPlugin` effect converting MIDI to audio. Those instrument effects are configured with the exactly the same parameters as given in the batch file and hence correspondingly applied to the raw MIDI data.

When subtracting the rendered audio in Reaper and the externally rendered audio files from the `PedanticFluidSynthConverter`, they (almost) cancel out, because they use exactly the same scheduling of the MIDI events. This can be checked by a spectrum analyser in the master channel, which is shown in figure 12. It shows a noise floor of typically less than -100dB (also depending on the audio file bit depth).




Figure 11: Regression Test Setup in Reaper




Figure 12: Example Noise Floor for Regression Test in Reaper

# Chapter 5

## Notes on the Implementation

### 5.1 Overview

The implementation of the `FluidSynthPlugin` and the `PedanticFluidSynthConverter` is done in C++. The former relies on the JUCE library [JUCE] and both — of course — use the `FluidSynth` library. The sequencer from that library is not used, because it also has some event rasterization (independent from the inevitable internal rasterization of the library).

The *bit-exact reproduction* of the `PedanticFluidSynthConverter` (as well as `FluidSynth` itself) by the `FluidSynthPlugin` in a DAW is almost achieved (see section 4), but some restrictions have to be adhered to.

The complete source code of the `FluidSynthPlugin` and the `PedanticFluidSynthConverter` is open-source for easy review and adaptation. Currently there is only a tool chain for VST3 plugins under Windows 10, VST3 and AU plugins under MacOSX and VST3 under Linux, but in principle the code is easily portable to other plugin formats or platforms.

### 5.2 Building the Plugins

#### Preliminaries

In the GIT-project of `FluidSynthPlugin` (at [FluidSynthPlugin]) there is a build file for CMAKE to build the plugins for different platforms.

Minimum prerequisites for building are:

- a clone of the GIT-project at <https://github.com/prof-spock/FluidSynthPlugin>
- an installation of the audio framework JUCE [JUCE] with version 5 or

later,

- some C++ compiler suite for your platform (e.g. Visual Studio, XCode, clang or gcc), and
- an installation of the build automation platform CMAKE [CMAKE] with version 3.10 or later

For documentation generation you can *optionally* install:

- a  $\text{\LaTeX}$  installation — like e.g. MikTeX — (for the manual), and
- doxygen [DOXYGEN] and graphviz [GRAPHVIZ] for the internal program documentation

## Doing the Build

The full build process is started via CMAKE. It is recommended to do a so-called out-of-source-build for the FluidSynth-Plugins, that means, you define some build directory where all build activity is done.

The steps are as follows:

1. Define some build directory (lets say `_BUILD`) and change to it.
2. Find the path of the `CMakeList.txt` configuration file. Adapt the file `LocalConfiguration.cmake` accordingly to reflect the location of  $\text{\LaTeX}$  as well as the JUCE and the doxygen/graphviz installation.

3. Configure the build process via

```
cmake -S <pathTo>/CMakeList.txt -B . --config Release
```

4. Build all the plugins via

```
cmake --build . --config Release
```

5. Install the plugins into a architecture-specific subfolder in the `_DISTRIBUTION/targetPlatforms` directory and install also the documentation into the `_DISTRIBUTION` directory via

```
cmake --build . --config Release --target install
```




Figure 13: Example Namespace Page for Plugin from doxygen

## 5.3 Internal Documentation

In the github repository there is an extensive doxygen documentation available for the inner workings of the plugins at

<https://github.com/prof-spock/FluidSynthPlugin/tree/master/internalDocumentation/html>

with entry point

<https://github.com/prof-spock/FluidSynthPlugin/tree/master/internalDocumentation/html/index.html>.

Every public and private feature of all classes and data types is documented and can be analyzed in an HTML browser. Figure 13 gives an impression how such an HTML page looks like for the namespaces in FluidSynth-Plugins.

If you want to regenerate this documentation from the code, you need an installation of doxygen [DOXYGEN] and ideally also graphviz [GRAPHVIZ] on your computer. If you have that available, the generation can be done via the CMAKE chain as target `doxygenDocumentation` in the build directory:

```
cmake --build . --config Release \
      --target internalDocumentation
```

If the command completes, the documentation in the `internalDocumentation` subdirectory of the project is updated.



Target Name	Description
documentation	the complete project documentation
<code>←-- internalDocumentation</code>	the HTML doxygen documentation for the code
<code>←-- pdfDocumentation</code>	the PDF manual for the plugins
FluidSynthFileConverter	the program for the command line PedanticFluidSynthConverter
FluidSynthPlugins	the static libraries for the FluidSynth-Plugin
<code>←-- FluidSynthPlugins_Effect</code>	the static effect library for the FluidSynthPlugin
<code>←-- FluidSynthPlugins_VST</code>	the VST3 library for the FluidSynth-Plugin
<code>←-- FluidSynthPlugins_AU</code>	the AU libraries for the FluidSynth-Plugin (only on MacOSX)
SupportLibraries	the static libraries supporting the effects
<code>←-- JuceFramework</code>	the static library with utility classes from the JUCE framework

Figure 14: Available Build Targets for CMAKE

To trigger regeneration, it suffices to delete the file `internalDocumentation/html/index.html`.

## 5.4 Available Build Targets

Figure 14 shows the available CMAKE targets. They can be used as

```
cmake --build . --config Release --target XXX
```

where XXX is the target name.

## 5.5 Debugging

For debugging purposes, for both the `FluidSynthPlugin` and the `PedanticFluidSynthConverter` a debugging version is also available that does an extensive entry-exit-logging into the temp directory. Note that this debugging slows down processing extremely and produces large log files, but it helps to understand problems in case of errors. Figure 15 shows how a logging file looks like.

Every non-trivial function is logged there at least twice with timestamps: “»” indicates the entry of that function (possibly with information on the

## 5.5. DEBUGGING

---

```
>>Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.07): sampleRate = 44100.000000, samplesPerBlock = 1024
--Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.07): currentTime = 0 [samples]
>>MIDI.MidiEventConverter.prepareToPlay (220338.07): sampleRate = 44100.000000, samplesPerBlock = 1024
>>MIDI.MidiEventConverterDescriptor.changeSettings (220338.07): key = synth.sample-rate, value = 44100.000000
>>Libraries.FluidSynth.FluidSynthSettings.set (220338.07): key = synth.sample-rate, value = 44100.000000
--Libraries.FluidSynth.FluidSynthSettings.set (220338.07): kind = F, value = 44100.000000
<<Libraries.FluidSynth.FluidSynthSettings.set (220338.07): true
<<MIDI.MidiEventConverterDescriptor.changeSettings (220338.07): true
<<MIDI.MidiEventConverter.prepareToPlay (220338.07)
<<Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.07)
>>Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.getStateInformation (220338.10)
>>Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.settings (220338.10)
<<Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.settings (220338.10):
<<Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.getStateInformation (220338.10): settings =
>>Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.11): sampleRate = 44100.000000, samplesPerBlock = 512
--Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.11): currentTime = 0 [samples]
>>MIDI.MidiEventConverter.prepareToPlay (220338.11): sampleRate = 44100.000000, samplesPerBlock = 512
>>MIDI.MidiEventConverterDescriptor.changeSettings (220338.11): key = synth.sample-rate, value = 44100.000000
>>Libraries.FluidSynth.FluidSynthSettings.set (220338.11): key = synth.sample-rate, value = 44100.000000
--Libraries.FluidSynth.FluidSynthSettings.set (220338.11): kind = F, value = 44100.000000
<<Libraries.FluidSynth.FluidSynthSettings.set (220338.11): true
<<MIDI.MidiEventConverterDescriptor.changeSettings (220338.11): true
<<MIDI.MidiEventConverter.prepareToPlay (220338.11)
<<Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.11)
>>Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.11): sampleRate = 44100.000000, samplesPerBlock = 512
--Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.11): currentTime = 0 [samples]
>>MIDI.MidiEventConverter.prepareToPlay (220338.11): sampleRate = 44100.000000, samplesPerBlock = 512
>>MIDI.MidiEventConverterDescriptor.changeSettings (220338.11): key = synth.sample-rate, value = 44100.000000
>>Libraries.FluidSynth.FluidSynthSettings.set (220338.11): key = synth.sample-rate, value = 44100.000000
--Libraries.FluidSynth.FluidSynthSettings.set (220338.11): kind = F, value = 44100.000000
<<Libraries.FluidSynth.FluidSynthSettings.set (220338.11): true
<<MIDI.MidiEventConverterDescriptor.changeSettings (220338.11): true
<<MIDI.MidiEventConverter.prepareToPlay (220338.11)
>>Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.prepareToPlay (220338.11)
>>Main.FluidSynthPlugin.FluidSynthPlugin_EventProcessor.setStateInformation (220338.11)
```

Figure 15: Example for Logging File

argument values), “«” the exit of that function (possibly with the return value) and “--” indicates some intermediate information during the function processing. The logging data is hierarchical, hence you can see the function call structure in this file precisely.

All logging files go to the directory specified by the `temp` environment variable.

# Bibliography

- [CMAKE] Kitware, Inc.  
*CMAKE Build Automation System.*  
<http://cmake.org>
- [DOXYGEN] Dimitri van Heesch.  
*Doxygen - Generate Documentation from Source Code.*  
<https://www.doxygen.nl>
- [FluidSynthDOC] Tom Moebert et al.:  
*FluidSynth.*  
<http://www.fluidsynth.org>
- [FluidSynthSettings] Tom Moebert et al.:  
*FluidSynth - Synthesizer Settings Documentation.*  
[https://www.fluidsynth.org/api/settings\\_synth.html](https://www.fluidsynth.org/api/settings_synth.html)
- [FluidSynthVST] Alexey Zhelezov.  
*FluidSynth VST Plugin.*  
<https://github.com/AZSlow3/FluidSynthVST>
- [FluidSynthPlugin] Thomas Tensi.  
*FluidSynth-Plugins*  
<https://github.com/prof-spock/FluidSynthPlugin>
- [GRAPHVIZ] Ellson, John; Gansner, Emden; Hu, Yifan; North, Stephen et al.:  
*Graphviz - Open Source Graph Visualization Software.*  
<https://graphviz.org/>
- [JUICE] Raw Material Software Limited.  
*JUCE Audio Framework.*  
<https://www.juce.com>
- [JuicySFPlugin] Alex and Jamie Birch.  
*Juicy SF Plugin.*  
<https://github.com/Birch-san/juicysfplugin>

## BIBLIOGRAPHY

---

- [LTBVC] Thomas Tensi.  
*LilypondToBandVideoConverter — Converter from  
Written Music to Notation Videos.*  
<https://github.com/prof-spock/LilypondToBandVideoConverter>
- [REAPER] Cockos Incorporated.  
*Reaper Digital Audio Workstation.*  
<https://www.reaper.fm>
- [VCCLib] Microsoft.  
*Visual C++ Redistributable.*  
<https://learn.microsoft.com/cpp/windows/latest-supported-vc-redist>