\\wsl.localhost\Debian\home\joshua\csc228\cybersecurity\sql_cheat_sheet.md

SQL Quick Reference

SELECT — Read rows

```
SELECT * FROM customers;
SELECT name, email FROM customers WHERE (balance > 100 AND name = 'Bob');
SELECT name, email FROM customers WHERE (balance < 50 OR name = 'Alice');
SELECT * FROM customers ORDER BY balance DESC LIMIT 5;
```

DELETE — Remove rows

```
DELETE FROM customers WHERE id = 1;
DELETE FROM customers;       -- Removes ALL rows
```

UPDATE — Change rows

```
UPDATE customers SET balance = 500 WHERE id = 1;
UPDATE customers SET balance = balance + 50 WHERE id <> 1;
```

Common WHERE conditions

```
WHERE id = 1                      -- equal
WHERE id <> 1                     -- not equal
WHERE balance >= 100              -- comparison: > < >= <=
WHERE name LIKE 'A%'              -- starts with A
WHERE id IN (1, 2, 3)             -- one of several values
WHERE balance BETWEEN 50 AND 100
WHERE email IS NULL               -- missing value
WHERE balance > 0 AND id < 10     -- can combine AND / OR
```

Remember: UPDATE or DELETE without WHERE affects **every row**.