

# Dynamic Catalog

Converting your HTML prototype to PHP and MySQL

CSCI 210 Web Programming

Melissa Holmes

# Before you begin:

You should have the following:

- HTML prototype of your catalog (styled with CSS)
  - You can change and fine-tune this as you move forward, if you like
- MySQL database with a Products table
- These instructions assume the Products table has these columns:
  - ProductID (unique to each product)
  - ProductName
  - ProductDesc
  - ImagePath (this is the folder/file in your website where the image is stored)
  - Price
  - Keywords, Color, other attributes that apply to your specific project

# Example HTML Prototype

[Home](#) [News](#) [Contact](#) [About](#)

## Pumpkin Catalog



Fresh Pumpkin

Add to Cart



Old Pumpkin

Add to Cart



Another Pumpkin

Add to Cart

# Prototype HTML Code

- This is the code for the black box with the three pumpkins, not the whole page. CSS is not included.
- Identify what will be pulled from the database, i.e. ProductID, ProductName, ImagePath

```
<div class="catalogItems">
  <div class="product">
    <img src = "images/pumpkin.jpg"><br>
    Fresh Pumpkin<br>
    <button>Add to Cart</button>
  </div>

  <div class="product">
    <img src = "images/pumpkin.jpg"><br>
    Old Pumpkin<br>
    <button>Add to Cart</button>
  </div>

  <div class="product">
    <img src = "images/pumpkin.jpg"><br>
    Another Pumpkin<br>
    <button>Add to Cart</button>
  </div>
</div>
```

In this example, the Image Path and Product Name will be replaced with PHP code. These values will be pulled from the Products table in the database.

# Products Table

| ProductID | ProductName     | ProductDesc                     | Color    | imagePath          | Price |
|-----------|-----------------|---------------------------------|----------|--------------------|-------|
| P1        | Fresh Pumpkin   | Fresh pumpkin for sale!         | orange   | images/pumpkin.jpg | 10.99 |
| P2        | Old Pumpkin     | Very old pumpkin, may have mold | green    | images/pumpkin.jpg | 1.99  |
| P3        | Another Pumpkin | A magic pumpkin                 | changing | images/pumpkin.jpg | 100   |

# PHP / Database Overview:

- Begin with the HTML prototype; be sure the filename has the php extension.
- Include the dbconnect.php file. See the notes on Canvas and W3Schools. This is the same as in user authentication and user registration.
- Query the Products table for all rows:  

```
SELECT * FROM Products;
```
- Insert php code for the values identified in the prototype.

# PHP Code Example:

This is the code used to print all the products that exist in the Products table, using the format in the HTML prototype.

```
<?php
    $sql = "SELECT * FROM Products";
    // Execute the SQL query
    $result = $conn->query($sql);

    // Display the results
    if ($result->num_rows > 0) {

        // Output data of each row
        while($row = $result->fetch_assoc()) {

?>
// notice how PHP and HTML code are used together
    <div class="product">
        <img src = "<?php echo $row['imagePath'] ?>"><br>
        <?php echo "Fresh Pumpkin<br>" ?>
        <button>Add to Cart</button>
    </div>
<?php
    }
    } else {
        echo "No Products existP";
    }
?>
```

# W3Schools Resource

- This page describes how to query a table and display all of the resulting rows:
- [https://www.w3schools.com/php/php\\_mysql\\_select.asp](https://www.w3schools.com/php/php_mysql_select.asp)



# More development

- This tutorial describes how to turn your HTML prototype into a dynamic catalog, with data displayed from the database.
- The “Add to Cart” button doesn’t do anything – implementation instructions and code are in the in the Shopping Cart instructions on Canvas.
- The catalog should also have Search and/or Filter capabilities, which are described in the Search / Filter slides.