

Implementing the Cart

CSCI 210 Web Programming

Melissa Holmes

What is the cart?

- The cart, or shopping cart, is a temporary area where customers store the products they want to buy.
 - Products are placed in the cart by clicking the Add to Cart button in the catalog.
 - When the customer clicks an Order button on the cart page, the items will be copied from the Cart into the Orders table.
- The cart can be implemented various ways: using a database table, session variables, or even cookies.
- These slides describe how to create the shopping cart using a database table.

Before you begin, you should have....

- A working Catalog page. The “Add to Cart” button should be present, but doesn’t need to be functional yet.
- A database with:
 - The Customers table with a CustomerID;
 - The Products table with a Product ID; and
 - The Orders table with CustomerID and ProductID for each item the customer orders.
 - As described in *The BackEnd* module, each item that is ordered by the customer will be represented by a row in the table.
 - If you are experienced in database design, feel free to create a more complex design. However, it is not required for this project.
- Session variables set up to capture CustomerID when the customer logs in.

Steps:

1. Create the Cart table.
 - See screenshot on the next page
 - Notes about how the table is used:
 - When the user clicks the *Add to Cart* button, it will copy the CustomerID and the ProductID into a row in the Cart table.
 - When the user clicks the *Order* button in the cart, the rows in the Cart table will be copied into the Orders table, AND the rows will be deleted from the Cart table.
2. Write the *Add to Cart* script for the button on the Catalog page. This should insert `$_Session['CustID']` and the ProductID into the Cart table. Example code is provided on Canvas.
3. Write the *Order Items* script for the button on the Cart page.

The Cart Table

CustID	ProdID
13	P1
13	P2
23	P2
23	P3

The Cart table should have the CustID and ProductID. These columns should have the same length and data type as the Orders, Customers and Products tables. The Customer and Product should already exist, i.e. in the example, Customers 13 and 23 should already exist in the Customers table; and Products P1, P2 and P3 should exist in the Products table

This table should be a subset of the Orders table, which is illustrated below.

The Orders Table

OrderID	CustID	ProductID	OrderDate
125ABD	13	M1	2026-02-26
ABC333	13	P1	2026-04-01
ABC333	13	P2	2026-04-01

The Orders table should have the CustID and ProductID. These rows will be copied into the Orders table when the user clicks “Order Items.”

Add to Cart Button



The call to the JavaScript function is called with the button's onclick method.

```
<html>
<head>

<script>
function addToCart(productID) {
    alert(productID);
    document.location.href = "cart.php?" + productID;
}
</script>
</head>
<body>

<?php
$prodID = "ABC123";    //test value. Replace with the actual product ID.
echo "<button onclick=\"addToCart('" . $prodID . "')\">Add to Cart</button>";
?>

</body>

</html>
```

addToCart is a JavaScript function, which appears within <script> tags in the head of the document. The function is passed productID, creates an alert (a pop-up - -you can delete this after testing), and opens the cart.php page. The productid is passed to cart.php on the querystring, and may be retrieved by the cart by using the \$_GET superglobal.

Important Note: This code is not stand-alone. It must be incorporated into your Dynamic Catalog page.

Adding a row to the Cart table

Write a PHP script to add a row to the cart table. These are the steps:

1. CustomerID should already be stored in a session variable (login)
2. ProductID should be passed in using the script on the previous page. This will come from the Catalog page.
3. Write an INSERT query to insert CustomerID and ProductID into the Cart table.

Note: this can all happen on the Cart page (cart.php) or you can write an in-between script that doesn't actually display anything. The JavaScript function will pass the ProductID to the appropriate .php page.

Order Items in Cart

- The goal is to copy the data in the Cart (for the current customer) into the Orders table.
- Refer to the slide with the screenshots of the Cart and Orders table.
- Create an OrderID. This can be a random number or some set of characters created from, say, part of the username and part of the data.
- Store the current data in a variable.
- Do one of the following:
 - Loop through all rows in the Cart table and insert them into the Orders table one at a time; OR
 - Use the INSERT INTO SELECT statement
https://www.w3schools.com/mysql/mysql_insert_into_select.asp

Shopping Cart Icon with Number of Items

- This is an extra that may be implemented if desired.
- Add the icon to your header, and count the items in the cart using a query.
- Replace the number (plain HTML) with PHP code that runs the query and displays the number.
- See the files in cart.zip posted on Canvas.