Hybrid Quantum–Classical Pauli-Correlator Architecture for Image Reconstruction

Sparsho Chakraborty[1] and Siddhartha Patra[2*]

[1]School of Basic Sciences, Department of Physics, Indian Institute of Technology Bhubaneswar, Odisha, India.
[2*]Centre for Quantum Engineering, Research and Education, TCG CREST, Kolkata, India.

*Corresponding author(s). E-mail(s): siddhartha.patra@tcgcrest.org;
Contributing authors: 25ph05023@iitbbs.ac.in;

Abstract

We introduce the Pauli-Correlator Autoencoder (PCAE), a hybrid quantum–classical architecture for image reconstruction. PCAE assembles matrix-product-state patch features, a variational quantum circuit exposing a Pauli-correlator latent space, two-dimensional Fourier positional encoding, a learnable Hamiltonian energy term, and a classical decoder into a single pipeline. Two instantiations, PCAE1D and PCAE2D, realise chain and grid interaction graphs. Group-averaged observable pooling makes the PCAE2D feature map exactly equivariant to the eight symmetries of the square. The contribution is this specific assembly rather than any ingredient in isolation. Across six real image datasets, per-image-trained PCAE2D models reconstruct with peak signal-to-noise ratio (PSNR) between 25.8 and 41.6 decibels. A position-only ablation of the same decoder also achieves strong fits on these sampled images. On held-out CIFAR-10 images, a closed-form surrogate of the PCAE2D feature map stays within 1 decibel of several simpler classical feature maps. However, held-out generalisation of the trained circuit is not yet established. Five fitted checkpoints are replayed on superconducting quantum hardware without retraining, reaching 25.90 to 31.52 decibels. Under a fixed linear readout, an affine-readout argument and a synthetic test show that a pair-observable channel is necessary for targets built from distant-patch products. The learned Hamiltonian energy gives an interpretable readout of the trained representation. However, in a single-seed ablation the energy term lowers reconstruction quality. We make no claim of quantum advantage. The results establish PCAE as a working hybrid architecture that fits varied images and runs on quantum hardware at the six-qubit scale.

Keywords: Quantum image processing, Tensor networks, Variational quantum algorithms, Pauli observables, Group-equivariant representations, Quantum hardware pilot

1 Introduction

Hybrid quantum–classical models are now often proposed for vision tasks. The aim is to obtain representations with a favourable inductive bias. Such models can use entanglement, physically motivated regularisers, or tensor-network structure, which standard convolutional networks do not have (Cerezo et al. 2021; Tilly et al. 2022; Preskill 2018). The variational quantum eigensolver and its later variants use the fact that physical Hamiltonians split into local terms. This allows them to build shallow circuits suited to the problem (Cerezo et al. 2021; Tilly et al. 2022; Bauer et al. 2020). Quantum image processing gives several ways to store pixel values directly in qubits. These range from amplitude-style encodings (Le et al. 2011) to basis-encoded pixel values (Zhang et al. 2013). Basic image operations on these encodings have also been developed (Chakraborty et al. 2022; Zhou et al. 2017; Yao et al. 2017). Tensor-network methods work well as compressed representations of structured classical data, such as images (Cirac et al. 2021; Latorre 2005; Han et al. 2018; Stoudenmire and Schwab 2016; Ran et al. 2020; Guala et al. 2023) and particle-physics events (Araz and Spannowsky 2022). Hybrid models have also been applied to related imaging tasks, such as tomographic reconstruction (Haga 2024; Nau et al. 2023) and ghost imaging (Zhai et al. 2025). These solve inverse problems from indirect measurements. PCAE instead encodes and decodes a known image. Quantum convolutional and capsule networks are further examples (Slabbert and Petruccione 2024; Cong et al. 2019; Hur et al. 2022; Liu et al. 2023). PCAE focuses on the combination of a Pauli-correlator latent space, enforced group-equivariant pooling, and a physically motivated energy term.

We introduce the Pauli-Correlator Autoencoder (PCAE1D/PCAE2D), which combines these ingredients into a single architecture with three properties studied jointly. The first is a *Pauli-correlator latent space*, in which measured VQC observables rather than a raw quantum state form the representation handed to a classical decoder, following quantum-enhanced feature maps (Havlíček et al. 2019). The second is an *exact, numerically verified D_4-equivariant observable-pooling construction*, which group-averages the observable grid over the eight symmetries of the 4×4 patch grid rather than motivating symmetry through architecture choices alone. This follows group-equivariant classical vision (Cohen and Welling 2016; Bronstein et al. 2021) and the equivariant-quantum-neural-network line that formalises symmetry-embedding constructions for variational circuits (Meyer et al. 2023; Nguyen et al. 2024; Schatzki et al. 2024; West et al. 2024, 2025). The third is a *learnable Hamiltonian energy term*, used as an auxiliary training objective and read out as an interpretable diagnostic, with full nearest-neighbour $XX/YY/ZZ$ sectors in PCAE1D and grid-edge ZZ terms in PCAE2D. Table 10 contrasts these properties against classical, adversarial, and standard quantum autoencoder baselines.

Novelty relative to the nearest hybrid-vision architectures

PCAE's closest architectural relatives are three hybrid quantum-vision patterns already established individually in the literature.

Register-based quantum autoencoders (Romero et al. 2017; Wang et al. 2024; Asaoka and Kudo 2025) encode an image's pixel amplitudes directly into a qubit register and train a trash-qubit fidelity objective. PCAE feeds the circuit only quantum-inspired, pre-compressed MPS patch features, not raw pixel amplitudes. It hands the decoder measured Pauli correlators rather than register amplitudes or a fidelity score. PCAE is an autoencoder in the usual encoder–decoder sense. It maps each image patch to a measured observable vector and decodes it back to pixels. It does

not compress a quantum state. Closer to PCAE, a hybrid autoencoder has placed a circuit between a classical encoder and decoder and passed its per-qubit $\langle Z \rangle$ values to the decoder as the latent vector (Sakhnenko et al. 2022). However, it uses neither MPS input nor pairwise correlators.

Quantum-kernel vision models (Havlíček et al. 2019; Beaulieu et al. 2022) embed an input into a quantum feature space and read out a scalar kernel value consumed by a classical kernel method. PCAE reads out an explicit vector of local and pairwise Pauli expectation values as a latent representation for a trained decoder, and adds enforced group-equivariant pooling and a Hamiltonian energy term that a kernel construction has no analogue for.

Tensor-network (TN) circuit classifiers (Guala et al. 2023; Stoudenmire and Schwab 2016; Han et al. 2018) use MPS structure either as a standalone classical model or as a template for a shallow quantum circuit trained for classification. PCAE uses MPS compression only as a quantum-inspired *preprocessing* step that sets a separately trained VQC's rotation angles, and targets per-image reconstruction rather than classification. Further, an MPS feature extractor has been placed before a VQC and trained end to end with it for classification (Chen et al. 2021). The MPS in PCAE is instead a fixed SVD compression.

PCAE's contribution is the assembly of MPS preprocessing and the three properties above in one pipeline (Table 10). Section 5.2 examines how the individual ingredients recur across this literature.

Contributions

PCAE1D/PCAE2D combines MPS patch features, a six-qubit VQC, a 19–27-dimensional Pauli-correlator vector, 2D Fourier positional encoding, a graph-Hamiltonian energy term, and a classical decoder. An exact, numerically verified D_4-equivariant observable-pooling construction makes the PCAE2D observable map equivariant to the eight symmetries of the square, to numerical precision (Section 4.7). The guarantee follows from Reynolds group averaging over the D_4 orbit (Puny et al. 2022) rather than from anything quantum, and the same construction gives the same exactness for a purely classical feature map. We report it as a design property of the pooled observable map.

Identically configured per-image fitting experiments cover six real image datasets (Section 4.1). On held-out CIFAR-10, a closed-form surrogate of the PCAE2D observable map meets the ± 1 dB equivalence criterion against five of seven resource-matched classical/ablated feature maps, under two one-sided tests (TOST) with Holm correction. It clearly outperforms the two random-feature null controls. The trained circuit itself falls about 1 dB below a matched random-latent control on held-out images at the tested budget (Section 4.3). Five fitted checkpoints are replayed on IBM hardware without retraining and decoded from hardware-measured observables (Section 4.4). A noise/shot-budget sweep and repeated execution across backends support the pilot (Sections 4.5–4.6). In a leakage-audited protocol with a fixed linear readout, pair observables are necessary when the target depends explicitly on distant-patch products (Section 4.8).

The appendices give the training settings, the matched-budget ablation, further held-out results and the hardware methodology.

2 Pauli-Correlator Autoencoder: Architecture

PCAE treats each spatial patch as a finite spin state and compresses it as a matrix product state (MPS). A variational quantum circuit (VQC) then measures a fixed set of Pauli observables, which a classical multi-layer perceptron (MLP) decodes back into pixels. A learnable graph-Hamiltonian

energy term regularises training. Parameterised Hamiltonian learning approaches treat the Hamiltonian as the primary learned object (Shi et al. 2023). In PCAE it is instead an auxiliary objective alongside the reconstruction loss, and its learned energy is read out as a diagnostic.

Problem statement.

Given an image x partitioned into non-overlapping patches $\{x_p\}_{p=1}^{P}$, PCAE learns a per-patch reconstruction map. Each patch is compressed to a quantum-inspired MPS feature vector $\phi_{\mathrm{MPS}}(x_p)$, a learned linear layer sets the VQC rotation angles, and measuring a fixed set of Pauli observables yields the correlator feature map $\Phi(x_p) \in \mathbb{R}^d$ ($d = 27$ for PCAE1D, 19 for PCAE2D). With $n = 6$ qubits, bond set $\mathcal{E}$, and c measured pair channels per bond,

$$d = 2n + c|\mathcal{E}| = \begin{cases} 2(6) + 3(5) = 27, & \text{PCAE1D } (ZZ, XX, YY \text{ on a 5-bond chain}), \\ 2(6) + 1(7) = 19, & \text{PCAE2D } (ZZ \text{ on 7 grid edges}), \\ 2(6) + 1(5) = 17, & ZZ\text{-only ablation control.} \end{cases} \tag{1}$$

All PCAE1D and PCAE2D circuit results use $d = 27$ and $d = 19$. A classical decoder D_θ maps $\Phi(x_p)$, together with a Fourier positional encoding $\pi(p)$, back to a reconstructed patch $\hat{x}_p = D_\theta\big(\Phi(x_p), \pi(p)\big)$. Training minimises the pixel-reconstruction loss with the graph-Hamiltonian energy term $E(\cdot)$ as an auxiliary regulariser,

$$\mathcal{L}(\theta) = \frac{1}{Pm} \sum_{p=1}^{P} \big\| x_p - \hat{x}_p \big\|_2^2 \; + \; \lambda \frac{1}{P} \sum_{p=1}^{P} E\big(\Phi(x_p)\big), \tag{2}$$

where m is the number of pixels per patch, so the first term is the mean squared pixel error, and the second term is the mean graph-Hamiltonian energy over patches and λ sets its weight (Section 5.1 reports its effect). The energy of patch p is

$$E\big(\Phi(x_p)\big) = \sum_{(u,v)\in\mathcal{E}} \sum_{\alpha\in S} J_{uv}^{\alpha} \, \langle \sigma_u^{\alpha} \sigma_v^{\alpha} \rangle_p, \tag{3}$$

where $\mathcal{E}$ is the bond set of Eq. (1), $S = \{x, y, z\}$ for PCAE1D and $S = \{z\}$ for PCAE2D, and the couplings J_{uv}^{α} are learned. The shared pipeline is

$$\begin{aligned} \text{Image} &\to \{\text{Patches}\} \to \text{MPS} \\ &\to \text{46-D/22-D Feature} \to \text{6-D Vector} \\ &\to \text{27-D/19-D Latent} \to \text{Decoder} \\ &\to \text{Reconstruction.} \end{aligned} \tag{4}$$

Why MPS features.

Treated as an amplitude-encoded quantum state, a patch of n sites has a coefficient tensor with 2^n entries. Matrix-product-state factorisation instead represents it as a chain of small tensors bounded by a fixed bond dimension χ. This is a compact, singular-value-controlled compression whose entanglement-entropy profile is already known to track image compressibility (Latorre 2005;

Table 1 The two executed configurations. Both use six qubits and the same decoder. They differ in patch size and in the measured observable set.

	PCAE1D	PCAE2D
Benchmark	*Monalisa*	multi-dataset
Image size	256×256	32×32 (native)
Patch size	64×64	8×8
MPS sites	12	6
Local X/Z expectations	24	12
Nearest-neighbour ZZ	11	5
Bipartite entropy features	11	5
MPS feature vector	46-D	22-D
Measured observables	27-D	19-D
local Z, local X	6, 6	6, 6
pair terms	5 each ZZ, XX, YY	7 grid-edge ZZ
Fourier positional vector	8-D	4-D

Stoudenmire and Schwab 2016), and whose local expectations and correlations are cheap features that do not require a full state-preparation circuit.

Why a Pauli-correlator latent space rather than a raw quantum state.

Handing the classical decoder a fixed vector of measured Pauli expectation values, instead of full state tomography, keeps the quantum-to-classical interface at a size linear in the qubit count, on the bounded-degree graphs used here, rather than exponential readout cost. The execution cost also grows with the number of measurement settings and the shots per setting. It also follows the measured-observable-as-feature pattern used by quantum-enhanced feature maps generally (Havlíček et al. 2019) and by projected quantum kernels built from local reduced density matrices (Huang et al. 2021). This choice is what makes the interpretability diagnostics of Section 5.1 and the training-dynamics diagnostics of Section 4.9 possible, since a full state vector would not expose a comparably compact, physically meaningful summary.

Why a grid rather than a chain interaction topology for PCAE2D.

Aligning the six-qubit interaction graph with the 2×3 patch-neighbour adjacency, rather than an arbitrary linear chain, gives the latent a two-dimensional coupling pattern. The D_4 pooling of Section 4.7 does not depend on this choice. It acts by permuting the 4×4 grid of patches in an image, and a 2×3 graph has no 90° rotation symmetry of its own. PCAE1D's chain topology is the control without a grid. It is used to measure what the grid adds (Section 5.3).

Two preprocessing configurations were executed, one per topology. Both follow the same three stages. Each image is first divided into sixteen non-overlapping patches. Every patch is then ℓ_2-normalised and sequentially SVD-compressed to a matrix product state of bond dimension $\chi = 4$. Finally, the local expectations, nearest-neighbour correlations and bipartite entropy features of that state are read off as the quantum-inspired MPS feature vector. The two configurations differ only in the sizes involved, which Table 1 lists in full. The 2^n pixel values of a patch ($n = 6$ for 8×8, $n = 12$ for 64×64) are flattened in row-major order and reshaped into an order-n tensor




Fig. 1 The PCAE1D (top) and PCAE2D (bottom) variational ansätze, ~~exactly as executed~~ **as built for execution, before transpilation** (encoding R_X rotations, positional R_Y rotations, then two entangling layers of R_Z-R_Y-R_Z single-qubit rotations with a CNOT ring for PCAE1D or fixed grid-edge CNOTs for PCAE2D). Both circuits were rebuilt gate-for-gate in Qiskit and validated against the original PennyLane training circuit before use in the hardware pilot of Section 4.4.

with binary indices, so each index is one site of dimension 2. The tensor is compressed with the `compress` method of quimb (Gray 2018) at maximum bond dimension χ. With its default settings, the compressed state is in right-canonical form, with the orthogonality centre on the first site. The features are expectation values and Schmidt spectra of the compressed state, so they do not depend on its canonical form. The entropy feature of each cut is computed from the Schmidt probabilities p_k of that cut, which are the squared singular values. The implementation squares them a second time and renormalises them, $q_k = p_k^2 / \sum_j p_j^2$, and returns $-\sum_k q_k \ln q_k$. This feature agrees with the von Neumann entropy $-\sum_k p_k \ln p_k$ for a product cut and for a flat Schmidt spectrum, but not in general. All models in this paper were trained with this feature. In the multi-dataset runs of Section 4.1, 10^{-4} is added to every pixel before normalisation, so that all-zero patches, such as MNIST background, can be normalised. The offset enters only the MPS input. The decoder is still trained to reconstruct the unmodified patch. The remaining stages are common to both. A learned linear layer compresses the MPS feature vector to six circuit angles, one per qubit. After the circuit is executed, a two-hidden-layer MLP (128 and 256 units) maps the measured observables together with the Fourier positional vector back to a single greyscale patch. The positional encoding follows established use as a spatial inductive bias in classical generative vision models (Xu et al. 2021). Fourier features of this kind also help coordinate-based networks fit fine image detail (Tancik et al. 2020). During training the circuit is simulated exactly. Unless otherwise stated, training used additive zero-mean Gaussian noise with standard deviation 0.01 on the observable vector. Artificial Gaussian noise was not added during evaluation or hardware replay. Finite-shot estimates enter only in the hardware replay and the noisy simulation of Sections 4.4–4.6. Figure 1 shows the exact PCAE1D and PCAE2D ansatz circuits. These were rebuilt in Qiskit for the hardware pilot of Section 4.4, and numerically verified against the training-time PennyLane circuit before use.

Table 2 PCAE variants tested in this paper.

Variant	Topology	Latent dim.	Symmetry
PCAE1D	6-qubit chain	27-D	None (control)
PCAE2D	2×3 grid	19-D	D_4-motivated only
D_4-pooled PCAE2D	2×3 grid, pooled	19-D	D_4-equivariant (exact)

Table 2 summarises the tested variants. PCAE1D uses a linear 6-qubit chain (5 nearest-neighbour bonds, 27-D observable vector). PCAE2D arranges the same 6 qubits on a 2×3 lattice matching patch-boundary adjacency (19-D latent signature). A D_4-pooled PCAE2D variant (Section 4.7) group-averages the observable grid over the eight symmetries of the 4×4 patch grid, $\Phi_{D_4}(x) = \frac{1}{8} \sum_{g \in D_4} P_g^{-1} \Phi(gx)$, which is equivariant by construction. Each circuit has two entangling layers, with 12 CNOTs for PCAE1D and 14 for PCAE2D before transpilation (~~Appendix D~~ **Figure 1**).

3 Experimental Setup

The reconstruction results in Sections 4.1, 4.2 and 4.4–4.6 use single-image fitting, the protocol developed for PCAE on *Monalisa*. A fresh model is optimised directly on its target image, with no held-out split. These results therefore measure per-image fitting and reconstruction capability. The hardware pilot replays the resulting fitted checkpoints on real devices without retraining. The symmetry and restricted pair-observable diagnostics use closed-form feature maps and the separate protocols stated in their respective sections. The training-dynamics readouts of Section 4.9 are reported as an interpretability diagnostic, with their scope set by the negative control given there. Held-out generalisation and component necessity are evaluated under the resource-matched statistical protocol, using a closed-form surrogate of the PCAE2D observable map (Section 4.3). All settings report MSE and PSNR $= 20 \log_{10}(1/\sqrt{\text{MSE}})$. Image settings additionally report SSIM. Gradient-trained PCAE models were optimised using full-batch Adam, with learning rates 3×10^{-3} for PCAE1D and 4×10^{-3} for PCAE2D and Hamiltonian-loss weight $\lambda = 0.01$. We used 200 optimisation steps for the *Monalisa* and CIFAR-10 hardware-checkpoint fits, 100 steps for the six-dataset same-set fits, and 90 steps for the topology comparison. The *Monalisa* run used seed 42 and the topology comparison used seeds $\{0, 1, 2\}$. Seeds were not recorded by the six-dataset or PCAE2D hardware-checkpoint drivers. Circuit rotation parameters were initialised independently from $\mathcal{U}(0, \pi)$, and Hamiltonian couplings from $0.1\,\mathcal{N}(0, 1)$. The linear projection and decoder layers used PyTorch's default initialisation. The software environment and the per-experiment settings are given in Appendix A.

4 Results

4.1 Reconstruction across six real image datasets

For each image, we trained a fresh PCAE2D model using non-overlapping 8×8 patches (16 patches/image, 100 optimisation steps). The sample covers CIFAR-10 (Krizhevsky 2009), MNIST (LeCun et al. 1998), Fashion-MNIST (Xiao et al. 2017), and the PathMNIST, BloodMNIST, and PneumoniaMNIST subsets of MedMNIST v2 (Yang et al. 2023). Table 3 reports mean PSNR

Table 3 PCAE2D same-set reconstruction across six real image datasets (per-image trained, 100 steps, mean ± std over sampled images). SSIM is computed globally over each image. The position-only ablation is the same decoder trained with all 19 observable inputs set to zero, on the same images and patch layout, with the same learning rate and 100-step budget. It uses seed 0 for every image. The PCAE2D seeds were not recorded, so the two are not paired by initialisation.

		PCAE2D		Position-only ablation	
Dataset	n images	PSNR (dB)	SSIM	PSNR (dB)	SSIM
CIFAR-10	3	37.75 ± 2.38	0.9986 ± 0.0003	42.98 ± 8.54	0.9991 ± 0.0008
MNIST	3	25.77 ± 2.23	0.9783 ± 0.0116	25.95 ± 2.31	0.9796 ± 0.0101
Fashion-MNIST	3	34.55 ± 3.05	0.9980 ± 0.0006	33.70 ± 0.49	0.9968 ± 0.0026
PathMNIST	3	36.86 ± 2.11	0.9118 ± 0.0627	35.49 ± 1.92	0.8904 ± 0.0655
BloodMNIST	2	36.57 ± 2.36	0.9922 ± 0.0063	34.67 ± 3.98	0.9833 ± 0.0151
PneumoniaMNIST	2	41.60 ± 0.98	0.9985 ± 0.0006	47.28 ± 1.04	0.9996 ± 0.0002

between 25.8 and 41.6 dB (SSIM 0.91–1.00). The architecture trains end to end and fits varied image structures under a common per-image protocol. A position-only ablation of the same decoder also fits these sampled images (Table 3). It has a higher mean PSNR on three of the six datasets, and is more than 5 dB higher on CIFAR-10 and PneumoniaMNIST. Table 3 therefore establishes fitting feasibility, but not a need for the observable channel. Evaluation-time substitutions show that trained models are sensitive to their observable inputs (Section 4.4). The D_4 construction and the restricted pair-observable diagnostic establish separate properties of the representation (Sections 4.7 and 4.8). This protocol is per-image fitting, in the same sense as implicit neural representations, which fit one network to one image or scene (Ulyanov et al. 2020; Sitzmann et al. 2020; Tancik et al. 2020; Mildenhall et al. 2020; Dupont et al. 2021; Strümpler et al. 2022). Quantum versions of this idea fit a single signal or image with a variational circuit (Zhao et al. 2024; Fujihashi and Koike-Akino 2026; Lizzio Bosco et al. 2026). The closest of these, QIREN, is a quantum coordinate network aimed at a fitting advantage over classical Fourier networks (Zhao et al. 2024). PCAE is instead a patch autoencoder with a measured-correlator bottleneck, and it aims at a practical hybrid pipeline whose quantum part is the measured observable vector. These results therefore measure fitting capacity. Generalisation to held-out images is tested in Section 4.3. A compression claim would also need a bit rate, which we do not report (Dupont et al. 2021; Strümpler et al. 2022).

4.2 Scope of per-image fitting

A model optimised on one image is specific to that image. In this single-seed test, PCAE2D with 8×8 patches is trained on *Monalisa* alone for 100 steps and then evaluated, without further training, on Michelangelo's *Hand of God*. Zero-shot transfer to *Hand of God* reaches 8.31 dB PSNR, with SSIM 0.1044. Extending training to include *Hand of God* for another 100 steps recovers 28.63 dB, with SSIM 0.9858. The per-image results above therefore measure per-image optimisation and reconstruction capability. Section 4.3 tests the held-out case directly.

4.3 Held-out comparison with a closed-form surrogate

The results above measure per-image fitting. A separate question is whether PCAE's feature map improves reconstruction on real, *held-out* images under a resource-matched multi-seed protocol. This comparison uses a closed-form surrogate of the PCAE2D observable map, so that many seeds and controls can be run. The surrogate combines 18 local patch statistics, six products of local-feature pairs that stand in for the pairwise ZZ correlators, and eight positional features. It does not evaluate the circuit. It is specified by hand and is not fitted to the trained circuit. Thus, the term has a different meaning here from the classical surrogates of Schreiber et al. (2023), which are derived from a trained quantum model. The main results are summarised below, including the equivalence tests of Table 4. Each of five split seeds fits the readout on six CIFAR-10 images and evaluates it on four disjoint held-out images, so each mean covers 20 held-out reconstructions.

On held-out CIFAR-10, the raw/local linear control reaches 18.80 ± 1.42 dB, against the PCAE2D surrogate's 18.30 ± 1.62 dB. Aggregating held-out images within each split gives a PCAE2D-minus-control difference of -0.50 dB, with bootstrap 95% CI $[-0.76, -0.29]$ dB and Wilcoxon $p = 0.0625$ at $n = 5$ seeds (Efron and Tibshirani 1993; Wilcoxon 1945). The same numerical direction holds on five further real datasets, which use an earlier feature allocation (Appendix C). The surrogate map is therefore informative. Its mean stays within 1 dB of the simpler maps. The raw/local linear control is 0.50 dB ahead of it.

All controls are matched at the readout. Each passes a 32-D feature vector to the same linear readout with 2112 parameters, on the same splits. This matches the readout resources. It does not match the feature class. The controls differ in what their features can express. The no-entanglement and ZZ-only controls remove all or half of the six raw pair products, and the quadratic classical control adds second-order classical terms. The ZZ-only control keeps exactly three of them. The surrogate is a 32-D map, not the 19-D circuit map of Table 1. The quadratic classical control keeps the 18 local features, the first six of its nine products of adjacent local-feature pairs, and the eight positional features, which gives the same 32-D width. Neither the surrogate nor the quadratic control includes the sines of its products. The ZZ-only and raw/local maps are padded with three and six zero columns, respectively, to reach 32-D.

A TOST equivalence test (Schuirmann 1987; Lakens 2017) at a declared ± 1 dB margin asks whether each gap is small enough to call two maps equivalent rather than merely "not shown to differ". The estimand is the seed-level PCAE2D-minus-control PSNR difference, averaged over held-out images within each seed. Without correction, equivalence requires both one-sided tests to reject at $\alpha = 0.05$. This is the same as the 90% confidence interval lying inside $[-1, +1]$ dB (Table 4). The margin is a declared choice. With five seeds, $p = 0.0625$ is the smallest attainable nonzero two-sided Wilcoxon signed-rank p-value, so that test cannot reject at the 0.05 level. The t-based 90% interval is wider than the percentile-bootstrap 95% interval in these data. Bootstrap intervals can be unstable with only five seed-level observations. For scale, a 1 dB PSNR difference corresponds to a factor of approximately $10^{0.1} \simeq 1.26$ in MSE. After Holm correction (Holm 1979) across the seven comparisons, five controls meet the equivalence criterion against PCAE2D within that margin. These are raw/local linear, no entanglement, ZZ-only observables, quadratic classical features, and shuffled pair observables. The raw/local linear control has the largest of these gaps. It meets the criterion with TOST $p = 0.009$ and Holm-adjusted $p = 0.027$. The two weakest controls, strict classical random features and random-VQC, are not equivalent because the surrogate substantially outperforms them. The trained circuit has been tested on held-out images in the topology comparison of Section 5.3. Trained on two images for 90 steps, PCAE2D reaches

Table 4 TOST equivalence test on held-out CIFAR-10 (± 1 dB margin, $\alpha = 0.05$, five seed-level paired differences, closed-form PCAE2D surrogate minus control). The verdict uses the Holm-adjusted p. Without correction, equivalence is the same as the 90% CI lying inside $[-1, +1]$ dB. "No entanglement" removes the pair products. "Random VQC" is a block of Gaussian random features.

Control	ΔPSNR (dB)	90% CI (dB)	TOST p	Holm p	Verdict
Raw/local linear	-0.50	$[-0.78, -0.22]$	0.009	0.027	**Equivalent**
No entanglement	-0.16	$[-0.52, +0.20]$	0.004	0.016	**Equivalent**
ZZ-only observables	-0.26	$[-0.46, -0.07]$	0.001	0.004	**Equivalent**
Quadratic classical	-0.14	$[-0.24, -0.04]$	< 0.001	< 0.001	**Equivalent**
Shuffled pair observables	-0.13	$[-0.38, +0.11]$	0.001	0.004	**Equivalent**
Strict classical random features	$+2.45$	$[+2.06, +2.84]$	0.999	1.000	**PCAE2D better**
Random VQC	$+7.15$	$[+5.73, +8.57]$	1.000	1.000	**PCAE2D better**

11.57 ± 1.53 dB on three unseen CIFAR-10 images, about 1 dB below a matched random-latent control under the same protocol (12.64 ± 2.12 dB, Appendix C). Held-out generalisation of the trained circuit is therefore not established at this budget. In a larger end-to-end test with 150 training and 50 held-out images, a parameter-matched classical control reconstructs the held-out images better than the trained PCAE2D model (Appendix C).

We report this as a complement to the positive pair-observable and symmetry results below. It delineates their tested boundary and records the provenance checks that prevented exploratory artifacts from becoming claims.

A matched-budget, multi-seed rerun of the component-ablation table reaches the same conclusion on ordinary per-image reconstruction. The rerun uses 240 steps and 3 seeds per variant (4 for the baseline). A plain classical-replacement control ties or slightly exceeds the quantum baseline. Apart from a freeze-classical sanity check, only a circuit-free random-VQC control performs clearly worse. Freeze-classical holds the decoder fixed, so it cannot learn to reconstruct and is expected to fail. This rerun uses a descriptive pooled-standard-deviation comparison rule at 3 seeds rather than a calibrated test. Full results are in Appendix B. Section 5.2 discusses why this ties-with-classical result and the pair-observable necessity result of Section 4.8 are consistent.

4.4 A real hardware reconstruction pilot

The results above are noiseless-simulator results. We now report a small but complete image-reconstruction pilot executed on real IBM Quantum hardware (`ibm_fez`, a 156-qubit Heron-class processor).

The pilot covers five images. These are the full 16-patch *Monalisa* benchmark and four native-resolution CIFAR-10 images (*cat*, *ship*×2, *airplane*), each optimised directly on its own target image following the same per-image protocol as Sections 4.1 and 4.2. For each image we took an already-trained PCAE1D/PCAE2D checkpoint's exact learned parameters and rebuilt its measurement circuits gate-for-gate in Qiskit. We verified the translation against the original PennyLane simulator to within numerical noise, at most 7.9×10^{-4} maximum absolute error per observable across every patch. We then executed the same circuits on real hardware with 256 shots per measurement basis. This is a fixed per-basis shot budget, rather than an adaptive shadow-tomography-style estimation scheme (Huang et al. 2020). The hardware-measured observables were decoded by the same trained classical decoder, with no retraining and no simulator involved anywhere in the reconstruction path.

Table 5 Real IBM hardware reconstruction pilot (backend `ibm_fez`, 256 shots/basis, no retraining). PSNR compares hardware-decoded and simulator-decoded reconstructions against the same ground-truth image.

Image	Patches	Sim. PSNR (dB)	HW PSNR (dB)
Monalisa (PCAE1D)	16	37.99	25.90
CIFAR cat (PCAE2D)	16	44.85	31.52
CIFAR ship, hydrofoil (PCAE2D)	16	36.56	26.44
CIFAR ship, sea boat (PCAE2D)	16	42.57	31.20
CIFAR airplane (PCAE2D)	16	46.79	29.10
CIFAR mean ± std (4 images)	—	42.69 ± 3.84	29.56 ± 2.03

Reconstructions from real, noisy hardware measurements retain recognisable image structure. *Monalisa* reaches 25.90 dB PSNR from hardware measurements, against a 37.99 dB noiseless-simulator replay of the identical circuit (Figure 2). The four CIFAR-10 images average 29.56 ± 2.03 dB on hardware against 42.69 ± 3.84 dB in simulation (Figure 3, Table 5). The observed gap is consistent with noise in these unmitigated device executions, although the five-image pilot does not isolate individual noise sources. Circuits were transpiled at optimisation level 1 and submitted through SamplerV2 with default options. Dynamical decoupling, Pauli twirling and readout-error mitigation were not enabled (see Temme et al. 2017; van den Berg et al. 2022; Kim et al. 2023). Each image used 256 shots per basis, totalling 12,288 shots for *Monalisa* and 8,192 for each CIFAR-10 image. The original jobs' physical-qubit layouts and contemporaneous calibration timestamps were not serialised and could not subsequently be recovered. Every hardware reconstruction remains above the random-latent control ~~range~~. ~~Substituting random latents for the observables at evaluation gives 13.92 and 14.61 dB on the *Monalisa* PCAE1D checkpoints.~~ On the *Monalisa* hardware checkpoint, substituting random latents for the observables at evaluation gives 12.49 dB. The pilot used 176 circuits. The contemporaneous account-meter reading increased by 16 quantum-processor seconds. A similar protocol, with training in simulation and inference on IBM hardware, has been used for MedMNIST classification with error suppression and mitigation (Singh et al. 2026). Here, it is applied to reconstruction without mitigation.

The pilot establishes that the trained PCAE observable channel survives execution on present-day hardware. With five images it is a pilot, and it makes no hardware-advantage claim. The learned parameters, the measurement circuits and the classical decoder all transfer unchanged, and the decoded images remain quantitatively informative at 256 shots per basis on an unmitigated device. This is the sense in which PCAE runs on real quantum hardware. ~~Gate sequences, measurement construction~~ **The measurement construction** and validation results are in Appendix D.

4.5 Noise/shot trade-off: a free simulator complement

The five-image pilot above used a single shot budget (256/basis) and one execution per image, which bounds how much it can say about noise sensitivity on its own. To use IBM Quantum time well, we separate what a *calibrated device-noise simulation* can establish at zero hardware cost from what genuinely requires hardware. Using `qiskit-aer` with the live calibration snapshot of `ibm_fez` (`FakeFez`, no quantum-processor time consumed), we replay the same already-trained checkpoints' circuits at four shot budgets (256/512/1024/4096 shots per basis, three repeated



Fig. 2 *Monalisa* reconstructed from real IBM Quantum hardware measurements (right) against the same trained checkpoint's noiseless-simulator replay (centre) and ground truth (left). The hardware image is visibly noisier and exhibits patch-boundary banding, while the subject remains recognisable.

executions each) and compare against both the noiseless-simulator ceiling and the real-hardware point already reported above.

Two findings follow, averaged over the five checkpoints (Figure 4). First, shot noise accounts for only part of the noiseless-to-real gap. Moving from the noiseless ceiling to a calibrated-noise simulation at the same 256-shot budget already costs 8.68 dB on average, before any real device is involved. Second, more shots do not reliably recover it. Increasing to 4096 shots per basis changes PSNR by only -0.05 dB on average across the five checkpoints, with individual images ranging from a 1.33 dB gain to a 0.96 dB loss. At this circuit size and shot range, shot count is not a lever that reliably improves reconstruction quality.

Comparing the 256-shot noisy simulation directly against the real-hardware point isolates what the calibration snapshot does *not* capture. That comparison leaves a further 4.24 dB average gap, ranging from 2.26 to 8.06 dB across images. This residual is consistent with effects that the calibration model does not capture, such as drift between calibration and execution, crosstalk, and correlated errors. The pilot does not separate these sources. The airplane image is the clear outlier, with an 8.06 dB residual gap, ~~roughly double~~ **well above** any other image. We report it rather than exclude it, since a single-execution, five-image pilot cannot distinguish an image-specific effect from ordinary job-to-job variation. This calibrated-noise simulation is a free, repeatable complement to the pilot, not a substitute for it. It bounds how much of the observed hardware gap is attributable to modelled device noise rather than unmodelled effects, using zero additional quantum-processor time.

4.6 Real-hardware anchor points: repeated execution and a second backend

The simulated trade-off above is useful only if it reflects real devices. We checked this directly on hardware with four jobs from the free-tier IBM Quantum allowance. These four jobs used well under 1% of the monthly limit. Two checkpoints, *Monalisa* and CIFAR *cat*, were replayed with no retraining on `ibm_marrakesh` and `ibm_kingston`. Both backends are distinct from the




Fig. 3 Four CIFAR-10 images reconstructed from real IBM Quantum hardware measurements (bottom row) against noiseless-simulator replays of the same trained PCAE2D checkpoints (middle row) and ground truth (top row).

original pilot's `ibm_fez`. We ran them at the original 256-shot budget and, separately, at 1024 shots (Table 6).

Monalisa reproduces almost exactly across backends at matched shots (25.94 vs. 25.90 dB, `ibm_marrakesh` vs. `ibm_fez`), and gains only 0.16 dB from quadrupling shots to 1024, consistent with the simulated finding above that shot count is not a reliable lever. The CIFAR *cat* point is the more informative one. On `ibm_kingston` at the original 256-shot budget it reaches 28.93 dB, which is 2.59 dB below the `ibm_fez` pilot point. Its own 1024-shot execution on the same backend recovers to 31.24 dB, within 0.28 dB of the original. This is real job-to-job and backend-to-backend variation of a magnitude comparable to the unmodelled residual identified by the simulator comparison (Section 4.5). It gives direct evidence that repeated execution matters at least as much as backend choice or shot count. A single 256-shot run on one backend is not yet a stable estimate of hardware performance.




Fig. 4 Calibrated device-noise simulation (`FakeFez`, mean ± std over three executions). Dotted lines show noiseless ceilings and stars show real-hardware measurements. Increasing 256 to 4096 shots changes mean PSNR by only −0.05 dB.

Table 6 Real-hardware anchor points: same checkpoints, no retraining, on two further backends. The original pilot's `ibm_fez` point is shown for reference.

Image	Backend	Shots	PSNR (dB)
Monalisa	`ibm_fez` (original)	256	25.90
Monalisa	`ibm_marrakesh`	256	25.94
Monalisa	`ibm_kingston`	1024	26.10
CIFAR cat	`ibm_fez` (original)	256	31.52
CIFAR cat	`ibm_kingston`	256	28.93
CIFAR cat	`ibm_kingston`	1024	31.24

4.7 Exact D_4-equivariant observable pooling

A D_4-pooled PCAE2D observable-grid map is equivariant to the eight symmetries of the square *by construction*:

$$\Phi_{D_4}(x) = \frac{1}{8} \sum_{g \in D_4} P_g^{-1} \Phi(gx), \qquad \Phi_{D_4}(hx) = P_h \, \Phi_{D_4}(x) \quad \forall \, h \in D_4. \tag{5}$$

Here D_4 acts on an image x by rotating or reflecting its 4×4 grid of patches, and P_g permutes the per-patch observable vectors in the same way, so that $P_{gh} = P_g P_h$. The property then holds exactly for any base map Φ. This is the standard group-averaging construction (Puny et al. 2022). It needs one evaluation of the base map for each of the eight group elements. Substituting hx and re-indexing

Table 7 D_4 equivariance error for unpooled and pooled observable-grid maps. Lower is better. The pooled map is group-averaged over all eight square symmetries. Values are computed on the closed-form surrogate map.

Model	Mean error	Std. dev.
D_4-pooled PCAE2D	9.57×10^{-17}	1.26×10^{-17}
No positional encoding	7.40×10^{-1}	1.52×10^{-1}
PCAE2D positional	8.15×10^{-1}	1.29×10^{-1}
Local/raw	8.37×10^{-1}	1.31×10^{-1}

the sum with $g' = gh$ gives $P_g^{-1} = P_h P_{g'}^{-1}$, and hence $\Phi_{D_4}(hx) = P_h \Phi_{D_4}(x)$. The numerical check below therefore tests the implementation, not the property. We run it on the closed-form surrogate feature map over 7000 patch transforms of cached CIFAR images (Table 7, Figure 5). The pooled map's equivariance error is $9.57 \times 10^{-17} \pm 1.26 \times 10^{-17}$, which is floating-point noise. The unpooled positional map has an error of 0.815 ± 0.129, and the local/raw control has 0.837 ± 0.131. Both are of order one. The patch grid's geometry therefore makes the unpooled map D_4-*motivated* only, and the explicit pooling construction is what delivers the property. Applied to the trained circuit, the same pooling reduces the equivariance error to order 10^{-8}. On the four trained PCAE2D hardware checkpoints, with an exact statevector pass over all eight transformed copies of each image, the mean error falls from 0.2777 without pooling to 5.39×10^{-8} with it. This construction operates at the feature-grid level and serves here as a numerical diagnostic, rather than as a component of the trainable reconstruction pipeline. Integrating it end-to-end (Section 5.4) is concrete future work. This route to symmetry differs from equivariant quantum neural networks, in which every circuit layer is built to commute with the group action (Nguyen et al. 2024). A recent image classifier of that kind builds C_4 rotation symmetry into the circuit itself (San Sebastian Sein et al. 2025). In PCAE the symmetry comes from averaging the observable grid over the group after measurement. The circuit itself is not equivariant, and the same average applies equally to a classical feature map.

4.8 Pair-observable necessity in the nonlocal-structure protocol

The diagnostic tests whether a pair-observable channel is needed to fit a target that depends on pair correlations. The target is a fixed synthetic function of *simulated* patch features, and those features are not concatenated into any candidate's own input block. Every control receives the same raw inputs as PCAE2D. The protocol is audited for leakage. For each feature block, we check whether a linear or near-linear map reaches near-zero residual on the features used to build the target, since such a fit would copy the target from the input. The diagnostic reported here passes this check. All feature maps in this diagnostic are closed-form, and no circuit is evaluated. The pair-observable channel is represented by the analytic pair products that a pair measurement would supply. By construction, these products match the pair terms of the target. The experiment demonstrates representational capability under a deliberately aligned protocol, not a general performance advantage.




Fig. 5 D_4 equivariance diagnostic. The group-pooled map is equivariant to numerical precision. The unpooled positional map is not.

Table 8 and Figure 6 report the result across five seeds. PCAE2D's pair-observable channel reaches mean $R^2 = 0.9735$, or 32.77 dB PSNR. This is a 17.74 dB improvement over a no-pair-observables control ($R^2 = 0.019$) and 18.52 dB over the Random VQC control (Gaussian random latents, $R^2 = -0.173$). Randomly rescaling and masking the pair features ("freeze quantum"), with only the readout trained, still reaches $R^2 = 0.853$. A raw-linear classical control ($R^2 = 0.0133$), a parameter-matched classical control ($R^2 = -0.030$), and a frozen-classical control ($R^2 = -0.903$) all fail on this deliberately pair-dependent target. The no-pair-observables control retains only single-site nonlinear channels and removes every cross-site product feature. Under the fixed linear readout, it therefore cannot construct the cross terms on which the target depends.

The mechanism is explicit under the fixed linear readout. A linear map of single-patch expectations $\{\langle O_i \rangle\}$ cannot form the cross-term $\langle O_i \rangle \langle O_j \rangle$ that the target depends on. The pair measurement supplies the joint correlator $\langle O_i O_j \rangle$ directly as a feature. Formally, let $z_i = \langle O_i \rangle$ and let every admissible predictor be affine, $f(z) = w^\top z + b$. Then $\partial^2 f / \partial z_i \partial z_j = 0$ for all i, j. A target with a term $c\, z_i z_j$, $c \neq 0$, has this mixed derivative equal to c wherever z_i and z_j vary independently, so no affine f can fit it. Adding $z_i z_j$ to the feature vector makes the term linearly representable. A pair-observable channel is therefore *representationally necessary within the tested feature class and fixed linear-readout protocol* to fit this target. A classical model that forms the same products, for example through quadratic features or a nonlinear readout, would also fit this target. For this reason we scope the claim to the linear protocol rather than to classical models in general.

4.9 A scoped training-dynamics diagnostic

Beyond the results above, we tracked two exploratory training-dynamics readouts. These are a magnetisation-style statistic $M_z(t)$ and a signed energy-to-entanglement ratio $R_{ES}(t)$. Here $M_z(t)$ is the mean of the local $\langle Z \rangle$ observables over all qubits and patches at optimisation step t. $R_{ES}(t)$ is the learned Hamiltonian energy divided by the fixed sum of the MPS bond entropy features,

Table 8 PCAE2D restricted pair-correlation diagnostic across five seeds. The task is deliberately favourable to pair-observable structure. The table gives evidence for pair-observable necessity under a matched linear readout. All features are closed-form. "Random VQC" is a block of Gaussian random features.

Model	Mean MSE	Mean PSNR (dB)	Mean R^2
PCAE2D pair observables	8.5969×10^{-4}	32.77	0.9735
Freeze quantum	4.7904×10^{-3}	27.34	0.8533
No pair observables	3.1461×10^{-2}	15.03	0.0191
Raw-linear classical	3.1654×10^{-2}	15.00	0.0133
Parameter-matched classical	3.3033×10^{-2}	14.82	−0.0297
Random VQC	3.7616×10^{-2}	14.25	−0.1732
Freeze classical	6.0973×10^{-2}	12.17	−0.9025




Fig. 6 Restricted pair-correlation diagnostic summary (mean ± std over five seeds). The pair-observable feature map dominates every control on this deliberately favourable task.

so it tracks the energy up to a constant scale. Both drift smoothly over training with run-to-run fluctuations, and neither shows a sharp transition. Any apparent onset is a within-run median-plus-2σ threshold crossing, rather than a calibrated statistical test. The rule flags a run when the largest step-to-step change in M_z exceeds that run's median change plus two standard deviations.

A negative control fixes the scope. We applied the identical protocol to a classical-replacement variant, in which the Hamiltonian energy is identically zero throughout training. That variant crosses the threshold in all 4/4 tested cases, which is as often as the Hamiltonian-regularised model's 4/4. The threshold therefore fires whether the Hamiltonian term is present or absent, and it does not track that term. We therefore report these traces as an interpretability readout on the learned energy and entanglement. The readout is descriptive. It shows how the two quantities evolve during optimisation. We do not treat it as evidence of a phase transition or a critical point. An earlier phase-transition reading of these traces has been withdrawn.

Table 9 Hamiltonian-sector controls (single-seed, fresh same-environment reproduction: *Monalisa*, 200 steps, seed 42). The energy objective is diagnostically useful but does not improve reconstruction accuracy.

Experiment	PSNR (dB)	Interpretation
Legacy baseline, signed energy	38.63	Standard energy-regularised run
No energy loss	44.56	Removing energy improves PSNR
Contrastive Hamiltonian core	42.92	Stronger objective helps modestly vs. baseline, still below no-energy-loss

5 Discussion

5.1 Effect of the Hamiltonian energy term

In this single-seed comparison, the signed Hamiltonian-energy objective substantially reduces reconstruction quality. Removing it increases PSNR from 38.63 to 44.56 dB (Table 9). The legacy objective adds a signed mean energy to the reconstruction loss. Because learned energy can go negative, the optimiser can lower total loss by driving energy down without improving reconstruction. A contrastive variant, assigning lower energy to correct feature–position pairs than to shuffled pairs, recovers part of the gap (42.92 dB) but stays below its no-energy counterpart. These are fresh same-environment measurements (*Monalisa*, 200 steps, seed 42), and they supersede earlier values produced by a script that cannot be audited. The effect of the signed energy term is in general agreement with an independent study, which finds no benefit beyond simple classical regularisers from a VQE-inspired energy term added to the loss of a generative adversarial network (Strnadel 2025).

The learned couplings do not enter the decoder directly, but the energy term contributes gradients during training and therefore changes the learned circuit representation. It is consequently an auxiliary training objective as well as a post-training diagnostic. A physically motivated regulariser has room to help when it resolves an otherwise underdetermined objective. Under this protocol, the reconstruction loss alone provides the stronger optimisation signal.

The training-dynamics readouts of Section 4.9 provide a descriptive window into how the learned energy and entanglement evolve.

5.2 Task-dependent representational scope

Whether a quantum feature map offers any advantage over a classical model is a property of the specific data and target, not a fixed property of the model class. Dequantisation results have repeatedly shown that apparent quantum advantages on structured, low-entanglement classical data can be matched once the right classical feature is identified (Huang et al. 2021; Tang 2019). Where provable separations do exist, they are established for carefully constructed learning problems rather than for generic structured data (Gyurik and Dunjko 2023). We separate three questions. First, PCAE at six qubits can be simulated exactly on a classical computer, which says little about larger scales. Second, whether its model class admits an efficient classical replacement at scale is open. Tensor-network analyses give conditions for such dequantisation of variational models (Shin et al. 2024), and a classical tie at small scale does not settle it. Random Fourier features can also replace some variational models efficiently, under stated conditions (Sweke et al. 2025). Quantum convolutional networks on common image benchmarks can be simulated efficiently by a classical method

based on Pauli shadows (Bermejo et al. 2026). Third, on held-out CIFAR-10, a closed-form surrogate of the PCAE2D map stays within 1 dB of matched classical feature maps. The trained circuit has not yet shown held-out generalisation. This matches large benchmarks in which simple classical models often match or beat small quantum models, and removing entanglement often costs little (Bowles et al. 2024). In PCAE the quantum processor evaluates only the circuit and returns the vector of measured Pauli expectation values. The MPS compression is quantum-inspired but runs on classical hardware, as do the Fourier positional encoding, the D_4 pooling, the decoder and the optimisation. Any quantum contribution to PCAE must therefore enter through the measured observable vector.

The restricted diagnostic of Section 4.8 is constructed so that the relevant structure is a genuine distant-element product, which raw or local features cannot represent under a fixed linear readout. That is the regime in which PCAE's pair-observable channel separates. Natural image patches at the resolution and patch size used here are low-entanglement, locally structured data (Martyn et al. 2020; Lu et al. 2025), where a linear or shallow classical readout is already close to sufficient. For the images of Table 3, the bipartite von Neumann entropy of the compressed patch states is at most 0.58 nats for CIFAR-10 and 0.24 nats for MedMNIST, over all five cuts of every patch. The largest value allowed at bond dimension four is $\ln 4$. The distinction lies in the measured pair-observable channel rather than in the circuit. The ansatz uses strongly-entangling layers and does generate an entangled state, but whether the measured channel carries task-relevant information is a property of the target. On natural-image targets the pair observables add little beyond the local ones. On the constructed nonlocal target they are necessary. Together with the held-out comparisons of Section 4.3, these results delineate where the tested entangling representation does and does not yield a measurable benefit.

Three of PCAE's ingredients recur individually in the hybrid quantum-vision literature, covering MPS compression of structured input (Stoudenmire and Schwab 2016; Han et al. 2018; Cirac et al. 2021; Guala et al. 2023), a Pauli-correlator latent space handed to a classical decoder (Havlíček et al. 2019), and a physically motivated auxiliary regulariser alongside a task loss (Shi et al. 2023). Its specific instantiation, a six-qubit VQC with a 19–27-D correlator vector and a graph-Hamiltonian term, sits within the parameter ranges typical of that literature. The measured behaviour is therefore evidence about the design pattern itself. We do not claim the boundary transfers unchanged to every dataset, patch size, or qubit count.

5.3 Topology alignment as an inductive bias

Aligning the latent interaction graph with image-patch adjacency (PCAE2D vs. PCAE1D) is an architectural inductive bias, and we test it directly under matched held-out conditions. The real-circuit comparison (3 seeds, 3 held-out CIFAR-10 images) gives a PCAE1D-minus-PCAE2D mean PSNR difference of 0.16 dB. After averaging images within seed, the bootstrap 95% CI is $[-0.38, 0.46]$ dB and the seed-level Wilcoxon test gives $p = 0.50$. PCAE2D completes the matched 90-step runs in roughly half the wall-clock time. At the tested scale, topology is therefore primarily a resource-cost choice rather than a reliable accuracy advantage. These tests do not establish formal equivalence.

Table 10 contrasts PCAE's structural properties against reference frameworks, including the three nearest hybrid-vision architecture families. Its distinguishing features are a Pauli-correlator latent space, a 2D Fourier positional bias with enforced D_4 pooling, and a Hamiltonian energy term, each documented and scoped in the preceding sections.

Table 10 Architectural differentiation from representative baseline designs, including the three nearest hybrid-vision architecture families (register-based QAE, quantum-kernel vision, TN-circuit classifier).

Axis	Conv. AE baseline	GAN baseline	Register-based QAE	Quantum-kernel vision	TN-circuit classifier	PCAE (ours)
Latent representation	Continuous $\mathbb{R}^d$	Continuous $\mathbb{R}^d$	Quantum register	Scalar kernel value	MPS/circuit state	Pauli-correlator vector
Spatial bias	Convolutional	Convolutional	Encoding-dependent	Encoding-dependent	MPS chain ordering	2D Fourier encoding
Auxiliary objective	Bottleneck / reconstruction	Adversarial loss	Fidelity / reconstruction	None (kernel value only)	Classification loss	Hamiltonian energy term
Enforced group symmetry	Not in baseline	Not in baseline	Not in reference design	Not in reference design	Not in reference design	D_4 observable pooling
Evaluated role	Reconstruction	Reconstruction	Compression	Classification	Classification	Reconstruction + diagnostics

5.4 Validated scope

Every circuit-based reconstruction result in this paper is per-image trained. The held-out comparison of Section 4.3 uses a closed-form surrogate of the PCAE2D map. On held-out images the trained circuit falls below a matched random-latent control at the tested budget, so its held-out generalisation is not established. The per-image results of Section 4.1 are not compared with a matched-size classical per-image network, as is usual for implicit neural representations. A single-seed position-only ablation of the same decoder has a higher mean PSNR than PCAE2D on three of the six datasets (Table 3).

The D_4-pooled map (Section 4.7) is a feature-grid-level construction and numerical diagnostic, measured on the closed-form surrogate in Table 7. Integrating it into the trainable end-to-end pipeline is future work. The pair-observable necessity result (Section 4.8) is scoped to a synthetic task with closed-form features, constructed to require nonlocal structure. Ordinary natural-image reconstruction lies outside that scope (see Section 5.2). The training-dynamics traces (Section 4.9) are an interpretability readout. The threshold fires whether the Hamiltonian term is present or absent, at 4/4 in both cases.

The hardware pilot (Section 4.4) is a five-image, unmitigated pilot with one run per image on the main backend rather than a statistically resolved hardware benchmark. The matched real-circuit topology comparison uses 3 seeds and 3 held-out images per topology. These results support a resource-cost interpretation rather than formal equivalence of the topologies. Every result here is at a six-qubit, two-layer scale. Trainability of variational models is known to degrade with width and depth through barren-plateau effects (McClean et al. 2018; Larocca et al. 2025). Further, models that provably avoid barren plateaus are often also efficiently simulable on a classical computer (Cerezo et al. 2025). Thus, whether the tested boundary moves at larger scale is an open question.

6 Conclusion

We presented the Pauli-Correlator Autoencoder (PCAE), a hybrid quantum–classical architecture for image reconstruction that assembles matrix-product-state patch features, a measured Pauli-correlator latent space, enforced D_4-equivariant observable pooling, and a learnable Hamiltonian energy term into a single pipeline (Section 2). Across six real image datasets, per-image-trained PCAE2D models reach 25.8–41.6 dB PSNR. A position-only ablation of the same decoder also achieves strong fits on these sampled images. On held-out CIFAR-10, a closed-form surrogate of the PCAE2D observable map is equivalent within 1 dB to five resource-matched feature maps. Held-out generalisation of the trained circuit remains to be shown (Section 4.3). A hardware pilot replayed trained checkpoints on IBM Quantum devices without retraining, establishing feasibility at a five-image scope with one run per image on the main backend (Section 4.4).

Pair observables are necessary on a synthetic task requiring nonlocal structure, under a fixed linear readout (Section 4.8). The Hamiltonian energy term acts as an auxiliary training objective, and its learned energy is an interpretable readout of the trained representation (Section 5.1). In a single-seed ablation it lowers reconstruction quality. The pooled observable map is also exactly D_4-equivariant by construction, which we report as a design-correctness property rather than a quantum capability, since the same Reynolds averaging applied to a classical feature map is equally exact. We make no claim of quantum advantage. At the six-qubit scale tested here, PCAE fits varied real images and runs on real quantum hardware.

Future work should integrate the D_4-pooled map into an end-to-end trainable pipeline (Section 5.4), scale the hardware pilot toward a statistically resolved benchmark with error mitigation and repeated trials, test held-out generalisation of the trained circuit against the same resource-matched controls, search for further real-world tasks with nonlocal structure where PCAE's pair-observable separation translates into a reconstruction advantage, and extend the resource-matched, leakage-audited evaluation protocol to other hybrid quantum vision architectures.

Acknowledgements. We thank the maintainers of the open-source scientific computing libraries used in this work. We acknowledge support from ANRF, India (grant ANRF/ECRG/2025/003752).

Statements and Declarations

Competing interests. The authors declare no competing interests.

Funding. This work was supported by the Anusandhan National Research Foundation (ANRF), India, under grant ANRF/ECRG/2025/003752.

Data availability. Dataset provenance and access routes are cited in the manuscript. All datasets used (CIFAR-10, MNIST, Fashion-MNIST, and the PathMNIST, BloodMNIST and PneumoniaMNIST subsets of MedMNIST v2) are publicly available.

Code availability. The code supporting this study is available from the corresponding author upon reasonable request.

Author contributions. **Sparsho Chakraborty:** Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data curation, Writing – original draft, Visualization. **Siddhartha Patra:** Conceptualization, Supervision, Writing – review & editing, Resources. Both authors reviewed and approved the final manuscript.

Appendix A Training settings and evaluation protocol

All trained models use Adam with full-batch updates over the patches of their training images. The loss is the reconstruction mean squared error plus $\lambda = 0.01$ times the mean Hamiltonian energy, except where an ablation removes or replaces the energy term. The held-out comparison fits no network. Its linear readout is solved in closed form as a ridge regression with regularisation 10^{-6}. Table A1 lists the settings of each experiment.

Table A1 Training settings. Learning rates are for Adam. Patches are non-overlapping unless a stride is given.

Experiment	Model	Patches	Steps	Learning rate	Seeds
Monalisa hardware checkpoint[a]	PCAE1D	16, 64×64	200	0.003	42
240-step ablation	PCAE1D	16, 64×64	240	0.003	0, 1, 2[b]
Six-dataset fits	PCAE2D	16, 8×8	100	0.004	not recorded
CIFAR-10 hardware fits	PCAE2D	16, 8×8	200	0.004	not recorded
Topology comparison	1D / 2D	49, 8×8, stride 4	90	0.003 / 0.004	0, 1, 2
Held-out comparison	surrogate	16, 8×8	n/a	n/a (ridge)	0–4[c]

[a] The hardware pilot uses the legacy `shared-baseline-seed-42` checkpoint. The Hamiltonian-control values in Table 9 are independent fresh reruns made with the same nominal 200-step, seed-42 settings; they are not the hardware checkpoint.
[b] The reported baseline mean also includes seed 3.
[c] Split seeds; each split fits the ridge readout on six CIFAR-10 images and holds out four disjoint images.

Where Table A1 lists seeds, the experiment drivers set the Python, NumPy and PyTorch random seeds explicitly. The drivers of the six-dataset fits and the CIFAR-10 hardware fits did not set or record a seed, so these are reported as not recorded. "Mean ± std" denotes the mean and the population standard deviation over the unit named in each caption. Bootstrap intervals are percentile 95% intervals, and Wilcoxon values are two-sided signed-rank tests. The runs used ~~Python 3.11.9,~~ PyTorch 2.6.0 with CUDA 12.4, PennyLane 0.42.3~~, Qiskit 2.5.0, NumPy 2.4.6~~ and quimb ~~1.11.2~~ 1.14.0 on an NVIDIA GeForce GTX 1050.

Appendix B Matched-budget component ablation

All nine variants were trained on *Monalisa* with a matched 240-step budget and an identical learning rate and schedule, for three seeds each (seeds 0–2), with a fourth seed (3) for the baseline (Table B2). The first freeze-quantum attempts at seeds 0–2 failed with undefined (NaN) metrics because of an implementation error, and only the three successful reruns enter its mean. Freeze-classical trains only the circuit and the Hamiltonian couplings, with the decoder and projection layers fixed, and freeze-quantum does the reverse. No-entanglement removes the CNOT rings, and no-energy-loss removes the energy term. No-MPS replaces the MPS feature extractor with a 46-dimensional vector of direct patch statistics (mean, standard deviation, minimum, maximum, seven percentiles and a normalised intensity histogram), and keeps the projection, circuit, positional encoding and decoder. Random-VQC replaces the circuit observables at every forward pass with an independently resampled standard-Gaussian vector of the same dimension, sets the energy to zero, and trains the decoder normally. Classical-replacement replaces the circuit with a tanh map,

and classical-matched limits that map to the circuit's parameter count. The classical-replacement variant exceeds the quantum baseline by 0.081 dB, against a pooled standard deviation of 0.019 dB. The classical-matched variant falls 0.197 dB below the baseline.

Table B2 Matched-budget (240-step) component ablation on *Monalisa*, three seeds per variant (four for the baseline), mean ± std.

Variant	PSNR (dB)	SSIM	Variant	PSNR (dB)	SSIM
Baseline (quantum)	33.42 ± 0.02	0.99385 ± 0.00003	Classical-replacement	33.50 ± 0.01	0.99395 ± 0.00002
Freeze-quantum	33.39 ± 0.06	0.99381 ± 0.00006	Classical-matched	33.22 ± 0.19	0.99356 ± 0.00027
No-entanglement	33.48 ± 0.02	0.99392 ± 0.00003	Random-VQC	28.09 ± 0.23	0.97907 ± 0.00135
No-MPS	33.34 ± 0.05	0.99374 ± 0.00008	Freeze-classical	10.94 ± 0.00	0.0219 ± 0.0001
No-energy-loss	33.44 ± 0.01	0.99387 ± 0.00001			

Appendix C Held-out reconstruction

The held-out protocol of Section 4.3 was repeated on cached subsets of six datasets, with three stratified split seeds (Table C3). From the first 400 images of each dataset, each split draws 20 training and 10 held-out images per class (one and one for CIFAR-10), and skips any class with fewer than 30 images among them. This gives 10/10, 200/100, 200/100, 160/80, 120/60 and 40/20 training/held-out images per split for CIFAR-10, MNIST, Fashion-MNIST, PathMNIST, BloodMNIST and PneumoniaMNIST, so PathMNIST uses 8 of its 9 classes and BloodMNIST 6 of its 8. These results predate the correction of the positional channel in the CIFAR-10 comparison of Section 4.3. The earlier width selection retained only two of the eight positional features for the PCAE2D surrogate and none for the quadratic control. The no-entanglement and raw/local controls retained all eight. The feature allocation here therefore differs from that of the corrected comparison. The local/raw control has equal or higher mean PSNR on every dataset. After averaging within each split seed, all six seed-bootstrap intervals exclude zero, and each two-sided signed-rank test gives $p = 0.25$, the smallest value attainable with three seeds.

Table C3 Held-out PSNR (dB) on cached subsets, mean ± std over held-out images, for the best local/raw control and the PCAE2D surrogate.

Dataset	Best local/raw	PCAE2D surrogate	Higher mean
CIFAR-10	21.17±1.98	19.99±2.02	Local/raw
MNIST	16.55±1.27	16.12±1.34	No-entanglement/local
Fashion-MNIST	17.67±1.71	17.33±1.80	Local/raw
PathMNIST	27.52±6.02	27.01±5.81	Local/raw
BloodMNIST	24.79±1.78	24.24±1.66	Local/raw
PneumoniaMNIST	26.49±2.48	25.73±2.29	Local/raw

In the held-out topology test of Section 5.3, PCAE1D reaches 11.73 ± 1.99 dB and PCAE2D reaches 11.57 ± 1.53 dB. A random-latent control under the identical protocol replaces the observable vector with resampled noise and trains the decoder normally. It reaches 12.74 ± 2.21 dB

for PCAE1D and 12.64 ± 2.12 dB for PCAE2D. The trained circuits are about 1 dB below this floor, and the paired difference is negative in all six seed-level comparisons (two-sided Wilcoxon $p = 0.031$). At 90 steps, only the PCAE1D-minus-PCAE2D difference in this test is informative.

In a separate end-to-end test, one PCAE2D model is trained with full-batch Adam for 20 epochs on 150 CIFAR-10 images and evaluated, without further training, on 50 held-out images. Each of three seeds reshuffles the split. The model reaches 14.39 ± 0.26 dB, against 15.61 ± 0.29 dB for a parameter-matched classical linear control trained the same way. The control is higher at each of the three seeds.

Appendix D Hardware pilot methodology

The *Monalisa* circuit is the legacy PCAE1D checkpoint `shared-baseline-seed-42`, trained for 200 steps with seed 42 and learning rate 0.003. It is distinct from the fresh "Legacy baseline, signed energy" rerun of Table 9. Its noiseless reference of 37.99 dB (Table 5) is an exact statevector replay of the saved checkpoint through the hardware-reconstruction pipeline. Both the hardware and the simulator PSNR are computed over the decoded patches, without stitching them or blending the seams. The training-run evaluation of the same checkpoint blends the seams of the stitched image and records 32.24 dB. The four CIFAR-10 circuits are PCAE2D checkpoints, each trained on its own image with 16 non-overlapping 8×8 patches (Table A1). PCAE1D measures Z, X, ZZ, XX and YY (27 observables). Its pair correlators are joint parities of the same all-Z, all-X and all-Y basis measurements that give the single-qubit values, so three measurement circuits per patch suffice, or 48 circuits for *Monalisa*. PCAE2D measures Z, X and ZZ (19 observables) and needs two circuits per patch, or 128 circuits for the four CIFAR-10 images.

Before any hardware submission, every circuit was checked against the cached training-time observables by exact statevector simulation. The largest absolute error was 7.89×10^{-4} for *Monalisa* and at most 9.42×10^{-6} for the CIFAR-10 checkpoints. On hardware, the mean absolute deviation of the observables from the statevector values was 0.096–0.125, so gate translation is not the main source of the hardware–simulator PSNR gap. Hardware counts were converted to expectation values with the standard parity estimator and passed, with the training-time positional encoding, through the unmodified trained decoder.

References

Araz JY, Spannowsky M (2022) Classical versus quantum: comparing tensor-network-based quantum circuits on Large Hadron Collider data. Physical Review A 106(6):062423. https://doi.org/10.1103/PhysRevA.106.062423

Asaoka H, Kudo K (2025) Quantum autoencoders for image classification. Quantum Machine Intelligence 7(2):71. https://doi.org/10.1007/s42484-025-00297-x

Bauer B, Bravyi S, Motta M, et al (2020) Quantum algorithms for quantum chemistry and quantum materials science. Chemical Reviews 120(22):12685–12717. https://doi.org/10.1021/acs.chemrev.9b00829

Beaulieu D, Miracle D, Pham A, et al (2022) Quantum kernel for image classification of real world manufacturing defects. arXiv preprint arXiv:2212.08693 https://doi.org/10.48550/arXiv.2212.

08693

van den Berg E, Minev ZK, Temme K (2022) Model-free readout-error mitigation for quantum expectation values. Physical Review A 105(3):032620. https://doi.org/10.1103/PhysRevA.105.032620

Bermejo P, Braccia P, Rudolph MS, et al (2026) Quantum convolutional neural networks are effectively classically simulable. PRX Quantum 7:020304

Bowles J, Ahmed S, Schuld M (2024) Better than classical? The subtle art of benchmarking quantum machine learning models. arXiv preprint arXiv:2403.07059

Bronstein MM, Bruna J, Cohen T, et al (2021) Geometric deep learning: grids, groups, graphs, geodesics, and gauges. arXiv preprint arXiv:2104.13478 https://doi.org/10.48550/arXiv.2104.13478

Cerezo M, Arrasmith A, Babbush R, et al (2021) Variational quantum algorithms. Nature Reviews Physics 3(9):625–644. https://doi.org/10.1038/s42254-021-00348-9

Cerezo M, Larocca M, García-Martín D, et al (2025) Does provable absence of barren plateaus imply classical simulability? Nature Communications 16:7907. https://doi.org/10.1038/s41467-025-63099-6

Chakraborty S, Mandal SB, Shaikh SH (2022) Quantum image processing: challenges and future research issues. International Journal of Information Technology 14(1):475–489. https://doi.org/10.1007/s41870-018-0227-8

Chen SYC, Huang CM, Hsing CW, et al (2021) An end-to-end trainable hybrid classical-quantum classifier. Machine Learning: Science and Technology 2(4):045021. https://doi.org/10.1088/2632-2153/ac104d

Cirac JI, Pérez-García D, Schuch N, et al (2021) Matrix product states and projected entangled pair states: concepts, symmetries, theorems. Reviews of Modern Physics 93(4):045003. https://doi.org/10.1103/RevModPhys.93.045003

Cohen T, Welling M (2016) Group equivariant convolutional networks. In: Proceedings of the 33rd International Conference on Machine Learning, Proceedings of Machine Learning Research, vol 48. PMLR, pp 2990–2999

Cong I, Choi S, Lukin MD (2019) Quantum convolutional neural networks. Nature Physics 15(12):1273–1278. https://doi.org/10.1038/s41567-019-0648-8

Dupont E, Goliński A, Alizadeh M, et al (2021) COIN: COmpression with implicit neural representations. arXiv preprint arXiv:2103.03123

Efron B, Tibshirani RJ (1993) An Introduction to the Bootstrap. Chapman and Hall/CRC, New York

Fujihashi T, Koike-Akino T (2026) Quantum implicit neural compression. In: Quantum Computing and Artificial Intelligence. Springer Nature Switzerland, Communications in Computer and Information Science, pp 60–69, https://doi.org/10.1007/978-3-032-15931-1_5

Gray J (2018) quimb: A Python package for quantum information and many-body calculations. Journal of Open Source Software 3(29):819. https://doi.org/10.21105/joss.00819

Guala D, Zhang S, Cruz E, et al (2023) Practical overview of image classification with tensor-network quantum circuits. Scientific Reports 13(1):4427. https://doi.org/10.1038/s41598-023-30258-y

Gyurik C, Dunjko V (2023) Exponential separations between classical and quantum learners. arXiv preprint arXiv:2306.16028 https://doi.org/10.48550/arXiv.2306.16028

Haga A (2024) Quantum annealing-based computed tomography using variational approach for a real-number image reconstruction. Physics in Medicine and Biology 69(4):04NT02. https://doi.org/10.1088/1361-6560/ad2155

Han ZY, Wang J, Fan H, et al (2018) Unsupervised generative modeling using matrix product states. Physical Review X 8(3):031012. https://doi.org/10.1103/PhysRevX.8.031012

Havlíček V, Córcoles AD, Temme K, et al (2019) Supervised learning with quantum-enhanced feature spaces. Nature 567(7747):209–212. https://doi.org/10.1038/s41586-019-0980-2

Holm S (1979) A simple sequentially rejective multiple test procedure. Scandinavian Journal of Statistics 6(2):65–70

Huang HY, Kueng R, Preskill J (2020) Predicting many properties of a quantum system from very few measurements. Nature Physics 16(10):1050–1057. https://doi.org/10.1038/s41567-020-0932-7

Huang HY, Broughton M, Mohseni M, et al (2021) Power of data in quantum machine learning. Nature Communications 12(1):2631. https://doi.org/10.1038/s41467-021-22539-9

Hur T, Kim L, Park DK (2022) Quantum convolutional neural network for classical data classification. Quantum Machine Intelligence 4(1):3. https://doi.org/10.1007/s42484-021-00061-x

Kim Y, Eddins A, Anand S, et al (2023) Evidence for the utility of quantum computing before fault tolerance. Nature 618:500–505. https://doi.org/10.1038/s41586-023-06096-3

Krizhevsky A (2009) Learning multiple layers of features from tiny images. Tech. rep., University of Toronto, Toronto, Ontario

Lakens D (2017) Equivalence tests: A practical primer for t tests, correlations, and meta-analyses. Social Psychological and Personality Science 8(4):355–362. https://doi.org/10.1177/1948550617697177

Larocca M, Thanasilp S, Wang S, et al (2025) Barren plateaus in variational quantum computing. Nature Reviews Physics 7:174–189. https://doi.org/10.1038/s42254-025-00813-9

Latorre JI (2005) Image compression and entanglement. arXiv preprint arXiv:quant-ph/0510031 https://doi.org/10.48550/arXiv.quant-ph/0510031

Le PQ, Dong F, Hirota K (2011) A flexible representation of quantum images for polynomial preparation, image compression, and processing operations. Quantum Information Processing 10:63–84. https://doi.org/10.1007/s11128-010-0177-y

LeCun Y, Bottou L, Bengio Y, et al (1998) Gradient-based learning applied to document recognition. Proceedings of the IEEE 86(11):2278–2324. https://doi.org/10.1109/5.726791

Liu Z, Shen PX, Li W, et al (2023) Quantum capsule networks. Quantum Science and Technology 8(1):015016. https://doi.org/10.1088/2058-9565/aca55d

Lizzio Bosco D, Wang S, Serra G, et al (2026) Quantum implicit neural representations for novel view synthesis. arXiv preprint arXiv:2601.05250

Lu S, Kanász-Nagy M, Kukuljan I, et al (2025) Tensor networks and efficient descriptions of classical data. Physical Review A 111(3):032409. https://doi.org/10.1103/PhysRevA.111.032409

Martyn J, Vidal G, Roberts C, et al (2020) Entanglement and tensor networks for supervised image classification. arXiv preprint arXiv:2007.06082

McClean JR, Boixo S, Smelyanskiy VN, et al (2018) Barren plateaus in quantum neural network training landscapes. Nature Communications 9(1):4812. https://doi.org/10.1038/s41467-018-07090-4

Meyer JJ, Mularski M, Gil-Fuster E, et al (2023) Exploiting symmetry in variational quantum machine learning. PRX Quantum 4(1):010328. https://doi.org/10.1103/PRXQuantum.4.010328

Mildenhall B, Srinivasan PP, Tancik M, et al (2020) NeRF: Representing scenes as neural radiance fields for view synthesis. In: Computer Vision – ECCV 2020, Lecture Notes in Computer Science, vol 12346. Springer, pp 405–421, https://doi.org/10.1007/978-3-030-58452-8_24

Nau MA, Vija AH, Gohn W, et al (2023) Exploring the limitations of hybrid adiabatic quantum computing for emission tomography reconstruction. Journal of Imaging 9(10):221. https://doi.org/10.3390/jimaging9100221

Nguyen QT, Schatzki L, Braccia P, et al (2024) Theory for equivariant quantum neural networks. PRX Quantum 5(2):020328. https://doi.org/10.1103/PRXQuantum.5.020328

Preskill J (2018) Quantum computing in the NISQ era and beyond. Quantum 2:79. https://doi.org/10.22331/q-2018-08-06-79

Puny O, Atzmon M, Ben-Hamu H, et al (2022) Frame averaging for invariant and equivariant network design. In: International Conference on Learning Representations (ICLR)

Ran SJ, Sun ZZ, Fei SM, et al (2020) Tensor network compressed sensing with unsupervised machine learning. Physical Review Research 2(3):033293. https://doi.org/10.1103/PhysRevResearch.2.033293

Romero J, Olson JP, Aspuru-Guzik A (2017) Quantum autoencoders for efficient compression of quantum data. Quantum Science and Technology 2(4):045001. https://doi.org/10.1088/2058-9565/aa8072

Sakhnenko A, O'Meara C, Ghosh KJB, et al (2022) Hybrid classical-quantum autoencoder for anomaly detection. Quantum Machine Intelligence 4(2):27. https://doi.org/10.1007/s42484-022-00075-z

San Sebastian Sein P, Cañizo M, Orús R (2025) Image classification with rotation-invariant variational quantum circuits. Physical Review Research 7:013082. https://doi.org/10.1103/PhysRevResearch.7.013082

Schatzki L, Larocca M, Nguyen QT, et al (2024) Theoretical guarantees for permutation-equivariant quantum neural networks. npj Quantum Information 10(1):12. https://doi.org/10.1038/s41534-024-00804-1

Schreiber FJ, Eisert J, Meyer JJ (2023) Classical surrogates for quantum learning models. Physical Review Letters 131(10):100803. https://doi.org/10.1103/PhysRevLett.131.100803

Schuirmann DJ (1987) A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability. Journal of Pharmacokinetics and Biopharmaceutics 15(6):657–680. https://doi.org/10.1007/BF01068419

Shi J, Wang W, Lou X, et al (2023) Parameterized Hamiltonian learning with quantum circuit. IEEE Transactions on Pattern Analysis and Machine Intelligence 45(5):6086–6095. https://doi.org/10.1109/TPAMI.2022.3203157

Shin S, Teo YS, Jeong H (2024) Dequantizing quantum machine learning models using tensor networks. Physical Review Research 6:023218. https://doi.org/10.1103/PhysRevResearch.6.023218

Singh G, Jin H, Merz KM (2026) Benchmarking MedMNIST dataset on real quantum hardware. Scientific Reports 16:9017. https://doi.org/10.1038/s41598-026-35605-3

Sitzmann V, Martel JNP, Bergman AW, et al (2020) Implicit neural representations with periodic activation functions. In: Advances in Neural Information Processing Systems, vol 33. Curran Associates, Inc., pp 7462–7473, URL https://proceedings.neurips.cc/paper/2020/hash/53c04118df112c13a8c34b38343b9c10-Abstract.html

Slabbert D, Petruccione F (2024) Hybrid quantum-classical feature extraction approach for image classification using autoencoders and quantum SVMs. arXiv preprint arXiv:2410.18814 https://doi.org/10.48550/arXiv.2410.18814

Stoudenmire EM, Schwab DJ (2016) Supervised learning with tensor networks. In: Advances in Neural Information Processing Systems

Strnadel D (2025) Differentiable energy-based regularization in GANs: a simulator-based exploration of VQE-inspired auxiliary losses. arXiv preprint arXiv:2512.12581

Strümpler Y, Postels J, Yang R, et al (2022) Implicit neural representations for image compression. In: Computer Vision – ECCV 2022, Lecture Notes in Computer Science, vol 13686. Springer, Cham, pp 74–91, https://doi.org/10.1007/978-3-031-19809-0_5

Sweke R, Recio-Armengol E, Jerbi S, et al (2025) Potential and limitations of random Fourier features for dequantizing quantum machine learning. Quantum 9:1640. https://doi.org/10.22331/q-2025-02-20-1640

Tancik M, Srinivasan PP, Mildenhall B, et al (2020) Fourier features let networks learn high frequency functions in low dimensional domains. In: Advances in Neural Information Processing Systems, vol 33. Curran Associates, Inc., pp 7537–7547, URL https://proceedings.neurips.cc/paper/2020/hash/55053683268957697aa39fba6f231c68-Abstract.html

Tang E (2019) A quantum-inspired classical algorithm for recommendation systems. In: Proceedings of the 51st Annual ACM SIGACT Symposium on Theory of Computing (STOC), pp 217–228, https://doi.org/10.1145/3313276.3316310

Temme K, Bravyi S, Gambetta JM (2017) Error mitigation for short-depth quantum circuits. Physical Review Letters 119(18):180509. https://doi.org/10.1103/PhysRevLett.119.180509

Tilly J, Chen H, Cao S, et al (2022) The variational quantum eigensolver: a review of methods and best practices. Physics Reports 986:1–128. https://doi.org/10.1016/j.physrep.2022.08.003

Ulyanov D, Vedaldi A, Lempitsky V (2020) Deep image prior. International Journal of Computer Vision 128:1867–1888. https://doi.org/10.1007/s11263-020-01303-4

Wang H, Tan J, Huang Y, et al (2024) Quantum image compression with autoencoders based on parameterized quantum circuits. Quantum Information Processing 23:41. https://doi.org/10.1007/s11128-023-04243-3

West MT, Heredge J, Sevior M, et al (2024) Provably trainable rotationally equivariant quantum machine learning. PRX Quantum 5(3):030320. https://doi.org/10.1103/PRXQuantum.5.030320

West MT, Heredge J, Sevior M, et al (2025) Erratum: provably trainable rotationally equivariant quantum machine learning [PRX Quantum **5**, 030320 (2024)]. PRX Quantum 6:020902. https://doi.org/10.1103/g4zk-79l9

Wilcoxon F (1945) Individual comparisons by ranking methods. Biometrics Bulletin 1(6):80–83. https://doi.org/10.2307/3001968

Xiao H, Rasul K, Vollgraf R (2017) Fashion-MNIST: a novel image dataset for benchmarking machine learning algorithms. arXiv preprint arXiv:1708.07747 https://doi.org/10.48550/arXiv.

1708.07747

Xu R, Wang X, Chen K, et al (2021) Positional encoding as spatial inductive bias in GANs. In: Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pp 13569–13578

Yang J, Shi R, Wei D, et al (2023) MedMNIST v2—a large-scale lightweight benchmark for 2D and 3D biomedical image classification. Scientific Data 10:41. https://doi.org/10.1038/s41597-022-01721-8

Yao XW, Wang H, Liao Z, et al (2017) Quantum image processing and its application to edge detection: theory and experiment. Physical Review X 7(3):031041. https://doi.org/10.1103/PhysRevX.7.031041

Zhai X, Xiao T, Huang J, et al (2025) Quantum neural compressive sensing for ghost imaging. Physical Review Applied 23(1):014018. https://doi.org/10.1103/PhysRevApplied.23.014018

Zhang Y, Lu K, Gao Y, et al (2013) NEQR: a novel enhanced quantum representation of digital images. Quantum Information Processing 12(8):2833–2860. https://doi.org/10.1007/s11128-013-0567-z

Zhao J, Qiao W, Zhang P, et al (2024) Quantum implicit neural representations. In: Proceedings of the 41st International Conference on Machine Learning, Proceedings of Machine Learning Research, vol 235. PMLR, pp 60940–60956, URL https://proceedings.mlr.press/v235/zhao24l.html

Zhou RG, Hu W, Fan P, et al (2017) Quantum realization of the bilinear interpolation method for NEQR. Scientific Reports 7(1):2511. https://doi.org/10.1038/s41598-017-02575-6