

## Concurrency Theory

Prof. Dr. Peter Thiemann  
Marius Weidner, Leonardo Mieschendahl


University of Freiburg  
Winter 2025

### Sheet 5

Due: Monday, 2025-12-01

#### Exercise 5.1

Consider the LTS below:



a) Decide whether state  $s$  satisfies the following HML formulae:

- 1)  $s \models \langle a \rangle tt$
- 2)  $s \models \langle b \rangle tt$
- 3)  $s \models [a] ff$
- 4)  $s \models [b] ff$
- 5)  $s \models [a] \langle b \rangle tt$
- 6)  $s \models \langle a \rangle \langle b \rangle tt$
- 7)  $s \models [a] \langle a \rangle [a] [b] ff$
- 8)  $s \models \langle a \rangle (\langle a \rangle tt \wedge \langle b \rangle tt)$
- 9)  $s \models [a] (\langle a \rangle tt \wedge \langle b \rangle tt)$
- 10)  $s \models \langle a \rangle ([b] [a] ff \wedge \langle b \rangle tt)$
- 11)  $s \models \langle a \rangle ([a] (\langle a \rangle tt \wedge [b] ff) \wedge \langle b \rangle ff)$

b) Evaluate the following expressions according to the HML semantics:

- 1)  $\llbracket [a] [b] ff \rrbracket$
- 2)  $\llbracket \langle a \rangle (\langle a \rangle tt \wedge \langle b \rangle tt) \rrbracket$
- 3)  $\llbracket [a] [a] [b] ff \rrbracket$
- 4)  $\llbracket [a] (\langle a \rangle tt \vee \langle b \rangle tt) \rrbracket$

---

If you have questions, please post a message in the dedicated [chat](#).




### Exercise 5.2

Find a single LTS (i.e. not three different LTS) with an initial state  $s$  such that the following statements are true:

- $s \models \langle a \rangle (\langle b \rangle \langle c \rangle tt \wedge \langle c \rangle tt)$
- $s \models \langle a \rangle \langle b \rangle ([a] ff \wedge [b] ff \wedge [c] ff)$
- $s \models [a] \langle b \rangle ([c] ff \wedge \langle a \rangle tt)$

### Exercise 5.3

Consider the three finitely branching LTS below:



Prove the following statements:

- a)  $s \not\sim t$
- b)  $s \not\sim v$
- c)  $t \not\sim v$

By providing distinguishing HML formulae.

### Exercise 5.4

Decide whether the following CCS statements are true or not. Provide distinguishing HML formulae for the expressions that are not strongly bisimilar.

- a)  $b.a.nil + b.nil \sim b.(a.nil + b.nil)$
- b)  $a.(b.c.nil + b.d.nil) \sim a.b.c.nil + a.b.d.nil$
- c)  $a.nil \parallel b.nil \sim a.b.nil + b.a.nil$
- d)  $(a.nil \parallel b.nil) + c.a.nil \sim a.nil \parallel (b.nil + c.nil)$