

Модуль 2 — Полное распределение действий по машинам

ISP

Настройка Chrony сервера

apt-get install -y chrony (скорее есть)

chronyc makestep && mcedit /etc/nginx/sites-available.d/reverse-proxy.conf

Location / {
auth_basic "Authorized access"

printf "WEB:\${(openssl passwd -apr1 'P@ssw0rd')}\n" > /etc/nginx/.htpasswd

chmod 644 /etc/nginx/.htpasswd

nginx -t

systemctl restart nginx

```
sed -i 's/^pool/#pool/' /etc/chrony.conf
cat << EOF >> /etc/chrony.conf
server ntp0.ntp-servers.net iburst prefer minstratum 4
local stratum 5
allow 0.0.0.0/0
EOF
systemctl restart chronyd.service
```

- Проверить:

```
chronyc tracking
```

systemctl restart chronyd

HQ-RTR

Настройка Static NAT для HQ

ip nat source static tcp 10.10.100.2 80 172.16.1.2 8080

ip nat source static tcp 10.10.100.2 2026 172.16.2.2 2026

ntp timezone utc+3

ntp server 172.16.1.1

write memory

(Статика вписана)

BR-RTR

Настройка Static NAT для BR

```
ip nat source static tcp 10.20.20.2 8080 172.16.1.2 8080
ip nat source static tcp 10.20.20.2 2026 172.16.2.2 2026
ntp timezone utc+3
ntp server 172.16.1.1
write memory
```

(Статика вписано)

BR-SRV

Настройка Samba DC

```
apt-get update
apt-get install -y task-samba-dc "bind bind-utils" – не скачен
```

```
samba-tool domain provision
--realm=AU-TEAM.IRPO --domain=AU-TEAM --adminpass='P@ssw0rd' --server-role=dc --
dns-backend=BIND9_DLZ
```

Чекай че предлагает,смотришь команду

```
systemctl enable --now samba
cp /var/lib/samba/private/krb5.conf /etc/krb5.conf
samba-tool user create hquser1 P@ssw0rd
samba-tool user create hquser2 P@ssw0rd
samba-tool user create hquser3 P@ssw0rd
samba-tool user create hquser4 P@ssw0rd
samba-tool user create hquser5 P@ssw0rd
```

```
samba-tool group add hq
samba-tool group addmembers hq hquser1,hquser2,hquser3,hquser4,hquser5
```

Настройка Ansibleвщслук

```
apt-get install -y ansible sshpass
```

```
mcedit /etc/ansible/hosts
```

```
[hq]
```

```
hq-srv ansible_host=10.10.100.2
```

```
hq-cli ansible_host=10.10.200.2
```

```
[branch]
```

```
br-rtr ansible_host=172.16.2.  
ansible all -m ping
```

Развёртывание Docker testapp

```
apt-get install -y docker docker-compose  
systemctl enable --now docker
```

```
mount /dev/sr0 /mnt  
docker load < /mnt/docker/site_latest.tar  
docker load < /mnt/docker/mariadb_latest.tar
```

```
mkdir /opt/testapp
```

```
nano /opt/testapp/docker-compose.yml
```

```
sed -i 's/^pool/#pool/' /etc/chrony.conf  
echo "server 172.16.1.1 iburst" >> /etc/chrony.conf  
systemctl restart chronyd
```

HQ-SRV

Создание RAID0

```
apt-get install -y mdadm
```

```
mdadm --create --verbose /dev/md0 --level=0 --raid-devices=2 /dev/sdb /dev/sdc
```

```
mkfs.ext4 /dev/md0  
mkdir /raid  
mount /dev/md0 /raid
```

```
mcedit /etc/fstab  
Добавить:mk  
/dev/md0 /raid ext4 defaults 0 0
```

(Говорят, что Реиди нфс преднастрой)

Настройка NFS сервера

```
apt-get install -y nfs-server nfs-utils  
apt-get install -y nfs-utils nfs-clients  
mkdir -p /raid/nfs
```

```
chmod 777 /raid/nfs
```

```
mcedit /etc/exports
```

```
/raid/nfs 10.10.200.0/28(rw,sync,no_root_squash) 10.20.30.0/29(rw,sync,no_root_squash)
```

```
sed -i 's#(rw,sync,no_root_squash)#(rw,sync,no_subtree_check,no_root_squash)#g'  
/etc/exports
```

```
exportfs -ra
```

```
exportfs -v
```

```
systemctl restart nfs-server
```

Настройка Apache + MariaDB

```
apt-get install -y lamp-server
```

```
mount /dev/sr0 /mnt
```

```
cp /mnt/web/index.php /var/www/html
```

```
cp /mnt/web/logo.png /var/www/html
```

```
systemctl enable --now mariadb
```

```
CREATE DATABASE webdb;
```

```
CREATE USER 'webc'@'localhost' IDENTIFIED BY 'P@ssw0rd';
```

```
GRANT ALL PRIVILEGES ON webdb.* TO 'webc'@'localhost';
```

```
FLUSH PRIVILEGES;
```

```
mc
```

```
sed -i 's/^pool/#pool/' /etc/chrony.conf  
echo "server 172.16.1.1 iburst" >> /etc/chrony.conf  
systemctl restart chronyd
```

HQ-CLI

Ввод в домен

```
apt-get install -y task-auth-ad-sssd
```

```
apt-get install -y yandex-browser-stable
```

```
apt-get install -y nfs-utils
```

```
useradd -m sshuser
```

```
passwd P@ssw0rd
```

```
realm join AU-TEAM.IRPO -U Administrator
```

(вроде преднастрой)

```
mcedit /etc/sudoers
```

#hq ALL=(ALL) NOPASSWD: /usr/bin/cat, /usr/bin/grep, /usr/bin/id (не прописано)

```
mkdir -p /mnt/nfs
chmod -R 777 /mnt/nfs
mcedit /etc/fstab
```

10.10.100.2:/raid/nfs /mnt/nfs nfs defaults.soft_netdev 0 0 (все прописано)

mount -a

```
sed -i 's/^pool/#pool/' /etc/chrony.conf
echo "server 172.16.1.1 iburst" >> /etc/chrony.conf
systemctl restart chronyd
```

Финальная проверка

```
systemctl status samba
cat /proc/mdstat
showmount -e
chronyc sources
ansible all -m ping
docker ps
nginx -t
```