

Модуль 2 — Полное распределение действий по машинам

BR-SRV

Настройка Samba DC

```
apt-get update
apt-get install -y task-samba-dc bind bind-utils

samba-tool domain provision --realm=AU-TEAM.IRPO --domain=AU-TEAM --
adminpass='P@ssw0rd' --server-role=dc --dns-backend=BIND9_DLZ

systemctl enable --now samba
host -t SRV _ldap._tcp.au-team.irpo
```

Создание пользователей и группы hq

```
samba-tool user create hquser1 P@ssw0rd
samba-tool user create hquser2 P@ssw0rd
samba-tool user create hquser3 P@ssw0rd
samba-tool user create hquser4 P@ssw0rd
samba-tool user create hquser5 P@ssw0rd

samba-tool group add hq
samba-tool group addmembers hq hquser1,hquser2,hquser3,hquser4,hquser5
```

Настройка Ansible

```
apt-get install -y ansible sshpass

nano /etc/ansible/hosts

[hq]
hq-srv ansible_host=192.168.100.2
hq-cli ansible_host=192.168.100.3
hq-rtr ansible_host=192.168.100.1

[branch]
br-rtr ansible_host=192.168.200.1

ansible all -m ping
```

Развёртывание Docker testapp

```
apt-get install -y docker docker-compose  
systemctl enable --now docker
```

```
mount /dev/sr0 /mnt  
docker load < /mnt/docker/site_latest.tar  
docker load < /mnt/docker/mariadb_latest.tar
```

```
mkdir /opt/testapp
```

```
nano /opt/testapp/docker-compose.yml
```

HQ-SRV

Создание RAID0

```
apt-get install -y mdadm
```

```
mdadm --create --verbose /dev/md0 --level=0 --raid-devices=2 /dev/sdb /dev/sdc
```

```
mkfs.ext4 /dev/md0  
mkdir /raid  
mount /dev/md0 /raid
```

```
nano /etc/fstab
```

Добавить:

```
/dev/md0 /raid ext4 defaults 0 0
```

Настройка NFS сервера

```
apt-get install -y nfs-kernel-server
```

```
mkdir -p /raid/nfs  
chmod 777 /raid/nfs
```

```
nano /etc/exports
```

```
/raid/nfs 192.168.100.0/24(rw, sync, no_subtree_check)
```

```
exportfs -ra  
systemctl restart nfs-server
```

Настройка Apache + MariaDB

```
apt-get install -y lamp-server
```

```
mount /dev/sr0 /mnt
```

```
cp /mnt/web/index.php /var/www/html  
cp /mnt/web/logo.png /var/www/html
```

```
systemctl enable --now mariadb
```

```
CREATE DATABASE webdb;  
CREATE USER 'webc'@'localhost' IDENTIFIED BY 'P@ssw0rd';  
GRANT ALL PRIVILEGES ON webdb.* TO 'webc'@'localhost';  
FLUSH PRIVILEGES;
```

Настройка Chrony клиента

```
apt-get install -y chrony
```

```
nano /etc/chrony.conf
```

```
server <IP_ISP> iburst
```

```
systemctl restart chronyd
```

HQ-CLI

Ввод в домен

```
get install -y task-auth-ad-sssd
```

```
realm join AU-TEAM.IRPO -U Administrator
```

```
id hquser1
```

Настройка ограниченного sudo

```
visudo
```

```
%hq ALL=(ALL) NOPASSWD: /usr/bin/cat, /usr/bin/grep, /usr/bin/id
```

Настройка NFS клиента

```
apt-get install -y nfs-utils
```

```
mkdir -p /mnt/nfs
```

```
nano /etc/fstab
```

```
192.168.100.2:/raid/nfs /mnt/nfs nfs defaults 0 0
```

```
mount -a
```

Установка Яндекс.Браузера

```
apt-get install -y yandex-browser-stable
```

```
yandex-browser
```

ISP

Настройка Chrony сервера

```
apt-get install -y chrony
```

```
nano /etc/chrony.conf
```

```
server pool.ntp.org iburst
```

```
local stratum 5
```

```
allow 192.168.0.0/16
```

```
systemctl restart chronyd
```

Настройка Reverse Proxy nginx

```
apt-get install -y nginx apache2-utils
```

```
nano /etc/nginx/sites-available/reverse-proxy
```

Настройка web-auth

```
htpasswd -c /etc/nginx/.htpasswd WEB
```

Пароль:

P@ssw0rd

```
nginx -t
```

```
systemctl restart nginx
```

HQ-RTR

Настройка Static NAT для HQ

```
conf t
```

```
ip nat source static tcp 192.168.100.2 80 172.16.1.2 8080  
ip nat source static tcp 192.168.100.2 2026 172.16.1.2 2026
```

```
write memory  
(Вписано)
```

BR-RTR

Настройка Static NAT для BR

```
conf t
```

```
ip nat source static tcp 192.168.200.2 8080 172.16.2.2 8080  
ip nat source static tcp 192.168.200.2 2026 172.16.2.2 2026
```

```
write memory  
(Вписано)
```

Финальная проверка

```
systemctl status samba  
cat /proc/mdstat  
showmount -e  
chronyc sources  
ansible all -m ping  
docker ps  
nginx -t
```