

CSCI 1061U

Programming Workshop 2

Arrays

Learning Objectives

- Introduction to Arrays
 - Declaring and referencing arrays
 - For-loops and arrays
 - Arrays in memory
- Arrays in Functions
 - Arrays as function arguments, return values
- Programming with Arrays
 - Partially Filled Arrays, searching, sorting
- Multidimensional Arrays

Introduction to Arrays

- Array is a collection of data of same type
 - An array of integers aggregates multiple integers
 - An array of doubles aggregates multiple doubles
- Used for lists of like items
 - Test scores, temperatures, names, etc.
 - Avoids declaring multiple simple variables
 - Can manipulate "list" as one entity

Declaring Arrays

- Declare the array (allocates memory)

`int score[5];`

- Declares array of 5 integers named "score"
- Similar to declaring five variables:

`int score[0], score[1], score[2], score[3], score[4]`

- Individual parts called many things:

- Indexed or subscripted variables
- "Elements" of the array
- Value in **brackets** called index or subscript
 - Numbered from 0 to size - 1

Accessing Arrays

- Access using index/subscript
 - `cout << score[3];`
- Note two uses of brackets:
 - In declaration, specifies SIZE of array
 - Anywhere else, specifies a subscript
- Size, subscript need not be literal
 - `int score[MAX_SCORES];`
 - `score[n+1] = 99;`
 - If n is 2, identical to: `score[3]`


Array Usage

- Powerful storage mechanism
- Can issue command like:
 - "Do this to i^{th} indexed variable" where i is computed by program
 - "Display all elements of array score"
 - "Fill elements of array score from user input"
 - "Find highest value in array score"
 - "Find lowest value in array score"

Array Program Example:

Sample output

```
Enter 5 scores:
5 9 2 10 6
The highest score is 10
The scores and their
differences from the highest are:
5 off by 5
9 off by 1
2 off by 8
10 off by 0
6 off by 4
```



```
05-01.cpp UNREGISTERED

1 //Reads in 5 scores and shows how much each
2 //score differs from the highest score.
3 #include <iostream>
4 using namespace std;
5
6 int main( )
7 {
8     int i, score[5], max;
9
10    cout << "Enter 5 scores:\n";
11    cin >> score[0];
12    max = score[0];
13    for (i = 1; i < 5; i++)
14    {
15        cin >> score[i];
16        if (score[i] > max)
17            max = score[i];
18        //max is the largest of the values score[0],..., score[i].
19    }
20
21    cout << "The highest score is " << max << endl
22         << "The scores and their\n"
23         << "differences from the highest are:\n";
24    for (i = 0; i < 5; i++)
25        cout << score[i] << " off by "
26             << (max - score[i]) << endl;
27
28    return 0;
29 }
```

Line 29, Column 2 0 misspelled words Spaces: 4 C++

for-loops with Arrays

- Natural counting loop
 - Naturally works well "counting through" elements of an array

- Example:

```
for (idx = 0; idx<5; idx++)  
{  
    cout << score[idx] << "off by "  
        << max - score[idx] << endl;  
}
```

- Loop control variable (idx) counts from 0 – 5

Major Array Pitfall

- Array indexes always start with zero!
- Zero is "first" number to computer scientists
- C++ will "let" you go beyond range
 - Unpredictable results
 - Compiler will not detect these errors!
- Up to programmer to "stay in range"

Major Array Pitfall Example

- Indexes range from 0 to (array_size – 1)
 - Example:

```
double temperature[24];    // 24 is array size
// Declares array of 24 double values called
temperature
```

 - They are indexed as:
temperature[0], temperature[1] ... temperature[23]
 - Common mistake:

```
temperature[24] = 5;
```

 - Index 24 is "out of range"!
 - No warning, possibly disastrous results

Defined Constant as Array Size

- Always use defined/named constant for array size

- Example:

```
const int NUMBER_OF_STUDENTS = 5;  
int score[NUMBER_OF_STUDENTS];
```

- Improves readability
- Improves versatility
- Improves maintainability

Uses of Defined Constant

- Use everywhere size of array is needed
 - In for-loop for traversal:

```
for (idx = 0; idx < NUMBER_OF_STUDENTS; idx++)  
{  
    // Manipulate array  
}
```
 - In calculations involving size:
lastIndex = (NUMBER_OF_STUDENTS – 1);
 - When passing array to functions (later)
- If size changes → requires only ONE change in program!

Ranged-Based For Loop

- The C++11 ranged-based for loop makes it easy to iterate over each element in a loop

- Format

```
for (datatype varname : array)
{
    // varname is set to each successive
    // element in the array
}
```

- Example

```
int arr[] = {20, 30, 40, 50};
for (int x : arr)
    cout << x << " ";
cout << endl;
```


Output: 20 30 40 50

Arrays in Memory

- Recall simple variables:
 - Allocated memory in an "address"
- Array declarations allocate memory for entire array
- Sequentially-allocated
 - Means addresses allocated "back-to-back"
 - Allows indexing calculations
 - Simple "addition" from array beginning (index 0)

An Array in Memory

Display 5.2 An Array in Memory



Initializing Arrays

- As simple variables can be initialized at declaration:

```
int price = 0; // 0 is initial value
```

- Arrays can as well:

```
int children[3] = {2, 12, 1};
```

- Equivalent to following:

```
int children[3];
```

```
children[0] = 2;
```

```
children[1] = 12;
```

```
children[2] = 1;
```


Auto-Initializing Arrays

- If fewer values than size supplied:
 - Fills from beginning
 - Fills "rest" with zero of array base type
- If array-size is left out
 - Declares array with size required based on number of initialization values
 - Example:
`int b[] = {5, 12, 11};`
 - Allocates array b to size 3

Arrays in Functions

- As arguments to functions
 - Indexed variables
 - An individual "element" of an array can be function parameter
 - Entire arrays
 - All array elements can be passed as "one entity"
- As return value from function
 - Can be done → chapter 10

Indexed Variables as Arguments

- Indexed variable handled same as simple variable of array base type

- Given this function declaration:

```
void myFunction(double par1);
```

- And these declarations:

```
int i; double n, a[10];
```

- Can make these function calls:

```
myFunction(i);           // i is converted to double  
myFunction(a[3]);        // a[3] is double  
myFunction(n);           // n is double
```

Subtlety of Indexing

- Consider:


`myFunction(a[i]);`

- Value of `i` is determined first
 - It determines which indexed variable is sent
- `myFunction(a[i*5]);`
- Perfectly legal, from compiler's view
- Programmer responsible for staying "in-bounds" of array

Entire Arrays as Arguments

- Formal parameter can be entire array
 - Argument then passed in function call is array name
 - Called "array parameter"
- Send size of array as well
 - Typically done as second parameter
 - Simple int type formal parameter

Entire Array as Argument Example



```
05-03.cpp UNREGISTERED
05-01.cpp 05-03.cpp
1 //Demonstrates an array parameter.
2 #include <iostream>
3 using namespace std;
4
5 void fillUp(int a[], int size);
6 //Precondition: size is the declared size of the array a.
7 //The user will type in size integers.
8 //Postcondition: The array a is filled with size integers
9 //from the keyboard.
10
11 int main( )
12 {
13     int a[5], b[10];
14
15     fillUp(a, 5);
16     fillUp(b, 10);
17
18     return 0;
19 }
20
21 void fillUp(int a[], int size)
22 {
23     cout << "Enter " << size << " numbers:\n";
24     for (int i = 0; i < size; i++)
25         cin >> a[i];
26     cout << "The last array index used is " << (size - 1) << endl;
27 }
```

Line 27, Column 2 0 misspelled words Spaces: 4 C++

Entire Array as Argument Example

- Given previous example:
- In some main() function definition, consider this calls:

```
int score[5], numberOfScores = 5;  
fillup(score, numberOfScores);
```

- 1st argument is entire array
- 2nd argument is integer value
- Note no brackets in array argument!

Array as Argument: How?

- What's really passed?
- Think of array as 3 "pieces"
 - Address of first indexed variable (arrName[0])
 - Array base type
 - Size of array
- Only 1st piece is passed!
 - Just the beginning address of array
 - Very similar to "pass-by-reference"

Array Parameters

- May seem strange
 - No brackets in array argument
 - Must send size separately
- One nice property:
 - Can use SAME function to fill any size array!
 - Exemplifies "re-use" properties of functions
 - Example:

```
int score[5], time[10];  
fillUp(score, 5);  
fillUp(time, 10);
```

The const Parameter Modifier

- Recall: array parameter actually passes address of 1st element
 - Similar to pass-by-reference
- Function can then modify array!
 - Often desirable, sometimes not!
- Protect array contents from modification
 - Use "const" modifier before array parameter
 - Called "constant array parameter"
 - Tells compiler to "not allow" modifications

Functions that Return an Array

- Functions cannot return arrays same way simple types are returned
- Requires use of a "pointer"
- Will be discussed in chapter 10...

Programming with Arrays

- Plenty of uses
 - Partially-filled arrays
 - Must be declared some "max size"
 - Sorting
 - Searching

Partially-filled Arrays

- Difficult to know exact array size needed
- Must declare to be largest possible size
 - Must then keep "track" of valid data in array
 - Additional "tracking" variable needed
 - `int numberUsed;`
 - Tracks current number of elements in array

Partially-filled Arrays Example:

Display 5.5 Partially Filled Array (1 of 5)

Display 5.5 Partially Filled Array

```
1 //Shows the difference between each of a list of golf scores and their average.
2 #include <iostream>
3 using namespace std;
4 const int MAX_NUMBER_SCORES = 10;

5 void fillArray(int a[], int size, int& numberUsed);
6 //Precondition: size is the declared size of the array a.
7 //Postcondition: numberUsed is the number of values stored in a.
8 //a[0] through a[numberUsed-1] have been filled with
9 //nonnegative integers read from the keyboard.

10 double computeAverage(const int a[], int numberUsed);
11 //Precondition: a[0] through a[numberUsed-1] have values; numberUsed > 0.
12 //Returns the average of numbers a[0] through a[numberUsed-1].

13 void showDifference(const int a[], int numberUsed);
14 //Precondition: The first numberUsed indexed variables of a have values.
15 //Postcondition: Gives screen output showing how much each of the first
16 //numberUsed elements of the array a differs from their average.
```

(continued)

Partially-filled Arrays Example:

Display 5.5 Partially Filled Array (2 of 5)

Display 5.5 Partially Filled Array

```
17  int main( )
18  {
19      int score[MAX_NUMBER_SCORES], numberUsed;

20      cout << "This program reads golf scores and shows\n"
21           << "how much each differs from the average.\n";

22      cout << "Enter golf scores:\n";
23      fillArray(score, MAX_NUMBER_SCORES, numberUsed);
24      showDifference(score, numberUsed);

25      return 0;
26  }
```

Partially-filled Arrays Example:

Display 5.5 Partially Filled Array (3 of 5)

```
27 void fillArray(int a[], int size, int& numberUsed)
28 {
29     cout << "Enter up to " << size << " nonnegative whole numbers.\n"
30         << "Mark the end of the list with a negative number.\n";
31     int next, index = 0;
32     cin >> next;
33     while ((next >= 0) && (index < size))
34     {
35         a[index] = next;
36         index++;
37         cin >> next;
38     }
39     numberUsed = index;
40 }
```


Partially-filled Arrays Example:

Display 5.5 Partially Filled Array (4 of 5)

```
41 double computeAverage(const int a[], int numberUsed)
42 {
43     double total = 0;
44     for (int index = 0; index < numberUsed; index++)
45         total = total + a[index];
46     if (numberUsed > 0)
47     {
48         return (total/numberUsed);
49     }
50     else
51     {
52         cout << "ERROR: number of elements is 0 in computeAverage.\n"
53             << "computeAverage returns 0.\n";
54         return 0;
55     }
56 }
```

Partially-filled Arrays Example:

Display 5.5 Partially Filled Array (5 of 5)

Display 5.5 Partially Filled Array

```
57 void showDifference(const int a[], int numberUsed)
58 {
59     double average = computeAverage(a, numberUsed);
60     cout << "Average of the " << numberUsed
61         << " scores = " << average << endl
62         << "The scores are:\n";
63     for (int index = 0; index < numberUsed; index++)
64         cout << a[index] << " differs from average by "
65             << (a[index] - average) << endl;
66 }
```

SAMPLE DIALOGUE

This program reads golf scores and shows how much each differs from the average.

Enter golf scores:
Enter up to 10 nonnegative whole numbers.
Mark the end of the list with a negative number.

69 74 68 -1

Average of the 3 scores = 70.3333

The scores are:

69 differs from average by -1.33333
74 differs from average by 3.66667
68 differs from average by -2.33333

Global Constants vs. Parameters

- Constants typically made "global"
 - Declared above main()
- Functions then have scope to array size constant
 - No need to send as parameter then?
 - Technically yes
 - Why should we anyway?
 - Function definition might be in separate file
 - Function might be used by other programs!

Searching an Array

- Very typical use of arrays
- Display 5.6 next slide

Display 5.6

Searching an Array (1 of 4)

Display 5.6 Searching an Array

```
1 //Searches a partially filled array of nonnegative integers.
2 #include <iostream>
3 using namespace std;
4 const int DECLARED_SIZE = 20;

5 void fillArray(int a[], int size, int& numberUsed);
6 //Precondition: size is the declared size of the array a.
7 //Postcondition: numberUsed is the number of values stored in a.
8 //a[0] through a[numberUsed-1] have been filled with
9 //nonnegative integers read from the keyboard.

10 int search(const int a[], int numberUsed, int target);
11 //Precondition: numberUsed is <= the declared size of a.
12 //Also, a[0] through a[numberUsed -1] have values.
13 //Returns the first index such that a[index] == target,
14 //provided there is such an index; otherwise, returns -1.
```

Display 5.6

Searching an Array (2 of 4)

```
15  int main( )
16  {
17      int arr[DECLARED_SIZE], listSize, target;
18
19      fillArray(arr, DECLARED_SIZE, listSize);
20
21      char ans;
22      int result;
23      do
24      {
25          cout << "Enter a number to search for: ";
26          cin >> target;
27
28          result = search(arr, listSize, target);
29          if (result == -1)
30              cout << target << " is not on the list.\n";
31          else
32              cout << target << " is stored in array position "
33                  << result << endl
34                  << "(Remember: The first position is 0.)\n";
```

Display 5.6

Searching an Array (3 of 4)

Display 5.6 Searching an Array

```
32         cout << "Search again?(y/n followed by Return): ";
33         cin >> ans;
34     } while ((ans != 'n') && (ans != 'N'));
35     cout << "End of program.\n";
36     return 0;
37 }

38 void fillArray(int a[], int size, int& numberUsed)
39     <The rest of the definition of fillArray is given in Display 5.5>
40 int search(const int a[], int numberUsed, int target)
41 {
42     int index = 0;
43     bool found = false;
44     while ((!found) && (index < numberUsed))
45     if (target == a[index])
46         found = true;
47     else
48         index++;
```

Display 5.6

Searching an Array (4 of 4)

```
49     if (found)
50         return index;
51     else
52         return -1;
53 }
```

SAMPLE DIALOGUE


Enter up to 20 nonnegative whole numbers.
Mark the end of the list with a negative number.
10 20 30 40 50 60 70 80 -1
Enter a number to search for: **10**
10 is stored in array position 0
(Remember: The first position is 0.)
Search again?(y/n followed by Return): **y**
Enter a number to search for: **40**
40 is stored in array position 3
(Remember: The first position is 0.)
Search again?(y/n followed by Return): **y**
Enter a number to search for: **42**
42 is not on the list.
Search again?(y/n followed by Return): **n**
End of program.

Sorting an Array:

Display 5.7 Selection Sort

- Selection Sort Algorithm

Display 5.7 Selection Sort



Sorting an Array Example:

Display 5.8 Sorting an Array (1 of 4)

Display 5.8 Sorting an Array

```
1  //Tests the procedure sort.
2  #include <iostream>
3  using namespace std;

4  void fillArray(int a[], int size, int& numberUsed);
5  //Precondition: size is the declared size of the array a.
6  //Postcondition: numberUsed is the number of values stored in a.
7  //a[0] through a[numberUsed - 1] have been filled with
8  //nonnegative integers read from the keyboard.
9  void sort(int a[], int numberUsed);
10 //Precondition: numberUsed <= declared size of the array a.
```

(continued)

Sorting an Array Example:

Display 5.8 Sorting an Array (2 of 4)

Display 5.8 **Sorting an Array**

```
11  //The array elements a[0] through a[numberUsed - 1] have values.
12  //Postcondition: The values of a[0] through a[numberUsed - 1] have
13  //been rearranged so that a[0] <= a[1] <= ... <= a[numberUsed - 1].

14  void swapValues(int& v1, int& v2);
15  //Interchanges the values of v1 and v2.

16  int indexOfSmallest(const int a[], int startIndex, int numberUsed);
17  //Precondition: 0 <= startIndex < numberUsed. Reference array elements
18  //have values. Returns the index i such that a[i] is the smallest of the
19  //values a[startIndex], a[startIndex + 1], ..., a[numberUsed - 1].

20  int main( )
21  {
22      cout << "This program sorts numbers from lowest to highest.\n";

23      int sampleArray[10], numberUsed;
24      fillArray(sampleArray, 10, numberUsed);
25      sort(sampleArray, numberUsed);

26      cout << "In sorted order the numbers are:\n";
27      for (int index = 0; index < numberUsed; index++)
28          cout << sampleArray[index] << " ";
29      cout << endl;

30      return 0;
31  }
```

Sorting an Array Example:

Display 5.8 Sorting an Array (3 of 4)

```
32 void fillArray(int a[], int size, int& numberUsed)
33     <The rest of the definition of fillArray is given in Display 5.5.>
```

```
34 void sort(int a[], int numberUsed)
35 {
36     int indexOfNextSmallest;
37     for (int index = 0; index < numberUsed - 1; index++)
38     {//Place the correct value in a[index]:
39         indexOfNextSmallest =
40             indexOfSmallest(a, index, numberUsed);
41         swapValues(a[index], a[indexOfNextSmallest]);
42         //a[0] <= a[1] <= ... <= a[index] are the smallest of the original array
43         //elements. The rest of the elements are in the remaining positions.
44     }
45 }
```

```
46 void swapValues(int& v1, int& v2)
47 {
48     int temp;
49     temp = v1;
50     v1 = v2;
```

Sorting an Array Example:

Display 5.8 Sorting an Array (4 of 4)

Display 5.8 **Sorting an Array**

```
51     v2 = temp;
52 }
53
54 int indexOfSmallest(const int a[], int startIndex, int numberUsed)
55 {
56     int min = a[startIndex],
57         indexOfMin = startIndex;
58     for (int index = startIndex + 1; index < numberUsed; index++)
59         if (a[index] < min)
60         {
61             min = a[index];
62             indexOfMin = index;
63             //min is the smallest of a[startIndex] through a[index]
64         }
65     return indexOfMin;
66 }
```

SAMPLE DIALOGUE

This program sorts numbers from lowest to highest.
Enter up to 10 nonnegative whole numbers.
Mark the end of the list with a negative number.
80 30 50 70 60 90 20 30 40 -1
In sorted order the numbers are:
20 30 30 40 50 60 70 80 90

Multidimensional Arrays

- Arrays with more than one index
 - `char page[30][100];`
 - Two indexes: An "array of arrays"
 - Visualize as:
page[0][0], page[0][1], ..., page[0][99]
page[1][0], page[1][1], ..., page[1][99]
...
page[29][0], page[29][1], ..., page[29][99]
- C++ allows any number of indexes
 - Typically no more than two

Multidimensional Array Parameters

- Similar to one-dimensional array
 - 1st dimension size not given
 - Provided as second parameter
 - 2nd dimension size IS given

- Example:

```
void DisplayPage(const char p[][100], int sizeDimension1)
{
    for (int index1=0; index1<sizeDimension1; index1++)
    {
        for (int index2=0; index2 < 100; index2++)
            cout << p[index1][index2];
        cout << endl;
    }
}
```

Summary 1

- Array is collection of "same type" data
- Indexed variables of array used just like any other simple variables
- for-loop "natural" way to traverse arrays
- Programmer responsible for staying "in bounds" of array
- Array parameter is "new" kind
 - Similar to call-by-reference

Summary 2

- Array elements stored sequentially
 - "Contiguous" portion of memory
 - Only address of 1st element is passed to functions
- Partially-filled arrays → more tracking
- Constant array parameters
 - Prevent modification of array contents
- Multidimensional arrays
 - Create "array of arrays"