

Bitwise Operators in C - GeeksforGeeks

Source: <https://www.geeksforgeeks.org/bitwise-operators-in-c-cpp/>

Courses Tutorials Practice Jobs C Tutorial Interview Questions Examples Quizzes Projects Cheatsheet File Handling Multithreading Memory Layout DSA in C C++ Technical Scripter 2026 Explore C Basics C Language Introduction Identifiers in C Keywords in C Variables in C Data Types in C Operators in C Decision Making in C (if, if..else, Nested if, if-else-if) Loops in C Functions in C Arrays & Strings Arrays in C Strings in C Pointers and Structures Pointers in C Function Pointer in C Unions in C Enumeration (or enum) in C Structure Member Alignment, Padding and Data Packing Memory Management Memory Layout of C Programs Dynamic Memory Allocation in C What is Memory Leak? How can we avoid? File & Error Handling File Handling in C Read/Write Structure From/to a File in C Error Handling in C Using goto for Exception Handling in C Error Handling During File Operations in C Advanced Concepts Variadic Functions in C Signals in C language Socket Programming in C _Generics Keyword in C Multithreading in C Three 90 Challenge 90% Refund Bitwise Operators in C Last Updated : 13 Dec, 2025 In C, bitwise operators are used to perform operations directly on the binary representations of numbers. These operators work by manipulating individual bits (0s and 1s) in a number. The following 6 operators are bitwise operators (also known as bit operators as they work at the bit-level). They are used to perform bitwise operations in C. The & (bitwise AND) in C takes two numbers as operands and does AND on every bit of two numbers. The result of AND is 1 only if both bits are 1. The | (bitwise OR) in C takes two numbers as operands and does OR on every bit of two numbers. The result of OR is 1 if any of the two bits is 1. The ^ (bitwise XOR) in C takes two numbers as operands and does XOR on every bit of two numbers. The result of XOR is 1 if the two bits are different. The << (left shift) in C takes two numbers, the left shifts the bits of the first operand, and the second operand decides the number of places to shift. The >> (right shift) in C takes two numbers, right shifts the bits of the first operand, and the second operand decides the number of places to shift. The ~ (bitwise NOT) in C takes one number and inverts all bits of it. Let's look at the truth table of the bitwise operators.

X	Y	X & Y	X Y	X ^ Y	0 0	0 1	1 0	1 1
0	0	0	0	0	0	0	1	1
0	1	0	1	1	0	1	1	0
1	0	0	1	1	0	1	1	0
1	1	1	1	0	0	1	1	1

```
C#include <stdio.h> int main () { // a = 5 (00000101 in 8-bit binary) // b = 9 (00001001 in 8-bit binary) unsigned int a = 5, b = 9; // The result is 00000001 printf ( "a&b = %u\n", a & b ); // The result is 00001101 printf ( "a|b = %u\n", a | b ); // The result is 00001100 printf ( "a^b = %u\n", a ^ b ); // The result is 11111111111111111111111111111111010 (assuming 32-bit unsigned int) printf ( "~a = %u\n", a = ~ a ); // The result is 00010010 printf ( "b<<1 = %u\n", b << 1 ); // The result is 00000100 printf ( "b>>1 = %u\n", b >> 1 ); return 0; }
```

Output a&b = 1 a|b = 13 a^b = 12 ~a = 4294967290 b<<1 = 18 b>>1 = 4

Interesting Facts About Bitwise Operators

Shift Operators : Left-shift (<<) and right-shift (>>) should not be used with negative numbers. Shifting by a negative number or more than the size of the integer leads to undefined behavior. No shift occurs if the number of shifts is 0.

Bitwise OR (|) : The OR of two numbers is like adding them if no carry occurs. If there is a carry, the sum is calculated as a | b + a & b.

Bitwise XOR (^) : Very useful in programming problems. For example, finding the odd occurring number in a set where all other numbers occur even times can be done efficiently using XOR.

```
C#include <stdio.h> int main ( void ) { int arr [] = { 12, 12, 14, 90, 14, 14, 14 }; int n = sizeof ( arr ) / sizeof ( arr [ 0 ] ); int res = 0, i; for ( int i = 0; i < n; i ++ ) res ^= arr [ i ]; printf ( "%d", res ); return 0; }
```

Output 90

Logical vs Bitwise : Bitwise operators should not replace logical operators. Logical operators (&&, ||, !) return 0 or 1, while bitwise operators return an integer value.

```
C#include <stdio.h> int main () { int x = 2, y = 5; ( x & y ) ? printf ( "True " ) : printf ( "False " ); ( x && y ) ? printf ( "True " ) : printf ( "False " ); return 0; }
```

Output False True

Shift and Arithmetic : Left-shift (<<) is equivalent to multiplication by 2, and right-shift (>>) is equivalent to division by 2 for positive numbers.

```
C#include <stdio.h> int main () { int x = 19; printf ( "x << 1 = %d\n", x << 1 ); printf ( "x >> 1 = %d", x >> 1 ); return 0; }
```

Output x << 1 = 38 x >> 1 = 9

Check Odd/Even : The AND operator (&) can quickly check if a number is odd or even. (x & 1) is non-zero if x is odd, and 0 if even.

```
C#include <stdio.h> int main () { int x = 19; ( x & 1 ) ? printf ( "Odd" ) : printf ( "Even" ); return 0; }
```

Output Odd

Time Complexity: O(1) **Auxiliary Space:** O(1)

Bitwise NOT (~) : Should be used carefully. Applying ~ can produce large numbers for unsigned variables or negative numbers for signed variables due to 2's complement representation.

```
C#include <stdio.h> int main () { unsigned int x = 1; printf ( "Signed Result %d\n", ~ x ); printf ( "Unsigned Result %u", ~ x ); return 0; }
```

Output Signed Result -2 Unsigned Result 4294967294

Note The output of the above program is compiler dependent .

Comment Article

Tags: Article Tags: C Language Bitwise-XOR cpp-operator C-Operators