LOSSLens

Complete Feature Documentation

Source-based technical and product inventory

Confidential technical review edition

Table of Contents

Table of Contents 2

1. Product overview 3

2. Public website 3

- Landing page . . . 3
- Authentication entry pages . . . 3
- Pricing and family join . . . 3

3. User accounts and profiles 3

4. Gambling recovery and CBT 3

- Recovery diary . . . 3
- CBT modules . . . 3
- Urge Toolkit . . . 4
- Gamification . . . 4
- Crisis support . . . 4

5. AI companion and chat 4

6. Community features 4

- The Circle . . . 4
- Whispers . . . 4

7. Events and support 4

8. Media and personal commitments 5

- Monthly Mirror . . . 5
- Precious Pacts . . . 5

9. Admin dashboard 5

10. Super Admin dashboard 5

11. Backend and database architecture 5

- RPC functions evidenced by source . . . 5
- Storage . . . 6
- Realtime . . . 6

12. Security and privacy 6

13. External integrations 6

14. Deployment and configuration 6

15. Outstanding work 6

16. Master feature matrix 7

- Route coverage matrix . . . 7

LossLens Complete Feature Documentation

Version: source audit current to this delivery

Scope note. This document describes behavior visible in the checked-in frontend, Edge Functions, Supabase migration files, and existing database reports. It does not claim live Supabase runtime behavior has been tested.

1. Product overview

LossLens is a Vite/React recovery application built around gambling-recovery diary, CBT, crisis support, AI-assisted chat, community support, events, resources, supporter relationships, media reflections, and administration. The browser application uses Supabase authentication, PostgREST tables, RPC functions, Storage, Realtime, and an Edge Function. Groq is called directly from the browser in the current implementation.

The application separates ordinary users, administrators, and Super Administrators through both frontend route guards and profile roles. Database RLS remains necessary for security because browser route checks are not a security boundary.

2. Public website

Landing page

The landing page presents product entry points and navigation to signup, login, pricing, and related public content. The implementation is confirmed by src/pages/public/Landing.jsx.

Authentication entry pages

Login supports email/password and Google OAuth. Password reset requests a Supabase recovery email and the reset page applies the returned recovery session. Signup collects profile identity, performs Supabase signup, creates or updates the profile, and configures an email confirmation redirect.

Pricing and family join

Pricing is implemented as a frontend pricing presentation. Family join accepts supporter invitation context and is documented as partially implemented because the anonymous acceptance path and exact session model require database and migration decisions.

3. User accounts and profiles

Profiles support full name, username, phone, goal, avatar, preferences, risk level, streak information, clean-start date, money saved, freeze state, badges and accountability fields. Signup and dashboard creation are implemented. Profile updates include profile-password reporting, contact details, avatar emoji or file upload, preferences, and account deletion.

Ordinary users are client-guarded through profiles.role. Assignment and entitlement changes require server-side database authorization. Client-side role checks are duplicated with the migration RLS and privileged-field protections, but live policy enforcement remains unverified.

4. Gambling recovery and CBT

Recovery diary

Diary creates and updates one daily entry, lists recent entries, records mood, triggers, coping, thoughts, notes, amount gambled, gamble state, and updates streak/money-saved profile fields. It uses owner-filtered CRUD on diary_entries and profile updates.

CBT modules

CBT modules retrieve completed progress and upsert module completion, answers, title, and completion time. The source-level contract indicates (user_id, module_id) is the logical completion identity, but exact live constraints remain migration-dependent.

Urge Toolkit

Urge Toolkit provides client-side coping exercises and controls, including timers, breathing, delay, grounding, and crisis access where implemented. This page should be treated as UI and interaction behavior backed by frontend state, rather than a complete server event audit.

Gamification

Badges, streak days, money saved, freeze days, and recovery coins are implemented in frontend logic. add_recovery_coins is disabled in the migration package, so recovery coin calls are unavailable until a secure reward mechanism is established.

Crisis support

Crisis chat detection writes crisis_alerts; admins can review unresolved alerts and update approved resolution/escalation fields subject to database authorization.

5. AI companion and chat

The AIChat component sends messages through the browser Groq integration. src/lib/groq.js retrieves profile and recovery context, injects crisis safeguards, calls a Groq chat-completions endpoint, and persists user/assistant history in chat_history using the current canonical user_id, role, message, created_at fields where supported by the migration package.

The interface provides loading and error states, suggested prompts, voice recognition, speech synthesis, and text chat. Direct browser VITE_GROQ_API_KEY exposure is a security risk. Runtime integration success, provider availability, and exact database history behavior are unverified.

6. Community features

The Circle

Circle supports room selection, membership state, unread counts, recent membership activity, text messages, deletion, Realtime inserts/deletes, and local reaction state. The RPC increment_reaction is called but canonical reaction columns and mapping are unresolved; reaction functionality is therefore not fully verifiable.

Whispers

Whispers implements matching, active private matches, candidate selection, reporting, and message sending/listing. Participant authorization, immutable match identity, report validation, and identity provisioning are subject to migration review and live policy testing.

7. Events and support

Events list active public or authenticated event records, user RSVPs, attendance updates, discussion replies, and event messages. Admin pages create/update/cancel or manage events, including event capacity and scheduling fields.

Groups support membership, join/leave, messages, and active-room visibility. Group message flow requires RLS and membership checks. Broadcasts target notifications or broadcast recipient records, with scheduled/publication visibility enforced by planned publication state.

The supporter flow creates invitations, shares public join links or lookup values, stores supporter messages and feedback, and supports crisis-contact designation. Anonymous public lookup and supporter chat acceptance require explicit migration decisions; direct anonymous table access is not treated as confirmed.

8. Media and personal commitments

Monthly Mirror

Monthly Mirror records browser audio/video media, persists metadata, creates signed/download URLs as product work proceeds, updates rating or reflection fields, and deletes recordings. The current source uses public URLs and is not compatible with the private mirror-recordings bucket without application changes.

Precious Pacts

Precious Pacts supports written metadata and voice recording, playback counts, removal, and public URL retrieval. Written pacts use storage_path = 'written' as canonical metadata. Private bucket signed URL changes are still required.

9. Admin dashboard

Admin pages implement:

• crisis alert monitoring and resolution/escalation;

• event creation and management;

• group creation and membership management;

• resource catalogue management;

• analytics and reporting;

• broadcast creation and recipient delivery.

Admin access to private recovery records is not restored by the migration package. This includes diary entries, CBT progress, chat history, mirror recordings, and Precious Pacts.

10. Super Admin dashboard

Super Admin pages implement user and administrator management, email lookup through get_user_email, password-reset invocation, role/status and subscription updates, system settings, audit logs, B2B clients, insurance partners, grant applications, and chat history viewing.

The Super Admin chat viewer conflicts with owner-only chat privacy because direct Super Admin table access was removed. Runtime compatibility requires a future privacy-reviewed server function or product decision rather than migration RLS bypass.

11. Backend and database architecture

The application has source evidence for at least the following tables:

profiles, diary_entries, cbt_progress, badges, notifications, chat_history, crisis_alerts, resources, resource_ratings, resource_suggestions, events, event_rsvps, event_messages, event_discussions, broadcasts, broadcast_recipients, groups, group_members, circle_rooms, circle_room_members, circle_messages, whispers_matches, whispers_messages, whispers_reports, mirror_recordings, precious_pacts, supporter_invitations, supporter_messages, supporter_feedback, audit_logs, b2b_clients, grant_applications, insurance_partners, system_settings

Migration reports also indicate additional tables or views used in administrative workflows. Wildcard queries do not prove every column. Canonical conflicts, exact foreign keys, defaults, nullability and uniqueness must remain based on migration/old-schema evidence; no live schema dump has been obtained.

RPC functions evidenced by source

• increment_reaction — Circle reactions; mapping unresolved.

• increment_pact_play_count — pact playback count update.

• add_recovery_coins — recovery rewards; disabled/revoked in migration package.

• get_user_email — privileged email lookup.

• supporter_invitation_lookup — public invite lookup.

Additional Edge Function calls include admin-reset-password.

Storage

• avatars: public profile images are intended.

• mirror-recordings: owner-private media.

• precious-pacts: owner-private media.

Realtime

Confirmed subscription targets include circle_messages, notifications, crisis_alerts, and audit_logs; Realtime publication membership requires migration execution and live verification.

12. Security and privacy

Confirmed browser-only controls are insufficient. Authentication depends on Supabase sessions. Route guards check profile roles for ordinary user, admin, and Super Admin views. Privileged profile fields, crisis escalation and resolution, broadcasts, event administrator replies, Circle membership, Whispers identity/reporting, support invitations, Storage objects, and audit writes require database enforcement.

Private recovery records remain owner-only in the migration design. Administrative access has deliberately been excluded for those records. Direct browser Groq access and the hardcoded site password are known security risks requiring changes outside the migration package.

13. External integrations

• **Supabase:** authentication, database, Storage, Realtime, RPC, and Edge Functions.

• **Groq:** browser direct AI chat completions using environment configuration.

• **Resend:** server-side invite delivery only if the checked-in Edge Function configuration includes it.

• **Google OAuth:** browser OAuth provider.

• **Email providers:** Supabase authentication and password recovery.

No secret value is reproduced in this document. Configuration names include VITE_SUPABASE_URL, VITE_SUPABASE_ANON_KEY, and VITE_GROQ_API_KEY.

14. Deployment and configuration

Deployment is expected on Vercel with environment variables supplied at build and runtime. Supabase URL/keys come from Vite environment variables. OAuth redirect allowlists and confirmation URLs must match the deployed host. No live deployment or database execution has been verified by this documentation audit.

15. Outstanding work

• Replace browser Groq requests with a server-side or Edge Function proxy.

• Replace private Media public URL calls with signed URL flows and application change/error handling.

• Restore circle reaction functionality only after canonical mappings are established.

• Validate Whispers identity provisioning and anonymous supporter flows against the live database.

• Replace direct Super Admin chat viewing with privacy-reviewed server access or remove the feature.

• Reconsider recovery coin reward security and authorization.

• Remove or protect the hardcoded development site password.

• Replace or validate Kingsly OAuth redirect URLs.

• Verify all migration and RLS behavior in isolated runtime validation before deployment.

16. Master feature matrix

See LOSSLENS_FEATURE_IMPLEMENTATION_MATRIX.xlsx for route-by-route coverage.

|---|---|---|---|---|

Route coverage matrix

Route	Feature	Role	Status
*	Catch-all redirect to login	All	Fully implemented
/	Landing	Public	Fully implemented
/login	Login	Public	Fully implemented
/signup	Signup	Public	Fully implemented
/forgot-password	Forgot password	Public	Fully implemented
/reset-password	Reset password	Public	Fully implemented
/pricing	Pricing	Public	Fully implemented
/family-join	Family join	Supporter/public	Partially implemented
/dashboard	Dashboard	User	Fully implemented
/diary	Recovery diary	User	Fully implemented
/cbt	CBT modules	User	Fully implemented
/urge-toolkit	Urge Toolkit	User	Fully implemented
/circle	The Circle	User	Partially implemented
/whispers	Whispers	User	Partially implemented
/events	Events	User	Fully implemented
/resources	Resources	User	Fully implemented
/profile	Profile	User	Fully implemented
/precious-pact	Precious Pacts	User	Partially implemented
/monthly-mirror	Monthly Mirror	User	Partially implemented
/family-portal	Family/supporter portal	User/supporter	Partially implemented
/onboarding	Onboarding	User	Fully implemented
/admin	Admin dashboard	Admin	Fully implemented
/admin/events	Manage events	Admin	Fully implemented
/admin/groups	Manage groups	Admin	Fully implemented
/admin/resources	Manage resources	Admin	Fully implemented
/admin/analytics	User analytics	Admin	Fully implemented
/admin/broadcast	Broadcasts	Admin	Fully implemented
/admin/crisis	Crisis alerts	Admin	Fully implemented
/super-admin	Super Admin dashboard	Super Admin	Fully implemented
/super-admin/users	User management	Super Admin	Fully implemented
/super-admin/admins	Admin management	Super Admin	Fully implemented
/super-admin/settings	System settings	Super Admin	Fully implemented
/super-admin/logs	Audit logs	Super Admin	Fully implemented
/super-admin/b2b	B2B clients	Super Admin	Fully implemented
/super-admin/insurance	Insurance partners	Super Admin	Fully implemented

Route	Feature	Role	Status
/super-admin/grants	Grant applications	Super Admin	Fully implemented
/super-admin/chats	Chat viewer	Super Admin	Broken or requires investigation