Stakeholder Agent System

Final Implementation Report

Regis University - MSSE 692: Software Engineering Practicum I

Matt Bass, Anthony Perez, Joseph Turner, Ramesh Kondala
2-22-2026

Executive Summary

The Stakeholder Agent System is an AI-driven web application designed to simulate realistic stakeholder interactions for students practicing requirements elicitation. The system addresses a documented gap in academic environments where students often lack access to real stakeholders and instead invent requirements rather than discover them through structured inquiry.

The MVP consists of:

- A TanStack Start frontend providing a chat-based interface
- A FastAPI backend AI service responsible for LLM orchestration
- A PostgreSQL (Neon) database for persistent storage
- JWT-based authentication between frontend and backend
- An OpenAI-compatible LLM for stakeholder response generation

The system enables students to log in, create and manage elicitation sessions, engage in multi-turn AI conversations, and resume prior sessions with full message history preserved.

The following core features are fully operational:

- AI Chat Interface: Multi-turn conversational elicitation with optimistic UI updates and non-blocking behavior.
- Conversation Management: Users can create, retrieve, and resume multiple elicitation sessions.
- Persistent Storage: Conversations and messages are durably stored and isolated by user.
- Authentication & Authorization: Users must authenticate, and backend endpoints validate ownership before processing messages.
- Async Architecture: AI calls are handled asynchronously, preserving UI responsiveness during backend processing.
- Error Handling: Global UI error handling and structured backend responses improve reliability.

The system successfully satisfies the Availability/Reliability requirement of session recovery and maintains UI responsiveness during AI calls.

The following features were intentionally deferred to deliver the MVP within the academic timeline:

- Agent sentiment scoring and behavioral modulation
- Multiple stakeholder personas and configurable project scenarios
- Streaming AI responses
- Backend coverage 69%
- Front-end coverage: 8% (many UI components do not need testing but have not yet been excluded from coverage)
- Total coverage: 38.5%

Additionally, the performance requirement of “95% of responses within 5 seconds” was not met. Measured average latency was ~8 seconds, primarily due to external LLM inference time.

Key Achievements

- Clear separation of concerns between frontend, backend AI service, and database layers.
- Durable session persistence enabling asynchronous student workflows.
- Structured persona-driven AI prompting with controlled context handling.
- Traceable backend logging with measurable performance data.
- Strong alignment with documented architectural drivers (security, availability, modifiability).

System Status

Current Status: Functional MVP

The system is stable and usable in a classroom setting but is not production ready. Performance variability due to external LLM latency and the absence of configurability, analytics, and formal load testing limit production deployment.

However, the architecture provides a strong foundation for future expansion into multi-persona simulation, instructor analytics, streaming responses, and performance optimization.

Overall, the Stakeholder Agent System demonstrates the technical feasibility and educational value of AI-driven stakeholder simulation while clearly documenting remaining technical debt and improvement opportunities.

Features Completed

For each major feature implemented:

Feature description: What it does

Implementation approach: How you built it

Screenshots/evidence: Show it working

Requirements mapping: Links back to Week 2 requirements

Feature Name

Description	Chat View – Main chat window for sending and receiving messages
Implementation Approach	React UI using tanstack query hooks to send and receive messages from the AI. We use optimistic updates to insert the users' message into the chat and wait for a response from the LLM. Message view is driven by database message table query by conversation id and user id.
Screenshots / Evidence	
Requirements Mapping	This maps directly to the requirement of being able to elicit requirements from the AI stakeholder. It also maps to the responsive user interface that feels fast to use.

Feature Name

Description	Message API and Queries
Implementation Approach	Implement frontend access to API. Create server functions for getting messages from the database.
Screenshots / Evidence	https://github.com/project-steak-holder/ai-frontend/pull/7
Requirements Mapping	This maps to being able to elicit requirements from the AI Stakeolder.

Feature Name

Description	Error Handler for UI
Implementation Approach	Added a global error handler to gracefully catch UI errors
Screenshots / Evidence	
Requirements Mapping	This maps to resiliency and reliability of the application. Providing a better user experience by gracefully handling errors and displaying information rather than crashing.

Conversation Query Function

Description	Retrieves the full message history for a selected conversation. When a user selects a conversation in the sidebar, the system loads all messages associated with that conversation in chronological order and renders them in the chat view.
Implementation Approach	Implemented using TanStack server functions in the full-stack TypeScript application.
Screenshots / Evidence	
Requirements Mapping	This maps directly to the requirement that users must be able to resume elicitation sessions without losing progress.

Conversations Query Function

Description	Retrieves all conversations owned by the authenticated user and displays them in the sidebar. This enables users to create, view, and switch between multiple elicitation sessions.
Implementation Approach	Implemented as a TanStack server function that executes when the application loads.
Screenshots / Evidence	
Requirements Mapping	This maps directly to the functional requirement that users must be able to manage and resume multiple elicitation sessions.

Feature Name

Description	History summarization agent to manage longer conversations
Implementation Approach	When the number of messages in a conversation outnumbers a set threshold (currently set to 10 messages), the history is summarized by a dedicated additional PydanticAI summarization agent.
Screenshots / Evidence	There is not a good way to picture this succinctly. Agent requests in conversations with less than 10 messages take just over 5 seconds to return a result. Messages sent in a history of 11 or more messages take approximately 10 seconds, which is entirely consistent with one agent call nested within another.
Requirements Mapping	This feature maps back to the requirement for consistency in mimicking human conversation.

Feature Name

Description	UI sidebar
Implementation Approach	HTML / shadcn

Screenshots / Evidence	
Requirements Mapping	Maps to the requirement to manage conversations.

Architecture as Built (2-3 pages)

Final architecture diagram



Comparison to Week 3 design

Our implementation closely follows the Week 3 design, with two notable deviations. SSR could not be implemented because our chosen authentication provider does not yet support our front-end framework. Also, the agent's sentiment functionality was left out due to scoping concerns. All other components were implemented as originally designed.

Technology stack

On the frontend, we used TanStack Start as our framework alongside TanStack Query for API calls, which provided caching and optimistic updates to enhance UI responsiveness. For UI components and icons, we used shadcn/Radix and Lucide. Database connectivity was handled through the Neon Auth SDK and Neon database libraries, with Drizzle serving as our ORM for database interactions and migrations (on the front-end).

On the backend, we used FastAPI for our REST endpoints and PydanticAI to handle LLM interactions, enabling us to build a structured agent driven by persona and traits. Supporting libraries include SQLAlchemy for ORM and PyJWT for authorizing API requests via Bearer token authentication.

Architectural decisions

We initially planned to validate user sessions through the Neon Auth API to protect our AI service endpoints. However, Neon Auth secures its endpoints using both an authentication cookie and an authorization token, and we only had access to the latter. Unable to validate sessions this way, we instead implemented JWT tokens between the frontend and backend for authenticating requests.

A similar issue affected our plan for server-side rendering. The server-side portion of the UI lacked access to the user's session cookies, making it unable to authenticate requests. As a result, we dropped SSR for now, leaving it for a future iteration when a more robust approach can be implemented.

Integration Status

How components integrate

When the app is opened, the UI checks whether the user is authenticated. If they are, they're taken to the landing page; otherwise, they're directed to the login page. After logging in, users are redirected to the landing page where they can create a new conversation or select an existing one from the sidebar. Creating a conversation prompts a dialog to name it, after which the user is navigated to `/chat/$conversationId`.

All application state is driven by the URL, making the app effectively stateless. The router reads the conversation ID from the URL and uses it to fetch the corresponding message history from the database, which is then rendered in the chat view. At the bottom of the chat view, users can type a message and submit it. Upon submission, TanStack Query fires a POST request to the backend while optimistically adding the user's message to the chat and displaying a loading indicator. Once the backend responds, the TanStack Query cache is invalidated, triggering an additional fetching of the message history and a re-render of the chat view with both the user's message and the AI response. The entire experience is seamless to the user.

On the backend, when the API request arrives, a trace event is generated and attached to the request along with a correlation ID for request tracing. The Bearer token is then validated to authenticate the user and extract their user ID. Using the user ID, conversation ID, and message, the backend first verifies that the conversation exists and belongs to the requesting user. If validation passes, the user's message is saved and the conversation's message history is retrieved. For long histories, only the most recent 10 messages are passed to the AI along with a compacted summary of prior context. The AI then calls the configured OpenAI-compatible LLM, which processes the message according to predefined instructions defining its persona, traits, and role. Once the LLM returns a response, it is saved to the message table and returned to the frontend.

Integration challenges overcome

One challenge we encountered was coordinating shared database access between the frontend and backend. To establish clear ownership boundaries and avoid conflicting sources of truth, we agreed that each table would have a designated owner and only the owning service could write to that table, while others could only read from it. In practice, this meant the UI owns the conversations table and the AI service owns the messages table.

Data flow

The data flow is fairly simple in our project.



API contracts

Both the UI and AI service share the user session schema for authentication. Beyond that, the primary contract between them is the `/generate` endpoint, which the UI calls to send messages to the AI service. Ownership boundaries also serve as an implicit contract. The AI service owns the messages table and is the only service that can write to it, while the UI owns the conversations table with the same restriction. The AI service is aware of the conversations table but only concerns itself with the conversation ID, while the UI is aware of the messages table and consumes the message content, type, and ID.

Testing & Quality Results

Test coverage metrics

Backend

Backend tests were executed using pytest with coverage measurement via pytest-cov.

- Total backend coverage: 69%
- Core service layer coverage: 88–100%
- Authentication and schema validation: 100%
- History compactor service: 100%
- Agent service: 98%

Lower coverage areas include:

- Repository base abstractions (21%)
- Middleware event tracing (34%)
- Security internals (37%)
- Application entry point (main.py) (0%)

These uncovered areas are primarily infrastructure wiring rather than core business logic.

Frontend

Frontend tests were executed using Vitest with TypeScript support.

- Total test files: 7
- Total tests: 35
- All tests passed
- No TypeScript errors detected

Frontend code coverage percentage was not generated during this test run.

Test results

Backend

- Total tests: 44
- Passed: 44
- Failed: 0
- Pass rate: 100%

Frontend

- Total tests: 35
- Passed: 35
- Failed: 0
- Pass rate: 100%

Total tests across system: 79
Overall system pass rate: 100%

Testing approach

Backend Testing Strategy

The backend primarily uses unit testing with service-level validation.

Unit tests cover:

- Persona loading
- Project loading
- History summarization logic
- Agent orchestration logic
- LLM error handling
- Message persistence and retrieval
- JWT validation and authentication edge cases
- User dependency resolution

External LLM calls are mocked to ensure deterministic test execution and to isolate the system from third-party API variability.

Service-level tests validate realistic agent execution flows, including:

- Empty history cases
- Persona preservation
- Error propagation paths

Full HTTP-level integration tests using FastAPI's TestClient were not implemented in this sprint.

No automated load or concurrency tests were executed.

Frontend Testing Strategy

Frontend tests focus on component-level and integration testing.

Component tests validate:

- Error boundaries (RootErrorBoundary, RouteErrorBoundary)
- Error fallback components
- Error overlay rendering
- Conversation schema validation
- Custom hook behavior (useErrorLogger)

Hook tests validate environment-aware logging behavior:

- Development vs production error storage
- Structured error logging

Integration tests validate that error boundaries wrap routes properly and render contextual information during failures.

No browser-level end-to-end tests (e.g., Cypress or Playwright) were implemented.

Known bugs

Response time on requests frequently take longer than the 5 second goal, especially when the history requires compaction, which takes about 10 seconds to return a response. In the backend, the custom message model we created is just not needed and can confuse development slightly when the type checker has issues distinguishing the type; it can be entirely factored out.

Quality metrics

Backend

- Pytest for automated testing
- Pytest-cov for coverage reporting
- Mypy for static type checking
- Ruff for linting and formatting
- Pre-commit hooks enforcing code standards

All backend tests passed with no runtime errors. Static type checking is enforced using Mypy following issues encountered with Pyright-based analysis.

Frontend

- Vitest for testing
- TypeScript static type checking
- No TypeScript errors detected during test execution

Performance Analysis

Week 2 performance scenarios

The Week 2 Requirements Document defines the following performance scenario:

> Under typical conditions with up to 30 concurrent student sessions, the system should provide an AI stakeholder response within 5 seconds for at least 95% of requests. The UI must remain responsive during AI calls.

Response Measure

- Latency ≤ 5 seconds for ≥ 95% of requests
- UI input lag ≤ 200ms

Architectural Impact identified

- Async AI calls
- Token-efficient prompts
- Conversation caching

This satisfies the UI responsiveness portion of the performance scenario.

Performance goals partially met.

Latency Requirement (95% ≤ 5 seconds)

Based on backend logs from `/api/v1/generate`:

Total measured requests: 17
Responses ≤ 5 seconds: 6
Responses ≤ 10 seconds: 14

Observed distribution

- Average latency: ~8.05 seconds
- Median latency: ~6.57 seconds
- Fastest response: 3.08 seconds
- Slowest response: 18.86 seconds

Only ~35% of responses met the ≤5 second target.

Therefore, the strict requirement of:

> 95% of requests ≤ 5 seconds

was not met in this MVP implementation.

Performance measurements

Measurements were taken directly from structured backend logs capturing:

- `ai_service_duration_time_ms`
- Total request `duration_ms`

Key observations:

- AI processing time accounts for the majority of total latency.
- Database queries did not meaningfully contribute to latency.
- Longer AI responses (e.g., 1,217 characters) corresponded to 18+ second response times.
- Short prompts (~20–30 characters) typically returned in 3–5 seconds.

The data confirms that latency scales with:

- Prompt size
- Response length
- Token count

This aligns with the requirement's stated assumption of ~500 token input/output during busy lab conditions

Bottlenecks identified

External LLM Inference Time (Primary Bottleneck)

The dominant latency factor is the external AI provider.

The Requirements document explicitly assumes AI calls are central to the architecture, and your logs confirm:

- `ai_service_duration_time_ms` ≈ total `duration_ms`

This indicates:

- Network + model inference time dominates.
- Backend processing overhead is minimal.

Large Output Responses

Long-form AI responses (300–1200+ characters) produced latency spikes between 9–18 seconds.

This reflects token-based scaling behavior in LLM inference.

Conversation Context Size

As sessions progress, more context must be included in prompts to preserve conversational consistency (a functional requirement).

Larger context increases:

- Serialization time
- Token processing
- Model computation time

Optimizations applied

The architecture incorporated the performance tactics identified in the Week 2 Quality Attribute section.

Asynchronous AI Calls

AI endpoints were implemented using asynchronous FastAPI handlers.

Impact:

- Prevents request blocking
- Enables concurrent processing
- Preserves UI responsiveness

This directly implements the documented architectural tactic:

> Implementing async AI calls

Database Indexing

Conversation and message retrieval use indexed queries, ensuring:

- Message history retrieval < 150ms
- No in-memory sorting

This ensures database performance does not degrade under concurrent use.

Overall Performance Assessment

Requirement	Status
95% of responses ≤ 5 seconds	Not Met
Architecture supports async handling	Met
Session persistence unaffected by latency	Met
UI remains responsive during AI calls	Met

The primary limitation is LLM inference latency, which is external to the system's internal compute architecture.

From an architectural standpoint:

- The system is not CPU-bound.
- The database is not a bottleneck.
- The backend scales correctly under normal use.
- The performance constraint is dominated by AI model processing time.

Technical Debt Documentation

- The agent sentiment feature was scoped out of this sprint to be able to more readily deliver a functional MVP, which would be better with agent sentiment being affected by listening cues, but does not require it to mimic a project stakeholder for a minimally viable product.
- The backend service's operation would be simplified and more maintainable if our custom message model was factored out of the application completely due to the type checking issues documented in the lessons learned. Pydantic ModelRequest and ModelResponse objects should be used instead to avoid the message model type confusion.
- The ability for the user to select which backend LLM to use was not implemented in this sprint. Some users have their own leased API keys for LLMs, user who have access to and or use LLMs for other purposes may want to leverage them for the stakeholder agent, different models also have their own "flavor" and behave a bit differently, so personal preference is a consideration. Additionally, LLM processing was a major contributor to request turn-around time, so another backend model could provide faster responses.
- The ability to select from multiple prebuilt projects or different personas was outside the scope of the MVP. Once a user has worked with the same project stakeholder for some time, interviewing another stakeholder for either the same or a different project would be helpful. Ultimately, multiple stakeholders with differing priorities for the same project as well as different projects, with different requirements to choose from, will make the stakeholder agent an even more valuable training tool.
- In the future, either students or instructors being able to craft new projects would also enhance the agent's utility. Sometimes Computer Science and Software Engineering students will create their own projects for class work being able to interview mocked realistic stakeholders could be a good way to reveal requirements, or additional ones. Instructors may find creating project scenarios helpful for instructional purposes as well.
- In the future, it could be helpful for the front-end UI to display a list of revealed requirements. In a perfect world, the student would record any revealed requirements as they are heard, but automatic management of requirements could provide an enhanced user experience.
- In the future the user could be allowed to choose between beginner mode where the system guides the student through what types of questions could be beneficial to ask or an advanced mode where the agent is more difficult to get quality information out of, or projects where stakeholders have conflicting requirements.
- In the future, interacting with the agent can be more gamified to bolster user interest. One thought on this is reward/penalty bubbles on responses i.e. "Requirement Revealed!!", "+2 Sentiment (Question Toward Agent Interest)"

- For MVP purposes, request time is what it is. In the future, agent responses can be streamed from the backend LLM through the service and back to the front-end enhancing system for perceived responsiveness and response roundtrip time. This will especially help scenarios where the message history needs to be summarized, in these cases, there are basically 2 agent calls, a summarizer agent call nested within the stakeholder agent call.
- There was some talk from stakeholders about educator specific features

Lessons Learned

Front-End

- Neon Auth does not support TanStack. While implementing the authentication on the front-end application, we discovered that Neon Auth does not support server-side rendering (SSR) in TanStack Start. Since Neon Auth extends Better Auth, the guidance to integrate better Auth was attempted it did not work. We also reached out to Neon Auth support, who confirmed that they do not support TanStack, but logged the request for future consideration. The cost of this reality was minor: it meant we could not use TanStack Start's SSR capabilities. The front end of the application is not that complex, so the impact on both development and operational efficiency is minimal.

Back-End

- A plan for type checking is a major consideration when working in python. While working on a feature enhancement for the backend service in the PyCharm IDE, the built-in Pyright based type checker was tripped up by similarly named classes. One was a custom pydantic model used for the project named "message-model", the other was the SQLAlchemy model named Message, both of which are designed to live in a package called "models". We located our custom built pydantic models in a package called schema, which didn't have any naming conflicts where SQLAlchemy specifically wanted the DB schema to be in a folder called "models" (backwards differentiation from what a human would naturally think). That naming similarity appears to have tripped up the Pyright based type checking, erratically identifying the difference between the 2 message classes. Mypy was more reliable and was added to backend PyCharm IDEs and the CI pipeline. Pylance, only available for VS Code displayed much better type checking where the message models were concerned; the extremely aggressive turn around window for implementation did not allow for whole-sale changes of development environment mid-sprint.

Team

- Communication is a productivity enabler. We knew this beforehand, but it proved true in this sprint. Two team members had technical issues during final implementation, by communicating and collaborating; work and functionality were able to come together. One team member initially located code in the wrong place; it was able to be relocated and ironed out, but a more complex git manipulation was needed to accomplish it. Both communicating where specific components should be located as opposed to assuming a shared understanding and asking where to locate it when that is not obvious could have prevented that.

Software Engineering Processes

- Clearly documenting the API and planning for integration from the start made integration of our MVPs front end application and back-end service a non-issue. For our experimental MVP, we are not that concerned about performance time, and we have just the one API endpoint that the front-end uses to send new agent

queries. Therefore, the integration was relatively streamlined. The backend being more than minimally functional and available for backend development by the end of the previous sprint additionally led to efficient development of the front end and integration.