```
(.venv) sri@slugbot:~/terraforma-smolboard$ python analysis.py --checkpoint results/kr3_v2_checkpoint.csv
30000 rows from results/kr3_v2_checkpoint.csv
```

model	prompt	n	n_ok	accuracy	precision	recall	f1	parse_failure_rate
falcon3-7b-instruct	dspy	1000.0	1000.0	0.938	0.936255	0.940	0.938124	0.000
qwen3-4b-instruct	dspy	1000.0	1000.0	0.882	0.970443	0.788	0.869757	0.000
mistral-7b-instruct-v0.3	dspy	1000.0	1000.0	0.876	0.806189	0.990	0.888689	0.000
phi-3-mini-4k-instruct	dspy	1000.0	1000.0	0.807	0.722787	0.996	0.837679	0.000
olmo-2-7b-instruct	dspy	1000.0	1000.0	0.685	0.613776	0.998	0.760091	0.000
yi-1.5-6b-chat	dspy	1000.0	1000.0	0.546	0.802632	0.122	0.211806	0.000
granite-3.1-2b-instruct	dspy	1000.0	1000.0	0.527	0.965517	0.056	0.105860	0.000
smollm2-1.7b-instruct	dspy	1000.0	754.0	0.466	0.618037	1.000	0.763934	0.246
gemma-3-4b-it	dspy	1000.0	0.0	0.000	NaN	NaN	NaN	1.000
llama-3.2-3b-instruct	dspy	1000.0	0.0	0.000	NaN	NaN	NaN	1.000
granite-3.1-2b-instruct	json	1000.0	1000.0	0.589	0.556978	0.870	0.679157	0.000
olmo-2-7b-instruct	json	1000.0	1000.0	0.534	0.520286	0.872	0.651719	0.000
falcon3-7b-instruct	json	1000.0	1000.0	0.505	0.502564	0.980	0.664407	0.000
smollm2-1.7b-instruct	json	1000.0	1000.0	0.500	0.500000	1.000	0.666667	0.000
yi-1.5-6b-chat	json	1000.0	1000.0	0.500	0.500000	1.000	0.666667	0.000
phi-3-mini-4k-instruct	json	1000.0	1000.0	0.498	0.498994	0.992	0.663989	0.000
qwen3-4b-instruct	json	1000.0	1000.0	0.497	0.498492	0.992	0.663545	0.000
mistral-7b-instruct-v0.3	json	1000.0	1000.0	0.476	0.485437	0.800	0.604230	0.000
gemma-3-4b-it	json	1000.0	0.0	0.000	NaN	NaN	NaN	1.000
llama-3.2-3b-instruct	json	1000.0	0.0	0.000	NaN	NaN	NaN	1.000
falcon3-7b-instruct	text	1000.0	1000.0	0.899	0.882917	0.920	0.901077	0.000
mistral-7b-instruct-v0.3	text	1000.0	1000.0	0.889	0.838261	0.964	0.896744	0.000
qwen3-4b-instruct	text	1000.0	1000.0	0.885	0.866667	0.910	0.887805	0.000
olmo-2-7b-instruct	text	1000.0	1000.0	0.884	0.844086	0.942	0.890359	0.000
phi-3-mini-4k-instruct	text	1000.0	1000.0	0.848	0.770186	0.992	0.867133	0.000
yi-1.5-6b-chat	text	1000.0	1000.0	0.848	0.804196	0.920	0.858209	0.000
granite-3.1-2b-instruct	text	1000.0	1000.0	0.772	0.972222	0.560	0.710660	0.000
smollm2-1.7b-instruct	text	1000.0	1000.0	0.500	0.500000	1.000	0.666667	0.000
gemma-3-4b-it	text	1000.0	0.0	0.000	NaN	NaN	NaN	1.000
llama-3.2-3b-instruct	text	1000.0	0.0	0.000	NaN	NaN	NaN	1.000

Rows by status. unparseable_truncated: no MATCH/NOT_MATCH, and the reply was cut off by the 20-token cap; unparseable: no verdict in a reply that ended on its own. Both count as parse failures above.

model	prompt	model_load_error	ok	unparseable_truncated
falcon3-7b-instruct	dspy	0	1000	0
	json	0	1000	0
	text	0	1000	0
gemma-3-4b-it	dspy	1000	0	0
	json	1000	0	0
	text	1000	0	0
granite-3.1-2b-instruct	dspy	0	1000	0
	json	0	1000	0
	text	0	1000	0
llama-3.2-3b-instruct	dspy	1000	0	0
	json	1000	0	0
	text	1000	0	0
mistral-7b-instruct-v0.3	dspy	0	1000	0
	json	0	1000	0
	text	0	1000	0
olmo-2-7b-instruct	dspy	0	1000	0
	json	0	1000	0
	text	0	1000	0
phi-3-mini-4k-instruct	dspy	0	1000	0
	json	0	1000	0
	text	0	1000	0
qwen3-4b-instruct	dspy	0	1000	0
	json	0	1000	0
	text	0	1000	0
smollm2-1.7b-instruct	dspy	0	754	246
	json	0	1000	0
	text	0	1000	0
yi-1.5-6b-chat	dspy	0	1000	0
	json	0	1000	0
	text	0	1000	0

Accuracy / precision / recall / F1 by prompt format (pooled across all models):

prompt	n	n_ok	accuracy	precision	recall	f1	parse_failure_rate
text	10000.0	8000.0	0.6525	0.769592	0.901000	0.830128	0.2000
dspy	10000.0	7754.0	0.5727	0.749678	0.733989	0.741751	0.2246
json	10000.0	8000.0	0.4099	0.506683	0.938250	0.658017	0.2000

Accuracy by pair_type x prompt (pooled across models). hard_negative is the diagnostic case: high match/easy_negative accuracy with low hard_negative accuracy means a model (or prompt) is pattern-matching on name text rather than actually comparing address/locality.

pair_type	dspy	json	text
easy_negative	0.6600	0.087333	0.699667
hard_negative	0.4180	0.042000	0.411000
match	0.5822	0.750600	0.720800

Runtime that produced each model's rows:

qwen3-4b-instruct	cpu-nf4-float16 @ slugbot
phi-3-mini-4k-instruct	cpu-nf4-float16 @ slugbot
gemma-3-4b-it	(not recorded -- predates the runtime log)
llama-3.2-3b-instruct	(not recorded -- predates the runtime log)
mistral-7b-instruct-v0.3	cpu-nf4-float16 @ slugbot
smollm2-1.7b-instruct	cpu-nf4-float16 @ slugbot
granite-3.1-2b-instruct	cpu-nf4-float16 @ slugbot
yi-1.5-6b-chat	cpu-nf4-float16 @ slugbot
falcon3-7b-instruct	cpu-nf4-float16 @ slugbot
olmo-2-7b-instruct	cpu-nf4-float16 @ slugbot

30000 rows from results/kr3_v2_checkpoint.csv

model	prompt	n	n_ok	accuracy	precision	recall	f1	parse_failure_rate
falcon3-7b-instruct	dspy	1000.0	1000.0	0.938	0.936255	0.940	0.938124	0.000
qwen3-4b-instruct	dspy	1000.0	1000.0	0.882	0.970443	0.788	0.869757	0.000
mistral-7b-instruct-v0.3	dspy	1000.0	1000.0	0.876	0.806189	0.990	0.888689	0.000
phi-3-mini-4k-instruct	dspy	1000.0	1000.0	0.807	0.722787	0.996	0.837679	0.000
llama-3.2-3b-instruct	dspy	1000.0	1000.0	0.785	0.787879	0.780	0.783920	0.000
olmo-2-7b-instruct	dspy	1000.0	1000.0	0.685	0.613776	0.998	0.760091	0.000
yi-1.5-6b-chat	dspy	1000.0	1000.0	0.546	0.802632	0.122	0.211806	0.000
granite-3.1-2b-instruct	dspy	1000.0	1000.0	0.527	0.965517	0.056	0.105860	0.000
smollm2-1.7b-instruct	dspy	1000.0	754.0	0.466	0.618037	1.000	0.763934	0.246
gemma-3-4b-it	dspy	1000.0	0.0	0.000	NaN	NaN	NaN	1.000
granite-3.1-2b-instruct	json	1000.0	1000.0	0.589	0.556978	0.870	0.679157	0.000
gemma-3-4b-it	json	1000.0	1000.0	0.534	0.517598	1.000	0.682128	0.000
olmo-2-7b-instruct	json	1000.0	1000.0	0.534	0.520286	0.872	0.651719	0.000
falcon3-7b-instruct	json	1000.0	1000.0	0.505	0.502564	0.980	0.664407	0.000
llama-3.2-3b-instruct	json	1000.0	1000.0	0.501	0.666667	0.004	0.007952	0.000
smollm2-1.7b-instruct	json	1000.0	1000.0	0.500	0.500000	1.000	0.666667	0.000
yi-1.5-6b-chat	json	1000.0	1000.0	0.500	0.500000	1.000	0.666667	0.000
phi-3-mini-4k-instruct	json	1000.0	1000.0	0.498	0.498994	0.992	0.663989	0.000
qwen3-4b-instruct	json	1000.0	1000.0	0.497	0.498492	0.992	0.663545	0.000
mistral-7b-instruct-v0.3	json	1000.0	1000.0	0.476	0.485437	0.800	0.604230	0.000
falcon3-7b-instruct	text	1000.0	1000.0	0.899	0.882917	0.920	0.901077	0.000
mistral-7b-instruct-v0.3	text	1000.0	1000.0	0.889	0.838261	0.964	0.896744	0.000
qwen3-4b-instruct	text	1000.0	1000.0	0.885	0.866667	0.910	0.887805	0.000
olmo-2-7b-instruct	text	1000.0	1000.0	0.884	0.844086	0.942	0.890359	0.000
phi-3-mini-4k-instruct	text	1000.0	1000.0	0.848	0.770186	0.992	0.867133	0.000
yi-1.5-6b-chat	text	1000.0	1000.0	0.848	0.804196	0.920	0.858209	0.000
gemma-3-4b-it	text	1000.0	1000.0	0.832	0.875566	0.774	0.821656	0.000
granite-3.1-2b-instruct	text	1000.0	1000.0	0.772	0.972222	0.560	0.710660	0.000
llama-3.2-3b-instruct	text	1000.0	1000.0	0.576	0.887755	0.174	0.290970	0.000
smollm2-1.7b-instruct	text	1000.0	1000.0	0.500	0.500000	1.000	0.666667	0.000

Rows by status. unparseable_truncated: no MATCH/NOT_MATCH, and the reply was cut off by the 20-token cap; unparseable: no verdict in a reply that ended on its own. Both count as parse failures above.

model	prompt	ok	unparseable_truncated
falcon3-7b-instruct	dspy	1000	0
	json	1000	0
	text	1000	0
gemma-3-4b-it	dspy	0	1000
	json	1000	0
	text	1000	0
granite-3.1-2b-instruct	dspy	1000	0
	json	1000	0
	text	1000	0
llama-3.2-3b-instruct	dspy	1000	0
	json	1000	0
	text	1000	0
mistral-7b-instruct-v0.3	dspy	1000	0
	json	1000	0
	text	1000	0
olmo-2-7b-instruct	dspy	1000	0
	json	1000	0
	text	1000	0
phi-3-mini-4k-instruct	dspy	1000	0
	json	1000	0
	text	1000	0
qwen3-4b-instruct	dspy	1000	0
	json	1000	0
	text	1000	0
smollm2-1.7b-instruct	dspy	754	246
	json	1000	0
	text	1000	0
yi-1.5-6b-chat	dspy	1000	0
	json	1000	0
	text	1000	0

Accuracy / precision / recall / F1 by prompt format (pooled across all models):

	n	n_ok	accuracy	precision	recall	f1	parse_failure_rate

```
prompt
text    10000.0  10000.0    0.7933   0.780777  0.81560  0.797809              0.0000
dspy    10000.0   8754.0    0.6512   0.753997  0.73914  0.746495              0.1246
json    10000.0  10000.0    0.5134   0.507999  0.85100  0.636214              0.0000

Accuracy by pair_type x prompt (pooled across models). hard_negative is the diagnostic case: high
match/easy_negative accuracy with low hard_negative accuracy means a model (or prompt) is pattern-matching on name
text rather than actually comparing address/locality.
prompt             dspy      json      text
pair_type
easy_negative  0.757667  0.198667  0.899667
hard_negative  0.469000  0.141500  0.578000
match          0.660200  0.851000  0.815600

Runtime that produced each model's rows:
  qwen3-4b-instruct          cpu-nf4-float16 @ slugbot
  phi-3-mini-4k-instruct     cpu-nf4-float16 @ slugbot
  mistral-7b-instruct-v0.3   cpu-nf4-float16 @ slugbot
  smollm2-1.7b-instruct      cpu-nf4-float16 @ slugbot
  granite-3.1-2b-instruct    cpu-nf4-float16 @ slugbot
  yi-1.5-6b-chat             cpu-nf4-float16 @ slugbot
  falcon3-7b-instruct        cpu-nf4-float16 @ slugbot
  olmo-2-7b-instruct         cpu-nf4-float16 @ slugbot
  gemma-3-4b-it              cpu-nf4-float32 @ slugbot
  llama-3.2-3b-instruct      cpu-nf4-float32 @ slugbot
```