






LED Wall Pack		www.lileds.com	
Names	Blazer 100C		Blazer 100
Pictures			
Light Source	40 High Power LED @700mA Constant Current (LumiLEDs Rebel ES) LM-80 listed		40 High Power LED @700mA Constant Current (LumiLEDs Rebel ES) LM-80 listed
LED life	50,000 hrs		
Color Temperature	Cool White 5300-6000° K (other colors on request)		
Colorimetric index	Ra 75		
Light distribution			
Total flux	8000 lumens per LM-79 test		6000 lumens per LM-79 test
PF	> 0.9		
Total Harmonic	< 10%		
Total power	100W		100W
Electric Protections	OVP, SCP, OTP		
Input voltage	90 ~ 277VAC 50/60Hz (480V step down optional)		
Dimensions	Length	17'(432MM)	17" (431MM)
	Width	9.21' (234MM)	9.33" (237MM)
	Height	13.78' (350MM)	9.06" (230MM)
Weight	21.34lbs (9.7kg)		24.2lbs (11kg)
UL & cUL	UL/cUL E351013		
DLC	Pending		N/A
Operating temperature	-25 ~ 55°C (-13~ 130°F)		
Operating Humidity	10 ~ 95%		
Weather protection	Suitable for Wet Location		
Packaging	Dimensions	500*420*305MM	490*300*315MM
	PCS per box	1	1
	G.Weight (lb)	24.2	22
Standard Warranty	5 years Limited		5 years Limited