





# LED Flood Light

www.lileds.com



Names		Festival WF	Festival NS
Pictures			
Light Source		30pcs High Power LED@400mA Constant Current (LumiLEDs Rebel) LM-80 listed	30pcs High Power LED@400mA Constant Current (LumiLEDs Rebel) LM-80 listed
LED life		50.000 hrs	50.000 hrs
Color Temperature		Cool White 5300-6000° K (other colors on request)	Cool White 5300-6000° K (other colors on request)
Colorimetric index			
Light distribution			
Total flux		2560 lumens, per LM-79 test method	2560 lumens, per LM-79 test method
PF		> 0.9	> 0.9
Total Harmonic		< 20%	< 20%
Total power		37W	37W
Electric Protections		OVP, SCP, OTP	OVP, SCP, OTP
Input voltage		90 ~ 277VAC 50/60Hz (480V step down optional)	90 ~ 277VAC 50/60Hz (480V step down optional)
Dimensions	Length	16.7" (425MM)	16.7" (425MM)
	Width	11.22" (285MM)	11.22" (285MM)
	Height	5.1" (130MM)	5.1" (130MM)
Weight		8.36 lbs (3.8kg)	8.36 lbs (3.8kg)
UL/cUL		UL/cUL E351013	UL/cUL E351013
DLC		DesignLights Consortium qualified luminaire	DesignLights Consortium qualified luminaire
Operating temperature		-25 ~ 55°C (-13~ 130°F)	-25 ~ 55°C (-13~ 130°F)
Operating Humidity		10 ~ 95%	10 ~ 95%
Weather protection		Suitable for Wet locations	Suitable for Wet locations
Packaging	Dimensions	450*330*200MM	450*330*200MM
	PCS per box	1	1
	G.Weight (lb)	10.56	11
Standard Warranty		5 years Limited	5 years Limited