


LED Tube		www.lileds.com		DESIGNLIGHTS ILLUMINATION		cULus		RoHS 2002/95/EC	
Names		T8-TB							
Pictures									
Light Source		2835 SMD LEDs							
LED life		>50,000 hours							
Model/Part Number		LiLEDs-T8-4FT-4000K-Clear		LiLEDs-T8-4FT-5000K-Clear		LiLEDs-T8-4FT-4000K-Frost		LiLEDs-T8-4FT-5000K-Frost	
Color Temperature		4000-4200K		5000-5200K		4000-4200K		5000-5200K	
Color rendering index		Ra 80							
Light distribution		180°							
Total flux		1700-2100 lm		1800~2150 lm		1700~1950 lm		1800~2100 lm	
PF		0.9							
Total Harmonic Distortion(THD)		< 20%							
Total power		16W							
Dimmable		NO							
Electric Protections		OVP, OCP, SCP, OTP							
Input voltage		100~277 VAC							
Housing		Extruded Aluminum							
Cover		Clear				Frosted			
Socket		G13							
Dimensions	Diameter (Inch)	1							
	Length (Inch)	48							
Weight (lb)		5/7							
Certification		UL, cUL, FCC, CE, PSE, ROHS							
DLC		YES							
Operative Humidity		10 ~ 90%							
Warranty		5 Years Limited Warranty							
Packaging	QTY (pcs)	25							
	Size	1260*195*195 mm							
	GW (lb)	28 3/4							