



Names		Metro 60H	
Pictures			
Light Source		Imported High Power 60 LED@500mA (LumiLEDs Rebelor Rebel)	
LED life		>50.000 hrs, tested per LM-80 test method	
Color Temperature		White 5500K	
Colorimetric index		Ra65	
Light distribution		Type III	
			
Total flux		7500 lumens, per LM-79 test method	
PF		>0.9	
Total Harmonic Distortion (THD)		<10%	
Total power		100W	
Light Efficiency		75 lm/w	
Electric Protections		OVP, OCP, SCP, OTP	
Input voltage		120 ~ 277VAC 50/60Hz 480V step down available as an option	
Housing		Die cast, Stainless Steel latches, tool-less access to LED drivers	
Sensor Day/Night		On/off (Bi-level optional)	
Dimensions	Length	20 inch (510 mm)	
	Width	16.5 inch (420 mm)	
	Height	10 inch (175 mm)	
Weight		24.42lbs (11 kg)	
Packaging		1pcs/Box, box size 550x470x255mm, G.W 11.5Kg	
Attachments		Head of pole or parallel (can be adjust 0° to 90°)	
		2~3 inch (60mm)	
UL/cUL		UL/cUL E351013	
DLC		Yes	
Operating temperature		-25 ~ 55°C (-13~ 130°F)	
Operating Humidity		10 ~ 90%	
Weather protection		Suitable for Dry, Damp and Wet locations	
Packaging	Dimensions	555*475*260MM	
	PCS per box	1	
	G.Weight (lb)	25.3	
Standard Warranty		5 Years Limited	