



LED Street Lightwww.lileds.com

Names		Cobrai 60H	
Pictures			
Light Source		Imported High Power 60 LED (LumiLEDs Rebel 500mA)	
LED life		>50.000 hrs, tested per LM-80 test method	
Color Temperature		5300 K	
Colorimetric index		Ra70	
Light distribution		Type III	
			
Total flux		7500 lumens, per LM-79 test method	
PF		>0.9	
Total Harmonic Distortion (THD)		<10%	
Total power		95W	
Light Efficiency		80 lm/w	
Electric Protections		OVP, OCP, SCP, OTP	
Input voltage		120 ~ 277VAC 50/60Hz 480V step down available as an option	
Housing		Die cast, Stainless Steel latches, tool-less access to LED drivers	
Sensor Day/Night		On/off (Bi-level optional)	
Dimensions	Length	27.95 inch (710 mm)	
	Width	12.2 inch (310 mm)	
	Height	10 inch (255 mm)	
Weight		9.3kg	
Packaging		1pcs/Box, box size 710x330x330mm, G.W 9.8Kg	
Attachments		Head of pole or parallel (can be adjust 5°-10°-15°)	
		2~3 inch (60mm)	
Certification		UL/cUL	
DLC		Yes	
Operating temperature		-25 ~ 55°C (-13~ 130°F)	
Operating Humidity		10 ~ 90%	
Weather protection		Suitable for Dry, Damp and Wet locations	