







LED Canopy Lights		www.lileds.com	   
Names	Atlas GS30H		
Pictures			
Light Source	30 High Power LED @700mA Constant Current (LumiLEDs Rebel), LM-80 listed		
LED life	>50,000 hrs		
Color Temperature	White 5500 K		
Colorimetric index	Ra70		
Light distribution	Type IV		
			
Total flux	5700 lumens, per LM-79 test method		
PF	0.98		
Total Harmonic Distortion(THD)	9.10%		
Total power	60W		
Light Efficiency	95 lm/w		
Lux	75 lux @ 14 feet high		
Electric Protections	OVP, OCP, SCP, OTP		
Input voltage	120 ~ 277VAC50/60Hz (480V step down optional)		
Dimensions	Length	9.29 inch (236 mm)	
	Width	11.8inch (300 mm)	
	Height	3.98 inch (101 mm)	
Weight	9.7 lb (4.4 kg)		
Installation	Surface mounting		
Certification	UL/cUL E351013		
Operating temperature	-25 ~ 55°C (-13~ 130°F)		
DLC	Yes		
Operating Humidity	10 ~ 95%		
Weather protection	Suitable for Dry, Damp and Wet locations		
Packaging	Dimensions	410*305*165MM	
	PCS per box	1	
	G.Weight (lb)	9.46	
Standard Warranty	5 Years Limited		