




LED Canopy Lights		www.lileds.com			
Names		Atlas GS60H-RS			
Pictures					
Light Source		60 High Power LED @550mA Constant Current (LumiLEDs Rebel), LM-80 listed			
LED life		>50,000 hrs			
Color Temperature		COOL White 5500 K			
Colorimetric Index		Ra72			
Light distribution		Type IV, Type V			
					
Total flux		7500 lumens, per LM-79 test method			
PF		0.98			
Total Harmonic Distortion(THD)		9.10%			
Total power		100W			
Light Efficiency		80 lm/w			
Lux		150 lux @ 14 feet high			
Electric Protections		OVP, OCP, SCP, OTP			
Input voltage		90 ~ 277VAC 50/60Hz (480V step down optional)			
Dimensions	Length	13.6" (346MM)			
	Width	13.6" (346MM)			
	Height	4.41" (112MM)			
Weight		17.64 lbs (7.9kg)			
Installation		Recess mounting			
Certification		UL/cUL E351019			
Operating temperature		-25 ~ 55°C (-13~ 130°F)			
DLC		DesignLights Consortium qualified luminaire			
Operating Humidity		10 ~ 95%			
Weather protection		Suitable for Dry, Damp and Wet locations			
Packaging	Dimensions	430*430*210MM			
	PCS per box	1			
	G.Weight (lb)	19.14			
Standard Warranty		5 Years Limited			