| LED Flood Light       | www.lileds.com  | ι (VL) με <u>R</u> (€ RoHS |
|-----------------------|---|----------------------------|
| Names                 | Festival WF   |                            |
| Pictures              |   |                            |
| Light Source          | 30pcs High Power<br>LED@400mA Constant Current<br>(LumiLEDs Rebel) LM-80 listed |                            |
| LED life              | 50,000 hrs  |                            |
| Color Temperature     | White 5500 K  |                            |
| Colorimetric index    | Ra 66   |                            |
| Light distribution    |   |                            |
| Total flux            | 3000 lumens, per LM-79 test method  |                            |
| Light distribution    | 60° Light beam angle  |                            |
| PF                    | > 0.9   |                            |
| Total Harmonic        | < 15%   |                            |
| Total power           | 40W   |                            |
| Electric Protections  | OVP, SCP, OTP   |                            |
| Input voltage         | 120 ~ 277VAC 50/60Hz (480V step down optional)                                  |                            |
| Length                | 16.7" (425MM)   |                            |
| Dimensions Width      | 11.22" (285MM)  |                            |
| Height                | 5.1" (130MM)  |                            |
| Weight                | 8.36 lbs (3.8kg)  |                            |
| Certification         | UL/cUL E351013  |                            |
| DLC                   | Yes   |                            |
| Operating temperature | -25 ~ 55°C (-13~ 130°F)   |                            |
| Operating Humidity    | 10 ~ 95%  |                            |
| Weather protection    | Suitable for Dry, Damp and Wet locations  |                            |
| Standard Warranty     | 5 Years Limited   |                            |