










LED Wall Pack		www.lileds.com		DESIGNLIGHTS CONSORTIUM		UL US	CE	RoHS 2002/95/EC
Names		Blazer 25		Blazer 35		Blazer 50C		
Pictures								
Drawings								
Light Source		13 High Power LED @400mA Constant Current (LumiLEDs Rebel) LM-80 listed		20 High Power LED @500mA Constant Current (LumiLEDs Rebel) LM-80 listed		30 High Power LED @400mA Constant Current (LumiLEDs Rebel) LM-80 listed		
LED life		50,000 hrs						
Color Temperature		Cool White 5300-6000° K (other colors on request)						
Colorimetric index		Ra 75						
Light distribution								
Total flux		1045 lumens per LM-79 test		2250 lumens per LM-79 test		1900 lumens per LM-79 test		
PF		> 0.9						
Total Harmonic		< 10%						
Total power		18W		30W		37W		
Electric Protections		OVP, SCP, OTP						
Input voltage		90 ~ 277VAC 50/60Hz (480V step down optional)						
Dimensions	Length	13" (330MM)		14" (356MM)		14" (350MM)		
	Width	7.8" (200MM)		9" (229MM)		9" (230MM)		
	Height	5.5" (140MM)		11.5" (292MM)		7.5" (190MM)		
Weight		6.61 lbs (3kg)		10.6 lbs (4.8kg)		11.5 lbs (5.2kg)		
UL & cUL		UL/cUL E351013						
DLC		N/A		DesignLights Consortium qualified luminaire		N/A		
Operating temperature		-25 ~ 55°C (-13~ 130°F)						
Operating Humidity		10 ~ 95%						
Weather protection		Suitable for Dry, Damp and Wet locations						
Packaging	Dimensions	395*265*215MM		400*290*360MM		415*300*265MM		
	PCS per box	1		1		1		
	G.Weight (lb)	7.7		11.44		11		
Standard Warranty		5 years Limited		5 years Limited		5 years Limited		