LED Higl	n Bay Lights	www.lileds.com	DESIGNLIGHTS CE
Names	Radiant 100H		100H
Pictures			
Light Source		100 High Power LED @440mA Constant Current	
LED life		>50.000 hrs	
Color Temperature		COOL White 5300-6500° K (other colors on request)	
Colorimetric index		Ra70~75	
Light distribution		Type IV, Type V	
		THE STATE OF THE S	
Total flux		10500 lumens, per LM-79 test method	
PF		0.97	
Total Harmonic Distortion(THD)		< 10%	
Total power		145W	
Light Efficiency		72 lm/w	
Electric Protections		OVP、OCP、SCP、OTP	
Input voltage		100∼277VAC 50/60Hz	
Housing		Casting Aluminum	
Dimensions	Length	20.4 inch (518.16mm)	
	Width	14.4 inch (365.76mm)	
	Height	3.4 inch (86.36mm)	
Weight		29.3lb (13.29kg)	
UL/cUL		UL/cUL E351013	
DLC		DesignLights Consortium qualified luminaire	
Operating temperature		-25 ~ 55°C (-13~ 130°F)	
Operating Humidity		10 ~ 90%	
Weather protection		Suitable for Dry, Damp and Wet locations	
Packaging	Dimensions	520*440*210MM	
	PCS per box	1	
	G.Weight (lb)	31.46	
Standard War	ranty	5 Years Limited	