



LED T8		www.lileds.com		c  RoHS 2002/95/EC	
Pictures					
Light Source		2835 SMD LEDs			
LED life		>50,000 hours			
Names		LiLEDs-18W-4000K-F		LiLEDs-18W-5000K-F	
Color Temperature		4000K		5000K	
Color rendering index		>80			
Light distribution		180 °			
Total flux		2097lm		1900lm	
PF		>0.8			
Total Harmonic Distortion(THD)		<20%			
Total power		18W		18W	
Dimmable		NO			
Electric Protections		OVP, OCP, SCP, OTP			
Input voltage		AC100-277V 50/60Hz			
Housing		Extruded Aluminum			
Cover		Frosted			
Socket		G13			
Dimensions	Diameter (Inch)	1			
	Length (Inch)	48			
Weight (lb)		5/7			
Certification		CE, Rohs, FCC, UL			
DLC		YES			
Operative temperature		-25 ~ 55 °C (-13~ 130 ℉)			
Operative Humidity		10 ~ 90%			
Warranty		5 Years Limited Warranty			
Packaging	QTY (pcs)	25			
	Size (Inch)	1290mm*240mm*240mm			
	GW (lb)	37 2/5			
MOQ Price<1500pcs					

Note:

- 1) Price FOB Shanghai. Spec and price subject to change without notice. Please check update information before place order.
- 2) Exchange rate based on 1USD=6.15RMB (±2%), Quotation will be adjusted accordingly when the tolerance of exchange rate 1USD=6.15RMB is over 2%.
- 3) 50% TT, 50% before shipping
- 4) Bank surcharge and handling fees: \$100 if order less than US\$10K on FOBs
- 5) Spec and prices are subject to change without advanced notice.