

LED Street Lights

www.lileds.com

DESIGNLIGHTS
CONSORTIUM



CE RoHS
2002/95/EC

Names	Metro 60H	
Pictures		
Light Source	Imported High Power LED (LumiLEDs Rebelor Rebel ES)	
LED life	>50,000 hrs, tested per LM-80 test method	
Color Temperature	Cool White/Warm White 3700-6500°K	
Colorimetric index	Ra 70~75	
Light distribution	Type I/ Type II/Type III/Type IV/Type V	
Total flux	8300 lumens, per LM-79 test method	
PF	>0.9	
Total Harmonic	<10%	
Total power	100W	
Light Efficiency	83 lm/w	
Electric Protections	OVP, OCP, SCP, OTP	
Input voltage	90 ~ 277VAC 50/60Hz 480V step down available as an option	
Housing	Die cast, Stainless Steel latches, tool-less access to LED drivers	
Sensor Day/Night	On/off (Bi-level optional)	
Dimensions	Length	20 inch (510 mm)
	Width	16.5 inch (420 mm)
	Height	10 inch (175 mm)
Weight	24.42lbs (11 kg)	
Packaging	1pcs/Box, box size 550x470x255mm, G.W 11.5Kg	
Attachments	Head of pole or parallel (can be adjust 0° to 90°)	
	2~3 inch (60mm)	
UL/cUL	UL/cUL E351013	
DLC	DesignLights Consortium qualified luminaire	
Operating temperature	-25 ~ 55°C (-13~ 130°F)	
Operating Humidity	10 ~ 90%	
Weather protection	Suitable for Wet Locations	
Packaging	Dimensions	555*475*260MM
	PCS per box	1
	G.Weight (lb)	25.3
Standard Warranty	5 Years Limited	