







LED Canopy Lights		www.lileds.com		  	
Names		Atlas GS60H			
Pictures					
Light Source		60 High Power LED @440mA Constant Current (LumiLEDs Rebel), LM-80 listed			
LED life		>50,000 hrs			
Color Temperature		COOL White 5500 K (other colors on request)			
Colorimetric index		Ra70			
Light distribution		Type IV, Type V			
		 			
Total flux		7500 lumens, per LM-79 test method			
PF		0.98			
Total Harmonic Distortion(THD)		9.10%			
Total power		97W			
Light Efficiency		80 lm/w			
Lux		150 lux @ 14 feet high			
Electric Protections		OVP, OCP, SCP, OTP			
Input voltage		120 ~ 277VAC50/60Hz (480V step down optional)			
Dimensions	Length	15.75" (400MM)			
	Width	15.75" (400MM)			
	Height	3.82" (97MM)			
Weight		17 lbs (7.7kg)			
Installation		Surface mounting			
Certification		UL/cUL E351013			
Operating temperature		-25 ~ 55°C (-13~ 130°F)			
DLC		DesignLights Consortium qualified luminaire		-	-
Operating Humidity		10 ~ 95%			
Weather protection		Suitable for Dry, Damp and Wet locations			
Packaging	Dimensions	480*470*170MM			
	PCS per box	1			
	G.Weight (lb)	18.7			
Standard Warranty		5 Years Limited			