









LED Canopy Lights		www.lileds.com	DESIGNLIGHTS CONSORTIUM				
Names		Atlas GS60H		Atlas GS60H-RS			
Pictures							
Light Source		60 High Power LED @500mA Constant Current (LumiLEDs Rebel), LM-80 listed		60 High Power LED @500mA Constant Current (LumiLEDs Rebel), LM-80 listed			
LED life		>50,000 hrs					
Color Temperature		COOL White 5300-6500° K (other colors on request)					
Colorimetric index		Ra70~75					
Light distribution		Type IV, Type V					
							
Total flux		8300 lumens, per LM-79 test method		8300 lumens, per LM-79 test method			
PF		0.99					
Total Harmonic Distortion(THD)		9.10%					
Total power		110W		110W			
Light Efficiency		75 lm/w		75 lm/w			
Lux		150 lux @ 14 feet high		150 lux @ 14 feet high			
Electric Protections		OVP, OCP, SCP, OTP					
Input voltage		90 ~ 277VAC 50/60Hz (480V step down optional)					
Dimensions	Length	15.75" (400MM)		13.6" (346MM)			
	Width	15.75" (400MM)		13.6" (346MM)			
	Height	3.82" (97MM)		4.41" (112MM)			
Weight		17 lbs (7.7kg)		17.64 lbs (7.9kg)			
Installation		Surface mounting		Recess mounting			
UL/cUL		UL/cUL E351013		UL/cUL E351019			
DLC		DesignLights Consortium qualified luminaire		DesignLights Consortium qualified luminaire			
Operating temperature		-25 ~ 55°C (-13~ 130°F)					
Operating Humidity		10 ~ 95%					
Weather protection		Suitable for Dry, Damp and Wet locations		Suitable for Dry, Damp and Wet locations			
Packaging	Dimensions	480*470*170MM		430*430*210MM			
	PCS per box	1		1			
	G.Weight (lb)	18.7		19.14			
Standard Warranty		5 Years Limited		5 Years Limited			