Polygonal Senses: Translating Edge-Based Geometry into Multimodal Sensory Experiences

1. Introduction: The Generative Potential of Polygonal Senses

Defining the Ambition

The translation of abstract geometric logic, specifically the structural properties of polygons, into rich, coherent, and expressive multimodal sensory experiences encompassing sound, texture, and scent represents a frontier in generative systems and human-computer interaction. This endeavor moves beyond conventional data representation, aspiring to imbue geometric forms with affective resonance and narrative potential through carefully orchestrated sensory patterns (User Query). The ambition is to create a "polysensory" language where the fundamental characteristics of polygons—their edges, angles, symmetries, and hierarchical arrangements—become the generative grammar for composing complex experiences. Such systems hold considerable promise for applications in data art, the creation of deeply immersive virtual environments, the development of novel sensory substitution devices for individuals with visual impairments [1], and the formulation of new paradigms for conveying geometric information through non-visual channels. Existing explorations in polysensory art and immersive experiences [3] and commercial ventures like Polygon Productions, which aim for "extraordinary spatial audio experiences" with synchronized lighting and scent dispersion [5], underscore a cultural and technological appetite for such integrated sensory encounters, setting the stage for more systematic and deeply generative approaches.

The core of this investigation lies in the systematic translation of polygonal features into dynamic patterns across auditory, tactile, and olfactory modalities. This pursuit is not merely about direct one-to-one mapping but about discovering and leveraging the inherent "sensory grammar" within polygonal structures to evoke meaningful and expressive experiences. The term "Polygonal Senses" itself suggests this deeper, almost embodied understanding, moving towards a form of synesthetic translation where geometric logic dictates the composition of cross-sensory narratives.

Overview of the Core Inquiry

This report addresses several central research questions: How can the intrinsic structural logic of polygons—such as edge count, angularity, symmetry, and nesting—be systematically translated into temporal, tactile, and olfactory metaphors? What are the perceptual and implementational challenges that emerge, including phenomena such as drift thresholds, metaphor fractures, binding misalignments, modal collapse, and semantic flattening? Furthermore, how can a symbolic computational framework, termed PolySensory(), be conceptualized and designed to operationalize these translations, ensuring cross-modal coherence and providing nuanced control over the generative process?

To navigate these questions, this report employs a "Multimodal Lens Framework," examining specific mapping strategies through Temporal (Polygon → Pulse), Tactile (Polygon → Pressure Maps), and Olfactory (Polygon → Volatility & Notes) lenses. Concurrently, "Reflexive Insight Loop Additions"—critical inquiries into the stability of polygonal mappings, the limits of metaphor, the perceptibility of recursion, and the avoidance of modal clichés—will guide the evaluation and refinement of these translation methodologies. The ultimate success of such translations will significantly depend on understanding and achieving semantic congruence between the chosen geometric metaphors and their sensory manifestations.[7] Arbitrary mappings, even if systematically implemented, may fail to evoke meaningful or the intended affective experiences, such as the "ritualistic" tone suggested in the PolySensory() example.

2. Foundations of Cross-Sensory Perception and Geometric Metaphor

The systematic translation of polygonal geometry into multimodal sensory experiences necessitates a foundational understanding of how humans perceive and integrate information across different senses, and how abstract concepts like geometric forms acquire meaning through sensory metaphors.

Cross-Modal Correspondences

Cross-modal correspondences refer to the consistent, non-arbitrary associations individuals make between features or stimuli across different sensory modalities.[7] These correspondences are not random but appear to be governed by underlying principles. Proposed mechanisms for these associations include innate structural connections in the brain, statistical regularities learned from environmental co-occurrences, shared affective (emotional) content evoked by stimuli in different senses, and linguistic mediation where common descriptive terms bridge sensory experiences.[8] For instance, the association between high pitch and visual brightness may stem from shared linguistic metaphors ("bright sound") or affective qualities (both can be perceived as "intense" or "sharp"). Understanding these mechanisms is pivotal for designing PolySensory() mappings that feel intuitive and robust.

Several correspondences are directly relevant to polygonal features:

- **Shape-Sound:** The most well-known is the "bouba/kiki effect," where rounded shapes are overwhelmingly associated with soft-sounding nonsense words like "bouba" (containing bilabial consonants and rounded vowels), and angular, spiky shapes with sharp-sounding words like "kiki" (containing plosive consonants and front vowels).[9] This suggests an inherent link between visual form and articulatory-acoustic features. Research further indicates that angular shapes are associated with higher-pitched sounds, while rounded shapes are linked with lower pitches and potentially smoother timbres.[9]
- **Shape-Tactile:** Angularity consistently correlates with the perception of tactile sharpness.[8] Studies involving haptic rendering of geometric shapes have shown that corners (vertices) and edge transitions are critical cues for tactile identification.[11] Dynamic exploration, such as tracing a shape, often enhances recognition compared to static presentation.[12]
- **Shape-Olfactory:** While less direct, correspondences exist. For example, scents judged as "arousing," "joyful," "pleasant," or "sweet" are often associated with higher pitches and round-curved shapes, whereas "arousing" scents can also be linked to angular shapes.[10] Lemon and pepper scents (often described as "sharp" or "piquant") have been associated with angular shapes, while vanilla ("smooth," "sweet") aligns with rounded shapes.[13] The hedonic quality (pleasantness) and intensity of odors also play a role in these associations.[13]

The developmental trajectory of these correspondences is also noteworthy; young children often exhibit fewer or different cross-modal associations compared to adults, suggesting that some mappings may be learned or refined through experience.[8] This implies that while some fundamental polygonal-sensory mappings might be immediately intuitive, more complex or abstract translations within a PolySensory() system might necessitate a learning period for users.

Insights from Synesthesia and Ideasthesia

Synesthesia, a neurological phenomenon where stimulation in one sensory or cognitive pathway leads to

involuntary experiences in a second pathway [15], offers naturalistic examples of profound cross-modal integration. Synesthetes might "see" colors when hearing music, "taste" words, or, pertinently, perceive geometric shapes when experiencing tastes.[15] These experiences can be *projective* (e.g., actually seeing a colored aura around a letter) or *associative* (e.g., feeling a strong, consistent, but internal connection between a letter and a color).[16] While PolySensory() aims to create deliberate, designed cross-sensory experiences rather than inducing involuntary synesthesia, the consistency, automaticity, and often affective richness of synesthetic perceptions serve as an inspiration for the types of coherent and evocative mappings the system might strive for.

The "semantic vacuum hypothesis" posits that some of the most common forms of synesthesia (e.g., grapheme-color, sequence-space) involve early-learned abstract concepts like letters and numbers.[16] Polygons, as fundamental abstract geometric forms also typically learned early in cognitive development, may thus be particularly potent inducers for designed cross-modal experiences. Their abstract nature might "invite" sensory associations more readily than concrete objects with pre-existing, fixed sensory profiles.

Closely related is the concept of *ideasthesia*, which suggests that the activation of a concept (an idea) can evoke a perception-like experience.[9] For example, the concept of "sharpness" derived from viewing a triangle (an ideational process) might trigger a sensory quality of sharpness that can then be mapped to auditory, tactile, or even olfactory domains. This framework is highly relevant as PolySensory() explicitly attempts to translate conceptual geometric properties (like angularity or symmetry) into specific sensory experiences. It underscores that the *meaning* extracted from the polygon is a critical intermediary in the translation process.

The Perceptual Basis of Sensory Metaphors

Abstract concepts, including the mathematical and geometric properties of polygons, are frequently understood through metaphors grounded in more concrete, sensorimotor experiences.[17] For instance, "a sharp argument" borrows from the tactile experience of sharpness. The "perceptual strength"—the vividness, salience, and directness of the sensory experience in the concrete (base) domain—plays a crucial role in how effectively the metaphor helps to grasp the abstract (target) domain.[17] A strong perceptual grounding makes the abstract concept more imageable and cognitively tractable.

This principle is evident in architecture, where geometric forms, materials, and structures are employed to evoke specific feelings and experiences through sensory metaphors.[18] A soaring arch might evoke "uplift" or "aspiration" by metaphorically mapping its vertical geometry to kinesthetic and emotional sensations. However, a critical consideration emerging from architectural studies is that symbolic richness or visual complexity does not automatically guarantee a positive or intended sensory-affective experience.[18] A building might be visually intricate and evoke many symbolic associations (e.g., resembling various objects) yet feel "gloomy" or "unpleasant".[18] This serves as a vital cautionary principle for PolySensory() design: a polygon rich in geometric features (e.g., high edge count, complex symmetries, intricate nesting) might translate into a cacophony of sensory information if not carefully curated for perceptual coherence, aesthetic balance, and human sensory processing limits. The system must aim not just for complexity in translation but for *expressive clarity* aligned with the intended tone.

3. A Multimodal Lens Framework for Polygonal Translation

To systematically translate the structural logic of polygons into sensory experiences, a "Multimodal Lens Framework" is proposed. This framework considers distinct mapping strategies for temporal (sound), tactile, and olfactory modalities, drawing upon established cross-modal correspondences and generative principles.

3.1. Temporal Mapping Lens (Polygon → Pulse)

This lens focuses on translating polygonal features into rhythmic and temporal structures in sound.

- **Edge count = beat cycles:** A direct and quantifiable mapping involves translating the number of polygon sides (n) into the number of primary beats within a rhythmic cycle or the subdivisions of a beat. Research based on a game visualizing rhythm through geometry demonstrates that regular n-gons can be systematically mapped to subdivide a duration of (n−2) beats into n equal segments.[19] This is derived from the geometric property that the sum of internal angles of a regular n-sided polygon is (n−2)×180◦. If 180◦ of angular traversal is equated to one beat of music, then a triangle (3 sides, 1×180◦ internal angle sum) generates 3 hits within 1 beat (a triplet). A square (4 sides, 2×180◦) generates 4 hits over 2 beats. A hexagon (6 sides, 4×180◦) generates 6 hits over 4 beats.[19] This rule provides a deterministic and scalable method for linking edge count to musical time and pulse, forming a strong anchor for temporal mappings.
- **Symmetry → polyrhythmic resolution:** Polygonal symmetry (e.g., reflective, rotational) can be metaphorically mapped to symmetrical structures within polyrhythms or to points of rhythmic stability and resolution. Polyrhythms, the simultaneous use of two or more conflicting rhythms, possess inherent mathematical and perceptual symmetries.[20] For instance, the cumulative rhythm generated by a polyrhythm (the resultant pattern of all onsets) is often palindromic, exhibiting bilateral symmetry.[20] A visually symmetrical polygon could thus be translated into a polyrhythm whose structural symmetry is perceivable auditorily, perhaps leading to a sense of rhythmic resolution or balance. Geometric operations, such as selecting equidistant points on a circle to form a polygon, can also directly generate polyrhythmic structures (e.g., distributing 7 beats over 12 slots to create a bembé rhythm, or overlaying 3-beat and 4-beat cycles derived from triangular and square subdivisions of a circle).[21] The mapping of geometric symmetry to polyrhythmic stability implies that visually balanced polygons might generate soundscapes perceived as more rhythmically resolved or consonant, while asymmetrical polygons could translate to more rhythmically tense or complex patterns.
- **Nesting = layered loop structures:** The hierarchical arrangement of nested polygons (e.g., an octagon inside a triangle) can be translated into layered audio loops, where each polygon corresponds to a distinct sonic layer. The user query's example, "Translate a nested octagon inside a triangle as a multi-layer rhythm: the outer shell is ambient, the triangle is percussion," illustrates this concept. The characteristics of each loop (timbre, rhythmic complexity, melodic content, perceived role) would be determined by the properties of the polygon it represents and its position within the nested hierarchy. While direct research on sonifying nested polygons is limited, analogies exist in computational data mapping (mapping nested data loops [22]), generative art (layered noise frequencies for terrain generation [23]), and generative music systems that extensively use layered loops and polyphonic textures.[24] Sonification of hierarchical data structures like treemaps also employs distinct auditory channels or parameters to represent different levels of the hierarchy.[28] For nested polygons, conveying the *relationship* between layers (e.g., containment, contrast, foreground/background) is paramount. This can be achieved through timbral differentiation (e.g., ambient pads for outer layers, percussive attacks for inner layers), rhythmic interplay (e.g., a foundational rhythm for the outer polygon, with inner polygons playing subdivisions or counter-rhythms), or harmonic relationships.

3.2. Tactile Metaphor Lens (Polygon → Pressure Maps)

This lens explores how polygonal geometry can be rendered into tactile sensations, focusing on pressure, texture, and the demarcation of key features.

- **Angularity = sensation sharpness:** The degree of angularity in a polygon, determined by its vertex angles, can be mapped to the perceived sharpness of a tactile sensation. Triangles, with their acute angles, would intuitively translate to sharper sensations than decagons with more obtuse angles. This aligns with established

cross-modal correspondences linking visual angularity to tactile sharpness.[8] Research using mid-air haptics to render geometric shapes like circles, squares, and triangles has demonstrated that corners are critical distinguishing features.[11] The bouba/kiki effect also indirectly supports this, linking angular visual forms to "kiki" sounds, which often possess phonetically "sharp" qualities.[9] The critical insight here is that the *dynamic* rendering of shapes, such as tracing an outline with a haptic pointer, is generally more effective for recognition than a static, uniform pressure map, especially when these dynamic renderings include pauses or emphasis at vertices.[11] This suggests that PolySensory() tactile outputs should prioritize temporal evolution and explicit signaling of geometric discontinuities. However, the "sharpness" metaphor must be carefully calibrated to be informative rather than aversive, particularly with technologies like focused ultrasound that can create intense localized sensations.

- **Edge transitions = haptic texture transitions:** The transition from one edge of a polygon to another at a vertex can be rendered as a perceptible change in haptic texture. For example, as a user haptically explores a polygon, crossing a vertex could trigger a modulation in perceived friction, softness, roughness, or thermal sensation. "Laterotactile rendering" techniques for vector graphics define transversal profiles (the sensation of crossing over a line) and longitudinal textures (the sensation while tracing along a line).[29] The perceived sharpness of a rendered stroke can be modulated by altering the transition profile at its edges.[29] Similarly, systems for haptic force feedback in polygonal environments interpolate forces at edges to create sensations of smooth or sharp corners.[30]
- **Vertices = haptic markers:** Vertices, as key structural points of a polygon, can be rendered as distinct haptic events or markers. These could be brief pulses, localized vibrations, or distinct pressure points. Research has shown that representing polygons as a set of individually drawn haptic strokes with short pauses at the corners drastically enhances shape recognition accuracy.[11] Superimposing vibrating markers on vertices can also improve their perceptual salience and aid in localization.[29] This underscores the importance of treating vertices not just as points of angular change but as explicit perceptual landmarks in the tactile domain.

A significant consideration for tactile rendering of complex polygons is the human haptic system's tendency to simplify complex shapes into more basic geometric primitives.[31] For instance, a haptically explored shape composed of several connected arcs might be perceived as being made of fewer, simpler semicircles. This implies that as the number of sides in a polygon increases (e.g., a 20-gon or 30-gon), the haptic system might perceptually "smooth out" the fine angular details, potentially leading to a perception closer to a circle or a less complex polygon. This represents a natural "drift threshold" for tactile fidelity, where the perceived shape diverges from the geometric source due to inherent perceptual simplification processes.

3.3. Olfactory Cascade Lens (Polygon → Volatility & Notes)

This lens investigates the translation of polygonal features into olfactory experiences, focusing on complexity, symmetry, and temporal evolution.

- **High-n polygons = layered aromatic complexity:** The number of sides (n) or the overall geometric complexity of a polygon can be mapped to the number of perceptible scent notes or layers in an olfactory composition. This aligns with the perfumery concept of the "fragrance pyramid," which describes a scent's structure in terms of top, middle (heart), and base notes that emerge sequentially due to differing volatilities.[32] A simple polygon (e.g., triangle) might translate to a scent with fewer, more distinct notes (perhaps only top and middle), while a high-n polygon (e.g., a 14-gon) could inspire a more complex blend with multiple notes unfolding across all three phases of the pyramid. The "complexity" could also relate to the richness of individual notes or the intricacy of their interplay. Research into cross-modal correspondences also links scents to other sensory dimensions like light/dark or warm/cool, which could be modulated by polygonal

complexity.[10] While direct mapping of abstract geometry to scent is an emerging area, AI-driven scent generation and analysis of olfactory space geometry offer potential pathways.[34]

- **Folded symmetry = mirrored scent trails:** Polygonal symmetry, particularly bilateral symmetry, can be metaphorically translated into symmetrical structures within a scent's temporal evolution. The user query's example of a "14-gon: 7 mirrored scent pairs progressing from citrus to incense" suggests this. This could manifest as a sequence of scent pairs where each pair has a mirrored or complementary relationship (e.g., a bright citrus paired with a grounding woody note, followed by a delicate floral paired with a resinous note). Alternatively, it could be a temporal mirroring, where a sequence of notes (A→B→C) is followed by a related reversed sequence (C'→B'→A'), where the primed notes are analogous or complementary to the originals. The fragrance pyramid itself is often depicted as a symmetrical triangle [32], and the fragrance wheel can be used to identify complementary (symmetrically opposite) scents.[38] The existence of perfumes with names like "Mirrored Image" [39] and the concept of perfumes mirroring narrative structures [41] also support this metaphorical link. Furthermore, research indicates bilateral symmetry in the neural organization of the olfactory bulb, suggesting a biological predisposition for processing symmetrical olfactory information.[42]

The temporal unfolding of scents, governed by the volatility of their components, provides a natural mechanism for mapping the evolution or sequential reveal of polygonal features, especially when orchestrated by a system like PolyCycle(). A complex polygon's olfactory representation might not be a static aroma but a "scent journey" where different facets, mapped from geometric properties, emerge and recede over time. However, a significant challenge is the relatively low dimensionality of human olfactory perception. Studies suggest that natural odor space can be described by approximately three dimensions.[37] Attempting to map the numerous distinct features of a high-n polygon onto this limited perceptual space could easily lead to "olfactory mud"—a muddled, undifferentiated scent where individual notes are lost, rather than a clearly perceivable complex and layered aroma. This represents a critical risk of semantic flattening in the olfactory domain. The concept of "mirrored scent trails" is particularly abstract and artistic; its success would depend on identifying scent pairs that are genuinely perceived as "mirrored" and controlling their release to create a discernible symmetrical temporal structure.

The following table summarizes foundational cross-modal correspondences relevant to polygonal features, providing a lexicon for the PolySensory() framework.

Table 1: Foundational Cross-Modal Correspondences for Polygonal Features

Polygonal Feature	Target Modality	Established/Hypothesized Sensory Correlate	Key Supporting Research
Edge Count (n)	Sound	Beat cycles (e.g., n subdivisions in n−2 beats), tempo modulation	19
	Touch	Number of distinct haptic markers (vertices), complexity of exploratory path	11
	Scent	Number of primary scent notes/layers, overall aromatic complexity	32

Angularity	Sound	Perceived sharpness of timbre (e.g., "kiki" sounds), higher pitch, dissonance for acute angles	9
	Touch	Perceived tactile sharpness, distinct pressure points at vertices	8
	Scent	"Sharp" or "piquant" scents (e.g., citrus, pepper) for acute angles; "smoother" scents for obtuse angles	10
Symmetry (Regularity)	Sound	Rhythmic stability, palindromic/symmetrical polyrhythmic structures, harmonic consonance/resolution	20
	Touch	Uniformity of texture/pressure along edges, predictable haptic markers at vertices	29
	Scent	Balanced blend of notes, mirrored scent trails (e.g., A→B→C then C'→B'→A'), symmetrical evolution of fragrance pyramid phases	38
Nesting (Hierarchy)	Sound	Layered audio loops, differentiation of timbres/rhythms per layer, foreground/background relationships	22
	Touch	Layered tactile surfaces (if physically possible), sequential exploration revealing depth, variation in pressure/texture with depth	31
	Scent	Depth of blend, evolution from outer (ambient) to inner (focal) scent characteristics, multiple interacting fragrance pyramids	32
Complexity (Overall)	Sound	Richness of timbre, density of sonic events, harmonic complexity	25
	Touch	Intricacy of texture, number of distinct tactile features, cognitive load of exploration	31

	Scent	Number of discernible scent notes, complexity of blend, duration of olfactory experience	32
Size/Area	Sound	Loudness/amplitude, resonance (larger = more resonant/lower fundamental), perceived "spaciousness" of sound	45
	Touch	Area of applied pressure, intensity of sensation	
	Scent	Intensity/projection of scent, duration of dominant notes	13
Convexity/Concavity	Sound	Pitch contour inflections (rising for convex, falling for concave segments), timbral shifts (e.g., open vs. closed vowel sounds)	
	Touch	Direction of pressure change (outward for convex, inward for concave), perceived curvature	11
	Scent	Shifts in scent profile (e.g., expansive/radiant for convex, focused/introspective for concave)	

4. Navigating Perceptual Challenges: Drift, Fracture, and Collapse

The translation of polygonal geometry into multimodal sensory experiences is fraught with perceptual challenges. These arise from the limitations of human sensory processing, the inherent ambiguity of metaphors, and the complexities of integrating information across different modalities. Understanding these challenges is crucial for designing PolySensory() systems that are robust, intuitive, and expressive.

Modal Collapse & Synesthetic Drift

Modal collapse, in this context, refers to a scenario where the distinct sensory experiences intended for different modalities become undifferentiated or lose their unique character, collapsing into a singular, often impoverished, percept. For example, if all features of a highly complex polygon are mapped to sensations of "high intensity" across sound (loud, piercing), touch (strong, sharp pressure), and scent (overpowering aroma), the specific geometric information is lost in a general wave of intensity. This is distinct from the logical concept of modal collapse [46] but metaphorically captures the loss of modal specificity.

Synesthetic drift describes the unintentional shift or blending of sensory mappings, where the perceived qualities deviate from the intended geometric correspondences. A sound designed to represent "angularity" might, due to its specific timbre or associated cultural connotations, evoke unintended color or even taste associations that conflict with or obscure the primary geometric metaphor. This can be exacerbated by individual differences in sensory processing and cross-modal associations.[47] For instance, Multimodal Large Language Models (MLLMs),

when attempting to process or generate multimodal information, can exhibit "multisensory overrating" or rely on "loose semantic associations," which are analogous to drift or metaphor fracture in human perception.[48]

A primary driver of these issues is **metaphor overload or ambiguity**. The user query provides an apt example: "Triangle as 'sharp' → tactile, sonic, aromatic confusion." If "sharpness" is translated too literally or crudely across modalities—a piercing high note for sound, a painfully acute point for touch, and an acrid chemical scent—the resulting experience may be unpleasant, confusing, or overly simplistic, failing to convey a nuanced or coherent multimodal impression of the triangle's geometric nature. The individual sensory translations might be technically "correct" according to a rule, but their combination fails to produce a meaningful or aesthetically satisfying whole. This can also occur if the system attempts to map too many geometric features simultaneously, overwhelming the user's capacity to process and integrate the information.[47]

Metaphor Fractures & Binding Misalignments

Metaphor fracture occurs when the chosen sensory metaphor fails to adequately or convincingly represent the intended geometric property within a specific modality. For instance, if the "closed" boundary of a polygon is mapped to a scent universally perceived as "open," "diffuse," or "airy," the metaphor breaks down, and the intended geometric meaning is not conveyed. This can happen if the chosen correspondence is weak, counterintuitive, or culturally specific.[8]

Binding misalignment refers to the failure of individually translated sensory outputs (even if each is metaphorically valid on its own) to integrate into a coherent, unified multimodal percept of the source polygon. The brain naturally attempts to bind sensory information that is temporally correlated, spatially coincident (where applicable), and semantically congruent into singular events or objects.[7] If the PolySensory() system generates outputs that violate these principles—for example, a sound representing an edge count that is significantly delayed relative to a haptic sensation representing angularity, or if a "smooth" visual curve is mapped to a "rough" texture and a "jagged" sound—the different sensory streams will be perceived as separate and unrelated, or worse, as conflicting, preventing the formation of a unified "polygonal sense." O'Callaghan's work on intermodal feature binding awareness highlights the complex mechanisms involved in perceiving stimuli as part of the same event.[49]

Semantic Flattening & Information Overload

Semantic flattening is the loss of distinct meaning or detail when the complexity of the input geometry exceeds the capacity of a target sensory modality to represent that complexity faithfully. The user query's example, "100-gon as 'infinite' → semantic flattening into noise," perfectly illustrates this. While a 100-sided polygon is visually distinct from a circle (though perhaps only subtly at a distance), its translation into sound (e.g., 100 rapid pulses) might be perceived merely as a continuous buzz or texture, losing the "100-sidedness." Similarly, in olfaction, attempting to represent 100 distinct geometric features with 100 unique scent notes would likely result in an undifferentiated "olfactory mud" rather than a perceivably complex aroma, due to the lower dimensionality of olfactory perception.[37] The specific geometric information is thus "flattened" into a more general or undifferentiated sensory quality (e.g., "many-ness," "roundness," "intense complexity").

Information overload occurs when the sheer volume, intensity, or rate of change of multimodal sensory information surpasses the user's perceptual and cognitive processing capabilities.[50] This can lead to confusion, cognitive fatigue, an inability to discern meaningful patterns, or even sensory aversion.[47] Visually complex images, for instance, require more time and effort for humans to process [48], and this principle extends to complex multimodal displays generated from intricate polygons. If PolySensory() attempts to translate every nuance of a highly complex, nested, and asymmetrical polygon into simultaneous, rapidly changing sonic, tactile, and olfactory

stimuli, the user is likely to experience overload rather than enlightenment. Strategies for managing noise and enhancing salient features in multimodal data [51] are crucial for mitigating this.

Investigating the 17-gon Misinterpretation Prompt

The prompt to "Simulate polygonal metaphor drift: describe how a 17-gon is misinterpreted across touch, sound, and scent models" provides a concrete test case for these challenges:

- **Touch:** A regular 17-gon has relatively small exterior angles between its edges (approximately $360/17 \approx 21.18^\circ$). Haptically, especially if rendered dynamically with a device of limited spatial resolution or if the overall size of the polygon is small, distinguishing its 17 distinct vertices and edges from those of a 16-gon, an 18-gon, or even a circle could be exceedingly difficult.[11] The specific "17-sidedness" (the core metaphor) might be lost, leading to a metaphor fracture. The perception could simplify to "a many-sided, somewhat roundish object" (semantic flattening), consistent with the haptic system's tendency to decompose complex shapes into simpler primitives.[31]
- **Sound:** Mapping 17 sides to a 17-beat rhythmic cycle [19] presents challenges. Seventeen is a prime number, making the rhythm inherently less divisible and potentially harder to entrain to compared to rhythms based on 2, 3, 4, or 6. If the tempo is too fast, the 17 discrete events might blur into a continuous roll or texture (semantic flattening into "fast rhythm" or "buzz"). If the tempo is very slow, maintaining attention and perceiving the 17-beat structure could be difficult. Since a 17-gon lacks the simpler symmetries of even-sided or highly divisible polygons, its translation into polyrhythmic structures might result in complex, less obviously resolved patterns that are hard to parse auditorily.
- **Scent:** Attempting to map 17 distinct geometric features (e.g., each side or vertex, or perhaps 8 mirrored scent pairs plus one unique note if an artificial axis of symmetry is imposed) to 17 discernible olfactory notes would almost certainly overwhelm human olfactory discrimination capacity.[37] The likely outcome would be a single, complex but muddled scent, where only a few dominant or hedonically salient notes are perceived, and the remaining notes contribute to an undifferentiated background (semantic flattening). The "17-ness" of the polygon would be entirely lost in the olfactory translation, and the perceived scent character would depend more on the specific chemistry of the chosen odorants than on the polygon's geometry.

These challenges underscore that "drift" is not just a loss of fidelity but a potential transformation of meaning, where the sensory output evokes an experience different from that intended by the geometric input. "Binding misalignments" often stem from failures in temporal or semantic coherence across modalities [7], while "semantic flattening" is a direct consequence of mismatches between the information density of the source geometry and the channel capacity of the target sense.

The following table provides a taxonomy of these perceptual challenges:

Table 2: Taxonomy of Perceptual Challenges in Polygonal Sensory Translation

Challenge Category	Description	Example Manifestation	Potential Contributing Factors	Relevant Research
Metaphor Overload	Excessive or overly intense sensory translation of a single geometric metaphor across multiple modalities, leading to	Triangle's "sharpness" as piercing sound, painful touch, & acrid scent simultaneously, causing discomfort.	Literal/crude translation, exceeding intensity thresholds, lack of nuance per modality.	47

	negative affect or confusion.			
Synesthetic Drift	Unintended shift or blending of sensory mappings, where perceived qualities deviate from intended geometric correspondence.	Sound for "angularity" unintentionally evokes strong color association that overshadows or conflicts with the geometry.	Idiosyncratic associations, influence of unattended stimulus features (e.g., timbre over pitch).	47
Binding Misalignment	Failure of individually translated sensory outputs to integrate into a coherent multimodal percept of the source polygon.	"Sharp" sound for a vertex arrives noticeably later than the "sharp" haptic pulse for the same vertex.	Temporal asynchrony, spatial incongruity (if applicable), semantic incongruence between modalities, weak cross-modal links.	7
Metaphor Fracture	The chosen sensory metaphor fails to adequately represent the intended geometric property in a given modality.	Mapping "openness" of an incomplete polygon to a scent perceived as "closed" or "heavy."	Weak or counterintuitive correspondence, cultural misinterpretation of metaphor, insufficient sensory parameter range.	8
Semantic Flattening	Loss of distinct geometric meaning or detail when complexity exceeds a modality's representational capacity.	A 100-gon translated to sound becomes an undifferentiated "buzz" or "noise," losing its "100-sidedness."	Exceeding modality channel capacity, insufficient sensory resolution, perceptual simplification mechanisms.	31
Information Overload	Sheer volume, intensity, or rate of change of multimodal sensory information overwhelms perceptual/cognitive processing.	Rapidly changing complex sounds, textures, and scents for a transforming polygon lead to confusion and fatigue.	High data density, rapid temporal changes, excessive concurrent stimuli, exceeding cognitive load limits.	47

5. The PolySensory() Symbolic Schema: A Framework for Generative Implementation

To systematically manage the translation of polygonal geometry into multimodal sensory experiences and address the aforementioned perceptual challenges, a symbolic schema, PolySensory(), is proposed. This schema serves as a conceptual framework and a potential blueprint for a computational system capable of such generative tasks.

Defining the PolySensory() Function

The PolySensory() function can be conceptualized as a high-level interface that takes a polygonal definition and a set of mapping directives as input, and produces corresponding sensory outputs. Its parameters are designed to offer control over both the structural translation and the affective quality of the experience:

- **shape**: This parameter defines the input polygon. It could accept a string representing common polygons (e.g., "heptagon", "triangle", "octagon") or a more detailed data structure for arbitrary or complex polygons

(e.g., a list of vertex coordinates, a graph representation defining edges and connectivity, or parameters for a fractal generation algorithm if edge recursion is involved).

- **modality**: An array specifying the target sensory modalities for output, for example, ["sound", "touch", "scent"]. This allows the system to generate unimodal, bimodal, or fully multimodal experiences based on the request.
- **mapping**: A dictionary or structured object that contains the core translation rules. Each key would correspond to a modality (e.g., "sound"), and its value would specify how geometric features of the shape are mapped to parameters of that sensory output. Examples from the user query include:
  - "sound": "pulses = edge_count; symmetry = harmony_inversion"
  - "touch": "edges = pressure_gradients; vertices = haptic_markers"
  - "scent": "phases = volatility_stages; nesting = depth_of_blend" These rules would internally reference specific geometric properties (e.g., number of edges, type of symmetry, vertex angle sharpness, presence of nesting) and map them to controllable sensory parameters (e.g., number of sonic pulses, harmonic intervals, tactile pressure intensity, number of scent notes, rate of scent evolution). The development of these mapping rules forms the central intellectual challenge, requiring integration of perceptual research [8] and potentially machine learning from human-rated examples.[55]
- **tone**: This parameter dictates the overall affective or aesthetic quality of the generated sensory experience (e.g., "ritualistic", "playful", "somber"). It acts as a high-level constraint that modulates the specific choices made within the mapping rules. For a "ritualistic" tone, sound mappings might favor resonant timbres, slow tempos, and perhaps specific scales or modes; touch might involve smooth, deliberate pressure changes; and scent might lean towards incense, earthy notes, or specific culturally significant aromas. This parameter acknowledges that the same geometry can be expressed with different emotional characters.
- **binding**: Specifies the mechanism for ensuring cross-modal coherence and mitigating drift. This is critical for creating unified multimodal percepts.

The conceptualization of PolySensory() aligns with frameworks in generative art that describe systems in terms of entities (polygons), processes (mapping rules), and sensory outcomes.[57] Computational approaches from multimodal data fusion and geometric feature mapping in brain imaging [59] or the use of sound-symbolic words to bridge vision and auditory concepts [55] provide analogous examples of structured cross-modal translation.

Ensuring Cross-Modal Coherence: Drift-Safety Mechanisms

To prevent perceptual drift and ensure that the different sensory outputs are perceived as belonging to a single, coherent multimodal object, PolySensory() incorporates "drift-safety" mechanisms, primarily through the binding parameter:

- **binding = "phase-sync"**: This mechanism focuses on synchronizing the temporal aspects of the generated sensory experiences. It goes beyond simple simultaneous onsets of events. For sound and touch, it could mean that rhythmic pulses in an auditory stream align precisely with haptic pulses, or that the amplitude envelope (Attack, Decay, Sustain, Release - ADSR) of a sound is mirrored in the pressure profile or intensity curve of a tactile sensation. For scent, the distinct phases of olfactory evolution (top, middle, and base notes emerging due to differential volatility) could be synchronized with major sections, dynamic shifts, or rhythmic cycles in an accompanying sound composition or a sequence of haptic explorations. Research into cross-modal influences mediated by the synchronization of neural oscillations [60] suggests that such phase synchronization can tap into fundamental neural binding mechanisms, making the multimodal experience more compelling and unified. Systems like JavisDiT for audio-video synchronization [61] and PhysioSync for aligning physiological signals [63] demonstrate computational approaches to achieving fine-grained temporal alignment

across modalities.

- **anchor = true**: This parameter enables a strategy where one particularly robust or perceptually salient feature-modality mapping serves as a central "anchor" to which other sensory outputs are keyed. For instance, if the mapping of polygon edge_count to beat_cycles in sound proves to be highly intuitive and stable (as suggested by [19]), this primary sonic rhythm could act as the temporal anchor. Tactile events (e.g., haptic markers at vertices) and phases of scent evolution would then align their timing and structure to this dominant auditory rhythm. This is analogous to spatial anchors used in augmented and virtual reality to maintain positional consistency and prevent drift of virtual objects relative to the real world.[64] A perceptual anchor in PolySensory() would provide a stable temporal or structural reference, helping to ground the other sensory experiences and prevent them from being perceived as disconnected.

Temporal Synchronization with PolyCycle(): Layering Narrative and Sensory Grammar

The PolySensory() function, as described, primarily handles the translation of a single (potentially nested) polygon at a given moment. To create dynamic, evolving experiences, it is proposed to be layered with a PolyCycle() system. PolyCycle() would function as a higher-order controller or sequencer that orchestrates multiple calls to PolySensory() over time, or dynamically modulates PolySensory()'s parameters (like shape or tone) according to a predefined or interactive narrative structure.

This introduces the concept of synchronizing a "narrative grammar" (which dictates the thematic development, emotional arc, or sequence of events in the experience) with the "sensory grammar" (the set of mapping rules within PolySensory()). For example, PolyCycle() could define a narrative that involves a simple geometric form gradually increasing in complexity, or a transformation from a regular, symmetrical polygon to an irregular, asymmetrical one. PolySensory() would then be invoked at each stage of this transformation, generating sensory outputs that reflect the changing geometry, with PolyCycle() ensuring smooth transitions and overall temporal coherence.

Methodologies from multimodal video understanding, such as the use of recurrent transformers and explicit memory controllers to generate temporally coherent visual stories from text [65], offer valuable architectural inspiration for PolyCycle(). An "explicit polygonal memory controller," for example, could maintain a history of the geometric transformations and their associated sensory outputs, allowing the system to generate future sensory states that are consistent with the established narrative and sensory trajectory. This moves PolySensory() from a static translator to a component within a dynamic storytelling engine, capable of generating rich, evolving multimodal narratives based on polygonal logic. The integration of such systems is crucial for creating experiences that unfold meaningfully over time, aligning with human perceptual and cognitive processes that are inherently dynamic and context-aware.[67]

The mapping rules within PolySensory() are the intellectual engine of the system. Their design necessitates a profound interdisciplinary synthesis, merging principles from geometry, perceptual psychology (particularly cross-modal research), neuroscience, and even artistic practice. These rules are unlikely to be static; they might be learned through machine learning techniques, adapted based on user feedback, or even co-created interactively. The binding = "phase-sync" mechanism implies more than mere simultaneous event onsets; it points towards a deeper structural coherence in the temporal domain across modalities, potentially mirroring the phase relationships of neural oscillations involved in natural cross-modal binding.[60] This could involve shared rhythmic motifs, aligned rates of change in intensity or complexity, or correlated evolutionary paths in scent and sound. Furthermore, the PolyCycle() layer transforms PolySensory() into a dynamic narrative tool. For example, if PolyCycle() dictates an emotional arc from "tension" to "release," PolySensory() would need to adjust its tone and mapping parameters to ensure the sensory outputs for a given polygon reflect this overarching emotional state,

making the system highly expressive and adaptive.

The following table deconstructs the PolySensory() schema, clarifying its parameters and their generative implications.

Table 3: PolySensory() Schema Parameters and Generative Logic

Parameter	Data Type/Structure	Example Value(s) from Query	Core Generative Logic Implied	Key Considerations/Challenges for Implementation
shape	String (for common polygons) or Object (e.g., vertex list, graph)	"heptagon"	Defines the primary geometric input. The system must parse this into quantifiable features (edge count, angles, symmetry, etc.).	Handling arbitrary polygons, defining a comprehensive feature extraction process.
modality	Array of Strings	["sound", "touch", "scent"]	Selects which sensory outputs to generate.	Managing computational resources if all modalities are active; ensuring graceful degradation if some modalities are unavailable.
mapping	Dictionary (Modality: RuleString/Object)	{"sound": "pulses = edge_count; symmetry = harmony_inversion"}	Contains the core translation rules linking geometric features to sensory parameters for each selected modality.	Defining a robust, expressive, and perceptually valid rule set; developing a rule language or structure. This is the primary research area.
sound_map	String or Object	"pulses = edge_count; symmetry = harmony_inversion"	Specific rules for sound generation (e.g., rhythm from edge count, harmonic properties from symmetry).	Mapping geometric features to musical parameters like pitch, timbre, rhythm, loudness, spatialization.
touch_map	String or Object	"edges = pressure_gradients; vertices = haptic_markers"	Specific rules for tactile rendering (e.g., edge transitions as pressure changes, vertices as distinct pulses).	Mapping geometry to haptic parameters like pressure, vibration, texture, temperature, shape tracing. Device capabilities are a major constraint.
scent_map	String or Object	"phases = volatility_stages; nesting = depth_of_blend"	Specific rules for olfactory display (e.g., complexity mapped to scent layers/volatility, nesting to blend depth).	Mapping geometry to scent notes, intensity, complexity, and temporal evolution. Delivery mechanisms and olfactory

				perception limits are key challenges.
tone	String	"ritualistic"	Defines the affective or aesthetic quality of the output, modulating the mapping rules.	Quantifying "tone" and translating it into concrete sensory parameter adjustments. Requires understanding of emotional impact of sensory stimuli.
binding	String	"phase-sync"	Specifies the strategy for ensuring cross-modal coherence and preventing perceptual drift.	Implementing robust temporal synchronization across disparate sensory generation systems; defining what "phase" means for each modality.
anchor	Boolean	true / false	If true, a dominant feature-modality pair acts as a reference to key other sensory outputs, enhancing coherence.	Identifying suitable anchor mappings; designing how other modalities dynamically align to the anchor.

6. Reflexive Insights and Future Research Directions

The exploration of translating polygonal geometry into multimodal sensory experiences opens numerous avenues for reflexive inquiry and future research. These questions challenge the foundational assumptions of such translations and point towards the refinement of systems like PolySensory().

Stability of Geometric Forms Across Modalities

A key question is whether certain polygons exhibit greater "cross-modal stability," meaning their essential geometric characteristics are more readily and consistently perceived when translated into sound, touch, and scent. It is plausible that simpler, more common geometric forms like triangles, squares, and hexagons might possess more robust and universally understood cross-modal associations. This could be due to their frequent appearance in natural and cultural contexts, leading to what might be termed "perceptual economy"—they are easily processed and have strong, pre-existing (or easily learned) sensory correlates. Research on the temporal stability of taste-shape correspondences, which found that associations like sweet-round are remarkably stable over time [69], provides a methodological precedent for investigating the stability of polygon-sensory mappings. Furthermore, studies on neural processing suggest that while primary sensory cortices are adaptable, the influence of other modalities (extramodal inputs) can be surprisingly stable [70], hinting that some cross-modal links are deeply embedded. The clear rhythmic mappings for hexagons, for example [19], suggest a high degree of stability for that specific feature-modality pairing. Future research should systematically test a range of polygons, from simple to complex, to identify which geometric features and forms translate most reliably and intuitively across different sensory outputs.

Limits of Metaphorical Translation

Another critical area of inquiry concerns the limits of metaphorical translation: which geometric concepts or properties "break down" when forced into non-visual sensory forms? The user query's example, "decagons as scent layers," prompts this question. At what point does the abstraction become too great for a meaningful or discernible sensory correlate? Visual limitations in understanding geometry, especially when students are confronted with unfamiliar problems or representations [71], offer an analogy for potential breakdowns in cross-sensory metaphor. Sensory substitution research highlights that perception in a substituted modality (e.g., "seeing" with touch) is not a direct replication of the original sense but a new form of perception shaped by the capabilities of the substituting sense and the translation process.[72] This implies inherent limits to the fidelity of any cross-modal metaphor. The challenges faced by advanced AI models, such as MLLMs, in achieving robust physical grounding and generalization from abstract inputs [73], further underscore the difficulties in maintaining metaphor fidelity, especially with increasing complexity. Identifying these breaking points is crucial for defining the operational boundaries of PolySensory() and for developing strategies to handle highly abstract or complex geometric inputs—perhaps through simplification, abstraction, or by acknowledging that not all geometric features can be equally well represented in all sensory modalities.

Perceptibility of Geometric Recursion

The concept of "edge recursion," such as in fractal-like polygonal edges, poses a fascinating challenge: can such recursive geometric patterns be meaningfully sensed through non-visual modalities, or are they primarily a visual phenomenon? Translating geometric recursion into perceivable auditory, tactile, or olfactory patterns likely requires mapping the *concept* of recursion—self-similarity at different scales—into analogous sensory structures.

- **Auditory:** This could involve repeating melodic or rhythmic motifs at different tempos, pitches, or timbral complexities, creating nested sonic structures.[75] Listeners have shown an ability to categorize and identify fractal contours in sound when mapped to pitch and loudness [78], suggesting a capacity to perceive self-similar statistical patterns auditorily.
- **Tactile:** Haptic perception of complex shapes often involves simplification into geometric primitives [31], which might make the direct perception of fine-grained edge recursion difficult. However, recursive patterns could be represented through layered textures with similar structural properties at different intensities or scales of exploration.[79] The Recursive Fractal Modeling (RFM) method for visual fractals, with its adaptive recursion [75], could metaphorically inform the generation of recursive tactile patterns.
- **Olfactory:** Direct olfactory representation of geometric edge recursion seems highly challenging due to the low dimensionality of scent perception.[37] Perhaps a recursive scent structure could involve a core base accord that is iteratively revisited with evolving top and middle notes that share some self-similar characteristic with the base.

The key is likely not a literal point-by-point mapping of recursive edge detail, but a translation of the *generative rule* or the *percept of self-similarity* into each target modality.

Avoiding Modal Clichés

A significant challenge in designing PolySensory() systems is to avoid "modal clichés"—mappings that are overly simplistic, predictable, or stereotypical (e.g., sharp angle always equals high pitch and fast tempo). Such clichés can diminish the expressive power and novelty of the generated experiences. Research on cross-modal correspondences often employs explicit matching tasks between stimuli with opposing features (e.g., angular vs. rounded, high vs. low pitch) [80], which, while useful for establishing basic links, can inadvertently reinforce simplistic mappings if not expanded upon. To achieve true symbolic fidelity and innovation, mappings must move towards more context-dependent and relational interpretations. Cassirer's "Philosophy of Symbolic Forms" [81] suggests a

deeper inquiry into how meaning is grounded in sensory experience and symbolic representation, which can inform the creation of more nuanced translations. The tone parameter within the PolySensory() schema is specifically designed to address this, allowing for modulation of basic mapping rules. For example, a "sharp" angle under a "ritualistic" tone might be translated differently (e.g., a resonant, clear, but not aggressive high pitch) than under an "aggressive" tone (e.g., a piercing, dissonant high pitch).

The Role of Advanced AI in PolySensory Systems

Generative AI and Multimodal Large Language Models (MLLMs) hold considerable potential for enhancing PolySensory() systems, but also present challenges.

- **Potential:** MLLMs could assist in interpreting the semantic and affective qualities of input polygons, help select appropriate tone parameters, or even learn complex mapping functions from data.[24] Generative models are already being used for music synthesis [24], scent creation [34], and multimodal understanding.
- **Challenges:** Current MLLMs exhibit deficiencies in fine-grained geometric perception, precise spatial reasoning, and handling abstract geometric concepts.[84] They may struggle with the nuanced, step-by-step logical reasoning required to translate complex polygonal structures into coherent sensory outputs without significant human-defined rules or specialized training data. Issues like "hallucinations" during reasoning or reliance on superficial semantic associations are pertinent.[48] While MLLMs can process multimodal inputs, their ability to autonomously *derive* nuanced and perceptually valid sensory mappings directly from abstract geometric logic is still an active area of research. Systems like GeoGen, which use symbolic reasoning to generate training data for MLLMs in geometry problem solving [85], suggest a hybrid approach might be most fruitful for PolySensory().

Future research should focus on empirical validation of hypothesized polygon-sensory mappings, development of computational tools for PolySensory() and PolyCycle(), fostering artistic explorations of these concepts [5], and targeted improvements in MLLMs' geometric reasoning capabilities. The stability of polygonal mappings might correlate with their "perceptual economy," where simpler, common forms have more robust cross-modal links. Avoiding modal clichés will require moving towards context-dependent and relational mappings, potentially guided by the tone parameter and a deeper semantic understanding.

The following table outlines these reflexive insights and associated research questions:

Table 4: Reflexive Insights and Research Questions for Polygonal Sensory Mapping

Reflexive Question from Query	Key Associated Geometric Properties	Relevant Modalities	Hypothesized Factors Influencing the Answer	Illustrative Research & Snippets	Specific Research Questions for Future Work
Are certain polygons more stable across modalities?	Simplicity (low edge count), regularity, commonality (e.g., triangle, square, hexagon)	Sound, Touch, Scent	Perceptual economy, prevalence in nature/culture, strength of innate/learned cross-modal associations, lower cognitive load for	[69] (taste-shape stability)[19] (hexagon rhythm)	Which specific polygons (and their features) show highest test-retest reliability in cross-modal translation tasks? Do mappings for simpler polygons

			processing.		require less cognitive load?
Which metaphors break when forced into non-visual form?	High complexity (e.g., high-n decagons), highly abstract geometric concepts (e.g., non-Euclidean properties if applicable)	Primarily Scent, potentially Touch for very fine detail.	Exceeding channel capacity of target modality, lack of established sensory analogue for the geometric concept, metaphor too abstract or arbitrary.	[71] (visual limits in geometry)[72] (sensory substitution limits)[37] (olfactory dimensionality)	At what level of polygon complexity (e.g., n-value for n-gon) do olfactory or tactile translations lose meaningful distinctiveness and flatten into general percepts?
Can edge recursion be sensed or only seen?	Fractal dimensions, self-similarity at multiple scales, iterative generative rules.	Sound, Touch, (potentially Scent at a highly abstract level).	Translation of the *concept* of recursion (e.g., repeating motifs, layered self-similar textures) rather than literal edge detail. Perceptual limits on resolving fine recursive detail.	[31] (haptic simplification)[75] (auditory/visual fractals)	What are the most effective auditory and tactile parameters for conveying the *sensation* of recursion or self-similarity derived from a fractal polygon? What are the JNDs for perceived recursiveness?
At what point does symbolic fidelity collapse into modal cliché?	Basic, overly direct mappings (e.g., angularity = high pitch only).	All (Sound, Touch, Scent).	Lack of nuance, context-insensitivity, failure to incorporate affective dimensions (tone), over-reliance on simplest dichotomies (sharp/round).	[80] (explicit matching tasks)[81] (symbolic forms)	How can the tone parameter in PolySensory() be algorithmically defined to modulate basic mappings and create richer, less clichéd outputs? Can MLLMs be trained to identify and avoid modal clichés?

7. Conclusion: Towards Expressive and Coherent Polygonal Senses

The systematic translation of polygonal geometry into multimodal sensory experiences—sound, touch, and scent—represents a compelling research endeavor at the intersection of generative AI, perceptual psychology, and art. This report has outlined a conceptual framework, grounded in existing research on cross-modal correspondences, synesthesia, and sensory metaphor, for achieving such translations. The proposed "Multimodal Lens Framework" offers specific strategies for mapping polygonal features like edge count, angularity, symmetry, and nesting into corresponding sensory parameters. The PolySensory() symbolic schema, augmented by drift-safety mechanisms like "phase-sync" and "anchoring," and temporally orchestrated by a PolyCycle() system, provides a structured approach for generative implementation.

However, the journey towards creating truly expressive and coherent "polygonal senses" is laden with significant perceptual challenges. Issues such as metaphor overload, synesthetic drift, binding misalignments between modalities, modal collapse, and semantic flattening due to information overload or sensory channel capacity limits

must be carefully navigated. The inherent tendency of some sensory systems (e.g., haptics, olfaction) to simplify complex inputs or their lower dimensionality compared to vision poses fundamental constraints on the fidelity and richness of translation for highly complex polygons.

The development of PolySensory() systems is, therefore, not merely a technical undertaking but a deeply creative one. It demands a synergistic blend of scientific rigor in understanding perceptual mechanisms and artistic intuition in crafting evocative and meaningful sensory outputs. The "ritualistic" tone example within the PolySensory() schema hints at the potential for these systems to move beyond mere information display into realms of contemplative, affective, or even transformative art.

Recommendations for Future Directions:

1. **Empirical Validation:** Conduct rigorous psychophysical experiments to validate the hypothesized polygon-sensory mappings outlined in Table 1. Investigate the perceptual thresholds for distinguishing complex polygonal features in each target modality and identify the points at which drift, fracture, or semantic flattening occur (Table 2). Test the intelligibility and aesthetic appeal of different mapping strategies for features like recursion.
2. **Computational Tool Development:** Develop prototype implementations of the PolySensory() schema (Table 3) and the PolyCycle() narrative engine. Explore machine learning approaches, potentially leveraging generative adversarial networks (GANs) or reinforcement learning, to train mapping functions based on human perceptual ratings or by analyzing existing successful cross-modal artworks.
3. **Artistic and Design Exploration:** Foster collaborations between researchers, AI developers, artists, and designers to create and evaluate polysensory installations and experiences based on these principles.[5] Such practice-based research is invaluable for uncovering novel expressive possibilities and refining the underlying generative logic.
4. **Advancing MLLM Capabilities:** Address the current deficiencies in MLLMs regarding fine-grained geometric perception and multi-step abstract reasoning (Table 4[84]). Research efforts should focus on developing MLLMs that can better understand and translate abstract structural logic into nuanced, cross-modally coherent conceptual representations, potentially through integration with symbolic reasoning systems or training on curated datasets of geometric-sensory correspondences.

By systematically addressing these research questions and embracing an interdisciplinary approach, the field can move closer to unlocking the profound generative potential of polygonal senses, creating novel forms of expression, interaction, and understanding that engage the full spectrum of human perception.

Works cited

1. Multi-Sensory Interaction for Blind and Visually Impaired People - MDPI, accessed May 14, 2025, https://mdpi-res.com/bookfiles/book/4976/MultiSensory_Interaction_for_Blind_and_Visually_Impaired_People.pdf?v=1742090734
2. Vibrotactile feedback for conveying object shape information as perceived by artificial sensing of robotic arm - PMC, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC4947058/
3. Thesaurus - ADA - Archive of Digital Art, accessed May 14, 2025, https://digitalartarchive.at/archive/keywords/
4. GEODE BY ESTEBAN GARCIA BRAVO - ADA | Archive of Digital Art, accessed May 14, 2025, https://www.archive-digitalart.eu/database/literature/work/geode.html

5. Polygon's Powerful Immersive Experiences Are Grounded in The ..., accessed May 14, 2025, https://theartofsound.l-acoustics.com/polygons-is-grounded-in-artistry/
6. FAQs | Polygon Productions, accessed May 14, 2025, https://polygon-productions.live/faqs/
7. 11.2 Cross-modal perception - Fiveable, accessed May 14, 2025, https://library.fiveable.me/perception/unit-11/cross-modal-perception/study-guide/yHA8eL7n75UrhgJ0
8. (PDF) Crossmodal Associations with Olfactory, Auditory, and Tactile ..., accessed May 14, 2025, https://www.researchgate.net/publication/356819010_Crossmodal_Associations_with_Olfactory_Auditory_and_Tactile_Stimuli_in_Children_and_Adults
9. Bouba/kiki effect - Wikipedia, accessed May 14, 2025, https://en.wikipedia.org/wiki/Bouba/kiki_effect
10. Multi-Sensory Color Code Based on Sound and Scent for Visual Art ..., accessed May 14, 2025, https://www.mdpi.com/2079-9292/10/14/1696
11. Mid-air haptic rendering of 2D geometric shapes with a dynamic tactile pointer - Sussex Figshare, accessed May 14, 2025, https://sussex.figshare.com/articles/journal_contribution/Mid-air_haptic_rendering_of_2D_geometric_shapes_with_a_dynamic_tactile_pointer/23474645/1/files/41183768.pdf
12. discovery.ucl.ac.uk, accessed May 14, 2025, https://discovery.ucl.ac.uk/10112400/1/Toh_shapes.pdf
13. Smelling Shapes: Crossmodal Correspondences Between Odors and Shapes | Request PDF - ResearchGate, accessed May 14, 2025, https://www.researchgate.net/publication/232766064_Smelling_Shapes_Crossmodal_Correspondences_Between_Odors_and_Shapes
14. (PDF) “Like Popcorn”: Crossmodal Correspondences Between Scents, 3D Shapes and Emotions in Children - ResearchGate, accessed May 14, 2025, https://www.researchgate.net/publication/331928939_Like_Popcorn_Crossmodal_Correspondences_Between_Scents_3D_Shapes_and_Emotions_in_Children
15. Synesthesia: Definition, Examples, Causes, Symptoms, and Treatment - Healthline, accessed May 14, 2025, https://www.healthline.com/health/synesthesia
16. Synesthesia - Wikipedia, accessed May 14, 2025, https://en.wikipedia.org/wiki/Synesthesia
17. The role of perceptual and action effector strength of graphs and ..., accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC10445147/
18. An Empirical Study to Understand Symbolic and Sensory Metaphors ..., accessed May 14, 2025, https://www.mdpi.com/2075-5309/14/8/2561
19. Made a game about visualizing rhythm in geometry! : r/musictheory, accessed May 14, 2025, https://www.reddit.com/r/musictheory/comments/amh7wz/made_a_game_about_visualizing_rhythm_in_geometry/
20. www.jonathandimond.com, accessed May 14, 2025, http://www.jonathandimond.com/downloadables/Introduction_to_Polyrhythm-Di

mond_2018.pdf
21. Maths and music, together in harmony - Chalkdust, accessed May 14, 2025, https://chalkdustmagazine.com/blog/maths-music-together-harmony/
22. Mapping nested loops - Qlik Help, accessed May 14, 2025, https://help.qlik.com/talend/en-US/data-mapper-user-guide/8.0-R2024-12/mapping-nested-loops
23. Making maps with noise functions - Red Blob Games, accessed May 14, 2025, https://www.redblobgames.com/maps/terrain-from-noise/
24. A Geometrical Approach to Deep Generative Music Modeling, accessed May 14, 2025, https://www.sorbonne-universite.fr/sites/default/files/media/2025-03/CELLA%20Carmine-Emanuele_ED130.pdf
25. A Survey of Music Generation in the Context of Interaction - arXiv, accessed May 14, 2025, https://arxiv.org/html/2402.15294v1
26. Musical Building Blocks: Wwise Layered Loops - YouTube, accessed May 14, 2025, https://www.youtube.com/watch?v=ylCt3y_KC50
27. How Generative Music Works, accessed May 14, 2025, https://teropa.info/loop/
28. Towards a unified terminology for sonification and visualization - PMC - PubMed Central, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC10589160/
29. cim.mcgill.ca, accessed May 14, 2025, https://cim.mcgill.ca/~haptic/laterotactile/papers/VL-VH-EH-10.pdf
30. A Polygonal Method for Haptic Force Generation - OSTI, accessed May 14, 2025, https://www.osti.gov/servlets/purl/453502
31. Factors Influencing Haptic Perception of Complex Shapes - PMC, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC2609756/
32. Top, Middle & Bottom Notes: Understanding the Fragrance Pyramid ..., accessed May 14, 2025, https://www.craftovator.co.uk/blogs/academy/top-middle-bottom-notes-understanding-the-fragrance-pyramid-and-scent-notes
33. The Art of Perfume-Making: Understanding Top, Middle, and Base Notes - Edens Garden, accessed May 14, 2025, https://www.edensgarden.com/blogs/news/the-art-of-perfume-making-understanding-top-middle-and-base-notes
34. Generative AI Perfects the Craft of Scent Creation - BIOENGINEER.ORG, accessed May 14, 2025, https://bioengineer.org/generative-ai-perfects-the-craft-of-scent-creation/
35. A Principal Odor Map Unifies Diverse Tasks in Olfactory Perception - PMC, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC11898014/
36. Navigating the Fragrance space Via Graph Generative Models And Predicting Odors - arXiv, accessed May 14, 2025, https://arxiv.org/html/2501.18777v1
37. Hyperbolic geometry of the olfactory space - PMC, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC6114987/
38. The Science of Perfume: Decoding the Composition and Structure of Fragrances, accessed May 14, 2025,

https://sartorialmagazine.com/beauty/2024/2/5/the-science-of-perfume-decoding-the-composition-and-structure-of-fragrancesnbsp
39. Mirrored Image Mirrored Image for $4.95 | Scentbird, accessed May 14, 2025, https://www.scentbird.com/perfume/murillo-twins-mirrored-image-3149
40. Mirrored Image Eau De Parfum - Murillo Twins Fragrance, accessed May 14, 2025, https://murillotwinsfragrance.com/products/mirrored-image
41. The Intersection of Scent and Art: How Perfumery Mirrors Contemporary Culture, accessed May 14, 2025, https://ourculturemag.com/2025/02/05/the-intersection-of-scent-and-art-how-perfumery-mirrors-contemporary-culture/
42. 3D spatial transcriptomics reveals the molecular domain structure of the mouse olfactory bulb - bioRxiv, accessed May 14, 2025, https://www.biorxiv.org/content/10.1101/2025.02.19.639192v1.full.pdf
43. Symmetry, Stereotypy, and Topography of Odorant Representations in Mouse Olfactory Bulbs - PMC - PubMed Central, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC6762614/
44. The Complexity of Olfactory Art The Use of Scent as Concept and Context in the Work of Art, accessed May 14, 2025, https://www.researchgate.net/publication/357410923_The_Complexity_of_Olfactory_Art_The_Use_of_Scent_as_Concept_and_Context_in_the_Work_of_Art
45. “Like Popcorn”: crossmodal correspondences between scents, 3D shapes and emotions in children - Sussex Figshare, accessed May 14, 2025, https://sussex.figshare.com/ndownloader/files/41176256/1
46. Modal collapse - Wikipedia, accessed May 14, 2025, https://en.wikipedia.org/wiki/Modal_collapse
47. 8 Senses of the Body: the Hidden Sensory Systems - Neurodivergent Insights, accessed May 14, 2025, https://neurodivergentinsights.com/8-senses/
48. (PDF) Multimodal LLM Augmented Reasoning for Interpretable ..., accessed May 14, 2025, https://www.researchgate.net/publication/390892770_Multimodal_LLM_Augmented_Reasoning_for_Interpretable_Visual_Perception_Analysis
49. Multisensory perception as an associative learning process - Frontiers, accessed May 14, 2025, https://www.frontiersin.org/journals/psychology/articles/10.3389/fpsyg.2014.01095/full
50. Sensory Augmentation for the Blind - PMC - PubMed Central, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC3290767/
51. Multimodal mismatch responses in mouse auditory cortex - eLife, accessed May 14, 2025, https://elifesciences.org/reviewed-preprints/95398
52. Multimodal Hypersensitivity Derived from Quantitative Sensory Testing Predicts Pelvic Pain Outcome: an Observational Cohort Study - PubMed Central, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC10440257/
53. Multimodal Point Cloud Semantic Segmentation With Virtual Point Enhancement - arXiv, accessed May 14, 2025, https://arxiv.org/html/2504.01449v1
54. ISDrama: Immersive Spatial Drama Generation through Multimodal Prompting -

arXiv, accessed May 14, 2025, https://arxiv.org/html/2504.20630v1
55. Computer Vision System for Expressing Texture Using ... - Frontiers, accessed May 14, 2025, https://www.frontiersin.org/journals/psychology/articles/10.3389/fpsyg.2021.654779/full
56. SyncNoise: Geometrically Consistent Noise Prediction for Text-based 3D Scene Editing, accessed May 14, 2025, https://arxiv.org/html/2406.17396v1
57. On the cover: Voronoi diagrams and generative art - Chalkdust, accessed May 14, 2025, https://chalkdustmagazine.com/regulars/on-the-cover/on-the-cover-voronoi-diagrams-and-generative-art/
58. A Comprehensive Framework to Understand Generative Art - Visual Alchemist, accessed May 14, 2025, https://visualalchemist.in/2024/10/04/a-comprehensive-framework-to-understand-generative-art/
59. A Geometric Framework for Feature Mappings in Multimodal Fusion of Brain Image Data, accessed May 14, 2025, https://pubmed.ncbi.nlm.nih.gov/31871388/
60. Synchronisation of Neural Oscillations and Cross-modal Influences - PMC - PubMed Central, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC7653674/
61. JavisDiT : Joint Audio-Video Diffusion Transformer with Hierarchical Spatio-Temporal Prior Synchronization - arXiv, accessed May 14, 2025, https://arxiv.org/html/2503.23377v1
62. arXiv:2503.23377v1 [cs.CV] 30 Mar 2025, accessed May 14, 2025, http://arxiv.org/pdf/2503.23377
63. PhysioSync: Temporal and Cross-Modal Contrastive Learning Inspired by Physiological Synchronization for EEG-Based Emotion Recognition - arXiv, accessed May 14, 2025, https://arxiv.org/html/2504.17163v1
64. Spatial Anchors Best Practices | Meta Horizon OS Developers, accessed May 14, 2025, https://developers.meta.com/horizon/documentation/unity/unity-spatial-anchors-best-practices/
65. "Towards Multi-modal Explainable Video Understanding" by Kashu Yamazaki, accessed May 14, 2025, https://scholarworks.uark.edu/etd/4919/
66. Generating a Temporally Coherent Visual Story by Multimodal ..., accessed May 14, 2025, https://openreview.net/forum?id=L99I9HrEtEm
67. A Novel Integrated Information Processing Model of Presence | Request PDF, accessed May 14, 2025, https://www.researchgate.net/publication/349839116_A_Novel_Integrated_Information_Processing_Model_of_Presence
68. Coherence in multimodal arts installations - John Benjamins, accessed May 14, 2025, https://benjamins.com/catalog/pbns.254.07hue
69. How stable are taste-shape crossmodal correspondences over time ..., accessed May 14, 2025, https://www.researchgate.net/publication/384939984_How_stable_are_taste-sha

pe_crossmodal_correspondences_over_time
70. Stability of cross-sensory input to primary somatosensory cortex across experience - PMC, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC11326227/
71. (PDF) Circumventing visual limitations in teaching the geometry of shapes - ResearchGate, accessed May 14, 2025, https://www.researchgate.net/publication/227223329_Circumventing_visual_limitations_in_teaching_the_geometry_of_shapes
72. Sensory substitution - Wikipedia, accessed May 14, 2025, https://en.wikipedia.org/wiki/Sensory_substitution
73. Neural Brain: A Neuroscience-inspired Framework for Embodied Agents - arXiv, accessed May 14, 2025, https://arxiv.org/html/2505.07634v1
74. Exploring Embodied Multimodal Large Models: Development, Datasets, and Future Directions - arXiv, accessed May 14, 2025, https://arxiv.org/html/2502.15336v1
75. Mathematical Modeling and Recursive Algorithms for Constructing Complex Fractal Patterns, accessed May 14, 2025, https://www.mdpi.com/2227-7390/13/4/646
76. Fractal - Wikipedia, accessed May 14, 2025, https://en.wikipedia.org/wiki/Fractal
77. hspublishing.org, accessed May 14, 2025, https://hspublishing.org/ASRP/article/download/264/211/363
78. Auditory Perception of Fractal Contours - ResearchGate, accessed May 14, 2025, https://www.researchgate.net/profile/Mark-Schmuckler/publication/14868618_Auditory_Perception_of_Fractal_Contours/links/5c8fd3baa6fdcc38175ca280/Auditory-Perception-of-Fractal-Contours.pdf
79. FRACTAL DESCRIPTION OF ROUGH SURFACES FOR HAPTIC DISPLAY - Lunar and Planetary Laboratory, accessed May 14, 2025, https://www.lpl.arizona.edu/~shane/fractal/costa_phd_2000.pdf
80. Crossmodal correspondences between visual and speech angularity and tactile jaggedness of response key - PMC, accessed May 14, 2025, https://pmc.ncbi.nlm.nih.gov/articles/PMC11561357/
81. The cognitive roots of multimodal symbolic forms with an analysis of multimodality in movies - Frontiers, accessed May 14, 2025, https://www.frontiersin.org/journals/communication/articles/10.3389/fcomm.2024.1352252/epub
82. Why Multimodal Models Are the Future of AI? - SoluLab, accessed May 14, 2025, https://www.solulab.com/multimodal-models/
83. Download PDF (8MB) - Zurich Open Repository and Archive, accessed May 14, 2025, https://www.zora.uzh.ch/id/eprint/277246/1/Dissertation_Armitage_Jason.pdf
84. GePBench: Evaluating Fundamental Geometric Perception for Multimodal Large Language Models - arXiv, accessed May 14, 2025, https://arxiv.org/html/2412.21036v2
85. [2504.12773] Enhancing the Geometric Problem-Solving Ability of Multimodal LLMs via Symbolic-Neural Integration - arXiv, accessed May 14, 2025,

https://arxiv.org/abs/2504.12773
86. Enhancing the Geometric Problem-Solving Ability of Multimodal LLMs via Symbolic-Neural Integration - arXiv, accessed May 14, 2025, https://arxiv.org/html/2504.12773v1
87. (PDF) Improving Multimodal LLMs Ability In Geometry Problem Solving, Reasoning, And Multistep Scoring - ResearchGate, accessed May 14, 2025, https://www.researchgate.net/publication/386375152_Improving_Multimodal_LLMs_Ability_In_Geometry_Problem_Solving_Reasoning_And_Multistep_Scoring
88. SENSIBLY SOUND: HUMAN-CENTERED INTEGRATION OF SONIFICATION AND VISUALIZATION - Simple search, accessed May 14, 2025, https://liu.diva-portal.org/smash/get/diva2:1946353/FULLTEXT01.pdf
89. João Carvalho Oliveira das Neves Acoustic Mirrors From Sound to Tangibility, accessed May 14, 2025, https://baes.uc.pt/retrieve/277682/nevesj_dissertacao_single.pdf