



## Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document Group:** 30-7061-2  
**Issue Date:** 11/10/25

**Version Number:** 6.06  
**Supersedes Date:** 08/06/24

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ HoldFast 70 Adhesive (Bulk)

#### Product Identification Numbers

ID Number                      UPC  
62-4847-7535-8

ID Number                      UPC  
62-4847-8530-8

62-4847-9530-7

62-4847-9531-5

62-4850-9530-1

7010366348, 7010310268, 7010366347, 7100253139

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive, Industrial use

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Industrial Adhesives and Tapes Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 2.

Skin Corrosion/Irritation: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

##### Signal word

Danger

**Symbols**

Flame | Exclamation mark |

**Pictograms****Hazard Statements**

Highly flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

**Precautionary statements****Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating and lighting equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid breathing vapor or spray.

Wash exposed skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, eye protection, and face protection.

**Response:**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If skin irritation occurs: Get medical advice.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:**

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**SECTION 3: Composition/information on ingredients**

| Ingredient                             | C.A.S. No.    | % by Wt                |
|----------------------------------------|---------------|------------------------|
| Cyclohexane                            | 110-82-7      | 10 - 30 Trade Secret * |
| Hydrotreated Light Naphtha (Petroleum) | 64742-49-0    | 10 - 30 Trade Secret * |
| Pentane                                | 109-66-0      | 10 - 30 Trade Secret * |
| Non-Volatile Components                | Trade Secret* | 20 - 30                |
| Acetone                                | 67-64-1       | 5 - 10 Trade Secret *  |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Aldehydes

Hydrocarbons

Methane

Carbon monoxide

Carbon dioxide

Ketones

Toxic Vapor, Gas, Particulate

#### Condition

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient           | C.A.S. No. | Agency | Limit type               | Additional Comments |
|----------------------|------------|--------|--------------------------|---------------------|
| Pentane              | 109-66-0   | OSHA   | TWA:2950 mg/m3(1000 ppm) |                     |
| Pentane, all isomers | 109-66-0   | ACGIH  | TWA:1000 ppm             |                     |
| Cyclohexane          | 110-82-7   | ACGIH  | TWA:100 ppm              |                     |

|                                    |            |       |                          |                                                              |
|------------------------------------|------------|-------|--------------------------|--------------------------------------------------------------|
| Cyclohexane                        | 110-82-7   | OSHA  | TWA:1050 mg/m3(300 ppm)  |                                                              |
| Hexane (Commercial, <54% n-Hexane) | 64742-49-0 | ACGIH | TWA:100 ppm              | A3: Confirmed animal carcin., Danger of cutaneous absorption |
| NAPHTHA                            | 64742-49-0 | OSHA  | TWA:400 mg/m3(100 ppm)   |                                                              |
| Acetone                            | 67-64-1    | ACGIH | TWA:250 ppm;STEL:500 ppm | A4: Not class. as human carcin                               |
| Acetone                            | 67-64-1    | OSHA  | TWA:2400 mg/m3(1000 ppm) |                                                              |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Nitrile Rubber, Polymer laminate

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

|                                                   |                                                       |
|---------------------------------------------------|-------------------------------------------------------|
| Physical state                                    | Liquid                                                |
| Color                                             | Clear Yellow                                          |
| Odor                                              | Mild Solvent                                          |
| Odor threshold                                    | No Data Available                                     |
| pH                                                | No Data Available                                     |
| Melting point/Freezing point                      | No Data Available                                     |
| Boiling point/Initial boiling point/Boiling range | <=56.1 °C                                             |
| Flash Point                                       | <=-40 °C [Test Method: Closed Cup]                    |
| Evaporation rate                                  | No Data Available                                     |
| Flammability                                      | Flammable Liquid: Category 2.                         |
| Flammable Limits(LEL)                             | 1.5 % volume                                          |
| Flammable Limits(UEL)                             | 27 % volume                                           |
| Vapor Pressure                                    | <=20,531.6 Pa                                         |
| Relative Vapor Density                            | > 1 [Ref Std: AIR=1]                                  |
| Density                                           | 0.754 g/ml                                            |
| Relative Density                                  | <=0.754 [Ref Std: WATER=1]                            |
| Water solubility                                  | Nil                                                   |
| Solubility- non-water                             | No Data Available                                     |
| Partition coefficient: n-octanol/ water           | No Data Available                                     |
| Autoignition temperature                          | No Data Available                                     |
| Decomposition temperature                         | No Data Available                                     |
| Kinematic Viscosity                               | 265 mm <sup>2</sup> /sec                              |
| Volatile Organic Compounds                        | No Data Available                                     |
| Percent volatile                                  | No Data Available                                     |
| VOC Less H <sub>2</sub> O & Exempt Solvents       | <=554 g/l [Test Method: calculated SCAQMD rule 443.1] |
| Solids Content                                    | 20 - 30 % weight                                      |

|                          |                |
|--------------------------|----------------|
| Particle Characteristics | Not Applicable |
|--------------------------|----------------|

**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Sparks and/or flames

**10.5. Incompatible materials**

Strong oxidizing agents

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

##### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

##### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

##### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

| Name            | Route                      | Species | Value                                          |
|-----------------|----------------------------|---------|------------------------------------------------|
| Overall product | Dermal                     |         | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr)     |         | No data available; calculated ATE >50 mg/l     |
| Overall product | Ingestion                  |         | No data available; calculated ATE >5,000 mg/kg |
| Pentane         | Dermal                     | Rabbit  | LD50 3,000 mg/kg                               |
| Pentane         | Inhalation-Vapor (4 hours) | Rat     | LC50 > 18 mg/l                                 |
| Pentane         | Ingestion                  | Rat     | LD50 > 2,000 mg/kg                             |
| Cyclohexane     | Dermal                     | Rat     | LD50 > 2,000 mg/kg                             |
| Cyclohexane     | Inhalation-Vapor (4        | Rat     | LC50 > 32.9 mg/l                               |

|                                        | hours)                     |               |                     |
|----------------------------------------|----------------------------|---------------|---------------------|
| Cyclohexane                            | Ingestion                  | Rat           | LD50 6,200 mg/kg    |
| Hydrotreated Light Naphtha (Petroleum) | Dermal                     | Rabbit        | LD50 > 3,160 mg/kg  |
| Hydrotreated Light Naphtha (Petroleum) | Inhalation-Vapor (4 hours) | Rat           | LC50 > 14.7 mg/l    |
| Hydrotreated Light Naphtha (Petroleum) | Ingestion                  | Rat           | LD50 > 5,000 mg/kg  |
| Acetone                                | Dermal                     | Rabbit        | LD50 > 15,688 mg/kg |
| Acetone                                | Inhalation-Vapor (4 hours) | Rat           | LC50 76 mg/l        |
| Acetone                                | Ingestion                  | Rat           | LD50 5,800 mg/kg    |
| Non-Volatile Components                | Dermal                     | Not available | LD50 > 2,000 mg/kg  |
| Non-Volatile Components                | Ingestion                  | Not available | LD50 > 2,000 mg/kg  |

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

| Name                                   | Species                | Value                     |
|----------------------------------------|------------------------|---------------------------|
| Pentane                                | Rabbit                 | Minimal irritation        |
| Cyclohexane                            | Rabbit                 | Mild irritant             |
| Hydrotreated Light Naphtha (Petroleum) | Rabbit                 | Irritant                  |
| Acetone                                | Mouse                  | Minimal irritation        |
| Non-Volatile Components                | Professional judgement | No significant irritation |

### Serious Eye Damage/Irritation

| Name                                   | Species                | Value                     |
|----------------------------------------|------------------------|---------------------------|
| Pentane                                | Rabbit                 | Mild irritant             |
| Cyclohexane                            | Rabbit                 | Mild irritant             |
| Hydrotreated Light Naphtha (Petroleum) | Rabbit                 | Mild irritant             |
| Acetone                                | Rabbit                 | Severe irritant           |
| Non-Volatile Components                | Professional judgement | No significant irritation |

### Skin Sensitization

| Name                                   | Species    | Value          |
|----------------------------------------|------------|----------------|
| Pentane                                | Guinea pig | Not classified |
| Hydrotreated Light Naphtha (Petroleum) | Guinea pig | Not classified |
| Non-Volatile Components                |            | Not classified |

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

| Name        | Route    | Value                                                                        |
|-------------|----------|------------------------------------------------------------------------------|
| Pentane     | In vivo  | Not mutagenic                                                                |
| Pentane     | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Cyclohexane | In Vitro | Not mutagenic                                                                |
| Cyclohexane | In vivo  | Some positive data exist, but the data are not sufficient for classification |



|                                        |          |                                                                              |
|----------------------------------------|----------|------------------------------------------------------------------------------|
| Hydrotreated Light Naphtha (Petroleum) | In Vitro | Not mutagenic                                                                |
| Acetone                                | In vivo  | Not mutagenic                                                                |
| Acetone                                | In Vitro | Some positive data exist, but the data are not sufficient for classification |

### Carcinogenicity

| Name                                   | Route         | Species                 | Value                                                                        |
|----------------------------------------|---------------|-------------------------|------------------------------------------------------------------------------|
| Hydrotreated Light Naphtha (Petroleum) | Inhalation    | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Acetone                                | Not Specified | Multiple animal species | Not carcinogenic                                                             |

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

| Name        | Route      | Value                                  | Species | Test Result           | Exposure Duration    |
|-------------|------------|----------------------------------------|---------|-----------------------|----------------------|
| Pentane     | Ingestion  | Not classified for development         | Rat     | NOAEL 1,000 mg/kg/day | during organogenesis |
| Pentane     | Inhalation | Not classified for development         | Rat     | NOAEL 30 mg/l         | during organogenesis |
| Cyclohexane | Inhalation | Not classified for female reproduction | Rat     | NOAEL 24 mg/l         | 2 generation         |
| Cyclohexane | Inhalation | Not classified for male reproduction   | Rat     | NOAEL 24 mg/l         | 2 generation         |
| Cyclohexane | Inhalation | Not classified for development         | Rat     | NOAEL 6.9 mg/l        | 2 generation         |
| Acetone     | Ingestion  | Not classified for male reproduction   | Rat     | NOAEL 1,700 mg/kg/day | 13 weeks             |
| Acetone     | Inhalation | Not classified for development         | Rat     | NOAEL 5.2 mg/l        | during organogenesis |

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

| Name                                   | Route      | Target Organ(s)                   | Value                                                                        | Species                 | Test Result         | Exposure Duration |
|----------------------------------------|------------|-----------------------------------|------------------------------------------------------------------------------|-------------------------|---------------------|-------------------|
| Pentane                                | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Multiple animal species | NOAEL Not available | not available     |
| Pentane                                | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Not available           | NOAEL Not available | not available     |
| Pentane                                | Inhalation | cardiac sensitization             | Not classified                                                               | Dog                     | NOAEL Not available | not available     |
| Pentane                                | Ingestion  | central nervous system depression | May cause drowsiness or dizziness                                            | Professional judgement  | NOAEL Not available | not available     |
| Cyclohexane                            | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human and animal        | NOAEL Not available |                   |
| Cyclohexane                            | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human and animal        | NOAEL Not available |                   |
| Cyclohexane                            | Ingestion  | central nervous system depression | May cause drowsiness or dizziness                                            | Professional judgement  | NOAEL Not available |                   |
| Hydrotreated Light Naphtha (Petroleum) | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human and               | NOAEL Not available |                   |

|                                        |            |                                   |                                                                              |                        |                     |                        |
|----------------------------------------|------------|-----------------------------------|------------------------------------------------------------------------------|------------------------|---------------------|------------------------|
|                                        |            |                                   |                                                                              | animal                 |                     |                        |
| Hydrotreated Light Naphtha (Petroleum) | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification |                        | NOAEL Not available |                        |
| Hydrotreated Light Naphtha (Petroleum) | Ingestion  | central nervous system depression | May cause drowsiness or dizziness                                            | Professional judgement | NOAEL Not available |                        |
| Acetone                                | Inhalation | central nervous system depression | May cause drowsiness or dizziness                                            | Human                  | NOAEL Not available |                        |
| Acetone                                | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human                  | NOAEL Not available |                        |
| Acetone                                | Inhalation | immune system                     | Not classified                                                               | Human                  | NOAEL 1.19 mg/l     | 6 hours                |
| Acetone                                | Inhalation | liver                             | Not classified                                                               | Guinea pig             | NOAEL Not available |                        |
| Acetone                                | Ingestion  | central nervous system depression | May cause drowsiness or dizziness                                            | Human                  | NOAEL Not available | poisoning and/or abuse |

### Specific Target Organ Toxicity - repeated exposure

| Name        | Route      | Target Organ(s)                 | Value          | Species    | Test Result           | Exposure Duration     |
|-------------|------------|---------------------------------|----------------|------------|-----------------------|-----------------------|
| Pentane     | Inhalation | peripheral nervous system       | Not classified | Human      | NOAEL Not available   | occupational exposure |
| Pentane     | Inhalation | heart                           | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | skin                            | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | endocrine system                | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | gastrointestinal tract          | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | bone, teeth, nails, and/or hair | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | hematopoietic system            | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | liver                           | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | immune system                   | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | muscles                         | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | nervous system                  | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | eyes                            | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | kidney and/or bladder           | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Inhalation | respiratory system              | Not classified | Rat        | NOAEL 20 mg/l         | 13 weeks              |
| Pentane     | Ingestion  | kidney and/or bladder           | Not classified | Rat        | NOAEL 2,000 mg/kg/day | 28 days               |
| Cyclohexane | Inhalation | liver                           | Not classified | Rat        | NOAEL 24 mg/l         | 90 days               |
| Cyclohexane | Inhalation | auditory system                 | Not classified | Rat        | NOAEL 1.7 mg/l        | 90 days               |
| Cyclohexane | Inhalation | kidney and/or bladder           | Not classified | Rabbit     | NOAEL 2.7 mg/l        | 10 weeks              |
| Cyclohexane | Inhalation | hematopoietic system            | Not classified | Mouse      | NOAEL 24 mg/l         | 14 weeks              |
| Cyclohexane | Inhalation | peripheral nervous system       | Not classified | Rat        | NOAEL 8.6 mg/l        | 30 weeks              |
| Acetone     | Dermal     | eyes                            | Not classified | Guinea pig | NOAEL Not available   | 3 weeks               |

|         |            |                                 |                |            |                        |               |
|---------|------------|---------------------------------|----------------|------------|------------------------|---------------|
| Acetone | Inhalation | hematopoietic system            | Not classified | Human      | NOAEL 3 mg/l           | 6 weeks       |
| Acetone | Inhalation | immune system                   | Not classified | Human      | NOAEL 1.19 mg/l        | 6 days        |
| Acetone | Inhalation | kidney and/or bladder           | Not classified | Guinea pig | NOAEL 119 mg/l         | not available |
| Acetone | Inhalation | heart                           | Not classified | Rat        | NOAEL 45 mg/l          | 8 weeks       |
| Acetone | Inhalation | liver                           | Not classified | Rat        | NOAEL 45 mg/l          | 8 weeks       |
| Acetone | Ingestion  | kidney and/or bladder           | Not classified | Rat        | NOAEL 900 mg/kg/day    | 13 weeks      |
| Acetone | Ingestion  | heart                           | Not classified | Rat        | NOAEL 2,500 mg/kg/day  | 13 weeks      |
| Acetone | Ingestion  | hematopoietic system            | Not classified | Rat        | NOAEL 200 mg/kg/day    | 13 weeks      |
| Acetone | Ingestion  | liver                           | Not classified | Mouse      | NOAEL 3,896 mg/kg/day  | 14 days       |
| Acetone | Ingestion  | eyes                            | Not classified | Rat        | NOAEL 3,400 mg/kg/day  | 13 weeks      |
| Acetone | Ingestion  | respiratory system              | Not classified | Rat        | NOAEL 2,500 mg/kg/day  | 13 weeks      |
| Acetone | Ingestion  | muscles                         | Not classified | Rat        | NOAEL 2,500 mg/kg      | 13 weeks      |
| Acetone | Ingestion  | skin                            | Not classified | Mouse      | NOAEL 11,298 mg/kg/day | 13 weeks      |
| Acetone | Ingestion  | bone, teeth, nails, and/or hair | Not classified | Mouse      | NOAEL 11,298 mg/kg/day | 13 weeks      |

**Aspiration Hazard**

| Name                                   | Value             |
|----------------------------------------|-------------------|
| Pentane                                | Aspiration hazard |
| Cyclohexane                            | Aspiration hazard |
| Hydrotreated Light Naphtha (Petroleum) | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal

facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable), D018 (Benzene)

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

##### Health Hazards

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

##### Ingredient

Cyclohexane

##### C.A.S. No

110-82-7

##### % by Wt

Trade Secret 10 - 30

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

#### NFPA Hazard Classification

**Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 30-7061-2 | <b>Version Number:</b>  | 6.06     |
| <b>Issue Date:</b>     | 11/10/25  | <b>Supersedes Date:</b> | 08/06/24 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**