



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

---

**SECTION 1. IDENTIFICATION**

Product name : Valvoline™ SAE 80W-90 High Performance Gear Oil

Product code : VV831

**Manufacturer or supplier's details**

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way  
Lexington, KY 40509  
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Skin sensitisation : Category 1

**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**  
P261 Avoid breathing mist or vapours.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.  
**Response:**  
P302 + P352 IF ON SKIN: Wash with plenty of water.



# SAFETY DATA SHEET

Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

| Chemical name                                                                 | CAS-No.    | Concentration (% w/w)                  |
|-------------------------------------------------------------------------------|------------|----------------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | 64742-54-7 | Trade secret ( $\geq 60$ - $\leq 80$ ) |
| Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified     | 64742-70-7 | Trade secret ( $\geq 10$ - $\leq 30$ ) |
| Polysulfides, di-tert-Bu                                                      | 68937-96-2 | Trade secret ( $\geq 1$ - $\leq 5$ )   |

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

Most important symptoms : No symptoms known or expected.



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

and effects, both acute and  
delayed

Notes to physician

May cause an allergic skin reaction.

: No hazards which require special first aid measures.  
Treat symptomatically.

---

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.



# SAFETY DATA SHEET

Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

| Components                                                                    | CAS-No.    | Value type<br>(Form of exposure)   | Control parameters /<br>Permissible concentration | Basis    |
|-------------------------------------------------------------------------------|------------|------------------------------------|---------------------------------------------------|----------|
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | 64742-54-7 | TWA (Mist)                         | 5 mg/m3                                           | OSHA Z-1 |
|                                                                               |            | TWA (Inhalable particulate matter) | 5 mg/m3                                           | ACGIH    |
| Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified     | 64742-70-7 | TWA (Mist)                         | 5 mg/m3                                           | OSHA Z-1 |

### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection : Impervious clothing



## SAFETY DATA SHEET

Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

Hygiene measures : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
: Wash hands before breaks and at the end of workday.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                                  |                                                                 |
|--------------------------------------------------|-----------------------------------------------------------------|
| Appearance                                       | : liquid                                                        |
| Colour                                           | : amber                                                         |
| Odour                                            | : No data available                                             |
| Odour Threshold                                  | : No data available                                             |
| pH                                               | : No data available                                             |
| Melting point/freezing point                     | : No data available                                             |
| Boiling point/boiling range                      | : > 424.9 °F / 218.3 °C<br>(1013.333 hPa)                       |
| Flash point                                      | : 394 - 480 °F / 201 - 249 °C<br><br>Method: Cleveland open cup |
| Evaporation rate                                 | : > 1<br>Ethyl Ether                                            |
| Flammability (solid, gas)                        | : No data available                                             |
| Self-ignition                                    | : No data available                                             |
| Upper explosion limit / Upper flammability limit | : No data available                                             |
| Lower explosion limit / Lower flammability limit | : No data available                                             |
| Vapour pressure                                  | : < 0.1000000 mmHg                                              |
| Relative vapour density                          | : > 1<br>AIR=1                                                  |
| Relative density                                 | : 0.89 (60.00 °F / 15.56 °C)                                    |
| Density                                          | : 0.8916 g/cm3 (60.01 °F / 15.56 °C)                            |
| Solubility(ies)<br>Water solubility              | : No data available                                             |



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

|                                        |   |                                         |
|----------------------------------------|---|-----------------------------------------|
| Solubility in other solvents           | : | No data available                       |
| Partition coefficient: n-octanol/water | : | No data available                       |
| Decomposition temperature              | : | No data available                       |
| Viscosity                              |   |                                         |
| Viscosity, dynamic                     | : | No data available                       |
| Viscosity, kinematic                   | : | 146 mm <sup>2</sup> /s (104 °F / 40 °C) |
| Oxidizing properties                   | : | No data available                       |

---

#### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |                                                     |
|------------------------------------|---|-----------------------------------------------------|
| Reactivity                         | : | No decomposition if stored and applied as directed. |
| Chemical stability                 | : | No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : | No decomposition if stored and applied as directed. |
| Conditions to avoid                | : | excessive heat                                      |
| Incompatible materials             | : | Strong oxidizing agents                             |
| Hazardous decomposition products   | : | No hazardous decomposition products are known.      |

---

#### SECTION 11. TOXICOLOGICAL INFORMATION

##### Acute toxicity

Not classified due to lack of data.

##### Components:

##### **Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

|                       |   |                         |
|-----------------------|---|-------------------------|
| Acute oral toxicity   | : | LD50 (Rat): > 15 g/kg   |
| Acute dermal toxicity | : | LD50 (Rabbit): > 5 g/kg |

##### **Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified:**

|                       |   |                                                                                                                                                                                      |
|-----------------------|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity   | : | LD50 (Rat): > 2,000 mg/kg<br>Assessment: The substance or mixture has no acute oral toxicity<br>Remarks: The toxicological data has been taken from products of similar composition. |
| Acute dermal toxicity | : | LD50 (Rabbit): > 2,000 mg/kg<br>Assessment: The substance or mixture has no acute dermal toxicity                                                                                    |



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

Remarks: The toxicological data has been taken from products of similar composition.

**Polysulfides, di-tert-Bu:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: No mortality observed at this dose.

**Skin corrosion/irritation**

Not classified due to lack of data.

**Product:**

Remarks : May cause skin irritation and/or dermatitis.

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified:**

Assessment : Slight, transient irritation  
Result : Slight, transient irritation

**Polysulfides, di-tert-Bu:**

Result : Mild skin irritation

**Serious eye damage/eye irritation**

Not classified due to lack of data.

**Product:**

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Result : No eye irritation  
Assessment : No eye irritation

**Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified:**

Result : Slight, transient irritation  
Assessment : Slight, transient irritation

**Polysulfides, di-tert-Bu:**

Result : Slight, transient irritation

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified due to lack of data.

**Product:**

Remarks : Causes sensitisation.

**Components:**

**Polysulfides, di-tert-Bu:**

Test Type : Maximisation Test  
Species : Guinea pig  
Assessment : The product is a skin sensitiser, sub-category 1B.  
Method : OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified due to lack of data.

**Components:**

**Polysulfides, di-tert-Bu:**

Genotoxicity in vitro : Test Type: in vitro assay  
Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test  
Species: Mouse  
Cell type: Bone marrow  
Method: OECD Test Guideline 474  
Result: negative





**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

**Carcinogenicity**

Not classified due to lack of data.

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation  
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified due to lack of data.

**STOT - single exposure**

Not classified due to lack of data.

**STOT - repeated exposure**

Not classified due to lack of data.

**Aspiration toxicity**

Not classified due to lack of data.

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks : No data available



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
plants Exposure time: 72 h

Toxicity to fish (Chronic : NOEC (Fish): 10 mg/l  
toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l  
aquatic invertebrates  
(Chronic toxicity)

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Polysulfides, di-tert-Bu:**

**Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

**Persistence and degradability**

**Components:**

**Polysulfides, di-tert-Bu:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 13 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**Bioaccumulative potential**

**Components:**

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:**

Partition coefficient: n- : log Pow: Expected > 7  
octanol/water

**Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — unspecified:**

Partition coefficient: n- : log Pow: > 3.5  
octanol/water

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological : An environmental hazard cannot be excluded in the event of  
information : unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

---

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water  
courses or the soil.  
Do not contaminate ponds, waterways or ditches with



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

Contaminated packaging : chemical or used container.  
Send to a licensed waste management company.  
Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

### SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

**Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

**US State Regulations**

**Massachusetts Right To Know**

Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — 64742-70-7  
unspecified

**Pennsylvania Right To Know**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil 64742-54-7  
— unspecified  
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil — 64742-70-7  
unspecified

**Maine Chemicals of High Concern**

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- 72623-86-0  
based; Baseoil — unspecified

**Vermont Chemicals of High Concern**

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- 72623-86-0  
based; Baseoil — unspecified

**Washington Chemicals of High Concern**

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- 72623-86-0  
based; Baseoil — unspecified

**California Permissible Exposure Limits for Chemical Contaminants**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil 64742-54-7  
— unspecified

**The components of this product are reported in the following inventories:**

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

|       |                                                          |
|-------|----------------------------------------------------------|
| AIIC  | : On the inventory, or in compliance with the inventory  |
| DSL   | : All components of this product are on the Canadian DSL |
| ENCS  | : On the inventory, or in compliance with the inventory  |
| KECI  | : On the inventory, or in compliance with the inventory  |
| PICCS | : On the inventory, or in compliance with the inventory  |
| IECSC | : On the inventory, or in compliance with the inventory  |
| NZIoC | : Not in compliance with the inventory                   |

**TSCA list**

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**Inventories**

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

---

**SECTION 16. OTHER INFORMATION**

**Further information**



# SAFETY DATA SHEET


Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

## NFPA 704:



## HMIS® IV:

|                 |   |   |
|-----------------|---|---|
| HEALTH          | / | 2 |
| FLAMMABILITY    |   | 1 |
| PHYSICAL HAZARD |   | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

|                |   |                                                                                     |
|----------------|---|-------------------------------------------------------------------------------------|
| ACGIH          | : | USA. ACGIH Threshold Limit Values (TLV)                                             |
| OSHA Z-1       | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1<br>Limits for Air Contaminants |
| ACGIH / TWA    | : | 8-hour, time-weighted average                                                       |
| OSHA Z-1 / TWA | : | 8-hour time weighted average                                                        |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration;



**SAFETY DATA SHEET**  
Valvoline™ SAE 80W-90 High Performance  
Gear Oil

Version: 3.3

Revision Date: 02/13/2025

Print Date:  
01/23/2026

NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/13/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : R0091437