

# Idris

2014 г.

# Idris

- ▶ Haskell-подобный,
- ▶ с зависимыми типами,
- ▶ строгий по-умолчанию,
- ▶ с опциональной проверкой на тотальность,
- ▶ с тактиками,
- ▶ ...

# Haskell-подобный

```
data MyList a = Nil | (::) a (MyList a)
```

```
(++) : MyList a → MyList a → MyList a
```

```
[] ++ ys = ys
```

```
(x :: xs) ++ ys = x :: (xs ++ ys)
```

```
instance Functor MyList where
```

```
  map f Nil = Nil
```

```
  map f (x :: xs) = f x :: map f xs
```

# Haskell-подобный

**instance** *Applicative* *MyList* **where**

*pure* *x* = [*x*]

[] <\$> \_ = []

(*f* :: *fs*) <\$> *xs* = *map* *f* *xs* ++ (*fs* <\$> *xs*)

**instance** *Monad* *MyList* **where**

[] »= \_ = []

(*x* :: *xs*) »= *f* = *f* *x* ++ (*xs* »= *f*)

*test* : *MyList* *Int*

*test* = **do**

*f* ← [*id*, (\*2)]

*x* ← [3, 4]

*return* \$ *f* *x*

## С зависимыми типами

**data** *MyVect* : *Nat*  $\rightarrow$  (*a* : *Type*)  $\rightarrow$  *Type* **where**

*Nil* : *MyVect* 0 *a*

(::) : *a*  $\rightarrow$  *MyVect* *n* *a*  $\rightarrow$  *MyVect* (*S* *n*) *a*

(++) : *MyVect* *n* *a*  $\rightarrow$  *MyVect* *m* *a*  $\rightarrow$  *MyVect* (*n* + *m*) *a*

[] ++ *ys* = *ys*

(*x* :: *xs*) ++ *ys* = *x* :: (*xs* ++ *ys*)

**infix** 9 !!

(!!) : *MyVect* *n* *a*  $\rightarrow$  *Fin* *n*  $\rightarrow$  *a*

(*x* :: *xs*) !! *fZ* = *x*

(*x* :: *xs*) !! (*fS* *y*) = *xs* !! *y*

## Строгий по-умолчанию

*broken* : *Int* → *Int*

*broken* 0 = 1

*broken* *n* = *n* \* *broken* (*n* − 1)

*ifThenElse* : *Bool* → *a* → *a* → *a*

*ifThenElse* *True* *t* *\_* = *t*

*ifThenElse* *False* *\_* *f* = *f*

> *ifThenElse* *True* 0 (*broken* (−1))

Интерпретатор:

0 : *Int*

Скомпилированный код(с точностью до оптимизаций):

segmentation fault ./a.out

## С опциональной проверкой на тотальность

**total** *myHead* : *List a*  $\rightarrow$  *a*

*myHead* (*x* :: *xs*) = *x*

> Main.myHead is not total as there are missing cases

**%default** *total*

*go* : *Int*

*go* = *go*

> Main.go is possibly not total due to recursive path Main.go

## С тактиками

```
lemma_applicative_identity : (vs : MyList a) → (pure id <$> vs = vs)
lemma_applicative_identity [] = refl
lemma_applicative_identity (v :: vs) =
  let rec = lemma_applicative_identity vs
  in ?lemma_applicative_identity_rhs

lemma_applicative_identity_rhs = proof
  intro a, x, xs, rec
  rewrite rec
  trivial
```



- Effects вместо трансформеров

$$f : \{ [STDIO, STATE \text{ Int}] \} \text{ Eff } ()$$

- Именованные инстансы

```
instance [myord] Ord Int where
```

...

```
sort @{myord} [2, 1, 3]
```

- Idiom brackets(для аппликативных функторов)

$$f : \text{Maybe Int} \rightarrow \text{Maybe Int} \rightarrow \text{Maybe Int}$$

$$f \times y = [|x + y|]$$

- ...  
▶ !-нотация(для монад)

$$f : \text{Maybe } \text{Bool} \rightarrow \text{Maybe } a \rightarrow \text{Maybe } a \rightarrow \text{Maybe } a$$
$$f \times t \ f = \text{if } !x \ \text{then } t \ \text{else } f$$

- ▶ Опциональная ленивость

$$\text{data } \text{Lazy} : \text{Type} \rightarrow \text{Type} \text{ where}$$
$$\text{Delay} : a \rightarrow \text{Lazy } a$$
$$\text{Force} : \text{Lazy } a \rightarrow a$$

- ▶ Изменяемый синтаксис

$$\text{syntax if } [test] \text{ then } [t] \text{ else } [e] = \text{boolElim test } (\text{Delay } t) (\text{Delay } e)$$

...

- ▶ Минимальный вывод типов в **where**
- ▶ Гетерогенное равенство

**data**  $(=) : a \rightarrow b \rightarrow \text{Type}$  **where**  
*refl* :  $x = x$

- ▶ FFI with C TODO

- ▶ **public**, **abstract**, **private** спецификаторы видимости

```
%access public
abstract f : Int → Int
```

- ▶ **records**

```
record R : Type where
  MkR : (f1 : Int) → (f2 : String) → R
```

- ▶ Levels are implicit TODO
- ▶ auto implicit args TODO

# Type providers

```
%language TypeProviders
```

```
strToType : String → Type
```

```
strToType "Int" = Int
```

```
strToType _ = Nat
```

```
fromFile : String → IO (Provider Type)
```

```
fromFile fname = Provide (strToType (trim !(readFile fname)))
```

```
%provide (T : Type) with fromFile "config.h"
```

```
f : T
```

```
f = 42
```

# TODOs

- ▶ Proof automation
- ▶ More better termination checker
- ▶ More better editor support (goto definition, autocomplete, ...)
- ▶ More bindings (incl. low-level C bindings)
- ▶ More backends (e.g. GHC)
- ▶ Bugfixing