

# 1 Exporting from Agda to Haskell

## 1.1 Goal

As of Agda 2.3.2.2 there is a way to call Haskell code from Agda but no way to call Agda code from Haskell: i.e. to compile Agda code into a library usable from Haskell.

The feature is desirable because one can create a formally verified library in Agda, create a simple API around it and then use it in Haskell for real world applications.

## 1.2 Current state of things in Agda

### 1.2.1 As of Agda 2.3.2.2

There is a compiler from Agda to Haskell called MAlonzo<sup>[1]</sup>(which is a rewrite of Alonzo<sup>[2]</sup> compiler) - it translates Agda code into a Haskell code so that observable behaviour of running an Agda interpreter and generated Haskell code is the same.

MAlonzo focuses on generating executables and therefore it has some undesirable characteristics:

- Names for functions and datatypes are of the form: a letter + a magic number
- Type signatures for functions are not written
- Generated datatypes omit all type parameters

On the other hand, apart from datatype parameters nothing is omitted: even arguments that represent proofs are carried (but are replaced with `()` type)

Still, at this state using generated code from Haskell is not pleasant.

### 1.2.2 Since Agda 2.3.4

New `{-# COMPILED_EXPORT AgdaName HaskellName #-}` pragma is added. It will force the MAlonzo compiler to use *HaskellName* instead of a generated name for *AgdaName* function and will also generate an explicit type signature for *HaskellName* according to the rules:

$$\begin{aligned} T\llbracket \text{Set } A \rrbracket &= \text{Unit} \\ T\llbracket x \text{ As} \rrbracket &= x \ T\llbracket \text{As} \rrbracket \\ T\llbracket (x : A) \rightarrow B \rrbracket &= \forall x. T\llbracket A \rrbracket \rightarrow T\llbracket B \rrbracket, \quad x \in \text{freevars}(B) \\ T\llbracket (x : A) \rightarrow B \rrbracket &= T\llbracket A \rrbracket \rightarrow T\llbracket B \rrbracket, \quad \text{otherwise} \\ T\llbracket k \text{ As} \rrbracket &= T \ T\llbracket \text{As} \rrbracket, \quad \text{COMPILED\_TYPE } k \ T \\ T\llbracket k \text{ As} \rrbracket &= \text{Unit}, \quad \text{COMPILED } k \ E \end{aligned}$$

Also MAlonzo gained the ability to generate a Haskell library - not only an executable.

While improving the experience it still lacks better datatype generation.

## 1.3 The scope of this work

This work was developed on Agda 2.3.2.2 and features of 2.3.4 were not available.

The `{-# EXPORT AgdaName HaskellName #-}` pragma is introduced which will create a wrapper named *HaskellName* for MAlonzo generated code for *AgdaName* function or datatype.

The primary motivation is exposing functions with such types that using them in any legitimate way from Haskell (i.e. no `unsafeCoerce` and such) will not break any internal invariant in Agda code. It automatically means that only functions with types that can be expressed in Haskell can be exposed - otherwise we lose information and invariants as a consequence.

Also for convenience Church polymorphism is converted to Curry polymorphism: instead of (as can be seen in Agda 2.3.4)

$$TT\llbracket (A : \text{Set}) \rightarrow B \rrbracket = \forall a. () \rightarrow TT\llbracket B \rrbracket$$

this holds

$$TT\llbracket (A : \text{Set}) \rightarrow B \rrbracket = \forall a. TT\llbracket B \rrbracket.$$

Overview of features:

1. Functions with types expressed in Haskell can be exported and will undergo Church to Curry polymorphism transformation.

2. Datatypes can be exported as abstract datatypes when their type parameters are of types equivalent to kinds in Haskell (a combination of *Set<sub>0</sub>* and arrows).
3. Constructors of this datatypes can be exported as Haskell functions (i.e. loosing the ability to pattern match on them) via feature 1.
4. Some Agda primitives: **INTEGER**, **FLOAT**, **CHAR**, **STRING**, **IO** will be exported as *Int*, *Float*, *Char*, *String*, *IO* respectively.
5. **COMPILED\_TYPES** will be exported accordingly.

Section 2 gives formal definition of wrappers generated, section 3 gives proofs that exposed interface will not break the system.

## 2 Wrapper generation

### 2.1 Kinds

$$KT\llbracket Kind \rrbracket = HaskellKind$$

$$\begin{aligned} KT\llbracket Set_0 \rrbracket &= * \\ KT\llbracket Kind_1 \rightarrow Kind_2 \rrbracket &= KT\llbracket Kind_1 \rrbracket \rightarrow KT\llbracket Kind_2 \rrbracket \end{aligned}$$

### 2.2 Type declarations

*DTMA* gives MAlonzo generated type name.

*DT*, *DTD* are defined when `{-# EXPORT AgdaTypeName HaskellTypeName #-}` is specified.

$$\begin{aligned} DTMA\llbracket AgdaTypeName \rrbracket &= HaskellTypeName \\ DT\llbracket AgdaTypeName \rrbracket &= HaskellTypeName \\ DTD\llbracket AgdaTypeName \rrbracket &\doteq HaskellTypeDeclaration \end{aligned}$$

Considering declaration:

**data** *AgdaDataType* (*A*<sub>1</sub> : *Kind*<sub>1</sub>) ··· (*A*<sub>*m*</sub> : *Kind*<sub>*m*</sub>) : *Kind*<sub>*m*+1</sub> → ··· → *Kind*<sub>*n*</sub> → *Set* **where** ...

$$\begin{aligned} DTD\llbracket AgdaDataType \rrbracket &\doteq \\ \mathbf{newtype} \ DT\llbracket AgdaDataType \rrbracket \ (a_0 :: KT\llbracket Kind_1 \rrbracket) \cdots (a_n :: KT\llbracket Kind_n \rrbracket) \\ &= DT\llbracket AgdaDataType \rrbracket \ (\forall b_1 \cdots b_k. \ DTMA\llbracket AgdaDataType \rrbracket \ b_1 \cdots b_k) \end{aligned}$$

*k* is an arity of type constructor generated by MAlonzo.

It also works for **records**.

### 2.3 Types

First about primitives. Only those that are used for postulates are allowed. MAlonzo gives the following *PTMA* transformation:

$$\begin{aligned} PTMA\llbracket \mathbf{INTEGER} \rrbracket &= Int \\ PTMA\llbracket \mathbf{FLOAT} \rrbracket &= Float \\ PTMA\llbracket \mathbf{CHAR} \rrbracket &= Char \\ PTMA\llbracket \mathbf{STRING} \rrbracket &= String \\ PTMA\llbracket \mathbf{IO} \rrbracket &= IO \end{aligned}$$

$$\begin{aligned} TT\llbracket AgdaType \rrbracket (Context) &= HaskellType \\ Context &= \{ AgdaTypeVarName \mapsto HaskellTypeVarName \} \end{aligned}$$

$$\begin{aligned}
TT[A \text{ args } \dots](\Gamma) &= a \text{ } TT[\text{args } \dots](\Gamma), \quad (A \mapsto a) \in \Gamma \\
TT[CT \text{ args } \dots](\Gamma) &= CT \text{ } TT[\text{args } \dots](\Gamma), \quad CT \text{ is a } \text{COMPILED\_TYPE} \\
TT[PT \text{ args } \dots](\Gamma) &= PTMA[PT] \text{ } TT[\text{args } \dots](\Gamma) \\
TT[ET \text{ args } \dots](\Gamma) &= DT[ET] \text{ } TT[\text{args } \dots](\Gamma) \\
TT[(A : Kind) \rightarrow T](\Gamma) &= \forall(a :: KT[Kind]). TT[T](\Gamma \cup \{A \mapsto a\}) \\
TT[(x : T_1) \rightarrow T_2](\Gamma) &= TT[T_1](\Gamma) \rightarrow TT[T_2](\Gamma), \quad x \notin \text{freevars}(T_2) \\
TT[(x : T_1, T_2)](\Gamma) &= (TT[T_1](\Gamma), TT[T_2](\Gamma)), \quad x \notin \text{freevars}(T_2)
\end{aligned}$$

## 2.4 Terms

$Wrap^0[AgdaType](term)$  is defined only when  $TT[AgdaType](\emptyset)$  is defined.

$$\begin{aligned}
Wrap^{2k}[AgdaType](MAlonzoTerm) &= MyTerm \\
Wrap^{2k+1}[AgdaType](MyTerm) &= MAlonzoTerm
\end{aligned}$$

$$\begin{aligned}
Wrap^k[A \text{ args } \dots](term) &= \text{unsafeCoerce } term \\
Wrap^{2k}[(A : Kind) \rightarrow T](term) &= Wrap^{2k}[T](term \text{ }) \\
Wrap^{2k+1}[(A : Kind) \rightarrow T](term) &= Wrap^{2k+1}[T](\lambda_. term) \\
Wrap^k[(x : T_1) \rightarrow T_2](term) &= \lambda x. Wrap^k[T_2](term \text{ } Wrap^{k+1}[T_1](x)) \\
Wrap^k[(x : T_1, T_2)](term_1, term_2) &= (Wrap^k[T_1](term_1), Wrap^k[T_2](term_2))
\end{aligned}$$

## 2.5 Value declarations

$VTMA$  gives  $MAlonzo$  generated value name

$VT$ ,  $VTD$  are defined when  $\{-\# \text{EXPORT } AgdaName \text{ HaskellName } \#\}$  is specified.

$$\begin{aligned}
VTMA[AgdaName] &= HaskellName \\
VT[AgdaName] &= HaskellName \\
VTD[AgdaName] &\doteq HaskellDeclaration
\end{aligned}$$

Considering declaration:

$$\begin{aligned}
AgdaName &: AgdaType \\
AgdaName &= \dots
\end{aligned}$$

$$\begin{aligned}
VTD[AgdaName] &\doteq \\
VT[AgdaName] &:: TT[AgdaType](\emptyset) \\
VT[AgdaName] &= Wrap^0[AgdaType](VTMA[AgdaName])
\end{aligned}$$

It works in the same way for constructors(it exports them as Haskell functions - not Haskell constructors). It also works seamlessly with parametrized modules and, consequently, with record functions.

## 3 Proofs

### 3.1 Old Intro

I need to prove that Haskell types and terms that I expose wouldn't break the system. It means two things:

1. Types preserve the same set of invariants
2. Terms have the same interface: any combination of `APPLY` that can be used(ignoring types) to original term must be usable with generated one; and primitives(numbers, strings, ... and their ops) are the same.

## 3.2 Preserving type invariants

Three cases:

### 1. **newtype** wrappers.

A datatype can be viewed as a logical statement and its constructors — as proofs of this statement. **newtype** wrapping gives us a statement but hides proofs. Acquiring an instance of this datatype in Haskell can only be done when some Agda function returns it. Therefore it was constructed with all the invariants checked by Agda. We can only use this datatype with functions exported from Agda that used the original version of it. Therefore all the internal invariants are safely passed from Agda to Agda invisibly through Haskell.

### 2. Transformation from Church polymorphism to Curry polymorphism.

$$(A : Kind) \rightarrow Type$$
$$(\forall a :: KT\llbracket Kind \rrbracket). HaskellType$$

They both mean the same thing but the first one always requires a proof that *Kind* is inhabited:

- If  $A \notin freevars(Type)$  and, by construction(*TT*),  $a \notin freevars(HaskellType)$ .
- $A$  (and consequently  $a$ ) is a phantom type(i.e. only used as a type parameter).

In both cases Haskell will completely ignore the inhabitation of  $KT\llbracket Kind \rrbracket$ . Agda however will require you to provide an evidence that *Kind* can be constructed. Now, *Kind* is defined as a combination of  $Set_0$  and arrows. Therefore some *Kind A* can be viewed as follows:  $Arg_1 \rightarrow \dots \rightarrow Arg_n \rightarrow Set_0$  for  $n \geq 0$ . Let's define a simple *Unit* type:

```
data Unit : Set where
  unit : Unit
```

We can now construct an  $A$ :  $A = \lambda arg_1 \dots arg_n. Unit$ . Therefore, each *Kind* is inhabited and we can safely omit this proof in our transformation.

### 3. In every other case type is exactly the same.

So invariants are clearly the same.

## 3.3 Preserving term interface

*Wrap* clearly deals with the issue of passing and skipping type parameters with MAlonzo-generated code. A thing to watch for is **unsafeCoerce**. There are three cases for a coerced type:

### 1. a **newtype** wrapper around an MAlonzo-generated datatype.

Safe because **newtype** is required to have the same internal structure as its wrapped type.

### 2. a primitive as defined by *PTMA*.

Safe because type of MAlonzo-generated code is the same as ours by construction.

### 3. $a\ args \dots$ , where $a$ is a type variable.

Safe because all terms with type  $a\ args \dots$  will have the same internal structure. That's because from Haskell side compiler will guarantee that and from Agda side terms will have a corresponding type  $A\ args \dots$  (via  $\Gamma$  in *TT*) so the compiler will guarantee it too.

## References

- [1] Makoto Takeyama, *a new compiler MAlonzo*. <http://thread.gmane.org/gmane.comp.lang.agda/62>, 2008.
- [2] Marcin Benke, *Alonzo — a compiler for Agda*. TYPES2007, 2007.