@prism project

Christophe BAL

1 Jan 2026 – Version 1.3.0

The `@prism` project [1] provides color palettes that can be used to create content based on expressive colors.

Last changes

1.3.0
2026-01-01

Fix.

- Lua product: the `use-std.tex` and `use-dark.tex` codes have been fixed.

Break.

- `luadraw` product becomes Lua product.
- Lua product: the dict-like variable `palNames` has been removed. Therefore, the responsibility of adding this specific variable will lie with `luadraw`.

New.

- New CSS and LaTeX products have been coded.
- The `Palettable` palettes have been added.
- Three semantic palettes `TdocBW`, `TdocCol` and `TdocDark` have been created to be used by the `tutodoc` class (LaTeX creation process used).
- Added an `online demo of @prism` (the CSS product showcase is used).

Update.

- Manual.
  - Added lists of renamed and removed palettes.
  - Added two appendixes, one with all palettes grouped by user-friendly categories, and another showing similar palettes.
  - Added explanations about the utility of palettes for non-designers.
  - Added explanations about the minimal common optional sets of extra features implemented.
- Better palette references.
- Better showcases.
  - Several category PDF files are proposed (one PDF per category and theme).
  - 2D chart and Delaunay triangulation added.

[1] The name comes from "***@·esthetic P·roducts*** *for* ***R·epresenting I·nformative S·cientific M·aps***". This name is a double play on words: [1] a prism splits light into an informative spectrum, symbolizing how data are decomposed into meaningful color, and [2] "@" read as "at" indicates where the light meets the prism to be broken down into an informative spectrum.

Contents

I. Motivations **3**

II. Where do the color palettes come from? **4**

III. Reuse from... **5**

IV. How to choose a palette? **6**

V. Supported implementations **6**
1. JSON, the versatile default format 7
2. CSS 7
3. LaTeX 8
   a. Basic use 8
   b. Creating palettes from scratch 9
   c. Creating palettes from existing ones 9
   d. Retrieving the internal definition of a palette 10
4. Lua 10
   a. Basic use 10
   b. Creating palettes from existing ones 10

VI. Contribute via Git **11**
1. Complete the translations 11
   a. The en folder 11
   b. The changes folder 11
   c. The status folder 11
   d. The README.md and LICENCE.txt files 11
   e. New translations 11
2. Improving the source code 12

VII. History **13**

Appendix 1 – All palette names **15**

Appendix 2 – Palettes by category **18**
- Colorblind palettes 18
- Cyclic palettes 20
- Dark palettes 21
- Divergent palettes 22
- Qualitative palettes 25
- Semantic palettes 29
- Sequential palettes 30

I. Motivations

This project was born out of a desire to enhance `luadraw` with a set of color palettes to easily produce graphics like the 3D plot shown below. Despite the availability of palette generation tools such as `Coolors`, the choice has been made to offer pre-built palettes, because this serves several key purposes for non-designers.

- **Reduced cognitive load:** pre-configuration eliminates design decisions, allowing to focus on content.
- **Consistency:** it becomes easy to ensure visual coherence across documents and projects, regardless of technology.
- **Accessibility compliance:** some pre-configured palettes guarantee colorblind-safe combinations.
- **Perceptual uniformity:** most palettes ensure distinguishable and meaningful colors for data visualization, while others serve artistic purposes.



Technically, to generate the graphics in this section, `luadraw` is provided with a finite list of colors and uses linear interpolations to calculate the intermediate color values. In the example above, the finite color palette used is defined as follows.

Using this palette, `luadraw` can produce the following spectrum, allowing us to create the graphic above.

Note.

Using the `Lua` *implementation of* `@prism`*, see the section V-4, via* `luadraw`*, we can create the palettes below made from the previous one named* `'GeoRainbow'`*. Each instruction used is given below each palette.*




```
getPal('GeoRainbow', {reverse = true})
```

```
getPal('GeoRainbow', {shift = 3})
```

`getPal('GeoRainbow', {extract = {7, 1, 4}})`

This features provide remarkable creative flexibility: with the same surface as before, using the setting `getPal('GeoRainbow', {extract = {6, 5, 4, 3, 1, 2}})` *instead of* `getPal('GeoRainbow')`*, we change the visual tone, shifting from a seaside feel to a snow-covered world.*



II. Where do the color palettes come from?

`@prism` includes some original creations, but most color palettes are derived from the projects listed below.

- `Asymptote` is used, but currently offers nothing beyond `Matplotlib` (despite different implementations).
- `CarbonPlan` provides palettes designed for data visualization..
- `CARTOColors` palettes are extracted from `Palettable` project.
- `cmocean` palettes are extracted from `Palettable` project.
- `Colorbrewer` provides professional color palettes for mapping and data visualization.
- `Light and Bartlein` palettes are extracted from `Palettable` project.
- `Matplotlib` compiles color maps from diverse projects.
- `MyCarta` palettes are extracted from `Palettable` project.
- `Plotly` palettes are extracted from `Palettable` project.
- `Scientific Coulour Maps` provides palettes designed for colorblind accessibility.
- `Tableau` palettes are extracted from `Palettable` project.
- `Wes Anderson Palettes` palettes are extracted from `Palettable` project.

We retain only palettes that comply with the following rules.

- **No repetition.** Unlike `Matplotlib`,[2] `@prism` use a one-to-one map from names to palettes.
- **No reversed versions.** Unlike `Matplotlib`,[3] `@prism` never includes reversed palettes as fixed data.

[2] Some `Matplotlib` palettes are duplicated, likely for historical reasons.
[3] Most `Matplotlib` color maps have a reversed version named with the `_r` suffix, possibly for performance reasons.

Note.

Adding new palettes to `@prism` is straightforward (no coding skills required). See section VI-2 to get started.

III. Reuse from...

Here are the key points to remember when using palettes similar to those offered by projects listed in the section II.

1. `@prism` uses 'semantic' `CamelCase` naming. Therefore, palette names such as `berlin`, `gist_heat` and `Pinkgrey` become `Berlin`, `GistHeat` and `PinkGrey`.
2. `Matplotlib` palettes with a name ending with `_r` (reversed color order) are not included in `@prism`.
3. The following palettes have been renamed: $\boxed{\Rightarrow}$ indicates a name modification, with the `@prism` name displayed on the right.

Table 1: Renamed palettes

Asymptote	Brg	⇒	BRG
	Bwr	⇒	BWR
CARTOColors	Prism	⇒	PrismCC
CMasher	Copper	⇒	CopperCM
	Fall	⇒	FallCM
	Ghostlight	⇒	GhostLight
	Iceburn	⇒	IceBurn
	Ocean	⇒	OceanCM
	Redshift	⇒	RedShift
	Sunburst	⇒	SunBurst
CarbonPlan	Bluegrey	⇒	BlueGrey
	Blues	⇒	BluesCP
	Cool	⇒	CoolCP
	Earth	⇒	EarthCP
	Greens	⇒	GreensCP
	Greys	⇒	GreysCP
	Orangeblue	⇒	OrangeBlue
	Orangegrey	⇒	OrangeGrey
	Oranges	⇒	OrangesCP
	Pinkgreen	⇒	PinkGreen
	Pinkgrey	⇒	PinkGrey
	Purplegrey	⇒	PurpleGrey
	Purples	⇒	PurplesCP
	Rainbow	⇒	RainbowCP
	Redgrey	⇒	RedGrey
	Reds	⇒	RedsCP
	Redteal	⇒	RedTeal
	Sinebow	⇒	SineBow
	Tealgrey	⇒	TealGrey
	Yellowgrey	⇒	YellowGrey

Continued on next page

Table 1: Renamed palettes (Continued)

	`Yellowpurple`	⇒	`YellowPurple`
Colorbrewer	`PRGn`	⇒	`PrGn`
	`YlOrRd`	⇒	`YlOrRdCBW`
Matplotlib	`Afmhot`	⇒	`AfmHot`
	`Coolwarm`	⇒	`CoolWarm`
	`Hsv`	⇒	`HSV`
Plotly	`Bluered`	⇒	`BlueRedPLY`
	`Hot`	⇒	`HotPLY`
	`Jet`	⇒	`JetPLY`
	`Rainbow`	⇒	`RainbowPLY`
Tableau	`Gray`	⇒	`MidGray`

4. The following palettes are excluded because they duplicate `@prism` palettes either directly or in reversed order, except that exact duplicates (same name and colors) are omitted: we use $\boxed{=}$ for equality, and $\boxed{\rightleftharpoons}$ for reversal, and the rightmost palettes are the ones retained in `@prism`.

Table 2: Ignored palettes

Matplotlib	`Gray`	⇌	`Binary`
	`GistYarg`	⇌	`GistGray`
Plotly	`D3`	=	`Tab10`
Tableau	`Tableau`	=	`Tab20`

Caution.

Most `@prism` implementations add the `pal` prefix to standardized `CamelCase` names. See the section V.

Note.

Most `@prism` implementations provide methods to easily obtain reversed palettes, sub-palettes, and color-shifted palettes. See the section V.

IV. How to choose a palette?

Here are a few tips to help you select your color palette.

1. An `online demo of @prism`[4] proposes an intuitive way to look for a palettes.
2. Appendix 2 (page **??**) presents all palettes, organized by category, along with a visualization of their continuous spectra, or their corresponding discrete palette definitions.

V. Supported implementations

All implementations are located in the `products` folder. Each implementation provides the following features:

- Palette formats in both modular (one file per palette) and monolithic (all palettes in a single file) versions.
- Palette definitions in both high-fidelity (original size) and small (currently 40 colors) size.
- Select specific colors from an existing palette using their indices.

[4] https://projetmbc.github.io/for-writing/

- Shift the palette left (negative value) or right (positive value) by any number of steps.
- Reverse the order of the colors.

Important.

To explain how new palettes can be built, we will refer to the colors in the standard palette as `coul_1`, `coul_2`, *etc., and suppose that the extracted indices are* `{1, 3, 6, 9}`, *the shift used is 1+, and the* `reverse` *option is enabled. The new palette will then be built sequentially as follows: first* `{coul_1, coul_3, coul_6, coul_9}` *(extraction), second* `{coul_9, coul_1, coul_3, coul_6}` *(shift to the right), and finally* `{coul_6, coul_3, coul_1, coul_9}` *(reverse).*

Note.

Extra features are limited to discrete palette operations. For example, color interpolation is not provided, as this is usually handled out of the box by visualization and formatting tools.

1. JSON, the versatile default format

The `JSON` product allows unsupported programming languages to integrate `@prism` palettes easily. Below are the first lines of the `palettes-hf.json` file.

```
{
  "Accent": [
    [0.49803922, 0.78823529, 0.49803922],
    [0.74509804, 0.68235294, 0.83137255],
    [0.99215686, 0.75294118, 0.5254902],
    [1, 1, 0.6],
    [0.21960784, 0.42352941, 0.69019608],
    [0.94117647, 0.00784314, 0.49803922],
    [0.74901961, 0.35686275, 0.09019608],
    [0.4, 0.4, 0.4]
  ],
  ...
}
```

2. CSS

Note.

The `HTML`, `CSS`, *and* `JavaScript` *files for product development and demonstration were created using* `Claude` *and* `Gemini` *AI assistants.*

Note.

All formats are provided: modular (each palette is in a dedicated file) and monolithic (files provide all the palettes).

Each palette color is defined as an individual variable named according to the pattern `--pal<name>-<nb>`, where `<name>` is the standard palette name and `<nb>` is the desired index ranging. Each palette color variable is defined as an `RGB` value using percentage notation. For example, the file `palettes-hf/GistHeat.css` looks like the following partial code.

```
:root {
  --palGistHeat-1: rgb(0% 0% 0%);
  --palGistHeat-2: rgb(0.59% 0% 0%);
  /* Other RBG colors.*/
  --palGistHeat-256: rgb(100% 100% 100%);
}
```

Here is one first possible use case.

```
.warning-text {
  color: var(--palGistHeat-3);
}

.gist-heat-gradient {
  background: linear-gradient(
    90deg,
    var(--palGistHeat-1),
    var(--palGistHeat-64),
    var(--palGistHeat-128),
    var(--palGistHeat-256)
  );
}
```

The example below demonstrates creating gradient variables through selective color extraction and custom reordering.

```
:root {
  --transformed-gist-heat-gradient: linear-gradient(
    90deg,
    var(--palGistHeat-6),
    var(--palGistHeat-3),
    var(--palGistHeat-9),
    var(--palGistHeat-1)
  );
}

.transformed-gist-heat-gradient {
  background: var(--transformed-gist-heat-gradient);
}
```

3. LaTeX

a. Basic use

Note.

Just one kind of format is provided: modular (each palette is in a dedicated file).

Accessing a single palette color is straightforward: use `\palUse{<name>}{<index>}` where `<name>` is the standard palette name (without prefix), and `<index>` is the color number (ranging from 1 to 10). For example, `\palUse{GistHeat}{8}` is the eighth color of the `GistHeat` palette, an `xcolor` format color that can be easily used as shown in the following compilable example.

```
\documentclass{article}

% Load the palette (LaTeX can't work with all the palettes).
\usepackage{palettes-hf/GistHeat}

% Load the palette API.
\usepackage{palapi}

\usepackage{tikz}

\begin{document}

\textcolor{\palUse{GistHeat}{8}}{\bfseries Colored text.}

Representation of the first ten palette colors.

\begin{tikzpicture}
  \foreach \i in {1,...,10} {
    \fill[\palUse{GistHeat}{\i}]
      (1.25*\i - 1, 0) rectangle (1.25*\i, 1);
```

```
  }
\end{tikzpicture}

\end{document}
```

b. Creating palettes from scratch

For creating new palettes manually, the following high-level commands are available.

1. `\palCreateFromNames` works with a comma separated list of named colors, while `\palCreateFromRGB` creates a palette by entering it as an array-like variable.
2. `\palSize{<name>}` returns the palette size (useful for loops, for example).

The following example demonstrates the `\palCreateFromRGB` and `\palCreateFromNames` commands.

```
\usepackage{palapi}

\usepackage[svgnames]{xcolor}

\palCreateFromRGB{MyRGBPal}{
  {0.0, 0.0, 0.0},
  {0.4, 0.0, 0.2},
  {0.8, 0.2, 0.0},
}

\palCreateFromNames{MyNameUsePal}{
  YellowGreen,
  green!60!black,
  LimeGreen!80,
}
```

Note.

All built-in palettes are created using the `\palCreateFromRGB` macro.

A lower-level approach is also available through the following commands.

1. `\palNew{<name>}` initializes a new (empty) palette.
2. `\palAddNames{<name>}{<color-using-names>}` appends a color defined with named colors to the palette.
3. `\palAddRGB{<name>}{<r>, <g>, <b>}` appends an `RGB` color to the palette, where `<r>`, `<g>`, and `<b>` are decimal values ranging from 0 to 1.

The following example demonstrates the flexibility offered by these low-level commands.

```
\usepackage{palapi}

\usepackage[svgnames]{xcolor}

\palNew{LowLevelPal}
\palAddNames{LowLevelPal}{IndianRed}
\palAddRGB{LowLevelPal}{0.0, 0.0, 0.0}
\palAddNames{LowLevelPal}{green!60!black}
\palAddRGB{LowLevelPal}{0.8, 0.2, 0.0}
```

c. Creating palettes from existing ones

Building new palettes by transforming existing ones can be achieved using the `\palCreateFromPal` command, which has the signature `\palCreateFromPal{<new-name>}[<options>]{<existing-name>}`. The following example shows how to do this (all options are used).

```
\usepackage{palettes-hf/Blackbody}
\usepackage{palapi}
```

```
\palCreateFromPal{BlackbodyTransformed}[
  extract = {1, 3, 6, 9},
  shift   = 1,
  reverse
]{Blackbody}
```

Tip.

\palCreateFromPal{<new-name>}{<existing-name>} builds a copy of an existing palette.

d. Retrieving the internal definition of a palette

The internally stored definition of a palette named `MyPal`, for example, is `\g_palette_MyPal_seq` which is a LaTeX3 variable (keep in mind the pattern `\g_palette_PaletteName_seq`).

Note.

Variables of type `\g_palette_PaletteName_seq` are not used internally to retrieve the colors themselves; they are only there for technical reasons related to the development process of new palettes via LaTeX.

4. Lua

Note.

Initially, the `@prism` project was created to provide ready-to-use color palettes for `luadraw`, a package that greatly facilitates the creation of high-quality 2D and 3D plots using LuaLaTeX and `TikZ`.

a. Basic use

Note.

All formats are provided: modular (each palette is in a dedicated file) and monolithic (files provide all the palettes).

The `Lua` palette variables are named using the prefix `pal`. They are arrays of arrays of three floats (making it straightforward to use a color from a palette). For example, the definition of `palGistHeat` looks like the following partial code.

```
palGistHeat = {
    {0.0, 0.0, 0.0},
    {0.105882, 0.0, 0.0},
    {0.211764, 0.0, 0.0},
    -- Other RBG colors.
}
```

b. Creating palettes from existing ones

The `palCreateFromPal` function provides options to build new palettes by transforming existing ones. The following example shows how to do this (all options are used).

```
palBlackbodyTransformed = palCreateFromPal(
    palBlackbody,
    {
        extract = {2, 5, 8, 9},
        shift   = 1,
        reverse = true
    }
)
```

VI. Contribute via Git

Caution.

Never use the `main` *branch, which is for freezing the latest stable versions of each projects in the mono repository* `https://github.com/projetmbc/for-writing`.

1. Complete the translations

Important.

Although we're going to explain how to translate the documentation, it doesn't seem relevant to do so, as English should suffice these days.



Figure 1: Simplified view of the translation folder

The translations are roughly organized as in figure 1 where just the important folders for the translations have been "*opened*".[5] **A little further down, the section VI-1-e explains how to add new translations**.

a. The en folder

This folder, managed by the author of `@prism`, contains files easy to translate even if you're not a coder.

b. The changes folder

This folder is a communication tool where important changes are indicated without dwelling on minor modifications specific to one or more translations.

c. The status folder

This folder is used to keep track of translations from the project's point of view. Everything is done via well-commented `YAML` files, readable by a non-coder.

d. The README.md and LICENCE.txt files

The `LICENCE.txt` file is aptly named, while the `README.md` file takes up in English the important points of what is said in this section about new translations.

e. New translations

Note.

The folder `manual` *is reserved for documentation. It contains* `TEX` *files that can be compiled directly for real-time validation of translations.*

Warning.

Only start from the `en` *folder, as it's the responsibility of the* `@prism` *author.*

[5] This was the organization on October 26, 2025.

Let's say you want to add support for Italian.[6] To do this, you must use `Git` as follows.

1. Via `https://github.com/projetmbc/for-writing/tree/aprism/@prism`, recover the entire project folder. Do not use the `main` branch, which is used to freeze the latest stable versions of all the projects in the mono repository `https://github.com/projetmbc/for-writing`.
2. In the `@prism/contrib/translate` folder, create an `it` copy of the `en` folder, where `it` is the short name of the language documented in the page "*IIETF language tag*" from `Wikipedia`.
3. Once the translation is complete in the `it` folder, share it via `https://github.com/projetmbc/for-writing/tree/aprism/@prism` using a classic `git push`.

2. Improving the source code

Participation as a coder is made via the repository `https://github.com/projetmbc/for-writing/tree/aprism/@prism` corresponding to the `@prism` development branch. Here is what you can do, details can be found in the file `https://github.com/projetmbc/for-writing/blob/aprism/@prism/contrib/products/README.md`.

1. Create new palettes within an existing implementation. No coding skills required.
2. Propose a new implementation in your favorite programming language.
3. Combine both approaches.

[6] As mentioned above, there is no real need for the `doc` folder.

VII. History

1.3.0
2026-01-01

Fix.

- Lua product: the `use-std.tex` and `use-dark.tex` codes have been fixed.

Break.

- luadraw product becomes Lua product.
- Lua product: the dict-like variable palNames has been removed. Therefore, the responsibility of adding this specific variable will lie with luadraw.

New.

- New CSS and LaTeX products have been coded.
- The Palettable palettes have been added.
- Three semantic palettes `TdocBW`, `TdocCol` and `TdocDark` have been created to be used by the tutodoc class (LaTeX creation process used).
- Added an online demo of @prism (the CSS product showcase is used).

Update.

- Manual.
  - Added lists of renamed and removed palettes.
  - Added two appendixes, one with all palettes grouped by user-friendly categories, and another showing similar palettes.
  - Added explanations about the utility of palettes for non-designers.
  - Added explanations about the minimal common optional sets of extra features implemented.
- Better palette references.
- Better showcases.
  - Several category PDF files are proposed (one PDF per category and theme).
  - 2D chart and Delaunay triangulation added.

1.2.1
2025-11-09

Fix.

- Equal palettes: the floating point equality uses now a correct tolerance.

Break.

- Palettes: the extra `Greys` has been removed (it is equal to `Grays`).

New.

- Similar palettes: two PDF files show similar palettes in standard and black modes (semi-automated process used).

Update.

- luadraw product: the associative array palNames has been added for compatibility reasons with the luadraw package.
- `BlindFish` palette: the last color variation has been made smoother (luadraw process used).

1.2.0
2025-10-29

Break.

- Palettes: all final palettes now consist of 10 colors.
- luadraw products: the getPal dictionary array has been converted into a function accepting string palette names (with or without pal prefix). See below.

New.

- Palettes.
  - Added `Lemon` and `ShiftRainbow` palettes (luadraw creation process used).
  - Added 37 palettes from the Scientific Coulour Maps project.
- luadraw product: accessing a palette and creating new ones can be made using the getPal function which has an optional argument options (dict-like array) with the following keys and their values.
  - extract: a list of non-zero integers used to extract specific colors from the palette (the order is preserved).
  - reverse: a boolean value indicating whether to reverse the palette color order (false by default).
  - shift: an integer value for applying a circular color shift to the palette.
- Documentations
  - Added English PDF manual.
  - Showcase: two PDF files demonstrate the use of each palette (white and dark modes).

1.1.0
2025-10-14

Break.

- Duplicate palettes and those that are reverse of others are ignored (strict equalities only).

New.

- New palettes added: `BurningGrass`, `GeoRainbow` and `PastelRainbow` (`luadraw` creation process used).
- The `luadraw` palette product has a new dictionary like variable `getPal` to access a palette using its name (as a string variable).

Update.

- Palette contributions: in the mandatory `extend.py` file, the `build_code` function must work with the dictionary of all the palettes, and manage a credit to the `@prism` project.

1.0.0
2025-10-11

First public version of the project.

Appendix 1 – All palette names

Important.

The palette names in this appendix are standard, but some `@prism` implementations add a specific prefix, and the very last new palettes are marked by ★ .

A

Accent
Acton
AfmHot
AgGrnYl
AgSunset
Algae
Alphabet
Amber ★
Amethyst ★
Amp
Antique
Apple ★
Aquatic1
Aquatic2
Aquatic3
Arctic ★
ArmyRose
Autumn

B

Balance ★
Bam
Bamako
BamO
Batlow
BatlowK
BatlowW
Berlin
Bilbao
Binary
Blackbody
BlindFish
BlueDarkOrange12
BlueDarkOrange18
BlueDarkRed12
BlueDarkRed18
BlueGray
BlueGreen
BlueGrey ★
BlueOrange8
BlueOrange10
BlueOrange12
BlueOrangeRed
BlueRed
BlueRedPLY
Blues
Blues7
Blues10
BluesCP ★
BluGrn
BluYl
Bold
Bone
BrBG
BRG
Broc
BrocO
BrownBlue10
BrownBlue12
BrwnYl
Bubblegum ★
Buda
BuGn
Bukavu
BuPu
Burg
BurgYl
BurningGrass
BWR

C

Cavalcanti
Chevalier
Chroma ★
Cividis
Classic ★
CMRmap
ColorBlind
Cool
CoolCP ★
CoolWarm
Copper
CopperCM ★
Cork
CorkO
Cosmic ★
Cube1
Cubehelix
Cubehelix1
Cubehelix2
Cubehelix3
CubeYF
Curl

D

Darjeeling1
Darjeeling2
Darjeeling3
Darjeeling4
Dark2
Dark24
DarkMint
Davos
Deep
Delta
Dense
Devon
Dusk ★

E

Earth
EarthCP ★
Eclipse ★
Electric
Ember ★
Emerald ★
Emergency ★
Emrld

F

Fall
FallCM ★
FantasticFox1
FantasticFox2
Fes
Fire ★
Flag
Flamingo ★
Freeze ★
Fusion ★

G

G10
GasFlame
Gem ★
GeoRainbow

Geyser
GhostLight ★
GistEarth
GistGray ★
GistHeat
GistNcar
GistRainbow
GistStern
Glasgow
GnBu
Gnuplot
Gnuplot2
Gothic ★
GrandBudapest1
GrandBudapest2
GrandBudapest3
GrandBudapest4
GrandBudapest5
Gray ★
GrayC
Greengrey ★
GreenMagenta
GreenOrange
Greens
GreensCP ★
Greys ★
GreysCP ★
Guppy ★

H

Haline
Hawaii
Heart ★
Holly ★
Horizon ★
Hot
HotPLY ★
HSV

I

Ice
IceBurn ★
Imola
Inferno
Infinity ★
IsleOfDogs1
IsleOfDogs2
IsleOfDogs3

J

Jet
JetPLY ★
JimSpecial
Jungle ★

L

Lajolla
Lapaz
Lavender ★
Lemon
Light24
Lilac ★
LinearL
Lipari
Lisbon

M

Magenta
Magma
Managua
Margot1
Margot2
Margot3
Matter
Mendl
MidGray ★
Mint
Moonrise1
Moonrise2
Moonrise3
Moonrise4
Moonrise5
Moonrise6
Moonrise7

N

Navia
NaviaW
Neon ★
Neutral ★
NipySpectral
Nuclear ★
Nuuk

O

Ocean
OceanCM ★
OkabeIto ★
Oleron
OrangeBlue ★
OrangeGrey ★
Oranges
OrangesCP ★
OrRd
OrYel
Oslo
Oxy

P

Paired
Pastel
Pastel1
Pastel2
PastelRainbow
Peach
Pepper ★
PerceptualRainbow
Petroff6 ★
Petroff8 ★
Petroff10 ★
Phase
Picnic
Pink
PinkGreen ★
PinkGrey ★
Pinks ★
PinkYl
PiYG
Plasma
Plotly
Portland
PrGn
Pride ★
Prinsenvlag ★
Prism
PrismCC
PuBu
PuBuGn
PuOr
PuRd
Purp
Purple
PurpleGray
PurpleGrey ★
Purples
PurplesCP ★
PurpOr

R

Rainbow
RainbowCP ★
RainbowPLY

Rainforest ★
RdBu
RdGy
RdPu
RdYlBu
RdYlGn
Red
RedGrey ★
RedOr
Reds
RedsCP ★
RedShift ★
RedTeal ★
RedYellowBlue
Roma
RomaO
Royal1
Royal2
Royal3

S

Safe
Sapphire ★
Savanna ★
Seasons ★
Seaweed ★
Seismic
Sepia ★
Set1
Set2
Set3
ShiftRainbow
SineBow ★
Solar
Spectral
Speed
Spring
Summer
SunBurst ★
Sunset
SunsetDark
Swamp ★

T

T10
Tab10
Tab20
Tab20b
Tab20c
TableauLight
TableauMedium
TdocBW
TdocCol
TdocDark
Teal
TealGrey ★
TealGrn
TealRose
Teals ★
Tempo
Temps
Terrain
Thermal
Tofino
Tokyo
Torch ★
Toxic ★
TrafficLight
Tree ★
Tropic
Tropical ★
Turbid
Turbo
Turku
Twilight
TwilightShifted

V

Vanimo
Vik
VikO
Viola ★
Viridis
Vivid
Voltage ★

W

Warm ★
Water ★
Waterlily ★
Watermelon ★
Wildfire ★
Wind ★
Winter
Wistia

Y

YellowGrey ★
YellowPurple ★
Yellows ★
YlGn
YlGnBu
YlOrBr
YlOrRd
YlOrRdCBW ★

Z

Zissou

Appendix 2 – Palettes by category

Warning.

The palette names in this appendix are standard, but some `@prism` *implementations add a specific prefix.*

Note (Qualitative and semantic palettes).

The threshold of 40 colors has been established for qualitative and semantic palettes. The following lines outline the rationale for this limit.

- *In qualitative color palettes, each color represents a single data point or a group of data. Experience shows that about ten colors are more than enough.*
- *Semantic palettes associate a color with a specific context, such as warning levels (see the three frames in this document). Choosing 40 colors allows for 10 different contexts, each with 4 sub-categories. Here are some examples of sub-categories.*

  10-19 ***Initial / Idle:*** *default states such as "To Do", "Clickable", or "To be analyzed".*
  20-29 ***Active / Transition:*** *states in flux, including "In Progress" or UI "Hover" effects.*
  30-39 ***Success / Final:*** *terminal positive states like "Done", "Clicked", or "Validated".*
  40-49 ***Alert / Rejection:*** *error handling and negative outcomes, e.g., "Error", "Inactive", or "Rejected".*

Important.

Categories were generated semi-automatically, followed by manual selection to obta in relevant choices.

Colorblind palettes

Colorblind palettes provide high-contrast hues specifically optimized for users with color vision deficiency.

Acton

Bam

BamO

Bamako

Batlow

BatlowK

BatlowW

Berlin

Bilbao

Broc

BrocO

Buda

Bukavu

Cork

CorkO

Cubehelix

Davos

Devon

Fes

Glasgow

GrayC

Hawaii

Imola

Lajolla

Lapaz

Lipari

Lisbon

Managua

Navia

NaviaW

Nuuk

OkabeIto

Oleron

Oslo

Petroff6

Petroff8

Petroff10

Roma

RomaO

Safe

Tofino

Tokyo

Turku

Vanimo

Vik

VikO

Wistia

Cyclic palettes

Cyclic palettes create seamless loops for periodic data, such as angles, seasons, or 24-hour cycles.

CopperCM

Emergency

Flag

Infinity

RainbowCP

Seasons

SineBow

Dark palettes

Dark palettes offer high-contrast schemes specifically optimized for terminal interfaces and dark-mode backgrounds.

Autumn

BWR

Cool

GistRainbow

HSV

Jet

Lemon

Prism

Rainbow

Seismic



Spring

Summer

Tab10

Tab20



Tab20b

Tab20c

TdocDark

Terrain

Viridis

Winter

YlOrRd

Divergent palettes

Divergent palettes highlight deviations from one or more midpoints toward contrasting extremes.

ArmyRose

BWR

Balance

BlindFish

BlueDarkOrange12

BlueDarkOrange18

BlueDarkRed12

BlueDarkRed18

BlueGray

BlueGreen

BlueGrey

BlueOrange8

BlueOrange10

BlueOrange12

BlueOrangeRed

BrBG

BrownBlue10

BrownBlue12

BurningGrass

CoolWarm

Curl

Delta

Earth

Fall

Flag



Fusion

Geyser

GistNcar

GistRainbow

GistStern

GreenMagenta

Greengrey

Guppy

HSV

Holly

IceBurn


Jet
NipySpectral
Ocean
OrangeBlue
OrangeGrey
PiYG
Picnic
PinkGreen
PinkGrey
Portland
PrGn
Pride
Prinsenvlag
Prism
PuOr
PurpleGrey
RdBu
RdGy
RdYlBu
RdYlGn
RedGrey
RedShift
RedTeal
RedYellowBlue
Seaweed
Seismic
Spectral
Tab10
Tab20
Tab20b
Tab20c
TealGrey
TealRose
Temps
Terrain
Tropic
Twilight
TwilightShifted
Viola
Waterlily

Watermelon

Wildfire

YellowGrey

YellowPurple

Qualitative palettes

Qualitative palettes use distinct hues to separate categorical data without implying any order or hierarchy.

Accent



AgGrnYl



AgSunset

Alphabet



Antique



Aquatic1

Aquatic2



Aquatic3



Autumn



BRG



BWR



Binary



BlindFish



BlueRed



Bold



BurningGrass

CMRmap



Cavalcanti



Chevalier



ColorBlind



Cool



Darjeeling1



Darjeeling2



Darjeeling3



Darjeeling4



Dark2

Dark24



FantasticFox1



FantasticFox2



G10

GasFlame



GeoRainbow

GrandBudapest1



GrandBudapest2



GrandBudapest3

GrandBudapest4



GrandBudapest5



GreenOrange



IsleOfDogs1



IsleOfDogs2



IsleOfDogs3



Lemon



Light24



Margot1

Margot2



Margot3



Mendl



MidGray



Moonrise1



Moonrise2

Moonrise3



Moonrise4



Moonrise5



Moonrise6



Moonrise7



NipySpectral



Paired



Pastel



Pastel1



Pastel2



PastelRainbow



Plotly



PrismCC



PurpleGray



Royal1

Royal2



Royal3

Safe



Seismic



Set1



Set2



Set3



ShiftRainbow

Spring



Summer



T10



Tab10

Tab20



Tab20b



Tab20c



TableauLight



TableauMedium



TrafficLight



Vivid



Winter



YlOrRd



Zissou

Semantic palettes

Semantic palettes assign colors to categories — such as UI states, system status, or pedagogical elements — to convey immediate meaning.



Sequential palettes

Sequential palettes represent ordered data using a single or multi-hue gradient with increasing lightness.

AfmHot

Algae

Amber

Amethyst

Amp

Apple

Arctic

Autumn

BRG

BWR

Binary

Blackbody

BlindFish

BluGrn

BluYl

BlueRedPLY

Blues

Blues7

Blues10

BluesCP

Bone

BrwnYl

BuGn

BuPu

Bubblegum

Burg

BurgYl

BurningGrass

CMRmap

Chroma

Cividis

Classic

Cool

CoolCP

Copper

Cosmic

Cube1

CubeYF

Cubehelix

Cubehelix1

Cubehelix2

Cubehelix3

DarkMint

Deep

Dense

Dusk

EarthCP

Eclipse

Electric

Ember

Emerald

Emrld

FallCM

Fire

Flamingo

Freeze

GasFlame

Gem

GeoRainbow

GhostLight

GistEarth

GistGray

GistHeat

GistNcar

GistRainbow

GistStern

GnBu

Gnuplot

Gnuplot2

Gothic

Gray

Greens

GreensCP

Greys

GreysCP

HSV


Haline
Heart
Horizon
Hot
HotPLY
Ice
Inferno
Jet
JetPLY
JimSpecial
Jungle
Lavender
Lemon
Lilac
LinearL
Magenta
Magma
Matter
Mint
Neon
Neutral
NipySpectral
Nuclear
Ocean
OceanCM
OrRd
OrYel
Oranges
OrangesCP
Oxy
PastelRainbow
Peach
Pepper
PerceptualRainbow
Phase
Pink
PinkYl
Pinks
Plasma
PuBu

PuBuGn

PuRd

Purp

PurpOr

Purple

Purples

PurplesCP

Rainbow

RainbowPLY

Rainforest

RdPu

Red

RedOr

Reds

RedsCP

Sapphire

Savanna

Seismic



Sepia

ShiftRainbow

Solar

Speed

Spring

Summer

SunBurst

Sunset

SunsetDark

Swamp

Teal

TealGrn

Teals

Tempo

Terrain



Thermal

Torch

Toxic

Tree

Tropical

Turbid

Turbo

Twilight

TwilightShifted

Viridis

Voltage

Warm

Water

Wind

Yellows

YlGn

YlGnBu

YlOrBr

YlOrRd

YlOrRdCBW