

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-1									
1	1	In the JSON syntax, data is separated by ____.	Commas	0.5		Semicolons	Colons	Commas	Hyphens
2	1	which of the following is incorrect about JSON: 1.JSON stands for JavaScript Object Notation 2.JSON is a lightweight format for storing and transporting data 3.In JSON Curly braces hold Arrays 4.JSON is often used when data is sent from a server to a web page 5.JSON is "self-describing" and easy to understand	3only	1	LJU-2025	2,3	3,4	3 only	5 only
3	1	How do you represent a JSON array of strings?	{ "days" : ["SUN", "MON", "TUE", "WED", "THU", "FRI", "SAT"] }	1		["days" : { "SUN", "MON", "TUE", "WED", "THU", "FRI", "SAT" }]	["days" : { SUN , MON , TUE , WED , THU , FRI , SAT }]	{ "days" : { "SUN", "MON", "TUE", "WED", "THU", "FRI", "SAT" } }	{ "days" : ["SUN", "MON", "TUE", "WED", "THU", "FRI", "SAT"] }
4	1	Which of the following code will throw an error?	JSON.parse(undefined);	1	LJU-2023	JSON.parse(false);	JSON.parse(null);	JSON.parse(undefined);	JSON.parse("0");
5	1	Which of the following JSON values cannot be one of the following data types?	a function	0.5		a number	a string	a function	null
6	1	JavaScript has a _____ built in function for converting an object into a JSON string:	JSON.stringify()	0.5		JSON.parse()	JSON.stringify()	JSON_Parse ()	JSON_Stringify()
7	1	JavaScript has a _____ built in function for converting JSON strings into JavaScript objects	JSON.parse()	0.5		JSON.parse()	JSON.stringify()	JSON_Parse ()	JSON_Stringify()
8	1	The extension and MIME type for JSON text is	.json & application/json	0.5		.json & application/json	.js & application/json	.json & text/js	.js & text/json

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
9	1	What will be the output of following code var obj= { "employee" : { "name" : "John", "age" : 30, "city" : "New York" } } console.log(employee)	Error	1		{ "name" : "John", "age" : 30, "city" : "New York" }	"employee" : { "name" : "John", "age" : 30, "city" : "New York" }	Error	Undefined
10	1	What will be the output of following code var obj= { "employee" : { "name" : "John", "age" : 30, "city" : "New York" } } console.log(obj.name);	undefined	1	LJU-2023	{ "name" : "John", "age" : 30, "city" : "New York" }	undefined	Syntax error	John
11	1	const person= { name:"xyz", age:28, employee: [{ emp_name:"pqr", designation:"prof", weekly_lec:["Tuesday"] }, { emp_name:"jkl", designation:"Asst prof", weekly_lec:["Friday","Saturday"] } } } Identify the correct statement to print no. of weekly lectures of "pqr" employee.	console.log(person.employee[0].weekly_lec.length);	1	LJU-2023	console.log(person.employee[0].weekly_lec.length());	console.log(person.employee[0].weekly_lec[0].length);	console.log(person.employee[1].weekly_lec.length);	console.log(person.employee[0].weekly_lec.length);
12	1	What is the correct way to convert a JavaScript object into a JSON string?	const obj = { name: "John", age: 30 }; const jsonString = JSON.stringify(obj); console.log(jsonString);	1		const obj = { name: "John", age: 30 }; const jsonString = JSON.stringify(obj); console.log(jsonString);	const obj = { name: "John", age: 30 }; const jsonString = obj.toJSON(); console.log(jsonString);	const obj = { name: "John", age: 30 }; const jsonString = obj.toString(); console.log(jsonString);	const obj = { name: "John", age: 30 }; const jsonString = JSON.stringify(obj, null, 2); console.log(jsonStringify);
13	1	Consider the following JSON object: const jsonObject= { "name": "John", "age": 25, "city": "New York", "hobbies": ["reading", "running", "painting"] } Which of the following options correctly accesses the second hobby "running" from the above JSON object?	jsonObject.hobbies[1]	1		jsonObject.hobbies[0]	jsonObject.hobbies[1]	jsonObject.hobbies[2]	jsonObject.hobbies{"running"}
14	1	How do you represent a JSON array of objects?	{ "students": [{ "name": "Alvin", "age": 21, "city": "Mumbai" }, { "name": "Alex", "age": 24, "city": "Delhi" }] }	1		{ "students": [{ "name": "Alvin", "age": 21, "city": "Mumbai" }, { "name": "Alex", "age": 24, "city": "Delhi" }] }	{ "students": [{ "name": "Alvin", "age": 21, "city": "Mumbai" }, { "name": "Alex", "age": 24, "city": "Delhi" }] }	{ "students": [{ "name": "Alvin", "age": 21, "city": "Mumbai" }, { "name": "Alex", "age": 24, "city": "Delhi" }] }	{ "students": [{ "name": "Alvin", "age": 21, "city": "Mumbai" }, { "name": "Alex", "age": 24, "city": "Delhi" }] }
15	1	Consider the following JSON object: const jsonObject= { "name": "John", "age": 25, "city": "New York" } Which of the following options correctly accesses the value of the "age" property from the above JSON object?	jsonObject["age"]	1		jsonObject.set{age}	jsonObject.getValue("age")	jsonObject["age"]	jsonObject.value("age")

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
16	1	Identify Output const user={ "name":"XYZ", "course":["MATHS","COA","FSD-2"], "division":{ "A1":25, "B1":30, "C1":["A","B","C"]} } console.log(user.name) console.log(user.course) console.log(user.division.B1) console.log(user.division.C1[1])	XYZ ["MATHS", "COA", "FSD-2"] 30 B	1		XYZ ["MATHS", "COA", "FSD-2"] 30 B	XYZ MATHS, COA, FSD-2 30 C	XYZ MATHS 30 B	XYZ MATHS, COA, FSD-2 B1 B
17	1	Identify the output: var myJson = { 'key':'value', 'key2':'value2' }; for(var myKey in myJson) { console.log("key:"+myKey+", value:"+myJson[myKey]);}	key:key, value:value key:key2, value:value2	1		key:key, value:value key:key2, value:value	key:key, value:value key:key2, value:value2	key:key, value:value2 key:key2, value:value	key:key2, value:value key:key, value:value2
18	1	What is the value of obj in the following code? var obj = JSON.parse('{"fruit": "apple"}', function(a,b) {if(b=="apple") return "orange"; else return b;}) console.log(obj)	{ fruit: 'orange' }	1		{ fruit: 'apple' }	{ fruit: 'apple,orange' }	{ fruit: ['orange', 'apple']}	{ fruit: 'orange' }
19	1	Identify the correct output from the following code: profiledata={ "name": "yen", "age": 30, "intrest": ["travel", "science", {"movie": true}], "myobj": { "name": "nested", "age": 20 } }; obj=JSON.parse(profiledata); console.log(obj.myobj.age);	20	1	20	30	null	undefined	
20	1	Identify the correct output from the following code: profiledata={ "name": "yen", "age": 30, "intrest": ["travel", "science", {"movie": true}], "myobj": { "name": "nested", "age": 20 } }; obj=JSON.parse(profiledata); console.log(profiledata.age);	undefined	1	20	undefined	30	null	
21	1	Identify the correct output from the following code: profiledata={ "name": "yen", "age": 30, "intrest": ["travel", "science", {"movie": true}], "myobj": { "name": "nested", "age": 20 } }; obj=JSON.parse(profiledata); console.log(obj.intrest[2].movie);	true	1	false	undefined	true	Error	
22	1	Identify the correct output from the following code: profiledata={ "name": "yen", "age": 30, "intrest": ["travel", "science", {"movie": true}], "myobj": { "name": "nested", "age": 20 } }; obj=JSON.parse(profiledata); console.log(obj.intrest[0]);	travel	1	science	movie	null	travel	
23	1	let person = { name: "John", age: 25 }; Which line of code correctly updates the age to 30?	person["age"] = 30	1	person.age == 30;	person["age"] = 30	person(age) = 30	update person.age = 30	

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
24	1	Write a script of JSON array containing objects and display the same in console.		2					
25	1	Write a JSON script by entering user detail of three different person having same age group in string format method. Print the following result in object form. (1) User Details (2) Name of 2nd person and his/her age.		2					
26	1	Write a JSON script to store information related to books based on their id, topic, edition and author. (Minimum details of three books having id=1,2,3)		2					
27	1	Write a function 'FirstAndLast' that takes in an array, and returns an object with: 1) the first element of the array as the object's key, and 2) the last element of the array as that key's value. (Example input: ['ABC', 'DEF', 'Employee', 'Manager'] output: ABC : 'Manager')		3					
28	1	Write a JSON script to define Name, DOB, Age and birthplace of one person. Then print his birthdate in console as well as in chrome after clicking birthdate button.		3					
29	1	Write a script to define two JSON objects named as "division1" and "division2" having an array to store 5 names of students along with their roll number and list of subjects they opted.		3					
30	1	Write a JS to store an array of objects having height and name. display name and height of person with highest height.		3					
31	1	Write a script to define two JSON objects named as "division1" and "division2" having an array to store names of students. These name should be sorted alphabetically in the object and should be written to the file. At last, both division objects should be visible with names sorted alphabetically in file.		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
32	1	Write a JSON object which contains array of 3 objects. Each object contains 2 properties name and age. Now, sort an array values by age in descending order. Print name in terminal as per the sorted age.		5					
33	1	Write one JSON string with date property (yyyy-mm-dd) and print date in India standard time.		5					
34	1	Create a JSON object named Home Expenses in which you have to add monthly expenses of transport , food bill and names of different family members including mother,father,brother and sister.Print the expenses of father with his name.		3					
35	1	Below JSON object a is given. Print below sentence in console from the given object. Hi ! We are students of LJU . Exam - FSD2 const a = { "A" : "LJU", "B" : ["CSE", { 'M' : [{ "N" : "FSD2" } , "Exam"] }], "C" : [{ "D" : "Hi", "E" : ['are', 4, { 'F' : ['semester', 'We'] }] }], "G" : { "H" : "students", "I" : ["of", "!"] }, "J" : [{ "K" : "LJU", "L" : "FSD-2" }] }		5					
36	1	Print following statement in console from given JSON objects. const a = { "Name" : "Ramesh", "Subects" : ["Maths", "Scence", "chemistry"], "Grade" : { "Type" : "marks", "Total" : [88, 90, 99, 87] }, "Range" : { "opt" : "100", "type" : ["secure", "subject", "class"] }, "achive" : [{ "Rank" : "rank", "place" : [1, 2, 3] }, { "Ordinalindicator": "st", "12" }, "joins" : ['outof', 'got', 'and'] } Output: Ramesh got 99 outof 100 marks and secure 1st rank.		5	LJU-2025				

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-2									
37	2	which function is used to include modules in Node Js.	require()	0.5		include();	require();	attach();	None of the above
38	2	Which of the following is true about fs module of Node?	Both of the above	0.5		fs module have synchronous as well as asynchronous form	Asynchronous methods of fs module take last parameter as completion function callback and first parameter of the callback function as error.	Both of the above	None of the above
39	2	Which of the following statements are true?	js is both Server Side and Client Side Language.	0.5		js is Server Side Language.	js is the Client Side Language.	js is both Server Side and Client Side Language.	None of the above.
40	2	Identify output of following statement. console.log(pm.basename("D:/hello/abc/1.doc")); Where pm is an object of path module.	1.doc	1		D:/hello/abc	D:/hello/abc/1.doc	1.doc	doc
41	2	Which of the following options correctly demonstrates the usage of the Path module in Node.js to render only the filename including its extension?	path.basename("E:/abc/file.txt ")	1		path.fullname("E:/abc/file.txt")	path.filename("E:/abc/file.txt ")	path.name("E:/abc/file.txt ")	path.basename("E:/abc/file.txt ")
42	2	Which method is used to delete a file using the 'fs' module?	fs.unlink()	1		fs.removeFile()	fs.unlink()	fs.delete()	fs.unlinkFile()
43	2	Which of the following is an advantage of using Node.js?	It has a non-blocking I/O model	1		It is a statically typed language	It is a compiled language	It has a large standard library	It has a non-blocking I/O model
44	2	Identify the correct code which produces following output. D:/ABC/DEMO .txt abc.txt	var pm=require("path"); path1=pm.dirname("D:/ABC/DEMO/abc.txt"); console.log(path1); path2=pm.extname("D:/ABC/DEMO/abc.txt"); console.log(path2); path3=pm.basename("D:/ABC/DEMO/abc.txt"); console.log(path3);	1		var pm=require("path"); path1=pm.dir("D:/ABC/DEMO/abc.txt"); console.log(path1); path2=pm.extension("D:/ABC/DEMO/abc.txt"); console.log(path2); path3=pm.base("D:/ABC/DEMO/abc.txt"); console.log(path3);	var pm=require("path"); path1=pm.dirname("D:/ABC/DEMO/abc.txt"); console.log(path1); path2=pm.extname("D:/ABC/DEMO/abc.txt"); console.log(path2); path3=pm.basename("D:/ABC/DEMO/abc.txt"); console.log(path3);	var pm=require("path"); path1=pm.dir("D:/ABC/DEMO/abc.txt"); console.log(path1); path2=pm.ext("D:/ABC/DEMO/abc.txt"); console.log(path2); path3=pm.base("D:/ABC/DEMO/abc.txt"); console.log(path3);	var pm=require("path"); path1=pm.directory("D:/ABC/DEMO/abc.txt"); console.log(path1); path2=pm.extension("D:/ABC/DEMO/abc.txt"); console.log(path2); path3=pm.file("D:/ABC/DEMO/abc.txt"); console.log(path3);
45	2	Identify the equivalent code of given code snippet which produces same Output. var pm=require("path"); var path="D:/abc/def/jkl/some.txt"; var ans=pm.parse(path); var sep=ans.split("."); console.log("Filename="+sep[0]); console.log("Extension="+sep[1]);	var pm=require("path"); var path="D:/abc/def/jkl/some.txt"; var ans=pm.parse(path); console.log("Filename="+ans.name); console.log("Extension="+ans.ext);	1	LJU-2023, LJU-2025	var pm=require("path"); var path="D:/abc/def/jkl/some.txt"; console.log("Filename="+ans.filename); console.log("Extension="+ans.ext);	var pm=require("path"); var path="D:/abc/def/jkl/some.txt"; console.log("Filename="+ans.filename); console.log("Extension="+ans.extension);	var pm=require("path"); var path="D:/abc/def/jkl/some.txt"; console.log("Filename="+ans.filename); console.log("Extension="+pm.extname(path));	var pm=require("path"); var path="D:/abc/def/jkl/some.txt"; console.log("Filename="+ans.name); console.log("Extension="+ans.ext);
46	2	Which of the following code deletes only contents of a "example.txt" file and keeps file as it is, if something is already written in it. Deletion should result without any error.	var fs=require("fs"); fs.writeFile("example.txt", "", (err)=> {console.log(err);});	1	LJU-2023	var fs=require("fs"); fs.writeFile("", "example.txt", (err)=> {console.log(err);});	var fs=require("fs"); fs.writeFile("example.txt", "", (err)=> {console.log(err);});	var fs=require("fs"); fs.writeFile("", "example.txt", (data, err)=> { console.log(err); console.log(data);});	var fs=require("fs"); fs.writeFile("", "example.txt", (data, err)=> { console.log(data.err);});

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
47	2	What will be the output of the following code ? var pm=require("path"); ext = pm.extname("D:/LJ/abc.txt") if(ext == ".txt"){ console.log("Text Document"); }else { console.log("Not a text Document"); }	Not a text Document	1		Text Document	Not a text Document	Error:No such method named extname() exists	Error : No such method named require exists
48	2	What will be the output of the following code in console? var ps=require("fs"); ps.writeFileSync("Hello.txt","Hello ! How are you !") console.log(ps.readFileSync("Hello.txt"))	<Buffer 48 65 6e 6e 6f 20 21 20 48 6f 77 20 61 72 65 20 79 6f 75 20 21>	1		Hello ! How are you	Error"Hello.txt" doesn't exist	null	<Buffer 48 65 6e 6e 6f 20 21 20 48 6f 77 20 61 72 65 20 79 6f 75 20 21>
49	1	Which of the following options demonstrates the correct usage of the fs.readFile method in Node.js to read a file asynchronously?	fs.readFile('file.txt', 'utf-8', (err, data) => { console.log(data) });	1		fs.readFile('file.txt', (data) => { console.log(file); });	fs.readFile('file.txt', 'utf-8', (err, data) => { console.log(data) });	fs.readFile('file.txt', 'utf-8'); console.log(read);	fs.readFile('file.txt', 'this',{ console.log(file.txt[data]) });
50	2	What will be the output of following code? In "Hello.txt" file "hello students" is written. var ps=require("fs"); var data=ps.readFileSync("Hello.txt"); console.log(data); ps.readFile("Hello.txt",function(err,data){ if(err){return console.error(err); } console.log(data.toString());}); console.log("Program ended");	<Buffer 68 65 6e 6e 6f 20 73 74 75 64 65 6e 74 73> Program ended hello students	1		<Buffer 68 65 6e 6e 6f 20 73 74 75 64 65 6e 74 73> Program ended hello students	<Buffer 68 65 6e 6e 6f 20 73 74 75 64 65 6e 74 73> hello students Program ended	hello students <Buffer 68 65 6e 6e 6f 20 73 74 75 64 65 6e 74 73> Program ended	hello students Program ended hello students□
51	2	How do we get the filename portion of a path to the file in Node.js ?	path.basename()	1		path.ext()	path.basename()	path.dirname()	path.extname()
52	2	What will be the output of the following code? var ps=require("fs"); ps.writeFileSync("source.txt","Hello"); ps.writeFileSync("source1.txt","World"); data=ps.readFileSync("source.txt","utf-8"); data2=JSON.stringify(data); ps.appendFileSync("source1.txt",data2);	World"Hello"	1		Hello World	Hello	World	World"Hello"
53	2	Identify the output of last statement: var path=require("path"); let result = path.basename('/public_html/home/index.html','html'); console.log(result);	index	1		index	index.html	.html	home

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
54	2	Identify the output: var events = require('events'); var EventEmitter = new events.EventEmitter(); var myEventHandler = function (msg) { console.log('I hear a scream!'); } eventEmitter.on('scream', myEventHandler); eventEmitter.emit('scream');	I hear a scream!	1		I hear a scream!!!	I hear a scream!	I didn't hear a scream!	I hear a scream! I hear a scream!
55	2	What function is used to fire an event?	emit()	0.5		fire()	calc()	listner()	emit()
56	2	Which method is used to bind connection event with its handler?	on()	0.5		emit()	on()	event()	listeners()
57	2	Which of the following class is used to create and consume custom events in Node.js?	EventEmitter	0.5		Events	NodeEvent	Emit	EventEmitter
58	2	Identify error/output. const h=require("events"); const ee=new h.EventEmitter(); const listener=()=>=> { console.log("Thanks") } const listener2=()=>=> { console.log("Bye") } ee.on("hii",listener); ee.on("hii",listener2); console.log(ee.listenerCount("hii"));	2	1	1	2	Thanks Bye	Thanks Bye 2	
59	2	How can you check the number of listeners for a specific event in Node.js?	listenerCount()	1		getListenersCount()	countListener()	CountListen()	listenerCount()
60	2	What will be the output of following code? const EventEmitter = require('events'); var eventEmitter = new EventEmitter(); var fun1 = (msg) => { console.log("Message from fun1: " + msg); }; var fun2 = (msg) => { console.log("Message from fun2: " + msg); }; eventEmitter.on('myEvent', fun1); eventEmitter.on('myEvent', fun2); eventEmitter.removeListener('myEvent', fun2); eventEmitter.emit('myEvent', "LJU"); eventEmitter.removeAllListeners('myEvent');	Message from fun1: LJU	1		Message from fun1: LJU	Message from fun2: LJU	Message from fun1: LJU Message from fun2: LJU	Generates an Error
61	2	Which of the following best describes the Node.js event loop?	It allows Node.js to perform non-blocking I/O operations	1		It is a blocking, synchronous model	It allows Node.js to perform non-blocking I/O operations	It is used only for HTTP requests	It runs multiple threads simultaneously
62	2	Which core module in Node.js is used for handling file operations?	fs	1		path	http	fs	events

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
63	2	What command is used to install packages locally in a Node.js project using npm?	npm install package-name	1		npm start	npm install package-name	npm update	npm run
64	2	Which of the following is true about callbacks in Node.js?	They enable non-blocking asynchronous operations	1		They always block the execution flow	They are synchronous functions	They enable non-blocking asynchronous operations	They are only used for error handling
65	2	Which method of the path module returns the directory name of a file path?	path.dirname()	1		path.basename()	path.dirname()	path.extname()	path.parse()
66	2	Describe the role of the package.json file in a Node.js project and how npm manages dependencies.		3					
67	2	Explain the difference between synchronous and asynchronous methods in the fs module with an example of each.		3					
68	2	Write a Node.js program using the path module to take a file path '/user/docs/report.txt' and print: The directory name The base file name The file extension		3					
69	2	Write node.js script to copy content of one file to the other file. data should be fetched from source.txt and insert to destination.txt		3					
70	2	Write a program to demonstrate various methods of path module in Node.js.		3					
71	2	Write a Node.js program to sort an interger array, where all element are available in a file separated by white space. Print sorted array elements on node.js server.		3					
72	2	Write a node.js script to write contents to the file in original manner. Delete file after finishing writing		3					
73	2	Write a node js script to write the text "You are creating a file" to help.txt file. After that append the text "you are appending data" to same help.txt file. After that read the file and print file contents on console. After finishing read operation , print the line "Thanks for using my program" on console. write ,append,read sequence must be maintain. all read ,write and append operations are asynchronous.		4	LJU-2023				
74	2	Write a node.js script to write the text "This is data" to new.txt file. After that append the text "That is data" to same new.txt file. After that read the file & print the file content on console. After finishing read operation print the line "Thank you for using program". Write, append & read sequence must be maintained & all operations are synchronous.		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
75	2	Write a Node.js program for following action 1. Write a file having five random elements separated by white space in .txt file. 2. append sorted array of these 5 elements in same file along with message : "Sorted array:" in new line. 3. Find maximum number from that and append with message "maximum number=" in same file.		5					
76	2	Write a function 'ArrayToObject' which takes in an array of arrays, and returns an object with each pair of elements in the array as a key-value pair and store the result in one arraytoobject.txt file. Input=[['Country', 'India'], ['State', 'Gujarat'], ['City', 'Ahmedabad']] Output= { Country : 'India', State : 'Gujarat', City : 'Ahmedabad' }		5					
77	2	Write a Node.js program to CRUD operation of file management. 1) Create folder named "Hello". 2) Create file in it named abc.txt and enter data in to it. 3) Add more data at last in file. 4) Read data without getting buffer data at first. 5) rename file 6) Delete both file and folder.		5					
78	2	Write a node.js script using event handling to consider an erroneous triangle to find area. Take fix values of all three sides. (1) If any of the side is negative, then print the message "Sides must be positive" using event handler. (2) If perimeter of triangle is negative then print the message "Perimeter must be positive" using event handler. (3) Both above messages must be printed in sequence.		5	LJU-2023				
79	2	Write a node.js script to create two listeners for a common event call their respective callbacks. Print number of events associated with an emitter. Remove one of the listeners & call remaining listeners again. Print number of remaining listeners also.		5					
80	2	What do you understand by an Event Emitter in Node.js?		2					
81	2	Create an event emitter instance and register a couple of callbacks.		3					
82	2	Explain node js events with appropriate example with all event methods.		5					
83	2	Write a nodeJS script to fire an event named calculate which calculates the total marks of 5 subjects about of 25 marks and displays the total marks on console as an output. The calculate event fires another event name percentage which takes total marks as argument and percentage should get displayed in console.		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
84	2	Write a node.js script using Event handling to perform following tasks in sequence: a) Create file in it named abc.txt and enter data into it. b) Append data to that file abc.txt and print message "Data Appended Successfully". c) Read the content of the file abc.txt and print the content on http web server. d) Do all the operations of File using asynchronous file system module. And Lastly print the message "All operations performed successfully" on console.		4					
85	2	Write a NodeJS program to create a file named test.txt containing the initial text "Exam attempt ". Then, it should add three more lines to the file: "Entry 1: Pass", "Entry 2: Fail", and "Entry 3: Pass". After writing, the program must read the file and count how many times the word "Pass" appears and if the word "Pass" appears three or more times, the program should erase the content inside test.txt.		5	LJU-2025				
86	2	Write a Node.js program that uses the events module to do the following: Fire an event "welcome" that prints "Welcome to Node.js" on the console. Fire an event "time" that prints the current system time. Fire an event "bye" that prints "Goodbye!".		5					
87	2	Write a Node.js program using the events module to create an event emitter, define three events (start, process, end) that print messages to the console, and fire all three events in order.		5					
88	2	Write a script to define two JSON objects named as "division1" and "division2" having an array to store 5 integer numbers. Write this object in a file named XYZ.txt using file system. Define third array as result which gives output as explained below: Suppose first array contains base value and second array contains power value and then third array will give output as: a^b. For example: first array[0]=2 and second array[0]=3 then it should return 8 in third array[0]. Also append this result in XYZ.txt and as well as on console.		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-3									
89	3	Which of the following is used to create a new HTTP server in Node.js?	http.createServer()	1		http.createServer()	http.createServer	http.newServer()	http.newServer
90	3	<pre>const h=require("http"); const obj= { name:"Demo", age:33 } h.createServer((req,res)=> { res.end(_____); }).listen(3000);</pre> Fill in the blank in res.end() method, so that it would not generate an error.	All of the above	1		JSON.stringify(obj)	obj.toString()	""+obj	All of the above
91	3	Http module falls under which type of module?	Core	0.5		Core	Local	Global	Third party
92	3	What will be the output of the following code? <pre>var u=require("url"); var ps=require("fs"); var adr1=" http://localhost:8080/default.html?year=2025&month=feb"; var q1=u.parse(adr1,true); var qdata=q1.query; ps.writeFile("fsd2.txt",qdata,(err)=> { console.log("completed"); });</pre> ☐	It will generate an error as data must be type of string	1		fsd2.txt file will be created and in console "completed" messaged will be displayed.	fsd2.txt file will be created and in console "completed" messaged will not be displayed.	fsd2.txt file will not be created and in console "completed" messaged will be displayed	It will generate an error as data must be type of string
93	3	Which of the following NodeJS module splits up a web address into readable parts?	url module	0.5		Path module	url module	OS module	HTTP module
94	3	Identify the output: <pre>var http = require('http'); http.createServer(function (req, res) { res.writeHead(200, {'Content-Type': 'text/plain'}); res.write('Hello World!'); res.end(); }).listen(3120);</pre>	Hello World!	1		Hello World!	will print Hello World! in bold	Hello World!	Hello World!
95	3	Identify the output: <pre>var u=require("url"); var addr="http://localhost:8080/default.htm?year=2017&month=february"; var q=u.parse(addr,true); console.log(q.pathname);</pre>	/default.htm	0.5		http://localhost:8080/default.htm	/default.htm	/default.htm?year=2017&month=february	undefined
96	3	What will be the exact output of following code <pre>var u=require("url"); var addr="http://localhost:8080/sdg.htm?year=2023&month=december"; var q1=u.parse(addr,true); console.log(q1.search);</pre>	?year=2023&month=december	1	LJU-2025	/sdg.htm?year=2023&month=december',	year=2023&month=december	?year=2023&month=december	{ year: '2023', month: 'december' }

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
97	3	Identify the output: var u=require("url"); var addr="http://localhost:8080/xyz.html?name=karan&age=21"; var q=u.parse(addr,false); query=q.query console.log(query.name);	undefined	1	LJU-2023	karan	null	undefined	false
98	3	Which method of the url module parses a URL string without parsing the query string?	url.parse(url, false)	1		url.parse(url, false)	url.parse(url, true)	url.format(url)	url.resolve(base, relative)
99	3	Which object provides details about the client request?	request	0.5		response	request	server	client
100	3	What is basic routing in Node.js?	Handling different URLs with conditions	0.5		Connecting database	Handling different URLs with conditions	Creating CSS files	Reading files
101	1	Which property of the request object is commonly used for basic routing in a Node.js HTTP server?	req.url	0.5		req.method	req.headers	req.url	req.body
102	3	Which conditional structure is commonly used to implement basic routing in a Node.js HTTP server?	if...else statement	1		if...else statement	for loop	try...catch block	setInterval() function
103	3	Write a Node.js program to create an HTTP server using the http module that listens on port 3000 and displays different messages for / and /about routes. Explain how basic routing is implemented using the request object.		3					
104	3	Develop a Node.js application that parses query parameters from a URL using the url module and displays them in the browser. Demonstrate the use of url.parse() with query parsing enabled.		3					
105	3	Explain how request and response objects work in the HTTP module of Node.js. Write a short code snippet demonstrating the use of res.write() and res.end().		3					
106	3	Create a Node.js server that sends a JSON response when the user visits /api. Set the correct response headers and explain the importance of sending JSON data in web applications.		3					
107	3	Write a node.js script to print query string of URL on console as well as on file using ES6.		5					
108	3	Write a node.js script to load a simple.html file on nodejs web server & prints its contents as an html content.		5					
109	3	Explain URL module with appropriate example.		5					
110	3	What do you mean by QueryString?		2					
111	3	How JSON processing is done in node js? Explain with suitable example.		5					
112	3	Write node js script to fetch values from url given below and display output as asked. "https://www.google.com/exam.txt?c1=Hello&c2=FSD2+T1+Test&c3=Welcome+to+LJU#AllTheBest" 1) Data must be written as below in file named "exam.txt". File name must be fetched from the url given above. Output: Hello! Welcome to LJU FSD2 T1 Test #AllTheBest 2) Read content from file "exam.txt" and send response to server and display data in " /" page in same format as above but in H1 tag and in red color. 3) If any other page is requested it shows "Page not found" message in plain text.		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
113	3	Create HTTP webpage on which Home page display "Welcome to Log in page" in blue color and font size must be 32px, Login page shows one HTML file from static URL having Form with detail for Username, Password, submit and reset button, Gallery page reflect one Image "hello.jpg" and any other page shows "Page Not found". Write all necessary files to perform task. (Image already exist in same folder)		5					
114	3	Write node.js script to print "Welcome Admin" on home page of server. If user request for second page it display "This is second page" in italic font-style and if any other request is requested it shows "Page not found" message.		5	LJU-2025				
115	3	Write node.js script to print "Welcome to Home Page" with two links containing two pages named as "About Us" and "Contact Us" on home page of server. If user request for About Us page it should display "Welcome to LJ University" in bold font-style with blue color and if user request for Contact Us page it should display "Email:abc@ljinstitutes.edu.in" in italic font-style with red color if any other request is requested it shows "Page not found" message in plaintext.		5					
116	3	Write a Node.js program using the HTTP module to create a server that sends a JSON response when the user visits the /api route. The JSON object should contain: name as "Rahul", course as "NodeJS", status as "Enrolled" Set the appropriate header for JSON data and display "404 – Page Not Found" for any other route.		5					
117	3	Write a Node.js program that uses the URL module to parse query parameters from the following URL: http://localhost:3000/?name=yen&course=NodeJS The server should extract the values of name and course and display them in the browser response. Explain how the url.parse() method is used to retrieve query parameters.		5					
118	3	Write a Node.js script that uses the URL module to extract values from the following URL: https://abc.com/data.txt?m1=Congrats&m2=Node+Test&m3=Best#Done The program should fetch the file name from the URL, create a file with that name, and write the following content into the file using the values from the URL: Congrats! Node Test #Done		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD									
Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)									
Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.									
Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-4									
119	4	Which of the following are the core features of the Express framework?	All of the above.	1		It allows us to set up middleware to respond to HTTP Requests.	It defines a routing table that can work as per HTTP Method and URL.	It is used to render the HTML pages dynamically.	All of the above.
120	4	Where are the captured values populated regarding the route parameters?	req.params	1		req.data	app.locals	req.params	All of the above
121	4	Which of the following function arguments are available to Express.js Route handlers?	All of the above	1		req - the request object	res - the response object	next	All of the above
122	4	Which of the following is a middleware in Express.js?	function(req,res,next){ }	1		function(req){ }	method(req){ }	function(req,res,next){ }	method(req,res,next){ }
123	4	Which of the following function is used to specify what to do when a get request at the given route is called?	app.get(route, callback)	1		app.get(route, callback)	get(route, callback)	js.get(route, callback)	fun.get(route, callback)
124	4	Which of the following HTTP method, are used to transmit a limited amount of data, as the data is included in the header?	GET	1		GET	POST	PUT	DELETE
125	4	_____ requests are used to transmit a large amount of data, as the data is included in the body of the request?	POST	1		GET	POST	PUT	DELETE
126	4	_____ functions are those that interact with the request and response objects (req, res) during the request-response cycle?	Middleware	1		Data binding	Routing	Middleware	Forms
127	4	What is the purpose of the Express.js app.listen() function?	To start the application server	1		To start the application server	To stop the application server	To restart the application server	To connect to a database
128	4	What is the purpose of the req object in Express.js?	To represent the HTTP request	1		To represent the HTTP request	To represent the HTTP response	To store session data	To store user authentication data
129	4	What is the purpose of the res object in Express.js?	To represent the HTTP response	1		To represent the HTTP request	To represent the HTTP response	To store session data	To store user authentication data
130	4	_____ method is used to set content type in express JS. Consider res, app and expr as objects of response, express alias and express respectively.	res.set()	1		app.set()	expr.set()	res.set()	app.use()
131	1	Identify the valid signature of app.get() method. req.res and next are the objects of request, response and middleware respectively.	app.get("/",function(req,res,next){ });	1		app.get("/",function(req){ });	app.get("/",function(res){ });	app.get("/",function(req,res){ });	app.get("/",function(req,res,next){ });
132	4	What is the purpose of the Express.js res.redirect() method?	To redirect the client to a different URL	0.5		To send data back to the client	To render a view template in the application	To redirect the client to a different URL	To handle errors that occur in the application
133	4	What is to be used to display captured values route parameters?	req.params	0.5		req.data	app.locals	req.params	res.data
134	4	What is the purpose of response.render() method in express.js?	to send response back to client with a rendered template	0.5		to send response back to client with a rendered template	to update database record based on data submitted in form	to redirect client to different URL	to parse incoming request bodies and extract form data
135	4	Identify output/error from following code. uname is a name of textfield having content "xyz". response.set("content-type","application/json") response.send(' \${request.body.uname} ')	xyz	1		xyz with <h1> effect	Error as content inside send() is not a JSON object	{ uname: "xyz"}	xyz
136	4	What will be the output on /html page if following code is there. app.get('/html', (req, res) => { const html = ` <html> <head> <title>HTML Response</title> </head> <body> <h1>This is an HTML response</h1> <p>You can send HTML content using Express.js</p> </body> </html>`;`; res.send(html); });	Will give html output	1		Error : html can not be defined as variable	Error : html can not be passed directly to res.send()	Will give html output	Error : html tags should be written in one line

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
137	4	What is the purpose of req.params object in Express.js?	To store HTTP request parameters	0.5		To store HTTP request cookies	To store HTTP request headers	To store HTTP request body	To store HTTP request parameters
138	4	What is the output of the following code? app.get("/",(req,res)=> { res.set("content-type", "text/html") res.send("<p style='color:red;'>welcome everyone</p>"); });	red-colored saying "welcome everyone";	1	LJU 2025	red-colored saying "welcome everyone";	red-colored big font saying "welcome everyone";	saying "welcome everyone"	plain text saying "welcome everyone"
139	4	Give output of following code on web browser: const expr=require("express"); const app=expr(); app.get("/",(req,res)=> { res.set("content-type","text/html"); res.write("Hello world!"); res.send(" Hello from LJ "); }); app.listen(5004);	Nothing gets print (Blank page) with error in console Cannot set headers after they are sent to the client	1		Hello from LJ	Hii Hello from LJ	Hello world!	Nothing gets print (Blank page) with error in console Cannot set headers after they are sent to the client
140	4	Give output of following code on web browser: const express = require('express'); const app = express(); var st = { user: 2 } app.get('/', function (req, res) { res.write("Hello"); res.json(st.user); }); app.listen(5004);	Nothing gets print (Blank page)	1		Hello	Hello world!	Nothing gets print (Blank page)	Hello 2
141	4	const expr=require("express"); const app=expr(); const student=[{name:"ABC",age:28},{name:"PQR",age:31},{name:"XYZ",age:20}]; app.get("/",(req,res)=> { res.set("content-type","text/html"); for (x=0;x<student.length;x++) { for(j=x+1;j<student.length;j++) {if(student[x].age > student[j].age) { temp=student[x].age; student[x].age=student[j].age; student[j].age=temp; } } for(i=0;i<student.length;i++) { res.write(student[i].name+" "+student[i].age+" ") } res.send() }); app.listen(6001);	ABC 20 PQR 28 XYZ 31	1	LJU-2023	ABC 20 PQR 28 XYZ 31	XYZ 20 ABC 28 PQR 31	ABC 31 PQR 28 XYZ 20	XYZ 31 ABC 28 PQR 20
142	4	What will be the output of the following code of middleware? const cb=(req,res,next)=> { res.write(" First "); next(); } const cb1=(req,res,next)=> { res.write(" Second "); next(); } app.use("/test",cb); app.get("/test",(req,res)=> { res.write(" Third "); res.send(); });	First Third	1	LJU 2025	First Third	First Third	First Second Third	Second Third
143	4	What does the following do, app.listen(port, [callback])?	This function binds and waits for connections on the provided host.	0.5	LJU-2023	This method accepts an object as input and returns it to the requesting client.	This method specifies what to execute when a get request at the specified route is made.	This method is used to transmit a limited amount of data.	This function binds and waits for connections on the provided host.

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
144	4	write an express.js script to load an HTML file having username and password and submit button. On clicking submit button. It should jump on "check" page using "POST" method. If username is "admin" , then jump on next middleware to print "welcome... admin" , if username is not "admin" , then stay on same middleware to print "warning msg" in red color.		5					
145	4	write an express.js script to print "hello World" also run on localhost:4000		3					
146	4	write an express.js script to use of routing method using home , about , contact , temp page and print message. /home- welcome to my home page , /about -welcome to my about page, /contact-welcome to my contact page ./temp - welcome to my temp page		5					
147	4	write an express.js script to make one index.html file in this file we write simple heading tag and make one css file index.css put style using appropriate selector and link with js file and show output on localhost:3030.		5					
148	4	write an express.js to implement a form that allows users to submit data via POST request. Write code to create a route that handles the POST request and logs the submitted data to the console.		5					
149	4	how can you create and use a middleware function in express js?		3					
150	4	write an express js to link html , css and js file and show one image o.jpg. And also show the description of image.		3					
151	4	using Express js make student information form only two fields like name and mobile no and send data on console after submitting "submit" button		5					
152	4	Write an ExpressJS to take a textarea & submit button. After clicking submit button the content of textarea should be represented on next page by writing each sentence (separated by dot) in new line.		5					
153	4	Write an expressJS code which loads login.html file upon browsing localhost:3010. The Login.html file contains input for username,password and two checkboxes named remember and subscribe,on submitting the file it should go to /data page where username,password and selected checkboxes are pnted,in addition to that a logout button should be there,onclicking this button it should go back to home page "localhost:3010"/.(GET/POST any method can be used)[Write all necessary files code]		5					

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
154	4	Write an express.js script to define one JSON array of 3 objects having members 'name' and 'height'. height must be sorted descending order according to name.		3					
155	4	Write an express.js script to define one JSON array of 3 objects having members 'name' and 'score'. score must be sorted descending order according to name.		3					
156	4	Write an express js script to link html , css and js file to show message "LJ University with a difference" with font size 50px and color "blue".		2					
157	4	Write an ExpressJS to take a UserName, Password, Textarea for "message" & submit button using get method. 1) After clicking submit button the content of submitted details should be represented on "/login" page along with one "show vowel" link. 2) By clicking "show vowel" link count of vowel used in submitted "message" will display on "/message" page. (Use next() to route page)		5					
158	4	Write an express.js script to print "The Pacific Ocean is the largest and deepest of the world ocean" also run on appropriate localhost.		2					
159	4	Write expressJS script to perform task as asked: (A) Create one HTML file which contains text-field named username, one dropdown which contains options of country like India, USA, Canada, Australia. & one submit button. (B) Once user clicked on submit button it will jump to next page than username & You are from "country name" which ever selected from drop box should be printed. (C) Use get method to request data.		4	LJU-2023				
160	4	what is middleware in express js? And how is it used in handling HTTP request?		2					
161	4	how to link html,css and js file in express js give any short example for it		2					
162	4	Write an ExpressJS application that creates a login form containing fields for username and password along with a submit button. The form data should be sent to the server using the POST method. Implement an authentication middleware that checks whether the entered username is "admin" and the password is "1234". If the credentials are correct, the application should display the message "Login Successful". Otherwise, it should display "Invalid Credentials".		5					
163	4	Write an ExpressJS application that creates an HTML form containing two text fields named name and age, along with a submit button. When the user submits the form, the data should be sent using the GET method. After submission, the application should redirect to a new page and display the message: "Hello <name>, your age is <age>", where the values are taken from the form input.		5					
164	4	how to send HTML and JSON data as a Response using Express js.		2					

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-5									
165	5	Which HTTP method is typically used for retrieving data from a RESTful API in Express.js?	GET	1		GET	PUT	POST	DELETE
166	5	Which of the following is a middleware that parses cookies attached to the client request object?	cookie-parser	1		cookie	cookies	cookie-parser	None of the above
167	5	Identify the correct code snippet to store passed "name" parameter to cookie, which expires after closing browser and terminate by printing "Done".	const username=req.query.name; res.cookie("uname",username); res.send("Done");	1	LJU-2025	const uername=req.query["name"]; res.cookie("uname",username); res.send("Done");	const username=req.query.name; res.cookie("uname",username); res.send("Done");	const username=req.query["name"]; res.cookie("uname",username,{expires:new Date(Date.now()+1000)}); res.send("Done");	const username=req.query.name; res.cookie("uname",username,{expires:new Date(Date.now()+1000)}); res.send("Done");
168	5	Consider following HTML file with 4 choices using checkboxes. Identify the correct option to retrieve values of all selected checkboxes after clicking submit button. <form action="http://localhost:6001/process_post" method="post"> <input type="checkbox" name="sports" value="Hockey"/>Hockey <input type="checkbox" name="sports" value="Cricket"/>Cricket <input type="checkbox" name="sports" value="Football"/>Football <input type="checkbox" name="sports" value="Volleyball"/>Volleyball</form>	sports=req.body.sports; res.write('Sports=\${sports}');	1	LJU-2025	sports=req.body.sports; res.write('Sports=\${sports[0]}');	sports=req.body.sports; res.write('Sports=\${sports}');	sports=req.query.sports; res.write('Sports=\${sports}');	sports=req.query.sports[0]; res.write('Sports=\${sports}');
169	5	Which of the following is the correct syntax for setting a cookie in Express.js?	res.cookie('cookieName', 'cookieValue')	1		res.cookies('cookieName', 'cookieValue')	req.cookies('cookieName', 'cookieValue')	res.cookie('cookieName', 'cookieValue')	app.cookies('cookieName', 'cookieValue')
170	5	Identify the method to destroy the cookie from browser.	response.clearCookie("CookieName")	0.5	LJU 2025	response.destroyCookie("CookieName")	response.clearCookie("CookieName")	request.clearCookie("CookieName")	request.destroy("CookieName")
171	5	Which method should be used to destroy a session and remove session data in express-session?	req.session.destroy()	0.5		req.session.destroy()	req.session.remove()	req.session.clear()	req.session.delete()
172	5	Identify the correct syntax for setting a cookie with expiry time in Express JS ?	res.cookie('Name', 'Value', { expires: new Date(Date.now() + 86400000) });	1		res.cookie('Name', 'Value', { expires: new Date(Date.now() + 86400000) });	res.cookie('Value', 'Value', { maxAge: 86400000 });	res.cookie('Name', 'Value', { maxAge: 86400000 sec });	res.cookie('Name', 'Value', { maxAge:(Date.now() + 86400000) });
173	5	Select correct output/error option of below code. app.get('/cookie', function(req, res){ res.cookie('name', 'express'); //Sets name = express //req.cookie('ID','2',{ maxAge: 2000}); res.cookie('email', 'express@gmail.com'); res.clearCookies('email'); res.send(req.cookies); });	It will give an error regarding clearcookies function.	1		It will display json object of name, id and email in browser.	It will give an error regarding clearcookies function.	It will display json object of name and id in browser. And Id will not be expired in 2 seconds.	It will give an error regarding req.cookie function.
174		_____ are little pieces of information transmitted from a website and kept in the user's web browser when the user visits that page.	Cookies	1		Session	Cookies	Forms	parameters
175	5	Which of the following is the correct syntax for setting up a session in Express.js using the express-session middleware?	const session = require('express-session'); app.use(session({secret: 'mySecret'}));	1		const session = require('express-session'); app.use(session({secret: 'mySecret'}));	const session = require('express-session'); app.session({secret: 'mySecret'});	const session = require('express-session'); app.session(session({secret: 'mySecret'}));	const session = require('express-session'); app.use(session({session: {secret: 'mySecret'}}));
176	1	How can you set a cookie with an expiration based on maxAge using express.js?	res.cookie(name, value, {maxAge: milliseconds})	1	LJU 2025	res.setCookie(name, value, {maxAge: milliseconds})	res.cookie(name, value, {maxAge: milliseconds})	res.sendCookie(name, value, {maxAge: milliseconds})	res.cookie(name, value, {expires: date})
177	5	How do you retrieve the value of a cookie in Express.js?	Using the req.cookies object	1	LJU 2025	Using the req.value() method	Using the req.cookie() method	Using the req.cookies object	Using the req.body object
178	5	Identify the correct URL to fetch a JSON object named items having record_id=12 using RESTful API.	http://localhost:8000/items/12	0.5		http://localhost:8000/items	http://localhost:8000/	http://localhost:8000/items/record_id=12	http://localhost:8000/items/record_id:12
179	5	Which of the following is an example of a route parameter in Express.js?	/users/:id	1	LJU-2023	/users	/users/:id	/users/send	/users/delete

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
180	5	REST stands for.....	Representational State Transfer	0.5		Resource State Transfer	Request State Transfer	Remote Service Transfer	Representational State Transfer
181	5	Which method of request.cookies attribute is used to read a cookie?	get()	1	LJU-2023	set()	get()	read()	cp()
182	5	Which middleware is used in Express to serve static files like CSS, images, and JS?	express.static()	1		express.static()	express.json()	express.router()	app.listen()
183	5	Cookies in Express are used to:	Store small pieces of data on client side	1		Store large files	Store data permanently in database	Store small pieces of data on client side	Compile middleware
184	5	Which module is commonly used in Express to manage sessions?	express-session	1		fs	express-session	path	url
185	5	Which is correct syntax for HTML form using POST method?	<form method="POST">	1		<form type="POST">	<form method="POST">	<form action="POST">	<form send="POST">
186	5	Which syntax defines a GET route in Express (REST API)?	app.get("/users", (req,res)=>{});	1		app.GET("/users", function(req,res){});	app.get("/users", (req,res)=>{});	app.route.GET("/users");	express.get("/users");
187	5	Which syntax enables CORS in Express?	app.use(cors());	1		app.cors();	express.cors();	app.enable(cors);	app.use(cors());
188	5	Which syntax correctly defines a RESTful DELETE route with parameter id?	app.delete("/users/:id", (req,res)=>{});	1		app.delete("/users/id", ()=>{});	app.remove("/users/id", ()=>{});	app.delete("/users/:id", (req,res)=>{});	app.destroy("/users/:id");
189	5	Which syntax correctly initializes express-session?	app.use(session({ secret: "mySecret", resave: false, saveUninitialized: true }));	1		app.use(session({ secret: "mySecret", resave: false, saveUninitialized: true }));	app.session("mySecret");	express.session({ key: "mySecret" });	session.start("mySecret");
190	5	Which syntax correctly redirects after successful form submission?	res.redirect("/dashboard");	1		req.redirect("/dashboard");	redirect("/dashboard");	res.redirect("/dashboard");	res.move("/dashboard");
191	5	What does CORS stand for?	Cross Origin Resource Sharing	1		Cross Origin Resource Sharing	Common Origin Resource Sharing	Cross Order Request Sharing	Client Origin Response System
192	5	Which syntax correctly sets and reads cookie?	res.cookie("role","admin"); console.log(req.cookies.role);	1		res.cookie("role","admin"); console.log(req.cookies.role);	req.cookie("role","admin");	app.cookie("role","admin");	res.set("role","admin");
193	5	What is the purpose of the Express.js res.redirect() method?	To redirect the client to a different URL	1		To render a view template in the application	To send data back to the client	To redirect the client to a different URL	To handle errors that occur in the application
194	5	In an ExpressJS application, where can you retrieve the dynamic parameter id from the route /user/:id?	req.params.id	1		req.body.id	req.query.id	req.params.id	req.header.id
195	5	Identify correct syntax to handle route parameter and query parameter together: URL → /users/10?active=true	app.get("/users/:id", (req,res)=>{ const id = req.params.id; const active = req.query.active; });	1		app.get("/users/:id", (req,res)=>{ const id = req.params.id; const active = req.query.active; });	app.get("/users/id", (req,res)=>{ const id = req.query.id; const active = req.params.active; });	app.get("/users", (req,res)=>{ const id = req.body.id; });	app.get("/users/:id?active=true", ()=>{});
196	5	Process a form using post method. Form has fields like username, password, confirm password, gender, submit and reset buttons. After entering all fields, If password and confirm password matches, then form should be processed and all relevant and selected fields' values should be printed. Otherwise, by printing warning message in red color, it should terminate. No need to write file having form elements.		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
197	5	write a script to meet foll requirements. 1) create index.html page and open it on localhost 2) after clicking submit button, it should jump to savesessionpage.store username in session. 3) After saving session, redirect to fetchsession page and read session value. put a logout link button here. 4) destroy the session on this page and redirect to index.html		5	LJU-2023				
198	5	Write a script to meet following requirement using ExpressJS. 1. Create index.html which contains login page having fields like Username, Password & Gender. Open it on localhost. 2. After clicking on submit button, it should jump to savesession page. store username & gender in session. 3. After saving session, redirect to fetchsession page and read session values. Put a logout link button here. 4. After clicking logout button, it jumps to deletesession page. 5. Destroy the session on this page & redirect to index.html page.		5					
199	5	How to implement search and filtering in a REST API with Express.js ?		5					
200	5	You have been assigned to develop a user feedback form for a website using Express.js and cookies. Implement the following requirements: Process a form with the following fields: Name, Email , Message , Rating (radio buttons: Bad, Average, Good, Very Good, Excellent) When the user submits the form, store their feedback information (name, email, message, and rating) in a cookie named "feedback" that expires in 10 seconds. Display a confirmation message to the user after successfully submitting the form & Create a link to display the feedback details stored in the "feedback" cookie. When the user click to the link, retrieve the feedback information from the cookie and display it on the page also include a link on the feedback details page to Logout. When the user clicks the link, user redirected to home page. Make app.js file use get method in express js. No need to write html file having form elements.		5					
201	5	write express script to maintain session and print how many times user visit the page. For ex., if user visit first time ,"you have visited page First time" message will print. if user visit second time ,"you have visited page second time" message will print. and so on		3					
202	5	Write an express.js script to define 2 pages. 1st page has username and password. Store this username to cookie on 2nd page. Cookie must stay live for 1 day.		2					
203	5	Write express js script to perform tasks as asked below. 1. Create one HTML file which contains two number type input fields, one dropdown which contains options to select like (addition, subtraction, multiplication, division) and one submit button. 2. The input fields must contain the value greater than 0 else it will give a message "Please enter the valid number". Also, user must select any type of formula from the dropdown else give a message "You have not selected any formula". (Message will be displayed on "/calc" page.) 3. If one formula is selected and numbers are entered then Both numbers should be stored in cookies which expires in 50 seconds. Respective calculations will be performed on the page "/calc".		5					
204	5	give example of cookies. create cookies and delete cookies.		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
205	5	Write an ExpressJS script using RESTapi to create one array of json object named student_result which have properties like Name, Roll_no, Division, Percentage & Grade. Once user request for "/result" page it displays all student's data. If user request for particular Roll_no then respective students data will display i.e. if user request for "/result/2" then data of Roll_no 2 will display.		5					
206	5	Write an ExpressJS REST API script to create an array of JSON objects named employee_data having properties: Emp_id Name Department Salary Experience When the user requests: /employees → It should display all employees data. /employees/:id → It should display data of the employee whose Emp_id matches the given id. Example: /employees/3 → Display data of employee with Emp_id 3.		5					
207	5	Write an ExpressJS script to perform the following tasks: Create one HTML file that contains: Product Price (number input) Discount Percentage (number input) One dropdown (Festival Offer, Seasonal Offer, Clearance Sale) One submit button Validation Rules: Price and Discount must be greater than 0 Otherwise display message: "Enter valid price and discount" User must select an offer from dropdown Otherwise display: "Please select an offer type" (Messages will be displayed on /discount page)		5					
208	5	create a user signup form using Express.js and cookies. Implement the following requirements: Create a form with the following fields: o Name (input field) o Email (input field) o Gender (radio buttons: Male, Female, Others) o Submit button When the user submits the form, store their information (name, email, gender) in a cookie named "registered" that expires in 15 seconds. Display a confirmation message to the user after successfully submitting the form & Create a link to display the details stored in the "registered" cookie. When the user clicks to the link, retrieve the information from the cookie and display it on the /details page also include a link on the /details page to Logout. When the user clicks the link, user redirected to home page. Use post method.		5	LJU 2025				

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-6									
209	6	Which HTTP method is typically used for file uploads in web applications?	POST	0.5		GET	PUT	POST	DELETE
210	6	Identify correct statement/statements to set constraint of file size up to 1 KB during file upload.consider JSON code inside multer callback.	const maxsize=1*1024; limits: {fileSize:maxsize}	1		const maxsize = 1*1024; limits:maxsize	const maxsize=1*1024; limits: {fileSize:maxsize}	const maxsize=1*1024*1024;limits: {fileSize:maxsize}	const maxsize=1*1024*1024; limits:maxsize;
211	6	Identify correct specification of <form> tag to upload a file.	<form action="upload" method="post" enctype="multipart/form-data">	0.5	LJU 2025	<form action="upload" method="get" enctype="multipart/form-data">	<form action="upload" method="post" enctype="multipart/form-data">	<form action="upload">	<form action="upload" method="post">
212	6	Which of the following is the correct syntax to upload specific size file for defined variable as: Var maxSize=1*1024*1024	limits: {fileSize:maxSize}	1	LJU-2023	limits: {size:maxSize}	limit:maxSize	limit: {file:maxSize}	limits: {fileSize:maxSize}
213	6	Which middleware is commonly used in Express.js to handle file uploads?	multer	0.5		body-parser	multer	express-fileupload	connect-multiparty
214	6	Which event is emitted by Multer when a file upload is completed successfully?	'upload'	0.5		'upload'	'file'	'complete'	'finish'
215	6	_____ method is used to prepare storage of a file after uploading	multer.diskStorage()	0.5		multer.disk()	multer.diskStorage()	multer.keepStorage()	path.keepStorage()
216	6	What is the correct syntax for configuring disk storage for file upload using Multer in Express.js?	multer.diskStorage({ destination: 'uploads/', filename: (req, file, cb) => { cb(null, file.originalname); }, })	1		multer.diskStorage({ destination: 'uploads/', filename: (req, file, cb) => { cb(null, file.originalname); }, })	multer.diskStorage({ path: 'uploads/', filename: (req, file, cb) => { cb(null, file.originalname); }, })	multer.diskStorage({ folder: 'uploads/', filename: (req, file, cb) => { cb(null, file.originalname); }, })	multer.diskStorage({ dest: 'uploads/', filename: (req, file, cb) => { cb(null, file.originalname); }, })
217	6	Which attribute is used to filter specific file in choose files dialog box?	accept	0.5	LJU-2023	type	method	filter	accept
218	6	Which module is required to send an email in Express.js?	Nodemailer	1		Nodemailer	Express-mailer	NodeMail	Express-sendmail
219	6	Which of the following is the correct way to handle errors that occur during the email sending process in Express.js?	Using the .catch() method on the nodemailer promise	1		Using a try-catch block	Using the .catch() method on the nodemailer promise	Using the .then() method on the nodemailer promise	Using the .finally() method on the nodemailer promise
220	6	What is the correct syntax to send HTML formatted text in your email?	var mailOption={ from:"abc@gmail.com", to:"xyz@gmail.com", subject:"test mail", html:" its easy " }	1		var mailOption={ from:"abc@gmail.com", to:"xyz@gmail.com", subject:"test mail", text:" its easy " }	var mailOption={ from:"abc@gmail.com", to:"xyz@gmail.com", subject:"test mail", html:" its easy " }	var mailOption={ from:"abc@gmail.com", to:"xyz@gmail.com", subject:"test mail", text:"its easy" }	var mailOption={ from:"abc@gmail.com", to:"xyz@gmail.com", subject:"test mail", content_type:"text/html", content:" its easy " }
221	1	Which method is used to send an email using Nodemailer?	trans.sendMail()	0.5		trans.createMail()	trans.sendEmail()	trans.composeEmail()	trans.sendMail()
222	6	_____ is a template engine for JavaScript that is used for web development which allows users to generate dynamic HTML markup using JavaScript code within HTML templates.	EJS	0.5		MongoDB	Express.js	EJS	Multer
223	6	Which Express.js method is used to render an EJS template?	res.render()	0.5		res.send()	res.render()	app.use()	res.json()

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD									
Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)									
Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.									
Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
224	6	Which tag is used in EJS for writing JavaScript logic without displaying output?	<% %>	0.5		<%- %>	<% %>	<script> </script>	<%= %>
225	6	Which Express code correctly sends name = "Priya" to an EJS template?	res.render("index", { name: "Priya" })	0.5		res.send("Priya")	res.render("index")	res.render("index", { name: "Priya" })	app.use("Priya")
226	6	Which configuration is necessary to use EJS as a template engine in Express?	app.set("view engine", "ejs")	0.5		app.set("template", "ejs")	app.set("view engine", "ejs")	app.engine("ejs")	app.use("ejs")
227	6	Write an express.js script to upload image.		5					
228	6	Write a code to implement file uploading and downloading with Express ?		5					
229	6	Write a code to upload file and access uploaded file in express js.		3					
230	6	Write an express JS script to upload any type of file of size up to 50KB only.		3					
231	6	Write a code snippet to configure the multer middleware to store uploaded files in a specific directory called "uploads"		5					
232	6	Create an Express.js route that accepts file uploads using the multer middleware and resizes and saves the uploaded image in multiple sizes (e.g., small, medium, large) to a specific directory on the server.		5					
233	6	Write an express js script that allows only image type file to be uploaded using the multer middleware and saves the file to the specific directory called "IMAGES". If file other than image has been uploaded then it will give an error message that "Upload only image file".		4					
234	6	Write express js script to upload file with size limit of 1 MB to a specific directory named "Data" on the server.		5					
235	6	Write an express js script to configure the multer middleware. Perform following tasks. 1) Create a html form file named "form.html" in public folder. This file contain centrally oriented heading(h3) "Upload your File" in red color with background-color aqua. Along with choose file option(to browse and select file) and submit button(to upload the file). (Must use external css having name "effect.css" in public folder) 2) Create a js file to show result after uploading any type of file, message should be displayed on "upload" page "(file original name) has been uploaded".(Css effect must include while running js code) 3) Save uploaded files to specific directory named "File". And in this folder file must be stored in format of "data-file.pdf" where "data" is the field name.		5	LJU 2025				
236	6	Write an express.js script to send automatic mail to specified user.		7	LJU-2023				
237	6	Write a code to set up nodemailer in Express.js?		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
238	6	Perform the following tasks as asked: 1) Create a HTML file for response form and this file should be loaded on home("/") page. •Fields are : Name, Email and Submit button. 2) Once Response is submitted, message "Thank you for your response." Will be displayed on page '/response' and also send mail to the entered email id with the submitted response.		3					
239	6	Write a code to set up nodemailer in Express.js. Sender email id: "lju@gmail.com". Receiver email ids: "student@gmail.com and faculty@gmail.com". Mail subject should be "LJ University" Mail body contains "Welcome Student" in h3 tag and in table display data Date 28/06/23, Exam name FSD-2.		4					
240	6	Write an Express.js application to configure the Multer middleware to upload a file. Perform the following tasks: 1) Create an EJS file that displays a heading "Upload Document" and contains a form with: -One file input field -One submit button 2) Render this EJS file on the /home route. 3) Configure Multer to store uploaded files in a folder named uploads. 4) After successful upload, display a message on the /upload route showing the original name of the uploaded file.		5					
241	6	Write an Express.js application to perform the following tasks: 1) Create an EJS file named contact.ejs that displays a heading "Contact Form" and contains a form with: -Text input for Name -Email input for Email -Submit button 2) Render this EJS file on the /contact route. 3) Handle form submission using the POST method on the /submit route. 4) After form submission, display a message on the browser in the format: "Thank you (Name), we have received your email (Email)."		5					
242	6	Write an Express.js code to send a mail. Create one html file which has one email field and one submit button. Fetch the email address from email field and send a mail to that email address. Mail subject should be "Exam Timetable". Mail body contains "L J University" in h3 tag and display data (Date 21/05/25, Exam name FSD-2) in table.		5	LJU 2025				

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-7									
243	7	Correct the following code : function App() { const abc="Hello"; return (<div className="App"> <h1 style={{backgroundColor:"red"}}> Friends {2+2} </h1> <Example frame=abc age="30"/> </div>); } export default App;	<pre>{} missing at : <Example frame={abc} age="30"/></pre>	1		Quotes missing at : <Example "frame"= abc "age"="30"/>	\$ missing at : <h1 style={{backgroundColor:"red"}}> Friends \${2+2} </h1>	Quotes missing at : <h1 style={{"backgroundColor":"red"}}> Friends {2+2} </h1>	<pre>{} missing at : <Example frame={abc} age="30"/></pre>
244	7	What output will be generated by following program. Example.js import React from 'react' const Example = (Props)=>{ return({Props.Name} : {Prop.Price}); } export default Example; App.js import Example from "./Example"; function App() { return (<Example Name="Mobile" Price="20000" />);}export default App;	It will give an error regarding prop	1		Mobile : 20000	Mobile 20000	It will give an error regarding prop	Nothing will be printed.
245		Which command is used to create a React app using Vite?	npm create vite@latest myApp	1		npx create-react-app myApp	npm init react-app	npm create vite@latest myApp	vite create react
246		One key advantage of Vite over traditional bundlers is:	Faster development server startup	1		Slower startup time	Faster development server startup	Built only for backend projects	No support for modern frameworks
247		What is Vite mainly used for?	Frontend build tool and development server	1		Database management	Frontend build tool and development server	used for operating system features	none of these
248	7	What will be the output of following program? import React from 'react'; function App() { const handleClick = () => { alert ("Welcome to LJU"); } return (<center> <button onClick={handleClick}>Click me</button> </center>); } export default App;	It will show an alert box once page will be loaded for first time, and it will perform nothing while clicking on button	1	LJU-2023	By clicking on click me button it will show an alert box	It will show an alert box once page will be loaded for first time, and it will perform nothing while clicking on button	It will perform nothing	It will show an error.
249	7	What will be the correct syntax to perform any fuction on double click in REACT?	<pre><button onDoubleClick = {doubleClickHandler}>Double Click here</button></pre>	1		<pre><button oubleClick = {doubleClickHandler()}>Double Click here</button></pre>	<pre><button ondoubleClick = {doubleClickHandler}>Double Click here</button></pre>	<pre><button onDoubleClick = {{doubleClickHandler}}>Double Click here</button></pre>	<pre><button onDoubleClick = {doubleClickHandler}>Double Click here</button></pre>
250	7	Which of the following port is the default where react server runs?	3000	0.5		8080	3000	3030	3080
251	7	What are arbitrary inputs of components in react also known as?	Props	0.5		elements	Props	Ref	Keys
252	7	Select correct syntax to render output with "LJU" heading and textfield.	<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"/> </></pre>	1		<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"/> <div></div></pre>	<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"/> </></pre>	<pre><div></div> <h1>LJU</h1> <input type="text" className="demo"> </></pre>	<pre><h1>LJU</h1> <input type="text" className="demo"/> </></pre>
253	7	What will be the output of the following program? const x = 9; let text = "Welcome"; x = 10; if (x <= 10) { text = "Welcome To LJU"; } return ({text})	Error will be generated	1		Welcome To LJU	Error will be generated	Welcome	x=10

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
254	7	Correct syntax to write Arrow function Msg = ____ "Hi, there!";	() =>	0.5		> () =	() =>	() =	> () =>
255	1	Identify error/output in following code of App.js file. const arr=[10,20,30,40,50]; let sum=0; return({ arr.map(v) => { sum=sum+v; return sum = {sum} } });	Sum is printed correctly for each iteration in <h1> tag	1	LJU-2023	error, since sum=sum+v statement must be specified using JSX	Sum is printed correctly for each iteration in <h1> tag	error, since let sum=0 statement is specified at wrong place	sum is printed as "NaN" for each iteration in<h1> tag
256	7	Which is the correct syntax to get output of expression between HTML tags	const a=1; const b=1; return({a+b})	1		const a=1; const b=1; return({{a+b}})	const a=1; const b=1; return({a+b})	const a=1; const b=1; return({{a+b}})	const a=1; const b=1; return([a+b])
257	7	What will be the output of the following program? App.js import Example from './Example'; function App() { const Info = { name: "ABC" }; return (<div><h1>What is your name?</h1><Example name={ Info }></div> </div>); } export default App; ----- Example.js import React from 'react' function Example(props) { return(<h2>My name is { props.name.name }!</h2> </div>); }; export default Example;	What is your name? My name is ABC!	1		What is your name?	What is your name? My name is ABC!	My name is ABC!	Error will be generated
258	7	What will be the output of below program? App.js import {BrowserRouter,Route,Routes} from "react-router-dom"; import contact from './Contact' function App() { return (<div> <Navbar> <BrowserRouter> <Routes> <Route exact path="/Contact" element={}<contact> } /> </Routes> </BrowserRouter> </div> </div>); } export default App	SyntaxError	1		It will give an error as <BrowserRouter> tag is used in place of <Router> tag.	SyntaxError	It will run properly	It will not throw an error but wont display anything.
259	7	How many numbers of elements a valid react component can return?	1	0.5		Multiple	1	Not more than two	Null
260	7	What is the declarative way to render a dynamic list of components based on values in an array?	Using the Array.map() method	0.5		Using the reduce array method	Using the <Each /> component	Using the Array.map() method	With a for/while loop
261	7	In which of the following directory React.js components can be saved?	Inside the src folder	0.5		Inside the vendor folder	Inside the src folder	Inside the public folder	Inside the node modules
262	7	What will be the output of the following code? App.js import Example from './Example'; function App() { return (<div className="App"> <Example frame="A" + " B" + " C"/> </div> </div>); } export default App; ----- Example.js import React from 'react' const Example = (props) => { return (<div> <h1>Friends:{props.frame}</h1> </div> </div>); } export default Example	Error will be generated	1		Error will be generated	Friends : A B C	Friends:ABC	Friends:A+B+C

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
263	7	What will be the output of following code? App.js import Example from './Example'; function App() { const abc="LJU"; return (<div className="App"> <Example frame={abc} age="30"/> </div>);}export default App; Example.js import React from 'react' const Example = (p) => { return (<div> <h1>{p.frame}</h1> <h1 style={{backgroundcolor:"blue"}}>age</h1> </div>)}export default Example	LJU age	1		LJU Display "age" with blue background color	LJU Display "30" with blue background	LJU 30	LJU age
264	7	How to write comments in JSX?	{/* */}	0.5		{/* */}	{/* */}	{/* */}	{/* */}
265	7	What will be the output of following code. New.js import React from 'react'; import img1 from './P.jpg'; import img2 from './R.jpg'; const New = () => { const images=[{ id:1,pic:img1 }, {id:1,pic:img2}]; return ({images.map((val) => { return () }}))}export default New App.js import New from './New'; function App() { return (<New />);}export default App;	2 Images will be displayed vertically on browser.	1		It will display 2 images side by side on browser	It will only display first image on browser	2 Images will be displayed vertically on browser.	It will only display last image on browser.
266	7	Consider following code for App.js file. Identify error/output. function App(){ return(This is Demo1 This id Demo2); }export default App;	Error as JSX fragment tag must required	1		This is Demo1 This is Demo2	This is Demo1	This id Demo2	Error as JSX fragment tag must required
267	7	Consider following code in App.js file and Example.js file. Identify error/output import Example from './Example'; function App() {const obj= { type:"car",models:["i10","i20","Grandi10"] } const string=JSON.stringify(obj); return(<Example name={obj}/>)} export default App; Example.js const Example = (props)=>{ return({props.name.type}) } export default Example	"car" is printed successfully by referring props.name.type	1		"car" is printed successfully by referring props.name.type	Error as props.name.type is invalid use of props to refer type	Error since type must be fetched by passing "string" rather than "obj"	Error as JSON object can not be passed to other component.i.e. "Example"
268	7	What will following code do? const arr=['A','B','C','a','b'] const newArr=arr.filter((value)=>{ if(value===value.toUpperCase()) return false; else return true; })	Returns array having only small letters	1		Returns array having only capital letters	Returns empty array	Returns array having only small letters	Error as not proper use of ' toUpperCase()

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
269	7	Fill the blanks in following code to generate proper output. New.js import React from 'react'; import img1 from './P.jpg'; import img2 from './R.jpg'; const New = () => { const images=[{ id:1,pic:img1 }, {id:2,pic:img2}]; return ({_____map((val) => { return () }) }; export default New;	images_src={val.pic}	1		images, src={ {val.pic} }	img_src={val}	images_src={val.pic}	img_src="val.pic"
270	7	What will be the output of the following code : const arr=["a","java","Full Stack","567","Python"]; return map function { arr.map((value)-> {return array values= {value.toUpperCase()} }} }	map function array values= A array values= JAVA array values= FULL STACK array values= 567 array values= PYTHON	1		map function array values= A array values= JAVA array values= FULL STACK array values= 567 array values= PYTHON	A JAVA FULL STACK 567 PYTHON	Error:567 can't be added in list	Error:all inputs should be of type in array
271	7	Identify correct statement to apply CSS on a paragraph. The CSS is given as below. const css= { color:"cyan", textAlign:"center", backgroundColor:"red" }	<p style={css}>This is my data</p>	0.5		<p style={ {css} }>This is my data</p>	This is my data	<p style={css}>This is my data</p>	<p style=[css]>This is my data</p>
272	7	Identify error/output for following code. const arr=[10,2,30,3,50]; const newArr=arr.filter(v)-> { if(v%10===0) { return false; } else { return true; } } let arr1=newArr.join(",") function Form1() { return ({arr1}) }	2,3	0.5	10,30,50	10	10,2,30,3,50	2,3	
273	7	Identify correct code to change CSS, attributes of a paragraph & text on double click.	function changeCssAttr(e) { e.target.innerHTML="Thanks buddy"; e.target.style.fontFamily="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	1		function changeCssAttr(e) { e.target.value="Thanks buddy"; e.target.style.fontFamily="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	function changeCssAttr(e) { e.target.value="Thanks buddy"; e.target.style.font-family="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	function changeCssAttr(e) { e.target.innerHTML="Thanks buddy"; e.target.style.font-family="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)	function changeCssAttr(e) { e.target.innerHTML="Thanks buddy"; e.target.style.fontFamily="times new roman"; e.target.align="center"; } return (<p onDoubleClick={changeCssAttr}>This is my para</p> </>)
274	7	What will be the output of below program? App.js import {Router,Route,Routes,Link} from "react"; import CA from './CA' function App() { return (<Router> <Routes> <Route path="/CA" element={ <CA/> }/> </Routes> </Router>) }export default App	Cause of error is Router/Route/Routes/Link is imported from react	1	LJU 2023	It will give an error as <BrowserRouter> tag is not used	Reached at the end- no executable code	It will run properly	Cause of error is Router/Route/Routes/Link is imported from react
275	7	In ReactJS, to filter an array of objects named "dataArr" based on a specific condition, which of the following options shows the correct syntax?	dataArr.filter(item => item.id === 1)	1	LJU 2023	dataArr.filter(item => item.id === 1)	this.filterData(dataArr, item => item.id === 1)	filterData(dataArr, item => item.id === 1)	this.state.dataArr.filter(item => item.id === 1)

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
276	7	In a React application, a parent component ParentComponent is passing a prop called username to its child component ChildComponent. Which of the following options correctly accesses and displays the username prop in the ChildComponent?	<code><p>{props.username}</p></code>	1	LJU 2023	<code><p>{this.props.username}</p></code>	<code><p>{props.username}</p></code>	<code><p>{username}</p></code>	<code><p>{props}</p></code>
277	7	Which of the following represents the correct syntax for rendering a React component named "Button" with JSX in ReactJS?	<code><Button></Button></code>	0.5	LJU 2023	<code><Button></Button></code>	<code>render(Button)</code>	<code>React.render(Button)</code>	<code>React.createElement(Button)</code>
278	7	Complete the array method that will allow you to run a function on each item in the array and return a new array. <code>const myList = myArray. _____((item) => <p>{item}</p>)</code>	<code>map</code>	0.5		<code>execute</code>	<code>apply</code>	<code>map</code>	<code>iterate</code>
279	7	What is the correct syntax to write an expression in JSX?	<code>{ expression }</code>	0.5		<code>{{ expression }}</code>	<code><{ expression }></code>	<code>{ expression }</code>	<code># { expression }</code>
280	7	Which of the following options correctly represents JSX syntax in a React functional component?	<code><div>Hello, World!</div></code>	0.5		<code><div>Hello, World!</div></code>	<code>React.createElement("div", "Hello, World!")</code>	<code>("div", "Hello, World!")</code>	<code>div: "Hello, World!"</code>
281	7	Which of the following is used to access a function display() from h1 element in JSX?	<code><h1>{display()}</h1></code>	0.5		<code><h1>{{display}}</h1></code>	<code><h1>{'display'}</h1></code>	<code><h1>{display()}</h1></code>	<code><h1>{display()}</h1></code>
282	7	Which event handler in React is used to handle a form submission in a functional component?	<code>onSubmit</code>	0.5		<code>onFormSubmit</code>	<code>onSubmitForm</code>	<code>onSubmit</code>	<code>handleFormSubmit</code>
283	7	Identify error/output in following code of App.js file. <pre>const arr=["apple", "banana", "kiwi", "orange"]; const result = arr.filter((fruit) => { if(fruit.length > 5) { return true;} else { return false; } }); var arr1=result.join(",") return (<div> {arr1} </div>)</pre>	Output:banana,orange	1		Output: apple,kiwi	Error: The filter function should have a closing parenthesis.	Output:banana,orange	Error: JSX elements should be returned within a single parent element.
284	7	Which syntax is commonly used for defining a route in React using react-router-dom?	<code><Route path="/about" element= {<About />} /></code>	1		<code><Route path="/about" element=About /></code>	<code><Route url="/about" element={About} /></code>	<code><Route path="/about" element= {<About />} /></code>	<code><Route path="/about"><About /></Route></code>
285	7	Give the correct output. <pre>import React from 'react'; const App = () => { const name = "John"; const age = 30; return (<div> <h1>Hello, {name}</h1> <p>You are {age} years old.</p> You are an adult : You are a minor </div>); }; export default App;</pre>	Hello, John! and "You are 30 years old." with an unordered list item "You are an adult"	1		Hello, John! and "You are 30 years old." with an unordered list item "You are an adult"	Hello, John! and "You are 30 years old." with an unordered list item "You are a minor"	An error will occur due to incorrect syntax in the JSX	Nothing will be displayed on the screen
286	7	Consider following code in App.js file and Program.js file. Identify error/output. App.js <pre>const obj1={Name:"Hiyan",Age:32,Branch:["CSE","CE","IT"]}; const str = JSON.stringify(obj1); return(<div><Program Name={obj1} /></div>);</pre> Program.js <pre>const Program=(props)=>{ return(<div><h1>{props.Name.Branch[0]}</h1></div>);</pre>	CSE will be printed on browser in <h1> tag	1	LJU-2023	CSE will be printed on browser in <h1> tag	Prints entire JSON object including all members	Error: Value not initialized	CE will be printed on browser in <h1> tag
287	7	Identify error/output in following code of App.js file. <pre>function App() { const a="Hello"; const b=8; return (<div className="App"> <h1 style={{backgroundColor:"green"}}> The addition is: {a+2+b}</h1> </div>); } export default App;</pre>	Output:"The addition is: Hello28" with green background color in <h1> tag	1	LJU-2023	Output:"The addition is: Hello10" with green background color in <h1> tag.	Output:"The addition is: Hello28" with green background color in <h1> tag	Output:"The addition is: 28Hello" with green background color in <h1> tag	Error: "value not initialized"

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
288	7	What will be the output of following code? <pre>function map1() { let arr = [2, 4, 6, 3, 7, 5] const val = arr.sort(); return (<div> <h1>Output: </h1> { arr.map((value)=>{ const val = value + 3 + "2" return (<h2>{val}</h2>) })} </div>)}export default map1</pre>	Output: 52 62 72 82 92 102	1	102 92 82 72 62 52	7 9 11 8 12 10	Output: 52 62 72 82 92 102	232 432 632 332 732 532	
289	7	Random numbers stored as an array named "arr", how can you use the 'filter' method to get only even numbers in output?	arr.filter(num => num % 2 === 0)	1		arr.filter(num => num % 2 === 0)	arr.filter(num => num % 2 !== 0)	arr.filter(num => num.isEven())	arr.filter(num => num % 2 === 1)
290	7	Identify Correct CSS syntax in below code for mystyle to get proper output. <pre>function App(){ const mystyle= ?? return (<div> <h1 style={mystyle}>Demo1 </h1> </div>)} export default App;</pre>	{fontSize:"40px", color:"green", textTransform:"uppercase"}	1	font-Size:"40px", color:"green", text-Transform:"uppercase"	{font-Size:"40px", color:"green", text-Transform:"uppercase"}	{fontSize:"40px", color:"green", textTransform:"uppercase"}	fontSize:"40px", color:"green", textTransform:"uppercase"	
291	7	Which of the following is not an incorrect statement/s regarding react. 1.React components are composed to create a user interface with only webpack. 2.All React components must act like recursive functions with respect to their props. 3.map() function is a callback function that is called once for each element in the array. 4.First file loaded by the browser in a basic React project is index.js 5.React's virtual DOM is A library that handles asynchronous operations in React applications.	Only 3	1	1,2,3	3,5	3,4,5	Only 3	
292	7	What do you call the message wrapped in curly braces below? let message = 'Welcome to LJU'; const element = {message} ;	a JS expression	0.5	a JS function	a JS expression	a JS event	a JS property	
293	7	What will be the output of the following JSX code? <button onClick={() => alert("Button clicked!")}>Click me</button>	A button with the text "Click me" that triggers an alert when clicked.	1	A warning about the missing onClick handler.	A syntax error due to the arrow function syntax.	A button with the text "Click me" that triggers an alert when clicked.	A button is not clickable.	
294	7	What will be the output of the following code: import React from 'react'; export function App() { const arr = [10, 20, 30, 40, 50]; return (< {arr.map((v, index) => { let s = index * 5; return <h3 key={index}>s = {s}</h3>; })} </>;) }	s = 0 s = 5 s = 10 s = 15 s = 20	1	s = 0 s = 1 s = 2 s = 3 s = 4	s = 0 s = 5 s = 10 s = 15 s = 20	s = 10 s = 20 s = 30 s = 40 s = 50	s = 50 s = 100 s = 150 s = 200 s = 250	
295	7	In a React form, which event is typically used to handle changes in an input field?	onChange	1		onChange	onSubmit	onClick	onInputhere
296	7	Build basic react app that display "Hello World" in browser.		3					
297	7	Create an ReactJS app which shows the how to pass and read data using props		3					
298	7	Write a React code to print car's brand name and its model name which are passed as props using JSON.		4					
299	7	Write react js script to display alert box with text "Welcome to LJU" by clicking on button.		3					

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
300	7	Write react js script to display values in console while changing it in text box.		4					
301	7	Write react js script to display alert box with text "welcome to lju" only on double click button		3					
302	7	Create react app to perform tasks as asked. First create files as asked below in routing folder 1. Home.js - for the home page content 2. Shop.js - for the shop page content 3. Contact.js - for the contact page content 4. Nopage.js - for the page other than mentioned links Create Main.js file which contains Links for Home, Shop and Product page. Also, add functionality of page routing. Finally call Main.js in App.js.		4					
303	7	Create React app to pass student name, roll number, t1 marks and t2 marks of 2 students to component and read the information and display in table format. Use Props.		5					
304	7	Create react app and use routing functionality of react to perform the tasks as asked. Create one file named Main.js which contains links for home and about page and routing functionality. In Home.js file add one image and heading(h1) "LJ University" In About.js file add branch list (CSE,IT,CE).		5					
305	7	Write a ReactJS code in which we have apply filter to skip digits which are less than "10" from the array and display all remaining digits of the array [3,5,11,4,17,8,21,2,26,13,8]. Pass values as props.		4					
306	7	Create React app to pass color(red), background color(yellow), font size(25px) and font style(italic) as properties to component and apply css to "Lj Students" text written in p tag. use Props		4					
307	7	Write react js script to perform the tasks as asked below. Add an array of objects which contains name and age of people. Apply filter to find people with age less than 40. And display name of all people using map function. Use props.		4	LJU-2023				
308	7	Write react js script to perform the tasks as asked below. Add an array of objects which contains name and branch(CSE,IT,CE) of students. Apply filter to find students who are from CSE branch. And display name of all students of CSE branch using map function.		5					
309	7	Create react app and use routing functionality of react to perform the tasks as asked. Create one file named Main.js which contains links for React Js, Node Js and Express Js and routing functionality. Create components for each links and add heading "React JS","Node JS" and "Express JS" in component files Ex1.js, Ex2.js and EX3.js respectively.		4					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
310	7	Create a React app to perform tasks as asked using functional component: 1)Create a React Router that includes three routes: Home, Food Items, and Contact and implement navigation between these routes. 2)Create a route that displays a Home page, Food Items details page and Contact details page. 3) When a user clicks on Home page it should navigate to the home page and display "Welcome to LJU" in bold in the h1 heading. When a user clicks on a Food Items page, it should navigate to the Food Items Detail page and display three products with name, price and description using props. And when the user clicks on Contact page it should navigate to contact details page and display contact information with blue color font.		5	LJU-2025				
311	7	Create react app to pass product image, name and price as properties from one component to another component. Add an array of objects with pic, name and price properties of 2 products. Display Image name and price of the products in browser using map method.		4					
312	7	Create react app using function component to pass background color(green), font size(50px) font style(italic),text transform(uppercase) as properties to Example.js component and apply css to "This is an React Application" text written in h1 tag in Example2.js component. Use props.		3					
313	7	Create react app using function component to perform tasks as asked. First create files as asked below in folder named " component" 1. Login.js - for the login page content 2. Product.js - for the Product page content 3. Contact.js - for the contact page content 4. About.js - for the about page content Create Home.js file which contains Links for Login,Product,Contact and About page. Also, add functionality of page routing. Finally call Home.js in App.js. Write code for All necessary files.		4					
314	7	Write a react.js file to pass an integer value to a component, which is defined as a property in app.js file. Fetch that value in component and print its table on console. Write all necessary files i.e. App.js and Component.js. Perform task by function component.		5					
315	7	Write React JS script to display three products. Products having title, product image, price and description. All three products should be horizontally adjacent to each other. Note: using props show all products and use Functional component for complete this script.		3					
316	7	Write react js script to perform the tasks as asked below using functional component: 1)Add an array of objects which contains name and age of people. 2)Apply filter to find people with age less than 40. And display name of all people using map function. Use props.		3					
317	7	Create a React app to perform tasks as asked using functional component: 1)Create a react Router that includes three routes: Home, Product, and Contact and implement navigation between these routes. 2)Create a route that displays a Home page, Product details page and Contact details page. 3) When a user clicks on Home page it should navigate to home page and display "Welcome to LJU" in bold in h1 heading. When a user clicks on a Product page, it should navigate to the product detail page and display three products information with price and description using props. And when user clicks on Contact page it should navigate to contact details page and display contact information with blue color font.		4	LJU-2023				

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
318	7	Write a program to create function based ReactJS app having an array of 6 people having mentioned age [70,83,38,65,49,94] and display list of people whose age is greater than 60 using filter method. Also display total count of people whose age is greater than 60 on the same page. Use props.		4					
319	7	Create a React function component named File1 that receives two props, productName and price. The component should display the product name and price. Additionally, add a button labeled "Add to cart" to the component. When the button is clicked onClick event triggered and an alert should be displayed with the message "Your Product is Added to cart!".		5					
320	7	Write react js script to perform the task as below using function component: •Create array of objects which have id, name & city of person. •Display id & name of persons having city name "Ahmedabad" . Use props. No need to write App.js file.		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD									
Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)									
Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.									
Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-8									
321	8	Identify correct sequence to code API using Axios.	ios.get("url").then(response).catch(err	0.5		axios.get("url").catch(error).then(res ponse)	axios.get("url").then(response).catch(error)	axios.catch(error).then(response).get ("url")	axios.get("url").then(request).catch(e rror)
322	8	What is the use of useContext Hook ?	Used to create global variables	0.5		Used to create global variables	Used to transfer values as a agrgument to another components	To create a constant variable	To use createContext hook
323	8	What will be the error in the following program : import React, { useState } from 'react' const Hook3 = () => { const [firstName, setFirstName]=useState(""); function handleChange(){ setFirstName(e.target.value); } return (<input name="firstName" value={firstName} onChange={handleChange}/> {firstName}) } export default Hook3	e is not defined	1		Unexpected use of Input type	handleChange is undefined	e is not defined	firstname is undefined
324	8	We can not export more than one context from a module.(True/False)	False	0.5		TRUE	FALSE		
325	8	Identify the correct result of following code snippet const [cb, setCb] = useState(""); const handleChange=(e)=>{setCb(e.target.value);} const handleChange1=(e)=>{setCb(e.target.value);} return(<input type="radio" value="Male" onChange="{handleChange} name="gender" />Male <input type="radio" value="Female" onChange="{handleChange1} name="gender" />Female {cb});	Both "Male" and "Female" will be printed by selecting respective radio buttons	1		Error, since onChange event can't be applied on radio button	Error, since we have to take two separate useStates to store 2 radio button values	radio buttons are shown correctly, but events are not performed on both radio buttons, no error is shown	Both "Male" and "Female" will be printed by selecting respective radio buttons
326	8	_____ hook is used to maintain a state and its updating function with its definition.	useState	0.5		useState	useEffect	useForm	useReducer
327	8	Which of the following options correctly represents the syntax for using useReducer in ReactJS?	const [state, dispatch] = useReducer(reducerFunction, initialState);	0.5		const [state, dispatch] = useReducer(reducerFunction, initialState);	const {state, dispatch} = useReducer(reducerFunction, initialState);	const [dispatch, state] = useReducer(initialState, reducerFunction);	const {dispatch, state} = useReducer(initialState, reducerFunction);
328	8	The useContext hook in React is primarily used to:	Share state and data between components without prop drilling.	0.5		Manage and update the state of a component using a reducer function.	Fetch data from an API and handle asynchronous operations.	Create a new context for managing global state.	Declare state variables in functional components.
329	8	What does the useState hook in React return?	An array with two elements: the current state value and a function to update the state.	0.5		An object with properties state and setState.	An array with two elements: the current state value and a function to update the state.	A single value representing the current state.	An object with a get method to access the state and a set method to update the state.
330	8	How do you initialize a state variable named count with an initial value of 0 using the useState hook in a React component	const [count, setCount] = useState(0);	1		const [count, setCount] = useState(0);	const [count, setCount] = useState(\$count:0);	const {count, setCount} = useState(count: 0);	const [count, setCount] = useState(count: 0);
331	8	Consider you have a context named ThemeContext that provides a theme value. How would you consume this context value using the useContext hook inside a functional component	const theme = useContext(ThemeContext);	1		const { ThemeContext } = useContext();	const { theme } = {useContext(ThemeContext)};	const theme = useContext(ThemeContext);	const { [theme]} = ThemeContext;
332	8	What will be the output: import React, { useReducer } from 'react' const Hook = () => { const [sum, dispatch]=useReducer((state,action)=>{ return state+action; } ,20); return ({sum} <button onClick={()=>dispatch(5)}>Add</button>) } export default Hook	It displays number 20 and increase the number by 5 each time when DoubleClick on button	1		It displays number 20 and increase the number by 5 only once	It displays number 5 and increase the number by 20 only once	It displays number 20 and increase the number by 5 each time when button clicked	It displays number 5 and increase the number by 20 each time when button clicked
333	1	how do you use the useContext hook to access the context value?	const contextValue = useContext(myContext);	0.5		const contextValue = useContext(myContext);	const contextValue = useValue(myContext);	const contextValue = this.useContext(myContext);	const contextValue = this.useValue(myContext);
334	8	How do you handle errors in Axios?	By using the .catch() method on the promise returned by Axios	0.5		By using the .error() method on the response object	By using a try-catch block	Axios automatically handles errors and throws exceptions	By using the .catch() method on the promise returned by Axios
335	8	How do you invoke setTxt only when component mounts, using hooks? function MyComponent(props) { const [txt, setTxt] = useState(false); return Done: {txt} ; }	useEffect(() => { setTxt(true); }, []);	1		useEffect(() => { setTxt(true); });	useEffect(() => { setTxt(true); }, [setTxt]);	useEffect(() => { setTxt(true); }, [txt, setTxt]);	useEffect(() => { setTxt(true); }, []);

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD									
Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)									
Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.									
Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
336	8	What will be the output? import React, { useState, useEffect } from 'react'; const Ex = () => { const [seconds, setSeconds] = useState(0); useEffect(() => { setInterval(() => { setSeconds(prevSeconds => prevSeconds + 1); }, 1000); },[]) return (Seconds: {seconds}) } export default Ex	It renders the component every 2 seconds	1	LJU-2023	It updates the scroll position whenever the component renders	It increments the seconds state every second	It handles clicks on a button to increment seconds	It renders the component every 2 seconds
337	8	what will be the output of below code: import { useState } from "react"; function Example () { const [buttonText,setbuttontext]=useState("Hide"); const [text,setText]=useState("Hello"); function clickButton() { if(buttonText === 'Hide') { setbuttontext("Show") setText("") } else { setbuttontext("Hide") setText("Hello") } } return (<button onClick={clickButton}>Hide/show</button>) }	Initially the button text "Hide/show" and the text "Hello" will be displayed in the browser. Clicking that button will not change button text just the text will be hidden.	1	LJU-2023	Initially the button text "Hide" and the text "Hello" will be hidden in the browser. Clicking that button will change button text to "Show" and the text will be displayed.	Initially the button text "Show" and the text "Hello" will be hidden in the browser. Clicking that button will change button text to "Hide" and the text will be displayed	Initially the button text "Hide" and the text "Hello" will be hidden in the browser. Clicking that button will not change button text and the text will be displayed.	Initially the button text "Hide" and the text "Hello" will be displayed in the browser. Clicking that button will change button text to "Show" and the text will be hidden.
338	8	Find the correct syntax for Axios?	function fetchactivity(){ axios .get(siteURL) .then((data) => console.log(data.data)) .catch((error)=>console.log(error)) }	1		function fetchactivity(){ axios .get(siteURL) .then((data) => console.log(data.data)) .catch((error)=>console.log(error)) }	function fetchactivity(){ axios .get(siteURL) axios .then(data => console.log(data.data)) axios .catch(error=>console.log(error)) }	function fetchactivity(){ axios .get(siteURL) .then((data) => console.log(data.data)) .catch((error)=>console.log(error)) }	function fetchactivity(){ axios .get(siteURL) .then({data} => console.log(data.data)) axios.catch({error}=>console.log(error)) }
339	8	What will happen when the button is clicked? const [count,setCount] = useState(0); <button onClick={()=>setCount(count+1)}>Click</button> {count}	It increments the count value by 1 on each click	1		It decrements the count value	It increments the count value by 1 on each click	It resets the count to 0	It shows an error
340	8	How do you correctly initialize a state variable 'name' with value 'John' using useState?	const [name, setName] = useState('John');	1		const name = useState('John');	const [name, setName] = useState('John');	const {name, setName} = useState('John');	useState name = 'John';
341	8	What will be displayed initially? const [text,setText] = useState('Hello'); {text}	Hello	1		undefined	null	Hello	Nothing will be displayed
342	8	If the initial state is false: const [show,setShow] = useState(false); What is correct way to toggle it?	setShow(!show);	1		setShow(show++);	setShow(!show);	show = true;	setShow = true;
343	8	You created useContext in Parent component and wrapped <Child/> inside <UserContext.Provider value='abc'>. How will Child component access this value?	const user = useContext(UserContext);	1		const user = useContext(UserContext);	const user = useContext();	const user = this.useContext(UserContext);	useContext = useContext;
344	8	In a Theme application, ThemeContext provides value 'dark'. If value changes to 'light', what happens to components using useContext(ThemeContext)?	They automatically re-render with new theme value	1		They automatically re-render with new theme value	They need manual refresh	Application crashes	Nothing changes
345	8	You want to pass 'blue' color from Parent to deeply nested Child without passing props manually at each level. Which is correct approach?	Create Context in Parent and consume it using useContext in Child	1		Use useState in Child only	Create Context in Parent and consume it using useContext in Child	Use useEffect to send props	Store value in local variable
346	8	Consider: const value = useContext(MyContext); If MyContext has no Provider above this component, what will value be?	The default value passed while creating MyContext	1		undefined always	The default value passed while creating MyContext	Application error immediately	Null pointer exception

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD									
Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)									
Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.									
Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
347	8	You want to increase count by 1 using useReducer. Which dispatch call is correct if reducer handles action type 'increment'?	dispatch({type:'increment'});	1		dispatch({type:'increment'});	dispatch('increment');	setCount(count+1);	useReducer('increment');
348	8	Initial state is 0. Reducer returns state + action.payload. What will dispatch({payload:5}) do?	Increase state by 5	1		Reset state to 5	Increase state by 5	Multiply state by 5	Throw error always
349	8	When is useReducer preferred over useState in practical applications?	When state logic is complex with multiple actions	1		When state logic is complex with multiple actions	When only one variable is used	When API call is required	When styling components
350	8	What does useReducer return?	Current state and dispatch function	1		Only dispatch function	Only state value	Current state and dispatch function	Reducer function itself
351	8	If reducer does not match any action type, what should it return to avoid errors?	Return current state	1		Return null	Return current state	Return undefined	Return new object always
352	8	How do you run useEffect only once when component mounts?	useEffect(()=> {}, []);	1		useEffect(()=> {});	useEffect(()=> {}, [state]);	useEffect(()=> {}, []);	useEffect(state);
353	8	You want to fetch API data when component loads. Where should API call be written?	Inside useEffect with empty dependency array	1		Inside useState	Inside useEffect with empty dependency array	Inside return statement	Inside reducer
354	8	If dependency array contains [count], when will useEffect execute?	Whenever count value changes	1		Only once	Whenever count value changes	On every render regardless	Never executes
355	8	If no dependency array is provided in useEffect, what happens?	It runs after every render	1		It runs only once	It runs after every render	It never runs	It throws error
356	8	Write a program to build React app to perform the tasks as asked below using useState hook. •Add three buttons “Change Text”, “Change Color”, “Hide/Show”. •Add heading “LJ University” in red color(initial) and also add “React Js Hooks” text in h2 tag. •By clicking on “Change text” button text should be changed to “Welcome students” and vice versa. •By clicking on “Change Color” button change color of text to “blue” and vice versa. This color change should be performed while double clicking on the button. •Initially button text should be “Hide”. While clicking on it the button text should be changed to “Show” and text “React Js Hooks” will not be shown.		5					
357	8	Write a program to build React app having a button which changes image by clicking it. (Add two images)		3					
358	8	Write a program to build React app having 2 input text fields (First name and last name) and display the entered value on the same page.		3					
359	8	Write a program to build React app for task todo list. •Add 1 input field and button and by clicking on button display entered task on the same page. •Also, add delete button with each added task to delete the task.		5					
360	8	Write a program to build React app having text and button to show and hide the text.		3					
361	8	Write a program to build React app having 2 input number fields (Number 1 and Number 2) and display the entered value on the same page. And then click on add button to calculate the addition of two numbers. Display the addition in h2 tag.		3					

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
362	8	Write a program to build React app to perform the tasks as asked below. •Add a button "Change Text". •Add "Hello" text in h2 tag. •By clicking on "Change text" button text should be changed to "How are you?" and vice versa.		4					
363	8	Write a program to build React app having a button which increase count by 1 while clicking it. (useState)		3					
364	8	Create a program to build React app having buttons to increment and decrement the number by clicking that respective button. Also, increment of the number should be performed only if number is less than 10 and decrement of the number should be performed if number is greater than 0.		4					
365	8	Write a ReactJS script to create a digital clock running continuously. (useEffect)		3					
366	8	Write a reactJS program to perform the tasks as asked below. •Create one main file (parent file) name Comp.js and other 3 component files Comp1.js, Comp2.js, Comp3.js. •Pass Number1 and Number 2 from Comp.js file to Comp3.js file. Calculate multiplication of the numbers using useContext.		4					
367	8	Write a reactJS program to perform the tasks as asked below. 1) Create one main file (parent file)Main.js and other 2 component files Comp1.js, Comp2.js. Pass username from Main.js file to Comp2.js file. Display this user name in browser in Blue color. (useContext)		3					
368	8	Create a Sign-up form using React asking for username, age, email, password, and confirm password. When the user clicks on the 'submit' button, it will display an alert box with a username, age, and email details entered by the user.		4					
369	8	Create a React Form for email and password validation.		2					
370	8	Create a React Form for select any of pizza size using radio button.		3					
371	8	Create React Js app to perform the tasks as asked below. -Add buttons "increment" and "decrement" -By clicking on increment button the value should be incremented by 1 and by clicking on decrement button value should be decremented by 1. -Use useReducer hook to perform the above tasks.		3					
372	8	Create React Js app to perform the tasks as asked below. -Add button "Click" -By clicking on button the value should be incremented by 5. Initial value is 20. -Use useReducer hook to perform the above tasks.		3					
373	8	Create a react app to generate random joke using AXIOS to make API request.		4					
374	8	Create react app to create exam form. Fields are as under. Name -text, Email -email Password -password, Gender-radio, Exam date-datepicker, Exam center-dropdown) Use useState hook to save the state of the form. Also, add validation for the email and password fields. Display submitted values.		4	LJU-2023 LJU-2025				

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
375	8	Create a react app using function component to display image of flower using AXIOS to make API request. Use API Url (https://flower.ceo/api/image/random). Key name in API which store image is "sample".		3					
376	8	Create a Student Data Entry Form using React. Fields are Student Name (input Field), Gender (Radio Button values are Boy, Girl), Subjects (Dropdown values are English, Gujarati), Comments (textarea). When the user Click on the Submit button , it will display an alert and use useState hook.		4					
377	8	Build a survey form with radio buttons, and dropdowns. display selected results on the alert box on user responses using React JS Hooks.(App.js file not required).		5					
378	8	Create a React app with two components using functional component: Parent and Child. Use useContext to pass two colors from the Parent component to the Child component. The Child component should display the received color as its background(red) and other color(green) on its font to display "Welcome to LJU".		4	LJU-2023				
379	8	Create a React app with three components: parent component P.js and two child components C1.js, C2.js. Use useContext hook to pass two colors from the Parent component P.js to the Child component C2.js. (Yellow color as font color and Blue color as background color) In Child component C1.js import child component C2.js. In C2.js display "Full stack Development" text in h1 heading with above mentioned background color and font color using context.		5					
380	8	Create a ReactJS program using function component having two input fields for num1 and num2 and two buttons for addition and subtraction of the two numbers. Display the respective outputs on same page using useState hook. Also display alert box as an effect on every time the addition button is clicked using useEffect hook.		5					
381	8	Create react app which to perform following task using function component: •Create one main file name F1.js & other 2 component files F2.js & F3.js. •Main file contains form with following fields: oFirst Name (Input type text) oLast Name (Input type text) oMessage (Textarea) oCity (Dropdown) oGender (Radio Button) •Pass values of all fields from F1.js file to F3.js file. And display all submitted values in alert box using useContext & useState hook. No need to write App.js file.		5					
382		Create a React app with three components: parent component P.js and two child components C1.js, C2.js. Use useContext hook to pass fontStyle and fontSize from the Parent component P.js to the Child component C2.js. In Child component C1.js import child component C2.js. In C2.js display "Full stack Development" text in h1 heading with above mentioned fontStyle and fontSize using context.							
383	8	Create a React app: • Add two buttons "Dark Mode" and "Light Mode" • Initially background should be white and text black • On clicking "Dark Mode" change background to black and text to white • On clicking "Light Mode" revert back		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
384	8	Create a React app: • Add one textarea • Display live character count below it • If characters exceed 100, text color becomes red		5					
385	8	Create a React app: • Add Start and Stop buttons • When Start is clicked, counter increments every second • When Stop is clicked, counter stops • Use useEffect with cleanup		5					
386	8	Create a React app: • Display product quantity • Add buttons "Add Item" and "Remove Item" • Quantity should never go below 0 • Use useReducer to manage state		5					
387	8	Create a React app: • Parent component stores language value ("English" or "Hindi") • Pass language using useContext • Child component displays "Welcome" in selected language • Add button in parent to toggle language		5					
388	8	Create a React app that: • Add an input field to enter city name • On clicking "Get Weather", fetch weather data using Axios • Display temperature, humidity, and weather description • If city is invalid, display error message • Show loading message while fetching data		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD									
Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)									
Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.									
Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter-9									
389	9	MongoDB can only receive _____ to insert in collection.	Both A & B	0.5		Array of JSON	Simple JSON	Simple object	Both A & B
390	9	_____ command lists all collections in a DB.	show collections	0.5		desc collections	list collections	select collections	show collections
391	9	_____ command lists all databases.	show dbs	0.5		list dbs	select dbs	show dbs	desc dbs
392	9	_____ command creates a collection in MongoDB.	db.createCollection("Collection_name")	0.5		db.createCollection("Collection_name")	create table table_name	db.create.collection("Collection_name")	db.Collection("Collection_name")
393	9	_____ command deletes entire collection with all its documents.	db.collection_name.drop()	0.5	LJU 2025	db.collection_name.drop()	db.collection_name.delete()	db.collection_name.truncate()	db.collection_name.cancel()
394	9	_____ command creates a new database or switches to existing database.	use	0.5	LJU 2025	switch	use	apply	move
395	9	Identify the equivalent NoSQL command of following SQL command: create table student	db.createCollection("student")	1		db.create("student")	db.createTable("student")	db.createDatabase("student")	db.createCollection("student")
396	9	Identify the equivalent NoSQL command of following SQL command: drop table student	db.student.drop()	1		db.student.drop()	db.student.delete()	db.student.truncate()	db.student.cancel()
397	9	drop() command returns _____.	Boolean value	1		JSON specifying {OK:1}	integer value	null value	Boolean value
398	9	you have a MongoDB collection named "students" containing information about various students. You want to retrieve a list of students whose names match any of the following: "CCC," "PPP," or "BBB." Additionally, you want to display the results in descending order based on their names. How would you write a MongoDB query to accomplish this task?	db.students.find({ name: { \$in: ["CCC", "PPP", "BBB"] } }).sort({ name: -1 })	1	LJU 2023 LJU 2025	db.students.find({ name: { \$in: ["CCC", "PPP", "BBB"] } }).sort({ _id: -1 })	db.students.find({ name: "CCC" "PPP" "BBB" }).sort({ name: -1 })	db.students.find({ name: { \$in: ["CCC", "PPP", "BBB"] } }).sort({ name: 1 })	db.students.find({ name: { \$in: ["CCC", "PPP", "BBB"] } }).sort({ name: -1 })
399	9	Identify the equivalent NoSQL command of following SQL command: UPDATE lju SET status = "Active" WHERE age = 25 and name "ABC"	db.lju.updateMany({ age: 25,name:'ABC' }, { \$set: { status: "Active" } })	1	LJU 2023 LJU 2025	db.lju.updateMany({ age: 25,name:'AB' }, { \$set: { status: "Active" } })	db.lju.updateMany({ age: 25,name:'ABC' }, { \$set: { status: "Active" } })	db.lj.updateMany({ age: 25,name:'ABC' }, { \$set: { status: "Active" } })	db.lju.updateMany({ age: 25,uname:'ABC' }, { \$set: { status: "Active" } })
400	9	Identify the equivalent NoSQL command of following SQL command: SELECT COUNT(*) FROM lju WHERE age > 30	db.lju.find({ age: { \$gte: 30 } }).count()	1		db.lju.count({ age: { \$lt: 30 } })	db.lju.find({ age: { \$gt: 30 } }).count()	db.lju.find({ age: { \$gte: 30 } }).count()	db.lju.findcount({ age: { \$gte: 30 } })
401	1	Convert this SQL query to MongoDB: "ALTER TABLE data ADD join_date DATETIME"	db.data.updateMany({ }, { \$set: { join_date: new Date() } })	1		db.updateMany({ \$set: { join_date: new Date() } })	db.data.updateMany({ }, { \$set: { join_date: new Date() } })	db.data.updateMany({ join_date: { \$set: new Date() } })	db.data.updateOne({ join_date: { \$set: new Date() } })
402	9	Identify correct command to list name and age of all students excluding _id field.	db.student.find({ }, { name: 1, age: 1, _id: 0 })	1		db.student.find({ name: 1, age: 1 })	db.student.find({ name: 1, age: 1, _id: 0 })	db.student.find({ }, { name: 1, age: 1, _id: 1 })	db.student.find({ }, { name: 1, age: 1, _id: 1 })
403	9	1st and 2nd argument in find() command generally refers _____ & _____ respectively.	Condition & Projection	1		Projection & Condition	Condition & Projection	Condition & Selection	Condition & Join

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
404	9	Identify correct query to increment age of all documents by 10.	db.test.updateMany({}, {\$inc: {age: 10}})	1		db.test.updateMany({}, {\$set: {age: age+10}})	db.test.updateMany({}, {\$inc: {age: 10}})	db.test.updateMany({\$inc: {age: 10}})	All of the above
405	9	Identify correct query to count no. of documents excluding age=2 and 21.	db.student.find({age: {\$nin: [2, 21]}}).count()	1		db.student.find({age: {\$nin: [2, 21]}}).count()	db.student.find({\$and: [{age: {\$ne: 2}}, {age: {\$ne: 21}}]}).	db.student.find({\$or: [{age: {\$ne: 2}}, {age: {\$ne: 21}}]}).count()	db.student.find({\$and: [{age: {\$seq: 2}}, {age: {\$seq: 21}}]}).count()
406	9	Identify correct command to update name field of all documents of a "test" collection.	db.test.updateMany({}, {\$set: {name: "QQQ"}})	1		db.test.updateAll({name: {\$set: "QQQ"}})	db.test.updateMany({name: {\$set: "QQQ"}})	db.test.updateMany({\$set: {name: "QQQ"}})	db.test.updateMany({}, {\$set: {name: "QQQ"}})
407	9	Identify correct command equivalent to following SQL command: delete from student	db.student.deleteMany({})	0.5		db.sudent.deleteOne({})	db.student.deleteMany()	db.student.deleteMany({})	db.student.deleteAll()
408	9	Consider a collection "emp" having documents like this: [{ _id: 123433, name: "DDD", age: 32 }, { _id: 123434, name: "BBB", age: 20 }, { _id: 123435, name: "AAA", age: 10 },] Identify result of following query in cmd: db.emp.find({}, {name: 1, id: 0}).skip(1)	[{name: "BBB"}, {name: "AAA"}]	1		[{name: "DDD"}, {name: "BBB"}]	[{name: "BBB"}, {name: "AAA"}]	[{name: "BBB"}, {name: "DDD"}]	[{name: "AAA"}, {name: "DDD"}]
409	9	Consider a collection "emp" having documents like this: [{ _id: 123433, name: "DDD", age: 32 }, { _id: 123434, name: "BBB", age: 20 }, { _id: 123435, name: "AAA", age: 10 },] Identify the equivalent query, which will produce same result of following query. db.emp.find({}, {name: 1, id: 0}).skip(1).limit(2)	db.emp.find({}, {name: 1, id: 0}).skip(1)	1	LJU 2025	db.emp.find({}, {name: 1, id: 0}).skip(2).limit(1)	db.emp.find({}, {name: 1, id: 0}).limit(2)	db.emp.find({}, {name: 1, id: 0}).skip(2)	db.emp.find({}, {name: 1, id: 0}).skip(1)
410	9	_____property inserts a new record, if record to be updated is not found, while firing update query.	upsert	0.5		upsert	change	update	set
411	9	_____operator is used to exclude a list of values from a field during retrieval.	\$nin	0.5		\$in	\$restrict	\$nin	\$set
412	9	Consider following student collection: [{ _id: 123433, name: "SSS", age: 22 }, { _id: 123434, name: "ppp", age: 2 }, { _id: 123435, name: "PPP", age: 32 },] Identify result of following query: db.student.find({name: {\$in: ["ppp", "SSS"]}})	Returns only 2 records having names "ppp" & "SSS"	1		Returns all 3 records	Error in query as \$in operator takes JSON, not array	Error in query as \$in operator compares by \$eq operator only	Returns only 2 records having names "ppp" & "SSS"
413	9	Given a MongoDB collection named products, you need to find documents where the "price" field is greater than or equal to 50. Which of the following queries should you use?	db.products.find({ price: { \$gte: 50 } })	1	LJU 2025	db.products.find({ price: { \$gt: 50 } })	db.products.find({ price: { \$gte: 50 } })	db.products.find({ price: { \$lt: 50 } })	db.products.find({ price: { \$lte: 50 } })
414	9	Consider the following query using \$inc operator. Identify error/output. db.student.updateMany({\$inc: {age: -8}})	Error, as filter condition must be specified in update() function.	1		Increments age value of all documents and returns modified count.	Increments age value of all, but modified count is not returned.	Increments age value of 1st document only.	Error, as filter condition must be specified in update() function.
415	9	Which is/are the correct query/ies to find eldest person from emp collection?	db.emp.find().sort({age: -1}).limit(1)	1		db.emp.findOne({age: 50})	db.emp.find().sort({age: 1})	db.emp.find().sort({age: -1}).limit(1)	db.emp.findOne().sort({age: 1})
416	9	The MongoDB Aggregation Framework is mainly used to:	Perform complex data processing and transformation	1		Insert multiple documents	Perform complex data processing and transformation	Create indexes	Delete collections
417	9	Which stage is used to filter documents in an aggregation pipeline?	\$match	1		\$group	\$project	\$match	\$sort

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
418	9	The \$match stage is similar to which MongoDB operation?	find()	1		insertOne()	find()	updateOne()	drop()
419	9	Which stage is used to group documents based on a specified field?	\$group	1		\$group	\$match	\$sort	\$limit
420	9	In the \$group stage, which field is mandatory?	_id	1		groupBy	key	value	_id
421	9	To arrange documents in ascending or descending order, which stage is used?	\$sort	1		\$sort	\$project	\$group	\$match
422	9	In the \$sort stage, what does value 1 represent?	Ascending order	1		Random order	Descending order	Ascending order	No sorting
423	9	What does value -1 represent in \$sort?	Descending order	1		Ascending order	Descending order	Remove duplicates	Skip documents
424	9	Which stage is used to reshape documents by including, excluding, or creating new fields?	\$project	1		\$sort	\$project	\$match	\$group
425	9	To include a field in \$project, you assign it the value:	1	1	0	1	-1	true only	
426	9	To exclude a field in \$project, you assign it the value:	0	1	1	-1	0	false only	
427	9	Which of the following is a correct aggregation pipeline structure?	db.collection.aggregate([{stage1}, {stage2}])	1		db.collection.aggregate([{stage1}, {stage2}])	db.collection.group({})	db.aggregate.collection({})	aggregate.collection.db({})
428	9	db.students.aggregate([{ \$match: { marks: { \$gt: 80 } } }, { \$sort: { marks: 1 } }]) What does this pipeline do?	Filters students with marks > 80 and sorts ascending	1		Sorts all students and then filters	Groups students above 80	Filters students with marks > 80 and sorts ascending	Deletes students above 80
429	9	db.students.aggregate([{ \$project: { name: 1, marks: 1, _id: 0 } }]) What will be the result?	Displays only name and marks fields	1		Displays only name and marks fields	Displays all fields except name	Deletes _id field permanently	Groups by name
430	9	db.students.aggregate([{ \$group: { _id: "\$department" } }]) What will be the output?	Unique departments	1		Students ordered by department	Unique departments	Total students count	Sorted departments
431	9	Map following SQL queries to MongoDB query: (1)SELECT * FROM USER WHERE status = "A" ORDER BY age DESC (2)UPDATE USER SET age = age + 3 WHERE status = "A" (3)SELECT * FROM USER WHERE status != "A"		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
432	9	Create a collection named Student having fields Name, age, standard, percentage. Insert 5 to 10 random documents in collection. 1.Find name of all students having age > 7 2.Increase the standard for all students by 1. 3.Arrange all the records in ascending order of age. 4.Show the name of student who is the oldest student among all students. 5.Delete the record of the student if standard is 12.		5	LJU 2025				
433	9	Create a collection name Student. Having fields name, age, std, percentage. 1)insert 3 random records in table. 2)find name of all student age>5. 3) update the std for all by 1. 4) arrange all the record of descending order of age 5)show all the name of student who is the oldest student of all records.		4					
434	9	Write query to perform following tasks on employee collection having fields name, age, position, salary. 1) Insert 3 documents with random data of having fields name, age, position, salary. 2) Count all employees where age is not equal to 35 and position is "Full Stack Developer". 3) Update position of all employees to "Software Developer" whose name is "XYZ" and age is equal to 31. If not such document available than insert the document with updated values. 4) Display position and name of the employee having lowest salary.		4					
435	9	Map following SQL queries to MongoDB query: (1) select age,name from employee where status="active" (2) select * from employee where status!="active" (3) select name from employee order by age desc (4)select * from employee where status="active" or age=50		4					
436	9	Write commands to perform following tasks on employee collection having fields name,age & joiningDate: (1) Insert 3-4 records in collection. (2) List all employees who joined before 1st January, 2010. (3) Update the name of employee to "WWW" whose joiningDate is "05-05-2015"		3					
437	9	Write commands to perform following tasks on employee collection having fields having name,age & joiningDate: (1) Delete all records having joiningDate before 1st January, 2010. (2) List all employees having age>50 years. (3) List only 1st employee having age>60 years.		3					
438	9	Write commands to perform following tasks on employee collection having fields having name,age & joiningDate: (1) Update the name="Senior citizen" having age>60 years. (2) Update the name="JKL" having age=20 years. Insert this record, if it is not found. (3) Retire all employees by deleting senior citizens from collection.		3					
439	9	Write commands to perform following tasks on employee collection having fields having name,age & joiningDate: (1) Count no. of employees having age>=60 years. (2) List all employees in descending order of names having names "ABC", "PQR", "XYZ". (3) List all employees whose age lies between 25 to 50 years excluding all rest of the fields.		3					
440	9	Map following SQL queries to MongoDB query: (1) alter table people add joiningDate datetime (2) alter table people drop column joiningDate (3) select age,name from people where status="PH" (4) select * from people where status!="PH" (5) select name from people order by age desc		5					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
441	9	Map following SQL queries to MongoDB query: (1) update employee set name="TTT" where age not in {12,33,44,55} (2) select count(*) from employee where age>23 (3) update employee set age=age+10		3					
442	9	List out comparison operators in MongoDB and explain with example.		4					
443	9	Consider the following collection named student: [{ name: "Rahul", branch: "CSE", marks: 85 }, { name: "Anita", branch: "CE", marks: 72 }, { name: "Vikram", branch: "CSE", marks: 90 }, { name: "Priya", branch: "CE", marks: 65 }, { name: "Arjun", branch: "CSE", marks: 75 }] Using MongoDB Aggregation Framework, write queries to: 1. Group students by branch and count total students in each branch. 2. Calculate the average marks for each branch. 3. Find the highest marks in each branch. 4. Display only students who scored more than 75 marks. 5. Sort all students by marks in descending order.		5					
444	9	Consider following student collection: [{ _id:123433,name: "SSS",age:22}, { _id:123434,name: "YYY",age:2}, { _id:123435,name: "PPP",age:32},] Do as directed: (1) Update name="JJJ" and age=40, where age=20 occurs. Insert new document, if record is not found. (2) To retrieve age and name fields of documents having names "YYY" & "SSS". Don't project _id field.		4					

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
Chapter 10									
445	10	Identify a correct query returning documents having a field surname occurring 6-10 letters only.	db.student.find({surname: {\$regex: /^[A-Za-z]{6,10}\$/}})	1		db.student.find({surname: {\$regex: /^[A-z]{6,10}/}})	db.student.find({surname: {\$regex: /^[A-Za-z]{6,10}\$/}})	db.student.find({surname: {\$regex: /^[^d]{6,10}\$/}})	db.student.find({surname: {\$regex: /^[A-Za-z]{6,10}/}})
446	10	_____property is used to remove leading and trailing spaces before/after a field of type string.	trim	0.5		remove_space	validate	trim	rm_space
447	10	Consider a collection student having documents like this: [{ _id:123433,name: "SSS",age:22}, { _id:123434,name: "YYY",age:2}, { _id:123435,name: "PPP",age:22},] Let say simple indexing is applied on a student collection on age field and we fire following query. db.student.find({age:22}).explain("executionStats") Identify values of stage, docExamined and nReturned properties of JSON.	stage:IXSCAN, docExamined:2, nReturned:2	1		stage:IXSCAN, docExamined:2, nReturned:2	stage:IXSCAN, docExamined:3, nReturned:2	stage:COLLSCAN, docExamined:1, nReturned:1	stage:COLLSCAN, docExamined:1, nReturned:2
448	10	Consider a collection student having documents like this: [{ _id:123433,name: "SSS",age:22}, { _id:123434,name: "YYY",age:2}, { _id:123435,name: "PPP",age:22},] Let say compound indexing is applied on a student collection on {age,name} field and we fire following query. db.student.find({name:"YYY"}).explain("executionStats") Identify values of stage, docExamined and nReturned properties of JSON.	stage:COLLSCAN, docExamined:3, nReturned:1	1		stage:COLLSCAN, docExamined:3, nReturned:1	stage:COLLSCAN, docExamined:1, nReturned:1	stage:IXSCAN, docExamined:1, nReturned:1	stage:IXSCAN, docExamined:3, nReturned:1
449	10	By default indexing is always applied on _____ field.	_id field maintained by default	1		1st field of table	Last field of table	_id field maintained by default	All of the above
450	10	_____property is used to restrict values while defining schema of a collection.	enum	0.5	LJU 2025	in	valid	enum	list
451	10	_____command is used to delete a document by _id field and show it after deletion.	findByIdAndDelete()	0.5		findAndDelete()	findByIdAndDelete()	delete()	findByIdAndDrop()
452	10	Consider a collection people having documents like this: [{ _id:1, name:"Test1",age:22}, { _id:2, name:"Test2",age:21}, { _id:3 ,name:"Test3",age:20},] Let say simple indexing is applied on a student collection on age field and we fire following query: db.people.find({age:20}).explain("executionStats") Identify values of stage, docExamined and nReturned properties of JSON.	stage:IXSCAN, docExamined:1,nReturned:1	1		stage:IXSCAN, docExamined:2, nReturned:2	stage:IXSCAN, docExamined:3, nReturned:2	stage:IXSCAN, docExamined:1,nReturned:1	stage:COLLSCAN, docExamined:2,nReturned:1
453	10	What should be correct code to match a string beginning with "Bharat" only.	db.state.find({name: {\$regex:/^Bharat/}})	1		db.state.find({name: {\$regex:/Bharat/i}})	db.state.find({name: {\$regex:/Bharat/}})	db.state.find({name: {\$regex: {name:/^Bharat/}}})	db.state.find({name: {\$regex:/^Bharat/}}})
454	10	Which of the following statements is true about the insertMany method in MongoDB?	It inserts multiple documents into a collection in a single operation.	1		It inserts multiple documents into a collection in a single operation.	It is used to delete documents from a collection.	It upsert a single document into a collection.	insertMany is only available in MongoDB Atlas, not in the open-source version.
455	1	You are working with a MongoDB collection named "sales" containing millions of documents. To optimize a specific query, you need to create a compound index on the "product_id" and "sale_date" fields. The "product_id" should be sorted in ascending order, and the "sale_date" should be sorted in descending order. Which of the following MongoDB commands correctly creates a compound index with the specified sorting order?	db.sales.createIndex({product_id: 1, sale_date: -1})	1	LJU 2023	db.sales.createIndex({product_id: 1, sale_date: -1})	db.sales.createIndex({product_id: 1, sale_date: 1})	db.sales.createIndex({product_id: 1}, {sale_date: -1})	db.sales.createIndex({product_id: 1, sale_date: -1})

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
456	10	Write an express JS script to insert a document in database using Mongoose.		4					
457	10	Explain stepwise process to connect with Mongoose and insert a document.		3					
458	10	Create a schema using Schema() constructor having name, surname, age, active and date fields. Name must accept strings and it is a required field. Age must accept numeric values only. Active must accept true/false. Date should have default today's date if it is not entered.		4					
459	10	How can we enter multiple documents in a database using express JS?		3					
460	10	Consider following student collection: [{ _id:123433,name: "SSS",age:22}, { _id:123434,name: "YYY",age:2}, { _id:123435,name: "PPP",age:32},] Do as directed: (1) Update name="JJJ" and age=40, where age=20 occurs. Insert new document, if record is not found. (2) To retrieve age and name fields of documents having names "YYY" & "SSS". Don't project _id field.		4					
461	10	Write a script to define a schema having fields like name,age,gender,email. Apply following validations: (1) name field must remove leading/trailing spaces,minimum and maximum length should be 3 & 10 respectively (2) age must accept a value from 1<=age<=100 only. (3) Perform Email ID validation on Email field. (4) gender must accept values in small letters only and allowed values are "male" & "female" only.		4					
462	10	Consider following student collection: [{ _id:123433,name: "2DD", surname:"GGG", age:22}, { _id:123434,name: "LLL", surname:"RRR", age:2}, { _id:123435,name: "KKK", surname:"III", age:32} { _id:123436,name: "ZZZ", surname:"TTT", age:9}] Do as directed: (1) List all students whose name starts by digit only. (2) List all students whose surname has exactly 4 letters only. (3) List only names of students from youngest to oldest. (4) List all students whose name has 3-10 letters only. Don't allow digits & underscore.		4					
463	10	Write a node.js script to insert 4 documents simultaneously in a collection. Assume that schema is already created having name(string), surname(string), age(Number), active(Boolean) fields.		5					
464	10	Consider a collection student having documents like this: [{ _id:123433,name: "DDD",age:32}, { _id:123434,name: "BBB",age:20}, { _id:123435,name: "AAA",age:10},] Do as directed: (1) Create an index & fire a command to retrieve a document having age>15 and name is "BBB". Stats must return values nReturned=1, docExamined=1, stage="IXSCAN". Perform required indexing. (2) Create an index on subset of a collection having age>30. Also write a command to get a stats "IXSCAN" for age>30.		4					
465	10	How COLLSCAN and IXSCAN differs in terms of indexing? How is it determined?		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
466	10	How \$regex operator is used to filter a specific values of a field. Explain with example.		3					
467	10	Write a node.js script to define a schema having fields like name,surname,email,password,city. Apply following validations: (1)name field must required . (2)surname must accept values in small letters. (3) Perform Email ID validation on Email field. (4) password must have minimum and maximum length should be 8 & 12 respectively (5)city allowed values are “baroda”,”surat” and “ahmedabad” only		5					
468	10	Create one login form having username , password and submit button . By clicking submit button username and password should be store inside database. Use mongoose and express module. write all necessary files		5					
469	10	Write a program using react and node/express to demonstrate a full stack connectivity. Take one textfield, submit button on react and insert a corresponding record in database via node/express script. Write required files.		5	LJU 2025				
470	10	Consider a collection student having documents like this: [{ _id:123433,name: "DDD",age:32}, { _id:123434,name: "BBB",age:20}, { _id:123435,name: "AAA BBB",age:10}] (1) Retrieve all records having “BBB” as a substring in name by indexing. Apply required indexing. Predict the values of nReturned & docsExamined properties also. (2) Create an index and fire a command to retrieve documents having age>15. Stats must return values nReturned=2 & docExamined=2, even though total 3 records are there.		5					
471	10	Create a React form which accepts Name,Rollno and totalmarks,on submitting the form it should be saved in data table inside MongoDB database named student.		5					
472	10	Create a form containing username and submit button using .html file.After clicking on submit button,insert value of username in the database.(Note: .html and .js file required)		4	LJU 2023				
473	10	Write a node.js script to define a schema having fields like name, age and gender Apply following validations: (1) name field must be required field with minimum and maximum length of 4 & 12 respectively (2) age must accept a value from 1<=age<=35 only. (3) gender must accept values in capital letters only and allowed values are “male” & “female” only.		3					
474	10	Write a script to have a “NAME” text field and a submit button in Form.js file. After clicking on submit button, insert that value of text field in database named ‘mydb’. (React MongoDB Connectivity)		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
475	10	Consider following citizens collection: [{ _id:123433, name: "DD", surname: "abc", age:61}, { _id:123434, name: "LL", surname: "def", age:38}, { _id:123435, name: "KK", surname: "pqr", age:29} { _id:123436, name: "ZZ", surname: "xyz", age:62}] Insert above data in "userdata" collection under database named "maindata" and write a query to perform below task in node.js. (1)Insert a category field with value "SeniorCitizen" having age greater than 60. (2)Display total number of documents having age between 30 and 60 only.		5	LJU 2025				
476	10	Consider collection named "movie" having documents like this: [{"title": "Inception", "director": "Christopher Nolan", "release_year": 2010}, {"title": "The Matrix", "director": "The Wachowskis", "release_year": 1999}, {"title": "The Avengers", "director": "Joss Whedon", "release_year": 2012,}] Do as directed: (1) Create a subset-based index that includes only movies released after the year 2000. Specify the field or condition used in the subset. Additionally, write a command to get a scan stage = "IXSCAN" for		5					
477	10	Write a node.js script to define a schema having fields like name, age, gender, email. Apply following validations: 1.Name field must remove leading/trailing spaces, minimum and maximum length should be 3 & 10 respectively, and name should be stored in lowercase 2.Age must accept value greater than 0. 3.Perform Email ID validation on Email field. 4.Gender must accept values in uppercase only and allowed values are "MALE" & "FEMALE" only.		5	LJU 2025				
478	10	Write a node.js script to define a schema having fields like Firstname, age, email, citychoice and insert one random document having collection name "applicant" under "applicantdata" database. Apply following validations: (1) Firstname field must remove leading/trailing spaces, minimum and maximum length should be 3& 10 respectively. (2) aplicant's age must be between 18 to 30. (3) Perform Email ID validation on email field. (4). citychoice must accept values in capital letters only and allowed values are "AHMEDABAD", " PUNE" & " BANGALORE " only.		5					
479	10	Consider following faculty collection: [{ _id:123456788, name: "ABC", subject: "FSD-2", age:27}, { _id:123456789, name: "PQR", subject: "PYTHON-2", age:31}, { _id:123456790, name: "XYZ", subject: "FSD-2", age:29}] Write a query for following: (1) Update name= "DEF" & age= 32, where subject= "JAVA-2". Insert new document, if record is not found. (2) Retrieve only name & age of documents having age greater than 28 & less than equal to 30.		3					

L.J. INSTITUTE OF ENGINEERING AND TECHNOLOGY, AHMEDABAD

Full Stack Development -2 (FSD-2) Practice Book (SEM-IV-2026)

Note: This Practice book is only for reference purpose. LJU Test question paper may not be completely set from Practice book.

Sr. No.	Unit	Question	Answer	Marks	Previous year	option1	option2	option3	option4
480	10	Create a React form that accepts: Employee Name Employee ID Salary Department On submit: Save data into MongoDB database named company Store data in collection employees Display saved employees in a table below the form		5					
481	10	Course Enrollment System Create a React form that accepts: Student Name Course Name Email Requirements: Save in MongoDB database courseDB Prevent duplicate enrollments		5					
482	10	Consider the collection products: <pre>[{ name: "Laptop", category: "Electronics", price: 70000, rating: 4.5 }, { name: "Mobile", category: "Electronics", price: 30000, rating: 4.2 }, { name: "Chair", category: "Furniture", price: 5000, rating: 3.8 }]</pre> Perform the following: Create a compound index on category and price. Write a MongoDB query to find products where: category = "Electronics" price < 60000 Use explain("executionStats") for the above query. Write the values of: execution stage nReturned totalDocsExamined		5					
483	10	Create Collection: product <pre>[{ name: "Laptop", category: "Electronics", price: 70000, stock: 10 }, { name: "Mobile", category: "Electronics", price: 30000, stock: 20 }, { name: "Chair", category: "Furniture", price: 5000, stock: 50 }]</pre> Tasks: Create index only for products where stock > 15. Query products with stock > 15 and explain execution stats. Create compound index on category and price. Query electronics products with price < 50000 and give: Also, give output of below. Scan stage nReturned docsExamined		5					
484	10	Write a node.js script to define a schema having fields like name & age. Apply following validations: (1) Name field must remove leading/trailing spaces, must accept values in lowercase, allowed values are "abc", "def", "pqr", "xyz" & maximum length should be 10. (2) age must accept a value from 1<=age<=100 only.		3					