



## CFS-SP WB Firestop Joint Spray

### Product description

A sprayable fire rated seal for use in curtain wall edge of slab and head of wall joints where up to 50% movement is required.

### Typical Application Examples

- Curtain Wall Joint
- Top-of-wall Joint
- Expansion Joint

### Product features

- Contains no halogens, solvents or asbestos
- Water based, easy to clean
- Sprayable or may be applied by brush
- Excellent adhesion to most substrates

### System Advantages

- Quick and easy installation with an Airless Sprayer saves you time and money
- Maximum flexibility, exceeds 500 cycle requirements
- Proven to resist seismic type cycling movements
- CFS-SP WB contains no halogens, solvents or asbestos



### Technical Data

Color:	Red
Chemical basis	Latex based dispersion
Working time	30-45 minutes
Curing time	48 hours
Ph-value	Approx. 7.8
Movement capability	Approx. 50%
Sound transmission classification (ASTM E 90-00):	55
Shelf life	12 months

**Base materials:** Drywall, masonry, concrete, curtain-wall

**For use in:** Walls and floors.

**Fire rating:** Walls Up to 3 hrs, curtain-wall Up to 2 hrs.



Smoke



Water Tight



Acoustic



Seismic



Low VOC



Mould & Mildew



### Application Procedure

