



# Hilti Mineral wool board system Firestop Coated Acoustic Board

## Product Description

- An innovative system for fast, reliable and cost effective firestopping.

## Typical Application Examples

- Cable Tray Penetration
- Multiple Penetration

## Product Features

- Size of board : 1000mmx600mmx60mm
- Odourless and solvent free
- Less prone to damage due to pliancy of the material and the resilient elastic coating
- Fast tight seal, less sealant required for gap filling



**Base materials:** Drywall, masonry, concrete.

**Fire rating:** Upto 4 hours.



Smoke



Water  
Tight



Acoustic



Siesmic



Low VOC




Mould &  
Mildew




## Technical Data

Chemical basis,CP 606:	Acrylic dispersion 310ml
CP 606-Colour:	White
Curing rate:	Approximate 3mm in 3 days
CP 670-Color:	White
Curing rate:	Approximate 1 mm in 1 day
CP 670 Content:	6kg
Dry film Thickness:	0.7mm
Consistency	Can be applied by paint brush
Storage/transport temperature	-5°C to+ 30°C
Shelf life after production-GP 670 (stored in a dry place)	12 months


## Application Procedure




1. Clean the  
opening




2. Coat cut edges  
with CP 606



3. Fit CP 670



4. Fill gaps  
with CP 606



5. Fasten  
installation  
(if required)



CP670



310ml cartridge



Dispenser CFS- DISP