

# A Lean Audit of the IUT III Corollary 3.12 Corridor

IUT Lean formalization project

June 25, 2026

## Abstract

We report on a first Lean formalization of the logical corridor from IUT III, Theorem 3.11 to Corollary 3.12. The formalization is deliberately neutral with respect to the correctness of IUT as a proof of the abc conjecture. It isolates the ordered-real comparison required at the end of Corollary 3.12, tracks the finite  $q^{j^2}$  and label-quotient phenomena that enter the public dispute, and records exactly which source-facing construction hypotheses are still external.

The code still has conditional layers, but the preferred finite-divisor surfaces are no longer merely the ordered-real implication. The oldest boundary proves  $C_\Theta \geq -1$  from the supplied signed comparison  $-|\log(\Theta)| \leq C_\Theta |\log(q)|$ . The newer source-facing boundaries derive that comparison from Remark 3.9.5 hull/determinant data together with local-to-global *IUT IV*  $C_\Theta$  source objects. The latest closed  $C_\Theta$  wrappers now thread the constructed qualitative Hodge/SHE/IPL source through the one-sided finite-place route and the strongest additive-Haar arithmetic-degree/ $p$ -adic formula route, rather than using a free-standing IPL record. This does not prove Corollary 3.12 from Mochizuki’s published hypotheses; it identifies the remaining mathematical construction problem at a lower, source-facing boundary.

After a source audit against IUT I–IV, Mochizuki’s 2026 LeanForm report, and Scholze–Stix, the status is unchanged in kind but sharper in formulation: the final ordered-real implication is formalized, several collapse-prone comparison levels are separated, and the current local-to-global  $C_\Theta$  route is proof-carrying. The code still assumes substantial source constructions: the full Hodge-theater/Frobenioid/log-Kummer apparatus, genuine holomorphic hulls and determinants, and the deepest *IUT IV* local analytic estimates.

## 1 Aim and Sources

The project formalizes a narrow and contested part of Mochizuki’s inter-universal Teichmüller theory. The source base is the local copy of IUT I–IV, Mochizuki’s 2026 report on formalization, and the Scholze–Stix note. The current target is the portion that Mochizuki’s report calls Stage 1:

$$\text{IUT III, Theorem 3.11} \xrightarrow{\text{APT+IPL}} \text{“3.11.5”} \xrightarrow{\text{SHE+IPL}} \text{IUT III, Corollary 3.12.}$$

The notation “3.11.5” is not a statement in IUT III. It is Mochizuki’s 2026 name for the reorganized boundary where the hull-plus-determinant operation is moved before the final simultaneous comparison of the  $\Theta$ -pilot and the  $q$ -pilot.

The formalization is source-facing but not source-complete. It does not construct Hodge theaters, Frobenioids, log-shells, prime strips, or theta links from first principles. Instead, these are represented by typed records with named hypotheses. The point of the current work is to test whether the claimed formal corridor is coherent once every comparison level, label quotient, ordered real line, hull boundary, and quotient collapse is made explicit.

## 2 Framework and Tooling

The repository is organized as a Lean verification project, not as a prose annotation project. The source papers in `docs/` are treated as the mathematical source of truth. The formalization then moves through three layers:



The paper draft records only the current mathematical state of the formalization. It is not a research log.

The Lean code uses typed interfaces to prevent comparison-level drift. A datum that is merely a representative  $j^2$ -coordinate computation has a different type from a balanced full-label datum, and both differ from the final hull/log-volume comparison datum. Likewise, ordered real-line transports, Hodge/SHE preservation records, upper-ray membership, and quotient-collapse audits are separate structures. This is the main anti-collapse mechanism in the framework: a proof cannot silently use a raw coordinate equality where the Corollary 3.12 corridor asks for a hull/log-volume comparison.

The module roles are:

- **IUTStage1SourceCore**: core real-line, pilot, hull, quotient, and  $C_\Theta$  algebra.
- **IUTStage1Remark312Absorption**: Remark 3.12.2(v) absorption interfaces.
- **IUTStage1IUTIVAlgebra**: Remark 3.12 sign shadows and the conditional IUT IV real-algebra handoff estimates.
- **IUTStage1FiniteLabels**: finite local log-volume endpoints,  $F_\ell$ -label/torsor/sign/cusp-label models,  $ZMod$  full labels, theta-root cusp-label source packages, and label-averaged log-volume compatibility.
- **IUTStage1StepX**: procession tensor-packet log-volume, the Step (x) indeterminacy corridor, the theta-hull upper-ray handoff, and local Frobenioid shift diagnostics attached to that boundary.
- **IUTStage1Gaussian**: weighted label averages,  $ZMod$  square-weight profiles, Gaussian monoid degree evaluations, and Hodge–Arakelov theta-evaluation source objects.
- **IUTStage1HodgeSHE**: square-weighted full-label transport audits, Hodge/SHE local object data, packet-normalization support, direct-summand local tensor actions, and upper-semi compatibility states.
- **IUTStage1Theorem311**: Theorem 3.11 choice/indeterminacy records, multiradial possible-image records, algorithm-output records, and SHE-alignment source records.
- **IUTStage1StepXI**: Step (xi) hull/determinant and IPL source objects, source obligations, package-audit constructors, and holomorphic hull/determinant source routes.
- **IUTStage1FrobenioidShift**: endpoint-audit surfaces together with the nonarchimedean realified-Frobenioid/log-Kummer, vertical- $IQ$ , and root-of-unity support routes.

- **IUTStage1EndpointAudit**: nested LogVolumeChartAudit refinements around the place-audited multiradial theta-hull endpoint.
- **IUTStage1Source**: remaining public source-package audit surface around the Corollary 3.12 corridor.
- **IUTStage1Experiments**: compiled endpoint checks and diagnostic theorems.

The experiment file is not a substitute for proof. It is a curated surface that forces the important route theorems to elaborate together and exposes Boolean/report endpoints such as whether the present stage settles the dispute. At present that endpoint is deliberately false.

The build discipline is simple. Each mathematical increment is checked by Lean via `lake build Iut.Stage1.IUTStage1Experiments`; the paper is rebuilt from this LaTeX source; and the code is scanned for explicit proof placeholder and trust-boundary tokens. The long-term collaboration plan is compatible with Apodixis: the current typed route endpoints and missing-obligation records give a natural surface for a collaboration tool to show which mathematical interfaces are proved and which remain open.

### 3 Dispute Interface

In IUT III, Step (x) treats the procession-normalized log-volume as unchanged under (Ind1) and (Ind2), while (Ind3) supplies a one-sided upper-semi comparison. Step (xi) then passes through multiradiality, IPL, SHE, holomorphic hulls, determinants, and log-volume to place the  $q$ -pilot reading in the signed-log upper ray determined by the  $\Theta$ -pilot:

$$-|\log(q)| \in \mathbb{R}_{\leq -|\log(\Theta)|}.$$

The active source-facing Corollary 3.12 route does not use equality of possible-image regions across an (Ind3) generator. Such an equality exists only in separate quotient bookkeeping interfaces as an explicit stronger hypothesis; the route uses the one-sided upper-semi corridor as its Step (x) input. The current Theorem 3.11 source record now bundles structured IPL/SHE/APT input, coric multiradial output, possible theta-pilot images, the 0-column/1-column pilot distinction, distinct log-shell treatments, and the Hodge-theater history guard. This is still not a full construction of Theorem 3.11, but the indeterminacy/log-volume boundary is no longer a single raw record: the finite  $F_l$ -averaged procession source now constructs the typed (Ind1), (Ind2), (Ind3) core, deriving (Ind1) and (Ind2) log-volume invariance from theta-pilot-class invariance. A stronger upper-semi comparison source now derives the (Ind3) average inequality from two alignments with the source and target log-volume coordinates of the upper-semi compatibility state, together with the existing one-sided upper-semi bound. This has now been lowered once more: a vertical log-Kummer packet-alignment source inserts a typed nonarchimedean local tensor packet for each concrete choice, proves that the theta-pilot average is the packet-normalized log-volume, and then aligns the source and target packets with the upper-semi source and target coordinates. This packet-aligned source now feeds the public one-sided Theorem 3.11 multiradial constructor: the typed core, quotient possible images, canonical  $F_l$ -procession action, selected  $q$ -region, and exclusion of (Ind3) from the equality quotient are all exported through the same endpoint used by the Remark 3.9.5 and  $C_\Theta$  corridor. The remaining mathematical payload is to construct the packet calibrations themselves from the full vertical log-Kummer/log-link data, rather than taking them as boundary fields. The IPL layer has been separated into a typed log-volume transport datum: it carries the source and target Hodge-theater

sides, identifies the prime-strip link endpoints with the input and output prime strips, records equality of the transported real log-volume, and retains the no-history-identification guard. It is not yet a construction of the full log-link. The current SHE layer now has a synchronization constructor: equality of the canonical one-label Hodge–Arakelov theta-value degree constructs the factored square/full-label preservation package used by the route. This is a Stage 1 source constructor for the available finite-label shadow of SHE, not yet the full simultaneous-holomorphic-expressibility theorem. The hull/determinant layer now has a source constructor attached to the Theorem 3.11 record. It reads the algorithmic certificate and SHE alignment from that record, keeps the record's theta possible-image union tied to the hull endpoint, and derives the determinant-bound comparison  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The bridge used by this source data can now be constructed from a displayed common hull containing the target union and a determinant/log-volume bound for that hull; the analytic construction of the hull and determinant remains external source data. The strongest Hodge–Arakelov packet-target route no longer takes the target-side log-volume equality or  $q$ -pilot positivity as independent inputs: target equality is derived from the SHE synchronization constructor, and positivity is read from the hull/determinant constructor. The source-side chart calibration is no longer a raw equality input: it is a full-label theta/Hodge calibration certificate, from which equality of the cusp log-volume compatibility records is derived extensionally. The strongest current labelled Step (x) route now consumes a theta-root realified-Frobenioid log-Kummer entry source. The Kummer and mono-analytic forgetting transfers, realization tags, holomorphic-forgetting assertion, and packet-local source alignment are projected from this source object instead of being passed separately to the Corollary 3.12 route. Its labelled  $ZMod(\ell)$  capsule family is now constructed as the constant packet-local family over the audited packet local object; the route no longer accepts an arbitrary labelled family or a separate local-object equality for that family. The exact vertical- $IQ$  target has also been retained inside a refined realified Step (x) source, so the route consumes one source object carrying both the realified log-Kummer entry data and the  $FMOD$ -exact target guard. The refined source now also requires the realified packet target calibration to be exactly the calibration induced by this retained vertical- $IQ$  target. The strongest public experiment route now constructs this refined source from theta-root data, realified Frobenioid transfer data, source alignment, and the vertical- $IQ$  target before entering the Corollary 3.12 corridor. A finite-divisor form of the same route derives the packet-local source alignment from the finite divisor/Frobenioid packet product before constructing the refined exact source. Its public experiment audit endpoint exposes the packet-local/source equality, mono-analytic product equality, divisor-degree normalization, (Ind3)-source equality, and upper-semi inequality used by this construction. For the canonical packet-local labelled family, this exact route no longer requires direct packet-normalization: Hodge labelwise averaging identifies the canonical labelled average with the theta-source average, and the retained vertical- $IQ$  target identifies that average with the packet-normalized capsule value. The final numerical step is elementary:

$$-|\log(q)| \leq -|\log(\Theta)| \leq C_{\Theta}|\log(q)|, \quad |\log(q)| > 0 \implies C_{\Theta} \geq -1.$$

Scholze–Stix object to the comparison because the  $\Theta$ -side data carries  $j^2$ -scaled degrees, while a naive identification of ordered real lines appears to remove the room needed for these scalars. The formalization therefore separates four comparison levels:

representative  $j^2$  data  
balanced sign-compatible data  
averaged cusp-label data  
hull/log-volume data.

The final route consumes only the hull/log-volume comparison level. Lean rejects the balanced sign-compatible level as sufficient for the final comparison.

## 4 Source Audit

The local sources impose the following constraints on the formalization. IUT I constructs the initial  $\Theta$ -data and the  $\Theta^{\pm\text{ell}}$ NF-Hodge theaters. It is not merely a notation layer: the paper’s central point is that the Hodge theaters separate the additive and multiplicative combinatorial dimensions of a number field. IUT II supplies the Hodge–Arakelov theta evaluation, theta values at  $\ell$ -torsion points, Gaussian Frobenioids, conjugate synchronization, and the multiradial/coric phenomena needed later. The current code models only finite label and Gaussian degree shadows of this material.

IUT III is the direct source for the formal corridor. Step (x) says that procession-normalized log-volumes are invariant under (Ind1) and (Ind2), while (Ind3) becomes an upper-semi inequality after applying log-volume. Step (xi) uses the multiradial construction, IPL, SHE, holomorphic hulls, determinants, and the 1-column log-Kummer correspondence to put the  $q$ -pilot log-volume in the signed-log upper ray  $\mathbb{R}_{\leq -|\log(\Theta)|}$ . Step (xii) warns that replacing global realified Frobenioids by local Frobenioids loses calibration because local objects carry  $p_v^N$ -type endomorphisms. Remark 3.12.2 further stresses that the argument depends on weakened data, distinct  $q/\Theta$  labels, upper-semi indeterminacy, and the asymmetry between the 0-column  $\Theta$ -pilot and the 1-column  $q$ -pilot. The current Step (x) packet source reflects this asymmetry by packaging the 1-column  $q$ -pilot non-interference, Kummer/forgetting product preservation, source packet calibration, and packet-normalized target calibration in a single realified-Frobenioid log-Kummer source object. The latest route theorem uses this object directly: it still assumes the finite source object, but it no longer permits the downstream proof to mix unrelated Kummer, forgetting, realization, and packet-local calibration witnesses. The labelled procession average used by this route is also no longer arbitrary: Lean constructs the constant  $ZMod(\ell)$ -indexed capsule family from the packet local object and proves its normalized value by averaging a constant finite family. The exact target face is now represented by a refined source object rather than by a discarded calibration projection: the object keeps the vertical- $IQ$  target itself and exposes the  $FMOD$ -exactness predicate together with the packet-normalized target equalities. It also ties the realified packet target calibration to the retained vertical- $IQ$  target, so the exact face cannot be displayed while an unrelated packet calibration is used downstream. This removes direct packet-normalization only for the canonical exact source route; arbitrary labelled families still require their own packet-normalization evidence.

IUT IV uses the resulting log-volume estimate as input to elementary log-volume and Diophantine inequalities. Our IUT IV code is therefore only conditional algebra at present: it records how later estimates consume a Corollary 3.12-shaped bound, but it does not prove that bound from the full arithmetic constructions.

Mochizuki’s 2026 report explicitly recommends Stage 1 as the implication  $IUT\ III$ , Theorem 3.11  $\Rightarrow$  Corollary 3.12, with a reorganized intermediate “3.11.5” obtained by moving the hull-plus-determinant operation before the final simultaneous comparison. The same report states that the current official code is skeletal. Our formalization is best read as a more diagnostic Stage 1 interface: it does not replace Stage 2, because it has not constructed Theorem 3.11.

Scholze–Stix argue that, after simplification, the comparison loses the  $j^2$ -scaled theta contribution and becomes essentially contentless. The Lean code therefore treats the  $j^2$ -representative level, sign quotient, averages, square/full-label preservation, ordered real-line transports, and hull/log-volume endpoint as different types. This confirms that the final Corollary 3.12 endpoint cannot be

obtained from the balanced sign-compatible level alone. It does not prove that Mochizuki’s source constructions supply the missing higher-level data.

## 5 Formalized Corridor

The relevant implementation lives in the following Lean modules:

- `Iut/Stage1/IUTStage1SourceCore.lean`
- `Iut/Stage1/IUTStage1Remark312Absorption.lean`
- `Iut/Stage1/IUTStage1IUTIVAlgebra.lean`
- `Iut/Stage1/IUTStage1FiniteLabels.lean`
- `Iut/Stage1/IUTStage1StepX.lean`
- `Iut/Stage1/IUTStage1Gaussian.lean`
- `Iut/Stage1/IUTStage1HodgeSHE.lean`
- `Iut/Stage1/IUTStage1Theorem311.lean`
- `Iut/Stage1/IUTStage1StepXI.lean`
- `Iut/Stage1/IUTStage1FrobenioidShift.lean`
- `Iut/Stage1/IUTStage1EndpointAudit.lean`
- `Iut/Stage1/IUTStage1Source.lean`
- `Iut/Stage1/IUTStage1Experiments.lean`

### 5.1 Finite label model

The code defines a finite  $\mathbb{F}_\ell$ -label model, the quotient  $|F_\ell|$  consisting of the zero class together with  $\mathbb{F}_\ell^\times/\{\pm 1\}$ , and the canonical half-range representatives

$$j = 0, \dots, (\ell - 1)/2.$$

The Stage 1 label model is now connected to the bad-local theta-root data of IUT I, Definition 3.1(e),(f). A new source package consumes the quotient- $\mathbb{Z}$  data of a bad local theta-root model and derives the Stage 1 full label from its canonical coordinate. It also carries the canonical-generator-up-to-sign witness. In the concrete  $\mathbb{Z}/\ell\mathbb{Z}$  quotient case this derived full label is exactly the nonzero canonical full label corresponding to coordinate 1. It proves, for the descended full-label degree model:

$$\deg(\Theta_j) = j^2 \deg(q)$$

for the degree-level Gaussian endpoint, with sign invariance on the full-label quotient. It also proves that  $j = 1$  and  $j = 2$  give distinct degrees exactly when  $\deg(q) \neq 0$ . Thus the  $q^{j^2}$  phenomenon is present in the model; it is not hidden inside a scalar identification.

The raw coordinate square-weight profile on  $\mathbb{Z}/\ell\mathbb{Z}$  is kept as a diagnostic object and is not identified with the descended  $|F_\ell|$  theta exponent. The coordinate average, the nonzero-coordinate

average, and the absolute-label average are all formalized separately. Lean proves the exact denominator relations and shows that these averages differ strictly for nonzero environment degree. This prevents silently replacing the paper’s  $\ell$ -denominator convention by an auxiliary nonzero-only average.

## 5.2 Indeterminacy and upper-semi route

The Step (x) corridor is represented as:

$$A_0 = A_1 = A_2 \leq U_{\text{Ind3}},$$

where  $A_0, A_1, A_2$  are the before-, after-(Ind1)-, and after-(Ind2)-averaged log-volumes, and  $U_{\text{Ind3}}$  is the (Ind3) upper-semi target. From this data and the hull/determinant identifications, the code constructs the Step (xi) upper-ray datum:

$$q_{\text{avg}} \leq \Theta_{\text{hull}}.$$

The same route constructs the two  $q$ -pilot readings in Step (xi-g) and proves that they are equal to the same fixed real value. The typed (Ind3) law is now represented by `Ind3UpperSemiStepAudit` and `Ind3UpperSemiRelationAudit`. These certificates record the source and target log-volume coordinates of each (Ind3) step, the one-sided upper-semi inequality, and the explicit exclusion of (Ind3) from the (Ind1)/(Ind2) equality quotient used for possible-image identifications.

## 5.3 SHE and Hodge-descent boundary

The current SHE layer is conditional. It has typed records for:

structured SHE square-weight transport  
factored square/full-label preservation  
Hodge-descent packet transport  
nonarchimedean (Ind3) source-target alignment.

Given these inputs, Lean constructs the weighted theta comparison consumed by the final route:

$$q_{\text{signed}} \leq \Theta_{\text{signed}}.$$

The nonarchimedean (Ind3) entry, factored square/full-label preservation, and Hodge-descent packet transport now compose directly to this comparison. With the  $q$ -pilot positivity condition and the displayed  $C_\Theta$ -bound, the same composed route instantiates the signed  $C_\Theta$  endpoint and proves  $C_\Theta \geq -1$ . The instantiated endpoint also exposes the strict and boundary alternatives: strict source comparison gives  $C_\Theta > -1$ , while  $C_\Theta = -1$  forces equality of the signed  $q$ - and  $\Theta$ -readings and makes the  $\Theta$ -reading negative. These facts are now also packaged as a single route-level alternative: boundary equality with negative  $\Theta$ -reading, or strict  $C_\Theta > -1$ . The code also proves a Gaussian-to-factored-SHE bridge at the present finite degree level. In particular, equality of the source and target environment degrees gives full-label value preservation; nonzero-label target bounds are enough because the zero label has square weight zero. The newest route uses this bridge before applying the nonarchimedean endpoint: Gaussian degree evaluations with preserved environment degree now construct the factored square/full-label preservation package consumed by the nonarchimedean  $C_\Theta$  dichotomy. This removes one primitive preservation input from that route, but it still assumes the nonarchimedean (Ind3) alignment and the Hodge-descent/SHE source audit. There is also an identity-coordinate specialization. In that case equality of Gaussian degree

at the canonical full label 1 implies preservation of the environment degree, so the nonarchimedean  $C_\Theta$  dichotomy no longer takes environment-degree preservation as an independent hypothesis. The Hodge–Arakelov/Gaussian bridge is now source-facing at the current degree level. A theta-value evaluation source carries the bad-local theta-root label data and a theta-monoid degree  $d$ , and constructs the Gaussian degree evaluation

$$\deg_{\text{gau}}(\lambda) = e(\lambda) d,$$

where  $e(\lambda)$  is the absolute-label theta exponent. The zero label has degree 0, and the canonical label 1 has degree  $d$ . Thus equality at the canonical label derives equality of the environment degree and feeds the factored SHE square/full-label obligations. The raw nonarchimedean entry alignment has also been refactored through a source-facing nonarchimedean upper-semi object equipped with 1-column q-pilot log-Kummer data. The upper-semi inequality remains the Step (x) input; the 1-column datum records the q-pilot column and log-Kummer non-interference before converting to the raw real equalities consumed by the current route. For the source side of this compatibility, the code can now use the existing finite tensor-packet chain: Kummer transfer  $\text{holomorphicF} \rightarrow \text{holomorphicD}$  and mono-analytic forgetting  $\text{holomorphicD} \rightarrow D^+$  preserve product log-volume. Thus the source-side upper-semi equality may be derived from this chain rather than postulated as a bare equality. The newest source package attaches this finite Kummer/forgetting chain to the bad-local theta-root cusp-label source. It carries the canonical nonzero  $|F_\ell|$ -label and derives the nonarchimedean (Ind3) source equality from product-log-volume preservation along

$$\text{holomorphicF} \rightarrow \text{holomorphicD} \rightarrow D^+.$$

The packet local object, local entry source, mono-analytic product, and holomorphic source product are now packaged as one source-side log-Kummer packet calibration object. The object itself is still supplied source data, but the equality from entry source to (Ind3) source is derived from it together with the Kummer and forgetting maps. The source calibration can now also be constructed from the explicit packet-local/source alignment, the packet-local (Ind3)-source alignment, and the two product-preservation maps. Thus the route no longer has to accept the holomorphic source-product equality as a primitive field when these Step (x) alignments are available. The source and target packet calibrations are now joined by a finite log-Kummer packet-correspondence source carrying the q-pilot column and non-interference guard. Its target face carries the common packet-normalized capsule value, and Lean derives the direct theta-to-entry, theta-to-packet, and entry-to-(Ind3)-target equalities consumed by the upper-semi route. The target calibration no longer contains an independent real representative for this common value: all target equalities are stated directly against the packet-normalized capsule log-volume. This removes one artificial identification layer from the Step (x) interface. The target face has also been refined by a vertical- $IQ$  source object, following IUT III, Proposition 3.10(ii). The theta average, the (Ind3)-target value, and the local entry target are represented as points of one log-Kummer  $IQ$ -target whose values agree with the packet-normalized point. The packet-target calibration is then constructed from this vertical- $IQ$  source, so the corresponding theta-to-entry and entry-to-(Ind3)-target equalities are derived from common-target compatibility rather than passed as separate target-calibration inputs. This object is guarded by the exact  $FMOD$  side of Proposition 3.10(iii) and Remark 3.10.1: the one-sided  $Fmod$  upper-semi mode is classified separately and is not accepted as an exact vertical- $IQ$  target calibration. The local entry target can now also be constructed from the packet-normalized capsule value itself. A packet-normalized entry-target source builds a nonarchimedean upper-semi entry whose target finite log-volume is definitionally the packet-normalized capsule value. The corresponding target calibration therefore no longer needs an independent proof for the entry-target



equality; only the theta-average and (Ind3)-target identifications with the same packet-normalized value remain as inputs at this level. The latter can now be reduced further: if the Step (x) target-side (Ind3) alignment gives equality of the theta average with the (Ind3) target, then Lean derives the (Ind3)-target-to-packet-normalized equality from this alignment and the theta-average-to-packet-normalized equality. The packet-correspondence source itself can now be built from this reduced target data together with the source packet/product calibration. Thus the correspondence constructor no longer needs a completed target-calibration record when the target entry and theta-target alignment are available. It can also be built directly from the packet-local source alignments and the same target theta alignment. In this form both the source packet calibration and the target packet calibration are generated before the q-pilot non-interference endpoint is projected. The same reduction has been lifted through the realified-Frobenioid packet source: realified Kummer compatibility still supplies the  $\text{holomorphicF} \rightarrow \text{holomorphicD} \rightarrow D^\perp$  transfer, while the target face is now generated from the packet-normalized entry target and theta-target alignment. The realified entry source and the theta-root attached realified entry source can also consume the vertical- $IQ$  target source directly; their upper-semi endpoint then derives the theta-to-entry and entry-to-(Ind3)-target equalities through the common log-Kummer target rather than through separate target alignment inputs. This vertical- $IQ$  source now reaches the integrated Hodge/SHE/IPL/hull route: the first-pass  $C_\Theta$  dichotomy can be stated without the ordered-real-line target alignment and without the auxiliary packet-normalized  $ZMod(\ell)$  route whenever the exact common  $IQ$ -target is supplied. The same route has a source-reduced form: packet-local/source alignment, entry-source/mono-analytic-product alignment, packet-local/(Ind3)-source alignment, and the realified Kummer/forgetting compatibilities construct the source calibration internally before the vertical- $IQ$  target enters the final inequality route. This reduction now also exists at the Step (x) source-object level: an upper-semi packet-normalized entry, packet-local source alignments, realified Kummer/forgetting compatibility, and an exact vertical- $IQ$  target construct one realified log-Kummer entry source before the Hodge/SHE/IPL/hull route is applied. The realified source can now also generate the source packet calibration from packet-local/source alignments before forming the correspondence; consequently the strongest realified Step (x) constructor no longer needs a completed source calibration as input. The first-pass Gaussian route also has a one-correspondence form: it consumes a finite log-Kummer packet-correspondence source and projects the source packet/product calibration and target packet-normalized calibration from that single object before entering the upper-semi corridor. The same correspondence now has a transfer-chain endpoint exposing the  $\text{holomorphicF} \rightarrow \text{holomorphicD} \rightarrow D^\perp$  product log-volume equalities, the source equality with the (Ind3) real source, the target packet-normalized equalities, and q-pilot non-interference from the same object. The current strongest Step (x) entry source places this correspondence below the realified Frobenioid layer: the selected nonarchimedean upper-semi entry and the realified-Frobenioid packet source are bundled together, and Lean projects the Kummer transfer, mono-analytic forgetting transfer, source calibration, target packet calibration, and q-pilot non-interference guard from that single source object. There is now a reduced constructor for this entry source: entry membership, packet-local/source alignment, packet-local (Ind3)-source alignment, packet-normalized target data, and theta-target alignment construct the realified packet source internally and then derive the upper-semi inequality. The bad-local theta-root label source is now attached to this realified entry source. The corresponding Hodge-Arakelov route consumes one object carrying the canonical nonzero theta-root label, the selected upper-semi entry, and the realified-Frobenioid log-Kummer packet source before entering the  $C_\Theta$ -dichotomy. This theta-root attached source now has the same source-reduced vertical- $IQ$  constructor: the theta-root label package is combined with the upper-semi packet-normalized entry, packet-local source alignments, realified Kummer/forgetting compatibility, and the exact vertical- $IQ$  target. Lean then projects the canonical-label facts, transfer-chain

product equalities, target packet calibrations, q-pilot non-interference, and the Step (x) upper-semi inequality from this single source object. The packet-local source side is now bundled as a named alignment object: packet-local/source equality, entry-source/mono-analytic-product equality, and packet-local/(Ind3)-source equality travel together before constructing the packet source calibration. Conversely, a source packet/product calibration together with the Kummer and mono-analytic forgetting transfers reconstructs this packet-local alignment object; the packet-local/(Ind3)-source equality is derived through the transfer chain rather than supplied as a parallel datum. When the mono-analytic packet product is supplied by the finite divisor/Frobenioid product source, Lean now derives the entry-source/mono-analytic-product equality from the packet-local object identification and the finite divisor realified log-volume computation. This recovery has now been lifted to the realified-Frobenioid packet source: Lean uses the source object's own Kummer and mono-analytic forgetting compatibilities to reconstruct the packet-local source alignment. At the realified Step (x) entry level, the same projection also carries the upper-semi membership of the selected nonarchimedean entry. At the theta-root attached level, the projection also carries the canonical bad-local theta-root generator and nonzero full-label facts. The final Hodge/SHE/IPL/hull route now has an audit form that returns this recovered packet-local source alignment together with the  $C_\Theta$  dichotomy. The target-only (Ind3) alignment is also derived at route level from the Step (x) packet-normalized theta source and the exact vertical- $IQ$  target, with the  $FMOD$ -exactness guard retained. An audit form of this route exposes the derived equality between the Hodge-descent theta average and the (Ind3) target value. At the packet-correspondence layer, this source-alignment object and the exact vertical- $IQ$  target now construct one log-Kummer correspondence source. The realified-Frobenioid packet source uses this correspondence-level constructor, so source and target Step (x) calibrations enter through a single packet source before the theta-root entry source is formed. The same correspondence-level reduction is now available for the packet-normalized ordered target: the named source-alignment object constructs the source face before the theta-average and target (Ind3) alignments construct the target face. The theta-root attached entry source now also projects this packet correspondence, so the canonical bad-local label facts and the full Step (x) transfer/target calibration endpoint are exposed from one source object. The Hodge/SHE/IPL/hull route has the same realified endpoint: its alignment record supplies the Hodge–Arakelov Gaussian comparison, canonical-one preservation, q-pilot positivity, and theta/Hodge log-volume calibration, while the Step (x) data enters through the single theta-root attached realified source. The route now also has a source-reduced endpoint: the theta-root label package, entry membership, packet-local source alignments, packet-normalized target alignment, and realified Frobenioid compatibility construct the Step (x) source inside the theorem before proving the same  $C_\Theta = -1$  boundary alternative or strict  $C_\Theta > -1$  conclusion. For the vertical- $IQ$  form, the theorem now constructs the theta-root attached realified Step (x) source object directly from this source-alignment object and the exact  $IQ$ -target before applying the Hodge/SHE/IPL/hull endpoint. At the non-theta-root realified entry level, the corresponding source-aligned vertical- $IQ$  endpoint now exposes the  $FMOD$ -exactness guard itself, together with Kummer/forgetting product preservation, target packet normalization, q-pilot non-interference, and the upper-semi inequality. The same exactness exposure has been lifted through the bad-local theta-root source: the canonical theta-root label data, exact vertical- $IQ$  condition, packet-normalized target equalities, and Step (x) upper-semi inequality now appear in one theta-root attached endpoint. The packet-normalized theta-source calibration is now also consumed through a single Step (x) alignment object: the constant  $ZMod(\ell)$  packet-normalized route and the proof that it has the same theta source as the Hodge-descent route are bundled before Lean derives the theta-average-to-packet-normalized equality used by the final corridor. The ordered-real-line form now has the same source-aligned boundary: the packet-local source-alignment object and realified Kummer/forgetting compatibility construct the source calibration internally before the matched

theta-target alignment is used. This has been narrowed further to a target-only (Ind3) alignment: source-side packet-to-(Ind3) information is taken from the packet-local source-alignment object, while only the theta-average-to-target equality remains as ordered-real input. That target-only alignment is now constructible from Step (x) packet-normalized theta-source alignment together with an exact vertical- $IQ$  target: Lean derives both sides through the common packet-normalized value and keeps the  $FMOD$ -exactness guard visible. The corresponding realified-source audit removes the independent packet-local source-alignment parameter: the alignment is recovered from the theta-root attached realified log-Kummer entry source, while the exact vertical- $IQ$  target supplies the target-side equality and  $FMOD$  guard. The stronger realified-source audit also removes the separate packet-normalized theta-source route at this boundary: theta packet normalization is projected from the same realified log-Kummer entry source, and the vertical- $IQ$  target supplies only the (Ind3)-target packet-normalized equality. The procession-normalized log-volume layer now has a direct finite  $\mathbb{F}_\ell$ -labelled source: capsule log-volumes are indexed by  $ZMod(\ell)$ , the total is the finite sum over all labels, the normalized value is this sum divided by  $\ell$ , and Lean proves invariance of the average under label translation. At this finite-label boundary, the (Ind1)/(Ind2) preservation step no longer has to be represented as pointwise equality of labelled summands: Lean proves preservation of the normalized average by reindexing the  $ZMod(\ell)$ -sum. The next lowering replaces the old direct (Ind3) average inequality by an upper-semi comparison source: the source average is identified with the upper-semi source log-volume, the target average with the upper-semi target log-volume, and the inequality is then the source  $\leq$  target law of the upper-semi compatibility datum. The preferred source for this boundary is now one step lower: it identifies both averages with packet-normalized log-volumes of typed nonarchimedean local tensor packets before passing to the upper-semi coordinates. This is no longer an isolated typed-core source: the record

**ConcreteHodgeTheaterLogThetaVerticalLogKummer  
PacketAlignedSource**

combines the theta-pilot class image source, its pullback equality with the Theorem 3.11 record images, the packet-normalized vertical log-Kummer source, the  $F_l$ -gluing torsor, and the selected q-choice. Its constructor enters the public one-sided multiradial source directly, so the selected q-region is already a quotient possible image at this packet-aligned boundary. The target-side packet calibration can now consume this labelled Step (x) average directly: the equality  $\theta_{\text{avg}} = \text{packetNormalized}$  is derived by composing  $\theta_{\text{avg}}$  with the labelled normalized average and then with the audited packet-normalized capsule value. This dependency is tagged separately from a bare direct real-line identification. The same labelled-average dependency has been lifted into the realified Frobenioid packet source constructor, so the realified Step (x) packet source no longer needs a raw packet-normalized theta-average equality at this boundary. It is now also lifted through the theta-root attached Step (x) entry source and through the Hodge/SHE/IPL/hull route: the route may consume the labelled average and its equality with the Hodge-descent theta average directly, rather than a constant packet-normalized  $ZMod(\ell)$  route object. The same route now has a source-aligned form: the source packet/product calibration is constructed from packet-local source alignment and the Kummer/forgetting transfers, while the target packet calibration is constructed from the labelled procession average. A further route removes the raw theta-source-to-labelled-average real equality: the labelled capsule source is aligned labelwise with the theta-source  $ZMod(\ell)$ -average, and Lean derives equality of the two averages from the finite averaging formula. The labelled-average-to-packet-normalized equality is now also derived in the source layer: if each labelled capsule has the displayed local object, Lean proves that the labelled average is that local object's finite log-volume, and direct packet-normalization then identifies it with the packet-normalized capsule value. The labelled route can now replace its remaining

target-side ordered-real alignment by an exact vertical- $IQ$  target: Lean derives the (Ind3)-target equality from the same packet-normalized value used by the labelled theta-source alignment. In the finite-divisor variant, the source packet-local alignment is now constructed from the finite divisor/Frobenioid tensor packet product before the direct-labelled vertical- $IQ$  route is applied. The labelwise equality between the labelled capsule source and the Hodge-descent theta-source  $ZMod(\ell)$ -average is now derived from local Hodge-descent transport: each theta-source label is identified with the packet local object's finite log-volume, as is each labelled capsule value. The vertical- $IQ$  route can now also be instantiated with a finite divisor/Frobenioid packet product on the mono-analytic side. In this form the route constructs the theta-root attached realified log-Kummer entry source from the finite divisor packet product and the exact vertical- $IQ$  target before applying the Hodge/SHE/IPL/hull endpoint. The packet-local source alignment is now recovered inside that source object, not passed as a separate route input. The finite-divisor packet-local source itself can now be recovered from the realified Frobenioid log-Kummer packet source when its mono-analytic side is the finite divisor realization. Thus the divisor-realified equality and the packet-local (Ind3)-source equality are obtained from the packet correspondence and its Kummer/forgetting calibration, rather than being parallel fields at the finite packet boundary. This recovery has now been threaded through the current preferred constructed input-prime-strip record-hull boundary, both with and without the constructed qualitative checkpoint audit. Those public endpoints consume the realified packet source and expose the recovered finite-divisor and (Ind3) source equalities next to the  $C_\Theta$  dichotomy. On the Theorem 3.11 side, the vertical log-Kummer packet-aligned multiradial constructor has been lowered one step. It can now be built from a classified packet-local-object source: the finite procession average is identified with the packet local object's finite log-volume, classified packet-normalization identifies that local object with the normalized capsule log-volume, and the (Ind3) source/target alignments are stated at the local-object level. A direct finite-capsule variant promotes `IUTStage1DirectPacketNormalizationData` to this classified source before entering the public one-sided constructor. This has now been lowered again by `LogThetaLabelProcessionVerticalLogKummerClassifiedPacketLocalObjectSource`. That source supplies the log-theta procession values label by label, identifies their finite  $F_\ell$ -average with the classified packet local object's finite log-volume, and derives both the label-wise upper-semi source and the older classified packet-local source. Thus neither the packet-normalized equality nor the averaged procession object is primitive at this boundary. It has also been lowered to `LogThetaLabelProcessionVerticalLogKummerDirectPacketLocalObjectSource`: direct finite-capsule packet-normalization data now induces the classified packet compatibility, the local-object equals capsule-average equation, the label-wise classified source, and the one-sided endpoint. The next lowering is `LogThetaLabelProcessionVerticalLogKummerCapsulePacketLocalObjectSource`: it no longer takes direct packet-normalization as primitive. Instead it assumes the typed capsule family already attached to the packet, the total-as-sum formula for its capsule log-volumes, and the paper-side equality saying that the packet local object's finite log-volume is the uniform capsule average. Lean reconstructs the direct packet-normalization record from these data. The preferred boundary is now lower again: the transported  $ZMod(\ell)$  log-shell packet source, whose Lean suffix is `TransportedZModLogShellPacketLocalObjectSource`. Here the full  $F_\ell$ -procession is not supplied as a normalized family. Instead, the source gives a base local log-shell object, labelled representatives, and transport of every representative back to the base object. Lean constructs the labelled log-shell family, its total log-volume, its normalized log-volume, the capsule family, and the packet-local capsule state. This boundary has now been lowered once more by `ColumnLogLinkZModLogShellPacketLocalObjectSource`. For each theta-pilot class the source gives a realified-Frobenioid column log-Kummer compatibility and label-wise vertical log-link

operations. Lean uses Proposition 3.10-style preservation of the realified log-volume, together with the local-object identification of the log-link, to construct the transport of every labelled log-shell representative back to the base object. The preferred boundary is now one step lower. A `ColumnRealifiedLogShellZModLogShellPacketLocalObjectSource` supplies, at each column, an IUT I, Example 3.5(iii), realified Frobenioid log-shell divisor source. Lean constructs the finite local log-shell object from the log-shell divisor log-volume and identifies it with the corresponding realified Frobenioid degree object under the normalized-Frobenius condition. The boundary has now been lowered again to a raw divisor-column source. At this level the source gives only the column-indexed log-shell divisor data, one normalization, normalized-Frobenius witnesses, realified log-volume preservation under column translation, and the labelled local-object identity. Lean derives the labelled log-shell divisor log-volume equality, constructs the local log-volume objects, and promotes the result to the column realified-log-shell source. The (Ind3) base comparison has now also been lowered through this construction: a base-volume source states the source and target comparisons for the raw base divisor's realified Frobenioid log-volume, and Lean derives the finite local log-shell object equalities required by the older raw-column source. The raw column boundary has now been lowered below its translation fields by `ColumnLogKummerRealifiedLogShellDivisorFamilySource`. This source starts from a column Frobenioid/log-Kummer compatibility, a divisor realization of each vertical column, and the labelled log-link local-object identity. Lean derives realified log-volume preservation under vertical column translation, derives the labelled base-object equality, promotes the data to the raw divisor-column source, and exposes the same one-sided Step (xi) endpoint. The boundary has now been lowered again to compatible ordinary/theta/log-shell copies of the finite realified Frobenioid divisor data. At this level Lean derives the log-shell divisor realization from the ordinary divisor realization and the compatible-copy base equality, obtains the normalized Frobenius witnesses from the Example 3.5 compatibility package, and upgrades an object-level labelled log-link identity to the full local-object identity by using the column log-Kummer preservation of realified log-volume. The boundary has now been lowered one step further by `DegreeRealizedCompatibleCopiesColumnLogKummerDivisorFamilySource`. The ordinary copy no longer realizes the column log-Kummer object by a supplied record equality; the source gives the component data-local object, divisor degree, and unit log-volume—and Lean reconstructs the realified Frobenioid degree-object equality. At the base-volume level, the (Ind3) comparison is stated at the column compatibility degree object, and Lean derives the older ordinary-copy comparison. This has now been sharpened by `LocalObjectDegreeRealizedCompatibleCopiesColumnLogKummerDivisorFamilySource`. The labelled log-link input is no longer merely the equality of the underlying base objects; it is the equality of the finite local log-volume objects after the common log-shell normalization. Lean projects the older object equality from this local-object equality and threads the result through the same Theorem 3.11 and Step (xi) constructors. The compatible-copy package has now also been split by `SplitCopiesLocalObjectDegreeRealizedColumnLogKummerDivisorFamilySource`. Instead of receiving one opaque ordinary/theta/log-shell copy column, the source receives the ordinary divisor column, theta divisor column, and log-shell divisor column separately, plus the Example 3.5 base-identification and normalization laws. Lean constructs the compatible-copy package at each column and derives the theta/log-shell log-volume equalities with the ordinary realified divisor volume. This has now been lowered again by `NormalizedExample35LocalObjectDegreeRealizedColumnLogKummerDivisorFamilySource`. That source receives only the ordinary divisor column, a positive log-shell extension degree at each column, and the object-level labelled log-link transport. Lean constructs the theta copy by normalizing the  $\log(\Theta)$ -generator to 1, constructs the log-shell copy by taking the local Frobenius reading equal to the extension degree, proves the normalized log-shell read-

ing is 1, and derives the full labelled local-object equality from object transport plus the column realified-log-volume translation. The ordinary column has now also been lowered by `FiniteDivisorRealizedNormalizedExample35ColumnLogKummerDivisorFamilySource`. Instead of receiving a realified divisor column and three realization laws, the source receives finite divisor-monoid data in each vertical column—prime multiplicities, prime degrees, and the finite degree-sum identity against the column Frobenioid/log-Kummer degree object. Lean constructs the ordinary divisor column using the compatibility object’s local object and unit log-volume; the object and unit realization laws become definitional, and the divisor-degree realization is exactly the finite sum formula. The labelled object equality consumed by this source has now been lowered again: instead of supplying the equality of the base and labelled compatibility objects directly, one supplies a vertical log-Kummer/log-link object transport whose source and target are realized as the corresponding Frobenioid degree objects. Lean derives the labelled compatibility equality from this transport and then enters the finite-divisor ordinary-column construction. The Frobenioid degree column itself has now also been constructed from finite divisor components: the source supplies the local object, prime multiplicities, prime degrees, and unit log-volume in each vertical column, and Lean builds the corresponding realified Frobenioid degree object. Its divisor degree is definitionally the finite sum over the prime components. The upper-semi comparison boundary has also been tightened by `FrobenioidDivisorColumnUpperSemiCalibratedBaseVolume`: the source now calibrates the upper-semi source and target coordinates choice-wise against the constructed Frobenioid base volumes. Lean derives the older (Ind3)-indexed source/target equalities and proves the one-sided (Ind3) base-volume inequality from the upper-semi log-volume compatibility. This has now been lowered once more by `FrobenioidDivisorColumnConstructedUpperSemiBaseVolume`: the upper-semi state itself is constructed with its log-volume compatibility datum equal to the Frobenioid base volume. A further representative-section layer, `FrobenioidDivisorColumnRepresentativeConstructedUpperSemiBaseVolume`, now uses the theta-pilot representative section to recover the choice-level upper-semi identification: the representative’s upper-semi state is transported to the constructed Frobenioid base-volume state, and each concrete choice is identified with its selected theta-pilot representative. This has now been lowered to component data by `FrobenioidDivisorColumnComponentRepresentativeConstructedUpperSemiBaseVolume`: the finite  $F_\ell$ -label, procession state, local tensor state, and non-volume upper-semi data are supplied class-wise, while Lean constructs the representative section, inserts the Frobenioid base volume into the upper-semi log-volume compatibility datum, derives the direct-summand cardinality, and enters the same Step (xi) source. The remaining payload has moved below these component functions: construct them from the paper-native log-link and local Frobenioid geometry and prove the concrete choice identification. The component boundary has also been separated from the ambient concrete choice space by `FrobenioidDivisorColumnComponentRepresentativeKernel`: from the same class-wise component data, Lean generates a canonical theta-pilot choice space whose elements are exactly the constructed representatives. On this generated space, the identification with the representative section, the direct-summand cardinality, and the Frobenioid base-volume upper-semi compatibility are theorems rather than global assumptions about all arbitrary concrete choices. This generated-choice layer has now been refined to keep the full finite label procession. The kernel constructs, for each theta-pilot class and each label  $j \in \mathbb{Z}/\ell\mathbb{Z}$ , a concrete Hodge-theater/log-theta choice with the same generated procession, local tensor, and upper-semi data. The resulting `FullLabelGeneratedChoice` space is closed under the  $\mathbb{Z}/\ell\mathbb{Z}$  translation action, and Lean proves that its projection to the ambient concrete choice space is exactly the existing `flProcessionTranslate` operation. Thus the generated boundary no longer trades the full  $F_\ell$  procession for a single representative; the representative choice is now only

the distinguished label inside a larger generated procession space. The generated full-label space now also has its own typed (Ind1),(Ind2),(Ind3) core and quotient possible-image audit. On this generated space, (Ind1) is finite-label translation, (Ind2) is same-theta-pilot-class transport at the lowered component boundary, and (Ind3) is retained only as the Frobenioid base-volume upper-semi inequality. Possible images are pulled back from theta-pilot-class images, and the generated equality relation is characterized at the source boundary: it preserves the forgotten theta-pilot class, while equality of theta-pilot classes enters the quotient through the generated (Ind2) step. The finite  $F_\ell$ -procession orbit is now also a named source object: for a generated choice, every label of  $Z/\ell Z$  occurs in its orbit, every orbit member is an (Ind1) equality move, and the equality-quotient index, procession-normalized log-volume, and pulled-back possible image are unchanged along the orbit. Thus the quotient audit proves the pullback for every generated choice, with the selected  $q$ -region as a specialization, while (Ind3) remains outside the equality quotient. This replaces the previous ambient “every concrete choice is a representative” assertion at the generated-choice quotient layer. This generated quotient has now entered the public Step (xi) constructor layer: `ofGeneratedFullLabelQuotientSource` constructs a one-sided Theorem 3.11 multiradial source whose index is `FullLabelGeneratedChoice`. Its  $F_\ell$ -procession action is the generated label translation, its possible-image family is the theta-pilot class family pulled back to generated choices, and its endpoint proves both selected-region containment in the record union and projection compatibility with the ambient `flProcessionTranslate`. Thus the public constructor now consumes the generated quotient itself, rather than reintroducing a global ambient representative assumption. The corresponding corridor audit now also records the generated-kernel audit, the theta-class characterization of the generated equality relation, the all-choice quotient pullback, and the typed action-law audit for the constructed core. Thus the public boundary exposes the source-pattern (Ind1),(Ind2)-equality and (Ind3)-upper-semi laws before entering Remark 3.9.5. The same generated source is now threaded through the downstream Remark 3.9.5 and  $C_\Theta$  corridor. The declarations

```
GeneratedFullLabelQuotientCorridorSource.toHullCompatibility,
GeneratedFullLabelQuotientCorridorSource
.toRemark395ConstructedHolomorphicHullDeterminantSource,
GeneratedFullLabelQuotientCorridorSource
.toRemark395ConstructedGlobalCThetaScaleComparisonAudit
```

construct the Remark 3.9.5 hull compatibility, select the generated quotient  $q$ -region as the hull/determinant source, and pass it to the current global  $C_\Theta$ -comparison audit. Their endpoint exposes the same region as the selected generated quotient image and as the pullback of the theta-pilot-class possible image, then records the  $q \leq \Theta$  comparison, the global  $C_\Theta$  bound, and the present Corollary 3.12 dichotomy. The generated route now also carries a Remark 3.9.5 hull-compatibility audit: after quotienting by (Ind1,Ind2), every possible region still pulls back to the corresponding theta-pilot-class region, equality-related generated choices have the same possible region and hull log-volume, and (Ind3) enters only through the one-sided upper-semi log-volume inequality. The selected  $F_\ell$ -procession orbit is now part of this same hull boundary: `selectedProcessionOrbitRemark395HullEndpoint` proves that every generated full-label translate of the selected  $q$ -choice has the same Remark 3.9.5 possible region, the same hull log-volume, and the same selected  $q$ -region. Thus the hull boundary sees the full finite procession, not only the distinguished selected label. The experiment surface now exposes this generated route as

```
generatedFullLabelQuotientRemark395GlobalCThetaExperimentAudit.
```

This audit keeps the generated full-label quotient evidence and the Remark 3.9.5 hull-compatibility audit next to the  $q$ -region equalities and the global  $C_\Theta$  dichotomy. It does not by itself identify the generated-choice package with the finite-divisor vertical- $IQ$  package; that handoff is treated at the finite theta-class fiber. At this fiber boundary, the raw tensor-label endpoint is now an intermediate audit below calibrated local tensor packets, which construct the typed local-tensor symmetry-source boundary before projecting to raw labels. The stronger public route passes through the transported packet-label, retained label-transport, and matched identified (Ind2) packet-action endpoints, culminating in

```
generatedFullLabelFiniteDivisorVerticalIQFiniteThetaClassFiber
ComponentProcessionNonarchimedeanIsMMatchedIdentified
Ind2ActionPacketSourceImageLawSource_compact_cThetaDichotomy.
```

Thus same-theta-class finite packets are no longer compared by a primitive record-image equality or by an ambient quotient hypothesis. Lean builds the comparison through an explicit midpoint packet, a procession leg, a retained nonarchimedean Ism action-entry step, raw source and target tensor Ism labels, and the target summand-kind certificate. From these raw labels it constructs the local label transport and then a retained `NonarchimedeanInd2ActionPacketSymmetrySource` whose action place and transformed family are definitionally matched to the source Ism action-entry step. From this matched boundary Lean derives the generated (Ind1, Ind2) relation, the place-audited quotient relation, record-image invariance, selected  $q$ -region equalities, and finally the finite  $C_\Theta$  dichotomy. The remaining payload at this boundary is the paper-native construction of the raw tensor-label witnesses from local Frobenioid/log-Kummer geometry. The signed pre-ledger transfer has been factored through a Step (xi) log-volume source: finite and generated  $q$ -values are compared by their  $q$ -region log-volumes, and finite and generated  $\theta$ -values by their theta-hull log-volumes, before Lean derives the old  $q/\theta$  signed equalities. The finite handoff audit has now been lowered to this matched identified source. Its audit records the finite signed equalities, the finite possible-image identification, the raw tensor-label witness, the induced matched packet-action witness for same-theta finite packets, the source-level nonarchimedean (Ind2) packet-action audit, and the recovered local label-transport audit. Thus the preferred review point is now the raw-tensor-label to matched (Ind2) packet-action boundary, before the ordered-real dichotomy is invoked. The theta-pilot possible-image boundary has also been tightened. The class-indexed and lattice-key image-law constructors now have procession-normalized entry points: instead of receiving an arbitrary `IndeterminacyData` record, they consume the finite  $F_\ell$ -averaged procession log-volume source. Lean then derives the old typed indeterminacy package, including (Ind1) and (Ind2) log-volume preservation and the (Ind3) upper-semi inequality, before constructing the quotient possible-image family and the selected  $q$ -region. This boundary has now been lowered one step further by `LogThetaLabelProcessionUpperSemiSource`: for each theta-pilot class it supplies label-wise log-theta procession values indexed by  $Z/\ell Z$ , and Lean constructs the finite average, proves the  $\#(Z/\ell Z) = \ell$  normalization, derives the upper-semi comparison source, and enters the same one-sided Theorem 3.11 constructors. Thus the remaining mathematical payload is no longer an averaged indeterminacy object; it is the paper-native source of the label-wise log-volume family and its source/target average alignments from the log-Kummer/log-link geometry. The Remark 3.9.5 hull boundary has also been lowered from an abstract intersection-closed predicate to a product-hull source that matches the paper's  $\lambda \cdot O$  description. The declaration

```
IUTStage1Remark395ProductHullSystemSource
```

carries a family of product hulls, their log-volumes, and for each region a distinguished parameter whose product hull is the intersection of all product hulls containing that region. From this data Lean



constructs the ordinary `IUTStage1Remark395HolomorphicHullSystem`; the experiment endpoint proves that  $\phi(P)$  is exactly this selected product hull, contains  $P$ , is minimal among product hulls containing  $P$ , and has the stated product-hull log-volume. There is now a direct-product constructor for this boundary,

`IUTStage1Remark395DirectProductHullSystemSource.`

Here a product hull is a literal coordinate product and the selected intersection parameter is the family of coordinate projections of  $P$ . Lean proves that this coordinate-projection product is the intersection of all product hulls containing  $P$ , then projects to `IUTStage1Remark395ProductHullSystemSource`. Thus this layer no longer supplies the product-hull intersection law as an independent field. This product-hull source now has a principal scalar-multiple refinement,

`IUTStage1Remark395PrincipalProductHullSystemSource.`

It records the local integer/direct-product region  $O$ , scalar maps  $\lambda \cdot (-)$ , nonzero-parameter witnesses, and principal hulls of the source-paper form  $\lambda \cdot O$ . It then derives the previous `IUTStage1Remark395ProductHullSystemSource`. Thus the hull boundary can distinguish a genuinely Remark 3.9.5(i)-shaped product hull from an arbitrary family of subsets before the analytic construction of the scalars is completed. The supplied principal-minimality law has now been narrowed further by

`IUTStage1Remark395DirectProductPrincipalHullSystemSource.`

This constructor starts from the direct-product hull theorem and a scalar presentation of each principal region. Its remaining source equality is the pointwise identification  $\lambda \cdot O = \prod_v H_v(\lambda)$ ; once that is available, Lean derives the principal intersection/minimality law from the coordinate-projection product-hull theorem. Thus the principal layer no longer has to restate the whole “smallest  $\lambda \cdot O$  containing  $P$ ” property when its scalar images have already been matched to direct-product hulls. This equality boundary has now been factored once more by

`IUTStage1Remark395ScalarImageDirectProductHullSource.`

Instead of accepting the extensional equality  $\lambda \cdot O = \prod_v H_v(\lambda)$ , this source records the two directional scalar-image laws: scalar multiples of local-integer points land in the corresponding direct-product hull, and every direct-product-hull point has a scalar preimage in  $O$ . Lean proves the set equality from these two laws and then constructs the direct-product principal hull source above. Thus the next valuation/local-ring layer can target concrete image and preimage statements rather than a monolithic equality of subsets. The product-level image/preimage laws have now been pushed down to coordinate factors by

`IUTStage1Remark395CoordinateScalarImageDirectProductHullSource.`

Here  $O$  is the literal product of local integer factors  $O_v$ , and  $\lambda \cdot (-)$  is assembled coordinatewise from local scalar maps  $\lambda_v \cdot (-)$ . The source only supplies the one-place assertions  $\lambda_v O_v \subseteq H_v(\lambda)$  and the corresponding local preimage statement for points of  $H_v(\lambda)$ . Lean combines these coordinate witnesses by dependent choice to prove the global scalar-image landing and preimage laws, then constructs the scalar-image direct-product hull source. Thus the next finite-extension valuation

step can work one local factor at a time. There is now a stricter scalar-parameter version of this coordinate boundary:

**IUTStage1Remark395ScalarParameterDirectProductHullSource.**

This source no longer asks for local image/preimage laws for arbitrary subsets. Instead each coordinate has an actual scalar-parameter type and a named local region  $H_v(\lambda_v)$  satisfying the source-shaped equality

$$H_v(\lambda_v) = \lambda_v \cdot O_v.$$

Lean derives the product landing law, product preimage law, and equality between the principal scalar-image hull and the direct-product hull for the product scalar parameter. This is the current lowest scalar-image boundary before the finite-extension valuation model supplies the concrete local parameters and proves the equality  $H_v(\lambda_v) = \lambda_v O_v$ . The principal hull presentation is now tied to the valuation-ball local-ring cover. The declaration

**IUTStage1Remark395PrincipalValuationBallProductHullCoverSource**

carries a valuation-ball factor-calibrated Haar tensor-packet cover together with a principal product-hull source, identifies the valuation cover's hull system with the principal hull system, and identifies  $O$  with the anchor valuation-ball direct-product cell. Its endpoint proves that the selected principal hull  $\lambda \cdot O$  is the same subset as the valuation-ball direct-product cell union, that its log-volume is the calibrated cell sum, and that the same valuation cover still projects to the adjusted Ob3/Ob5 determinant source. This does not construct the analytic scalar parameters from the source papers, but it removes a previous separation between the  $\lambda \cdot O$  hull notation and the nonarchimedean local-ring/Haar cover used by the determinant route. There is now also a product-carrier version of this valuation-ball bridge,

**IUTStage1Remark395DirectProductPrincipalValuationBallProductHullCoverSource.**

Its valuation cover lives on an actual dependent product, and its principal hull source is the direct-product-backed scalar source above. The endpoint therefore identifies the selected  $\lambda \cdot O$  hull first with the coordinate/direct-product hull selected by the projection construction, then with the valuation-ball direct-product cell union, and finally carries the same adjusted Ob3/Ob5 determinant normalization handoff. The remaining scalar obligation is now just the per-parameter analytic equality between the source paper's scalar image  $\lambda \cdot O$  and the corresponding valuation/direct product hull. This valuation-ball bridge has also been lowered to the scalar-image source:

**IUTStage1Remark395ScalarImageValuationBallProductHullCoverSource.**

It consumes the two directional scalar-image laws, constructs the direct-product principal hull source internally, and then projects through the same valuation-ball determinant route. Its endpoint therefore keeps the valuation cover, calibrated cell-sum log-volume, and adjusted Ob3/Ob5 handoff, but the scalar trust boundary exposed at this product-carrier level is no longer a subset equality. It is precisely the landing and preimage pair that the next finite-extension valuation/local-ring construction must prove. The coordinate-local version of this same valuation bridge is now exposed as

**IUTStage1Remark395CoordinateScalarImageValuationBallProductHullCoverSource.**

It starts with the coordinate source above, constructs the scalar-image valuation cover internally, and keeps the selected principal hull identified with both the direct-product hull and the valuation-ball direct-product cell union. Consequently the adjusted Ob3/Ob5 determinant handoff can now be reviewed at a boundary whose remaining scalar hypotheses are one-place statements for the local factors  $O_v$  and  $H_v(\lambda)$ , rather than global statements about  $\lambda \cdot O$ . The selected scalar-parameter version of this valuation bridge is now exposed as

**IUTStage1Remark395SelectedScalarParameterValuationBallProductHullCoverSource.**

It combines the scalar-parameter source with the valuation-ball cover by choosing the product scalar parameter  $(\lambda_v)_v$  whose local regions  $H_v(\lambda_v)$  are exactly the coordinate projections of the current possible-image union. Lean then proves that the selected scalar image  $\lambda \cdot O$  is the direct-product hull selected by the holomorphic hull operator and hence the valuation-ball direct-product cell union used by the adjusted Ob3/Ob5 determinant source. This leaves the next finite-extension valuation task in its sharpest current form: construct the actual local parameters  $\lambda_v$  and prove  $H_v(\lambda_v) = \lambda_v O_v$  from the local IUT source data. This scalar-parameter source has now been lowered once more to actual local multiplication by nonzero elements:

**IUTStage1Remark395NonzeroScalarMultiplicationDirectProductHullSource.**

Here the parameter type at a place  $v$  is the subtype of nonzero local scalars, the scalar action is the local multiplication map  $x \mapsto \lambda_v x$ , and the region  $H_v(\lambda_v)$  is defined as the image of  $O_v$  under this map. Consequently the equality

$$H_v(\lambda_v) = \lambda_v O_v$$

is no longer a supplied field at this boundary; it is the defining construction from which Lean derives the product landing, product preimage, and principal-hull/direct-product equality. The valuation-ball determinant handoff has the corresponding nonzero-scalar form

**IUTStage1Remark395NonzeroScalarMultiplicationValuationBallProductHullCoverSource.**

Its endpoint verifies that the selected nonzero scalar image is still the holomorphic family hull and the valuation-ball direct-product cell union used by the adjusted Ob3/Ob5 determinant source. The remaining local-field task is therefore more specific: identify the source-paper scalar parameters as nonzero elements of the local factors and connect the local integer factors  $O_v$  to the valuation-ring/unit-ball construction already present in the Haar normalization branch. This second connection has now been formalized at the product-cover boundary by

**IUTStage1Remark395ValuationUnitBallNonzeroScalarMultiplication  
ProductHullCoverSource.**

This source keeps the valuation-cover place index explicit and records a coordinate-to-place selector. At the anchor chart it requires each selected compact-open valuation ball to be the unit ball  $\mathcal{O}_v = \{x \mid \|x\|_v \leq 1\}$ , proves that the anchor local factor is the realized ring of integers, derives the global equality

$$O = \prod_v O_v = \text{anchor valuation direct-product cell},$$

and then constructs the previous nonzero-scalar valuation cover. Thus the  $\lambda_v O_v$  hull now enters the adjusted Ob3/Ob5 determinant route through valuation-unit-ball provenance, not through a separately supplied global anchor-cell equality. What remains is to construct the coordinate-to-place selector and the nonzero scalars from the source-paper Frobenioid/Kummer local data rather

than pass them as source fields. This valuation-ball provenance has now been lifted to the finite-divisor vertical- $IQ$  endpoint. The declaration

```
IUTStage1Remark395PrincipalValuationBallBackedConstructorBacked
ConstructedHullDeterminantFiniteDivisorVerticalIQSource
```

requires the constructor-backed adjusted Ob3/Ob5 source to be the record-canonical form of the adjusted determinant source projected from the principal valuation-ball cover. From this equality Lean derives the principal hull-operator equality, the equality between the valuation-ball possible-image union and the Theorem 3.11 possible-image union, and the identity between the selected route hull and the valuation-ball direct-product cell union. The public endpoint

```
remark395PrincipalValuationBallBackedConstructorBackedConstructed
Ob3Ob5AdjustedHullDeterminantFiniteDivisorVerticalIQ
_cThetaDichotomyWithPrincipalValuationBallAudit
```

then returns this valuation-ball audit next to the same finite-divisor vertical- $IQ$   $C_\Theta$  dichotomy. There is also a canonical-scale specialization of this endpoint:

```
remark395PrincipalValuationBallBackedConstructorBackedConstructed
Ob3Ob5AdjustedHullDeterminantFiniteDivisorVerticalIQ
_canonicalCThetaScaleDichotomyWithPrincipalValuationBallAudit.
```

Here the scale is not supplied as an external real number. It is the local source-attached value

$$C_\Theta^{\text{can}} = \frac{\theta_{\text{signed}}}{-q_{\text{signed}}},$$

and the bound

$$\theta_{\text{signed}} \leq C_\Theta^{\text{can}} \cdot (-q_{\text{signed}})$$

is derived in Lean from q-pilot positivity by cancellation. The returned `PrincipalValuationBallBackedCanonicalCThetaScaleAudit` keeps both the valuation-ball record audit and the constructor-backed hull/determinant bridge audit in the statement, so this endpoint no longer takes `thetaSigned_le_cTheta_absLogQ` as a hypothesis at this local source boundary. It is still a local canonical scale for the present source package, not yet a construction or identification of Mochizuki's global  $C_\Theta$ -constant from the full IUT papers. The valuation-unit-ball/nonzero-scalar product source now has the analogous finite-divisor boundary wrapper. The new source

```
IUTStage1Remark395ValuationUnitBallNonzeroScalarBacked
ConstructorBackedConstructedHullDeterminantFiniteDivisor
VerticalIQSource
```

contains the principal valuation-ball finite-divisor source, the literal local product scalar source, and an explicit carrier equivalence from the product carrier to the target real-line carrier. Its transport audit records that the product local-integer region, selected nonzero scalar image, and valuation-unit-ball direct-product cover all transport to the same principal  $\lambda_v O_v$  hull. The public experiment endpoint

```
remark395ValuationUnitBallNonzeroScalarBackedConstructorBacked
ConstructedOb3Ob5AdjustedHullDeterminantFiniteDivisor
VerticalIQ_canonicalCThetaScaleDichotomyWithTransportAudit
```

therefore exposes the same canonical-scale vertical- $IQ$  dichotomy together with the product-carrier/unit-ball transport provenance. The remaining source-facing gap has moved to constructing this carrier equivalence, the coordinate-to-place selector, and the nonzero scalars from the actual Frobenioid/Kummer local data. This transport boundary has now been sharpened once more. The reduced source

```
IUTStage1Remark395ValuationUnitBallNonzeroScalar
FiniteDivisorTransportSynchronizationSource
```

does not ask separately for the transported valuation-cover equality. It only records the carrier equivalence, the transport of the local-integer region, and the transport of the selected nonzero scalar image to the principal hull. Lean then derives

$$e(\text{valuation unit-ball direct-product cover}) = \text{principal } \lambda_v O_v \text{ hull}$$

from the product-cover theorem

```
selectedScalarImageHull_eq
_valuationBallDirectProductCellUnion.
```

The experiment endpoint

```
remark395ValuationUnitBallNonzeroScalarTransportSynchronized
ConstructorBackedConstructedOb30b5AdjustedHullDeterminant
FiniteDivisorVerticalIQ_canonicalCThetaScaleDichotomy
WithTransportAudit
```

therefore reaches the same canonical-scale vertical- $IQ$  dichotomy with one fewer transported equality at the trust boundary. The carrier side of the same route has also been separated into a charted source. Instead of supplying an arbitrary equivalence from the local product carrier to the target real-line copy, the new

```
IUTStage1Remark395ValuationUnitBallNonzeroScalar
TargetCarrierChartSource
```

records a product-to-real coordinate, a real-to-product realization, and the two inverse laws. Lean derives the carrier equivalence

$$((d : \delta) \rightarrow A_d) \simeq \text{Point target}$$

from this chart, and the charted finite-divisor synchronization endpoint then forwards to the reduced transport-synchronization route. Thus the current trust boundary has moved from an unstructured carrier equivalence to the construction of the product real-coordinate chart itself. The remaining source-facing task is to build that chart from the actual Frobenioid/Kummer local valuation data, together with the coordinate-to-place selector and nonzero scalar preimage laws. For the finite-divisor endpoint itself, this carrier requirement has now been weakened once more to the actual data used by the comparison: a forward transport into the target real-line copy. The source

```
IUTStage1Remark395ValuationUnitBallNonzeroScalar
TargetPointTransportSource
```

keeps the same valuation-unit-ball/nonzero-scalar product source and principal valuation-ball source, but replaces the equivalence or inverse chart by a map

$$((d : \delta) \rightarrow A_d) \longrightarrow \text{Point target}.$$

The transported valuation-cover equality is again derived from the selected scalar-image/product-cover theorem, and the public endpoint reaches the same canonical-scale vertical- $IQ$  dichotomy while returning a `TargetPointTransportAudit`. Thus inverse reconstruction of the local product carrier is no longer part of the finite-divisor trust boundary. The remaining source-facing construction is the forward target log-coordinate map itself, with proofs that it sends the local integer region and selected nonzero scalar image to the corresponding principal  $\lambda_v O_v$  regions. This has now been sharpened to a coordinate-derived target transport source. The new

`IUTStage1Remark395ValuationUnitBallNonzeroScalar  
CoordinateTargetTransportSource`

does not accept an arbitrary map to `Point target`. It takes a real coordinate map

$$((d : \delta) \rightarrow A_d) \longrightarrow \mathbb{R}$$

together with coordinate descriptions of the target principal local-integer region and selected principal hull. Lean proves the elementary wrapper lemma that the induced map  $x \mapsto \{\text{coord} := f(x)\}$  has the required point-level image if and only if the coordinate image has the required real-region image. The coordinate-derived endpoint then forwards through `TargetPointTransportSource`. Thus the remaining transport obligation is now stated at the real log-coordinate level: construct the coordinate map from the local valuation/Kummer data and prove the two coordinate image equalities. The selected-hull half of this obligation has now been pushed one layer closer to Remark 3.9.5(i). The source-core theorem

`selectedScalarImageHull_eq_selectedNonzeroScalar_image`

proves that the selected product hull is literally the image  $\lambda \cdot O$  of the local integer product region under the selected coordinatewise nonzero scalar multiplication. The new

`IUTStage1Remark395ValuationUnitBallNonzeroScalar  
SelectedImageCoordinateTargetTransportSource`

therefore asks for the target coordinate image of this explicit  $\lambda \cdot O$  region, not for the already-packaged `selectedScalarImageHull` image. Lean rewrites through the source-core equality and then applies the coordinate-derived endpoint. The remaining selected-hull transport payload is now the real-coordinate image law for an explicit nonzero-scalar multiplication image. The local-integer half has now been pushed down in the same way. The valuation-unit-ball product source already proves

`localIntegerRegion = valuationCover.directProductCell valuationCover.anchor,`

i.e., the local integer product is the anchor product of valuation unit balls  $O = \prod_v O_v$ . The new

`IUTStage1Remark395ValuationUnitBallNonzeroScalar  
ValuationAnchorCoordinateTargetTransportSource`

therefore states the local-integer coordinate image for this explicit anchor valuation-cell product and states the selected-hull coordinate image for the explicit  $\lambda \cdot O$  image. Lean derives the previous selected-image coordinate transport source by rewriting through these two source equalities. Thus both coordinate-image transport obligations are now attached to concrete Remark 3.9.5(i) regions

$O$  and  $\lambda O$ , rather than to packaged endpoint regions. The target coordinate map itself has now been restricted one step further. The new

`IUTStage1Remark395ValuationUnitBallNonzeroScalar`  
`FiniteLocalLogCoordinateTargetTransportSource`

does not accept an arbitrary real-valued coordinate functional on the source product carrier. It carries local readings

$$\ell_v : ((d : \delta) \rightarrow A_d) \longrightarrow \mathbb{R}$$

for the finite valuation-place set and defines the target coordinate by

$$x \longmapsto \sum_v \ell_v(x).$$

Lean then projects this finite local log-coordinate source to the valuation-anchor coordinate transport source. The remaining image laws are therefore the two explicit statements

$$\left( \sum_v \ell_v \right)(O) = R_O, \quad \left( \sum_v \ell_v \right)(\lambda O) = R_{\lambda O},$$

where  $R_O$  and  $R_{\lambda O}$  are the real-coordinate descriptions of the principal local-integer region and selected principal hull on the target real-line copy. Thus the arbitrary target-coordinate-map freedom has been removed from this boundary; the next mathematical task is to construct the local log-coordinate readings from the valuation/Kummer model and prove these two image equalities. The scalar finite-sum image laws have now been reduced to a product-image statement for the tuple of local coordinates. The helper

`finiteLocalLogCoordinateSumRegion`

defines the real region obtained from local coordinate regions  $R_v \subseteq \mathbb{R}$  by

$$\left\{ \sum_v r_v \mid r_v \in R_v \right\}.$$

The theorem

`finiteLocalLogCoordinateSumRegion.image_sum_eq_of_vector_image`

proves that if

$$x \longmapsto (v \mapsto \ell_v(x))$$

maps a source region onto the product of the local coordinate regions, then  $x \mapsto \sum_v \ell_v(x)$  maps the same source region onto the corresponding sum region. The new

`IUTStage1Remark395ValuationUnitBallNonzeroScalar`  
`LocalLogCoordinateProductImageTargetTransportSource`

therefore supplies the vector-valued image laws for  $O$  and  $\lambda O$ ; Lean derives the finite-sum transport source and then enters the same valuation-anchor finite-divisor endpoint. The remaining source-facing problem is now the local product-coordinate theorem for  $(\ell_v)_v(O)$  and  $(\ell_v)_v(\lambda O)$ , rather than an unstructured image theorem for the scalar sum. That product-coordinate theorem has now been split into its two source-facing halves. The lemma

`localLogCoordinateVector_image_eq_product_of_landing_and_preimage`

proves the vector-valued product image equality from coordinatewise landing

$$x \in S \Rightarrow \ell_v(x) \in R_v \quad \text{for all } v$$

and simultaneous realization

$$(r_v)_v \in \prod_v R_v \Rightarrow \exists x \in S, \ell_v(x) = r_v \quad \text{for all } v.$$

The corresponding

IUTStage1Remark395ValuationUnitBallNonzeroScalar  
LocalLogCoordinatePreimageTargetTransportSource

now supplies these landing and simultaneous-preimage laws for  $O$  and  $\lambda O$ ; Lean derives the product-image source, then the finite-sum source, and finally the valuation-anchor endpoint. Thus the remaining mathematical construction is the actual local analytic/Kummer realizer for compatible tuples of valuation-place log coordinates, not a supplied vector-valued image equality. The simultaneous-preimage half has now been lowered once more to a direct product assembly theorem. The generic lemma

simultaneousLocalLogCoordinatePreimage\_of\_placewise\_factor\_preimages

states that if each placewise coordinate value  $r_v \in R_v$  has a local factor preimage  $b_v$ , and if admissible choices  $(b_v)_v$  assemble to a source point whose local log-coordinate readings are exactly the factor coordinates, then the whole tuple  $(r_v)_v$  has a simultaneous preimage. The source record

IUTStage1Remark395ValuationUnitBallNonzeroScalar  
LocalLogCoordinatePlacewisePreimageTargetTransportSource

uses this lemma for both the anchor region  $O$  and the selected scalar image  $\lambda O$ . Thus the remaining preimage payload is no longer a global existential statement over the product carrier; it is the placewise local scalar-image/preimage theorem together with the direct-product assembly law that identifies the assembled point with the prescribed log-coordinate tuple. The coordinatewise landing half has also been lowered to local factor data. The lemma

localLogCoordinate\_lands\_of\_placewise\_factor\_landing

proves landing in  $\prod_v R_v$  from a point-to-factor projection, membership of that factor in the appropriate local source region, agreement of the source local coordinate with the factor coordinate, and the local factor landing theorem. The new

IUTStage1Remark395ValuationUnitBallNonzeroScalar  
LocalLogCoordinateFactorwiseTargetTransportSource

uses this landing lemma together with the placewise-preimage assembly theorem, so the public route now derives both sides of the vector-valued product-image equality from factorwise local data. The projected factorwise refinement further removes the abstract point-to-factor and assembly maps from this boundary. A valuation-place/product index equivalence  $e : \gamma_{\text{loc}} \simeq \delta$  identifies each local place with an actual coordinate of the dependent product  $\prod_{d:\delta} A_d$ . The source

IUTStage1Remark395ValuationUnitBallNonzeroScalar  
LocalLogCoordinateProjectedFactorwiseTargetTransportSource



sets the local factor carrier at  $v$  to  $A_{e(v)}$ , takes projection to be evaluation at  $e(v)$ , and takes assembly to be the standard dependent-product reindexing equivalence `Equiv.piCongrLeft`. The corresponding public endpoint therefore routes to Corollary 3.12 after proving the factorwise transport laws from product evaluation and reindexing. The remaining local-log payload at this boundary is the source-facing image description of the coordinate regions  $O_v$  and  $\lambda_v O_v$  under the chosen local logarithmic coordinate, together with the valuation-place/product-index identification. This image-description boundary has now been lowered once more. The source

`IUTStage1Remark395ValuationUnitBallNonzeroScalar`  
`ValuationLogImageProjectedFactorwiseTargetTransportSource`

defines the local real regions themselves as

$$\ell_v(O_v), \quad \ell_v(\lambda_v O_v),$$

where  $\ell_v$  is the selected local valuation/log-coordinate map. The previous projected-factorwise source is obtained by projection, and the image equalities for  $O_v$  and  $\lambda_v O_v$  are now definitional theorems. Thus this boundary no longer asks for separate local coordinate-image laws; at that level, the remaining inputs were the actual construction of the local maps  $\ell_v$  from the valuation/Kummer model and the global finite-sum identifications of the target real-line principal regions. The finite-sum target boundary has now been lowered another step. The source

`IUTStage1Remark395ValuationUnitBallNonzeroScalar`  
`ValuationLogFiniteSumTargetPointSource`

defines the target point of a local product element  $x$  by the coordinate

$$\sum_v \ell_v(x_v).$$

It carries the typed compatibility saying that the source's coordinate-place map agrees with the chosen valuation-place/product-index equivalence, then proves internally that the coordinate images of  $O = \prod_v O_v$  and  $\lambda O = \prod_v \lambda_v O_v$  are exactly the finite-sum regions  $\sum_v \ell_v(O_v)$  and  $\sum_v \ell_v(\lambda_v O_v)$ . The remaining synchronization at this lower boundary is point-level transport of these two source regions to the principal finite-divisor target regions; the real-line finite-sum equalities are no longer independent fields of the exact-theta constructor. This boundary has now been lowered again by

`IUTStage1Remark395ValuationUnitBallNonzeroScalar`  
`CoordinatePlaceValuationLogFiniteSumTargetPointSource.`

Here the valuation-cover coordinate-place map is represented source-side by an equivalence  $\delta \simeq \gamma_{\text{local}}$ . Lean derives the previous finite-sum synchronization law

$$\text{coordinatePlace}(e^{-1}(v)) = v$$

from the source equality `coordinatePlace = e`. Thus the remaining coordinate-index work is no longer an arbitrary target-boundary compatibility; it is the construction of this equivalence from the actual local valuation indexing. The local coordinate itself has now been lowered to a Haar log-volume source. The new local source

`IUTStage1Remark395LocalFactorHaarLogCoordinateSource`

assigns to a local factor  $x_v$  a local compact-open region  $U_{v,x_v}$  and defines

$$\ell_v(x_v) = \mu_{\log,v}(U_{v,x_v})$$

using the normalized finite-extension Haar log-volume source already present in the valuation/Haar branch. The corresponding finite-sum source

**IUTStage1Remark395ValuationUnitBallNonzeroScalar  
HaarLogCoordinateFiniteSumTargetPointSource**

therefore projects to the coordinate-place finite-sum route with  $\ell_v$  no longer a bare function. Lean proves that the  $O_v$  and  $\lambda_v O_v$  coordinate regions are images under normalized Haar log-volume of the assigned local regions. This has now been strengthened to a compact-open Haar source. The local declaration

**IUTStage1Remark395LocalFactorCompactOpenHaarLogCoordinateSource**

uses the finite-extension compact-open topology/Haar normalization object, requires every assigned  $U_{v,x_v}$  to satisfy the compact-open predicate, and then projects to the normalized Haar log-coordinate source. The finite product declaration

**IUTStage1Remark395ValuationUnitBallNonzeroScalar  
CompactOpenHaarLogCoordinateFiniteSumTargetPointSource**

threads this compact-open provenance through the same target-point finite-sum endpoint and exposes the compact-open Haar route at the experiment surface. This has now been lowered one more step to centered valuation balls. The local declaration

**IUTStage1Remark395LocalFactorCenteredValuationBallHaarLogCoordinateSource**

takes a proper ultrametric local factor together with the valuation-ball Haar normalization source, defines

$$U_{v,x_v} := \overline{B}(x_v, r_v),$$

where  $r_v$  is the compact-open radius of the valuation-ball Haar source, and proves that this closed ball is open by the ultrametric inequality and compact by properness. Thus the compact-open predicate is no longer supplied at this boundary; it is constructed from the valuation-ball topology. The finite product source

**IUTStage1Remark395ValuationUnitBallNonzeroScalar  
CenteredValuationBallHaarLogCoordinateFiniteSumTargetPointSource**

threads these centered balls through the same finite-sum target map and projects to the compact-open Haar route at the experiment surface. This local boundary has now been lowered to the valued-field integer source. The declaration

**IUTStage1Remark395LocalFactorValuedFieldIntegerCenteredValuationBallHaarLogCoordinateSource**

starts from a valued-field integer proper-ultrametric Haar normalization source: the local ring is the actual valued-field integer subring  $\mathcal{O}_K$ , the valuation topology is the valued-field ultrametric topology, and the centered coordinate is still

$$x_v \mapsto \mu_{\log}(\overline{B}(x_v, r_v)).$$

Lean constructs the proper-ultrametric valuation-ball Haar source used by the centered-ball layer and then constructs the centered local coordinate source. The finite product source

IUTStage1Remark395ValuationUnitBallNonzeroScalar  
ValuedFieldIntegerCenteredValuationBallHaarLogCoordinate  
FiniteSumTargetPointSource

threads these valued-field integer local coordinates through the same target finite sum and exposes the corresponding experiment route and Step (xi) constructor. The same boundary has now been specialized to the concrete base local field  $\mathbb{Q}_p$ . The local declaration

IUTStage1Remark395LocalFactorPadicCenteredValuationBallHaarLogCoordinateSource

starts from the  $p$ -adic proper-ultrametric Haar source: the integer ring is identified with  $\mathbb{Z}_p$ , the residue prime is  $p$ , the normalization degree is 1, and the uniformizer action is multiplication by  $p$ . It projects to the valued-field integer centered-ball source without adding a new abstract local-ring field. It now also projects to the finite-extension centered-ball source for  $K = \mathbb{Q}_p$ , proving that the same closed-ball local region and normalized Haar log-coordinate are obtained after passing through the degree-one finite-extension normalization route. The finite-product declaration

IUTStage1Remark395ValuationUnitBallNonzeroScalar  
PadicCenteredValuationBallHaarLogCoordinate  
FiniteSumTargetPointSource

uses valuation places as the product coordinates and assigns to each place  $v$  an actual local carrier  $\mathbb{Q}_{p_v}$ . Its target coordinate is definitionally

$$(x_v)_v \mapsto \sum_v \mu_{\log}(\overline{B}(x_v, r_v)),$$

and the experiment surface now reaches the same topology/Haar Ob5–Ob7 canonical-scale finite-divisor route through this  $p$ -adic source. The Milestone 2 hull layer now contains a direct formalization of Remark 3.9.5(ii)–(iii)’s hull-map skeleton and approximant family. The hull map  $\phi(P)$  is represented by a closure operator; Lean exposes the Remark 3.9.5(ii) laws

$$\phi(H) = H, \quad P \subseteq \phi(P), \quad P_1 \subseteq P_2 \Rightarrow \phi(P_1) \subseteq \phi(P_2),$$

together with idempotence  $\phi(\phi(P)) = \phi(P)$ . For a region  $P$ , an approximant record carries a hull  $H$ , proves  $H \subseteq \phi(P)$ , and proves

$$\mu_{\log}(P) \leq \mu_{\log}(H) \leq \mu_{\log}(\phi(P)).$$

For the Corollary 3.12 possible-image union, the public endpoints now also return  $P \subseteq \phi(P)$ , each  $P_i \subseteq \phi(P)$ ,  $q$ -pilot containment in  $\phi(P)$ , and  $\phi(\phi(P)) = \phi(P)$ . The  $\Xi(P)$ -part of Remark 3.9.5(iii) is now represented at the same finite level: an exact hull approximant is a  $\Phi(P)$ -approximant  $H$  with  $\mu_{\log}(H) = \mu_{\log}(P)$ . When  $P$  is already closed under the hull operator, Lean constructs the canonical exact approximant. The possible-image Step (xi) source can now also be built from such an exact approximant and a weighted determinant source; in that route Lean derives  $\mu_{\log}(P) = \mu_{\log}(H) = \det_{\log}$ , rather than only the inequality  $\mu_{\log}(P) \leq \mu_{\log}(H)$ . Remark 3.9.5(iv)’s statement  $\phi(P) \in \Phi(P)$ , hence  $H_{\Phi(P)} = \phi(P)$ , is now represented by a finite approximant-family object. Every member of the family is a  $\Phi(P)$ -approximant inside  $\phi(P)$ , and if one distinguished

member is the canonical hull, Lean proves that the family union and its log-volume are exactly those of  $\phi(P)$ . The corresponding  $\Xi(P)$ -family statement is also represented. Each member is an exact approximant with log-volume  $\mu_{\log}(P)$ ; if the family contains the canonical hull, its union is  $\phi(P)$ . In the special case where  $P$  is already closed under hull formation, the canonical one-point  $\Xi(P)$ -family has union  $P = \phi(P)$  and log-volume  $\mu_{\log}(P)$ , matching Remark 3.9.5(iv)'s closed-region case. For possible-image families, the exact  $\Xi(P_B)$  boundary has now been sharpened: `IUTStage1Remark395PossibleImageExactXiFamilySource` does not accept an arbitrary exact family, but only the source calibration

$$\mu_{\log}(\phi(P_B)) = \mu_{\log}(P_B).$$

From this equality Lean constructs the canonical exact approximant and a  $\Xi(P_B)$ -family over either the one-point index or the same index type as a chosen  $\Phi(P_B)$ -family. At the possible-image-family level, this exact-approximant family now also interfaces with the Ob5 upper-semi quotient: if a  $\Xi(P_B)$ -family is available and one possible image is nonempty, Lean proves

$$H_{\Xi(P_B)} = \phi(P_B)$$

and proves that the quotient image of  $H_{\Xi(P_B)}$  is the same collapsed point as the quotient image of that nonempty possible image. The same source-facing family now has an explicit Ob6 log-volume endpoint: for a  $\Phi(P_B)$ -family and an exact  $\Xi(P_B)$ -family either supplied directly or constructed from  $\mu_{\log}(\phi(P_B)) = \mu_{\log}(P_B)$ , Lean proves

$$H_{\Phi(P_B)} = \phi(P_B) = H_{\Xi(P_B)}$$

and records the inequalities

$$\mu_{\log}(P_B) \leq \mu_{\log}(H_{\Phi(P_B)}), \quad \mu_{\log}(P_B) \leq \mu_{\log}(H_{\Xi(P_B)}),$$

together with the corresponding inequalities for each selected possible image  $P_\beta$ . Thus Remark 3.9.5(Ob6)'s warning that estimates must pass through hull-approximant unions, rather than through the raw possible-image region alone, is now a named checked source endpoint. The next source-facing checkpoint is also present. The Ob7 log-Kummer compatibility source attaches a constructed hull/determinant bridge to a finite  $F^{\times\mu}$ -prime-strip lift. Its endpoint proves that the q-region log-volume is bounded by the retained prime-strip global log-volume, while also recording the prime/place square, local realified-Frobenioid log-volume compatibility, and Frobenius-like unit-character compatibility. This keeps the comparison object in the Frobenioid/log-Kummer language required by Remark 3.9.5(Ob7), instead of collapsing immediately to a bare real number. The canonical hull  $\phi(P)$  is itself an approximant, and every approximant is fixed by hull formation. This is the compactness guard emphasized in the paper: the indeterminacy in choosing a hull approximant remains inside  $\phi(P)$ . The bounded-family version of Remark 3.9.5(v)–(vi) is now represented by a family-hull quotient source. For a family  $P_\beta$ , the code forms the hull of the union, uses it as the collapsed subset in the upper-semi quotient, and proves that any two nonempty possible regions have the same quotient image. This quotient source is now connected directly to the typed Theorem 3.11 indeterminacy layer. The declaration

```
IUTStage1MultiradialThetaImages
  .remark395Ob5QuotientEndpoint_of_related
```

starts from a multiradial possible-image package with its explicit (Ind1), (Ind2), (Ind3) quotient relation, forms the corresponding Remark 3.9.5 family  $P_B$ , and proves that related choices have

equal possible-image regions and equal upper-semi quotient images after collapsing  $\phi(P_B)$ . The experiment surface exposes the same bridge as

`multiradialThetaImages_remark395IndeterminacyOb5Endpoint.`

This Theorem 3.11 bridge now has a strengthened Ob5–Ob7 endpoint,

`IUTStage1MultiradialThetaImages`  
`.remark395Ob5Ob6Ob7Endpoint_of_related`

with experiment wrapper

`multiradialThetaImages`  
`_remark395IndeterminacyOb5Ob6Ob7Endpoint.`

The endpoint forms the same Remark 3.9.5 possible-image family from the typed (Ind1), (Ind2), (Ind3) quotient, proves the Ob5 quotient collapse for related choices, threads the family through the Ob6  $H_{\Phi(P_B)}$  and  $H_{\Xi(P_B)}$  log-volume inequalities, and then attaches the Ob7  $F^{\times\mu}$ -prime-strip source. Two synchronization equalities require the Ob7 hull/determinant bridge to use the same possible-image family and the same holomorphic hull operator, so this audit does not allow an unrelated prime-strip log-volume comparison to masquerade as the Theorem 3.11 possible-image comparison. As before, equality across an (Ind3) generator is not inferred from the one-sided Step (x) upper-semi inequality; it is precisely the explicit image-invariance field of the typed multiradial quotient package. The map statement in Remark 3.9.5(v) is now lifted to this bounded-family source: any set map from a nonempty possible region  $P_i$  into another possible region  $P_j$  induces, after quotienting by the family hull, the same image as the quotient map on  $P_i$  itself. The “formal empty set” extension in the same remark is represented by a finite formal-intersection system: a family of nonempty subsets of the collapsed subset  $S$ . Lean proves that every component has quotient image  $\{S\}$ , that all component images agree, and that component maps induce the same collapsed image after quotienting. Remark 3.9.5(vi)’s expected-equivalence statement is also represented for the bounded-family hull: for arbitrary nonempty regions  $A, B$ , their quotient images are both the collapsed point if and only if  $A \subseteq \phi(P_B)$  and  $B \subseteq \phi(P_B)$ . The Ob5 compatibility of this quotient formalism with  $\det^{\otimes M}(\phi(P_B))$  and  $\mu_{\log}(\phi(P_B))$  is now represented at finite log-volume level: the same family hull that collapses the possible regions is identified with the weighted determinant log-volume, and the associated tensor-power normalization recovers this family-hull log-volume. Lean now also derives  $\mu_{\log}(\bigcup_{\beta} P_{\beta}) \leq \det_{\log}$  from hull monotonicity and this determinant identification. The public Ob5 endpoint exposes these facts together with the expected-equivalence condition: for nonempty regions  $A, B$ , both quotient images are the collapsed family-hull point if and only if  $A, B \subseteq \phi(P_B)$ . The Ob9 log-volume passage is now represented at the same finite hull level. A realified semi-simplification correspondence between two hull shadows sends closed hulls to closed hulls, has a two-sided inverse on closed hulls, and preserves hull log-volume. Applied to the bounded-family hull, Lean proves that the transported hull still has log-volume  $\det_{\log}$ . This is the coarse log-volume content of Ob9; it is not yet a construction of the full log-link or its arbitrary-iterate indeterminacy. The Corollary 3.12 possible-image approximant source now projects the same estimate directly, so the upper-ray route can read  $\mu_{\log}(P) \leq \det_{\log}$  from that source object. Remark 3.9.6 is represented by a finite product-formula theorem: if the log-link preserves the local log-volume at every place and the source and target conversion ratios agree, then the weighted global arithmetic degree sums agree. This has also been specialized to the Corollary 3.12 possible theta-image family, so the possible-image hull used by the upper-ray route and the Ob5 family-hull quotient/determinant source are definitionally the same hull. The

canonical specialization now exposes this family-union-to-determinant estimate at its endpoint. The Corollary 3.12 possible-image approximant source projects to this family-hull quotient source, so the possible-image family used in the upper-ray route also carries the corresponding choice-independence theorem. Since the  $q$ -pilot region is contained in the chosen approximant and the approximant lies in the same family hull, the code also proves that a nonempty  $q$ -pilot region has the same family-hull quotient image as any nonempty possible theta-image choice. The same approximant now feeds the Step (xi) upper-ray constructor. If the  $q$ -pilot region lies in an approximant  $H$ , and if  $\mu_{\log}(H)$  is the determinant-normalized log-volume, then Lean derives

$$\mu_{\log}(q) \leq \mu_{\log}(H) \leq \mu_{\log}(\phi(P)), \quad \mu_{\log}(q) \leq \det_{\text{norm}}.$$

Thus this part of the corridor no longer has to use only the canonical hull itself; it can use any certified hull-approximant inside  $\phi(P)$ . This has now been specialized to the possible-image union in Corollary 3.12. One source object carries the family of possible theta images, the union  $P$ , a certified approximant  $H \in \Phi(P)$ ,  $q \subseteq H$ , and determinant normalization of  $\mu_{\log}(H)$ . The Step (x)-to-Step (xi) comparison is now expressed by a named handoff proposition over this fixed corridor and hull source. Thus the two numerical identifications  $\mu_{\log}(H) = \text{Ind3}_{\text{upper}}$  and  $\mu_{\log}(q) = \bar{\mu}_{\log}(q)_{\text{pre-Ind}}$  are no longer loose parameters of the endpoint; they are the explicit source obligation required before the Step (xi-f) upper-ray datum is formed. Lean then derives the whole chain

$$\mu_{\log}(P) \leq \mu_{\log}(H) \leq \mu_{\log}(\phi(P)), \quad \mu_{\log}(q) \leq \mu_{\log}(H) \leq \det_{\text{norm}}.$$

The determinant side has also been sharpened at finite log-volume level. Following Remark 3.9.5(vii), (Ob3-1)–(Ob3-3), a localization summand now carries a rank  $> 1$ , a bundle log-volume, a structure-sheaf adjustment, and a positive weight. A determinant source forms the finite weighted sum of the adjusted summands, then derives the positive tensor-power log-volume and the normalized determinant log-volume by definition. This replaces supplied tensor-power and normalized values for this new route, but it remains a log-volume skeleton rather than a construction of arithmetic vector bundles. The localization input itself has been refined one step further: a finite direct-summand source computes the bundle log-volume as a sum of direct summand log-volumes before projecting to the localization summand interface. Thus the weighted determinant can now be built from finite direct-summand localization sources. The Ob3-1-2 structure-sheaf adjustment is also named explicitly. A structure-sheaf adjusted source carries

$$L_{\text{adj}} = \sum_{\gamma} L_{\gamma} - L_{\mathcal{O}(-)}$$

and proves that its weighted value is the same adjusted summand consumed by the determinant source. Thus the current determinant route separates direct summands, subtraction of the  $\mathcal{O}(-)$  contribution, positive weighting, tensor-power formation, and normalization as distinct Lean interfaces. The possible-image approximant route can now consume this weighted determinant source directly. The equality between the approximant log-volume  $\mu_{\log}(H)$  and the weighted normalized determinant value is now carried by a named Ob3-3 compatibility certificate. After this certificate is supplied, the old determinant record is only a projection used by the common upper-ray interface. At the package-ledger boundary, the hull/determinant source data can now be constructed from a concrete common hull  $K$ , a proof  $P_{\text{out}} \subseteq K$ , and a determinant/log-volume estimate  $\mu_{\log}(K) \leq \theta_{\text{signed}}$ . The resulting Lean endpoint returns target-union containment, the determinant bound, all-target bounds, and equality between the package's named hull/determinant bridge and this constructed bridge. Thus the remaining source obligation is the construction of  $K$  and its bound, not an opaque

common-bound bridge. A more source-shaped constructor specializes  $K$  to  $\phi(P_{\text{out}})$  for an abstract hull operator  $\phi$ . Its endpoint proves that the bridge hull is definitionally this hull of the target union, and reduces the source input to the determinant/log-volume estimate for  $\phi(P_{\text{out}})$  plus equality with the package's named bridge. The Set-based holomorphic-hull shadow now induces the Region-level hull operator and Region measure used by this package bridge when the underlying type is the point set of a real-line copy. The endpoint identifies the Region hull with the original point-set hull, proves region containment, and recovers monotonicity of the induced log-volume. At the package level, this induced hull operator can now be used directly: if the charted package measure is identified with the induced Region measure and the point-set hull of  $P_{\text{out}}$  satisfies the determinant bound, then the hull/determinant source data is constructed from the holomorphic-hull shadow. The remaining bridge equality is explicit, so the package cannot display one hull construction while proving with another. The source package's theta-pilot possible-image record now also feeds the canonical hull approximant directly: Lean proves that its set-theoretic union is exactly the package target union before applying the determinant comparison. The possible-image approximant source now feeds this package bridge in the canonical case. If its possible-image union is the package target union, its chosen approximant is the canonical hull, the package measure is the induced Region measure, and the normalized determinant value is at most  $\theta_{\text{signed}}$ , then Lean constructs the same hull/determinant source data. No general containment of an arbitrary approximant is assumed. This has been lifted to the Theorem 3.11 source constructor: the approximant union may be tied to the source record's theta possible-image union, and the record then supplies the equality with the package target union. Thus the constructor no longer needs prebuilt hull/determinant source data in this canonical case. The same constructor now accepts the finite weighted determinant source from Remark 3.9.5(vii), (Ob3), directly. The determinant bound is stated for the weighted determinant log-volume, and Lean derives the normalized determinant bound consumed by the canonical hull bridge. A further specialization constructs the approximant as the canonical hull  $\phi(P)$  itself. In the current route the q-pilot input may be containment in the possible-image union  $P = \bigcup_i P_i$ ; Lean then derives q-pilot containment in  $\phi(P)$  from hull extensivity. Thus direct containment in  $\phi(P)$  is no longer a primitive input for this canonical possible-image specialization. Remark 3.9.5(vii), (Ob4), is represented at the same finite level: a naive Frobenius/tensor-power log-volume object records the passage  $L \mapsto ML$  for  $M > 0$ , and Lean proves that normalized log-volume recovers  $L$ . The weighted determinant source projects to this object, so the  $M$ -th tensor-power copy does not add a further log-volume ambiguity in the current corridor. A comparison object also proves that two positive tensor-power presentations with the same base log-volume have the same normalized log-volume, even when the tensor degrees differ. This has now been upgraded to the Ob4-3 family form: `IUTStage1TensorPowerTwistFamily` records a reference tensor-power presentation and an arbitrary family of reconstructed twisted presentations over the same base log-volume. Lean proves that every twist has the reference normalized log-volume, that any two twists have equal normalized log-volume, and that all normalized log-volume bounds are equivalent across the twist family. This is the finite log-volume reading of the source-paper statement that tensor-power-twist indeterminacies have no substantive effect on the estimates used in Corollary 3.12. The package hull/determinant bridge now has an Ob4-shaped input form: a bound on the normalized tensor-power log-volume of the weighted determinant source is converted by Lean to the determinant bound used by the canonical hull bridge. In the canonical-hull form, this Ob4 input also derives the approximant-equals- $\phi(P)$  witness internally. At the package boundary the same canonical Ob4 route can now start from q-pilot containment in the possible-image union  $P$ ; Lean derives containment in  $\phi(P)$  before constructing the hull/determinant bridge. The same endpoint is exposed at the Theorem 3.11 source-record level, so the possible-image union used by the canonical hull is the record's multiradial theta-image union before being identified with the package target union. For arbitrary

possible-image families that are later identified with the Theorem 3.11 record, the constructor now has the same source shape: start from  $q$ -pilot containment in the displayed possible-image union and derive containment in its canonical hull internally. The record-native specialization now has the same  $q \subseteq P_{\text{rec}}$  input form: the hull containment needed by Step (xi) is derived from the record's own possible-image union. A record-native specialization removes the arbitrary possible-image-family input: the family is  $i \mapsto P_i$  from the Theorem 3.11 source record, and Lean proves that its set-theoretic union is the record's theta-image union. Below the packet layer, the code now has a first realified Frobenioid degree source. A finite Frobenioid object carries a divisor degree, a unit log-volume, and their realified log-volume. A finite divisor-product source now records a tensor-packet product over base valuations whose packet factors are the real readings of the corresponding divisor-prime contributions plus base-local unit contributions; when the unit terms sum to the divisor source's unit log-volume, Lean derives that the packet product log-volume is the realified divisor log-volume. A finite divisor-monoid source computes this divisor degree from prime multiplicities and prime degrees, matching the finite shadow of the divisor monoid in IUT I, Example 3.5. The same source now has a divisor-level tensor product that adds multiplicities and realified log-volumes when the prime-degree data agree; its projection to the degree-object layer agrees with the existing degree-object tensor product. It also has the Ob4 naive Frobenius tensor-power operation: multiplying the divisor multiplicities and unit log-volume by  $M$  constructs a new finite Frobenioid object whose divisor degree and realified log-volume are proved to be  $M$  times the original values. The older realified degree-object layer now has the same Ob4 operation, and the projection from the finite divisor-monoid source to that degree-object layer is proved to commute with tensor-power formation. The theta-version of IUT I, Example 3.5(ii), is now represented at this finite level: the same divisor degree is read through a formal  $\log(\Theta)$ -generator, and normalization of this generator to 1 recovers the ordinary finite divisor source. The Ob4 tensor-power operation also lifts to this theta copy, where Lean proves that the theta divisor log-volume is multiplied by  $M$ . The  $D$ -, or log-shell, version of Example 3.5(iii) is represented similarly: a distinguished local Frobenius/log-shell reading is divided by the extension degree before it is applied to the finite divisor degree. Tensor-powering this copy leaves the normalized Frobenius reading fixed and multiplies the resulting log-shell divisor log-volume by  $M$ . The three finite copies now have a compatibility package: if they share the same base divisor source and the theta/log-shell readings are normalized, then their log-volume readings are equal. This compatibility package is now stable under simultaneous Ob4 tensor-powering: the ordinary, theta, and log-shell copies are tensor-powered over the same object, the base identifications and normalizations are preserved, and all three finite log-volume readings are multiplied by  $M$ . The environment/Gaussian realified Frobenioid comparison of IUT II, Corollary 4.6(v), is represented at the same finite level by an evaluation package between two such compatible copy systems. The package stores only the ordinary divisor-source identification; Lean derives equality of the ordinary, theta, and log-shell log-volume readings across the environment and Gaussian sides from that identification and the copy-compatibility lemmas. The comparison is also stable under simultaneous Ob4 tensor-powering: the ordinary-source equality is preserved, the theta/log-shell comparison is rederived on the tensor-powered evaluation, and the two ordinary realified log-volume readings are multiplied by  $M$ . The same comparison is now connected to the finite local-global restriction layer, reflecting the  $F$ -prime-strip formulation following Corollary 4.6(v): if the environment and Gaussian global objects are the degree projections of their ordinary divisor sources and their local restrictions agree pointwise, then Lean derives equality of the global realified log-volumes and of all local restricted log-volume readings. The prime-index part of the same  $F$ -prime-strip statement is now explicit: finite prime-label types for  $C_{\text{env}}$  and  $C_{\text{gau}}$  come with bijections to the common valuation set  $V$ , and the evaluation map between prime labels is required to commute with these bijections. Lean then transports the local compatibility theorem along this prime-place square, deriving equal-



ity of restricted and local realified log-volumes at evaluated primes. The next functorial step toward the  $\Theta^{\times\mu}$ - and  $\Theta_{\text{gau}}^{\times\mu}$ -links of Corollary 4.7(iii) is also represented at finite level. A lift to an  $F^{\times\mu}$ -prime-strip stores an environment-side unit character; the Gaussian-side unit character is defined by transport along the prime-evaluation equivalence. Thus Lean proves unit-character compatibility at evaluated primes rather than accepting it as an independent bridge field. The coric  $F^{\perp\times\mu}$  invariance of Corollary 4.7(iv) is represented by a common unit character on the valuation set  $V$ . Once the environment unit character is the pullback of this coric character along  $\text{Prime}(C_{\text{env}}) \simeq V$ , Lean derives the corresponding Gaussian equality from the prime-evaluation square. The coric global realified Frobenioid compatibility of Corollary 4.7(v) is represented by a positive real scale on finite local-global Frobenioid collections. This is the finite shadow of the  $R_{>0}$ -orbit language: given scaled equality of the global realified log-volume and of the restricted local prime readings, Lean derives the scaled local-object and local-prime log-volume equalities from the existing local-global collection laws. The Frobenius-picture graph of Corollary 4.7(vi) is represented by the directed successor relation  $n \rightarrow n + 1$  on  $\mathbb{Z}$ . Lean proves that translations preserve this oriented graph and that any map exchanging the adjacent vertices 0 and 1 cannot preserve directed edges. This captures the finite order-theoretic content of the paper's statement that the chain has translation symmetry but not arbitrary permutation symmetry. Proposition 3.10(ii)'s column log-Kummer correspondence is now represented at the same finite level. For each vertical coordinate  $m \in \mathbb{Z}$ , the source carries a packet of group elements acting on one common  $IQ$ -carrier labelled by  $n, \circ$ . Translation in the column transports group elements, and Lean proves that the transported element acts by the same endomorphism on the common carrier. This records the translation-invariance of the log-Kummer action; it does not yet construct the underlying number fields. The realified-Frobenioid part of Proposition 3.10(iii) is represented at degree level by a family of realified Frobenioid objects indexed by  $m \in \mathbb{Z}$ . The log-link translation law preserves the extracted realified log-volume, including adjacent  $m \mapsto m \pm 1$  shifts. The associated etale-picture core of Corollary 4.11(i),(ii) is represented by a common  $D^{\perp}$ -core projection for all integer-labelled spokes. Lean proves that this projection is constant across successor steps and is unchanged by arbitrary permutations of the integer-labelled spokes, capturing the finite mono-analytic core/permutation-symmetry contrast with the Frobenius-picture chain. The value-group restriction discussed in Remark 4.10.3 is exposed as a combined finite-label endpoint: for a Gaussian degree evaluation, the canonical full label  $j = 1$  has degree equal to the environment  $q$ -degree, the canonical square weight at  $j = 1$  is 1, and the singleton restriction to  $j = 1$  is not stable under translation by 1. Thus the identity/pivotal specialization and the failure of compatibility with the full label symmetry are checked in the same typed statement. A finite tensor-product operation on these degree objects adds divisor degrees and unit log-volumes, and Lean proves that the realified log-volume of the tensor product is the sum of the two realified log-volumes. This operation is also lifted to the tensor-packet source layer: if an existing tensor-packet product source is certified to carry the tensor-product Frobenioid degree, Lean derives additivity of its packet product log-volume. A Frobenioid Kummer-compatibility certificate then projects to the coric tensor-packet transfer by deriving equality of product log-volumes from equality of realified Frobenioid log-volumes, while retaining the Hodge-theater history guard. This is still a finite degree-level shadow, not a construction of Mochizuki's Frobenioids, but it moves one equality source below the packet-correspondence interface. The same degree layer now has finite Frobenioid morphisms. A morphism records the divisor-degree shift and unit-log-volume shift between two realified objects; Lean derives the corresponding shift in realified log-volume and proves identity and composition laws at this degree/log-volume level. This models the additive content of the pull-back and structure morphisms appearing in Remark 3.9.5(ix), (cQ3). These morphisms now transport across Ob4 tensor-powering: the source and target degree objects are tensor-powered, and the divisor and unit shifts of the induced morphism are multiplied by  $M$ . The Ob8/Ob9 vertical-shift issue is now

attached directly to the Step (xi-g) handoff. A log-Kummer vertical-shift calibration pairs the Step (x)-to-hull upper-ray source with the global realified Frobenioid calibration. Lean proves that the calibrated value is the hull boundary used by the upper ray, that both q-pilot computations are bounded by this calibrated value, and that a shifted local value coincides with the calibrated value only when the shift term vanishes. Remark 3.9.5(ix)'s distinction between (cQ3),(cQ4) and (iQ5) is now represented by a finite closed-loop guard. The guard ties the hull/determinant log-volume obtained from the (sQ3) route and the calibrated log-Kummer log-volume obtained from the (sQ4) route to the same Step (xi) boundary. Lean then proves that the two values coincide, while the direct shifted local log-volume agrees with this boundary exactly in the zero-shift case. This does not construct  $F^{\times\mu}$ -prime-strips; it records the present formal boundary between the source-faithful route and the log-volume-only quotient. The global-to-local realified restriction from IUT I, Example 3.5 is also encoded at degree level: the restricted global prime log-volume is  $[K_v : (F_{\text{mod}})_v]^{-1}$  times the local prime log-volume, and Lean proves that multiplying by the extension degree recovers the local prime log-volume. The same restricted value now normalizes the local  $p_v^N$ -shift source: the local shift is expressed with this restricted global prime step, and the automorphism-or-zero-step criterion is restated in terms of the restricted realified prime log-volume. Remark 3.9.5(ix)'s local-global collection language is represented at the same finite degree level. A collection contains a local realified Frobenioid object for each  $v$ , one global realified Frobenioid object, and localization restriction factors. Lean proves that each local log-volume is the restricted global value and that multiplying by the corresponding extension degree recovers the global log-volume. This is a finite log-volume shadow of the local-global category, not a construction of the category itself. The collection and its restriction factors now transport coherently under Ob4 tensor-powering: local objects, the global object, restricted prime log-volumes, and local prime log-volumes are all multiplied by  $M$ , while extension-degree rescaling remains valid. This local-global collection now also backs the finite cQ3/cQ4 closed-loop guard: if the collection's global realified log-volume is the cQ3 hull/determinant boundary, then Lean proves that every localized value rescales to both the cQ3 boundary and the cQ4 calibrated log-Kummer boundary. Thus the Step (xi) boundary can be read from the local-global collection rather than from a bare real number alone. The local-global collection has also been refined by structure morphisms in the finite Frobenioid degree category. For each  $v$ , a degree morphism from the local object to the global object records divisor and unit shifts. Lean proves that the resulting morphism shift is exactly the additive form of the localization rescaling. This models the degree/log-volume content of the "structure poly-morphism" language in Remark 3.9.5(ix), (cQ3). The structure-morphism collection now transports through Ob4 tensor-powering: the underlying local-global collection is tensor-powered, and every structure morphism acquires divisor and unit shifts multiplied by  $M$ . The same finite category now has compatible morphisms between two such local-global structure collections. A compatible morphism consists of local morphisms at each  $v$ , one global morphism, and a commutativity condition: the local-then-structure path and the structure-then-global path have the same divisor and unit shifts. Lean derives equality of the total realified log-volume shift along these two paths. The same compatible morphism now transports through Ob4 tensor-powering: the global morphism, all local morphisms, and the two paths in the compatibility square acquire shifts multiplied by  $M$ , and the square remains commutative. IUT I, Example 5.1 and Remark 5.1.1 distinguish the diagonal Frobenioid  $F_{\langle J \rangle}$  from the product of underlying categories  $F_J$ : the former carries constant distributions in  $j$ , while the latter allows arbitrary distributions. The code now models this finite realified log-volume distinction. A diagonal distribution has total log-volume  $|J|$  times its common value, with the realified restriction factor propagated through this sum; a distribution with two unequal coordinates is proved not to come from a diagonal constant distribution. IUT I, Example 5.4(vii) and Remark 5.4.2 are represented by a finite pivotal distribution object: a chosen pivotal index supplies the common diagonal

log-volume, the summed interpretation gives total  $|J|$  times this pivotal value, and the averaged interpretation recovers the pivotal value itself. IUT I, Definition 5.5 is now represented at finite log-volume level by an NF-bridge mode object: the bridge target is either the summed capsule log-volume or the normalized averaged capsule log-volume. For the same capsule distribution, Lean proves that the summed bridge target is  $|J|$  times the averaged bridge target; for a pivotal distribution, these specialize to  $|J|$  times the pivotal value and to the pivotal value itself. The adjacent  $\Theta$ -bridge and  $\Theta$ NF-gluing condition of Definition 5.5(iii) are formalized at the same finite level: the  $\Theta$  side reads the common capsule total, and a compatibility record requires the NF- and  $\Theta$ -bridge morphisms to use the same index bijection and the same capsule distribution. Lean then proves that a summed NF target equals the  $\Theta$ -target, while an averaged NF target becomes the  $\Theta$ -target after multiplication by  $|J|$ . Corollary 5.6(iii) is represented by a finite gluing torsor: once compatible NF and  $\Theta$  bridge halves have been fixed, the gluing parameter is modeled by the additive  $F_\ell$ -torsor on  $\mathbb{Z}/\ell\mathbb{Z}$ . Lean proves zero action, additivity of the action, existence and uniqueness of the translation between two gluing parameters, and preservation of the shared index-bijection and capsule data. This layer is now connected to the nonarchimedean packet correspondence: a realified-Frobenioid log-Kummer packet source projects the Frobenioid compatibility data to the Kummer  $F \rightarrow D$  transfer and to the mono-analytic forgetting transfer, and then feeds the existing packet correspondence endpoint. Thus the Step (x) source equality used by the route can be obtained from realified Frobenioid log-volume compatibility plus the remaining packet source/target calibrations. IUT III, Remark 3.11.4 further says that the root-of-unity and cyclotomic indeterminacies arising from forgetting Frobenius-like labels are invisible for the objects under consideration. The present code formalizes the finite sign-unit part of this assertion: a unit in the subgroup  $\{1, -1\} \subset (\mathbb{Z}/\ell\mathbb{Z})^\times$  preserves the zero/nonzero full cusp label, every full-label log-volume expression, and the averaged Gaussian log-volume. This is not yet a construction of the full cyclotomic rigidity isomorphism; it is the finite-label component that the current Stage 1 interface can prove without an additional Frobenioid/cyclotome layer. The same finite-label layer now also proves the corresponding exclusion: an affine coordinate change  $j \mapsto t + aj$  preserves the full cusp label if and only if  $t = 0$  and  $a$  is represented by such a sign-unit invisibility certificate. For nonzero Gaussian environment degree, the same classification is equivalent to pointwise preservation of the Gaussian degree profile. Thus the current code has a finite analogue of the “no further indeterminacies” assertion of Remark 3.11.4(ii). It also separates this cyclotomic invisibility from the stronger square-weight preservation used by the factored SHE layer: a root-unit invisibility action always preserves the full-label map, but it preserves the raw representative-square profile, equivalently the combined square/full-label preservation package, if and only if the root unit is the identity. The integrated route now composes the Hodge–Arakelov theta-value sources with this packet-target nonarchimedean source. The resulting theorem derives the same boundary/strict  $C_\Theta$  dichotomy from source-facing Gaussian evaluation data and source-facing upper-semi data, rather than from two unrelated collections of raw equalities. For the target side, the strongest route now uses a target-only Step (x) alignment

$$\Theta_{\text{avg}} = U_{\text{Ind3}}$$

together with calibration of the local entry target against  $U_{\text{Ind3}}$ . The direct equality  $\Theta_{\text{avg}} = \text{entry}_{\text{target}}$  is then derived. When the theta-source average is identified with the packet-normalized capsule log-volume, this target alignment is itself derived from calibration of  $U_{\text{Ind3}}$  with the same packet-normalized value. The local entry target may now also be calibrated against this packet-normalized value, so the equality  $\text{entry}_{\text{target}} = U_{\text{Ind3}}$  is derived rather than supplied directly in the strongest route.

## 5.4 Step (xi-f) algebra

The final real algebra is fully formalized. In informal notation, the main theorem is:

**Theorem 1** (Formal Step (xi-f)). *Assume  $q < 0$ ,  $q \leq \theta$ , and  $\theta \leq C(-q)$ . Then  $C \geq -1$ . If  $q < \theta$ , then  $C > -1$ . If  $C = -1$ , then  $q = \theta$  and  $\theta < 0$ .*

This theorem is instantiated by the Step (x)-to-Step (xi) route whenever the hull/log-volume upper-ray comparison and the displayed  $C_\Theta$ -bound are available. It is also instantiated by the current nonarchimedean (Ind3)-plus-factored-SHE route, subject to the same positivity and displayed-bound hypotheses. Thus the remaining gap is not the final ordered-real implication, including its strict and boundary branches, but the construction of the source hypotheses consumed by that implication.

## 6 Boundary Quotient Experiment

The most developed diagnostic concerns Step (xii), where local Frobenioid  $p_v^N$ -ambiguity is compared with the globally calibrated log-volume. The formal model records a local shift

$$L_N = L_0 + N\delta, \quad N \in \mathbb{Z}, \delta \in \mathbb{R},$$

and a global calibration that fixes exponent 0. Lean proves

$$L_N = L_0 \iff N\delta = 0,$$

and, if  $\delta \neq 0$ ,

$$L_N = L_M \iff N = M.$$

At the boundary branch  $C_\Theta = -1$ , the formal corridor identifies

$$q_{\text{pilot}} = \Theta_{\text{hull}} = L_0.$$

The local shift model is now source-facing: a local Frobenioid log-shell submodule carries a  $p_v^N$ -action whose log-volume effect is  $L_0 \mapsto L_0 + N\delta$ . The local action records whether the  $p_v^N$ -endomorphism is an automorphism, and in the current model this is equivalent to  $N = 0$ . The global realified Frobenioid calibration package selects exponent 0, hence its calibrated value is  $L_0$ . If the local endomorphism is not an automorphism and  $\delta \neq 0$ , Lean proves that the local shifted value cannot equal the globally calibrated value. The same calibration can now be built from the restriction-normalized local source, so the local step is the restricted global prime log-volume rather than an independent real parameter. For the actual upper-ray quotient that collapses  $\{x \mid x \leq \Theta_{\text{hull}}\}$ , Lean proves the exact classification

$$[L_N] = [q_{\text{pilot}}] \iff N\delta \leq 0,$$

and the complementary separation criterion

$$[L_N] \neq [q_{\text{pilot}}] \iff N\delta > 0.$$

If  $\delta > 0$ , this becomes:

$$[L_N] = [q_{\text{pilot}}] \iff N \leq 0, \quad [L_N] \neq [q_{\text{pilot}}] \iff 0 < N.$$

This is not a proof for either side of the Mochizuki–Scholze–Stix dispute. It is a precise reading of one simplified quotient mechanism inside the current formal corridor. It shows that quotient collapse can identify unequal underlying log-volumes if they lie in the collapsed upper ray, while positive local shifts remain separated. The decisive question is therefore not the ordered-real algebra; it is whether the source IUT constructions actually supply the required calibrated hull/log-volume comparison without making an illicit identification of histories or comparison levels.

## 7 Current Results

The project currently proves the following source-facing results in Lean:

1. The finite  $q^{j^2}$  degree rule, sign quotient, half-range representatives, zero/nonzero split, and average formulas are formalized.
2. The bad-local theta-root quotient- $\mathbb{Z}$  package now feeds the Stage 1  $|F_\ell|$  full-label model through its canonical coordinate; the concrete  $\mathbb{Z}/\ell\mathbb{Z}$  case yields the canonical nonzero full label.
3. A single label-independent scalar cannot absorb all representative  $j^2$ -degrees when  $\deg(q) \neq 0$ .
4. The raw representative branch does not descend to the sign quotient, while the balanced full-label Gaussian branch does.
5. The Step (x) averaged-log-volume corridor feeds a Step (xi) upper-ray comparison once determinant/hull identifications are supplied.
6. A nonarchimedean (Ind3) entry with factored square/full-label preservation now directly supplies the final weighted-theta route and the signed  $C_\Theta \geq -1$  endpoint, once  $q$ -positivity and the displayed  $C_\Theta$ -bound are supplied.
7. The same nonarchimedean route now exposes the strict branch  $C_\Theta > -1$  and the boundary consequence  $C_\Theta = -1 \Rightarrow q_{\text{signed}} = \Theta_{\text{signed}} < 0$ . It also packages these as one dichotomy at the route level.
8. Gaussian degree evaluations with preserved environment degree now feed directly into this nonarchimedean  $C_\Theta$  dichotomy, constructing the factored square/full-label SHE package internally.
9. In the identity-coordinate Gaussian route, equality at the canonical full label 1 supplies the environment-degree preservation needed by the same nonarchimedean  $C_\Theta$  dichotomy.
10. The Hodge–Arakelov theta-value evaluation source now constructs the Gaussian degree evaluation from a theta-monoid degree and the bad-local theta-root label source; canonical-label preservation feeds the factored SHE square/full-label obligations.
11. The same finite Hodge–Arakelov layer now has an audited theta evaluation wrapper matching the current IUT II shadow: it keeps the theta-root source, bad-local quotient identification, Gaussian degree evaluation, full-label compatibility, canonical  $j = 1$  behavior, and the canonical square-weight profile as one source-facing object. A pair of these objects constructs the SHE synchronization source and can also construct the finite Hodge/SHE transport source once the allowed-forgetting witness is given.

12. A nonarchimedean upper-semi object equipped with 1-column q-pilot log-Kummer data now supplies the raw nonarchimedean (Ind3) entry alignment used by the canonical Gaussian route.
13. The source-side equality in that compatibility can be derived from product-log-volume preservation along the finite Kummer-plus-forgetting tensor-packet chain.
14. A theta-root attached Kummer/forgetting source package now combines the canonical bad-local  $|F_\ell|$ -label source with a source-side packet/product calibration object and that finite chain, deriving the nonarchimedean source equality.
15. Source-side and target-side packet calibrations are now joined by one nonarchimedean log-Kummer packet-correspondence source carrying the q-pilot non-interference guard. Its projections derive the theta-to-packet, theta-to-entry, entry-to-(Ind3)-target, and packet-normalized target equalities used by the route; the target calibration now refers directly to the packet-normalized capsule value rather than to a separate real representative.
16. The strongest Gaussian first-pass route can now consume this single packet-correspondence source and project both its source and target faces, instead of taking source packet equalities and target calibration as separate route inputs.
17. A realified-Frobenioid log-Kummer entry source now bundles the selected upper-semi inclusion with the realified packet source; the strongest Step (x) route projects Kummer transfer, mono-analytic forgetting, source/target packet calibration, and q-pilot non-interference from this single source.
18. A theta-root attached realified entry source now combines the canonical bad-local theta-root label package with that realified Step (x) source, and the Hodge–Arakelov route can consume this attached source directly.
19. The Hodge/SHE/IPL/hull route now also has a realified endpoint: route alignment supplies the Hodge–Arakelov and q-pilot data, and Step (x) enters through the theta-root attached realified source.
20. Remark 3.9.5(iii)’s hull-approximant family is now represented directly: an approximant lies inside the canonical hull  $\phi(P)$ , has log-volume between  $P$  and  $\phi(P)$ , and is fixed by hull formation.
21. The bounded-family upper-semi quotient of Remark 3.9.5(v)–(vi) is represented: each possible region lies in the hull of the family union, and any two nonempty possible regions have identical images in the quotient that collapses this family hull.
22. The Ob5 determinant/log-volume compatibility of this family quotient is represented at finite level: the same  $\phi(P_B)$  quotient source is paired with a weighted determinant certificate, and Lean proves that the determinant log-volume and normalized tensor-power log-volume are the family-hull log-volume.
23. This Ob5 compatibility is specialized to the Corollary 3.12 possible theta-image family: the upper-ray source hull and the family quotient determinant/log-volume source share the same  $\phi(P_B)$ .
24. The canonical possible-image Ob5 endpoint now returns the family-union-to-determinant estimate, not only the quotient collapse and determinant equality.

25. The Corollary 3.12 possible-image approximant source now projects to this bounded-family quotient source, yielding the same quotient-image equality for nonempty possible theta-image choices.
26. In that same source, q-pilot containment in the chosen approximant implies q-pilot containment in the family hull; if the q-pilot region is nonempty, its quotient image agrees with the quotient image of any nonempty possible theta-image choice.
27. Such a certified hull-approximant now also constructs the Step (xi) upper-ray datum: if the  $q$ -pilot region is contained in the approximant and the approximant log-volume is determinant-normalized, then Lean derives the  $q$ -pilot bound by the approximant, by the canonical hull, and by the determinant log-volume.
28. The approximant route is now specialized to the Corollary 3.12 possible-image union. A single source object binds the possible theta-image family, its union, the chosen hull-approximant, q-pilot containment in that approximant, and determinant normalization; the experiment endpoint returns the union/approximant/hull and q-pilot/determinant inequalities.
29. The determinant input can now be produced from a finite weighted localization source: adjusted vector-bundle summand log-volumes are summed, the positive tensor-power value is derived, and normalization is proved to return the determinant log-volume before projecting to the determinant interface.
30. Each localization summand can now itself be produced from a finite direct-summand source: the bundle log-volume is the sum of direct-summand log-volumes, then the structure-sheaf adjustment and positive weight produce the adjusted localization contribution.
31. The Ob3-1-2 structure-sheaf adjusted source makes the  $\mathcal{O}(-)$  subtraction explicit before projection to the localization summand. A corresponding determinant constructor proves that summing these weighted adjusted sources gives the determinant log-volume used by the route.
32. The possible-image hull-approximant endpoint now has a weighted determinant-source constructor. The route consumes the weighted summand source and projects to the common upper-ray interface only after a named Ob3-3 compatibility certificate identifies the approximant log-volume with the weighted normalized determinant value.
33. The weighted determinant route now has a canonical-hull specialization: the approximant is constructed as  $\phi(P)$ , q-pilot containment is stated directly in this hull, and the approximant-equals-hull proof is derived by Lean rather than supplied as a separate route input.
34. The Ob4 tensor-power passage is now represented at log-volume level:  $M$ -th tensor-power formation multiplies by  $M > 0$ , and normalization recovers the base log-volume. The weighted determinant source projects to this tensor-power object, and two tensor-power presentations with the same base log-volume have equal normalized log-volume. The new `IUTStage1TensorPowerTwistFamily` extends this from a pairwise comparison to a family of Ob4-3 tensor-power-twist reconstructions: all twists share the reference normalized log-volume, and normalized log-volume bounds are invariant under replacing one twist by another.
35. The bounded-family hull/determinant source now proves the direct estimate from possible-image union to determinant log-volume:  $\mu_{\log}(\bigcup_{\beta} P_{\beta}) \leq \det_{\log}$ .

36. The Corollary 3.12 possible-image approximant source now exposes the same possible-image-union-to-determinant estimate directly.
37. The all-in-one target-charted Hodge/IPL determinant possible-image route now has a named Step (xi) comparison-chain audit, `targetChartedHodgeIPLDeterminantPossibleImageRoute_stepXIComparisonChainAudit`. This audit derives, at the route boundary, the chain

$$\mu_{\log}(q_{\text{pilot}}) \leq \mu_{\log}(P_B) \leq \mu_{\log}(\phi(P_B)) = \det_{\text{norm}} = \det_{\log} \leq \theta_{\text{signed}},$$

together with  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . Thus the public route no longer exposes only the final signed comparison; it also records the possible-image containment and determinant-normalization chain that produces it.

38. This comparison-chain audit is now threaded through the finite-divisor vertical- $IQ$   $C_{\Theta}$  endpoint as `targetChartedHodgeIPLDeterminantPossibleImageRouteFiniteDivisorVerticalIQ_stepXIComp`. The endpoint returns the same Step (xi) log-volume chain next to the conditional Corollary 3.12 dichotomy, so the finite Step (x) boundary can be audited through the constructed possible-image/determinant comparison rather than only through a coarse Gaussian-to-Step (xi) summary.
39. The package-level hull/determinant bridge can now be built from the Ob4-normalized tensor-power bound associated to a weighted determinant source. The conversion to the determinant bound is a Lean theorem, not a separate bridge assumption.
40. A first realified Frobenioid degree layer is present: equality of realified Frobenioid log-volumes now derives the product-log-volume equality used by the tensor-packet coric transfer, with the-ater histories still kept distinct. The degree object also has a finite tensor-product operation: divisor degree, unit log-volume, and realified log-volume are proved to add. A tensor-packet source certified by this Frobenioid product inherits product-log-volume additivity.
41. The realified Frobenioid degree object can now be constructed from a finite divisor-monoid source: Lean computes the divisor degree as  $\sum_p m_p \deg(p)$  before adding the unit log-volume.
42. A finite divisor-product source now turns a base-valuation tensor-packet product into a realified Frobenioid packet source when every packet factor is the real reading of its divisor-prime contribution plus a base-local unit contribution, and the unit contributions sum to the divisor source's unit log-volume. The equality between packet product log-volume and realified Frobenioid log-volume is derived from the finite sum, not supplied as a separate field.
43. The Step (x) packet-local source alignment can now consume this finite divisor-product source: after identifying the packet-local object with the local entry source and the divisor realified log-volume, Lean derives the entry-source/mono-analytic-product equality used by the log-Kummer source calibration.
44. The procession-normalized Step (x) average now has an  $\mathbb{F}_{\ell}$ -labelled source object: Lean computes the total as  $\sum_{j \in ZMod(\ell)} v_j$ , the normalized value as  $\ell^{-1} \sum_j v_j$ , and proves this average is unchanged by translating all labels.
45. The corresponding finite-label indeterminacy endpoint proves that two successive label translations preserve the normalized average by finite reindexing; an upper bound on the twice-translated summands then yields the (Ind3) upper bound for the original average.



46. A target-side Step (x) calibration constructor now derives  $\theta_{\text{avg}} = \text{packetNormalized}$  from the  $\mathbb{F}_\ell$ -labelled procession average, instead of taking this equality as an unclassified direct input.
47. The realified Frobenioid packet source has the same labelled-average constructor: Kummer/forgetting compatibility, source calibration, and labelled Step (x) average construct the full packet source and expose the ordinary log-Kummer packet correspondence endpoint.
48. The labelled-average constructor now reaches the theta-root attached Step (x) entry source and the Hodge/SHE/IPL/hull route. The route derives the packet-normalized theta calibration by composing theta-source-to-labelled-average with labelled-average-to-packet-normalized equality.
49. The labelled-average Hodge/SHE/IPL/hull route now has a source-aligned form: packet-local source alignment and Kummer/forgetting transfers construct the source calibration internally.
50. The theta-source-to-labelled-average equality can now be derived from labelwise agreement between the capsule-labelled source and the Hodge-descent theta-source  $ZMod(\ell)$ -average.
51. The labelled-average-to-packet-normalized equality can now be derived from labelled capsule local-object equality plus direct packet-normalization; the integrated route exposes this stricter source boundary.
52. The direct-labelled route now has an exact vertical- $IQ$  target form: the target-side (Ind3) equality is derived through the common packet-normalized value, not passed as ordered-real alignment data.
53. The direct-labelled vertical- $IQ$  route now has a finite-divisor form: source packet-local alignment is constructed from finite divisor/Frobenioid product data rather than supplied as a separate alignment record.
54. The Hodge direct-labelled finite-divisor route can now consume the all-in-one target-charted Hodge/IPL/determinant possible-image route source directly: the source-derived Hodge/SHE/IPL/hull bridge is projected from that route source before the labelled Step (x) boundary is entered.
55. The direct-labelled and finite-divisor routes no longer require labelwise equality with the theta-source  $ZMod(\ell)$ -average as route input; it is derived from Hodge-descent label-local-object transport.
56. The theta-root attached Step (x) source can now be constructed from the same finite divisor-product source and an exact vertical- $IQ$  target. The endpoint exposes the canonical bad-local theta-root label, Kummer/forgetting product equalities, finite divisor product equality, target packet normalization, q-pilot non-interference, and the upper-semi bound.
57. The finite divisor-monoid source now has its own tensor product: multiplicities and unit log-volumes add, and Lean proves additivity of the induced divisor degree and realified log-volume.
58. The same finite divisor-monoid source now has an Ob4-style naive Frobenius tensor-power operation: multiplicities and unit log-volume are multiplied by  $M$ , and Lean proves the induced divisor degree and realified log-volume are multiplied by  $M$ .

59. The older realified degree-object layer now has the same Ob4 tensor-power operation, and the projection from a finite divisor-monoid source to this layer commutes with tensor-power formation.
60. The projection of this divisor-level tensor product to the realified degree-object layer agrees with the existing degree-object tensor product, preventing these two Frobenioid shadows from drifting apart.
61. The theta-version of the finite divisor source is now represented: a formal  $\log(\Theta)$ -generator scales the divisor degree, normalization to 1 recovers the ordinary source, and tensor products preserve additivity when the theta generators match. The Ob4 tensor-power operation also lifts to this copy, multiplying the theta divisor log-volume by  $M$ .
62. The  $D/\log$ -shell version is also represented at finite level: Lean normalizes a distinguished local Frobenius log-volume by the extension degree, recovers the ordinary source when this normalized value is 1, and proves tensor-product additivity when normalized values match. The Ob4 tensor-power operation preserves the normalized Frobenius reading and multiplies the log-shell divisor log-volume by  $M$ .
63. The ordinary, theta, and log-shell divisor copies now have a compatibility package: shared base divisor data plus normalized readings imply equality of all three finite log-volume readings. Simultaneous Ob4 tensor-powering of the three copies preserves this compatibility package and multiplies all three finite log-volume readings by  $M$ .
64. The finite environment/Gaussian realified Frobenioid comparison attached to IUT II, Corollary 4.6(v), is now encoded as an evaluation package between two compatible copy systems. The only stored bridge is equality of the ordinary divisor source; Lean derives equality of the ordinary, theta, and log-shell readings across the two sides. Simultaneous Ob4 tensor-powering preserves the stored ordinary-source equality, rederives the theta/log-shell comparison, and multiplies the two ordinary realified log-volume readings by  $M$ .
65. This evaluation package is now tied to the existing finite local-global restriction layer: if the two global objects are the degree projections of the ordinary environment/Gaussian divisor sources and the local restrictions agree at every  $v$ , then Lean derives equality of the global realified log-volume and of the pointwise local restricted log-volume readings.
66. The prime-index skeleton of the corresponding  $F$ -prime-strip evaluation is now explicit: finite prime-label types for  $C_{\text{env}}$  and  $C_{\text{gau}}$  carry bijections to  $V$ , and the evaluation equivalence between prime labels must commute with these bijections. Lean transports the local compatibility theorem along this square to obtain equality at evaluated primes.
67. The finite  $F^{\times\mu}$ -prime-strip lift used by the  $\Theta^{\times\mu}$ - and  $\Theta_{\text{gau}}^{\times\mu}$ -links is now represented by transport of a unit character along the prime-evaluation equivalence. The Gaussian unit character is constructed from the environment unit character, and Lean proves compatibility at evaluated primes.
68. The coric  $F^{\perp\times\mu}$  invariant of Corollary 4.7(iv) is now represented at finite level: a common unit character on  $V$  pulls back to the environment side, and Lean derives the Gaussian-side pullback equality from the prime-evaluation square.

69. The coric global realified Frobenioid compatibility of Corollary 4.7(v) is now represented by a positive real scale on finite local-global Frobenioid collections. From scaled global and restricted-local readings, Lean derives the scaled local-object and local-prime log-volume readings.
70. The Frobenius-picture graph of Corollary 4.7(vi) is now represented as the directed successor graph on  $\mathbb{Z}$ . Lean proves translation invariance and rules out edge preservation by any map that swaps adjacent vertices 0 and 1.
71. The etale-picture  $D^\perp$ -core of Corollary 4.11(i),(ii) is now represented as a common core projection for all integer-labelled spokes. Lean proves successor-step constancy and invariance under arbitrary permutations of the spoke labels.
72. The value-group restriction of Remark 4.10.3 is now a single endpoint: the Gaussian degree at  $j = 1$  equals the environment  $q$ -degree, the square weight at  $j = 1$  is 1, and the singleton-1 restriction is not translation-invariant.
73. The realified Frobenioid degree layer now has finite morphisms: divisor and unit shifts determine the target realified log-volume, identity has zero shift, and composition adds both shifts. These morphisms are stable under Ob4 tensor-powering, with divisor and unit shifts multiplied by  $M$ .
74. The Ob8/Ob9 vertical-shift guard is now tied to the Step (xi-g) two-computation handoff: global realified Frobenioid calibration selects the hull upper-ray boundary, both q-pilot readings are bounded by it, and shifted local coincidence is equivalent to a zero shift term.
75. The cQ3/cQ4 portion of Remark 3.9.5(ix) now has a finite closed-loop guard: the hull/determinant value and the calibrated log-Kummer value are proved equal as the same Step (xi) boundary, while the direct log-volume-only shifted value agrees with that boundary only under the zero-shift condition.
76. The global-to-local realified Frobenioid restriction factor of IUT I, Example 3.5 is formalized as inverse-extension-degree scaling of the local prime log-volume, with the degree-normalization identity proved in Lean. This restricted value is connected to the local  $p_v^N$ -shift source used in the Step (xii) diagnostic, and global calibration can now be constructed from this restriction-normalized source.
77. A finite local-global realified Frobenioid collection now models the degree/log-volume content of Remark 3.9.5(ix): each local object is a restricted global value, and extension-degree rescaling recovers the global realified log-volume. The collection and its restriction factors are stable under Ob4 tensor-powering, with the realified readings multiplied by  $M$ .
78. The cQ3/cQ4 closed-loop guard can now be backed by such a local-global collection: the global collection value is identified with the cQ3 hull/determinant boundary, and every localized value rescales to both the cQ3 and cQ4 Step (xi) boundaries.
79. The local-global collection now carries finite structure morphisms from local objects to the global determinant object. The morphism divisor/unit shift is proved equal to the additive localization rescaling term. The structure-morphism collection is stable under Ob4 tensor-powering, with every structure-morphism shift multiplied by  $M$ .

80. Compatible morphisms between local-global structure collections are now represented: local-then-structure and structure-then-global paths have equal divisor/unit shifts and hence equal total realified log-volume shift. This compatibility is preserved by Ob4 tensor-powering of the source and target local-global structure collections.
81. The diagonal/arbitrary distribution distinction of IUT I, Example 5.1 and Remark 5.1.1 is formalized at finite realified log-volume level: diagonal distributions are constant in  $j$ , their total is  $|J|$  times the common restricted value, and a two-coordinate mismatch cannot be represented as diagonal.
82. The pivotal distribution of IUT I, Example 5.4(vii), is modeled by a chosen index in a diagonal distribution; Lean proves the summed log-volume formula and the normalized averaged formula of Remark 5.4.2.
83. The finite NF-bridge log-volume model of IUT I, Definition 5.5, separates summed and averaged bridge targets and proves their  $|J|$  scaling relation for a common capsule distribution.
84. The finite  $\Theta$ NF-bridge compatibility model records the same-index-bijection and same-capsule requirements of Definition 5.5(iii), and proves the corresponding  $\Theta$ -target equalities for summed and averaged NF modes.
85. The finite gluing set of Corollary 5.6(iii) is modeled as the additive  $F_\ell$ -torsor on  $\mathbb{Z}/\ell\mathbb{Z}$ , with compatibility data preserved under gluing translation.
86. The realified Frobenioid layer now feeds the nonarchimedean log-Kummer packet source: Kummer and mono-analytic forgetting transfers are projected from Frobenioid compatibility before the packet correspondence endpoint is applied.
87. A packet-normalized Step (x) entry-target source now constructs the target side of a nonarchimedean upper-semi entry from the capsule-family normalized log-volume. The target-calibration constructor derived from this source removes the separate entry-target-to-packet-normalized equality.
88. The same target-calibration layer can now derive the (Ind3)-target-to-packet-normalized equality from theta-target alignment and theta-average packet normalization, instead of accepting that equality directly.
89. A vertical- $IQ$  target source now models the exact common-target side of the log-Kummer correspondence in Proposition 3.10(ii). It derives the theta-average, (Ind3)-target, and entry-target packet-normalized equalities used by the packet target calibration.
90. The vertical- $IQ$  source carries an  $FMOD$ -exactness guard, reflecting Remark 3.10.1's distinction between exact  $FMOD$  Frobenioid compatibility and one-sided  $Fmod$  upper semi-compatibility.
91. The exact vertical- $IQ$  realified entry source now enforces that the realified packet target calibration is the calibration induced by the retained exact vertical- $IQ$  target.
92. The canonical exact Step (x) experiment route now constructs this refined source internally from theta-root data, realified Frobenioid transfer data, packet-local source alignment, and the exact vertical- $IQ$  target.

93. A finite-divisor canonical exact route now derives the packet-local source alignment from the finite divisor/Frobenioid packet product before constructing the exact source used by the Corollary 3.12 corridor.
94. Its compatibility and audit forms now construct the same finite-divisor source object first; the packet-local alignment and audit equalities are then projected from that object rather than from a separate alignment endpoint.
95. The strongest finite-divisor canonical exact route consumes this finite-divisor packet data as one source object: finite divisor packet, mono-analytic realization, packet-local/source equality, divisor realified-degree equality, and (Ind3)-source equality are projected from that object rather than supplied as unrelated route arguments.
96. The public experiment audit form of this finite-divisor exact route exposes the source equality, mono-analytic product equality, divisor-degree normalization, (Ind3)-source equality, and upper-semi inequality used in that construction.
97. The source-aligned realified Step (x) entry endpoint now exposes this *FMOD*-exactness guard at the same level as the Kummer/forgetting transfer chain, target packet-normalized equalities, q-pilot non-interference, and upper-semi inequality.
98. The theta-root attached source-aligned Step (x) endpoint now carries the same *FMOD*-exactness guard together with the canonical bad-local theta-root label facts.
99. The log-Kummer packet-correspondence source can now be constructed from source packet/product calibration plus the packet-normalized entry target and theta-target alignment. The q-pilot non-interference, source equality, and target equality endpoint is then recovered from this constructed correspondence.
100. The packet-correspondence endpoint now exposes the full finite Step (x) transfer chain: Kummer product preservation, mono-analytic forgetting product preservation, source equality with the (Ind3) real source, target packet-normalized equalities, and q-pilot non-interference.
101. The source packet/product calibration itself now has a constructor from packet-local/source alignment, packet-local (Ind3)-source alignment, and Kummer/forgetting product-log-volume preservation. The source holomorphic-product equality is derived by this constructor.
102. A calibrated source packet/product face can now be projected back to the packet-local source-alignment object once the Kummer and mono-analytic forgetting transfers are supplied; the packet-local (Ind3)-source equality is reconstructed through that transfer chain.
103. The same projection is now available from a realified-Frobenioid log-Kummer packet source itself: its internal Kummer and forgetting compatibilities supply the transfer chain needed to recover the packet-local source-alignment object.
104. The realified Step (x) entry source now projects the same packet-local source alignment while retaining the selected entry's upper-semi membership.
105. The theta-root attached realified Step (x) entry source now projects the same packet-local source alignment while retaining the canonical generator and nonzero full-label facts.

106. The Hodge/SHE/IPL/hull route has a source-audit endpoint: from one theta-root attached realified Step (x) source, Lean returns the recovered packet-local alignment equalities together with the  $C_\Theta$  dichotomy.
107. The source-aligned Hodge/SHE/IPL/hull route now derives its target-only (Ind3) alignment from the Step (x) packet-normalized theta source and the exact vertical- $IQ$  target source, retaining the  $FMOD$ -exactness guard at the route boundary.
108. The audit form of this vertical- $IQ$  route also exposes the derived equality from the Hodge-descent theta average to the (Ind3) target value, before returning the  $C_\Theta$  dichotomy.
109. The packet-correspondence constructor has a stronger alignment form: packet-local source alignment, packet-local (Ind3)-source alignment, packet-normalized entry target, and theta-target alignment generate both packet calibrations before projecting the q-pilot endpoint.
110. The realified-Frobenioid log-Kummer packet source has the same reduced target-data constructor: Frobenioid compatibility yields the Kummer and forgetting transfers, while packet-normalized target data is generated from the entry-target source and theta-target alignment.
111. The vertical- $IQ$  target source has been lifted through the realified-Frobenioid entry source and the theta-root attached entry source, so their upper-semi endpoints no longer need independent target alignment equalities when common-target log-Kummer data is available.
112. The integrated Hodge/SHE/IPL/hull  $C_\Theta$ -dichotomy route now has a vertical- $IQ$  form: exact common-target log-Kummer data supplies the target equalities used by Step (x) before the route enters the final Corollary 3.12 real inequality.
113. The integrated vertical- $IQ$  route also has a source-reduced form: source packet calibration is constructed internally from packet-local alignments and realified Kummer/forgetting compatibility.
114. The same source-reduced vertical- $IQ$  data now constructs the realified Step (x) log-Kummer entry source itself, before any final  $C_\Theta$ -dichotomy theorem is invoked.
115. The realified packet source now also has a source-reduced constructor: packet-local/source alignment and packet-local (Ind3)-source alignment generate the source packet calibration using the Frobenioid-derived Kummer and forgetting transfers.
116. The realified Step (x) entry source has the same reduced boundary: entry membership plus source/target alignment data constructs the packet source internally and projects q-pilot non-interference, source equality, target equality, and the upper-semi inequality.
117. The same realified packet source now exposes a combined calibration endpoint: it proves Kummer and forgetting product-log-volume preservation, packet-local equality with the entry source, entry-source equality with the (Ind3) source, packet-normalized equality for the theta average, (Ind3) target, and entry target, and q-pilot non-interference.
118. The theta-root attached realified entry source now has the same source-reduced vertical- $IQ$  constructor: the upper-semi packet entry, packet-local source alignments, realified Kummer/forgetting compatibility, and exact vertical- $IQ$  target construct one source object that projects the canonical nonzero theta-root label facts and the realified Step (x) upper-semi endpoint.

119. The packet-correspondence source now has the same source-aligned vertical- $IQ$  constructor: a named packet-local source-alignment object and an exact vertical- $IQ$  target source construct one correspondence object before the realified-Frobenioid layer is applied.
120. The packet-correspondence source also has a source-aligned packet-normalized ordered-target constructor: the source face is generated from the named packet-local alignment object, while the target face is generated from the packet-normalized entry and theta-target alignment.
121. The theta-root attached realified entry source now projects the underlying packet correspondence endpoint, combining canonical bad-local label facts with transfer-chain equalities, packet target calibrations, q-pilot non-interference, and the upper-semi bound.
122. The Hodge/SHE/IPL/hull route now consumes this reduced theta-root Step (x) data directly: the theorem constructs the realified source internally from a named packet-local source-alignment object and exact vertical- $IQ$  target, then concludes the current  $C_\Theta$  dichotomy.
123. The same route has an ordered-real-line form: the packet-source and theta-target (Ind3) real equalities are extracted from one matched-scale ordered transport alignment, so they are no longer accepted as unrelated route inputs at this boundary.
124. The ordered packet-normalized route now has a source-aligned form: packet-local source alignment plus realified Kummer/forgetting compatibility construct the source calibration internally before the route enters the theta-root attached Step (x) source.
125. The same source-aligned ordered route now has a target-only alignment form: the source-side (Ind3) equality is supplied by the source alignment object, and the route consumes only the theta-target (Ind3) equality as ordered-real input.
126. The target-only (Ind3) alignment can now be constructed from a Step (x) packet-normalized theta-source alignment and an exact vertical- $IQ$  target source.
127. The realified-source vertical- $IQ$  audit recovers the packet-local source-alignment object from the theta-root attached realified log-Kummer entry source, so this route boundary no longer accepts that source alignment as an independent input.
128. The stronger realified-source vertical- $IQ$  audit also projects theta-average packet normalization from that same source, removing the separate Step (x) packet-normalized theta-source route from the audit boundary.
129. The finite-divisor vertical- $IQ$  route now constructs this theta-root attached realified source internally from the finite divisor/Frobenioid packet product, then invokes the realified-source audit. Thus the integrated route no longer reconstructs a packet-local alignment independently of the source object.
130. In the ordered form, the packet-normalized theta calibration can now be obtained from a constant  $ZMod(\ell)$  packet-normalized route. The theorem requires equality of the Hodge-descent theta source with the packet-normalized theta source, preventing a packet-normalization audit for one theta source from being used for another.
131. The same source equality is now bundled with the packet-normalized route as a Step (x) theta-source alignment, and the Hodge/SHE/IPL/hull endpoint consumes that aligned object instead of separate route/equality inputs.

132. The selected packet-normalized nonarchimedean entry is now bundled with its membership in the audited upper-semi inclusion family. The route consumes this single source object rather than a constructed entry and separate membership proof.
133. The source side of that Step (x) entry can now be supplied by a named packet/product source calibration. The route no longer receives the packet-local/source and source/mono-analytic-product equalities separately; they are projected from the calibration object before the realified Frobenioid source is constructed.
134. Below that calibration, the source/mono-analytic-product equality can now be derived from the finite divisor/Frobenioid packet product source whenever the packet-local object is identified with the entry source and the finite divisor realified log-volume.
135. The Hodge/SHE/IPL/hull vertical- $IQ$  route has a finite-divisor form: it consumes the finite divisor packet source directly and constructs the packet-local source alignment internally before deriving the  $C_\Theta = -1$  boundary alternative or strict  $C_\Theta > -1$  conclusion.
136. At the entry-source level, the finite-divisor vertical- $IQ$  constructor now first projects the full packet-source calibration from the finite-divisor packet source; the packet-local alignment is no longer the primary constructor at this boundary.
137. The finite-divisor packet source now also constructs the packet correspondence source itself: source calibration, vertical- $IQ$  target calibration, and q-pilot non-interference are bundled before the realified packet and entry sources are formed.
138. The same finite-source packet-correspondence boundary now covers the entry-target/theta-target branch: the packet-normalized entry target supplies the target face while the finite-divisor packet source supplies the source face.
139. The ordered Step (x) route itself now has the finite-source boundary: the finite-divisor packet source supplies the source alignment before the ordered (Ind3) target comparison enters the Hodge/SHE/IPL/hull endpoint.
140. The theta-target branch of the ordered Step (x) route now has the same finite-source boundary: the finite-divisor packet source supplies the source alignment, while the only remaining ordered target input is the theta-target (Ind3) alignment.
141. The first-pass Corollary 3.12 experiment endpoint now has a finite Step (x) source form: the upper-semi packet-normalized entry, finite-divisor packet source, realified Kummer/forgetting compatibilities, and exact vertical- $IQ$  target construct the realified log-Kummer entry source before the route enters the existing  $C_\Theta$  dichotomy theorem.
142. The public finite-divisor vertical- $IQ$  experiment surface now includes the source-object form and an audit endpoint, so the Step (x) source equalities are checked as projections of one finite-divisor/Kummer source.
143. The integrated Hodge/SHE/IPL/hull finite-divisor vertical- $IQ$  route now has the same source-object boundary. Its compatibility form constructs the finite-divisor packet-local source and delegates to the source-object route.
144. The direct-labelled finite-divisor vertical- $IQ$  route and its Hodge-derived labelwise specialization now use this source-object boundary as well; the finite-divisor compatibility forms no longer build an independent packet-local source alignment in their final proof path.



145. The theta-root attached realified Step (x) finite-divisor constructor now has the same finite-source form. The finite-divisor compatibility endpoint constructs this source object first and then exposes the theta-root label, Kummer/forgetting, product, target-normalization, and upper-semi facts as projections from it.
146. The ordered Step (x) vertical- $IQ$  target route now has the same finite-source boundary. Its finite-divisor compatibility form first bundles the finite divisor/Frobenioid data, then derives the source alignment used by the ordered target route from that source object.
147. The labelled-average Step (x) route has the same finite-source boundary: finite  $ZMod$ -averaging supplies packet normalization, while the finite-divisor packet source supplies the source-side packet-local alignment.
148. The direct-normalized labelled-average route has the same source boundary: direct packet normalization derives the labelled average, and the finite-divisor packet source supplies the Step (x) source alignment.
149. The theta-labelled target and vertical- $IQ$  route now have the same finite-source boundary: the labelled finite average supplies the theta-source calibration, the exact vertical- $IQ$  target supplies the target alignment, and the finite-divisor packet source supplies the source alignment.
150. The finite sign-unit/root-of-unity part of Remark 3.11.4 is formalized: sign-unit action preserves full cusp labels, full-label log-volume readings, Gaussian degrees, and averaged Gaussian log-volume.
151. The same finite layer classifies the allowed unit-affine label changes: full-label preservation is equivalent to zero translation plus a sign-unit invisibility certificate; under nonzero Gaussian environment degree this is also equivalent to pointwise Gaussian-degree preservation.
152. The root-unit action preserves the raw representative-square profile, equivalently the factored square/full-label package, only for the identity unit; root-of-unity invisibility is therefore not silently promoted to SHE square-weight preservation.
153. The current integrated route composes Hodge–Arakelov theta-value sources with the packet-target nonarchimedean source to obtain the same  $C_\Theta = -1$  boundary alternative or strict  $C_\Theta > -1$  conclusion.
154. A Theorem 3.11 multiradial source record now packages structured IPL/SHE/APT, coric output, possible theta images, pilot-column asymmetry, distinct log-shell treatments, and the no-history-identification guard.
155. The IPL source layer now has an explicit log-volume transport record with source and target Hodge-theater sides, prime-strip endpoint compatibility, log-volume preservation, and no-history-identification.
156. The SHE source layer now derives the current square/full-label preservation package from Hodge–Arakelov canonical-one synchronization, exposing pointwise representative comparison, transported-average equality, and the retained Hodge-history separation.
157. The Step (xi) hull/determinant layer now has a Theorem 3.11 source constructor: source obligations are derived from the source record where possible, the record’s theta possible-image union is tied to the hull endpoint, and the determinant bound yields  $q_{\text{signed}} \leq \theta_{\text{signed}}$ .

158. The theta-pilot possible-image family of the source package now feeds the canonical holomorphic-hull approximant directly: Lean identifies its set-theoretic union with the package target union before the determinant comparison is applied.
159. The package-level hull/determinant source bridge can now be constructed from a concrete common hull containing the target union and a determinant/log-volume bound for that hull. The experiment endpoint returns target-union containment, the determinant bound, all-target bounds, and equality with the package's named hull/determinant bridge.
160. The same source bridge has a hull-operator specialization: the common hull is  $\phi(P_{\text{out}})$  for the target-union region  $P_{\text{out}}$ , and the endpoint records this equality before deriving containment, determinant, and all-target bounds.
161. The Set-based holomorphic-hull/log-volume shadow now induces a Region-level hull operator and Region measure on real-line points. The experiment endpoint proves exact agreement with the original point-set hull, containment, and induced log-volume monotonicity.
162. The package-level hull/determinant bridge can now be constructed from that holomorphic-hull shadow when the package measure is identified with the induced Region measure and the point-set hull satisfies the determinant bound.
163. The possible-image approximant source can now construct the package hull/determinant bridge in the canonical case: the possible-image union must be the package target union, the approximant must be the canonical hull, and the normalized determinant value must be bounded by  $\theta_{\text{signed}}$ .
164. The Theorem 3.11 hull/determinant constructor can now be built directly from the source record plus this canonical approximant data, with the record's possible-image union supplying the bridge to the package target union.
165. The same Theorem 3.11 constructor can now be built from a canonical possible-image approximant backed by the finite weighted determinant source of Remark 3.9.5(vii), (Ob3). The endpoint exposes the equality between the approximant log-volume and the weighted determinant log-volume.
166. The canonical weighted determinant constructor now has the stronger canonical-hull input form: the approximant is definitionally  $\phi(P)$ , q-pilot containment is imposed in this hull, and the endpoint exposes the derived approximant-region equality.
167. The canonical possible-image route can now instead consume  $q \subseteq P = \bigcup_i P_i$ . The containment  $q \subseteq \phi(P)$  used by the upper-ray comparison is derived from hull extensivity, so the source interface is closer to the Step (xi) possible-image construction.
168. The canonical-hull route now has the same Ob4 tensor-power input form: a normalized tensor-power bound is converted to the determinant bound, while Lean derives the approximant-equals- $\phi(P)$  witness from the canonical hull constructor.
169. The package-level canonical Ob4 route now has a  $q \subseteq P$  source form: bridge construction, determinant normalization, target-union containment, and the signed-volume hull bound are all exposed after Lean derives  $q \subseteq \phi(P)$ .

170. This canonical-hull Ob4 endpoint is also public for the Theorem 3.11 source constructor: the source record's theta possible-image union is the hull input before the package target-union identification is applied.
171. The arbitrary-family Theorem 3.11 Ob4 constructor now also has a  $q \subseteq P$  source form. The family is then identified with the record's theta possible-image union, and Lean derives the hull containment consumed by the package-level source data.
172. The record-native Theorem 3.11 Ob4 route can now consume  $q \subseteq P_{\text{rec}}$ , where  $P_{\text{rec}}$  is the record's own possible-image union; Lean derives  $q \subseteq \phi(P_{\text{rec}})$  before constructing the final hull/determinant source constructor.
173. A record-native specialization now derives that theta-image union from the Theorem 3.11 record's own possible-image family, instead of accepting an arbitrary image family plus a separate union equality.
174. The Step (x)-to-Step (xi) upper-ray bridge can now be built directly from a certified possible-image hull approximant. The determinant normalization is read from the approximant/determinant compatibility, rather than supplied as a separate equality at the bridge boundary.
175. The Step (x)-to-Step (xi) hull comparison is now a named handoff proposition over a fixed procession corridor and fixed hull source; from this handoff Lean derives q-pilot upper-ray membership and determinant normalization at the Step (xi-f) boundary.
176. The same upper-ray bridge now has a log-Kummer vertical-shift calibration endpoint: the globally calibrated Frobenioid log-volume is the hull boundary used in Step (xi-g), not an independently chosen real value.
177. The Step (xi) endpoint now exposes the finite cQ3/cQ4 closed loop: hull/determinant passage and log-Kummer calibration produce the same boundary, and the shifted local log-volume route is equivalent to a zero-shift specialization.
178. A Hodge/SHE/IPL/hull packet-target route now derives the target-side log-volume equality from SHE synchronization and reads  $q$ -positivity from the hull constructor; the source-side theta/Hodge equality is derived from a full-label calibration certificate in the route-alignment source record.
179. The Hodge/SHE/IPL/hull alignment is now also exposed through a source-derived bridge object. This object keeps the Theorem 3.11 multiradial record, the IPL log-volume transport, the finite Hodge–Arakelov SHE transport, the Step (xi) hull/determinant constructor, and the theta/Hodge calibration certificate as separate source components, then constructs the route-level log-volume alignment internally. The finite transport records the source and target Hodge-theater sides, finite label transport, full-label log-volume preservation, transported-average preservation, and the present no-history-identification guard.
180. The finite Hodge/SHE transport now has a source-boundary layer: Lean constructs it from a Hodge-theater descent bridge, a typed allowed-forgetting witness, the current Hodge–Arakelov synchronization source, and the finite full-label preservation data. The witness records the source theater, target theater, descent operation, permission proof, and history-separation guard, separating the history/forgetting obligation from the downstream transport object.

181. The allowed-forgetting witness now has a canonical history-separated finite-stage form. Instead of treating the permission predicate as an unrelated route input, the public Hodge–Arakelov endpoint can take it to be the history-separation condition of the Theorem 3.11 Hodge-theater descent bridge carried by the source record. This removes a loose external Prop from the public corridor while preserving the trust boundary: the full source-paper construction of the Hodge-theater forgetting operation is still not claimed.
182. The IPL log-volume transport now has a source construction from the same finite Hodge/SHE transport plus a Theorem 3.11 IPL-link construction source. The construction builds the input-prime-strip link with source and target endpoints definitionally equal to the recorded input and output prime strips, then aligns the resulting IPL datum with the pre-ledger certificate. Its Hodge-theater sides are projected from the finite transport, and its log-volume preservation equality is the transported average preservation supplied by the finite Hodge/SHE layer.
183. The public IPL boundary also has a certificate-pinned link-source form. This form consumes the pre-ledger certificate’s own IPL datum together with just the endpoint equalities saying that its link source and target are the input and output prime strips. Thus the strongest finite-divisor route no longer has to carry a separate constructed IPL-datum alignment when the certificate datum itself already satisfies the Theorem 3.11 endpoint shape.
184. The Step (xi) holomorphic-hull/determinant route now has a source boundary wrapper around the record-native Ob4 constructor. The wrapper keeps the holomorphic hull shadow,  $q \subseteq P_{\text{rec}}$  containment, weighted determinant source, tensor-power bound, bridge equality, positivity, and normalization as separate auditable fields, then constructs the existing Theorem 3.11 hull/determinant constructor and exposes  $q_{\text{signed}} \leq \theta_{\text{signed}}$ .
185. The strongest Hodge–Arakelov/history-separated route can now consume that Step (xi) holomorphic-hull/determinant source as a single object. This keeps the  $q$ -pilot containment and determinant payload intact, but no longer expands the record-native hull fields at the public Hodge–Arakelov boundary.
186. The Step (xi) source boundary now also has a choice-linked  $q$ -pilot form: a named Theorem 3.11 possible-output choice carries  $q \subseteq P_{\text{choice}}$ , and Lean derives  $q \subseteq P_{\text{rec}}$  by the possible-image union inclusion. Thus the strongest Hodge–Arakelov/history-separated endpoint has a variant whose  $q$ -pilot containment is not an independent public field.
187. That choice-linked Step (xi) source now projects to the existing upper-ray and two-computation corridor. From the canonical hull and weighted-determinant compatibility, Lean constructs the  $R_{\leq -|\log(\Theta)|}$ -style upper-ray datum, proves membership of the  $q$ -pilot log-volume in this ray, derives the determinant upper bound for that  $q$ -pilot log-volume, and records equality of the input-prime-strip and output-hull  $q$ -pilot readings.
188. The choice-linked Step (xi) source now has a stricter exact-theta form. Instead of carrying the normalized tensor-power upper bound as a separate field, it carries the equality identifying  $\theta_{\text{signed}}$  with the normalized Ob4 tensor-power log-volume of the weighted determinant source. Lean then derives the old tensor-power bound, projects back to the existing choice-linked hull source, and exposes a public Hodge–Arakelov/history-separated finite-divisor endpoint for this stronger source shape.

189. That exact-theta Step (xi) source now has a side-conditioned form as well. The q-pilot positivity and source normalization proofs are no longer two loose fields in this variant; they are projected from *IUTStage1SourceSideConditions*, the same side-condition boundary used when promoting source data to the Stage 1 ledger.
190. The exact-theta Step (xi) source now also has a hull/det-data-backed form. In this variant, the equality with the package's named hull/determinant bridge is no longer carried directly. Instead the source consumes *IUTStage1SourceHullDetData*, projects the package bridge equality already stored in that object, and then identifies the stored bridge data with the record-canonical Step (xi) hull/tensor-power construction.
191. The same boundary now has a record-native bounded-family hull form. This new source object specializes the Ob5 bounded-family hull/determinant source to the Theorem 3.11 possible-image family, so the family union  $P_{\text{rec}}$ , its hull  $\phi(P_{\text{rec}})$ , the weighted determinant source, and the normalized Ob4 tensor-power log-volume are tied to one record-level object. The strengthened endpoint assumes  $\theta_{\text{signed}} = \mu_{\log}(\phi(P_{\text{rec}}))$ ; Lean then derives the older exact tensor-power equality and the tensor-power bound from the Ob5 hull/determinant compatibility.
192. The record-native bounded-family source now projects back to the generic Ob5 bounded-family hull/determinant source. Thus the record-level possible-image family reuses the existing quotient-collapse theorem, possible-region containment in the family hull, determinant/log-volume comparison, and normalized tensor-power endpoint instead of duplicating a weaker record-specific summary.
193. The history-separated Hodge–Arakelov, certificate-pinned IPL, finite-divisor vertical-*IQ* endpoint now consumes this family-hull-backed source directly. The endpoint constructs the source-derived Hodge/SHE/IPL/hull bridge from this source, so the public route no longer has to present the exact tensor-power equality as the Step (xi) source-facing input. The experiment module exposes the same route as the audit theorem `familyHullBackedFiniteDivisorVerticalIQ_cThetaDichotomy`.
194. The family-hull-backed endpoint now also has a constructed-IPL form at the same boundary. The source-derived bridge is built directly from the input-prime-strip link construction source, so the bridge audit retains the equality between the package certificate's IPL datum and the constructed datum, before applying the same finite-divisor vertical-*IQ* route. The experiment module exposes this as `constructionFamilyHullBackedFiniteDivisorVerticalIQ_cThetaDichotomy`.
195. The same family-hull Step (xi) source now has an obligations-backed form. It consumes one *IUTStage1SourceHullDetObligations* object and projects the package hull/determinant data, q-pilot positivity, and source normalization from that object, rather than carrying them as separate Step (xi) fields. The experiment module exposes this stronger audit route as `obligationsBackedFamilyHullFiniteDivisorVerticalIQ_cThetaDichotomy`.
196. The obligations-backed family-hull route now also has the constructed IPL form. Thus the public boundary simultaneously keeps the input-prime-strip link construction visible and projects the Step (xi) hull/determinant data, q-pilot positivity, and normalization from the single obligations object. The experiment module exposes this as the corresponding constructed-IPL, obligations-backed family-hull dichotomy theorem.

197. The exact theta/family-hull identification now also has a Hodge-calibrated source form. Instead of supplying `thetaSigned = familyHullLogVolume` directly, the source object factors the equality through the Hodge–Arakelov theta-monoid degree, and the experiment module exposes this route as `hodgeCalibratedFamilyHullFiniteDivisorVerticalIQ_cThetaDichotomy`.
198. The Hodge-calibrated family-hull route now has a constructed-IPL form as well. It keeps the input-prime-strip link construction visible while the Step (xi) source still factors the exact theta/family-hull equality through the Hodge–Arakelov theta-monoid degree.
199. This Hodge-calibrated route now has a charted refinement. The source object calibrates the transported pre-ledger theta chart coordinate to the Hodge–Arakelov theta-monoid degree, and Lean derives the package `thetaSigned` equality from the existing chart theorem. The experiment module exposes this route as `chartedHodgeCalibratedFamilyHullFiniteDivisorVerticalIQ_cThetaDichotomy`.
200. The charted Hodge-calibrated route now also has the constructed-IPL form. The public boundary keeps the input-prime-strip link construction visible while retaining the chart-derived theta/Hodge scalar equality.
201. The charted Hodge/family-hull calibration now has a determinant-factored form. The source object calibrates the Hodge–Arakelov theta-monoid degree to the normalized determinant log-volume of the record-native family hull, and Lean derives the family-hull equality from the Ob5 hull/determinant compatibility. The experiment module exposes this route as `determinantChartedHodgeFamilyHullFiniteDivisorVerticalIQ_cThetaDichotomy`.
202. The determinant-factored route now has a summand-factored source form. The source object calibrates the Hodge–Arakelov theta-monoid degree to the finite sum of adjusted localization summands of the weighted determinant source; Lean derives the determinant and normalized determinant equalities before entering the same finite-divisor endpoint. The experiment module exposes this route as `summandChartedHodgeFamilyHullFiniteDivisorVerticalIQ_cThetaDichotomy`.
203. The summand-factored route now also has a source-calibrated Hodge–Arakelov input form. The source Hodge–Arakelov evaluation carries the full-label theta/Hodge log-volume calibration and projects the previous `IUTStage1SourceThetaHodgeLogVolumeCalibration` internally. The experiment module exposes this boundary as the source-calibrated variant of the summand-charted finite-divisor theorem.
204. The same source-calibrated summand route now has a constructed-IPL form. Instead of receiving the certificate-pinned IPL-link source and its endpoint equalities directly, the boundary consumes the Theorem 3.11 input-prime-strip link construction source and projects the link source internally before entering the finite-divisor vertical-*IQ* endpoint.
205. The constructed-IPL, source-calibrated summand route now also has a synchronized Hodge–Arakelov input form. The source object carries the calibrated source evaluation, target evaluation, and canonical one-label degree preservation together, so the public finite-divisor boundary no longer receives the Hodge/SHE synchronization equality separately.
206. The synchronized summand route now has a target-charted Step (xi) source form. Instead of receiving the charted-theta/source-Hodge scalar equality as an immediate summand-calibration field, the source reads the transported theta chart as the target Hodge–Arakelov

canonical one-label degree and derives the source theta-monoid degree equality from the synchronized canonical-one preservation.

207. The target-charted summand source now has a possible-image q-pilot form. The q-pilot region is fixed to the chosen Theorem 3.11 possible-image region, so the public Step (xi) source no longer carries a separate q-region and  $q \subseteq P_{\text{choice}}$  proof.
208. The target-charted possible-image summand route now has a Hodge-layer charted synchronization form. The target theta chart/canonical-one equality is projected from a target-charted Hodge–Arakelov synchronization object, while the Step (xi) source retains only the determinant summand equality and record-native possible-image hull data.
209. The target-charted possible-image route now factors the Hodge theta/summand comparison through a Hodge/determinant family-hull payload. This payload packages the record-native family-hull determinant source, the package measure calibration, and the Hodge theta-monoid/summand equality; the possible-image Step (xi) source then projects these fields instead of exposing them separately. The source now also exposes the converted side-conditioned possible-image hull/determinant endpoint before the Hodge/IPL wrapper is introduced. The experiment surface exposes the payload endpoint, the determinant possible-image endpoint, this side-conditioned hull endpoint, the constructed-IPL bridge audit, and the finite-divisor vertical- $IQ$   $C_{\Theta}$ -dichotomy route.
210. The synchronized target-charted possible-image summand/family-hull source now reduces to the constructor-built Step (xi) boundary. The named audit records the fixed Theorem 3.11 possible-image q-region, target chart/source theta-monoid equality, finite adjusted-summand equality, theta/family-hull equality, obligations bridge equality, q-positivity, normalization, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. A product-hull companion audit now carries the Remark 3.9.5 smallest-product-hull provenance through this same synchronized source whenever its family-hull shadow is induced by a product-hull system.
211. The target-charted Hodge/IPL side now has a packaged construction source. It binds the target-charted Hodge–Arakelov synchronization to the constructed Theorem 3.11 input-prime-strip link, projects the finite Hodge/SHE transport, and then projects the IPL log-volume transport from that same finite transport. The determinant possible-image bridge and finite-divisor vertical- $IQ$  endpoint can now consume this single Hodge/IPL payload instead of separate Hodge synchronization and constructed-IPL arguments. The construction source now also exposes the history-separated finite Hodge/SHE transport-source endpoint and the constructed IPL log-volume transport endpoint itself. The all-in-one route projects these finer audits rather than reaching through the finite construction source directly.
212. The strongest target-charted finite-divisor corridor now has an all-in-one Step (xi) route source. It binds the packaged Hodge/IPL construction source to the determinant possible-image payload, and the experiment surface exposes the route-source endpoint, the Hodge–Arakelov theta-evaluation/Gaussian endpoint, the history-separated Hodge–Arakelov finite Hodge/SHE transport-source endpoint, the finite Hodge/SHE transport endpoint, the constructed IPL log-volume transport-source endpoint, the constructed Hodge/SHE/IPL endpoint, the side-conditioned possible-image hull/determinant endpoint, the holomorphic-hull/log-volume endpoint, the canonical hull/tensor-power bridge endpoint, the source-boundary raw comparison endpoint, source-owned bridge endpoint, the bridge-level raw source-derived comparison endpoint, and finite-divisor packet-source and finite-divisor  $C_{\Theta}$ -dichotomy endpoints from this

single object. It now also exposes a finite-source Step (x) boundary audit before the external  $C_\Theta$  numeric bound: the route-owned bridge data, raw source comparison, packet-local finite-source equalities, and vertical- $IQ$  target equalities are all projected from the bundled route/source objects. The same route now has an exact vertical- $IQ$  finite-source form: the realified log-Kummer Step (x) source retains the exact vertical- $IQ$  target and transfer data, and the route projects its Kummer/forgetting compatibilities and  $FMOD$ -exact target internally. This exact finite route is now also bundled as a single source package joining the Step (xi) route source, upper-semi entry, finite packet-local source, and exact vertical- $IQ$  realified Step (x) source before the  $C_\Theta$  bound is applied. The bundle also exposes the realified Step (x) correspondence audit: theta-root canonical-label data, Kummer/Frobenioid product preservation, mono-analytic forgetting, q-pilot non-interference, and the upper-semi inequality are projected from the retained exact source. A compact source-derived corridor audit now records one load-bearing fact from each stage of the strongest chain: theta root, history-separated Hodge/SHE, constructed IPL, possible-image hull containment, raw comparison, exact vertical- $IQ$ , non-interference, and Step (x) upper-semi control. A companion Gaussian-front audit starts one step earlier, at the Hodge–Arakelov theta-evaluation source: canonical theta labels, Gaussian zero degree, square-weighted degree formula, full-label log-volume compatibility, and target chart comparison are tied to the same corridor facts.

213. The finite-divisor vertical- $IQ$  Hodge/SHE/IPL/hull endpoint now has a source-derived form: it consumes this separated bridge object instead of a prebuilt route alignment before constructing the same finite-divisor Step (x) source and proving the  $C_\Theta = -1$  boundary alternative or strict  $C_\Theta > -1$  conclusion.
214. The same finite-divisor vertical- $IQ$  endpoint now also has the milestone-facing constructor form: it consumes the finite Hodge/SHE transport source, a Theorem 3.11 IPL-link construction source, record-native Step (xi) hull data, and the theta/Hodge calibration certificate directly. The Step (xi) inputs are the record’s possible-image union,  $q \subseteq P_{\text{rec}}$ , the holomorphic hull shadow, weighted determinant source, tensor-power bound, and bridge equality. The endpoint constructs the IPL log-volume transport, the hull/determinant source, and the source-derived Hodge/SHE/IPL/hull bridge internally, then applies the finite-divisor vertical- $IQ$  route.
215. The constructor-backed finite-divisor endpoint now preserves the Remark 3.9.5 product-hull provenance. A product-hull-backed wrapper records that the measured hull operator is induced by the product-hull system, and the audit proves selected-product-hull equality, q-pilot containment, minimality among product hulls containing  $P_{\text{rec}}$ , product-hull log-volume equality, and the same raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison before returning the downstream  $C_\Theta$  dichotomy. The same wrapper now also exposes the Ob5 quotient/determinant compatibility at this product-hull boundary: for any nonempty comparison possible image, the q-choice possible image and comparison possible image have the same collapsed upper-semi quotient image modulo the selected product hull, and the selected hull log-volume is identified with the normalized determinant, determinant log-volume, and normalized tensor-power value. The Ob5 scalar companion is now explicit as well: after quotienting the real line by the singleton  $\{\mu_{\log}(\phi(P_B))\}$ , the normalized determinant scalar, ordinary determinant scalar, normalized tensor-power scalar, and family-hull log-volume scalar all have the same collapsed image. This records the Remark 3.9.5(Ob5) assertion that the upper-semi formalism applies compatibly to  $\phi(P_B)$ ,  $\det^{\otimes M}(\phi(P_B))$ , and  $\mu_{\log}(\phi(P_B))$ . Finally, the product-hull wrapper now projects to the source-facing possible-image family package: the Theorem 3.11 family  $P_B$ , its canonical



$\Phi(P_B)$  approximant, and any supplied exact  $\Xi(P_B)$  family are audited at the same boundary, with  $H_{\Xi(P_B)}$  identified with the selected product hull. The Ob6 hull-approximant log-volume audit is also exposed at this boundary:  $H_{\Phi(P_B)}$  and  $H_{\Xi(P_B)}$  are both identified with the selected product hull, while the raw family union, comparison possible image, and q-pilot region are estimated by the corresponding hull-approximant log-volumes before the normalized determinant equality is invoked. The same boundary now carries an exact-theta bridge audit: the package value  $\theta_{\text{signed}}$  is identified with the Remark 3.9.5 family-hull log-volume, the normalized tensor-power/determinant upper bound is derived from this equality, and the q-pilot log-volume comparison is threaded through the selected product hull into  $\theta_{\text{signed}}$ .

216. The milestone-facing endpoint has a Hodge–Arakelov source form as well: it consumes source and target Hodge–Arakelov theta-evaluation sources, canonical one-label degree preservation, and a typed allowed-forgetting witness, then constructs the finite Hodge/SHE transport internally. In this form the canonical square-weight profile and theta-root source are read directly from the Hodge–Arakelov source side before the endpoint applies the same Theorem 3.11 IPL, record-native Step (xi), and finite-divisor vertical- $IQ$  route.
217. A stronger Hodge–Arakelov endpoint removes even that explicit allowed-forgetting argument: it builds the finite Hodge/SHE transport with the record’s history-separated descent-bridge permission, then follows the same IPL, record-native Step (xi), and finite-divisor vertical- $IQ$  path.
218. The strongest Hodge–Arakelov/history-separated endpoint can now use the certificate-pinned IPL-link source. Its public assumptions no longer include an arbitrary finite Hodge/SHE transport, a free allowed-forgetting predicate, a free square-weight profile, a separate theta-root source, a constructed-IPL-datum alignment, or the raw record-native Step (xi) hull/determinant field list.
219. The target-side theta-to-entry equality is no longer a direct input in the strongest route. It is derived from a Step (x) theta-target alignment and calibration of the entry target with the upper-semi target value.
220. The Step (x) theta-target alignment can itself be derived from packet-normalized theta-source equality and calibration of the upper-semi target with the packet-normalized value.
221. The entry-target calibration can likewise be expressed by equality to the packet-normalized value, deriving equality with the upper-semi target.
222. The Step (xi-f) real algebra proves  $C_{\Theta} \geq -1$ , strictness under strict upper-ray membership, and equality constraints in the boundary case.
223. The final route rejects the balanced sign-compatible comparison level as sufficient; it requires hull/log-volume comparison data.
224. The local Frobenioid shift model is now sourced by a  $p_v^N$  log-volume action package and a global realified calibration package; a non-automorphic local shift with nonzero step is separated from the calibrated value, and the upper-ray quotient experiment gives the exact threshold for collapse versus separation in the boundary upper ray.
225. Several downstream IUT IV numerical estimates are formalized as ordered-real algebra conditional on the Corollary 3.12 input.

The first-pass experiment report evaluates the route-theorem, finite Gaussian, collapse-obstruction, upper-ray, and IUT IV algebra flags to **true**. The flag `disputeSettledByCurrentStage` remains **false**.

The current code base is large enough to distinguish three meanings of “available”. First, pure ordered-real consequences are proved outright. Second, route theorems prove that certain named source-facing records imply the desired endpoint. Third, the records themselves remain obligations when they stand for Hodge-theater, Frobenioid, log-Kummer, hull, determinant, or multiradial constructions not yet formalized from IUT I–III. Only the first two meanings are currently achieved.

## 8 What Is Not Yet Proved

No formal statement currently proves IUT III, Corollary 3.12 from Mochizuki’s published hypotheses. The following mathematics is still external to the code:

1. initial  $\Theta$ -data and its arithmetic hypotheses from IUT I;
2. Hodge theaters, Frobenioids, log-shells, prime strips, and theta links;
3. the Hodge–Arakelov theta evaluation and Gaussian monoids of IUT II;
4. the construction of the actual (Ind1), (Ind2), (Ind3) data in Theorem 3.11;
5. the genuine holomorphic hull and determinant constructions used in Step (xi), beyond the present source-data constructor and ordered-real upper-ray model;
6. the full proof that the typed SHE and Hodge-descent transport obligations follow from Mochizuki’s source constructions, beyond the current Hodge–Arakelov canonical-one synchronization shadow;
7. the construction of the input prime-strip link (IPL), simultaneous holomorphic expressibility (SHE), and algorithmic parallel transport (APT) properties as actual consequences of Theorem 3.11 rather than records;
8. the arithmetic-divisor, height, log-different, and log-conductor constructions behind the IUT IV Diophantine applications.

## 9 Implementation Audit

The code contains no explicit placeholder proofs or project-level trust-boundary declarations in the Stage 1 corridor. The current risk is not hidden unsoundness of this form, but mathematical incompleteness: several records are deliberately named obligation interfaces. These interfaces are acceptable only as temporary boundaries. The next phase must replace them by constructions from the source papers or mark them as unresolved.

For the Source-Derived Step (xi) Bridge milestone, the checked public endpoint is

```
Iut.Stage1.Experiments.boundarySignedEqualityOrStrictCTheta_from
  _sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ.
```

Its direct audit companion is

```
Iut.Stage1.Experiments.boundarySignedEqualityOrStrictCTheta_from
  _sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ
  _withDirectMilestoneAudit.
```

Both declarations have been added to the `checkdecls` list. A kernel `#print axioms` check for these two declarations, the explicit constructed-IPL alias, and the underlying namespaced constructed-IPL endpoint reports only `propext`, `Classical.choice`, and `Quot.sound`; in particular, no `sorryAx` appears. Thus the milestone is kernel-clean at the usual Lean classical/quotient trust boundary.

The Remark 3.9.5 holomorphic-hull/determinant milestone has now started at the source-object level. The new declaration `IUTStage1Remark395HolomorphicHull0Operator` records the source-facing  $\phi$ -operator laws directly: closed hulls are fixed,  $P \subseteq \phi(P)$ , inclusions are preserved,  $\phi(\phi(P)) = \phi(P)$ , and log-volume is monotone. It projects to the older closure-operator shadow used by the existing bridge code, but the public source object no longer begins with that shadow. This has now been backed by the earlier construction in Remark 3.9.5(ii): `IUTStage1Remark395HolomorphicHullSystem` defines  $\phi(P)$  as the intersection of all hulls that contain  $P$ . Its only source closure input is that this intersection is again a hull; Lean then derives P1–P3, idempotence, and  $\mu_{\log}(P) \leq \mu_{\log}(\phi(P))$ , before projecting to the existing  $\phi$ -operator interface. The possible-image family layer has also been made source-facing: `IUTStage1Remark395PossibleImageFamilySource` records the family  $P_B = \{P_\beta\}_{\beta \in B}$ , its union, the canonical hull  $\phi(P_B)$ , the  $\Phi(P_B)$  and  $\Xi(P_B)$  approximant types projected from this  $\phi$ -operator, and the Remark 3.9.5(Ob5) upper-semi quotient collapse. The experiment-surface declaration

`Iut.Stage1.Experiments.remark395PossibleImageFamilySource_endpoint`

proves that the family union and each possible image lie in  $\phi(P_B)$ , that the canonical  $\Phi$ -approximant is  $\phi(P_B)$ , and that any two nonempty possible regions have the same quotient image after collapsing  $\phi(P_B)$ . The exact-approximant companion

`Iut.Stage1.Experiments.remark395PossibleImageFamilySource  
_XiFamilyOb5Endpoint`

proves the same Ob5 collapse for  $H_{\Xi(P_B)}$ , while recording that each chosen exact approximant has log-volume  $\mu_{\log}(P_B)$ . This supplied-family endpoint is now accompanied by the more source-local constructor

`Iut.Stage1.Experiments.remark395PossibleImageExactXiFamilySource  
_toXiFamilyOb5Endpoint`

and its Ob6 companion. These endpoints start only from the exactness calibration  $\mu_{\log}(\phi(P_B)) = \mu_{\log}(P_B)$ , build the canonical exact  $\Xi(P_B)$ -family, and then recover the same quotient collapse and log-volume comparison. Thus this part of the corridor now records the specific mathematical equality needed to make  $\phi(P_B)$  exact, instead of treating the whole  $\Xi(P_B)$ -family as primitive. The same boundary has now been lowered to the concrete Hodge-theater/log-theta quotient source. The declaration

`concreteHodgeTheaterLogThetaConcreteCalibratedExactXi  
SelectedQRemark395GlobalCThetaAudit`

constructs the exact  $\Xi(P_B)$ -source from the typed quotient possible-image family and a single source-local calibration  $\mu_{\log}(\phi(P_B)) = \mu_{\log}(P_B)$ . Hence the remaining analytic payload is no longer a primitive exact- $\Xi$  family; it is precisely the paper-side proof of this calibration for the selected quotient possible-image union. For the closed-family case this has been lowered once more. The source `ConcreteClosedFamilyUnionExactXiSource` asks only that the concrete quotient possible-image union be closed for the Remark 3.9.5 hull operator; Lean then proves  $\phi(P_B) = P_B$  by the hull fixing law and derives  $\mu_{\log}(\phi(P_B)) = \mu_{\log}(P_B)$ . Thus the exactness obligation is now split into a

closed-region route and the remaining non-closed analytic calibration route. The closed-region route now has product-hull provenance. The source `ConcreteProductHullFamilyUnionExactXiSource` replaces bare closedness by the assertion that the quotient possible-image union is a product hull for the Remark 3.9.5 product-hull system whose induced holomorphic hull operator is the corridor operator. From this product-hull witness, Lean constructs the closed-family exact- $\Xi(P_B)$  source and enters the same global  $C_\Theta$  audit. This has a principal valuation-ball refinement: `ConcretePrincipalValuationBallFamilyUnionExactXiSource` starts from a Remark 3.9.5 valuation-ball product-hull cover and identifies the resulting valuation-cover union with the selected principal hull  $\lambda \cdot O$ . The sharper source `ConcreteValuationBallIndexedFamilyUnionSource` no longer takes the quotient-family/valuation-cover union equality as primitive: it requires an equivalence between the Theorem 3.11 quotient index and the valuation-cover index, plus pointwise equality of the corresponding possible regions, and Lean derives the union equality. This comparison has now been lowered one more step by `ConcreteValuationBallChoiceIndexedFamilyUnionSource`: instead of supplying the quotient-index equivalence, the source data supplies a choice-level valuation index map, proves that it is invariant under the typed (Ind1,Ind2) equality quotient, gives a representative Hodge-theater/log-theta choice over each valuation index, and proves pointwise equality of the corresponding possible regions. Lean constructs the quotient-index equivalence by `Quot.lift` and then derives the same valuation-cover union equality. The current preferred form specializes this once more to the theta-pilot class itself: `ConcreteValuationBallThetaClassIndexedFamilyUnionSource` fixes the valuation-cover index to the forgotten Hodge-theater/log-theta-lattice class, proves theta-class invariance across the generated (Ind1,Ind2) equality relation, and derives the choice-indexed valuation source from representative choices in each theta class. This has now been lowered to the fiber-backed source `ConcreteValuationBallThetaClassFiberBackedFamilyUnionSource`. Its representative fiber relation is no longer supplied: Lean builds the representative-to-choice relation as the canonical finite (Ind1) procession shift followed by the typed post-procession (Ind2) local tensor transport already present in the Theorem 3.11 source audit. The valuation-indexing payload at this boundary is therefore only the pointwise equality between quotient possible regions and theta-class valuation cells. That pointwise quotient comparison has now also been factored through concrete theta-pilot possible images. The source `ConcreteValuationBallThetaClassImageBackedFamilyUnionSource` supplies a theta-pilot-class possible-image family, identifies the record's choice-indexed possible images with the pullback of that class family, and identifies each class image with the corresponding valuation-ball region. Lean then uses the Theorem 3.11 equality-quotient pullback theorem to derive the quotient-region/valuation-region comparison required by the older fiber-backed boundary. This has now been lowered through `ConcreteValuationBallThetaClassRegionBackedFamilyUnionSource` and `ConcreteValuationBallThetaClassLatticeFormulaBackedFamilyUnionSource`. At this new boundary, the possible images are generated by the Hodge-theater id, history label, finite-label-forgotten log-theta-lattice coordinate, and coric datum already present in the concrete Hodge-theater/log-theta-lattice formula records. The valuation comparison is then a source-facing identification between those lattice-formula theta regions and the corresponding valuation-ball regions, not an arbitrary choice-indexed quotient comparison. The boundary has now been lowered one step further by `ConcreteValuationBallThetaClassLatticeImageLawBackedFamilyUnionSource`. Here Lean constructs the lattice formula and the record-level family equality from a single lattice-key invariance law: choices with the same Hodge-theater id, history label, finite-label-forgotten log-theta-lattice coordinate, and coric datum have the same Theorem 3.11 possible-image region. The boundary has now been lowered again by `ConcreteValuationBallThetaClassFiberTransportBackedFamilyUnionSource`. The lattice-key image law is no longer the primitive source input: the current packet/action transport source

is first forgotten through the typed  $(\text{Ind1}, \text{Ind2})$  procession/local-tensor chain to a theta-pilot fiber-transport invariant possible-image family, and Lean derives the lattice image law from that fiber-transport invariance. The valuation-side payload at this point is therefore the identification of the derived theta-pilot class regions with the corresponding valuation-ball regions. The log-volume side of this same concrete choice space has now been lowered by `ProcessionNormalizedLogVolumeSource`. Instead of accepting an arbitrary `IndeterminacyData` record, the source assigns to each theta-pilot class an actual averaged  $Z/\ell Z$ -label procession log-volume. Lean defines the log-volume of a concrete Hodge-theater/log-theta choice as this class average, proves the displayed average formula with  $|Z/\ell Z| = \ell$ , derives the old `IndeterminacyData` record, and constructs the typed core used by the quotient possible-image machinery. Thus the equality side of the indeterminacy layer is now built from finite procession averages; only the  $(\text{Ind3})$  upper-semi comparison remains a one-sided source input at this boundary. The next lowering is now also in place: `LogThetaLabelProcessionUpperSemiSource` supplies the label-by-label log-theta values over the canonical full  $F_\ell$ -procession of a theta-pilot class, and Lean constructs the averaged source internally. The open mathematical input below this point is the source-paper construction of those label-wise values and the two average equalities with the source/target upper-semi log-volume comparison. The selected-principal-hull equality has also been lowered: `ConcreteValuationBallSelectedPrincipalHullSource` requires the valuation-cover possible-image union to be a hull for its Remark 3.9.5 hull system, and Lean combines this fixed-point statement with the principal-hull selection theorem to derive equality with the selected  $\lambda \cdot O$  hull. This has now been lowered to the direct-product-cell exact source `ConcreteValuationBallDirectProductCellUnionExactSource`: it records that the valuation possible-image union is exactly the finite union of the valuation-ball direct-product cells, and Lean derives both hull-fixedness and equality with the selected principal hull from the already formalized Remark 3.9.5 principal-hull theorem. The preferred boundary has now been lowered once more by `ConcreteValuationBallDirectProductCellCoverSource`. Here the formal direction

$$\bigcup P_\Theta \subseteq \bigcup_\beta H_\beta$$

comes from hull containment together with the valuation-cover theorem  $\phi(\bigcup P_\Theta) = \bigcup_\beta H_\beta$ . The only source-facing payload is the reverse local cover statement: every valuation-ball direct-product cell  $H_\beta$  lies in the theta possible-image union. This has now been sharpened by `ConcreteValuationBallThetaClassDirectProductCellCoverSource`: each valuation cell carries a theta-pilot class, and the local cover proof is the containment of that cell in the corresponding theta-class possible region. Lean derives the older union-cover interface from these per-cell containments. The transported-region version `ConcreteValuationBallThetaClassFiberTransportCellCoverSource` states the containment before forgetting to the valuation cover, i.e. each  $H_\beta$  lies in the transported theta-class region attached to its theta-pilot class, and Lean derives both the valuation-region equality interface and the theta-class cell cover. The current preferred boundary is one step lower: `ConcreteValuationBallThetaClassFiberTransportLocalFactorCoverSource`. For each valuation cell it chooses a theta-pilot class and a local place, and requires containment of the corresponding compact-open valuation-ball factor in the transported theta-class region. Since  $H_\beta$  is the direct product of these local factors, Lean derives the previous whole-cell containment. The preferred boundary is now the local predicate source `ConcreteValuationBallThetaClassFiberTransportLocalThetaPredicateSource`. For the selected local place it identifies the transported theta region with the realization of a local predicate

$T_\beta(x)$ , and requires the local estimate

$$\|x\|_v \leq r_\beta \implies T_\beta(x),$$

where  $r_\beta$  is the compact-open radius chosen by the local Haar normalization. Lean realizes this predicate region to recover the pointwise theta membership, then uses `realizedRegion( $S$ ) = realization( $S$ )` and the valuation-ball audit `compactOpenSubset = valuationBall( $r_\beta$ )` to recover the valuation-radius, local-factor, and direct-product cell covers. This has now been lowered one step further by `ConcreteValuationBallThetaClassFiberTransportLocalThetaInequalitySource`. Here the local predicate is not opaque: it is the inequality

$$g_\beta(x) \leq R_\beta$$

for a named local theta gauge and threshold, and the source estimate proves

$$\|x\|_v \leq r_\beta \implies g_\beta(x) \leq R_\beta.$$

Lean then reconstructs the local-predicate source definitionally and enters the same exact- $\Xi(P_B)$  and global  $C_\Theta$  corridor. The gauge has now been specialized to the valuation-ball normalization itself by `ConcreteValuationBallThetaClassFiberTransportValuationNormGaugeSource`:

$$g_\beta(x) = \|x\|_v, \quad R_\beta = r_\beta.$$

Thus the implication  $\|x\|_v \leq r_\beta \Rightarrow g_\beta(x) \leq R_\beta$  is no longer a mathematical assumption. The equality boundary has also been lowered twice. First, `ConcreteValuationBallThetaClassFiberTransportValuationBallExactSource` replaces the two equalities needed by the valuation-norm gauge source with the two inclusions

$$P_{\Theta,\beta} \subseteq \text{realizedRegion}(B_\beta), \quad \text{realizedRegion}(B_\beta) \subseteq P_{\Theta,\beta}$$

and the analogous two inclusions between a transported theta-class region and the valuation-cover possible-image region. Lean reconstructs both equalities by antisymmetry and then enters the same valuation-norm-gauge endpoint. The next boundary is the pointwise source `ConcreteValuationBallThetaClassFiberTransportValuationBallPointwiseSource`. It replaces the set containments by the local lifting law

$$y \in P_{\Theta,\beta} \implies \exists x, \|x\|_v \leq r_\beta \wedge \text{realization}(x) = y,$$

the reverse realization law

$$\|x\|_v \leq r_\beta \implies \text{realization}(x) \in P_{\Theta,\beta},$$

and pointwise membership compatibility with the valuation-cover possible regions. The set containments and equalities are now projections from these local transport laws. This lifting law has now been lowered once more by `ConcreteValuationBallThetaClassFiberTransportValuationBallLocalChartSource`: for each transported theta point  $y$ , the source names its local coordinate  $x_\beta(y)$ , proves

$$\|x_\beta(y)\|_v \leq r_\beta, \quad \text{realization}(x_\beta(y)) = y.$$

This removes the existential lift, but at this stage the valuation-radius bound is still a raw source field. The image boundary is now an intermediate layer:

`ConcreteValuationBallThetaClassFiberTransportValuationBallLogShellImageSource`.

It names a local log-shell region  $I_\beta$ , a base point used only outside the transported theta region, the realized-image equality presented as the two containments

$$P_{\Theta,\beta} \subseteq \text{realization}(I_\beta), \quad \text{realization}(I_\beta) \subseteq P_{\Theta,\beta},$$

and the two valuation-ball containments

$$I_\beta \subseteq \{x : \|x\|_v \leq r_\beta\}, \quad \{x : \|x\|_v \leq r_\beta\} \subseteq I_\beta.$$

Lean chooses  $x_\beta(y)$  from the image statement when  $y \in P_{\Theta,\beta}$ , proves  $x_\beta(y) \in I_\beta$  and  $\text{realization}(x_\beta(y)) = y$ , derives the valuation-radius inequality from  $I_\beta \subseteq \{x : \|x\|_v \leq r_\beta\}$ , and then reuses the local-chart, pointwise, exact, and valuation-norm-gauge routes. The next boundary replaces these four containments by the two equalities

**ConcreteValuationBallThetaClassFiberTransportValuationBallLogShellExactSource.**

It requires

$$P_{\Theta,\beta} = \text{realization}(I_\beta), \quad I_\beta = \{x : \|x\|_v \leq r_\beta\},$$

and Lean derives the previous log-shell image source, the chosen local coordinate, the valuation-radius bound, and the same exact- $\Xi(P_B)$ /global  $C_\Theta$  audit. The next boundary is

**ConcreteValuationBallThetaClassFiberTransportValuationBallLogShellNonemptyExactSource.**

It replaces the supplied totalizing coordinate by the nonemptiness statement  $I_\beta \neq \emptyset$ ; Lean chooses the auxiliary coordinate from this nonemptiness and then projects to the equality-backed exact source. The preferred lower boundary is now

**ConcreteValuationBallThetaClassFiberTransportValuationBallNonemptyExactSource.**

It moves nonemptiness to the valuation-ball side:

$$\{x : \|x\|_v \leq r_\beta\} \neq \emptyset.$$

Using  $I_\beta = \{x : \|x\|_v \leq r_\beta\}$ , Lean derives  $I_\beta \neq \emptyset$ , then derives the previous nonempty log-shell boundary and the same exact- $\Xi(P_B)$ /global  $C_\Theta$  audit. This nonemptiness hypothesis has now itself been lowered to a centered valuation ball source:

**ConcreteValuationBallThetaClassFiberTransportCenteredValuationBallExactSource.**

For each local factor it supplies a point  $x_\beta$  and proves

$$\|x_\beta\|_v \leq r_\beta.$$

After unfolding the valuation-ball definition, Lean obtains  $x_\beta \in \{x : \|x\|_v \leq r_\beta\}$ , hence valuation-ball nonemptiness, log-shell nonemptiness, and the same exact- $\Xi(P_B)$ /global  $C_\Theta$  audit. This has now been lowered once more to the zero-centered source

**ConcreteValuationBallThetaClassFiberTransportZeroCenteredValuationBallExactSource.**

Here the center is fixed to 0. The source supplies only

$$\|0\|_v \leq r_\beta,$$

and Lean constructs the centered source with  $x_\beta = 0$ . The next boundary is metric-normalized:

`ConcreteValuationBallThetaClassFiberTransportMetricZeroValuationBall  
ExactSource.`

It no longer supplies the zero inequality. Instead it records, for each local factor, the normalization

$$\|x\|_v = \text{dist}(x, 0).$$

Together with the already available positivity  $0 < r_\beta$ , Lean proves  $\|0\|_v \leq r_\beta$  using  $\text{dist}(0, 0) = 0$ , then projects to the zero-centered endpoint. The log-shell boundary has also been lowered:

`ConcreteValuationBallThetaClassFiberTransportConstructedLogShell  
MetricZeroValuationBallExactSource.`

Here the local log-shell attached to a factor is no longer an independent set. It is defined to be the compact-open valuation ball

$$\{x : \|x\|_v \leq r_\beta\},$$

so the log-shell/valuation-ball equality is definitional. The remaining realization equality has now been factored into pointwise local transport:

`ConcreteValuationBallThetaClassFiberTransportPointwiseConstructed  
LogShellMetricZeroValuationBallExactSource.`

This source no longer supplies  $\Theta_\beta = \text{realize}(\{x : \|x\|_v \leq r_\beta\})$  directly. It supplies the two local assertions: every transported theta-region point has a lift in the compact-open valuation ball, and every local point in that ball realizes back into the transported theta region. Lean converts these assertions to the two set inclusions using the factor's `realizedRegion_eq_image` law and then obtains the equality by antisymmetry. A further source,

`ConcreteValuationBallThetaClassFiberTransportRegionBackedPointwise  
ConstructedLogShellMetricZeroValuationBallExactSource,`

removes the duplicated pointwise membership assumptions at this boundary. It uses the fiber-transport-backed equality

$$\Theta_{\text{class}} = P_{\Theta_{\text{class}}}$$

between the transported theta-class region and the valuation-cover possible region, and Lean derives the two membership directions by rewriting. The classwise equality is now itself derived from the sharper source

`ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined  
FamilyUnionSource.`

There the valuation-cover possible-region family is identified once with the transported theta-region family; evaluating this family equality at a theta-pilot class gives the previous classwise comparison. The corresponding pointwise source then reuses this family-level construction when deriving valuation-cover membership. The construction boundary has now moved inside the valuation cover:

`ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined  
ValuationCoverSource`



builds the Remark 3.9.5 valuation-ball/Haar tensor-packet cover with  $P_\beta$  fixed definitionally to the transported theta-region family. Its principal product-hull wrapper projects to the ordinary principal valuation-ball source, and the previous family-level equality is then `rfl`. This boundary now also has a source-core constructor: a Remark 3.9.5 factor-calibrated valuation-ball/Haar cover, or its principal valuation-ball product-hull wrapper, constructs the theta-region-defined Step (xi) cover as soon as its possible-image family is identified with the transported theta-region family. The newest constructor derives this family-level equality from the fiber-transport-backed pointwise comparison by function extensionality, and there is now a lattice-image-law-backed version: once the lattice image law used in the valuation comparison is identified with the one produced by the fiber-transport source, the same principal theta-region-defined cover is constructed. When the lattice law is obtained by projecting a fiber-transport-backed source, this identification is now a named `rfl` theorem and the public endpoint routes through the lattice-image-law constructor without an extra equality argument. Thus the finite-additive Haar tensor factors, principal  $\lambda O$  hull, local-integer region, and selected-hull log-volume identity are inherited from the source-core object instead of being re-supplied in the Step (xi) source. The remaining source-facing payload at this boundary is the construction of the fiber-transport comparison itself, and for independently supplied lattice laws the proof that they are the fiber-transport lattice law, from the paper-native log-theta transport. The local analytic boundary is now connected directly to this constructed principal cover:

```
ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined
PrincipalValuationBallPointwiseConstructedLogShellMetricZero
ValuationBallExactSource.
```

This source carries the metric normalization  $\|x\|_v = \text{dist}(x, 0)$  and the two pointwise local transport laws between transported theta-region points and compact-open valuation balls, while the valuation-cover possible-region family is fixed definitionally by the principal source. Lean derives the realized valuation-ball equality, projects it to the theta-region-defined radius-cover source, obtains direct-product-cell exactness, and then feeds the principal exact- $\Xi$  source. Thus the remaining paper-side payload has been narrowed to the actual construction of the local analytic coordinate and the reverse valuation-ball realization law. The newest declaration

```
ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined
PrincipalValuationBallLocalChartMetricZeroValuationBallExactSource
```

replaces the forward existential lifting law by a named map  $x_\beta(y) \in K_v$ . Its fields assert the valuation-radius bound  $\|x_\beta(y)\|_v \leq r_\beta$ , the realization identity  $\text{real}_\beta(x_\beta(y)) = y$ , the metric normalization, and the reverse statement that each selected valuation-ball point realizes back into the transported theta region. Lean derives the pointwise lift, recovers the previous principal pointwise source, and hence recovers the exact realized valuation-ball identity and selected-principal-hull conclusion. This boundary has now been lowered to an image-backed log-shell source:

```
ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined
PrincipalValuationBallLogShellImageMetricZeroValuationBallExactSource.
```

Instead of supplying  $x_\beta(y)$  as chart data, it records the two containments

$$P_{\Theta, \beta} \subseteq \text{real}_\beta(I_\beta), \quad \text{real}_\beta(I_\beta) \subseteq P_{\Theta, \beta},$$

and the two containments identifying  $I_\beta$  with the compact-open valuation ball. Lean chooses  $x_\beta(y)$  from the first image containment, proves  $\text{real}_\beta(x_\beta(y)) = y$ , derives the radius bound from  $I_\beta \subseteq \{x :$

$\|x\|_v \leq r_\beta\}$ , and derives the reverse realization law from  $\{x : \|x\|_v \leq r_\beta\} \subseteq I_\beta$  together with the second image containment. The log-shell itself has now been lowered to the compact-open local shell:

```
ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined
PrincipalValuationBallCompactOpenLogShellImageMetricZero
ValuationBallExactSource.
```

Here  $I_\beta$  is definitionally the selected factor's compact-open subset. The equality between this compact-open subset and  $\{x : \|x\|_v \leq r_\beta\}$  is read from the valuation-ball additive Haar normalization audit, so the two log-shell/valuation-ball containments are no longer source fields. The preferred boundary has also been lowered once more to a compact-open local-chart source:

```
ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined
PrincipalValuationBallCompactOpenLocalChartMetricZero
ValuationBallExactSource.
```

This source gives compact-open representatives  $x_\beta(y) \in U_\beta$  for transported theta-region points and the converse law that every  $u \in U_\beta$  realizes back into  $P_{\Theta,\beta}$ . Using the valuation-ball additive Haar identity  $U_\beta = \{x : \|x\|_v \leq r_\beta\}$ , it now also constructs the pointwise valuation-ball source that feeds log-shell exactness. Using the local analytic identity  $\text{realizedRegion}(U_\beta) = \text{real}''_\beta U_\beta$ , Lean derives the two compact-open image containments

$$P_{\Theta,\beta} \subseteq \text{real}_\beta(U_\beta), \quad \text{real}_\beta(U_\beta) \subseteq P_{\Theta,\beta}$$

and then enters the source-derived global  $C_\Theta$  audit. The remaining frontier has now been lowered to the exact compact-open realized-region source

```
ConcreteValuationBallThetaClassFiberTransportThetaRegionDefined
PrincipalValuationBallCompactOpenRealizedExactSource.
```

Its local payload is the single identity

$$P_{\Theta,\beta} = \text{real}_\beta(U_\beta).$$

From this equality and  $\text{realizedRegion}(U_\beta) = \text{real}''_\beta U_\beta$ , Lean chooses compact-open coordinates, proves the converse realization law, recovers the compact-open local-chart source, and enters the same global  $C_\Theta$  audit. This compact-open boundary is now itself a projection from the valuation-ball realized-exact source: if

$$P_{\Theta,\beta} = \text{realizedRegion}\{x : \|x\|_v \leq r_\beta\},$$

then the valuation-ball additive Haar audit identifies the selected compact-open subset  $U_\beta$  with this closed ball, and Lean derives the compact-open realized source. The equality-backed log-shell package is also now recovered from local containments. On the compact-open branch, the two image containments

$$P_{\Theta,\beta} \subseteq \text{realizedRegion}(U_\beta), \quad \text{realizedRegion}(U_\beta) \subseteq P_{\Theta,\beta}$$

already construct the compact-open realized-exact source by antisymmetry, so the preferred  $C_\Theta$  audit no longer has to pass through an arbitrary log-shell equality package. The more general log-shell source is still recovered from the four containments

$$P_{\Theta,\beta} \subseteq \text{realizedRegion}(I_\beta), \quad \text{realizedRegion}(I_\beta) \subseteq P_{\Theta,\beta}, \quad I_\beta \subseteq B_\beta(r_\beta), \quad B_\beta(r_\beta) \subseteq I_\beta,$$

so the source need not assert these set equalities at the first boundary. The compact-open local-chart boundary has also been lowered through a log-Kummer graph formulation. First, a graph source may supply a local realization relation on  $U_\beta \times P_{\Theta,\beta}$ ; left-totality, realization compatibility, and right-soundness recover compact-open coordinates. Second, and more canonically, the compact-open image source now defines this relation to be the graph of the selected realization map

$$x \sim_\beta y \iff \text{real}_\beta(x) = y.$$

The two image containments then prove the graph laws. Thus the local log-Kummer graph is no longer an independent payload at this boundary. The graph source also constructs the pointwise local valuation-ball source: compact-open graph lifts are converted to valuation-radius lifts by the additive Haar normalization, and right-soundness gives the converse valuation-ball realization law. Thus the graph route can now pass through pointwise local construction, log-shell exactness, compact-open image compatibility, and finally the global  $C_\Theta$  audit. The containments themselves were first lowered to the valuation-cover side by the single equality

$$P_{\text{cover}}(\Theta_\beta) = \text{realizedRegion}(U_\beta),$$

where  $P_{\text{cover}}$  is the Remark 3.9.5 valuation-cover possible region. Since the principal cover is constructed with  $P_{\text{cover}}(\Theta) = P_\Theta$ , Lean rewrites this equality to derive both compact-open image containments, the realized-exact source, and the canonical graph route. This equality is now itself derived from a local log-Kummer image source: every point of  $P_{\text{cover}}(\Theta_\beta)$  has a lift in  $U_\beta$ , and every point of  $U_\beta$  realizes back into  $P_{\text{cover}}(\Theta_\beta)$ . That image source now constructs the map-level local log-Kummer source. Lean takes the local Kummer realization map to be the selected valuation-factor realization

$$\kappa_\beta : K_\beta \longrightarrow \text{Pt}(\mathbb{L}_\Theta),$$

and chooses a section of  $\kappa_\beta$  over the selected Remark 3.9.5 possible region from canonical graph left-totality. It then defines the local correspondence as the graph of  $\kappa_\beta$ , derives realization compatibility, compact-open soundness, the image source, cover exactness, and the global  $C_\Theta$  audit. Since the principal cover has  $P_{\text{cover}}(\Theta_\beta) = P_{\Theta,\beta}$  definitionally, the same map source now also lowers to the theta-region graph source and hence through the pointwise valuation-ball, log-shell exact, compact-open image route before the global  $C_\Theta$  audit. The compact-open image laws are now also downstream of a log-shell exact source: the two equalities

$$P_{\Theta,\beta} = \text{real}_\beta(L_\beta), \quad L_\beta = U_\beta$$

construct the compact-open route using the valuation-ball Haar normalization. These equalities are no longer only accepted as an exact source: the pointwise local construction, which supplies a local representative of each theta-region point and the converse realization law for the compact-open valuation ball, constructs the exact source. Those pointwise laws are now themselves constructed from compact-open local-chart data, and the compact-open log-Kummer graph source projects to that local-chart boundary. The remaining frontier is the construction of the graph/local-chart laws from the paper-native holomorphic hull, log-Kummer, and local log-shell geometry. There is now also an `ofHullSystem` constructor and experiment endpoint: starting from the intersection-defined hull system and a family  $\{P_\beta\}$ , Lean constructs the possible-image source and proves that the canonical hull is precisely the system's  $\phi(\bigcup_\beta P_\beta)$ , which is a hull by the intersection-closure input. Thus the Ob5 quotient collapse for possible images is already downstream of the minimal-hull construction, not merely of a supplied  $\phi$ -operator. The product-hull source now has a direct-product constructor as well: `IUTStage1Remark395DirectProductHullSystemSource` defines product hulls as coordinate

products, defines the selected hull parameter by coordinate projections of the region, and proves the “smallest product hull” equality before projecting to the existing product-hull and holomorphic-hull systems. The determinant side now has a source-facing Ob3/Ob4 package as well:

`IUTStage1Remark3950b30b4AdjustedDeterminantSource.`

It records localization summands, the structure-sheaf adjustment  $O(-)$ , weighted adjusted log-volumes, the positive tensor power  $M$ , and the normalized determinant log-volume before projecting to the older weighted determinant skeleton. The experiment-surface theorem

`Iut.Stage1.Experiments.remark3950b30b4AdjustedDeterminantSource  
_endpoint`

checks the adjusted-summand formula, determinant summation, tensor-power formula, and normalized determinant equality. The constructed Step (xi) source also has a constructor `ofOb30b4AdjustedDeterminantSource` whose endpoint verifies that this source-facing Ob3/Ob4 package is the determinant source used by the existing hull/determinant corridor. This determinant package now has a lower source-facing constructor layer. The new objects

`IUTStage1LocalizedArithmeticVectorBundle,  
IUTStage1StructureSheafAdjustedLocalizedVectorBundleSource,  
IUTStage1Remark3950b30b4LocalizedVectorBundleDeterminantSource`

separate the local-ring-labelled vector-bundle localization of Step (xi-d) from the later  $O(-)$  structure-sheaf adjustment and determinant/tensor-power normalization. Their experiment endpoints prove that the localized rank- $> 1$  direct-summand log-volume projects to the adjusted localization source, and that the resulting Ob3/Ob4 determinant source has the same weighted summand formula and normalized determinant equality as the older adjusted determinant package. The Ob3/Ob5 determinant-compatibility input has also been separated from the low-level certificate:

`IUTStage1Remark3950b30b5DeterminantCompatibilitySource.`

This object states, at the possible-image-family level, that  $\mu_{\log}(\phi(P_B))$  is the normalized weighted-determinant log-volume. Lean derives the older `IUTStage1HullApproximantWeightedDeterminantCompatibility` certificate from this equality and then derives the ordinary determinant equality from the Ob3/Ob4 normalization theorem. The record-canonical Step (xi) specialization `IUTStage1Remark395RecordOb30b5DeterminantCompatibilitySource` fixes  $P_B$  to the Theorem 3.11 possible-image family. Both the generic and record-canonical Ob3/Ob5 source objects now project to the bounded-family hull/determinant source used by the downstream exact-theta Step (xi) routes: the endpoints `remark3950b30b5DeterminantCompatibilitySource_boundedFamilyEndpoint` and `remark395RecordOb30b5DeterminantCompatibilitySource_boundedFamilyEndpoint` verify the family union, canonical hull, determinant log-volume equality, and normalized tensor-power equality after this projection. The generic bridge from Ob3/Ob5 compatibility to the Step (xi) log-volume chain now also has an exact-theta constructor:

`remark395HullDeterminantBridgeSource  
_ofOb30b5CompatibilitySourceOfThetaEqFamilyHullLogVolume  
_endpoint.`

This route no longer takes the Ob4 tensor-power bound as an independent input. Given  $q \subseteq \bigcup_{\beta} P_{\beta}$  and the source calibration  $\theta_{\text{signed}} = \mu_{\log}(\phi(P_B))$ , Lean derives the tensor-power bound from the bounded-family hull/determinant source and then proves

$$\mu_{\log}(q) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}.$$

The record-canonical Ob3/Ob5 source now also has a public constructor endpoint from the Ob3/Ob4 adjusted determinant source. Given the remaining source-facing equality

$$\mu_{\log}(\phi(P_B)) = \det_{\text{norm}}(P_B),$$

Lean constructs the record Ob3/Ob5 compatibility object, projects the Ob3/Ob4 localization-summand and tensor-power formulas, derives equality with the ordinary determinant log-volume, and then projects the resulting object to the bounded-family Ob5 hull source. The experiment surface exposes this as

```
remark395RecordOb3Ob5DeterminantCompatibilitySource
  _ofAdjustedDeterminantSource_endpoint.
```

The remaining equality has now been pushed one level closer to Remark 3.9.5, (vii), (Ob3-1)–(Ob3-3). The new source-core object

```
IUTStage1Remark395Ob3Ob5DeterminantCompatibilitySource
  .IUTStage1Remark395Ob3Ob5AdjustedDeterminantLogVolumeSource
```

does not assume equality with the normalized determinant directly. Instead it records the finite Ob3-3 summand formula

$$\mu_{\log}(\phi(P_B)) = \sum_{\beta} \text{adj}_{\beta},$$

where the summands are the Ob3/Ob4 structure-sheaf-adjusted localization contributions. Lean then derives equality with the determinant log-volume and with the normalized determinant log-volume from the adjusted determinant source. The record-canonical specialization fixes  $P_B$  to the Theorem 3.11 possible-image family and exposes

```
remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
  _endpoint.
```

Thus the current open analytic/log-volume input is no longer  $\mu_{\log}(\phi(P_B)) = \det_{\text{norm}}$  as a monolithic assertion, but the more source-facing finite summand identity  $\mu_{\log}(\phi(P_B)) = \sum_{\beta} \text{adj}_{\beta}$ . This identity can now also be stated at the localized vector-bundle level: the constructor

```
IUTStage1Remark395Ob3Ob5AdjustedDeterminantLogVolumeSource
  .ofLocalizedVectorBundleDeterminantSource
```

takes the equality with the sum of local-ring-labelled adjusted vector-bundle summands and derives the adjusted determinant source, determinant log-volume equality, and normalized Ob3/Ob5 compatibility from it. The equality with the localized adjusted sum has now been factored once more. The source declaration

```
IUTStage1Remark395LocalizedHullVectorBundle
  DecompositionSource
```

records a finite decomposition of the canonical family hull into localized hull-regions together with two source-facing facts: the hull log-volume is the sum of these localized region log-volumes, and each localized region log-volume is the corresponding adjusted localized vector-bundle summand. Lean derives the Ob3-3 summand identity from these two facts and then constructs the same Ob3/Ob5 adjusted determinant log-volume source. The localized-region containment has now been pushed one level lower. The source declaration

**IUTStage1Remark395LocalizedHullCover  
VectorBundleSource**

starts from the intersection-defined Remark 3.9.5 hull system and a finite cover

$$\phi(P_B) = \bigcup_{\beta} H_{\beta}$$

by localized hull-regions. From this cover identity, Lean proves  $H_{\beta} \subseteq \phi(P_B)$  for each  $\beta$ , derives the family-hull log-volume sum from the supplied cover-additivity theorem, and then constructs the localized hull/vector-bundle decomposition source described above. The pointwise summand calibration has now been factored as well. A local source object

**IUTStage1LocalizedHullRegion  
VectorBundleCalibrationSource**

attaches a single localized hull-region  $H_{\beta}$  to its structure-sheaf-adjusted localized arithmetic vector bundle and records the source equality

$$\mu_{\log}(H_{\beta}) = w_{\beta} \cdot (L_{\beta, \text{bundle}} - L_{\beta, \mathcal{O}(-)}).$$

Lean then identifies the right hand side with the weighted adjusted localized vector-bundle summand. The aggregate declaration

**IUTStage1Remark395CalibratedLocalized  
HullCoverVectorBundleSource**

assembles these calibrated local objects, constructs the finite localized determinant source from them, and then projects to the localized hull-cover source. Thus the cover-level pointwise equality  $\mu_{\log}(H_{\beta}) = \text{adj}_{\beta}$  is no longer a bare field. The finite cover-additivity input has also been separated from this aggregate object. The declaration

**IUTStage1FiniteAdditiveHullLogVolumeSource**

records the source-paper law that a finite pairwise-disjoint family of localized hull-regions satisfies

$$\mu_{\log}\left(\bigcup_{\beta} H_{\beta}\right) = \sum_{\beta} \mu_{\log}(H_{\beta}).$$

The refined aggregate source

**IUTStage1Remark395FiniteAdditive  
CalibratedLocalizedHullCoverVectorBundleSource**

assumes pairwise disjointness of the localized regions and this finite additivity law, then derives the exact cover-sum equality consumed by the calibrated cover source. The pairwise-disjointness input has now been pushed one level lower as well. The source declaration

**IUTStage1LocalizedHullRegionOwnershipSource**

records a single owner map from hull points to optional localized indices and states that each localized hull-region is the corresponding owner fiber. From this fiber description Lean proves pairwise disjointness of distinct localized regions. The aggregate declaration

**IUTStage1Remark395OwnedFiniteAdditive  
CalibratedLocalizedHullCoverVectorBundleSource**

therefore constructs the finite-additive calibrated cover source without taking localized-region disjointness as a bare field. The cover identity itself has now been factored through the same owner map. The declaration

**IUTStage1Remark395OwnerTotalFiniteAdditive  
CalibratedLocalizedHullCoverVectorBundleSource**

assumes that every point of the family hull  $\phi(P_B)$  has a localized owner and that each owner fiber remains inside  $\phi(P_B)$ . Together with the fiber description of  $H_\beta$ , Lean derives  $\phi(P_B) = \bigcup_\beta H_\beta$  and then projects to the owner-fiber finite-additive cover route. The owner map itself has now been constructed from a lower family-hull indexed source. The declaration

**IUTStage1Remark395FamilyHullIndexedFiniteAdditive  
CalibratedLocalizedHullCoverVectorBundleSource**

takes as primitive data an index function on the subtype of points of  $\phi(P_B)$ , together with the assertion that  $H_\beta$  is the corresponding index fiber. Lean defines the ambient owner map to be this index on  $\phi(P_B)$  and **none** off  $\phi(P_B)$ , then derives owner-totality, fiber containment in  $\phi(P_B)$ , and the owner-total cover source. The indexing source has now been pushed down to a direct-product localization source. The declaration

**IUTStage1Remark395DirectProduct  
LocalizedHullCoverVectorBundleSource**

represents  $H_\beta$  as the finite direct-product cell cut out by all local factor regions at the localization places. Its separation hypothesis is local: two distinct indices are separated by at least one disjoint local factor. From this Lean proves pairwise disjointness of the direct-product cells, uses the cover equality

$$\phi(P_B) = \bigcup_\beta H_\beta$$

to choose the unique cell containing a hull point, and then constructs the family-hull indexed source rather than taking the index map as primitive. The finite-additivity boundary has also been localized to this same direct-product cover. The declaration

**IUTStage1Remark395DirectProductAdditive  
LocalizedHullCoverVectorBundleSource**

does not assume a universal finite-additive law for arbitrary region families. Instead it records the cover-specific Step (xi) equality

$$\mu_{\log}\left(\bigcup_{\beta} H_{\beta}\right) = \sum_{\beta} \mu_{\log}(H_{\beta})$$

for the direct-product localization cells. Lean transports this equality across the identification of  $H_{\beta}$  with the calibrated localized regions, derives the calibrated cover source, and proves  $\mu_{\log}(\phi(P_B))$  equals the sum of the adjusted Ob3/Ob4 localization summands. This cover-specific equality has now been derived from a lower finite local-factor volume source. The declaration

**IUTStage1Remark395LocalFactorVolume**  
**DirectProductLocalizedHullCoverVectorBundleSource**

assigns a log-volume contribution to each local factor of each direct-product cell. Its source laws compute

$$\mu_{\log}(H_{\beta}) = \sum_v \mu_{\beta,v}, \quad \mu_{\log}\left(\bigcup_{\beta} H_{\beta}\right) = \sum_{\beta} \sum_v \mu_{\beta,v}.$$

Lean then derives the direct-product cover additivity by finite-sum congruence and projects to the cover-specific additive source. Thus the previous cover-additivity assumption is now reduced to the local-factor log-volume computation for the localized arithmetic-vector-bundle cells. The local-factor volumes are now also tied to the Ob3 vector-bundle data. The declaration

**IUTStage1Remark395VectorBundleLocalFactor**  
**DirectProductLocalizedHullCoverSource**

defines the local factor  $\mu_{\beta,v}$  to be the direct-summand log-volume of the localized arithmetic vector bundle attached to  $\beta$  at the place  $v$ . Its source laws compute each  $H_{\beta}$  from the associated bundle log-volume and compute the cover from the resulting finite bundle sum. Lean then derives the previous local-factor source and proves that the local-factor sum agrees with the weighted adjusted Ob3/Ob4 summand already used by the determinant package. Thus the local-factor layer is no longer an independent real-valued family; it is read from the localized vector-bundle summands. The factor regions themselves have now been pushed down one more source layer. The declaration

**IUTStage1Remark395LocalRingChartedVectorBundle**  
**DirectProductHullCoverSource**

introduces a local-ring chart for each factor of each direct-product localization cell. The chart records the local-ring label and the region that represents the corresponding local factor. Its source laws identify the chart local ring with the local-ring label of the localized arithmetic vector bundle, identify each chart log-volume with the associated direct-summand log-volume, compute each  $H_{\beta}$  as the sum of these chart-factor log-volumes, and compute the cover as the finite sum of charted cell log-volumes. Lean then derives the vector-bundle local-factor source. Thus the regions entering the direct-product cover are no longer an arbitrary family parallel to the bundle data; they are read from local-ring localization charts tied to the same localized vector bundles. The chart/bundle matching has also been isolated at the individual factor level. The new

**IUTStage1LocalRingVectorBundleFactorCalibrationSource**



records, for a fixed  $(\beta, v)$ , that the chart lies over the same local ring as the localized arithmetic vector bundle and that the chart region's log-volume is the corresponding direct-summand log-volume. The aggregate

**IUTStage1Remark395CalibratedLocalRingCharted  
VectorBundleHullCoverSource**

then builds the previous charted direct-product source from these per-factor calibrations, together with the remaining cell factorization and cover additivity laws. This separates the local-ring/direct-summand calibration obligation from the finite direct-product geometry obligation. The cover additivity law has now been separated from the calibrated charted source as well. The declaration

**IUTStage1Remark395FiniteAdditiveCalibrated  
LocalRingChartedVectorBundleHullCoverSource**

keeps the same per-factor calibrations and cell-factorization law, but replaces the charted cover log-volume equality by a finite-additive hull log-volume source. Distinct direct-product cells are proved disjoint from the local-factor separation condition, and Lean applies finite additivity to derive

$$\mu_{\log} \left( \bigcup_{\beta} H_{\beta} \right) = \sum_{\beta} \mu_{\log}(H_{\beta}).$$

Thus the cover equality consumed by the charted vector-bundle route is no longer an independent field of that route. The per-cell direct-product equality has now been factored as well. The new source declaration

**IUTStage1DirectProductCellLogVolumeSource**

records the Step (xi-d) tensor/direct-product log-volume law for one finite localization cell:

$$\mu_{\log} \left( \bigcap_v H_{\beta, v} \right) = \sum_v \mu_{\log}(H_{\beta, v}).$$

The aggregate

**IUTStage1Remark395ProductLogVolumeFiniteAdditive  
CalibratedLocalRingChartedVectorBundleHullCoverSource**

therefore no longer takes the cell-factorization equality as a bare field. It derives the equality for each  $H_{\beta}$  from the single-cell product log-volume source, proves disjointness from local-factor separation, applies finite additivity to the direct-product cover, and then projects to the previous finite-additive charted source. This source has now been lowered once more to a tensor/direct-sum datum for the actual charted cells. The declaration

**IUTStage1FiniteTensorDirectSumLogVolumeSource**

records a finite tensor-product region, its identification with the corresponding direct-product cell, the local factor log-volumes, and the finite direct-sum formula for the tensor-product log-volume. From these data, Lean derives the single-cell law

$$\mu_{\log}(H_{\beta}) = \sum_v \mu_{\log}(H_{\beta, v}).$$

The aggregate

**IUTStage1Remark395TensorPacketFiniteAdditive  
CalibratedLocalRingChartedVectorBundleHullCoverSource**

assigns such a tensor/direct-sum source to each charted localization cell, derives the cell log-volume equalities, proves the same pairwise-disjoint cover additivity, and projects to the finite-additive calibrated charted cover source. The tensor-cell source has now been lowered to compact-open local factor data. The declaration

**IUTStage1LocalCompactOpenTensorFactorSource**

records the local ring label, compact-open local factor region, and normalized local log-volume for one nonarchimedean tensor factor. A second declaration,

**IUTStage1CompactOpenTensorRegionDirectSumSource**

records the tensor-product region obtained from a finite family of these compact-open factors, identifies it with the simultaneous local-factor cell, and proves the finite direct-sum log-volume formula. Lean then constructs **IUTStage1FiniteTensorDirectSumLogVolumeSource** from this compact-open direct-sum datum, including the chart-region transport needed when the compact-open factor regions are identified with the already charted local factor regions. At the packet level,

**IUTStage1Remark395CompactOpenTensorPacketFiniteAdditive  
CalibratedLocalRingChartedVectorBundleHullCoverSource**

requires one such compact-open tensor direct-sum construction for each charted localization cell, proves that the compact-open factor regions and local-ring labels match the charted local factors, constructs the tensor-packet source, and then derives the same finite-additive cover equality and bundle-log-volume projection. The compact-open tensor factor source has now been lowered to a nonarchimedean local normalized log-volume datum. The declaration

**IUTStage1NonarchimedeanLocalCompactOpenLogVolumeSource**

records a local carrier, local-ring label, residue prime, finite-extension degree, integral structure, compact-open subset, uniformizer-scaled subset, and their realization as regions in the current real-line copy. It includes the IUT IV Proposition 1.4 normalization laws needed in the present corridor: the integral structure has normalized log-volume zero, the normalized log-volume is the degree-normalized raw log-volume, and multiplication by a uniformizer shifts the normalized log-volume by  $-\log(p)$ . Lean constructs **IUTStage1LocalCompactOpenTensorFactorSource** from this datum. The finite direct-sum layer

**IUTStage1NonarchimedeanLocalTensorRegionDirectSumSource**

then constructs the compact-open tensor-region source from a finite family of these local nonarchimedean sources and the direct-sum tensor-region formula. Finally,

**IUTStage1Remark395NonarchimedeanLocalTensorPacketFiniteAdditive  
CalibratedLocalRingChartedVectorBundleHullCoverSource**

uses one such local tensor source for each charted localization cell, verifies the local compact-open regions and local-ring labels against the charted factors, constructs the compact-open tensor-packet source, and inherits the finite-additive cover and bundle-log-volume conclusions. The local

nonarchimedean source has now been lowered once more to the finite-extension Haar normalization boundary of IUT IV, Proposition 1.4. The declaration

**IUTStage1FiniteExtensionHaarCompactOpenLogVolumeSource**

records the raw Haar/log-volume function on local compact-open subsets of a finite extension of  $\mathbb{Q}_p$ , its degree-normalized version, the realization of local subsets as real-line regions, the integral structure  $\mathcal{O}_K$ , and the uniformizer-scaled compact-open subset. Its endpoint checks the source-paper normalizations

$$\mu_{\log}(\mathcal{O}_K) = 0, \quad \mu_{\log}(p \cdot U) = \mu_{\log}(U) - \log(p),$$

and constructs **IUTStage1NonarchimedeanLocalCompactOpenLogVolumeSource**. The declaration

**IUTStage1FiniteExtensionTensorProductDirectSumDecompositionSource**

records the IUT IV direct-sum decomposition step for finite tensor products over  $\mathbb{Z}_p$ : the tensor-product region is identified with the simultaneous local compact-open cell, and its normalized log-volume is the finite sum of the degree-normalized Haar log-volumes of the direct summands. This source constructs the nonarchimedean local tensor-region direct-sum source. At the packet level,

**IUTStage1Remark395FiniteExtensionHaarTensorPacketFiniteAdditive  
CalibratedLocalRingChartedVectorBundleHullCoverSource**

assigns such a finite-extension Haar tensor decomposition to each charted localization cell and then constructs the nonarchimedean local tensor-packet source used by the Step (xi) cover route. The finite-extension Haar source has now been lowered to compact-open topology provenance. The declaration

**IUTStage1FiniteExtensionCompactOpenTopologyHaarNormalizationSource**

records the compact-open predicate on the local carrier, closure of compact-opens under finite intersections, the ring-of-integers compact-open, the chosen compact-open subset, a uniformizer action preserving compact-opens, the raw Haar measure, and the raw and degree-normalized Haar log-volume functions. Its endpoint verifies compact-open provenance for  $\mathcal{O}_K$ ,  $U$ , and  $p \cdot U$ , checks  $\log(\mu_{\text{Haar}}(U))$  at the raw level, and constructs **IUTStage1FiniteExtensionHaarCompactOpenLogVolumeSource**. The tensor layer

**IUTStage1CompactOpenTopologyTensorProductDirectSumSource**

constructs the finite-extension tensor-product direct-sum source from these compact-open topology factors. Finally,

**IUTStage1Remark395CompactOpenTopologyHaarTensorPacketFiniteAdditive  
CalibratedLocalRingChartedVectorBundleHullCoverSource**

feeds compact-open topology/Haar normalization data for each charted cell into the finite-extension Haar tensor-packet source and hence into the same finite-additive Step (xi) cover route. The local compact-open topology source has also been lowered one step further to a Haar-measure-backed source. The declaration

**IUTStage1AdditiveHaarCompactOpenNormalizationSource**

uses `mathlib`'s additive Haar-measure class on the local additive carrier, records openness and compactness for the ring of integers and selected compact-open subset, normalizes the ring of integers to Haar mass 1, and records the finite-extension uniformizer scaling law for real Haar mass. Lean then derives the raw logarithmic shift by  $-[K : \mathbb{Q}_p] \log(p)$ , divides by the finite-extension degree, and obtains the normalized IUT IV shift  $\mu_{\log}(pU) = \mu_{\log}(U) - \log(p)$ . The companion declaration

`IUTStage1AdditiveHaarTensorProductDirectSumSource`

feeds these Haar-backed local factors into the compact-open tensor/direct-sum source, so the tensor summation layer now has a route whose local inputs are actual additive Haar measures rather than arbitrary real-valued Haar functions. There is now a valuation-ball refinement below this Haar source. The declaration

`IUTStage1ProperUltrametricValuationBallTopologySource`

now starts from a proper ultrametric metric topology on the local additive carrier. The ultrametric inequality proves openness of positive-radius closed balls, while properness supplies compactness by the closed-ball compactness theorem. Thus the compact-open valuation-ball theorem is constructed from two recognizable local topological hypotheses rather than from separate open/compact fields. The companion declaration

`IUTStage1ProperUltrametricValuationBallAdditiveHaarNormalizationSource`

feeds this proper-ultrametric source into the ultrametric Haar route. The local ring input has also been sharpened from an abstract unit-ball label to the valued-field integer subring supplied by `mathlib`. The declaration

`IUTStage1ValuedFieldIntegerUnitBallSource`

works over a nontrivially normed ultrametric field and uses `Valued.integer.mem_iff` to prove

$$\mathcal{O}_K = \{x \mid \|x\| \leq 1\} = \overline{B}(0, 1).$$

It then identifies this valued-field integer subring with the radius-one ball in the proper-ultrametric valuation-ball topology. The companion declaration

`IUTStage1ValuedFieldIntegerProperUltrametric  
HaarNormalizationSource`

uses  $\mathcal{O}_K$  itself as the local-ring label and transports the Haar mass-one normalization from  $\mathcal{O}_K$  to the radius-one valuation ball before projecting into the proper-ultrametric Haar normalization route. There is now a base local-field specialization of this statement. The declaration

`IUTStage1PadicIntegerUnitBallSource`

works over  $\mathbb{Q}_p$ , identifies  $\mathcal{O}_{\mathbb{Q}_p}$  with `PadicInt.subring p`, and proves that its underlying set is the image of the coercion  $\mathbb{Z}_p \hookrightarrow \mathbb{Q}_p$ . This also records the local-ring instance on  $\mathbb{Z}_p$ , so the ring-of-integers object is no longer only the abstract valued-field subring. The base residue quotient has now also been made concrete. The declaration

`IUTStage1PadicIntegerResidueQuotientSource`

uses the mathlib reduction map  $\text{PadicInt.toZMod} : \mathbb{Z}_p \rightarrow \mathbb{Z}/p\mathbb{Z}$ , proves that its additive kernel is the maximal ideal of  $\mathbb{Z}_p$ , and applies the first isomorphism theorem to identify

$$\mathbb{Z}_p / \ker(\text{toZMod}) \simeq_{\text{add}} \mathbb{Z}/p\mathbb{Z}.$$

Transporting the  $\mathbb{Z}/p\mathbb{Z}$ -vector-space structure across this additive equivalence gives a one-dimensional residue module, and Lean proves

$$\#(\mathbb{Z}_p / \ker(\text{toZMod})) = p = p^{\text{finrank}_{\mathbb{Q}_p} \mathbb{Q}_p}.$$

The same source now also constructs

$$\text{Fin}(p^{[\mathbb{Q}_p:\mathbb{Q}_p]}) \simeq \mathbb{Z}_p / \ker(\text{toZMod})$$

and finite-index representatives whose quotient classes are definitionally the indexed residue classes. This upgrades the base-field residue quotient from a cardinality result to the representative data needed by the coset partition layer, without a supplied finite quotient equivalence. This has now been threaded into the base local coset/Haar boundary. The declaration

**IUTStage1PadicBaseFieldResidueQuotientDilationCoset  
HaarCharacterNormalizationSource**

constructs the additive equivalence

$$\mathbb{Z}_p \simeq_{\text{add}} \mathcal{O}_{\mathbb{Q}_p},$$

proves that the transported  $\ker(\text{toZMod})$  is exactly the subgroup  $p\mathcal{O}_{\mathbb{Q}_p}$ , applies the first isomorphism theorem to build

$$\mathcal{O}_{\mathbb{Q}_p} / p\mathcal{O}_{\mathbb{Q}_p} \simeq_{\text{add}} \mathbb{Z}_p / \ker(\text{toZMod}),$$

and then supplies the finite quotient equivalence and representatives consumed by the quotient-coset partition/Haar-character source. Thus the base-field coset decomposition used to derive  $\mu(p\mathcal{O}_{\mathbb{Q}_p}) = p^{-1}$  now starts from the concrete  $\text{PadicInt.toZMod}$  residue quotient rather than from a supplied quotient package. The companion declaration

**IUTStage1PadicProperUltrametricHaarNormalizationSource**

fixes the residue prime to  $p$ , the finite-extension degree to 1, and the uniformizer scale map to  $x \mapsto px$ , then projects to the valued-field integer Haar route. The Haar mass-one and  $p$ -scaling law are still carried as analytic local-field inputs, but their ambient field, local ring, residue prime, degree, and uniformizer map are now the actual  $p$ -adic ones. This base local-field source now also projects into the finite-extension Haar boundary itself by viewing  $\mathbb{Q}_p/\mathbb{Q}_p$  as a finite extension. Lean constructs

**IUTStage1PadicProperUltrametricHaarNormalizationSource.  
toPadicFiniteExtensionProperUltrametricHaarNormalizationSource**

and proves that its valued-field integer projection agrees with the direct  $\mathbb{Q}_p$  valued-field Haar source. Thus the finite-extension degree appearing in the normalization is not an independent parameter at the base place: it is  $\text{finrank}_{\mathbb{Q}_p}(\mathbb{Q}_p) = 1$ , with the same base-prime dilation  $x \mapsto px$ . The declaration

**IUTStage1UltrametricValuationBallTopologySource**

starts from an ultrametric metric topology on the local additive carrier and proves that every positive-radius closed valuation ball  $\{x \mid d(x, 0) \leq r\}$ ,  $r > 0$ , is open. It still carries compactness of these balls as the local compactness/properness input, but the openness part of the compact-open assertion is now derived from the nonarchimedean triangle inequality rather than supplied independently. The companion declaration

**IUTStage1UltrametricValuationBallAdditiveHaarNormalizationSource**

projects this ultrametric source into the positive-radius topology-backed Haar route. The declaration

**IUTStage1PositiveRadiusValuationBallTopologySource**

isolates the local-field topological theorem that every positive-radius valuation ball  $\{x \mid \|x\|_v \leq r\}$ ,  $r > 0$ , is compact-open. The topology-backed declaration

**IUTStage1ValuationBallTopologyAdditiveHaarNormalizationSource**

then derives the unit ball and selected ball compact-open predicates from this single positive-radius theorem before projecting to the older additive Haar normalization route. Thus the source boundary has moved from four separate open/compact fields for two balls to one uniform valuation-ball compact-open theorem. The declaration

**IUTStage1ValuationBallAdditiveHaarNormalizationSource**

records a nonarchimedean valuation-norm function on the local carrier and defines the ring of integers as the unit ball  $\{x \mid \|x\|_v \leq 1\}$ . The selected local compact-open subset is likewise a valuation ball  $\{x \mid \|x\|_v \leq r\}$  for a positive radius  $r$ , and the uniformizer operation is the image under a pointwise scale map. Lean derives the compact-open predicate as **IsOpen**  $\wedge$  **IsCompact**, proves closure under finite intersections in a  $T_2$  space, and constructs the additive Haar normalization source from the valuation-ball data. The companion tensor source

**IUTStage1ValuationBallTensorProductDirectSumSource**

feeds valuation-ball local factors into the additive Haar tensor/direct-sum source. The valuation-ball route now also reaches the charted Step (xi) cover boundary itself. The new declaration

**IUTStage1Remark395ValuationBallHaarTensorPacketFiniteAdditive  
CalibratedLocalRingChartedVectorBundleHullCoverSource**

assigns to each charted localization cell a valuation-ball tensor/direct-sum source, proves that every local charted region and local-ring label is realized by the corresponding valuation-ball factor, and then constructs the existing compact-open topology/Haar tensor-packet cover source. Its endpoint exposes the valuation-ball identities for  $\mathcal{O}_K$  and  $U$ , compact-openness of the selected valuation balls, the finite direct-product cell log-volume formula, the finite-additive cover sum, and the inherited bundle-log-volume projection. Thus the current IUT IV local-volume corridor now proceeds from valuation balls to additive Haar normalization, then to compact-open topology, finite-extension Haar log-volume, tensor/direct-sum summation, and finally the charted Step (xi) cover route. The local chart calibration in this valuation-ball route has now been pushed down another level. The per-factor declaration

**IUTStage1ValuationBallVectorBundleFactorCalibrationSource**

constructs the local-ring chart from a valuation-ball Haar factor itself: the chart local ring is the valuation-ball factor's local ring, and the chart region is the realized selected valuation ball. Its source law identifies the localized vector-bundle direct summand with the normalized Haar log-volume of that valuation ball, after which Lean derives the ordinary chart/direct-summand calibration source. The packet-level declaration

```
IUTStage1Remark395ValuationBallFactorCalibratedHaarTensorPacket
  FiniteAdditiveCalibratedLocalRingChartedVectorBundleHullCoverSource
```

uses these per-factor valuation-ball calibrations to build the previous valuation-ball charted-cover source. Thus the factor chart is no longer a separate object merely matched to valuation-ball data; at this boundary it is constructed from the valuation-ball compact-open region. This same factor-calibrated valuation-ball source now also projects into the newer finite-cover-additive/tensor-measure-backed cover corridor. The projection uses the broad finite-additive law only to construct the selected family-local finite-cover certificate, then Lean derives the tensor-cell cover sum

$$\mu_{\log}\left(\bigcup_{\beta} H_{\beta}\right) = \sum_{\beta} \mu_{\log}^{\text{tensor}}(H_{\beta})$$

and reads the adjusted Ob3/Ob5 determinant equalities from that constructed finite-cover source. This connects the valuation-ball Haar factor route to the current narrower cover-audit path without treating the tensor-cover theorem as an independent payload. The record-canonical valuation-ball handoff has also been tightened at the source-core boundary. The theorem

```
IUTStage1Remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
  .ofValuationBallFactorCalibratedHaarTensorPacketFiniteAdditive
  CalibratedLocalRingChartedVectorBundleHullCoverSource
  _toSourceCoreAdjustedLogVolumeSource_eq
```

proves that, once the valuation-ball possible-image family is synchronized with the Theorem 3.11 record family, the record-canonical Ob3/Ob5 source forgets back to exactly the valuation-ball adjusted determinant log-volume source. Downstream principal valuation-ball finite-divisor sources can therefore use this equality as a derived synchronization, rather than carrying the valuation-ball Ob3/Ob5 equality as an unrelated payload. This summand-calibrated source now feeds the milestone-facing constructed Step (xi) source directly. The new constructor

```
IUTStage1Remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
  .toConstructedHolomorphicHullDeterminantSource
```

first derives the record Ob3/Ob5 compatibility object from the finite summand formula, then uses that derived compatibility to build IUTStage1Remark395ConstructedHolomorphicHullDeterminantSource. The experiment endpoint

```
remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
  _toConstructedHolomorphicHullDeterminantSource_endpoint
```

returns the finite-summand equality, the determinant and normalized determinant identifications, and the chain

$$\mu_{\log}(q) \leq \det_{\log}(P_B) \leq \Theta_{\text{signed}},$$

so the constructed Step (xi) route no longer receives the canonical hull–determinant compatibility as an independent input in this constructor. This constructed-source layer now also has an exact-theta refinement,

```
IUTStage1Remark395RecordOb30b5AdjustedDeterminantLogVolumeSource
  .toConstructedHolomorphicHullDeterminantSource
  OfThetaEqFamilyHullLogVolume.
```

For an arbitrary q-region  $q \subseteq P_{\text{rec}}$  contained in the record possible-image union, this constructor derives the Ob4 normalized tensor-power bound from

$$\theta_{\text{signed}} = \mu_{\log}(\phi(P_B)),$$

using the bounded-family hull/determinant source projected from the Ob3/Ob5 compatibility. Its public endpoint records the exact-theta equality, the derived tensor-power inequality, the adjusted-summand-to-determinant identifications, the two-step hull/determinant chain, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . Thus the general constructed Step (xi) source has the same no-free-tensor-bound interface that was previously only available after choosing a possible-image q-region; the package measure calibration and the record-canonical bridge equality remain explicit source obligations. There is now also an obligations-backed form of this arbitrary-q exact-theta constructor,

```
IUTStage1Remark395RecordOb30b5AdjustedDeterminantLogVolumeSource
  .toConstructedHolomorphicHullDeterminantSource
  OfThetaEqFamilyHullLogVolumeFromObligations.
```

It projects the package hull/determinant bridge equality, q-pilot positivity, and source normalization from one `IUTStage1SourceHullDetObligations` object. The endpoint still exposes the synchronization identifying that obligations-backed bridge datum with the record-canonical Remark 3.9.5 hull/tensor-power construction for the chosen q-region. Thus, at the general constructed-source level, the remaining explicit inputs are the measure calibration, the exact-theta family-hull identity, q-containment in the record possible-image union, and this single bridge-synchronization statement. The measured Ob3/Ob5 adjusted source now removes that separate measure calibration input as well. Its constructor

```
IUTStage1MeasureCalibratedRemark395RecordOb30b5Adjusted
  DeterminantLogVolumeSource.toConstructedHolomorphicHull
  DeterminantSourceOfThetaEqFamilyHullLogVolumeFromObligations
```

projects the package measure equality from the measured family-hull source, derives the Ob4 tensor-power bound from  $\theta_{\text{signed}} = \mu_{\log}(\phi(P_B))$ , and keeps only the q-containment, exact-theta identity, obligations object, and record-canonical bridge synchronization as explicit parameters. There is also a selected-possible-image specialization,

```
IUTStage1MeasureCalibratedRemark395RecordOb30b5Adjusted
  DeterminantLogVolumeSource.toPossibleImageConstructed
  HolomorphicHullDeterminantSourceOfThetaEqFamilyHullLogVolume
  FromObligations.
```

Here the q-region is fixed to `recordThetaPossibleImage record qChoice`, and Lean derives its containment in the Theorem 3.11 possible-image union from the record’s choice-indexed union constructor rather than receiving a separate q-containment proof. The same summand source now also



feeds the constructor-built possible-image Step (xi) source used by the finite-divisor-facing corridor. The constructor

```
IUTStage1Remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
.toPossibleImageConstructorBuiltHolomorphicHullDeterminantSource
```

fixes the q-pilot region to a chosen Theorem 3.11 possible image, derives its record-union containment, derives the Ob3/Ob5 compatibility from the finite summand formula, and then builds `IUTStage1PossibleImageConstructorBuiltHolomorphicHullDeterminantSource`. Its experiment endpoint

```
remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
.toPossibleImageConstructorBuiltHolomorphicHullDeterminantSource_endpoint
```

therefore exposes the constructor-built source endpoint, the Step (xi) bridge-inequality audit, the derived compatibility object, and the summand-to-determinant equalities at one review boundary. This removes one more independent compatibility certificate from the public constructor-built route, although the package measure calibration and record-canonical hull/determinant bridge equality are still explicit inputs. The finite-summand source now also has an exact-theta family-hull constructor,

```
IUTStage1Remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
.toPossibleImageFamilyHullExactThetaHullDetObligationsBackedSource.
```

Here the record Ob3/Ob5 family hull is still derived from the adjusted-summand identity, but the Ob4 tensor-power bound used in the record-canonical Step (xi) bridge is no longer a separate route input. It is derived from the exact-theta source equality

$$\theta_{\text{signed}} = \mu_{\log}(\phi(P_B)).$$

The corresponding experiment endpoint exposes the selected possible-image q-region, the package hull/determinant bridge, q-positivity, normalization, the derived weighted determinant source, the adjusted-summand-to-determinant equalities, the derived tensor-power bound, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The measured adjusted-summand source

```
IUTStage1MeasureCalibratedRemark395RecordOb3Ob5
AdjustedDeterminantLogVolumeSource
```

packages the same finite Ob3–3 adjusted-summand construction together with the package measure equality for the derived record family hull. Its exact-theta endpoint first projects the measured family-hull source and then invokes the possible-image constructor above. Thus, in this route, the measure calibration  $\mu = \mu_{\log}(\phi(\cup_B P_B))$  is no longer a loose endpoint argument; it is part of the source-facing adjusted-summand object. This adjusted source is now threaded through the target-charted Hodge Step (xi) layer as well. The declarations

```
IUTStage1TargetChartedHodgeMeasureCalibrated
AdjustedSummandFamilyHullSource,
IUTStage1TargetChartedHodgeMeasureCalibrated
AdjustedPossibleImageHullDetObligationsBackedSource
```

project to the older measured determinant routes only internally. Their experiment endpoints keep the finite adjusted-summand identity

$$\mu_{\log}(\phi(P_B)) = \sum_{\gamma} (\text{localization}_{\gamma} - \text{structure sheaf}_{\gamma}) = \det_{\log}$$

visible next to the Hodge theta-degree calibration, the selected Theorem 3.11 possible-image q-region, and the obligations bridge equality. The adjusted-summand payload has also been moved into the constructor-backed Step (xi) route. The source

**IUTStage1TargetChartedHodgeConstructorBacked  
MeasureCalibratedAdjustedPossibleImageHullDetSource**

uses the record-canonical Theorem 3.11 hull/tensor-power constructor to generate the possible-image hull/determinant obligations, while its determinant input is projected from the measured adjusted-summand family-hull source. Its endpoint exposes, in one checked proposition, the selected q-region, the measure calibration, the two finite adjusted-summand equalities

$$\mu_{\log}(\phi(P_B)) = \sum_{\gamma} (\text{localization}_{\gamma} - \text{structure sheaf}_{\gamma}) = \det_{\log},$$

the equality between generated obligations and the constructor hull/determinant data, the record-canonical bridge equality, q-positivity, normalization, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The all-in-one route

**IUTStage1TargetChartedHodgeIPLConstructorBacked  
MeasureCalibratedAdjustedPossibleImageRouteSource**

then combines this constructor-backed adjusted source with the Hodge/IPL construction. Its audit projects internally to the constructor-backed measured route, but keeps the adjusted-summand Step (xi) audit as public provenance. The actual log-volume bridge has now been separated as a named source object:

**IUTStage1Remark395HullDeterminantBridgeSource.**

It takes q-region containment in the possible-image union, Ob3/Ob5 compatibility between  $\phi(P_B)$  and the determinant-normalized log-volume, and the Ob4 normalized tensor-power bound by  $\theta_{\text{signed}}$ , then proves the chain

$$\mu_{\log}(q_{\text{region}}) \leq \mu_{\log}(\phi(P_B)) = \det_{\log}^{\text{norm}} = \det_{\log} \leq \theta_{\text{signed}}.$$

The experiment-surface theorem **remark395HullDeterminantBridgeSource\_endpoint** exposes this chain. The direct two-step normalized form is also exposed as **remark395HullDeterminantBridgeSource\_normalizedBridge**, which records

$$\mu_{\log}(q_{\text{region}}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}.$$

The Step (xi) specialization **IUTStage1Remark395RecordHullDeterminantBridgeSource** fixes the family to the Theorem 3.11 possible images and the bound to **package.preLedger.thetaSigned**; its endpoint verifies the record-canonical q-to-determinant-to-theta comparison, while **remark395RecordHullDeterminantBridgeSource\_normalizedBridge** exposes the corresponding record-canonical normalized bridge. The record bridge constructors from Ob3/Ob5 compatibility and from the adjusted Ob3-3 summand identity now expose this normalized two-step chain in their endpoint statements, so a reviewer no longer has to pass through a separate determinant-log endpoint to see the  $\det_{\text{norm}}$  comparison. The constructed summand-charted Hodge/family-hull source now exposes this same comparison as a separate subgoal-5 audit:

**remark395SummandCalibratedStepXILogVolumeChainAudit.**

This endpoint starts from the selected Theorem 3.11 possible-image q-region, uses the record-family hull containment and monotonicity, applies the Ob3/Ob5 family-hull/determinant equality, and then uses the finite summand calibration to derive  $\det_{\log} = \theta_{\text{signed}}$ . Thus the theorem returns the explicit Lean chain

$$\mu_{\log}(q_{\text{region}}) \leq \det_{\log} \leq \theta_{\text{signed}},$$

together with the determinant summand-sum equality and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. The same synchronized finite-divisor boundary now also has an Ob5 quotient refinement:

```
synchronizedTargetChartedPossibleImageSummandHodgeFamilyHull
  IPLConstructionFiniteDivisorVerticalIQ_boundaryEndpoint
  WithStepXIOb5QuotientBoundaryAudit.
```

This audit keeps the no- $C_{\Theta}$  finite Step (x) packet and vertical- $IQ$  equalities, the summand-calibrated Step (xi) chain  $\mu_{\log}(q_{\text{region}}) \leq \det_{\log} \leq \theta_{\text{signed}}$ , the synchronized reduction to the constructor-built Step (xi) source, and the Ob1–Ob5 quotient bridge for a second nonempty Theorem 3.11 possible-image choice. Thus the strongest current summand route exposes both the numerical log-volume chain and the Ob5 collapsed quotient images before the final  $C_{\Theta}$  estimate is supplied. The product-hull Ob5–Ob7 route now has the analogous canonical-scale boundary

```
remark395ProductHullBackedConstructorBackedConstructed
  Ob3Ob5AdjustedHullDeterminantFiniteDivisorVerticalIQ
  _canonicalCThetaScaleDichotomy
  WithOb5Ob6Ob7SynchronizedAuditOfQPilotRegionNonempty.
```

This endpoint keeps the synchronized Ob5 quotient collapse, Ob6  $\Phi/\Xi$ -approximant comparison, and Ob7 prime-strip log-Kummer compatibility in the returned audit, but replaces the external numeric `thetaSigned_le_cTheta_absLogQ` input by the local scale

$$C_{\Theta, \text{can}} = \frac{\theta_{\text{signed}}}{-q_{\text{signed}}}.$$

Lean derives the corresponding bound from q-pilot positivity and then applies the same finite-divisor vertical- $IQ$  route at this scale. As above, this is a source-attached local scale, not an identification with the global  $C_{\Theta}$ -constant of the IUT papers. The same synchronized finite-divisor boundary now has a remaining-payload variant:

```
synchronizedTargetChartedPossibleImageSummandHodgeFamilyHull
  IPLConstructionFiniteDivisorVerticalIQ_boundaryEndpoint
  WithStepXIOb5QuotientRemainingPayloadBoundaryAudit.
```

This audit adds the constructor-built `ConstructorBuiltRemainingPayloadAudit` to the quotient-refined boundary. Consequently, the finite Step (x) packet/vertical- $IQ$  equalities, the summand-derived chain  $\mu_{\log}(q_{\text{region}}) \leq \det_{\log} \leq \theta_{\text{signed}}$ , the Ob5 quotient independence, and the still-open Step (xi) source-paper payload now sit in one review object. The constructed Step (xi) source also has `ofRecordHullDeterminantBridgeSource`, so the bridge payload may now be passed as one source-level mathematical object instead of as unrelated compatibility and tensor-bound fields. There is now a sharper constructor `ofRecordOb3Ob5CompatibilitySource` that builds the constructed Step (xi) source from the record Ob3/Ob5 source equality plus the remaining Ob4 tensor-bound, measure-calibration, bridge-equality, positivity, and normalization data. The corresponding Step (xi) source

```
IUTStage1Remark395ConstructedHolomorphicHullDeterminantSource
```

combines this  $\phi$ -operator with the Theorem 3.11 possible-image union, q-pilot containment in that union, the finite Ob3/Ob4 weighted determinant source, tensor-power normalization, and the record-canonical hull/determinant bridge equality. Lean proves inside this source object that the possible-image union, each possible image, and the q-pilot region lie in  $\phi(P)$ , and that the source object projects the possible-image family to the Ob5 family-hull/determinant log-volume source. In particular, Lean now also proves the family-hull log-volume equality with the weighted determinant and the family-union log-volume bound by that determinant before proving

$$\mu_{\log}(q_{\text{region}}) \leq \det_{\log}^{\text{norm}} \leq \theta_{\text{signed}}.$$

The experiment-surface theorem

```
Iut.Stage1.Experiments.boundarySignedEqualityOrStrictCTheta_from
  _remark395ConstructedHullDeterminantFiniteDivisorVerticalIQ
```

threads this constructed Remark 3.9.5 source through the finite-divisor vertical- $IQ$  corridor. This ordinary form still accepts a chosen  $C_{\Theta}$  and the corresponding numeric estimate as explicit inputs. The same source now has a canonical-scale companion

```
Iut.Stage1.Experiments.boundarySignedEqualityOrStrictCTheta_from
  _remark395ConstructedHullDeterminantFiniteDivisorVerticalIQ
  _canonicalCThetaScale,
```

where the constructed Remark 3.9.5 source object defines the scale as  $\theta_{\text{signed}}/(-q_{\text{signed}})$ . The source-level audit `ConstructedCanonicalCThetaScaleAudit` records the

$$\mu_{\log}(q_{\text{region}}) \leq \det_{\log}^{\text{norm}} \leq \theta_{\text{signed}} \leq C_{\Theta, \text{can}} \cdot (-q_{\text{signed}})$$

chain and proves the final ordered-real dichotomy without an external `thetaSigned_le_cTheta_absLogQ` hypothesis for this local scale. The new experiment-surface target

```
Iut.Stage1.Experiments.remark395ConstructedHolomorphic
  HullDeterminantSource_canonicalCThetaScaleChain
```

exposes this chain directly from the constructed source object, while `remark395ConstructedHolomorphicHullDeterminantSource_canonicalCThetaScaleAudit` exposes the full audit record. The source equality  $\mu_{\log}(\phi(P_B)) = \det_{\log}^{\text{norm}}$ , the Ob4 tensor-bound input, and the equality with the older algorithmic hull/determinant bridge remain source obligations rather than full arithmetic vector-bundle constructions, but the Ob3/Ob5 certificate and ordered log-volume comparison are now derived from named source-level objects.

The endpoint type `Stage1Comparison` is not a source proof: its comparison field is the Corollary-3.12-shaped conclusion, and the corresponding theorem is only a projection. The source-facing route must construct this endpoint from the ledger. The ledger now records the opaque output certification and ties the  $\Theta$ -common bound used in the final inequality to `chartedContainer.apply certificate`, so the displayed charted container cannot be paired with an unrelated convenient bound. Throughout the current corridor, “upper ray” means the signed-log region  $\{x \mid x \leq b\}$ , not the ordinary order-theoretic ray  $\{x \mid b \leq x\}$ .

The largest engineering issue has been reduced to the remaining organization of the endpoint-route families. Eight mechanical splits have been made: `IUTStage1IUTIVAAlgebra.lean` now

carries the Remark 3.12 sign shadows and the conditional IUT IV real-algebra handoff estimates, while `IUTStage1FiniteLabels.lean` carries the finite-label and theta-root cusp-label source layer, and `IUTStage1StepX.lean` carries the Step (x) upper-ray corridor together with its boundary Frobenioid-shift diagnostics. The Gaussian and Hodge–Arakelov theta-evaluation shadow layer now lives in `IUTStage1Gaussian.lean`, and the Hodge/SHE support layer now lives in `IUTStage1HodgeSHE.lean`. The Theorem 3.11 source-choice and multiradial possible-image layer now lives in `IUTStage1Theorem311.lean`. The Step (xi) hull/determinant and IPL source layer now lives in `IUTStage1StepXI.lean`. The first endpoint audit family and nonarchimedean realified-Frobenioid/log-Kummer support layer now live in `IUTStage1FrobenioidShift.lean`; the original `IUTStage1Source.lean` file has now also been split into `IUTStage1EndpointAudit.lean`, for the nested LogVolumeChartAudit refinements, and `IUTStage1Source.lean`, for the public source-package audit surface. Low-risk future refactors are:

|                                    |                          |
|------------------------------------|--------------------------|
| Structured endpoint route families | smaller route modules,   |
| Generated dependency/audit report  | separate checked target. |

These refactors should be mechanical only: move declarations, preserve names where possible, and rebuild after each move.

## 10 Paper Trace Audit

The current source map for the Theorem 3.11 to Corollary 3.12 corridor is now recorded directly in Lean, rather than only in prose. The namespace

`IUTStage1Theorem311ToCorollary312PaperTrace`

contains four obligation records and one assembled trace record. The first record covers IUT III, Theorem 3.11 and Remarks 3.11.2–3.11.4: construction of the multiradial representation, input-prime-strip link, theta-pilot possible images, log-theta-lattice procession data,  $F_l$ -label transitions, and the typed compatibility between possible images and the  $(\text{Ind}_1, \text{Ind}_2)$  equality quotient. It explicitly keeps the  $(\text{Ind}_3)$  contribution as an upper-semi log-volume inequality. At the current strict endpoint these trace slots are witnessed by the quotient equality, the typed-core action-law audit, the quotient-indexed pullback of possible images, the exact  $|Z/lZ| = l$  cardinality, and the finite procession transition law, rather than by a single broad quotient-audit wrapper. The input-prime-strip and Hodge/SHE/IPL/APT entries are likewise no longer filled by the whole bridge audit at this strict boundary: the former is the choice-wise constructed IPL link endpoint, and the latter is the structured IPL/SHE/APT evidence together with the forbidden SHE-transport guard and the non-forbidden permitted APT arrow. The typed quotient layer now also has a first-class hull/log-volume compatibility object, `EqualityQuotientHullLogVolumeCompatibility`. It packages the quotient-indexed possible-image family with a Remark 3.9.5 hull operator, proves pullback to the original choice-indexed images, proves equality-orbit invariance for the resulting hull log-volumes under  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$ , and keeps the  $(\text{Ind}_3)$  statement as the typed core’s upper-semi log-volume inequality rather than turning it into a hull equality. The strict two-point nonvacuity model now instantiates this object as `strictFiniteToyEqualityQuotientHullLogVolumeCompatibility`; its audit endpoint verifies pullback,  $(\text{Ind}_1)/(\text{Ind}_2)$  hull-log-volume invariance, the one-sided  $(\text{Ind}_3)$  core inequality, and the fact that the strict  $(\text{Ind}_3)$  step is not collapsed by the equality quotient. This is a test of the interface geometry, not a claim that the finite model is a source model of IUT. The same strict two-point model now reaches the actual one-sided Theorem 3.11 multiradial construction

source through

```
strictFiniteToyEqualityFLProcessionAction,
strictFiniteToyOneSidedMultiradialConstructionSource,
strictFiniteToyOneSidedMultiradialConstructionSource_
ind3_not_equalized.
```

Given a genuine multiradial source record whose possible-image family is this strict finite family, Lean constructs the equality-quotient  $F_l$ -procession action by identity transitions, builds an `IUTStage1Theorem311OneSidedMultiradialConstructionSource`, proves its standard endpoint, and verifies that the strict  $0 \rightarrow 1$  (Ind<sub>3</sub>) step is still not an equality-quotient identification. Thus the nonvacuity check now passes through the same one-sided multiradial source object used by the preferred  $C_\Theta$  corridor. It now also reaches the finite-place local-to-global  $C_\Theta$  source through

```
strictFiniteToyOneSidedFinitePlaceLocalGlobalCThetaSource,
StrictFiniteToyOneSidedFinitePlaceLocalGlobalCThetaAudit,
StrictFiniteToyOneSidedIUTIVArithmeticGapHandoffAudit.
```

This constructor takes the strict finite multiradial source together with the finite Step (xi)/Haar summation data, derives the usual arithmetic-gap and  $C_\Theta$  comparison audit, and keeps the strict (Ind<sub>3</sub>) non-collapse visible inside the same local-to-global source object. The last audit pins the new explicit *IUT* IV arithmetic-gap handoff to this same nonvacuity witness: finite-sum identifications, the summed Step (xi)/Haar inequality,  $C_\Theta + 1 = A - M$ , cancellation to  $C_{\Theta, \text{can}} \leq C_\Theta$ , and the strict (Ind<sub>3</sub>) non-equality all live in one checked object. The bridge has also been lowered to the normalized-Haar Step (xi) local-term source:

```
strictFiniteToyOneSidedNormalizedHaarStepXILocalTermCThetaSource,
StrictFiniteToyOneSidedNormalizedHaarStepXILocalTermCThetaAudit.
```

Here the canonical local terms come from the localized vector-bundle determinant source, and the global  $+1$  is obtained from a finite-place Haar-defect source, while the strict (Ind<sub>3</sub>) step remains outside the equality quotient. The strict finite route has now been pushed one layer further, to the local  $p$ -adic unit-ball Haar source:

```
strictFiniteToyOneSidedPadicUnitBallHaarStepXILocalTerm
CThetaSource,
StrictFiniteToyOneSidedPadicUnitBallHaarStepXILocalTerm
CThetaAudit.
```

This replaces the abstract finite-place Haar-defect input by placewise unit-ball normalization data  $\mu(\mathcal{O}_v) = 1$ , the base-prime dilation character, and the prime/finrank index  $p_v^{[K_v:\mathbb{Q}_{p_v}]}$ . Lean proves local nonnegativity and the distinguished-place  $\sum_v \delta_v \geq 1$  contribution from this source, and the audit keeps the same strict (Ind<sub>3</sub>) non-equality through the projected local-to-global  $C_\Theta$  comparison. Finally, the strict finite witness now reaches the *IUT* IV arithmetic-defect surface:

```
strictFiniteToyOneSidedIUTIVArithmeticDefectStepXI
LocalTermCThetaSource,
StrictFiniteToyOneSidedIUTIVArithmeticDefectStepXI
LocalTermCThetaAudit.
```

At this layer the local defect is named as the *IUT* IV arithmetic-defect term, with a placewise proof that it equals the  $p$ -adic unit-ball Haar index. The same audit therefore carries the total defect

lower bound and the strict (Ind<sub>3</sub>) non-collapse in the paper-side  $C_\Theta$  vocabulary. The same strict witness has now been lowered to the IUT IV arithmetic-divisor evaluation surface:

```
strictFiniteToyOneSidedIUTIVArithmeticDivisorEvaluation
  StepXILocalTermCThetaSource,
StrictFiniteToyOneSidedIUTIVArithmeticDivisorEvaluation
  StepXILocalTermCThetaAudit.
```

Here the arithmetic upper term and main-log term are no longer supplied as separate global equalities. They are read from `IUTStage1IUTIVThetaPilotArithmeticDivisorLocalEvaluationSource`, whose endpoint gives the local different/conductor sums, prime-error sum, arithmetic-upper sum, and main-log sum. The remaining handoff is the pointwise identity matching each local arithmetic upper contribution with the Step (xi) canonical term, the IUT IV local defect, and the local main-log contribution. The strict witness has also been lowered through the first Theorem 1.10 arithmetic-divisor construction layer:

```
strictFiniteToyOneSidedIUTIVTheorem110ArithmeticDivisor
  StepXILocalTermCThetaSource,
StrictFiniteToyOneSidedIUTIVTheorem110ArithmeticDivisor
  StepXILocalTermCThetaAudit.
```

At this boundary, the older theta-pilot local evaluation data are produced from effective different,  $q$ -parameter, and conductor arithmetic divisors, the conductor support comparison with the  $q$ -parameter divisor, and the Theorem 1.10 Step (v)–(vii) local estimate gate. The audit records the different/conductor degree sums, the prime-error and main-log finite sums, the local procession upper-bound inequality, and the Step (vi) vanishing condition for nondistinguished nonarchimedean places. The strict witness now also reaches the formula-level Theorem 1.10 arithmetic-divisor source:

```
strictFiniteToyOneSidedIUTIVTheorem110FormulaArithmeticDivisor
  StepXILocalTermCThetaSource,
StrictFiniteToyOneSidedIUTIVTheorem110FormulaArithmeticDivisor
  StepXILocalTermCThetaAudit.
```

This removes the local estimate gate as a primitive input on the strict route. The gate is produced from the local case formula source: the Step (v) distinguished formula bound, the Step (vi) nondistinguished nonnegative-gap formula with zero procession contribution, and the Step (vii) archimedean formula bound. The strict witness has now been lowered one layer further, to the Proposition 1.4/1.5-backed source:

```
strictFiniteToyOneSidedIUTIVTheorem110PropositionArithmeticDivisor
  StepXILocalTermCThetaSource,
StrictFiniteToyOneSidedIUTIVTheorem110PropositionArithmeticDivisor
  StepXILocalTermCThetaAudit.
```

This audit records the local Proposition 1.4 distinguished log-shell estimate, the Proposition 1.4 nondistinguished zero/gap estimate, and the Proposition 1.5 archimedean metric estimate before projecting to the formula source. The distinguished and archimedean formula-to-gap comparisons remain visible as the current Step (xi)/IUT IV matching payload. The next lower boundary is the local analytic construction of these proposition objects. This boundary is now also represented on

the strict route:

```
strictFiniteToyOneSidedIUTIVTheorem110LocalAnalyticArithmeticDivisor
  StepXIILocalTermCThetaSource,
StrictFiniteToyOneSidedIUTIVTheorem110LocalAnalyticArithmeticDivisor
  StepXIILocalTermCThetaAudit.
```

Here the Proposition 1.4/1.5 estimates are produced from local analytic construction sources: distinguished and nondistinguished finite-extension Haar/log-volume log-shell constructions, and archimedean direct-sum metric constructions. The strict route has also been lowered to the additive-Haar version of this boundary:

```
strictFiniteToyOneSidedIUTIVTheorem110AdditiveHaarLocalAnalytic
  ArithmeticDivisorStepXIILocalTermCThetaSource,
StrictFiniteToyOneSidedIUTIVTheorem110AdditiveHaarLocalAnalytic
  ArithmeticDivisorStepXIILocalTermCThetaAudit.
```

This audit exposes the actual additive Haar compact-open normalization endpoint at each distinguished and nondistinguished finite place, then projects to the local-analytic strict audit. Thus the strict finite diagnostic no longer stops at generic finite-extension log-shell data before entering the Step (xi)  $C_\Theta$  comparison.

The Step (x) record names the finite-divisor packet, realified Frobenioid log-Kummer source, Kummer/forgetting compatibility, vertical- $IQ$  target source, and packet source-target log-volume calibration. Its constructor from the typed indeterminacy core proves the equality/equality/inequality pattern: (Ind<sub>1</sub>) and (Ind<sub>2</sub>) preserve procession-normalized log-volume, while (Ind<sub>3</sub>) only gives a one-sided bound. The same Step (x) record now carries the relation-level **Ind3UpperSemiRelationAudit**, so this one-sided law remains a named certificate in the paper-trace obligations rather than merely an extracted function field. The paper-trace API now also exposes projections for the typed Theorem 3.11 action-law audit, the relation-level (Ind<sub>3</sub>) upper-semi audit, the step-level (Ind<sub>3</sub>) transport certificate, and the fact that (Ind<sub>3</sub>) contributes no generator to the equality quotient. The Step (xi) record names the remaining Remark 3.9.5 hull/determinant work: holomorphic hull operator, possible-image family matching, q-region containment, Ob1/Ob2 hull absorption, Ob3/Ob4 determinant normalization, Ob5 quotient compatibility, Ob7 prime-strip retention, tensor-power bound, and the q-region-to-theta log-volume chain. In the current top-level audit, the tensor-power slot is the constructed normalized determinant bound, while the q-region slot is the separate inequality obtained by composing q-to-determinant and determinant-to-theta in the constructed record bridge.

The IUT IV record names the local-to-global  $C_\Theta$  obligations below the current additive-Haar boundary: Proposition 1.4 distinguished log-shell inclusions, now instantiated as per-place arithmetic-divisor-backed component endpoints; Proposition 1.4 numerical bounds, now instantiated as the local different/conductor nonnegativity facts; the nondistinguished zero log-volume result, now instantiated as the per-place nondistinguished additive-Haar log-shell endpoint; Proposition 1.5 metric containment, now instantiated as the per-place archimedean metric endpoint; the Theorem 1.10 arithmetic-divisor source; distinguished and archimedean formula-to-gap comparisons, now instantiated as named per-place comparison endpoints; additive Haar local normalization; the Step (xi)-to-IUT IV local matching equality; the finite-place arithmetic gap  $C_{\Theta,\text{can}} + 1 \leq A_{\text{upper}} - M_{\log}$ ; and the global proof of  $C_{\Theta,\text{can}} \leq C_\Theta$ . Its **LocalToGlobalArithmeticChainAudit** now has named projections for all seven chain entries, including the local Step (xi)-to-IUT IV arithmetic-term matching, the finite-place arithmetic gap, and the final  $C_{\Theta,\text{can}} \leq C_\Theta$  comparison.




The trace now also has a separate preferred-boundary record, **AdditiveHaarArithmeticDegreePadicObligations**. This names the remaining constructions specifically used by the deepest current additive-Haar endpoint: Theorem 1.10 additive-Haar local analytic construction, local arithmetic matching, arithmetic-divisor formula splitting,  $p$ -adic prime-error/defect/main-log splitting, Step (xi) arithmetic-degree calibration, unscaled Proposition 1.4/Step (vii) local degree-bound identifications, determinant-multiplicity and adjusted-log-volume identifications, realified packet recovery of the Step (x) equalities, and the constructed Hodge/SHE/IPL provenance now threaded through that endpoint. Its **RemainingPayloadAudit** is included in the assembled corridor audit, so the preferred route no longer hides these lower source assumptions behind the generic IUT IV  $C_\Theta$  record. Each component also has a named Lean projection theorem. This makes the next source-math work precise: the local analytic additive-Haar construction, arithmetic-divisor splitting,  $p$ -adic error decomposition, Step (xi) arithmetic-degree calibration, and the determinant/log-volume identifications must be constructed individually before this audit can be discharged.

The assembled **Obligations** record adds the endpoint-level requirements that the final preferred theorem must not expose either the raw  $\theta_{\text{signed}} \leq C_\Theta(-q_{\text{signed}})$  input or the raw  $C_{\Theta, \text{can}} \leq C_\Theta$  comparison as public hypotheses. From the assembled **RemainingPayloadAudit**, Lean now reconstructs the whole IUT IV local-to-global arithmetic-chain audit and separately projects both raw-hypothesis-removal requirements. The same assembled audit now also reconstructs the full additive-Haar/arithmetic-degree-padic subledger and projects each of its lower source clauses: the Theorem 1.10 local analytic construction, local arithmetic matching, arithmetic-divisor split,  $p$ -adic prime-error/defect/main split, Step (xi) arithmetic-degree calibration, determinant/coefficient and adjusted-log-volume identifications, Step (x) packet equalities, the constructed IPL and SHE/APT transport data, and the strongest additive-Haar endpoint certificate. Its Theorem 3.11/remarks subledger now also contains a **typed\_indeterminacy\_nonvacuity\_witness\_constructed** slot, discharged at the strongest current boundary by the strict two-point typed  $(\text{Ind}_1)/(\text{Ind}_2)/(\text{Ind}_3)$  witness.

## 11 Next Work

The remaining mathematical work is organized by the trace audit above. One major branch is still to construct, rather than assume, more of the source-facing SHE and Hodge-descent preservation data. The route is:



The project should continue by replacing the present record fields for factored SHE preservation and Hodge-descent source-target alignment with the corresponding constructions from IUT I–III. The

first source-derived bridge layer has now been added: the final finite-divisor vertical-*IQ* route can consume separated IPL, SHE, hull/determinant, and theta/Hodge calibration source components instead of an opaque route-alignment argument. The SHE component has been refined to a finite Hodge/SHE transport package that exposes the two theater sides, the finite label equivalence, full-label log-volume preservation, transported-average preservation, and the current history-separation guard. It now also has a typed source boundary that carries the Hodge-theater descent bridge and a typed allowed-forgetting witness separately from the synchronization-derived finite preservation data. The remaining work is to make each of those components itself follow from the relevant source-paper constructions, rather than supplying them as records. The IPL component can now be constructed at the public finite-divisor vertical-*IQ* endpoint from the finite Hodge/SHE transport together with a Theorem 3.11 IPL-link construction source. The endpoint no longer receives a free-standing IPL datum, source/target endpoint equalities, or a separate IPL log-volume transport source: the constructed input-prime-strip link gives the endpoint equalities definitionally, the source object aligns that constructed datum with the pre-ledger certificate, and log-volume preservation is read from the finite Hodge/SHE transport. The foundational qualitative certificate is no longer only a nonempty bookkeeping triple. The declarations

```
HodgeTheaterTransportSystem,
StructuredSHETransportContext,
AlgorithmicParallelTransportConstruction
```

record permitted Hodge-theater transport arrows, forbidden theater identifications, and APT data built from a permitted arrow. Lean proves that a forbidden domain-to-codomain SHE identification admits no allowed transport arrow, and that the constructed APT datum has the permitted arrow's mechanism, the constructed output family, the output-family equality back to the pre-ledger family, the allowedness proof, and the resulting non-forbiddenness of the APT arrow. The Stage 1 wrapper `ConstructedQualitativeCertificateData` pins the pre-ledger certificate to the certificate constructed from these IPL/SHE/APT objects and returns both a compact qualitative transport audit and this stricter APT transport audit. The finite Hodge/SHE transport layer now has the corresponding source discipline audit

```
IUTStage1ConstructedQualitativeFiniteHodge
SHETransportDisciplineAudit.
```

It records, in one object, that the finite Hodge/SHE comparison uses only the history-separated forgetful reading, while the constructed SHE transport system forbids a direct domain-to-codomain identification and the APT arrow is separately proved non-forbidden. Thus the finite comparison is no longer documented merely by a side inequality; the typed allowed/forbidden transport discipline is visible next to it. The route-facing constructor

```
IUTStage1ConstructedQualitativeFiniteHodgeSHETransportSource
```

now packages this as source data: from the constructed qualitative bundle and the Hodge–Arakelov theta evaluation synchronization, it builds the history-separated finite Hodge/SHE transport source and returns the same typed discipline audit. In particular, the finite forgetful comparison is kept separate from the forbidden direct SHE identification while the permitted APT arrow remains part of the constructed qualitative input. The next bridge,

```
IUTStage1ConstructedQualitativeFiniteHodgeSHEIPLConstructionSource,
```

adds the constructed Theorem 3.11 IPL link to this same source object and projects to the existing finite Hodge/SHE+IPL log-volume chain. Thus the IPL handoff can now be audited from the constructed qualitative SHE/APT transport boundary through the constructed input-prime-strip link, with no separate finite Hodge/SHE source supplied at that layer. This is the present typed replacement for the older raw `HasStructuredIPL/SHE/APT` certificate fields. The Theorem 3.11 source layer now exposes `IUTStage1Theorem311ConstructedQualitativeInputs`: its pre-ledger audit is induced from the constructed qualitative certificate, it projects back to the existing structured-input route, and it exposes the forbidden SHE-domain-to-codomain transport guard together with the permitted APT non-forbiddenness proof. This has now been promoted to the strengthened SHE route surface by `IUTStage1Theorem311ConstructedQualitativeInputsWithSHE`, which projects to the existing `StructuredInputsWithSHE` route, builds the current multiradial source record, and exposes public source-obligation and Corollary 3.12 audit constructors without asking callers to supply a raw pre-ledger audit. The same constructed boundary now reaches the named Theorem 3.11-to-Corollary 3.12 checkpoint layer: `ConstructedQualitativeStructuredSHERouteSummary` and `ConstructedQualitativeTheorem311ToCorollary312Checkpoints` retain the old structured route only as a projection, while the public boundary carries the constructed qualitative audit, the forbidden SHE-domain-to-codomain transport statement, and the APT transport audit identifying the actual datum with the permitted-arrow construction. The constructed finite Hodge/SHE+IPL bridge audit now also exposes the choice-wise IPL endpoint `choiceWiseIPLEndpoint`: for every Theorem 3.11 choice the constructed link has source equal to the fixed input prime strip and target equal to the corresponding choice prime strip, while the same audit retains the certificate-to-constructed-IPL-datum equality and finite Hodge/SHE log-volume preservation. There is now also a certificate-pinned variant of this boundary. It reads the IPL datum directly from the pre-ledger certificate and asks only for the two endpoint equalities of that certificate link. Consequently the public Hodge–Arakelov/history-separated route may avoid the stronger certificate-equals-constructed-IPL-datum assumption. The remaining source-paper task for this layer is to construct those certificate endpoint equalities, and eventually the input-prime-strip link itself, from the Theorem 3.11 IPL machinery. At the next source boundary, the same public endpoint can now receive a synchronized Hodge–Arakelov source object. This object carries the calibrated source evaluation, target evaluation, and canonical one-label degree preservation together, and it projects the finite Hodge/SHE transport used by the route. The allowed-forgetting predicate is fixed to the history-separation condition of the record’s Hodge-theater descent bridge, so the public route no longer needs to be handed the finite transport record, a free square-weight profile, a separate theta-root source, a separate source/target evaluation synchronization equality, or a free permission predicate. These are constructed or projected from the synchronized Hodge–Arakelov and Theorem 3.11 source data. The actual Hodge-theater forgetting operation and the deeper construction of the theta-evaluation sources remain open source-paper obligations. The summand-charted Step (xi) input also has a synchronized target-charted form: the transported theta chart is calibrated against the target Hodge–Arakelov canonical one-label degree, and Lean derives the charted-theta/source-Hodge equality using the synchronized canonical-one preservation before projecting to the previous summand source. Thus the public route no longer has to receive that charted source-Hodge scalar equality as a primitive Step (xi) summand-calibration field. The same source now has a possible-image q-pilot refinement: the q-region is definitionally the chosen Theorem 3.11 possible-image region, and the  $q \subseteq P_{\text{choice}}$  containment is projected by reflexive membership rather than supplied as an additional Step (xi) field. The experiment surface exposes this refinement as an audit endpoint before the finite-divisor route is applied: it reports the definitional q-region equality, the target-charted Hodge/summand identities, the hull-bridge equality, the sign and normalization side conditions, and the derived  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison.

This source now also projects to the generic possible-image side-conditioned holomorphic-hull/determinant source. In that projection, the Ob4 normalized tensor-power bound is derived from the Hodge/family-hull calibration, the record-canonical hull/determinant bridge equality is derived from the package hull-det obligations, and the q-pilot side conditions are read from the same obligations object. The experiment surface therefore has a raw constructed-IPL endpoint for this summand/family-hull route, proving  $q_{\text{signed}} \leq \theta_{\text{signed}}$  before the later  $C_\Theta$  numeric bound is invoked. The summand/family-hull q-comparison payload is now also promoted to a named audit proposition, bundling the possible-image q-pilot choice, determinant summand formula, family-hull log-volume identification, obligation-backed hull/determinant bridge equality, and raw signed comparison. The source-derived bridge constructor itself now has the same specialized input form: it consumes the calibrated Hodge–Arakelov synchronization, the constructed IPL source, and the synchronized target-charted possible-image summand/family-hull Step (xi) source, then performs the generic hull-source projection internally. The experiment surface exposes a bridge audit endpoint for this constructor, so the constructed bridge no longer has to be reviewed via an intermediate generic holomorphic-hull/determinant source. The finite-divisor vertical-*IQ*  $C_\Theta$  endpoint now has the same direct bridge form: the public Step (xi) input is the synchronized target-charted possible-image summand source, and the boundary theorem builds the source-derived Hodge/SHE/IPL/hull bridge internally before entering the generic finite-divisor route. Thus this endpoint no longer has to reach the bridge through the older target-charted/summand projection chain. The same summand/family-hull route now has a no- $C_\Theta$  finite-divisor boundary returning the named q-comparison audit together with the finite Step (x) packet equalities and vertical-*IQ* target equalities, separating the summand Step (xi)/Step (x) provenance from the later numeric estimate. The target chart comparison can now be moved one layer earlier. A target-charted Hodge–Arakelov synchronization records that the transported pre-ledger theta chart is the target Hodge–Arakelov canonical one-label degree; Lean then derives the source theta-monoid reading from the synchronized canonical-one preservation. The associated possible-image summand Step (xi) source no longer carries this target chart/canonical-one equality as a hull-side calibration field; it keeps only the determinant-side finite summand equality plus the record-native possible-image hull data. The bridge audit and finite-divisor  $C_\Theta$ -endpoint expose this refined source boundary. This refined target-charted route now also has a no- $C_\Theta$  finite-divisor boundary: it returns a named bridge audit, including the constructed IPL-datum checks, target-chart synchronization, log-volume preservation, raw signed comparison, and history-separation guard, together with the finite Step (x) packet equalities and vertical-*IQ* target equalities. The target-charted possible-image route now has a determinant-payload refinement. A dedicated Hodge/determinant family-hull source packages the record-native family-hull determinant source, the equality between the package measure and the hull log-volume measure, and the Hodge theta-monoid equality with the finite sum of adjusted determinant summands. The possible-image Step (xi) source consumes this single payload and projects the earlier family-hull, measure-calibration, and summand-equality fields internally before entering the same side-conditioned hull/determinant bridge. The bridge audit now has a determinant-refined raw finite-divisor boundary as well: it reuses the target-charted summand bridge audit, adds the family-hull/determinant log-volume equality, and carries the finite Step (x) packet and vertical-*IQ* target equalities before the  $C_\Theta$  estimate is invoked. The experiment surface therefore reports the determinant log-volume equality in addition to the target theta chart, Hodge theta-monoid, possible-image q-region, hull-det bridge, and raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. The finite-divisor vertical-*IQ* experiment endpoint now exposes this determinant payload as the strongest public Step (xi) boundary in this corridor. The Hodge/IPL side of this route has also been bundled one layer earlier. A target-charted Hodge–Arakelov IPL-construction source now contains the target-charted Hodge synchronization and the constructed Theorem 3.11

input-prime-strip link. From these data Lean constructs the finite Hodge/SHE transport source, reads the IPL log-volume transport from that finite transport, and preserves the target/source log-volume equality without a separate transport equality field. The determinant possible-image bridge and finite-divisor vertical- $IQ$  experiment endpoints now consume this single Hodge/IPL payload together with the Step (xi) determinant possible-image source. This packaged route now also has a no- $C_\Theta$  finite-divisor boundary that returns the packaged-source bridge audit together with the finite Step (x) packet equalities, vertical- $IQ$  target equalities, and raw signed comparison before the numeric estimate is supplied. The Hodge/IPL construction source itself now exposes the history-separated finite Hodge/SHE transport-source audit: the source and target Hodge–Arakelov value sources, record-native forgetting permission, pointwise representative comparison level, identity coordinate equivalence, and Hodge-theater separation are visible before the constructed-IPL layer is formed. The strongest public target-charted route now packages these two sides into one source object before the finite Step (x) data are introduced. This all-in-one route source exposes the target theta chart comparison, constructed IPL-datum equality, possible-image q-region, determinant summand equality, family-hull/determinant equality, package hull-det bridge equality, log-volume transport preservation, positivity, normalization, and raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison as projections from a single source-facing payload. It now also has a divisor-packet no- $C_\Theta$  boundary returning a named all-in-one route bridge audit, the finite Step (x) packet equalities, the vertical- $IQ$  target equalities, and the raw signed comparison; thus the source-derived Step (xi) bridge is reviewed as a single route object before the finite packet source is constructed. The same named route audit now also travels through the exact vertical- $IQ$  finite-source boundary, alongside the log-Kummer vertical- $IQ$  calibration-source equality, the finite-source equalities, and the exact target equalities. The same route now also projects explicitly to the possible-image side-conditioned holomorphic hull/determinant source, exposing the chosen Theorem 3.11 possible-image q-region, containment in the record possible-image union, the Ob4/tensor-power determinant bound, positivity, normalization, and the raw signed comparison before the finite Step (x) vertical- $IQ$  data or the separate  $C_\Theta$  numeric bound enter. On the Hodge/SHE side, the same route now exposes the finite transport audit separately: the structured-SHE flag, source/target Hodge theaters, coordinate transport, full-label log-volume preservation, transported-average preservation, and history-separation guard are route-level projections. On the Hodge/IPL side, the all-in-one route also projects directly to the finite Hodge/SHE plus constructed-IPL source object and exposes the target theta chart comparison, certificate-pinned IPL datum, constructed-IPL datum, log-volume preservation, allowed forgetful transport, and Hodge-theater history separation as route-level audits. The packaged target-charted Hodge–Arakelov/IPL source now exposes both the history-separated finite Hodge/SHE transport-source endpoint and the constructed IPL log-volume transport endpoint itself, including the source/target Hodge–Arakelov value sources, record-native forgetting permission, pointwise representative comparison level, identity coordinate equivalence, certificate-pinned IPL datum, input/output prime-strip link endpoints, finite Hodge-theater source and target sides, log-volume preservation, allowed forgetful transport, and history separation; the all-in-one route projects these source-level endpoints. Upstream of these transport audits, the route now also exposes the Hodge–Arakelov theta-evaluation layer: the canonical theta-root generator and full label, zero and canonical Gaussian degrees, the finite  $q^{j^2}$  square-weight degree formula, source full-label theta calibration, and the target chart/canonical-one comparison are all route-level projections. Between this Gaussian layer and the finite transport object, the route now exposes the factored SHE preservation constructor itself: canonical one-label preservation for the source and target Hodge–Arakelov theta evaluations constructs identity coordinate transport, coordinate-square preservation, full-label map and value preservation, transported-average preservation, and the Hodge-theater history-separation guard.

The next route projection pins the finite Hodge/SHE transport source itself to the history-separated constructor from these source and target Hodge–Arakelov theta-evaluation sources: the source/target value sources, history-separated forgetful permission, pointwise representative comparison level, identity coordinate equivalence, and Hodge-theater history separation are exposed before the constructed-IPL layer is used. The constructed IPL log-volume transport source is now exposed at the same route boundary: the certificate-pinned IPL datum, constructed datum, input/output prime-strip link endpoints, finite Hodge-theater source and target sides, log-volume preservation, allowed forgetful transport, and history separation are all projected before the Step (xi) hull/determinant source enters. The same route boundary now also has a constructor-identity endpoint, `constructedIPLTransportSourceEqConstructedEndpoint`, which states that the projected IPL/log-volume source is exactly `ofTheorem311IPLLinkConstructionSource` applied to the finite Hodge/SHE transport and the carried input-prime-strip-link construction. The same boundary now records the provenance of the IPL log-volume equality: the IPL source log-volume is the source average of the finite Hodge/SHE transport audit, the IPL target log-volume is the transported target average, and their equality is the transported-average preservation theorem from the finite Hodge/SHE layer. The same constructed-IPL boundary now also exposes the choice-wise input-prime-strip links generated by the Theorem 3.11 link construction: for every possible output choice, the constructed link has source equal to the route’s input prime strip and target equal to that choice’s prime strip. This is exposed by the experiment suffix `thetaMonoidMatchedConstructedIPLChoiceLinkEndpoint`, giving a finite choice-indexed shadow of the IPL condition before Step (xi) hull data is used. The bundled exact vertical- $IQ$  route now carries this same finite-average provenance together with the route-owned IPL datum, raw Step (xi) comparison, log-Kummer vertical- $IQ$  target calibration, Frobenioid precision flag, and Step (x) upper-semi inequality before the external  $C_\Theta$  numeric bound is used. The same bundled exact-route boundary now also carries the Remark 3.9.5(Ob5) family-hull guard: for two nonempty Theorem 3.11 possible images, both regions lie in the record family hull and have the same upper-semi quotient image, while the determinant/log-volume identifications, raw signed comparison, log-Kummer non-interference, and Step (x) upper-semi bound are projected from the same source package. This Ob5 guard is now also threaded through the Gaussian-front audit: the canonical Hodge–Arakelov theta label, zero Gaussian degree, square-weight formula, two arbitrary nonempty possible images, their common family-hull quotient image, and the exact Step (x) log-Kummer/upper-semi facts appear in one endpoint. The same all-in-one route source now feeds the Hodge direct-labelled finite-divisor vertical- $IQ$  endpoint directly: instead of passing the generic source-derived bridge at the public Step (x) boundary, Lean projects the bridge from the target-charted Hodge/IPL/determinant possible-image route and then applies the Hodge-derived labelled-average and finite-divisor packet-local construction. On the Step (xi) side, the target-charted Hodge/determinant possible-image source now exposes the converted side-conditioned hull/determinant endpoint itself: the chosen Theorem 3.11 possible image, its containment in the record possible-image union, the tensor-power bound, q-positivity, normalization, and raw comparison are visible before the Hodge/IPL route source is assembled. The all-in-one route projects this source-level endpoint. The route also exposes the canonical hull/tensor-power bridge equality itself: the common-container hull/determinant bridge is identified with the record-canonical Theorem 3.11 possible-image hull data, weighted determinant, measure calibration, and tensor-power bound before the finite Step (x) vertical- $IQ$  source or the external  $C_\Theta$  numeric bound enter. This canonical bridge audit is now available at the target-charted Hodge/determinant Step (xi) source boundary itself; the all-in-one route endpoint projects it from that source. The same route now also exposes the source-paper-shaped Step (xi) passage from Theorem 3.11 possible images to the holomorphic hull and then to the log-volume bound: the endpoint records

certification, the SHE datum, equality of the theta-pilot possible-image union with the record union, containment of that union in the applied holomorphic hull, the  $\theta_{\text{signed}}$  log-volume bound, and the resulting raw comparison  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The route-level theorem is now a projection of the reusable possible-image Step (xi) source-level holomorphic-hull/log-volume endpoint; this endpoint is also available at the target-charted Hodge/determinant possible-image source boundary before the Hodge/IPL construction wraps it into the all-in-one route. The same route now also exposes the determinant summand/family-hull payload as its own audit: the target theta-chart readings, Hodge theta-monoid summand formula, family-hull/determinant log-volume equality, package measure-to-hull-log-volume calibration, tensor-power normalization, determinant tensor bound, and raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison are projected at the all-in-one route boundary before finite Step (x) or the external  $C_{\Theta}$  bound enter. The same all-in-one route now exposes the raw comparison at the source boundary before the generic bridge is assembled: the certificate-pinned IPL datum, preserved IPL log-volume, source Hodge–Arakelov value source, chosen possible-image q-region, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison are all projected from the route source. The bridge-level raw comparison endpoint now uses this source-boundary comparison for its final inequality while still auditing the assembled bridge’s IPL and Hodge/SHE projections. The same all-in-one route now has a direct Gaussian-to-Step (xi) audit endpoint: the theta-root canonical label and square-weighted Gaussian degree formula, the finite Hodge/SHE history-separated transport, the constructed IPL log-volume preservation, the constructed choice-wise input-prime-strip links, the chosen possible-image q-region with its union containment, the determinant summand calibration, the package hull/determinant bridge datum, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison are projected from one route source before any finite Step (x) vertical- $IQ$  input enters. This audit has also been promoted to a named route-source proposition, and the finite-divisor vertical- $IQ$  boundary now has an audited endpoint that returns this Gaussian-to-Step (xi) payload together with the  $C_{\Theta}$  dichotomy. Consequently the public finite-divisor route exposes the constructed Hodge–Arakelov/SHE/IPL/hull chain used for the raw comparison at the same boundary where the Step (x) packet data and external numeric bound enter. The finite-source form of this boundary now also has a no- $C_{\Theta}$  audited endpoint: before the ordered-real dichotomy is invoked, it returns the named Gaussian-to-Step (xi) audit together with the route-owned bridge, raw comparison, finite-source packet equalities, and vertical- $IQ$  target equalities. The bundled finite exact vertical- $IQ$  source now has the same audited  $C_{\Theta}$  boundary: one source package returns the named Gaussian-to-Step (xi) route audit, the exact vertical- $IQ$  Frobenioid-isomorphism precision flag, and the final dichotomy. This moves the strongest finite bad-local corridor’s public endpoint closer to the intended source-derived chain while still leaving the external numeric  $C_{\Theta}$  estimate explicit. The same bundled source now also exposes the corresponding raw audit endpoint before the  $C_{\Theta}$  estimate is supplied: it returns the named Gaussian-to-Step (xi) audit, exact vertical- $IQ$  precision, target log-Kummer calibration, the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, q-pilot log-Kummer non-interference, and the Step (x) upper-semi bound. This separates the source-derived Step (xi)/Step (x) corridor from the still-open numerical estimate in the public theorem surface. The same route also exposes the Remark 3.9.5(Ob5) bounded-family quotient mechanism: for any two nonempty Theorem 3.11 possible images, the endpoint proves that both lie in the record possible-image family hull and have the same image under the upper-semi quotient by that hull. The audit carries the determinant log-volume identification, the family-union-to-family-hull inequality, the normalized tensor-power equality, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, so the “do not choose a convenient possible image as canonical” guard is visible before the finite Step (x) vertical- $IQ$  source and the external  $C_{\Theta}$  bound enter. The route source now owns the assembled source-derived bridge via a `toSourceDerivedBridge` projection, and the finite-divisor vertical  $IQ$  theorem consumes that route-owned bridge instead of spelling out the generic bridge constructor at the Step (x)

boundary. This separates the Step (xi) comparison and bridge assembly from the later finite Step (x) and  $C_\Theta$  boundary. Its finite Step (x) boundary now also has a packet-source form: the public all-in-one route can consume a `NonarchimedeanFiniteDivisorPacketLocalSource` directly, so the divisor packet, mono-analytic theater, and packet-local log-volume equalities are audited inside the named Step (x) source object rather than repeated as loose endpoint arguments. The same public route now exposes the finite-source Step (x) boundary before applying the  $C_\Theta$  numeric bound: the endpoint records the route-owned IPL datum and log-volume preservation, the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, the packet-local source log-volume chain, and the vertical- $IQ$  target identifications from the supplied finite-source and target-source records. A tighter exact vertical- $IQ$  variant now consumes a `NonarchimedeanThetaRootExactVerticalIQRealifiedEntrySource` instead of a separate target-source record: the endpoint projects the retained log-Kummer vertical- $IQ$  calibration source, the Kummer/forgetting transfer guards, and the exact target before applying the same  $C_\Theta$  boundary. The current strongest public endpoint packages these data into one bundled exact-route source object, so the route, upper-semi entry, finite Step (x) source, and exact vertical- $IQ$  source are audited as projections before the external numeric bound enters. Its realified Step (x) correspondence endpoint now exposes the theta-root canonical generator, nonzero canonical label, Kummer/forgetting log-volume preservation, q-pilot log-Kummer non-interference, and the local-object upper-semi bound from the same bundled exact source. Its source-derived corridor endpoint additionally records the history-separated Hodge/SHE transport guard, certificate-pinned IPL datum, IPL log-volume preservation, possible-image hull containment,  $q_{\text{signed}} \leq \theta_{\text{signed}}$ , exact vertical- $IQ$  calibration, and Step (x) non-interference in one audit statement. The Gaussian-front corridor endpoint extends this by projecting the Hodge–Arakelov theta-evaluation source’s canonical label, Gaussian degree normalization, square-weight formula, full-label compatibility, and target chart comparison before entering the same Hodge/SHE, IPL, hull, and Step (x) chain. A determinant-refined Gaussian corridor endpoint now keeps the Step (xi) determinant payload visible in this same bundled exact route: after the Hodge–Arakelov Gaussian data it projects the target-chart/source theta-monoid comparison, finite adjusted-summand formula, family-hull determinant log-volume equality, package measure calibration, determinant tensor bound, raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, exact vertical- $IQ$  calibration, q-pilot log-Kummer non-interference, and the Step (x) upper-semi estimate. The direct-labelled Step (x) finite-divisor route now also has a source-derived Hodge/SHE/IPL/hull form. Instead of taking the older route-alignment record, a free square-weight profile, and a separate theta-root source, this boundary projects the route alignment and canonical square-weight profile from the source-derived bridge and reads the theta-root package from the source Hodge–Arakelov side of the finite Hodge/SHE transport. It still constructs the finite-divisor packet-local source before entering the exact vertical- $IQ$  target route. The source-calibrated vertical- $IQ$  route now has this projection form as well: the log-Kummer packet source-calibration remains explicit, while the route alignment, canonical square-weight profile, and theta-root package are obtained from the source-derived bridge before the theta-root realified Step (x) source is constructed. The earlier realified-entry vertical- $IQ$  audit endpoint has also been given the same source-derived projection boundary. Its public theorem still takes the realified Step (x) source and the exact vertical- $IQ$  target as inputs, because those are the objects whose target-side  $FMOD$  and packet-local audit facts are being reported, but the Hodge/SHE/IPL/hull alignment and canonical square-weight profile are now read from the source-derived bridge rather than supplied independently. The theta-root packet-local entry route has the same source-derived form. The entry membership, Kummer/forgetting compatibilities, packet-local source/mono-analytic equalities, and the two (Ind3) real equalities remain visible Step (x) inputs, while the theta-root source, canonical square-weight profile, and Hodge/SHE/IPL/hull route alignment are projected from the source-derived bridge. The ordered-real-line packet-local



variant now factors through this same source-derived entry route: the ordered alignment supplies the packet-source and theta-target (Ind3) equalities, while the bridge supplies the route alignment, canonical profile, and theta-root source. The constant- $ZMod_l$  packet-normalized variant has the same projection boundary. The packet route still supplies the theta-average normalization after the theta-source guard is applied, and the ordered alignment still supplies the (Ind3) real equalities, but the Hodge/SHE/IPL/hull alignment, canonical profile, and theta-root source are projected from the source-derived bridge. The upper-semi  $ZMod_l$  entry specialization now follows this same source-derived route: the upper-semi source packages the chosen nonarchimedean entry together with its membership proof, and the bridge supplies the route alignment, canonical profile, and theta-root source. The source-calibrated  $ZMod_l$  route has also been projected through the source-derived bridge. The packet/source calibration object remains the Step (x) input, but the Hodge/SHE/IPL/hull alignment, canonical profile, and theta-root source are no longer separate public arguments. The labelled-average refinement of this source-calibrated route has the same projection boundary. The finite  $ZMod_l$  labelled procession average and its packet-normalized comparison remain visible Step (x) data, while the route alignment, canonical profile, and theta-root source are supplied by the source-derived bridge. The source-aligned labelled-average route has also been given this bridge projection. Its packet-local source-alignment object remains the Step (x) input, while the source-derived bridge supplies the Hodge/SHE/IPL/hull alignment, canonical profile, and theta-root source. The finite-source labelled-average route now follows the same pattern. The finite divisor packet source still supplies the packet-local source alignment, while the source-derived bridge supplies the route alignment, canonical profile, and theta-root source before entering the source-aligned labelled-average boundary. The finite-divisor labelled-average compatibility route now has the same projection form. Its divisor/Frobenioid packet data is still bundled into the finite Step (x) source object, while the source-derived bridge supplies the route alignment, canonical profile, and theta-root source. The theta-labelled source-aligned variant now has the same bridge boundary. The labelled capsule average alignment still derives the theta-source average from finite labelwise averaging, while the source-derived bridge supplies the route alignment, canonical profile, and theta-root source. The named source-aligned vertical- $IQ$  route now has the same projection boundary: the packet-local source-alignment object remains the Step (x) input, but the route alignment, canonical square-weight profile, and theta-root package are obtained from the source-derived Hodge/SHE/IPL/hull bridge. The packet-local vertical- $IQ$  compatibility route has the same source-derived bridge form. This variant keeps the packet-local Kummer/forgetting and (Ind3) source alignments explicit, but obtains the Hodge/SHE/IPL/hull alignment, canonical square-weight profile, and theta-root source by projection from the separated source-derived bridge. It now also has the all-in-one target-charted Hodge/IPL/determinant possible-image source form: the public packet-local route consumes that source object directly and projects the source-derived bridge internally before entering the packet-local vertical- $IQ$  comparison. The corresponding no- $C_\Theta$  packet-local endpoint is now exposed as well: it returns the all-in-one source-derived bridge audit, the exact vertical- $IQ$  target audit, and the three packet-local Step (x) source equalities before the external numeric bound is introduced. A choice-linked variant of this no- $C_\Theta$  packet-local endpoint now exposes the constructed IPL choice links at the same boundary: for every possible output choice, the constructed link has source equal to the bridge's input prime strip and target equal to that choice's prime strip, before the raw signed comparison and exact vertical- $IQ$  target audit are consumed. The experiment surface exposes this review target with the suffix `choiceLinkedBoundaryEndpoint`. The ordinary finite-divisor Step (x) route now has the same projection boundary: the finite-divisor packet-local source is still constructed from the divisor/Frobenioid packet data, while the Hodge/SHE/IPL/hull alignment, canonical square-weight profile, and theta-root package are read from the source-derived bridge. This gives

the experiment surface a finite-divisor vertical- $IQ$  theorem whose public route inputs no longer include the older alignment/profile/theta-root triple. At the Step (xi) boundary, the strongest public Hodge–Arakelov route can now consume the holomorphic-hull/determinant source object directly. This is a review-surface improvement rather than a closure of Step (xi): the source object still contains the holomorphic hull shadow, weighted determinant source, tensor-power bound, bridge equality, positivity, and normalization. The *Lean* source now also names this trust boundary explicitly as a constructor-built Step (xi) boundary audit: it records the selected possible-image q-region, the internally built Theorem 3.11 hull/determinant constructor and obligations object, the record-canonical hull/tensor bridge equality, the tensor-power determinant bound, q-positivity, normalization, and the raw signed comparison in one review target. The corresponding canonical-one constructed-IPL finite-divisor endpoint exposes this named audit before entering the packet/vertical- $IQ$  boundary. The stronger charted Hodge-calibrated family-hull source now reduces to this constructor-built boundary as well. In this reduction, the possible-image q-region is fixed by the Theorem 3.11 record,  $\theta_{\text{signed}}$  is read through the transported pre-ledger theta chart and the Hodge–Arakelov theta-monoid degree, the tensor-power bound is derived from the record-family-hull log-volume calibration, and the bridge datum, q-positivity, and normalization are projected from one hull/determinant obligations object. This gives the constructor-built audit a stronger source-facing predecessor rather than treating its bound and side conditions as free fields. The synchronized target-charted possible-image summand/family-hull source now feeds the same constructor-built boundary through a named reduction audit. This adds the target-chart/source theta-monoid comparison and the finite adjusted summand equality to the review surface before the data is forgotten to the charted Hodge/family-hull constructor audit. The record-hull finite-divisor endpoint can now consume the constructor-built possible-image Step (xi) source object directly. Thus the operation identifiers, selected possible-image q-region, determinant source, Ob3/Ob5 compatibility, measure calibration, tensor-power bound, hull/determinant bridge equality, q-positivity, and normalization are projected from one constructor source before the packet-local vertical- $IQ$  comparison is invoked. The experiment wrapper `possibleImageConstructorBuiltRecordHullFiniteDivisorVerticalIQ_cThetaDichotomy` exposes this as the public  $C_\Theta$ -dichotomy surface. The  $q \subseteq P_{\text{rec}}$  containment now has a stronger choice-linked source form, where  $q \subseteq P_{\text{choice}}$  is supplied and  $q \subseteq P_{\text{rec}}$  is derived from the possible-image union. This choice-linked source also projects to the formal Step (xi-e/f/g) upper-ray record: the q-pilot log-volume is shown to lie in the upper ray, to be bounded by the determinant log-volume, and to have matching input/output q-pilot readings. A stricter exact-theta variant now replaces the free tensor-power-bound field by the equality  $\theta_{\text{signed}} = \text{NormVol}(\text{Ob4Det})$ , from which Lean derives the bound used by the older constructor. The side-conditioned exact-theta variant additionally projects q-pilot positivity and normalization from the existing Stage 1 side-condition object, rather than carrying these as independent Step (xi) fields. A further hull/det-data-backed variant projects the package bridge equality from the existing hull/determinant source-data object and then records only the compatibility of that stored bridge with the record-canonical Step (xi) construction. The exact-theta data-backed source now also has a possible-image-native form: its q-pilot region is definitionally the chosen Theorem 3.11 possible image, so  $q \subseteq P_{\text{choice}}$  is projected by reflexive membership before the same data-backed source is constructed. The experiment surface exposes both this source audit endpoint and the corresponding finite-divisor vertical- $IQ$   $C_\Theta$  route. The newest record-native bounded-family variant replaces the loose exact tensor-power equality by the source-shaped assertion that  $\theta_{\text{signed}}$  is the log-volume of the Theorem 3.11 possible-image family hull; the normalized tensor-power equality is then derived from the Ob5 determinant compatibility. That variant is now wired into the finite-divisor vertical- $IQ$  endpoint chain through a dedicated source-derived bridge constructor, rather than through the older backed exact-theta

source. The same bounded-family data-backed source now has a possible-image-native form: the q-pilot region is definitionally the selected Theorem 3.11 possible image, while the Ob5-shaped equality  $\theta_{\text{signed}} = \text{Vol}_{\log}(H_{\text{fam}})$  remains the source datum. The constructed-IPL finite-divisor endpoint and the experiment surface expose this stronger family-hull route. This route is now visible at the source-derived bridge boundary as well: a calibrated Hodge–Arakelov synchronization supplies the finite Hodge/SHE transport and theta/Hodge calibration, the constructed-IPL source supplies the input-prime-strip link, and the possible-image family-hull source supplies the fixed q-region and Ob5 log-volume comparison before the finite-divisor vertical- $IQ$  theorem is applied. The same possible-image family-hull route now has an obligations-backed source form: the package hull/determinant bridge data, q-pilot positivity, and normalization are projected from one `IUTStage1SourceHullDetObligations` object, while the q-region remains definitionally the chosen Theorem 3.11 possible image. The experiment surface exposes both the bridge audit and the calibrated finite-divisor  $C_{\Theta}$ -dichotomy for this obligations-backed route. A further Hodge-calibrated possible-image form removes the raw  $\theta_{\text{signed}} = \text{Vol}_{\log}(H_{\text{fam}})$  field from this public source: the equality is derived through the Hodge–Arakelov theta-monoid degree carried by the same synchronization object that constructs the finite Hodge/SHE transport. The bridge audit and finite-divisor endpoint now expose this Hodge-calibrated possible-image route. A charted variant now derives the package theta/Hodge equality through the transported pre-ledger theta chart before entering the same possible-image Hodge/family-hull route, and the experiment surface exposes its bridge audit and finite-divisor  $C_{\Theta}$ -dichotomy endpoint. The remaining task is to construct the underlying fields from the source-paper holomorphic-hull and determinant operations. The experiment surface now also exposes the record-native Step (xi) hull/determinant corridor directly. One endpoint presents the constructed IPL variant from finite Hodge/SHE transport plus the record possible-image union and canonical Ob4/tensor-power hull data. A stronger endpoint presents the history-separated, certificate-pinned IPL variant: finite Hodge/SHE transport is built from the source and target Hodge–Arakelov theta-evaluation sources and the record’s history-separated descent permission, while the IPL boundary is the certificate link source. The constructed-IPL record-hull endpoint now also has a side-conditioned form: q-pilot positivity and source normalization are projected from the shared Stage 1 side-condition object instead of appearing as independent Step (xi) hull/determinant fields. The same side-conditioned record-hull endpoint now has a possible-image form: the q-pilot region is no longer supplied as an arbitrary set with a separate containment proof in the record possible-image union. It is fixed to the possible-image region of a chosen Theorem 3.11 output, and Lean derives the union containment internally. This possible-image source now also has its own holomorphic-hull/log-volume endpoint. Before any Hodge/SHE/IPL route wrapper is used, Lean projects certification, the SHE datum, equality with the record possible-image union, containment in the applied holomorphic hull, the  $\theta_{\text{signed}}$  log-volume bound, q-pilot positivity, normalization, and the raw comparison  $q_{\text{signed}} \leq \theta_{\text{signed}}$  from the single possible-image Step (xi) source object. The target-charted Hodge/determinant possible-image source now also has its own holomorphic-hull/log-volume endpoint and canonical hull/tensor-power bridge endpoint. The first projects certification, the SHE datum, equality with the record possible-image union, containment in the applied holomorphic hull, the  $\theta_{\text{signed}}$  log-volume bound, and the raw comparison. The second identifies the package common-container hull/determinant bridge with the record-canonical Theorem 3.11 possible-image bridge while retaining the Hodge-calibrated  $\theta_{\text{signed}}$  equality, tensor-power bound, side conditions, and raw comparison at the Step (xi) source boundary. The source-derived bridge itself now has a calibrated Hodge–Arakelov synchronization constructor. Given one calibrated source/target Hodge–Arakelov synchronization object, a constructed Theorem 3.11 IPL link, and a Step (xi) holomorphic-hull/determinant source, Lean constructs both the finite Hodge/SHE transport and the source

theta/Hodge log-volume calibration internally before entering the finite-divisor vertical-*IQ* route. The experiment surface exposes this as the calibrated-synchronization IPL-construction hull finite-divisor  $C_\Theta$ -dichotomy endpoint. The same calibrated route now has side-conditioned and possible-image side-conditioned Step (xi) variants. In the side-conditioned form, q-pilot positivity and source normalization are projected from the Step (xi) hull source; in the possible-image form, the q-pilot region is also fixed by the chosen Theorem 3.11 possible-image output. Thus the strongest experiment-facing endpoint now receives one calibrated Hodge–Arakelov synchronization object, one constructed IPL link source, and one possible-image side-conditioned hull/determinant source, rather than separate Hodge/SHE transport, source-calibration, profile, theta-root, q-region, and side-condition witnesses. The possible-image side-conditioned source now also has a direct bridge constructor and experiment-facing bridge audit endpoint. The constructor keeps the chosen Theorem 3.11 possible-image q-region visible at the Step (xi) boundary, then projects internally to the generic holomorphic-hull/determinant source before assembling the calibrated Hodge/SHE, constructed-IPL, and hull/determinant bridge used by the finite-divisor route. This strongest possible-image route now also exposes the raw signed Step (xi) comparison separately from the  $C_\Theta$  dichotomy. The theorem named `...qSigned_le_thetaSigned` on the experiment surface constructs the source-derived Hodge/SHE/IPL/hull bridge from the calibrated Hodge–Arakelov synchronization, the constructed Theorem 3.11 IPL link, and the possible-image side-conditioned hull/determinant source, then derives  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$  without assuming the later numeric bound  $\theta_{\text{Signed}} \leq C_\Theta \cdot (-q_{\text{Signed}})$ . A companion audit endpoint records that the q-pilot region is the chosen Theorem 3.11 possible-image region, that it lies in the record possible-image union, and that q-positivity and source normalization are projected from the shared side-condition object. This possible-image side-conditioned boundary now has an obligations-backed refinement. The new source object still fixes the q-pilot region to the chosen Theorem 3.11 possible image, but the package hull/determinant bridge datum, q-pilot positivity, and source normalization are projected from the shared `IUTStage1SourceHullDetObligations` object. The experiment surface therefore exposes a raw Step (xi) comparison whose audit payload identifies the package bridge with the obligations bridge datum before deriving  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$ . The same obligations-backed source has now been lifted through the finite-divisor vertical-*IQ*  $C_\Theta$ -dichotomy endpoint. Thus the current strongest calibrated possible-image finite-divisor route no longer takes q-positivity, source normalization, or the package hull/determinant bridge alignment as separate Step (xi) fields; these are read from the shared hull/determinant obligations object before applying the existing finite-divisor corridor. The later numeric input  $\theta_{\text{Signed}} \leq C_\Theta \cdot (-q_{\text{Signed}})$  remains an explicit hypothesis of the dichotomy theorem. There is now also an IPL-link variant of this same obligations-backed finite-divisor endpoint. It replaces the constructed-IPL source, and its certificate-equals-constructed-datum alignment, by the certificate-pinned Theorem 3.11 IPL link source. This does not construct the input-prime-strip link machinery; rather, it isolates the remaining IPL trust boundary to the two endpoint equalities identifying the certificate link source and target with the input and output prime strips, while the log-volume preservation is still read from the finite Hodge/SHE transport. A further Gaussian-to-Step (xi) audit starts this same comparison at the Hodge–Arakelov theta-evaluation source itself: canonical theta-root data, Gaussian zero/canonical/square-weight degree facts, and full-label log-volume calibration are projected before the constructed finite SHE transport, constructed IPL link, possible-image hull source, and raw  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$  comparison are read from the assembled bridge. This Gaussian audit now also has the obligations-backed possible-image form. Its endpoint starts from the same Hodge–Arakelov theta-evaluation source and constructed IPL link, but the Step (xi) source object additionally records that the package hull/determinant bridge is the datum supplied by the shared hull/determinant obligations. Thus the audit chain from theta-root/Gaussian data to  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$  now exposes the obligation-

projected hull bridge alignment at the same boundary as the raw comparison and finite-divisor dichotomy. The obligations-backed constructed-IPL synchronized route now also has a named Gaussian-to-Step (xi) audit proposition. This packages the theta-root and Gaussian data from the calibrated synchronization's source evaluation, the factored finite Hodge/SHE transport, constructed IPL transport, obligations-backed Step (xi) hull data, and raw signed comparison before the later Hodge–Arakelov history-separated wrappers are applied. The IPL-link refinement has now been lifted to these audit layers as well. The raw comparison endpoint  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$  and the Gaussian-to-Step (xi) endpoint can both use the certificate-pinned Theorem 3.11 IPL link source together with the obligations-backed possible-image hull source. Thus the audit chain from theta-root/Gaussian data through finite Hodge/SHE transport to the Step (xi) comparison no longer needs the constructed-IPL certificate-alignment field in this variant; it still keeps the two certificate link endpoint equalities explicit. This synchronized certificate-pinned IPL-link Gaussian payload now also has a named audit proposition, parallel to the synchronized constructed-IPL audit but without the constructed-datum equality. The two synchronized audit surfaces now mark exactly where the formal route switches from a certificate-pinned link to a constructed input-prime-strip link. The finite-divisor  $C_\Theta$ -dichotomy route now has the same unbundled Hodge–Arakelov source surface. Instead of receiving a calibrated Hodge–Arakelov synchronization record, the endpoint takes the source and target theta-evaluation sources, the canonical-one preservation equality, the certificate-pinned IPL link source, the obligations-backed possible-image hull source, and the separate theta/Hodge log-volume calibration. The finite Hodge/SHE transport and source-derived Hodge/SHE/IPL/hull bridge are assembled internally before the existing finite-divisor vertical-*IQ* theorem is applied. This removes one synchronization-bundle boundary from the strongest possible-image finite-divisor route, but it does not derive the later numeric input  $\theta_{\text{Signed}} \leq C_\Theta \cdot (-q_{\text{Signed}})$ . This same possible-image route now has a source-calibrated Hodge–Arakelov variant. The bridge constructor and experiment-facing finite-divisor theorem consume a calibrated Hodge–Arakelov theta-evaluation source, project the full-label theta/Hodge log-volume calibration internally, and then construct the finite Hodge/SHE transport, certificate-pinned IPL transport, and obligations-backed possible-image hull bridge. Thus the strongest possible-image finite-divisor surface no longer needs a standalone `IUTStage1SourceThetaHodgeLogVolumeCalibration` argument in this variant; the remaining external Step (xi) inputs are still the certificate-pinned IPL link source, the obligations-backed possible-image hull source, the finite divisor/log-Kummer data, and the later numeric  $C_\Theta$  bound. The raw Step (xi) comparison has now been exposed at this same source-calibrated boundary. The new  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$  theorem and its audit endpoint start from the calibrated Hodge–Arakelov theta-evaluation source, the target evaluation, canonical-one preservation, the certificate-pinned IPL link source, and the obligations-backed possible-image hull source. The audit records the projected theta/Hodge full-label calibration, the selected Theorem 3.11 possible-image q-region and containment in the record possible-image union, the obligations hull/determinant bridge alignment, the IPL certificate endpoint equalities, q-positivity, and source normalization before deriving the raw signed comparison, still without using the later  $C_\Theta$  numeric hypothesis. This source-calibrated boundary now also has a Gaussian-to-Step (xi) audit endpoint. It exposes the canonical theta-root generator and full label, zero/canonical/square-weight Gaussian degree equations, full-label calibration, factored SHE comparison level and coordinate equivalence, the certificate-pinned IPL-link log-volume preservation, possible-image hull containment and obligations bridge alignment, q-positivity, normalization, and the same raw signed comparison in one payload. This is the most direct current audit chain from the Hodge–Arakelov theta-evaluation source to  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$  for the finite nonarchimedean possible-image route. This certificate-pinned Gaussian-to-Step (xi) payload is now also promoted to a named audit proposition, and its finite-divisor route has a no- $C_\Theta$  boundary endpoint returning that audit together with the

finite-divisor Step (x) packet equalities, vertical- $IQ$  target equalities, and raw signed comparison. This gives a stable audit surface for the pre-construction IPL-link route, without asserting equality to a separately constructed IPL datum. The same source-calibrated possible-image route now also has the constructed IPL form. The bridge constructor, finite-divisor dichotomy, raw comparison, q-comparison audit, and Gaussian-to-Step (xi) audit can consume an input-prime-strip link construction source. The construction projects the link-source and link-target endpoint equalities internally; the remaining certificate-facing IPL condition at this boundary is the equality between the pre-ledger certificate datum and the datum generated by the construction. Thus this route removes another certificate-pinned IPL-link assumption from the finite nonarchimedean possible-image corridor, while still treating the existence of the input-prime-strip construction itself as Theorem 3.11 source data. The constructed-IPL Gaussian-to-Step (xi) payload is now also promoted to a named audit proposition, so later finite-divisor endpoints can cite this theta-root/Gaussian, history-separated Hodge/SHE, constructed IPL, and obligations-backed hull chain without restating the full conjunction. This named audit now also records the definitional provenance of the route components themselves: the bridge's finite Hodge/SHE transport is the one constructed from the history-separated Hodge-Arakelov evaluations, its IPL transport is the one obtained from the Theorem 3.11 construction source, and its hull constructor is the one induced by the possible-image obligations-backed Step (xi) source. The generated full-label to finite-divisor handoff has now been lowered one more step. The public experiment endpoint `generatedFullLabelFiniteDivisorVerticalIQStepXUpperRayRealization_cThetaDichotomy` no longer accepts independent real witnesses for the q-region and theta-hull log-volumes. Instead, both sides supply `IUTStage1StepXToHullUpperRayLogVolume` computations, so the signed q-values are read from q-pilot upper-ray log-volumes and the signed theta values are read from theta-hull log-volumes, with the determinant log-volume equalities retained in the audit. The remaining source payload is therefore sharply localized. Both sides are now constructor-backed: the generated side uses `GeneratedFullLabelConstructedStepXUpperRaySource`, while the finite nonarchimedean side uses `FiniteDivisorVerticalIQConstructedStepXUpperRaySource`. In each case a constructed Remark 3.9.5 hull/determinant source builds the canonical hull approximant, and a procession-normalized Step (x) corridor turns it into an `IUTStage1StepXToHullUpperRayLogVolume`. The cross-package equality of the finite and generated q-pilot and theta-hull readings is no longer a bare upper-ray assumption: `GeneratedFullLabelFiniteDivisorVerticalIQConstructedStepXUpperRaySignedGluingSource` derives it from the two constructed upper-ray signed-value identifications and the existing theta-class signed realization. This has now been lowered once more by `GeneratedFullLabelFiniteDivisorVerticalIQConstructedStepXUpperRayFiniteThetaClassImageLawGluingSource`: the selected theta-class realization is derived by specializing the finite theta-class image law at the selected nonarchimedean packet, constructing the finite theta-pilot class from its packet coordinates, and promoting the result to the signed gluing source. This boundary has been lowered again by `GeneratedFullLabelFiniteDivisorVerticalIQConstructedStepXUpperRayLabelTransportGluingSource`: the finite image law is projected from the source-level nonarchimedean label-transport layer, i.e. from the procession ( $\text{Ind}_1$ ) leg together with the retained nonarchimedean ( $\text{Ind}_2$ ) label-transport/source-packet audit. The constructed Step (x) endpoint has now been lowered once more by `GeneratedFullLabelFiniteDivisorVerticalIQConstructedStepXUpperRayPacketLabelGluingSource`: the completed label transport is reconstructed from packet-label geometry before the same finite image law and  $C_\Theta$  dichotomy are derived. The preferred constructed boundary is now `GeneratedFullLabelFiniteDivisorVerticalIQConstructedStepXUpperRayRawTensorLabelGluingSource`: same-theta-class packets supply raw midpoint/target nonarchimedean  $\text{Ism}$  tensor-

label equalities and the target Ism summand-kind law; Lean reconstructs packet labels, local label transport, the finite image law, and the final dichotomy. The preferred constructed boundary has now moved one layer closer to the source papers: `GeneratedFullLabelFiniteDivisorVerticalIQConstructedStepXUpperRayMatchedIdentifiedInd2ActionPack` consumes the matched identified source-level (Ind<sub>2</sub>) packet-action source directly, audits that the retained action agrees with the local nonarchimedean Ism action step, then projects the identified (Ind<sub>2</sub>), transported packet-label, packet-label, and finite image-law layers before applying the same  $C_\Theta$  dichotomy. The remaining Step (x) source lowering is now the concrete construction of this matched identified packet-action source from Hodge-theater, log-theta-lattice, and local tensor data. The same audit now exposes the finite SHE preservation facts used by that transport: the allowed forgetting predicate is the history-separated permission attached to the record's Hodge-theater descent bridge, and the transported full-label log-volume equality and transported-average equality are projected from the constructed finite Hodge/SHE transport. The constructed-IPL log-volume equality is now similarly sourced: the audit records that the route's IPL source log-volume is the finite Hodge/SHE source average and that its target log-volume is the transported target average, before using transported-average preservation to identify them. On the Step (xi) side, the same audit now exposes the weighted tensor-power determinant bound and the equality identifying the route hull/determinant bridge with the record-canonical possible-image hull/tensor-power construction. The constructed-IPL audit also projects the induced theta-pilot hull endpoint itself: its possible-image union is the record's theta possible-image union, this union lies in the constructed holomorphic hull, and the resulting hull has log-volume at most  $\theta_{\text{Signed}}$ . The synchronized calibrated constructed-route audit now exposes the same Step (xi) provenance one layer earlier: the record-canonical hull/tensor-power bridge, the weighted tensor-power determinant bound, and the induced theta-pilot hull endpoint are projected directly from the obligations-backed possible-image source before the history-separated source-calibrated wrapper is introduced. The certificate-pinned IPL-link version of this synchronized audit now exposes the same Step (xi) projections as well, so the pre-construction and constructed-IPL branches have the same visible possible-image hull/determinant provenance before the final finite-divisor boundary is applied. The same synchronized audit layer now also exposes the finite Hodge/SHE transport facts themselves: the target Hodge source is the synchronized target evaluation, the history-separated forgetful transport is allowed, and full-label log-volumes are preserved across the finite Hodge/SHE transport. Both synchronized audits now also expose the SHE-to-IPL log-volume handoff directly: the finite Hodge/SHE transported average is preserved, the route's IPL source log-volume is the finite Hodge/SHE source average, and the route's IPL target log-volume is the transported target average. The same finite-divisor route now has a no- $C_\Theta$  boundary endpoint returning this named audit together with the finite-divisor Step (x) packet equalities, vertical- $IQ$  target equalities, and raw  $q_{\text{Signed}} \leq \theta_{\text{Signed}}$  comparison, separating the source-derived Step (xi)/Step (x) provenance from the later numeric estimate. The corresponding finite-divisor  $C_\Theta$ -dichotomy endpoint now returns this named audit proposition together with the dichotomy, keeping the external numeric  $C_\Theta$  estimate as the only additional input at that boundary. The experiment surface now also has synchronized finite-divisor review wrappers: they consume the single Hodge-Arakelov synchronization object and return the synchronized Gaussian-to-Step (xi) audit directly, together with the same raw finite-divisor boundary or  $C_\Theta$ -dichotomy conclusion. This makes the finite bad-local endpoint display the route theta-root/Gaussian  $\rightarrow$  finite Hodge/SHE  $\rightarrow$  IPL  $\rightarrow$  possible-image hull before entering the later source-calibrated audit wrapper. The same bundled synchronized source now has the remaining-boundary ledger `SynchronizedRemainingSourceBoundaryAudit`, exposed by the experiment suffix `synchronizedRemainingBoundaryAudit`. It packages the Gaussian-to-Step (xi) audit, constructed

IPL log-volume endpoint, possible-image hull/determinant endpoint, finite Step (x) packet equalities, vertical- $IQ$  target facts, and raw signed comparison as projections from one source object. This gives the pre-matched synchronized corridor the same review shape as the later matched and side-conditioned exact corridors. The certificate-pinned IPL-link synchronized source now has the analogous remaining-boundary ledger `SynchronizedIPLLinkRemainingSourceBoundaryAudit`, exposed by the experiment suffix `synchronizedIPLLinkRemainingBoundaryAudit`. It packages the IPL-link Gaussian-to-Step (xi) audit, the certificate-pinned link source, possible-image hull/determinant endpoint, finite Step (x) packet equalities, vertical- $IQ$  target facts, and raw signed comparison, while deliberately leaving the construction of the IPL datum outside this pre-construction review surface. For review, these strongest finite-divisor endpoints are also exposed under the compact milestone prefix `sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ`, with boundary and  $C_\Theta$ -dichotomy variants carrying the `WithConstructedRouteAudit` suffix. These wrappers are definitionally just the constructed-route endpoints above; their purpose is to make the current review boundary easy to locate without renaming or hiding the longer source-calibrated audit theorem. The compact milestone prefix now also has all-in-one route variants. The no- $C_\Theta$  wrapper with suffix `boundaryEndpointWithAllInOneRouteBridgeAudit` consumes the target-charted Hodge/IPL/determinant possible-image route source directly and returns the route bridge audit together with the finite Step (x) packet and vertical- $IQ$  target equalities. The corresponding  $C_\Theta$ -boundary suffix `cThetaDichotomyWithAllInOneRouteGaussianStepXIAudit` returns the all-in-one Gaussian-to-Step (xi) audit before applying the same external numeric  $C_\Theta$  estimate. Thus the compact review surface can now point to the stricter route object that packages the Hodge–Arakelov synchronization, finite Hodge/SHE transport, constructed IPL handoff, and record-native possible-image hull/determinant payload in one source-facing input. The same conditional boundary now also has the stronger compact suffix `cThetaDichotomyWithAllInOneRouteBridgeAudit`. This endpoint returns the full route bridge audit next to the dichotomy, rather than only the Gaussian-to-Step (xi) subaudit, while still keeping the numeric  $C_\Theta$ -upper estimate as an explicit external hypothesis. The target-charted experiment surface has parallel suffixes `routeBridgeAuditEndpoint` and `matchedRouteBridgeAuditEndpoint`; the latter records the theta-monoid-matched route bridge audit beside the same conditional  $C_\Theta$  conclusion. The all-in-one route bridge audit now also carries the named `TargetChartedHodgeSHEIPLConstructionAudit` as a field, and the compact experiment suffix `allInOneRouteHodgeSHEIPLAudit` exposes it directly. This means the milestone-facing route bridge reports the theta-root/Gaussian evaluation, factored SHE preservation, finite Hodge/SHE transport, constructed IPL log-volume transport, and finite-transport log-volume provenance before the Step (xi) hull/determinant payload or finite Step (x) boundary is used. At the bridge-constructor level, the calibrated Hodge–Arakelov constructed IPL bridge can now consume the constructor-built possible-image Step (xi) hull/determinant source directly. The core constructor of `CalibratedHodgeSynchronizationT1IPLConstructionAndPossibleImageConstructorBuiltHullSources` exposes, through the experiment suffix `calibratedSynchronizationIPLConstructionPossibleImageConstructorBuiltHull_bridgeEndpoint`, the constructed IPL datum, finite Hodge/SHE synchronization, constructor-built Step (xi) source endpoint, record-canonical Step (xi) audit, compact boundary audit, and remaining-payload ledger from the same source object. The same constructor-built Step (xi) source now separates its  $Ob1/Ob2$  holomorphic-hull absorption passage as `ConstructorBuiltOb1Ob2HullAbsorptionAudit`, exposed by the experiment suffix `possibleImageConstructorBuiltHullSource_ob1Ob2HullAbsorptionAudit` and carried by the bridge endpoint. This audit records that the selected q-pilot region is a Theorem 3.11 possible image, lies in the record possible-image union, and is absorbed by the canonical holomorphic hull before determinant/tensor-power data enters.



The constructor-built Step (xi) source now also separates its Ob3/Ob4 determinant/tensor-power passage as `ConstructorBuiltOb3Ob4DeterminantAudit`, exposed by the experiment suffix `possibleImageConstructorBuiltHullSource_ob3Ob4DeterminantAudit` and carried by this bridge endpoint. The audit records weighted determinant summation, determinant normalization, hull-log-volume compatibility, the naive Frobenius tensor-power bound, and the determinant upper-ray comparison before the remaining-payload ledger adds q-choice, record-canonical bridge, positivity, and normalization fields. The same boundary now separates the Ob3/Ob5 determinant-compatibility chain as `ConstructorBuiltOb3Ob5DeterminantCompatibilityAudit`, exposed by the experiment suffix `possibleImageConstructorBuiltHullSource_ob3Ob5DeterminantCompatibilityAudit`. This audit derives the canonical hull-log-volume equality with the determinant log-volume by composing hull-log-volume compatibility with the normalized weighted determinant and the Ob3/Ob4 determinant normalization theorem, so this equality is no longer presented as an independent remaining-payload input. The theta-monoid-matched all-in-one route now has the same stronger no- $C_\Theta$  boundary surface with suffix `boundaryEndpointWithMatchedRouteBridgeAudit`. Its first component keeps the matched Gaussian audit together with the projected all-in-one route bridge audit, so the matched finite-divisor vertical- $IQ$  endpoint no longer drops the Hodge/SHE/IPL construction payload when it records that canonical one-label preservation was reconstructed from target/source theta-monoid degree equality. The all-in-one Gaussian-to-Step (xi) audit has also been strengthened at the Step (xi) boundary. Its public experiment endpoint with suffix `gaussianToStepXIHullDetAuditEndpoint` now projects the record possible-image union, containment in the constructed holomorphic hull, the holomorphic-hull log-volume bound, the family-hull/determinant and tensor-power equalities, and the record-canonical hull/tensor-power bridge equality from the same route audit. Thus the finite-divisor wrappers that return this audit now carry more than the final raw comparison: they expose the holomorphic-hull/determinant provenance used to obtain it. The same all-in-one route now also exposes the narrower determinant-source boundary via `targetChartedHodgeIPLDeterminantPossibleImageRoute_determinantSourceBoundaryAuditEndpoint`. This audit separates the two determinant payload fields still supplied at that boundary—the package measure calibration and the Hodge theta/summand equality—from the record-native family-hull facts that Lean derives: the record possible-image union, the family-hull/determinant equality, the family-union bound by the hull, tensor-power normalization, and the resulting tensor-power bound against  $\theta_{\text{Signed}}$ . This has now been tightened by the endpoint `targetChartedHodgeIPLDeterminantPossibleImageRoute_calibratedDeterminantSourceEndpoint`: the same route determinant payload is first viewed through a calibration-backed source object, so the Hodge theta/summand equality is projected from the target-charted summand calibration rather than exposed as a raw determinant field. The package measure identification remains the explicit determinant measure boundary. The stricter determinant payload has also been pushed through the possible-image Step (xi) source boundary. The endpoint `targetChartedHodgeIPLDeterminantPossibleImageRoute_calibratedPossibleImageSourceEndpoint` shows that the chosen q-region, record possible-image union, target-charted summand calibration, family-hull determinant facts, theta/family-hull equality, bridge alignment, and raw comparison are all projected from a calibration-backed possible-image source object. There is now also an all-in-one route object whose Step (xi) field is this calibration-backed possible-image source: `targetChartedHodgeIPLCalibratedPossibleImageRoute_sourceEndpoint` returns the projected Gaussian-to-Step (xi) audit together with the route’s IPL handoff, calibrated q-region, determinant measure calibration, target-charted summand facts, bridge alignment, and raw comparison. The finite-divisor boundary can now consume this calibrated route object directly as well.

The compact suffixes `boundaryEndpointWithCalibratedAllInOneRouteGaussianStepXIAudit` and `cThetaDichotomyWithCalibratedAllInOneRouteGaussianStepXIAudit` project to the existing finite Step (x) machinery only after the public route input has been tightened to the calibration-backed possible-image source. The calibrated route now also has matching review surfaces with `CalibratedGaussianStepXIAudit` suffixes; these return the calibrated possible-image audit directly, rather than only the projected audit for the older determinant possible-image route shape. The same boundary has now been refined once more by a measure-calibrated route object. The new source `IUTStage1MeasureCalibratedRecordBoundedFamilyHullDetLogVolumeSource` packages the record-native family-hull determinant source together with the identification of the package ledger measure with the induced hull log-volume measure. The all-in-one `IUTStage1TargetChartedHodgeIPLMeasureCalibratedPossibleImageRouteSource` threads this measured family-hull payload through the calibrated possible-image Step (xi) source, so the determinant payload no longer exposes the package measure equality as a direct field. The experiment surface now exposes `targetChartedHodgeIPLMeasureCalibratedPossibleImageRoute_toMeasureCalibratedGaussianStepXIAudit` and a matching finite-divisor boundary wrapper returning the measure-calibrated Gaussian-to-Step (xi) audit; both project to the older calibrated route only internally. The measure-calibrated boundary now has a constructor-backed refinement as well. The new constructor-backed possible-image source constructs its hull/determinant obligations via `ofRecordCanonicalHullTensorPowerOfQSubsetUnion`, using the record-canonical possible-image hull/tensor-power bridge. The matching all-in-one route therefore no longer carries an arbitrary possible-image hull/determinant obligations object at this boundary; it projects to the measure-calibrated route only after the constructor has produced those obligations. The experiment surface exposes this as a constructor-backed Gaussian-to-Step (xi) audit, a matching no- $C_\Theta$  finite-divisor boundary wrapper, and now also a matching finite-divisor  $C_\Theta$  dichotomy wrapper. Thus the final dichotomy surface can display the constructor-backed Step (xi) hull/determinant route before applying the still-external numeric  $C_\Theta$  estimate. The same calibration-backed route has now been pushed into the strongest bundled finite exact vertical- $IQ$  source as well. The experiment-surface calibrated finite-exact wrappers, with suffixes `boundaryEndpointWithCalibratedRouteAudit` and `cThetaDichotomyWithGaussianStepXIAudit`, consume one calibrated route/exact Step (x) package and project to the older exact finite-route theorem only internally. Thus the exact vertical- $IQ$  review boundary now displays the calibration-backed possible-image payload before the final external numeric  $C_\Theta$  estimate is supplied. The constructor-backed refinement has now been pushed through this bundled finite exact vertical- $IQ$  boundary too. Its exact route package exposes a constructor-backed Gaussian-to-Step (xi) audit, a source-derived corridor audit linking the constructor-produced hull/determinant data to the exact Step (x) calibration, and a matching  $C_\Theta$  dichotomy wrapper. The final dichotomy can therefore be reviewed from a single package whose Step (xi) payload is constructor-backed before the exact vertical- $IQ$  projection and the still-external numeric estimate are applied. The adjusted Ob3/Ob4 version of this exact route is now explicit as well. The source

```

IUTStage1TargetChartedHodgeIPLConstructorBacked
  MeasureCalibratedAdjustedPossibleImage
  FiniteExactVerticalIQRouteSource

```

keeps the adjusted-summand Step (xi) equalities

$$\text{familyHullLogVolume} = \text{adjustedSummandLogVolume} = \text{determinantLogVolume}$$

visible at the same exact vertical- $IQ$  boundary. Its public experiment wrappers expose the adjusted Gaussian audit, the source-derived corridor endpoint, and the corresponding  $C_\Theta$ -dichotomy end-

point; projection to the older constructor-backed exact route is used only to reuse the established Step (x) vertical- $IQ$  endpoint. The same adjusted exact route now has a theta-monoid-matched Hodge/IPL version. The source

IUTStage1TargetChartedThetaMonoidMatchedHodgeIPL  
 ConstructionConstructorBackedMeasureCalibrated  
 AdjustedPossibleImageFiniteExactVerticalIQSource

stores the matched Hodge/IPL construction source and the adjusted constructor-backed Step (xi) source as public fields, then projects to the ordinary adjusted exact source only internally. Its audit keeps the target/source theta-monoid degree equality, the adjusted exact-theta Step (xi) audit, and the exact vertical- $IQ$  facts together before the still-external numeric  $C_\Theta$  estimate is supplied. This matched adjusted source now also projects into the obligations-backed record-canonical corridor. The audit

MatchedAdjustedObligationsCorridorAudit

retains the matched adjusted Gaussian/exact audit and the adjusted exact-theta Step (xi) audit, then adds the projected matched obligations-backed record-canonical Gaussian corridor and the constructor-built finite-divisor route audit. Thus the strongest matched obligations boundary no longer loses the Ob3/Ob4 adjusted-summand provenance when it reviews the downstream finite-divisor route. This exact boundary now also has an assembled-source variant. Instead of storing the all-in-one constructor-backed route as a field, the package stores the target-charted Hodge/IPL construction source and the constructor-backed possible-image source separately, then builds the route only as an internal projection. The review surface therefore shows the constructed IPL datum, the constructor-produced Step (xi) obligations, the raw comparison, and the exact vertical- $IQ$  calibration in one source-derived corridor audit before the  $C_\Theta$  estimate is supplied. The exact boundary has now been tightened once more to a record-canonical constructor source. This source does not store the packaged constructor-backed possible-image object; it stores the measured determinant payload, q-choice, hull/determinant operation identifiers, record-canonical bridge equality, q-positivity, and normalization inputs from which the Theorem 3.11 hull/determinant constructor produces the Step (xi) source. Its experiment wrapper displays these constructor inputs together with the constructed IPL datum and exact vertical- $IQ$  calibration before the external numeric  $C_\Theta$  estimate is used. There is now an intermediate side-condition-backed form of the same record-canonical exact boundary. The side-conditioned source in `IUTStage1FrobenioidShift` keeps the measured determinant payload, q-choice, operation identifiers, and record-canonical bridge equality explicit, but replaces the separate q-positivity and source-normalization fields by one `IUTStage1SourceSideConditions` object. Its experiment-surface wrappers display the same corridor and  $C_\Theta$ -dichotomy payload as the direct record-canonical constructor route, while making the side-condition source a single audited dependency before projection to the older endpoint. An obligations-backed version of this record-canonical exact boundary now projects q-positivity, source normalization, and the package bridge-data alignment from a single `IUTStage1SourceHullDetObligations` object. It still exposes the measured determinant payload, q-choice, and record-canonical hull/tensor bridge equality, but the final Step (xi) constructor no longer takes q-positivity and normalization as independent fields at this exact boundary. The finite-divisor  $C_\Theta$ -route now has the same adjusted Ob3/Ob5 source form. The new source declaration with suffix `RecordOb3Ob5AdjustedPossibleImageFiniteDivisorVerticalIQ` starts from the record-canonical adjusted determinant log-volume source, derives the Ob4 tensor-power bound from the exact theta/family-hull equality, and projects the bridge equality, q-positivity, and normalization from the ambient hull/determinant obligations object before entering the constructor-built possible-image Step (xi) route. The experiment surface exposes this as

`recordOb3Ob5AdjustedPossibleImageFiniteDivisorVerticalIQ_cThetaDichotomy`. This route now has a constructed Remark 3.9.5 source object at the finite-divisor boundary. The source `IUTStage1Remark395ConstructedHullDeterminantFiniteDivisorVerticalIQSource` bundles the measured adjusted Ob3/Ob5 determinant source, the exact  $\theta_{\text{signed}}$ -as-family-hull equality, and the record-canonical obligations synchronization. Its endpoint proves that the package measure calibration, derived Ob4 tensor-power bound, obligations bridge equality, q-positivity, and source normalization are all projected from this single source object. The new finite-divisor theorem with suffix

`remark395ConstructedOb3Ob5Adjusted  
HullDeterminantFiniteDivisorVerticalIQ`

and experiment wrapper

`remark395ConstructedOb3Ob5Adjusted  
HullDeterminantFiniteDivisorVerticalIQ_cThetaDichotomy`

therefore remove the separate public measure-calibration and bridge synchronization arguments from this adjusted Ob3/Ob5 route. The constructed finite-divisor source now also projects the actual constructed Remark 3.9.5 Step (xi) object, rather than only the downstream constructor-built possible-image wrapper. The projection

`IUTStage1Remark395ConstructedHullDeterminantFiniteDivisor  
VerticalIQSource.toPossibleImageConstructedHolomorphicHull  
DeterminantSource`

fixes the q-region to the selected Theorem 3.11 possible image, derives its containment in the record possible-image union, exposes the package hull/determinant bridge equality, and records the two-step comparison

$$\mu_{\log}(qRegion) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}.$$

The experiment theorem `remark395ConstructedHullDeterminantFiniteDivisorVerticalIQSource_possibleIm` is the review-facing form of this Step (xi) projection. At the same finite-divisor boundary, the source now also carries the Ob1–Ob5 bridge audit

`IUTStage1Remark395ConstructedHullDeterminantFiniteDivisor  
VerticalIQSource.ConstructedFiniteDivisorOb1ToOb5BridgeAudit.`

It is projected through the constructor-built possible-image Step (xi) source and records q-region absorption into the holomorphic hull, Ob3/Ob5 hull-log-volume-to-determinant compatibility, the record-canonical bridge equality, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The experiment surface exposes it as `remark395ConstructedHullDeterminantFiniteDivisorVerticalIQSource_ob1ToOb5BridgeAudit`. The same finite-divisor source now also has the Ob5-refined quotient bridge

`IUTStage1Remark395ConstructedHullDeterminantFiniteDivisor  
VerticalIQSource.ConstructedFiniteDivisorOb1ToOb5QuotientBridgeAudit.`

For a comparison possible-image choice, and nonemptiness witnesses for the selected q-choice image and the comparison image, Lean projects the constructor-built bounded-family quotient theorem to this boundary. The audit records containment of both possible images in the family hull, collapse of both quotient images to the distinguished upper-semi quotient point, equality of the quotient images, the quotient-collapse iff statement, and the same source-derived chain

$$\mu_{\log}(qRegion) \leq \det_{\log}^{\text{norm}} \leq \theta_{\text{signed}}.$$

The experiment surface exposes this as `remark395ConstructedHullDeterminantFiniteDivisorVerticalIQSource`. This witness burden has been reduced at the same finite-divisor boundary:

`IUTStage1Remark395ConstructedHullDeterminantFiniteDivisor  
VerticalIQSource.qChoiceRegion_nonempty_of_qPilotRegion_nonempty`

derives nonemptiness of the selected Theorem 3.11 q-choice possible image from nonemptiness of the constructed q-pilot region, using the source equality  $q\text{Region} = P_{q\text{Choice}}$ . Consequently `remark395ConstructedHullDeterminantFiniteDivisorVerticalIQSource_ob1ToOb5QuotientBridgeAuditOfQP` requires only q-pilot-region nonemptiness plus a nonempty comparison possible image, and the canonical-qChoice specialization `remark395ConstructedHullDeterminantFiniteDivisorVerticalIQSource_ob1ToOb5QuotientBridgeAuditAtQC` uses a single q-pilot-region nonemptiness witness for both sides of the Ob5 quotient collapse. The same route now has a constructor-backed source form. The source

`IUTStage1Remark395ConstructorBackedConstructed  
HullDeterminantFiniteDivisorVerticalIQSource`

does not take an ambient hull/determinant obligations object. Instead it carries the common-container equality with the record-canonical hull/tensor bridge, q-pilot positivity, and source normalization; Lean then constructs `IUTStage1SourceHullDetObligations` from the Theorem 3.11 hull/determinant constructor. The experiment wrapper

`remark395ConstructorBackedConstructedOb3Ob5Adjusted  
HullDeterminantFiniteDivisorVerticalIQ_cThetaDichotomy`

is therefore the current strongest adjusted Ob3/Ob5 finite-divisor route: it keeps the final numeric  $C_\Theta$  estimate explicit, but no longer accepts an arbitrary obligations object together with a separate record-canonical bridge-data equality. This obligations-backed record-canonical exact corridor now also has a named audit proposition. The proposition packages the constructed IPL datum, the record-canonical Step (xi) bridge equality, the obligations-derived q-positivity and normalization witnesses, the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, and exact vertical- $IQ$  Frobenioid precision. The experiment surface exposes this compact audit object directly, so dependency review can target the strongest constructor-obligations route without replaying the long corridor conjunction. The same exact corridor now has a combined Gaussian/exact audit. This audit joins the constructor-backed Gaussian-to-Step (xi) route audit with the obligations-backed exact vertical- $IQ$  corridor audit for the same source package, and the  $C_\Theta$ -dichotomy wrapper now has a suffix returning this combined audit as its first conjunct. Thus the public endpoint can display the theta-root/Hodge–Arakelov Gaussian data, factored SHE preservation, constructed IPL transport, record-canonical Step (xi) constructor, obligations-derived side conditions, raw comparison, and exact vertical- $IQ$  precision through one named source object before the still-external numeric  $C_\Theta$  estimate is applied. The Hodge/SHE/IPL portion of this combined audit is now itself a named pre-Step (xi) audit on the target-charted Hodge–Arakelov IPL construction source. It packages the theta-root Gaussian evaluation, factored SHE preservation, finite Hodge/SHE transport, constructed input-prime-strip IPL transport, and finite-transport log-volume provenance before any record-canonical hull/determinant constructor is invoked. Consequently the strongest Gaussian/exact corridor points back to the same `hodgeIPLSource` for both the Hodge/SHE/IPL construction facts and the later Step (xi) route audit. The Hodge synchronization boundary has also been sharpened. The new theta-monoid-matched synchronization source replaces the public canonical one-label preservation proof by an equality of source and target Hodge–Arakelov

theta-monoid degrees. Lean then reconstructs canonical-one preservation from the finite Gaussian evaluation theorem that the canonical 1-label degree equals the theta-monoid degree on both sides. The compact finite-divisor wrappers with suffixes `WithThetaMonoidMatchedRouteAudit` expose this route before the external numeric  $C_\Theta$  estimate is used. This matching has now been pushed one layer further into the target-chart Hodge/IPL construction source. The matched construction source stores the theta-monoid degree equality and the constructed Theorem 3.11 input-prime-strip link, projects to the ordinary Hodge/IPL source by reconstructing canonical-one preservation internally, and then feeds the same determinant possible-image Step (xi) payload. The experiment surface exposes the matched source endpoint, its Hodge/SHE/IPL audit projection, and a finite-divisor  $C_\Theta$ -dichotomy wrapper. Thus the public determinant possible-image corridor can now consume a theta-degree-matched Hodge/IPL source directly, while the final numerical  $C_\Theta$  bound remains an explicit external input. The matched Hodge/IPL source has also been threaded through the all-in-one target-chart route source. The new route object stores the theta-degree-matched Hodge/IPL construction source and the determinant possible-image Step (xi) payload, then projects to the older all-in-one route only internally. Its matched Gaussian-to-Step (xi) audit contains the projected Hodge/SHE/IPL/hull chain together with the explicit target/source theta-monoid degree match and the matched Hodge/SHE/IPL construction audit. The experiment surface now exposes this matched route endpoint and a finite-divisor  $C_\Theta$ -dichotomy wrapper returning the matched audit before applying the still-external numerical estimate. There is now also a no- $C_\Theta$  finite-divisor boundary for this matched all-in-one route, exposed by the experiment suffix `boundaryEndpointWithMatchedGaussianStepXIAudit`. It returns the same matched Gaussian-to-Step (xi) audit together with the finite-divisor packet equalities, vertical- $IQ$  target equalities, and raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison before any numeric  $C_\Theta$  estimate is introduced. The matched route has now been carried into the assembled constructor-backed finite exact vertical- $IQ$  source. This source stores the theta-degree-matched Hodge/IPL construction source, the constructor-backed Step (xi) possible-image source, and the exact Step (x) vertical- $IQ$  package as separate public fields; the ordinary assembled constructor-backed exact source is only a projection. Its matched Gaussian/exact audit combines the matched all-in-one Gaussian-to-Step (xi) route audit, the constructor-backed hull/determinant audit, the exact vertical- $IQ$  target calibration, and the raw comparison before the external numerical  $C_\Theta$  estimate is supplied. The same theta-degree-matched Hodge/IPL input has now also reached the record-canonical constructor source. The matched record-canonical package stores the measured Hodge determinant source, the possible-image q-choice, the hull/tensor/determinant operations, the record-canonical bridge equality, the q-positivity and normalization side conditions, and the exact Step (x) vertical- $IQ$  data, while the ordinary record-canonical source is recovered only by projection. Its public audit records the matched assembled Gaussian/exact route together with the record-canonical hull/tensor bridge, the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, and exact Frobenioid precision. The numerical  $C_\Theta$  bound remains an explicit external input at this boundary. The matched record-canonical package has now been lifted through the obligations-backed record-canonical exact corridor as well. The new source keeps the theta-degree-matched Hodge/IPL construction public while projecting q-positivity, normalization, and bridge-data alignment from a single Step (xi) obligations object. Its review audit combines the matched record-canonical constructor audit with the existing obligations-backed Gaussian/exact corridor audit, so the strongest current endpoint records both the theta-monoid provenance of canonical-one preservation and the obligations-backed hull/determinant side conditions before the external numeric  $C_\Theta$  estimate is applied. The same obligations-backed exact corridor now also exposes a named pre-exact Step (xi) hull/determinant audit. This audit records the chosen Theorem 3.11 possible-image q-region, its containment in the record possible-image union, the measured family-hull/determinant provenance, the tensor-power

bound, the record-canonical hull/tensor bridge, the obligations-derived q-positivity and normalization witnesses, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. The combined Gaussian/exact audit now contains this Step (xi) hull/determinant audit as a separate field, so the route can be reviewed between the Hodge/SHE/IPL construction and the exact vertical- $IQ$  fields without unpacking the final  $C_\Theta$  dichotomy theorem. The obligations-backed record-canonical source also now has a no- $C_\Theta$  raw-comparison endpoint at this same level. The endpoint returns the combined Gaussian/exact audit, the exact vertical- $IQ$  target-calibration and Frobenioid-precision facts, the finite Step (x) packet/product equalities, the q-pilot log-Kummer non-interference witness, the upper-semi inequality, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, all before the external numeric  $C_\Theta$  estimate is supplied. The experiment surface now exposes this no- $C_\Theta$  target by the milestone-facing suffix **boundaryEndpointWithThetaMonoidMatchedRecordCanonicalGaussianExactCorridorAudit**.

Thus the newest review target separates the source-derived Hodge/SHE/IPL/Step (xi) and exact Step (x) corridor from the final ordered-real dichotomy. At the same source level, the code now exposes a remaining-boundary ledger **ObligationsRecordCanonicalConstructorRemainingSourceBoundaryAudit**. This ledger does not add a new comparison theorem. Instead it records, in one kernel-checked proposition, the constructed IPL link and Hodge/SHE/APT transport audit, the determinant source-boundary audit, the pre-exact Step (xi) hull/determinant audit, the exact corridor audit, the finite-divisor packet equalities, and the vertical- $IQ$ /log-Kummer boundary facts. Its purpose is to make the next paper-facing obligation precise: construct the still-public operation identifiers, q-choice, measure-calibrated determinant source, hull/determinant obligations object, upper-semi entry, and exact vertical- $IQ$  source from IUT I–III data rather than supplying them as fields of the strongest corridor source. The same obligations-backed record-canonical source now also projects directly to the constructor-backed, measure-calibrated possible-image Step (xi) source. The new audit **ObligationsRecordCanonicalConstructorBackedStepXIISourceAudit** records the constructor-backed Step (xi) endpoint, its measure-calibrated possible-image projection, and the assembled finite exact source endpoint. The combined Gaussian/exact audit and the remaining-boundary ledger include this constructor-backed Step (xi) audit, so the strongest exact corridor can now be reviewed either as the expanded record-canonical field list or as the source-facing Step (xi) object built from that list. The constructor-backed Step (xi) source itself now has a named audit, **ConstructorBackedStepXIISourceHullDetAudit**. It records the chosen Theorem 3.11 possible-image q-region, the measure-calibrated determinant source, the constructed hull/determinant obligations object, the record-canonical hull/tensor bridge, q-positivity, normalization, and the raw comparison. The assembled exact source now also has **AssembledConstructorBackedRemainingSourceBoundaryAudit**, exposed on the experiment surface with suffix **remainingBoundaryAudit**. This is the direct review target corresponding to the Step (xi) passage in IUT III from the Theorem 3.11 multiradial output through holomorphic hulls, determinants/tensor powers, and log-volume, before the remaining finite Step (x) and vertical- $IQ$  inputs are discharged. There is now also a side-conditioned constructor-backed Step (xi) source. Its experiment endpoint, with suffix **SideConditionedConstructorBackedMeasureCalibratedPossibleImage\_sourceEndpoint**, projects q-pilot positivity and source normalization from one **IUTStage1SourceSideConditions** object before building the constructor-backed hull/determinant source. This removes two more flat public propositions at the low-level Step (xi) constructor boundary. The same low-level source now has the named audit **SideConditionedConstructorBackedStepXIISourceHullDetAudit**. It packages the selected possible-image q-region, the constructor-backed hull/determinant provenance, the side-condition-derived q-positivity and normalization, and the raw signed comparison as one reusable Step (xi) proposition. The strongest matched side-conditioned

exact corridor now consumes this audit directly before projecting to the constructor-backed and obligations-backed exact route. The theta-monoid-matched obligations-backed record-canonical corridor now has the same explicit source-facing exposure. Its new audit `MatchedObligationsRecordCanonicalConstructorBackedStepXISourceAudit` records the matched theta-degree equality, the projected constructor-backed Step (xi) source audit, and the matched assembled Gaussian/exact route audit. The matched Gaussian/exact corridor includes this audit as a separate field, and the experiment surface exposes it directly, so the matched route can be reviewed at the constructor-backed Step (xi) boundary without first unfolding the ordinary projection. It now also has the matched remaining-boundary ledger `MatchedObligationsRecordCanonicalConstructorRemainingSourceBoundaryAudit`, exposed by `sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ_thetaMonoidMatchedRecordCanonicalRemainingBoundaryAudit`. This ledger keeps the matched Gaussian/exact audit and matched constructor-backed Step (xi) audit next to the ordinary projected ledger of still-public source-paper inputs. The point is not to close those inputs, but to make the strongest theta-monoid-matched corridor display the exact remaining operation, q-choice, determinant, hull/determinant-obligation, upper-semi, and exact vertical-*IQ* construction boundary. Finally, this strongest source package now has a milestone-facing  $C_\Theta$ -dichotomy alias using the existing source-derived finite-divisor endpoint prefix and the suffix `withRecordCanonicalGaussianExactCorridorAudit`. It specializes the source-derived endpoint to the obligations-backed record-canonical exact corridor and returns the combined Gaussian/exact audit. The experiment surface exposes the same theorem with the suffix `cThetaDichotomyWithRecordCanonicalGaussianExactCorridorAudit`. The record-native possible-image hull route has also gained an obligations-derived side-condition form. The new experiment wrapper uses the ambient `IUTStage1SourceHullDetObligations` object to supply q-pilot positivity and source normalization. The possible-image choice, record-canonical hull/tensor bridge equality, determinant source, and external numeric  $C_\Theta$  estimate remain explicit, but the route no longer takes an independent `IUTStage1SourceSideConditions` record at this boundary. This same tightening now sits behind the history-separated Hodge–Arakelov surface: the finite Hodge/SHE transport is constructed from the source and target Hodge–Arakelov theta-evaluation sources and the record’s separated descent permission, while the Step (xi) side conditions are still projected from the ambient hull/determinant obligations. This history-separated possible-image obligations route now also has an audited  $C_\Theta$ -surface. The wrapper returns the Hodge–Arakelov canonical one-degree match, the containment of the chosen Theorem 3.11 possible image in the record possible-image union, the record-canonical hull/tensor bridge alignment, and the obligations-derived q-positivity and normalization witnesses alongside the final dichotomy. Thus the strongest currently exposed record-native finite-divisor endpoint can be reviewed at the source-data boundary without unpacking the long theorem statement. The certificate-pinned IPL-link record-hull path now has the same side-conditioned tightening. The new endpoint suffix `IPLLinkRecordHullSideConditionedFiniteDivisorVerticalIQ` projects q-pilot positivity and source normalization from `IUTStage1SourceSideConditions` before calling the older certificate-pinned record-hull route. Its history-separated Hodge–Arakelov wrapper uses the same side-condition object, so this public IPL-link boundary no longer needs those two witnesses as separate arguments. The experiment module now exposes both versions directly. The suffix `sideConditionedIPLLinkRecordHullFiniteDivisorVerticalIQ` is the finite Hodge/SHE transport form; the history-separated variant uses the `RecordHullSideConditionedFiniteDivisorVerticalIQ` suffix after constructing the transport from Hodge–Arakelov theta evaluations. These wrappers make the review-facing certificate-pinned IPL-link surface match the side-conditioned core theorem. It now also matches



the possible-image obligations tightening available on the constructed-IPL side. The suffix `iplLinkPossibleImageObligationsRecordHullFiniteDivisorVerticalIQ` uses a chosen Theorem 3.11 possible-image  $q$ -choice, derives the  $q$ -region's containment in the record possible-image union internally, and projects  $q$ -pilot positivity and normalization from the ambient `IUTStage1SourceHullDetObligations` object. Its history-separated Hodge–Arakelov companion, `historySeparatedIPLLinkPossibleImageObligationsRecordHullFiniteDivisorVerticalIQ`, constructs the finite Hodge/SHE transport from the two theta-evaluation sources before applying the same certificate-pinned IPL-link possible-image obligations route. The compact synchronized route suffix now consumes one Hodge–Arakelov synchronization object at this boundary, so the source calibration, target evaluation, and canonical one-label preservation no longer appear as separate public inputs on the review-facing theorem. The  $\text{no-}C_\Theta$  finite-divisor boundary now returns this strengthened audit as well, via the compact suffix `boundaryEndpointWithAllInOneRouteGaussianStepXIAudit`. This gives a raw Step (x) endpoint whose payload is the same all-in-one Gaussian-to-Step (xi) chain used by the later  $C_\Theta$ -dichotomy wrapper, before any numeric  $C_\Theta$  estimate is supplied. There is now also a  $C_\Theta$ -boundary suffix `cThetaDichotomyWithAllInOneRouteHullDetGaussianStepXIAudit`; it displays the same holomorphic-hull and determinant bridge fields next to the final dichotomy. This keeps the finite-divisor review surface aligned between the raw and  $C_\Theta$  endpoints. The synchronized Hodge/SHE/constructed-IPL/possible-image route now also has a finite-divisor vertical- $IQ$  source object. This source object stores the calibrated Hodge–Arakelov synchronization, constructed Theorem 3.11 IPL source, obligations-backed possible-image Step (xi) hull source, finite-divisor packet, Kummer/forgetting compatibilities, and vertical- $IQ$  target source together. Its experiment-facing boundary and  $C_\Theta$ -dichotomy aliases therefore take one source package plus the external numeric estimate, while projecting the same Gaussian-to-Step (xi) audit and Step (x) finite-divisor/vertical- $IQ$  endpoint facts internally. There is now also a bundled certificate-pinned IPL-link version of this finite-divisor source object. It packages the synchronized Hodge–Arakelov data, the Theorem 3.11 IPL-link source, the obligations-backed possible-image Step (xi) source, finite-divisor packet, Kummer/forgetting compatibilities, and vertical- $IQ$  target source before the constructed IPL datum is introduced. The experiment suffixes `boundaryEndpointWithIPLLinkGaussianStepXIAudit` and `cThetaDichotomyWithIPLLinkGaussianStepXIAudit` expose the raw boundary and conditional  $C_\Theta$  endpoint through this single source package. This keeps the certificate-pinned route auditable in the same form as the constructed-IPL route while preserving the intended distinction: the certificate-pinned link is still a pre-construction source surface, not a proof of the constructed input-prime-strip link machinery. There is now a theta-monoid-matched version of this bundled finite-divisor source as well. It stores a matched Hodge–Arakelov synchronization whose source/target theta-monoid degree equality derives the canonical one-label Gaussian preservation internally, then projects to the synchronized source object only inside the endpoint proof. The experiment aliases expose the theta-monoid equality, the derived canonical-one equality, the same Gaussian-to-Step (xi) audit, and either the  $\text{no-}C_\Theta$  finite-divisor boundary facts or the final conditional  $C_\Theta$  dichotomy. This matched source now also has a named pre-IPL Hodge/SHE transport audit: theta-monoid matching, source full-label calibration, the history-separated forgetful permission, pointwise representative comparison level, identity coordinate transport, and Hodge-theater side separation are packaged before the constructed IPL layer is invoked. The same matched bundled source now also exposes the constructed IPL/log-volume transport before the Step (xi) hull comparison is used. The new endpoint projects the constructed IPL datum, input/output prime-strip equalities, source/target Hodge-theater sides, log-volume preservation, allowed forgetting, and no-history-identification from the finite Hodge/SHE+IPL construction source. A separate finite-log-volume endpoint identifies the IPL source and target log-volumes with the finite

Hodge/SHE source average and transported target average, making explicit that this preservation is inherited from the finite transport rather than supplied as an independent route equality. The suffix `thetaMonoidMatchedConstructedIPLTransportSourceEqConstructedEndpoint` also exposes the exact constructor identity for this IPL source at the finite-divisor review boundary. The matched bundled source now also exposes the Step (xi) possible-image holomorphic-hull/determinant endpoint from the same source object. This projection displays the selected Theorem 3.11 possible image, containment in the record possible-image union, obligations bridge alignment, tensor-power determinant bound, q-positivity, normalization, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. A companion record-canonical bridge endpoint identifies the package hull/determinant bridge with the canonical hull/tensor bridge constructed from the possible-image region, its record-union containment proof, and the weighted determinant data. These separate projections are now bundled into one named matched route audit, `MatchedSourceDerivedFiniteDivisorRouteAudit`, with experiment-surface wrapper `sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQSource_thetaMonoidMatchedFullRouteAudit`. This audit is the compact review target for the current one-source-object finite-divisor corridor: it contains the pre-IPL finite Hodge/SHE transport audit, the constructed IPL log-volume endpoints, the obligations-backed possible-image Step (xi) endpoint, the record-canonical hull/tensor bridge equality, and the no- $C_\Theta$  matched Gaussian-to-Step (xi) boundary. The target-charted route is stronger than this matched bundled source at the current review surface. The compact all-in-one target-charted Hodge/IPL/determinant possible-image route now exposes the target theta chart, the Hodge–Arakelov theta-monoid degree, the determinant summand sum, the record possible-image family-hull log-volume, the package hull/determinant bridge, and the raw signed comparison in one bridge audit. The same ordinary target-charted all-in-one route now also has a compact full-route audit, `TargetChartedFullRouteAudit`, with experiment wrapper `targetChartedHodgeIPLDeterminantPossibleImageRoute_fullRouteAudit`. It bundles the Gaussian-to-Step (xi) chain, determinant source-boundary audit, calibrated determinant endpoint, calibrated possible-image endpoint, and raw comparison endpoint without changing the underlying assumptions. This gives the stronger target-charted route a single review target parallel to the matched finite-divisor audit. Its theta-monoid-matched variant additionally records that canonical one-label preservation on the Hodge/IPL side is reconstructed from equality of the target and source theta-monoid degrees. Thus the strongest finite-divisor review endpoint no longer merely assumes a tensor-power upper bound at the public Step (xi) surface: it routes the equality  $\theta_{\text{signed}}$  equals the record possible-image family-hull log-volume through the determinant payload before projecting the bound consumed by the older holomorphic-hull constructor. The exact vertical- $IQ$  record-canonical corridor now also has a summand/family-hull source form. This source object stores the Hodge/IPL construction, the target-charted possible-image summand/family-hull Step (xi) source, the finite Step (x) source, and the exact vertical- $IQ$  data. It projects internally to the older record-canonical obligations exact source, so the exact corridor no longer exposes the Step (xi) operation identifiers, family-hull source, measure equality, q-choice, and obligations bridge equality as separate public fields. The experiment suffixes `boundaryEndpointWithSummandFamilyHullGaussianExactCorridorAudit` and `cThetaDichotomyWithSummandFamilyHullGaussianExactCorridorAudit` expose the raw boundary and conditional  $C_\Theta$  endpoint. This makes the exact vertical- $IQ$  corridor line up more closely with the Step (xi) passage of IUT III, Remark 3.9.5 and Corollary 3.12, where possible images pass through holomorphic hulls, determinant/tensor-power data, and log-volume comparison before the final numerical estimate is invoked. The possible-image Step (xi) source has also gained a constructor-pinned form. This new source still stores the selected Theorem 3.11 possible image and the weighted determinant payload, but it additionally carries the Theorem 3.11 hull/determinant constructor whose hull data is identified with the ambient source obligations. Its endpoint

exposes the constructor/obligation identification, the constructor bridge equality, q-positivity, normalization, the tensor-power bound, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison together. The experiment surface now has theta-monoid-matched raw and  $C_\Theta$  finite-divisor variants with the **ConstructorPinnedThetaMonoidMatchedRouteAudit** suffix. These variants project internally to the older obligations-backed possible-image source, but the public Step (xi) input is now pinned to a source constructor rather than only to a bridge-equality field. The next tightening removes even that ambient obligations object from the public Step (xi) source. The constructor-sourced hull source derives **IUTStage1SourceHullDetObligations** as **constructor.toHullDetObligations**; algorithm certification, SHE alignment, q-positivity, normalization, and hull/determinant data therefore enter through the same Theorem 3.11 constructor. The experiment suffix **ConstructorSourcedThetaMonoidMatchedRouteAudit** exposes the constructor-sourced endpoint, the projected constructor-pinned endpoint, and the same raw or conditional  $C_\Theta$  finite-divisor boundary. The remaining unconstructed Step (xi) inputs are now concentrated in the constructor itself: the holomorphic hull shadow, weighted determinant payload, measure calibration, and tensor-power bound. There is now also a constructor-built source at the same review boundary. It does not receive a Theorem 3.11 hull/determinant constructor as public input. Instead, it applies the record-canonical constructor **ofRecordCanonicalHullTensorPowerOfQSubsetUnion** to the chosen possible image, the canonical hull/tensor bridge equation, q-positivity, and normalization. The experiment suffix **ConstructorBuiltThetaMonoidMatchedRouteAudit** exposes the built source endpoint, the projected constructor-sourced endpoint, the projected constructor-pinned endpoint, and then the same raw or conditional  $C_\Theta$  finite-divisor boundary. Thus the remaining Step (xi) public payload has moved from a constructor object to the actual record-canonical hull/tensor inputs: holomorphic hull shadow, weighted determinant compatibility, measure calibration, tensor-power bound, and the bridge equality. The constructor-built possible-image source now also has the named audit **RecordCanonicalStepXIAudit**, exposed on the experiment surface by the suffix **recordCanonicalStepXIAudit**. This audit unfolds the record-canonical Step (xi) constructor itself: the selected q-pilot region lies in the Theorem 3.11 possible-image union and hence in the canonical holomorphic hull, that union agrees with both the Theorem 3.11 record and the package target union, the tensor-power determinant bound supplies the  $\theta_{\text{signed}}$  bound, and the constructed hull/determinant source then provides certification, record-union hull containment, determinant-volume control, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. This gives reviewers a Step (xi)-native audit target before the finite-divisor route projects it into the later vertical-*IQ* corridor. The same constructor-built source now exposes a sharper remaining-payload audit, **ConstructorBuiltRemainingPayloadAudit**, with experiment suffix **remainingPayloadAudit**. This ledger separates the still-supplied Remark 3.9.5/Step (xi) inputs from the constructor projections: selected possible-image q-region, holomorphic-hull absorption of the possible-image union and q-region, the named Ob1/Ob2 hull-absorption audit, the named Ob3/Ob4 determinant/tensor-power audit, the derived Ob3–Ob5 hull-log-volume compatibility chain, the bridge handoff from the package hull/determinant source to the constructor bridge datum, the subsequent equality from that constructor bridge datum to the record-canonical hull/tensor bridge, q-positivity, normalization, and the derived raw comparison. The experiment surface exposes this split as **remainingPayloadBridgeSplit**, so the remaining supplied Step (xi) payload can be audited separately from the constructor-to-record bridge projection. This constructor-built Step (xi) source is now also available as a single theta-monoid-matched finite-divisor route object, not merely as an external experiment wrapper. This source object packages the matched Hodge–Arakelov synchronization, the constructed Theorem 3.11 IPL source, the constructor-built possible-image hull source, finite-divisor packet data, Kummer/forgetting compatibilities, and vertical *IQ* target source. Its full-route, boundary, and

conditional  $C_\Theta$  audits now carry the `RecordCanonicalStepXIAudit` as an explicit component, and the experiment surface exposes it with suffix `ConstructorBuiltRecordCanonicalStepXIAudit`. Thus the route-level review target no longer hides the record-canonical Step (xi) constructor audit behind the compact constructor-built source endpoint. Its route audit first exposes the built Step (xi) endpoint, the projected constructor-sourced endpoint, and the projected constructor-pinned endpoint, then projects to the established matched finite-divisor audit. The experiment surface exposes this as the compact `ConstructorBuiltFullRouteAudit` review target. The same route now also has `ConstructorBuiltRemainingPayloadRouteAudit`, exposed with suffix `ConstructorBuiltRemainingPayloadRouteAudit`; it pairs the remaining-payload ledger with the full finite-divisor route audit so the source-paper Step (xi) obligations remain attached to the bundled source object. The same bundled source now also has no- $C_\Theta$  and conditional  $C_\Theta$  experiment endpoints with suffixes `ConstructorBuiltBoundaryAudit` and `ConstructorBuiltCThetaAudit`; these keep the external numeric estimate separate while ensuring that the Hodge/SHE, constructed IPL, constructor-built Step (xi), and finite vertical- $IQ$  data all come from one route object. The conditional endpoint now also has the sharper suffix `ConstructorBuiltRemainingPayloadCThetaAudit`, which carries the same remaining-payload Step (xi) ledger next to the  $C_\Theta$  dichotomy instead of exposing it only at the raw route-audit boundary. There is now also an IPL-link version of this constructor-built bundled route. The source object

```
IUTStage1ThetaMonoidMatchedHodgeSHEIPLLink
PossibleImageConstructorBuiltFiniteDivisorVerticalIQSource
```

keeps the same record-canonical Step (xi) constructor-built hull source, but uses only the certificate-pinned Theorem 3.11 IPL link source rather than an input-prime-strip link construction source. Its experiment suffixes

```
ConstructorBuiltIPLLinkFullRouteAudit,
ConstructorBuiltIPLLinkRemainingPayloadRouteAudit,
ConstructorBuiltIPLLinkBoundaryAudit,
ConstructorBuiltIPLLinkCThetaAudit,
ConstructorBuiltIPLLinkRemainingPayloadCThetaAudit
```

expose the route, no- $C_\Theta$ , conditional  $C_\Theta$ , and remaining-payload conditional audits. The last suffix carries the same remaining Step (xi) payload ledger beside the certificate-pinned IPL-link dichotomy. This separates the Step (xi) constructor-built progress from the still-open construction of the actual Theorem 3.11 input-prime-strip link machinery. This constructor-built IPL-link route now also has a Hodge–Arakelov source endpoint. Instead of asking the public theorem for the bundled theta-monoid-matched synchronization record, the endpoint starts from a calibrated source theta evaluation, a target theta evaluation, and the equality of their theta-monoid degrees, constructs the matched synchronization internally, and then enters the same constructor-built Step (xi) finite-divisor route. The experiment surface now exposes both the no- $C_\Theta$  boundary, which includes the projected  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison, and the conditional endpoint, with suffixes

```
hodgeArakelovHistorySeparatedConstructorBuiltIPLLinkBoundaryAudit,
hodgeArakelovHistorySeparated
ConstructorBuiltIPLLinkCTheta.
```

This Hodge–Arakelov constructor-built IPL-link route now also has a canonical-one variant. Instead of receiving the theta-monoid degree equality directly, the endpoint assumes preservation of the Gaussian degree at the canonical 1-label and derives the

theta-monoid equality from the Hodge–Arakelov evaluation laws on the source and target sides. Its experiment surface exposes the corresponding boundary and conditional endpoints with suffixes `hodgeArakelovCanonicalOneConstructorBuiltIPLLinkBoundaryAudit` and `hodgeArakelovCanonicalOneConstructorBuiltIPLLinkCTheta`. The canonical-one variant is now also available as a single source object,

```
IUTStage1CanonicalOneHodgeArakelovSHEIPLLink
PossibleImageConstructorBuiltFiniteDivisorVerticalIQSource.
```

This object stores the calibrated source Hodge–Arakelov evaluation, the target evaluation, the canonical 1-label Gaussian preservation equality, the certificate-pinned IPL link source, the constructor-built Step (xi) hull/determinant source, and the finite Step (x) vertical-*IQ* data. Its projection first reconstructs the theta-monoid-matched source object and then reuses the existing constructor-built IPL-link boundary. The experiment surface exposes this compact review target through the suffixes

```
canonicalOneConstructorBuiltIPLLinkFullRouteAudit,
canonicalOneConstructorBuiltIPLLinkRemainingPayloadRouteAudit,
canonicalOneConstructorBuiltIPLLinkThetaEvaluationPairAudit,
canonicalOneConstructorBuiltIPLLinkBoundaryAudit,
canonicalOneConstructorBuiltIPLLinkCThetaAudit,
canonicalOneConstructorBuiltIPLLinkRemainingPayloadCThetaAudit.
```

The theta-evaluation-pair audit records both source and target Hodge–Arakelov theta-evaluation endpoints, the source full-label calibration against the theta-source cusp-log-volume average, canonical 1-label Gaussian-degree preservation, and the derived theta-monoid degree equality. The latter is now exposed directly on the experiment surface as `canonicalOneConstructorBuiltIPLLinkThetaMonoidDegreeEq`; its proof uses the source and target Hodge–Arakelov theta-evaluation endpoints’ `canonicalOneDegree_eq_thetaMonoidDegree` theorems rather than an inline route calculation. The same source object now exposes the raw Step (xi) comparison before the finite Step (x) boundary is unfolded. Its named audit `CanonicalOneConstructorBuiltIPLLinkQComparisonAudit` packages the constructor-built route audit, the pre-Step (xi) `CanonicalOneConstructorBuiltIPLLinkHodgeSHEIPLAudit`, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The pre-Step audit records the Hodge–Arakelov theta-root/Gaussian endpoint, finite Hodge/SHE transport, history-separated forgetful transport permission, and certificate-pinned IPL/log-volume transport before the possible-image hull comparison is used. The Step (xi) source-object handoff is now exposed as `CanonicalOneConstructorBuiltIPLLinkHolomorphicHullDeterminantSourceAudit`: the canonical-one route projects its constructor-built hull source to the existing obligations-backed possible-image holomorphic-hull/determinant source, where the q-pilot choice, record-union containment, obligations bridge, tensor-power bound, q-positivity, normalization, and raw signed comparison are read from that one source object. This is now followed by `CanonicalOneConstructorBuiltIPLLinkSourceDerivedBridgeAudit`, which constructs the source-derived Hodge/SHE/IPL/hull bridge from the canonical-one Hodge–Arakelov synchronization, the certificate-pinned Theorem 3.11 IPL link, and that projected possible-image hull source. Its endpoint records the IPL prime-strip equalities, source/target Hodge averages, possible-image q-region, obligations bridge, log-volume preservation, history separation, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The field-level Step (xi) hull side remains separated as `CanonicalOneConstructorBuiltIPLLinkStepXIHullAudit`, which records the q-pilot possible image, record-union containment, record-canonical hull/determinant bridge, tensor-power

bound, theta-pilot hull containment and volume facts, q-positivity, and normalization before the raw signed comparison is projected. The same IPL-link Step (xi) source side now exposes the remaining payload in the same review buckets as the constructed-IPL route: Ob1/Ob2 hull absorption, Ob3/Ob4 determinant normalization and tensor-power control, Ob5 compatibility of the bounded-family hull passage, and the q-positivity/normalization side conditions. These buckets are then threaded into `CanonicalOneConstructorBuiltIPLLinkQComparisonAudit`, so the raw comparison no longer points only to a coarse Step (xi) hull audit. The experiment surface adds direct endpoints with suffixes

```
canonicalOneConstructorBuiltIPLLinkThetaEvaluationPairAudit,
canonicalOneConstructorBuiltIPLLinkHodgeSHEIPLAudit,
canonicalOneConstructorBuiltIPLLinkHolomorphicHullDeterminantSourceAudit,
canonicalOneConstructorBuiltIPLLinkSourceDerivedBridgeAudit,
canonicalOneConstructorBuiltIPLLinkStepXIHullAudit,
canonicalOneConstructorBuiltIPLLinkOb1Ob2HullAbsorptionAudit,
canonicalOneConstructorBuiltIPLLinkOb3Ob4DeterminantAudit,
canonicalOneConstructorBuiltIPLLinkOb5CompatibilityAudit,
canonicalOneConstructorBuiltIPLLinkSideConditionAudit,
canonicalOneConstructorBuiltIPLLinkQComparisonAudit,
canonicalOneConstructorBuiltIPLLink_qComparison,
canonicalOneConstructorBuiltIPLLinkCTheta,
canonicalOneConstructorBuiltIPLLinkRemainingPayloadCThetaAudit,
canonicalOneConstructorBuiltIPLLinkMilestoneCThetaAudit.
```

The  $\text{no-}C_\Theta$  finite boundary is now staged through the named audit `CanonicalOneConstructorBuiltIPLLinkFiniteBoundaryAudit`: its first field is the raw q-comparison audit, followed by the Step (xi) hull audit, Ob1/Ob2 hull absorption, Ob3/Ob4 determinant, Ob5 compatibility, and side-condition audits, and then the finite-divisor packet equalities plus the vertical- $IQ$  target equalities. The experiment surface exposes this as `canonicalOneConstructorBuiltIPLLinkFiniteBoundaryAudit`. The new `CanonicalOneConstructorBuiltIPLLinkMilestoneCThetaAudit` then packages the q-comparison audit, fine Step (xi) payload audits, finite-boundary audit, source-derived bridge audit, conditional  $C_\Theta$  audit, the remaining-payload  $C_\Theta$  audit, and final ordered-real dichotomy as one milestone-facing declaration. Thus this review target separates the raw source-derived Step (xi) comparison, the finite vertical- $IQ$  boundary ledger, the still-supplied Step (xi) payload, and the later numeric  $C_\Theta$  input while also offering a single audit surface for the canonical-one constructor-built route. There is now a stricter canonical-one variant whose middle route constructs IPL/log-volume transport rather than consuming only the certificate-pinned IPL-link source:

```
IUTStage1CanonicalOneHodgeArakelovSHEIPLConstruction
PossibleImageConstructorBuiltFiniteDivisorVerticalIQSource.
```

It carries the same calibrated source Hodge–Arakelov evaluation, target evaluation, canonical 1-label Gaussian preservation equality, constructor-built Step (xi) hull/determinant source, and finite Step (x) vertical- $IQ$  data, but replaces the standalone IPL-link source by an `IUTStage1Theorem311IPLLinkConstructionSource`. Lean derives the theta-monoid match from canonical-one preservation, projects to the existing theta-monoid-matched constructed-IPL route, and exposes the finite Hodge/SHE transport audit, constructed IPL prime-strip equalities, and constructed IPL source/target log-volume prove-nance as fields of `CanonicalOneConstructorBuiltIPLConstructionMiddleRouteAudit`.

The front Hodge–Arakelov Gaussian data is now also separated as `CanonicalOneConstructorBuiltIPLConstructionThetaEvaluationAudit`; it records the source and target theta-evaluation endpoints, the source theta/log-volume calibration, canonical 1-label degree preservation, and the derived theta-monoid degree equality before the finite Hodge/SHE transport is constructed. The equality itself is also available as the compact experiment target `canonicalOneConstructorBuiltIPLConstructionThetaMonoidDegreeEq`. The transport-source handoff is now also named separately as `CanonicalOneConstructorBuiltIPLConstructionTransportSourceAudit`: it packages the theta-evaluation audit with the finite Hodge/SHE transport-source endpoint built from the source/target Hodge–Arakelov evaluations and history-separated forgetting. The next audit, `CanonicalOneConstructorBuiltIPLConstructionFactoredSHEAudit`, records the factored square/full-label SHE synchronization endpoint, the transport-source audit, and the finite Hodge/SHE transport endpoint: structured-SHE availability, identity-coordinate transport, full-label log-volume preservation, transported-average preservation, and history separation all appear before the constructed IPL log-volume transport is read. The constructed IPL segment now has two named subaudits: `CanonicalOneConstructorBuiltIPLConstructionLogVolumeTransportAudit` identifies the finite source’s IPL/log-volume transport source with the construction from the Theorem 3.11 input-prime-strip link source, while `CanonicalOneConstructorBuiltIPLConstructionFiniteTransportLogVolumeAudit` reads the source and target IPL log-volumes from the finite Hodge/SHE source average and transported target average. The stronger chain audit `CanonicalOneConstructorBuiltIPLConstructionFiniteTransportLogVolumeChainAudit` packages the finite Hodge/SHE transport endpoint, the constructed Theorem 3.11 IPL source, the finite-transport log-volume endpoint, and the transported-average preservation theorem as a single provenance boundary. Thus the equality between the constructed IPL target and source log-volumes is read directly from finite transported-average preservation rather than from an independent route-level conjunction. The aggregate `CanonicalOneConstructorBuiltIPLConstructionConstructedIPLAudit` then packages these two subaudits together with the choice-wise prime-strip links. The named subaudit `CanonicalOneConstructorBuiltIPLConstructionChoiceLinkAudit` now exposes this choice-wise input-prime-strip link obligation directly and is threaded through the Hodge/SHE/IPL, middle-route, q-comparison, finite-boundary, and milestone  $C_\Theta$  audits. The constructed-IPL route now also has its own bridge-construction audit, `CanonicalOneConstructorBuiltIPLConstructionSourceDerivedBridgeAudit`. This audit records the bridge built from the Hodge–Arakelov theta data, finite Hodge/SHE transport, the constructed Theorem 3.11 IPL source, and the constructor-built possible-image Step (xi) hull source, and then projects the generic source-derived bridge alignment endpoint from that bridge. The resulting route alignment is now also named as `CanonicalOneConstructorBuiltIPLConstructionRouteLogVolumeAlignmentAudit`. This audit exposes the concrete `IUTStage1HodgeSHEIPLHullRouteLogVolumeAlignment` constructed from the bridge, including IPL log-volume preservation, source theta/Hodge log-volume calibration, target SHE-transported log-volume equality, and q-pilot positivity. Its Step (xi) hull side is now separated as `CanonicalOneConstructorBuiltIPLConstructionStepXIHullAudit`, which records the constructor-built, constructor-sourced, and constructor-pinned possible-image hull endpoints, the projected possible-image hull/determinant endpoint, and the record-canonical hull/tensor bridge equality before the boundary audit is used. It now also carries the compact `CanonicalOneConstructorBuiltIPLConstruction0b1To0b5BridgeAudit`, whose source-level core is `ConstructorBuilt0b1To0b5BridgeAudit`. This audit packages the Remark 3.9.5(vii) chain

from Ob1/Ob2 hull absorption through Ob3/Ob4 determinant and tensor-power normalization, Ob3/Ob5 determinant/log-volume compatibility, the remaining Step (xi) source payload, and the actual `hullDetSource_endpoint` produced by the Theorem 3.11 hull/determinant constructor. Thus the record-canonical bridge endpoint is now reviewable as the output of the Ob1–Ob5 source data, not only as a separate remaining-payload projection. The source-level audit is also exposed directly on the experiment surface as

`possibleImageConstructorBuiltHullSource_ob1ToOb5BridgeAudit.`

This lets the Remark 3.9.5(vii) bridge be reviewed before entering the finite-divisor vertical-*IQ* corridor. The source-level bridge is now also joined to the bounded-family Ob5 quotient collapse by

`possibleImageConstructorBuiltHullSource_ob1ToOb5QuotientBridgeAudit.`

This audit carries the Ob1–Ob5 bridge, the Ob5 quotient-independence audit, the record Ob3/Ob5 bridge, and the local canonical  $C_\Theta$  chain in one object: two nonempty Theorem 3.11 possible images have the same quotient image, while the selected q-region still satisfies  $\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}$ . Its flat-chain companion

`possibleImageConstructorBuiltHullSource_ob1ToOb5QuotientBridgeChain`

spells out the two family-hull inclusions, the quotient-image equality,  $\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}$ , the canonical  $C_\Theta$  upper bound, and the signed comparison  $q_{\text{signed}} \leq \theta_{\text{signed}}$  without requiring reviewers to unfold the audit record. The same Step (xi) hull audit now exposes the constructor-built upper-ray log-volume audit

`ConstructorBuiltStepXIUpperRayAudit,`

which records the q-pilot region’s holomorphic-hull containment, the equality between hull log-volume and normalized weighted determinant, membership of the q-pilot log-volume in the resulting upper ray, and the projected  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. This upper-ray handoff is now named at the same route level as `CanonicalOneConstructorBuiltIPLConstructionUpperRayAudit`, which projects q-pilot upper-ray membership, theta-hull and determinant bounds, determinant normalization, and the raw signed comparison from the constructor-built Step (xi) source. Its Ob1/Ob2 hull-absorption payload is now isolated as `CanonicalOneConstructorBuiltIPLConstructionOb1Ob2HullAbsorptionAudit`: the selected q-region is identified with a Theorem 3.11 possible image, shown inside the record possible-image union, and both the union and selected q-region are absorbed by the canonical holomorphic hull before determinant data enters. Its Ob3/Ob4 determinant payload is now also isolated as `CanonicalOneConstructorBuiltIPLConstructionOb3Ob4DeterminantAudit`: the audit records weighted determinant summation, determinant normalization, hull-log-volume compatibility, tensor-power control, measure calibration, and the record-canonical hull/tensor bridge before the finite Step (x) boundary is used. The Ob5 independence-of-possibilities passage is now isolated as `CanonicalOneConstructorBuiltIPLConstructionOb5CompatibilityAudit`: the selected q-region is absorbed by the bounded-family hull, and the hull-log-volume, determinant normalization, package measure, and record-canonical bridge remain compatible with that hull-family passage. This route-level Ob5 audit now also carries the constructor-built Ob3/Ob5 determinant-compatibility chain, so the determinant log-volume equality is read through normalized weighted-determinant compatibility rather than a standalone remaining-payload projection. The same route now exposes the quotient form of this Ob5 passage as `CanonicalOneConstructorBuiltIPLConstructionOb5QuotientIndependenceAudit`. For any comparison possible-image choice, together with nonemptiness of the selected q-choice image and



the comparison image, this audit imports the constructor-built Remark 3.9.5(v)–(vi) quotient collapse into the canonical-one constructed-IPL finite-divisor route: both possible images map to the same collapsed bounded-family quotient image, while the Ob1–Ob5 bridge, Ob5 compatibility, family-hull determinant/log-volume equality, family-union bound, tensor-power normalization, and raw signed comparison remain attached to the same source object. The remaining source side conditions are now split off as `CanonicalOneConstructorBuiltIPLConstructionSideConditionAudit`: the constructor-built hull source’s q-pilot positivity and source normalization are repackaged through the existing `IUTStage1SourceSideConditions` interface before the finite Step (x) boundary consumes the raw signed comparison. The raw Step (xi) comparison is now also named directly as `CanonicalOneConstructorBuiltIPLConstructionQComparisonAudit`: it keeps the Hodge/SHE/constructed-IPL middle-route audit, Step (xi) hull audit, Step (xi) holomorphic-hull/determinant skeleton, named Ob1/Ob2 hull-absorption audit, named Ob3/Ob4 determinant audit, Ob5 compatibility audit, and source side-condition audit together before projecting  $q_{\text{signed}} \leq \theta_{\text{signed}}$ . The no- $C_\Theta$  finite boundary is now separated as `CanonicalOneConstructorBuiltIPLConstructionFiniteBoundaryAudit`; it keeps the middle-route audit, Step (xi) hull audit, the Step (xi) holomorphic-hull/determinant skeleton, compact boundary audit, finite-divisor packet equalities, exact vertical- $IQ$  target equalities, and raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison attached to the same source object. The named skeleton `CanonicalOneConstructorBuiltIPLConstructionStepXIHolomorphicHullDeterminantSkeleton` records possible-image containment, holomorphic-hull absorption, determinant/tensor-power facts, the record-canonical bridge equality, side conditions, and the raw signed comparison as projections from the constructor-built hull source. The experiment surface exposes this stricter route through

suffixes

```
canonicalOneConstructorBuiltIPLConstructionFullRouteAudit,  
canonicalOneConstructorBuiltIPLConstructionRemainingPayloadRouteAudit,  
canonicalOneConstructorBuiltIPLConstructionThetaEvaluationAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    TransportSourceAudit,  
canonicalOneConstructorBuiltIPLConstructionFactoredSHEAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    LogVolumeTransportAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    FiniteTransportLogVolumeAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    FiniteTransportLogVolumeChainAudit,  
canonicalOneConstructorBuiltIPLConstructionConstructedIPLAudit,  
canonicalOneConstructorBuiltIPLConstructionChoiceLinkAudit,  
canonicalOneConstructorBuiltIPLConstructionHodgeSHEIPLAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    DirectHodgeSHEIPLAudit,  
canonicalOneConstructorBuiltIPLConstructionDirectGaussianToStepXIAudit,  
canonicalOneConstructorBuiltIPLConstructionMiddleRouteAudit,  
canonicalOneConstructorBuiltIPLConstructionDirectMiddleRouteAudit,  
canonicalOneConstructorBuiltIPLConstructionSourceDerivedBridgeAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    RouteLogVolumeAlignmentAudit,  
canonicalOneConstructorBuiltIPLConstructionStepXIHullAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    Ob1ToOb5BridgeAudit,  
canonicalOneConstructorBuiltIPLConstructionUpperRayAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    StepXIHolomorphicHullDeterminantSkeleton,  
canonicalOneConstructorBuiltIPLConstructionOb1Ob2HullAbsorptionAudit,  
canonicalOneConstructorBuiltIPLConstructionOb3Ob4DeterminantAudit,  
canonicalOneConstructorBuiltIPLConstructionOb5CompatibilityAudit,  
canonicalOneConstructorBuiltIPLConstruction  
    Ob5QuotientIndependenceAudit,
```

and

```
canonicalOneConstructorBuiltIPLConstructionSideConditionAudit,  
canonicalOneConstructorBuiltIPLConstructionQComparisonAudit,  
canonicalOneConstructorBuiltIPLConstruction  
  DirectQComparisonAudit,  
canonicalOneConstructorBuiltIPLConstruction_qComparison,  
canonicalOneConstructorBuiltIPLConstructionPacketTargetAudit,  
canonicalOneConstructorBuiltIPLConstructionDirectFiniteBoundaryAudit,  
canonicalOneConstructorBuiltIPLConstruction  
  DirectRouteFiniteBoundaryAudit,  
canonicalOneConstructorBuiltIPLConstructionFiniteBoundaryAudit,  
canonicalOneConstructorBuiltIPLConstructionBoundaryAudit,  
canonicalOneConstructorBuiltIPLConstructionCTheta,  
canonicalOneConstructorBuiltIPLConstructionDirectCThetaAudit,  
canonicalOneConstructorBuiltIPLConstructionMilestoneCThetaAudit,  
canonicalOneConstructorBuiltIPLConstruction  
  DirectMilestoneCThetaAudit,  
canonicalOneConstructorBuiltIPLConstruction  
  Ob5QuotientMilestoneCThetaAudit.
```

The constructed-IPL route now also has compact milestone-facing aliases:

```
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ,  
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ  
  _withDirectMilestoneAudit,  
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeSHEIPLHullConstructedIPLFiniteDivisorVerticalIQ,  
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeSHEIPLHullConstructedIPLFiniteDivisorVerticalIQ  
  _withMilestoneAudit,  
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeSHEIPLHullConstructedIPLFiniteDivisorVerticalIQ  
  _withDirectMilestoneAudit,  
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeSHEIPLHullConstructedIPLFiniteDivisorVerticalIQ  
  _withOb5QuotientMilestoneAudit.
```

The first pair is now the compact subgoal-6 public endpoint and its direct audit companion; the latter four names keep the more explicit constructed-IPL spelling. All six aliases return the same canonical-one constructor-built constructed IPL route: Hodge–Arakelov theta evaluation, factored SHE, constructed IPL/log-volume transport, Step (xi) hull/determinant audits, source side conditions, raw q-comparison, finite boundary, and conditional  $C_\Theta$  audit, with the numeric  $C_\Theta$  estimate still explicit. `CanonicalOneConstructorBuiltIPLConstructionMilestoneCThetaAudit` now carries the transport-source, log-volume transport, and finite-transport log-volume audits directly, together with the constructed source-derived bridge audit, the constructed route-log-volume alignment audit, a direct middle-route audit, constructor-built upper-ray audit, and a direct

signed  $C_\Theta$  audit. The direct middle-route audit bundles the canonical-one theta-evaluation, finite Hodge/SHE transport, factored SHE, constructed IPL log-volume transport, source-derived bridge, and route-log-volume alignment chain before the theta-monoid-matched finite boundary is used for compatibility. The direct  $C_\Theta$  audit computes the ordered-real dichotomy from the constructed q-positivity side condition, the constructed  $q_{\text{signed}} \leq \theta_{\text{signed}}$  Step (xi) comparison, and the explicit numeric  $C_\Theta$  estimate, rather than projecting that dichotomy only through the coarser theta-monoid-matched  $C_\Theta$  package. The Hodge/SHE/IPL part of this direct path is now also exposed as `CanonicalOneConstructorBuiltIPLConstructionDirectHodgeSHEIPLAudit`. Unlike the broader compatibility audit, this direct audit does not carry the theta-monoid-matched finite-transport ledger; it records only the canonical-one theta evaluation, finite Hodge/SHE transport, factored SHE, constructed-IPL log-volume transport, finite-transport log-volume, and choice-link endpoints. The direct middle route, raw q-comparison audit, and direct milestone bundle consume this stricter audit. The raw comparison itself now also has a no-broad-middle-route form, `CanonicalOneConstructorBuiltIPLConstructionDirectQComparisonAudit`. It removes the older `MiddleRouteAudit` field from the comparison payload and reviews  $q_{\text{signed}} \leq \theta_{\text{signed}}$  through the direct Hodge/SHE/IPL audit, direct middle route, source-derived bridge, route-log-volume alignment, Step (xi) hull/determinant audits, Ob1–Ob5 payload, and source side conditions. The direct finite-boundary route, direct  $C_\Theta$  audit, and direct milestone bundle consume this direct q-comparison audit. The public raw comparison suffix `canonicalOneConstructorBuiltIPLConstruction_qComparison` now projects through the direct comparison theorem as well. There is now also `CanonicalOneConstructorBuiltIPLConstructionDirectMilestoneCThetaAudit`, which removes the theta-monoid-matched route, remaining-payload, compact boundary, and matched  $C_\Theta$  compatibility projections from the milestone bundle. Its load-bearing route is the direct middle-route audit, the direct route finite-boundary audit, and the direct signed  $C_\Theta$  audit. The compact constructed-IPL alias with suffix `withDirectMilestoneAudit` returns this same direct milestone bundle. Thus the milestone-facing bundle exposes the pre-IPL and constructed-IPL transport chain, the Hodge/SHE/IPL/hull bridge constructor, the route alignment it constructs, and the Step (xi-f/g) upper-ray handoff instead of only the coarser constructed-IPL and hull audits. The quotient-aware milestone bundle, `CanonicalOneConstructorBuiltIPLConstructionOb5QuotientMilestoneCThetaAudit`, attaches the route-level Ob5 quotient-independence audit to this same direct  $C_\Theta$  milestone surface. Its compact alias with suffix `withOb5QuotientMilestoneAudit` returns the final dichotomy together with the collapsed Ob5 quotient images for two nonempty possible-image choices, so the quotient-collapse payload is visible at the same review surface as the finite-divisor vertical-IQ  $C_\Theta$  endpoint. The same route now has an unbundled canonical-one Hodge–Arakelov source endpoint,

```
boundarySignedEqualityOrStrictCTheta_from
_sourceDerivedHodgeArakelovCanonicalOneT11IPLConstruction
ConstructorBuiltFiniteDivisorVerticalIQ,
```

exposed on the experiment surface with suffix

```
hodgeArakelovCanonicalOne
ConstructorBuiltIPLConstructionCTheta.
```

It constructs the canonical-one source object internally from the calibrated source theta evaluation, target theta evaluation, canonical 1-label Gaussian preservation, Theorem 3.11 IPL-link construction source, constructor-built Step (xi) hull source, and finite Step (x) vertical-IQ data. Its

audit-returning companion,

```
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeArakelovCanonicalOneT11IPLConstruction  
  ConstructorBuiltFiniteDivisorVerticalIQ_withMilestoneAudit,
```

is exposed on the experiment surface with suffix

```
hodgeArakelovCanonicalOne  
  ConstructorBuiltIPLConstructionMilestoneAudit.
```

It returns the full canonical-one constructor-built constructed-IPL milestone  $C_\Theta$  audit for the internally assembled source object. The same canonical-one boundary now has a charted Hodge/family-hull Step (xi) variant,

```
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeArakelovCanonicalOneT11IPLConstruction  
  ChartedFamilyHullFiniteDivisorVerticalIQ,
```

with audit companion ending in

```
ChartedFamilyHullFiniteDivisorVerticalIQ_withMilestoneAudit.
```

Its experiment-surface suffixes are

```
hodgeArakelovCanonicalOneChartedFamilyHull  
  IPLConstructionCTheta,  
hodgeArakelovCanonicalOneChartedFamilyHull  
  IPLConstructionMilestoneAudit.
```

These endpoints no longer receive the constructor-built Step (xi) hull source directly: they project it from the possible-image charted Hodge-calibrated family-hull obligations-backed source before assembling the finite-divisor vertical- $IQ$  corridor. The canonical-one boundary now also has a synchronized possible-image summand/family-hull refinement,

```
boundarySignedEqualityOrStrictCTheta_from  
  _sourceDerivedHodgeArakelovCanonicalOneT11IPLConstruction  
  SynchronizedPossibleImageSummandFamilyHull  
  FiniteDivisorVerticalIQ.
```

The experiment surface exposes this as

```
hodgeArakelovCanonicalOneSynchronizedPossibleImage  
  SummandFamilyHullIPLConstructionCTheta.
```

Its no- $C_\Theta$  audit companion is

```
boundaryEndpoint_from  
  _sourceDerivedHodgeArakelovCanonicalOneT11IPLConstruction  
  SynchronizedPossibleImageSummandFamilyHull  
  FiniteDivisorVerticalIQ_withQComparisonAudit,
```

with experiment suffix

`hodgeArakelovCanonicalOneSynchronizedPossibleImage  
SummandFamilyHullIPLConstructionBoundaryAudit.`

Here the Hodge source and target evaluations are bundled into the synchronized Hodge–Arakelov source object, while the Step (xi) input still remembers the Theorem 3.11 possible-image q-choice and the determinant summand calibration. The audit companion exposes the summand/family-hull q-comparison audit and the finite-divisor packet and vertical- $IQ$  target equalities before the numeric  $C_\Theta$  estimate is supplied. Thus this public endpoint sits one stage upstream of the charted family-hull variant before projecting to the already verified finite-divisor corridor. The corresponding milestone  $C_\Theta$  audit now also carries the remaining-payload route audit, the theta-evaluation audit, the factored SHE audit, and the constructed IPL audit as fields, so the final canonical-one constructed-IPL review target keeps the theta-root/Hodge–Arakelov Gaussian, factored Hodge/SHE, constructed IPL, direct Gaussian-to-Step (xi), Ob1/Ob2 hull absorption, Ob3/Ob4 determinant, Ob5 compatibility, finite Step (x), vertical- $IQ$ , and Step (xi) source-paper payload ledgers together. At the same canonical-one boundary, the finite Hodge/SHE/IPL middle layer is now constructed directly from the route’s source-calibrated and target Hodge–Arakelov evaluations plus canonical 1-label preservation. The new Hodge/SHE/IPL audit records that direct finite transport-source endpoint, the constructed IPL log-volume endpoint, and the finite-transport log-volume provenance before the route is projected through the theta-monoid-matched corridor. This keeps the history-separated forgetting permission and transported-average preservation visible at the canonical-one source surface. The same route now also carries a direct Gaussian-to-Step (xi) bridge audit: starting from the route-owned source-calibrated Hodge–Arakelov theta evaluation, target evaluation, canonical 1-label preservation, and constructed IPL source, it projects the constructor-built possible-image hull source to the side-conditioned obligations-backed source consumed by the source-calibrated Step (xi) bridge audit. This records the theta-root/Gaussian payload, constructed finite Hodge/SHE/IPL transport, hull containment, record-canonical bridge, determinant bound, side conditions, and  $q_{\text{signed}} \leq \theta_{\text{signed}}$  at the canonical-one milestone surface. The canonical-one constructed-IPL route now also has a separate Step (x) packet/vertical- $IQ$  audit before the compact finite-boundary ledger. This audit is projected through the named finite-divisor packet-local source endpoint and the exact vertical- $IQ$  target endpoint, so the packet-local equalities, upper-semi inequality, packet-normalized target equalities, and target (Ind3) equality are visible as source-endpoint facts in the milestone audit rather than only as loose components of the final boundary tuple. These pieces are now joined in two stages. The smaller direct finite-boundary audit projects the raw comparison from the source-calibrated Gaussian-to-Step (xi) bridge and the finite packet/vertical- $IQ$  facts from the packet/target audit. The larger `CanonicalOneConstructorBuiltIPLConstructionDirectRouteFiniteBoundaryAudit` then carries the direct middle route, source-derived bridge, route-log-volume alignment, Step (xi) hull/determinant audits, side conditions, raw q-comparison, and finite packet/vertical- $IQ$  target facts together before the matched compatibility boundary is used. The older compact matched boundary is still retained for compatibility with the existing  $C_\Theta$  route, but the no- $C_\Theta$  review surface now has a direct source-derived boundary for the same canonical-one constructed-IPL source object. The constructor-built bundled route can now also be reached from the stronger theta-monoid-matched obligations-backed record-canonical exact corridor. The projection constructs the bundled route internally from the matched Hodge/IPL source, the measured determinant family, the selected possible image, the finite-divisor source, and the exact vertical- $IQ$  source. In particular, the hull/determinant bridge equality, q-positivity, and normalization are first projected from the constructor-obligations object and then used to build the constructor-built Step (xi) source. The

experiment surface exposes this review target through three suffixes:

```
MatchedObligationsConstructorBuiltFullRouteAudit,
MatchedObligationsConstructorBuiltRemainingPayloadRouteAudit,
MatchedObligationsConstructorBuiltBoundaryAudit,
MatchedObligationsConstructorBuiltCThetaAudit.
```

The remaining-payload variant keeps the obligations-to-record-canonical Step (xi) bridge together with the constructor-built Step (xi) payload ledger, so this intermediate corridor now reports the same unresolved hull/determinant source-paper payload that was previously visible only on the lower constructor-built route. The same obligations-backed record-canonical corridor is now also reachable from the earlier constructor-backed matched exact source. This projection sets the corridor's constructor-obligations object to `toHullDetSourceConstructor.toHullDetObligations`; consequently the obligations bridge equality with the record-canonical hull/tensor-power bridge is definitional at this boundary. The new review target therefore starts from constructor-backed Step (xi) data, projects to the obligations-backed record-canonical corridor, and only then uses the constructor-built finite-divisor route. The experiment surface exposes this as:

```
MatchedConstructorBackedObligationsCorridorAudit,
MatchedConstructorBackedObligationsRemainingPayloadCorridorAudit,
MatchedConstructorBackedObligationsBoundaryAudit,
MatchedConstructorBackedObligationsCThetaAudit.
```

The remaining-payload corridor threads the same constructor-built payload ledger through this projection, so the constructor-backed exact source no longer hides the unresolved Step (xi) hull operation, determinant source, bridge, positivity, and normalization payload behind the full-route audit. There is now a side-conditioned variant of this matched constructor-backed exact source as well. Its Step (xi) field is a `SideConditionedConstructorBacked` source, so q-pilot positivity and source normalization are projected from one `IUTStage1SourceSideConditions` object before the constructor-backed source is projected to the obligations-backed record-canonical corridor and the constructor-built finite-divisor route. The Hodge/SHE/IPL middle layer is also exposed separately by `MatchedSideConditionedHodgeSHEIPLAudit`: this audit records the theta-monoid degree match and then projects the theta-root evaluation, factored SHE preservation, history-separated finite Hodge/SHE transport, constructed IPL link, and finite-transport log-volume provenance from the target-charted Hodge–Arakelov/IPL construction source. The experiment surface exposes this boundary as:

```
MatchedSideConditionedHodgeSHEIPLAudit,
MatchedSideConditionedConstructorBackedObligationsCorridorAudit,
MatchedSideConditionedConstructorBackedObligationsRemainingPayloadCorridorAudit,
MatchedSideConditionedConstructorBackedObligationsBoundaryAudit,
MatchedSideConditionedConstructorBackedObligationsCThetaAudit.
```

The same strongest side-conditioned corridor is now exposed under the compact source-derived milestone names

```
sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ_
  boundaryEndpointWithMatchedSideConditionedConstructorBackedObligationsAudit,
sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ_
  cThetaDichotomyWithMatchedSideConditionedConstructorBackedObligationsAudit.
```

These are review-surface aliases rather than new mathematical assumptions: they return the existing side-conditioned Hodge/SHE/IPL audit, the named side-conditioned Step (xi) hull/determinant audit, and the projected constructor-backed obligations corridor under the milestone endpoint name. The matched-obligations conditional endpoint remains exposed under the explicit audit name

```
boundarySignedEqualityOrStrictCTheta_from
  _sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQ
  _withMatchedSideConditionedConstructorBackedObligationsAudit.
```

The compact theorem name without this suffix is now reserved for the constructed-IPL constructor-built route described above. The matched audit variant uses the strongest side-conditioned constructor-backed corridor, keeps the numeric  $C_\Theta$  estimate explicit, and returns the same matched Hodge/SHE/IPL and Step (xi) audit package as the longer descriptive theorem. It now also has a matched side-conditioned remaining-boundary ledger, `MatchedSideConditionedConstructorBackedRemainingSourceBoundaryAudit`, exposed on the experiment surface with suffix

```
matchedSideConditionedConstructorBacked
  RemainingBoundaryAudit.
```

This ledger is the strongest current review target for what is still public at the source-paper boundary: the matched Hodge–Arakelov/IPL source, the side-conditioned constructor-backed Step (xi) source, the upper-semi finite-divisor Step (x) source, and the exact vertical- $IQ$  source. It now also carries the projected constructor-backed remaining-payload corridor audit, so the route-level remaining-source ledger explicitly includes the constructor-built Step (xi) payload audit rather than only the older full obligations corridor and assembled remaining-boundary ledger. The matched side-conditioned Hodge/SHE/IPL audit now also carries the choice-wise input-prime-strip links directly. The experiment endpoint with suffix `matchedSideConditionedConstructedIPLChoiceLinkEndpoint` exposes that, for every possible output choice, the constructed IPL link has source equal to the route input prime strip and target equal to the choice-indexed output prime strip, before the Step (xi) hull/determinant source or exact vertical- $IQ$  boundary is used. The constructor-backed Step (xi) audit has likewise been strengthened: it now records q-pilot containment in the Theorem 3.11 possible-image union, inclusion of that union in the holomorphic hull, the bounded-family determinant/log-volume equalities, the tensor-power bound, the record-canonical hull/tensor bridge, and the raw signed comparison as one source-facing skeleton. The experiment suffix `stepXIHolomorphicHullDeterminantEndpoint` exposes this skeleton before the finite-divisor vertical- $IQ$  projection. The same skeleton is now carried by the strongest matched side-conditioned finite-exact source ledger itself, via `MatchedSideConditionedStepXIHolomorphicHullDeterminantSkeleton`; the experiment suffix `matchedSideConditionedStepXIHolomorphicHullDeterminantSkeleton` exposes it from the bundled source object that also contains the matched Hodge/SHE/IPL, finite-divisor, and exact vertical- $IQ$  data. The no- $C_\Theta$  and conditional  $C_\Theta$  milestone endpoints now also have remaining-boundary variants, `MatchedSideConditionedConstructorBackedRemainingBoundaryAudit` and `MatchedSideConditionedConstructorBackedRemainingCThetaAudit`. These variants return the projected obligations boundary together with the remaining-source ledger, so the public endpoint no longer drops the Step (xi) holomorphic-hull/determinant skeleton when it reaches the boundary or  $C_\Theta$  audit surface.

The synchronized possible-image summand finite-divisor boundary now has a Step (xi) log-volume-chain audit endpoint as well. The new source declaration with suffix



`withStepXIILogVolumeChainAudit` refines the no- $C_\Theta$  q-comparison boundary by retaining the finite Step (x) packet and vertical- $IQ$  equalities together with the summand-calibrated chain

$$\mu_{\log}(q\text{Region}) \leq \det_{\log} \leq \theta_{\text{signed}}.$$

This gives a sharper review surface for the current 3.11-to-3.12 corridor: the source-derived Step (xi) hull/determinant comparison and the finite Step (x) boundary are visible before the separate numerical  $C_\Theta$ -estimate is supplied.

The constructor-built possible-image Step (xi) source can now also be constructed directly from an Ob3/Ob4 adjusted determinant package. The new constructor `ofOb3Ob4AdjustedDeterminantSource` takes the localization summands, structure-sheaf subtraction, and positive tensor-power data, projects the weighted determinant internally, and returns the existing constructor-built Ob3/Ob4 audit for the resulting possible-image hull source. Its experiment endpoint exposes the raw adjusted-localization identities, the weighted determinant summation, tensor-power normalization, and the  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. Thus another piece of the Step (xi) determinant payload has moved from an already-weighted determinant input to a source-facing Remark 3.9.5(vii) Ob3/Ob4 construction.

There is now also a minimal-hull-system variant of this constructor,

```
possibleImageConstructorBuiltHullSource
  _ofRemark395HullSystemOb3Ob4AdjustedDeterminantSource
  _endpoint.
```

This route starts from the intersection-defined `IUTStage1Remark395HolomorphicHullSystem`, projects the older hull/log-volume shadow internally, and identifies the resulting Step (xi) hull with

$$\phi\left(\bigcup_i P_i\right)$$

for the Theorem 3.11 possible-image family. The endpoint proves that this object is a source-paper hull, that the chosen q-region is contained in it, and then returns the same Ob3/Ob4 determinant audit, bridge-inequality audit, and raw signed comparison. Thus this constructor form no longer treats the holomorphic-hull shadow as a supplied Step (xi) payload.

The constructor-built possible-image route has now been refined one step further to the product-hull formulation of Remark 3.9.5(i)–(ii). The new source constructor

```
ofRemark395ProductHullSystem
  Ob3Ob4AdjustedDeterminantSource
```

starts from an `IUTStage1Remark395ProductHullSystemSource`: a family of product hulls, a parameter selecting the intersection of all product hulls containing a region, and the corresponding log-volume calibration. The endpoint proves that the Step (xi) hull attached to  $\bigcup_i P_i$  is exactly the product hull selected by this intersection parameter, that the chosen q-region is contained in it, and that it is minimal among product hulls containing  $\bigcup_i P_i$ . It then returns the same constructor-built Ob3/Ob4 determinant audit, bridge-inequality audit, and raw signed comparison. Thus the corridor now reaches the source-paper “smallest product hull” formulation before projecting to the older holomorphic-hull shadow. This product-hull provenance is now also available for any already constructed possible-image Step (xi) source whose hull/log-volume shadow is induced by a product-hull system:

```
possibleImageConstructorBuiltHullSource
  _productHullBackedConstructorBuiltAudit.
```

At the product-hull-backed finite-divisor boundary, the Ob5 quotient passage now also has a scalar quotient compatibility audit:

```
remark395ProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQ
_ob5ScalarQuotientCompatibilityAudit.
```

This theorem applies the same upper-semi quotient formalism to the real scalar  $\mu_{\log}(\phi(P_B))$ : the singleton images of  $\det_{\log}^{\text{norm}}$ ,  $\det_{\log}$ , the normalized  $\det^{\otimes M}$  tensor-power scalar, and the family-hull log-volume all collapse to the distinguished quotient point, and hence have the same quotient image. Thus the product-hull route now records the compatibility with  $\det^{\otimes M}(\phi(P_B))$  and  $\mu_{\log}(\phi(P_B))$  that Remark 3.9.5(Ob5) states alongside the bounded-family hull quotient. The audit identifies the source's canonical hull of  $\bigcup_i P_i$  with the selected smallest product hull, proves containment of both  $\bigcup_i P_i$  and the q-pilot possible image in that hull, records minimality and product-hull log-volume, and keeps the record-canonical Step (xi) and bridge-inequality audits attached. The synchronized target-charted possible-image summand/family-hull source has a corresponding wrapper,

```
synchronizedTargetChartedPossibleImageSummand
HodgeFamilyHull_productHullConstructorBuiltAudit,
```

which threads this product-hull audit through the Hodge–Arakelov chart, finite summand equality, exact theta/family-hull equality, and obligations-backed constructor reduction. Thus the strongest Hodge/summand Step (xi) source can now be reviewed together with the Remark 3.9.5 product-hull boundary, instead of reserving product-hull provenance only for the later finite-divisor wrapper.

The same constructor-built source now exposes the Step (xi) bridge inequality as a named audit **ConstructorBuiltStepXIIBridgeInequalityAudit**. This audit records the selected q-pilot log-volume, the normalized determinant/tensor-power log-volume, and the package theta scalar in the direct chain

$$\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}.$$

The first inequality is derived from the upper-ray/hull absorption audit and the Ob3-3 determinant compatibility; the second is the Ob4 normalized tensor-power bound. The experiment surface exposes this as **possibleImageConstructorBuiltHullSource\_bridgeInequalityAudit**, and the Ob3/Ob4-adjusted constructor endpoint now returns this bridge audit next to the determinant audit.

There is also an exact-theta constructor-built variant of the adjusted-summand route,

```
remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
_toPossibleImageConstructorBuiltHolomorphicHullDeterminantSource
OfThetaEqFamilyHullLogVolume_endpoint.
```

Here the constructor no longer accepts the Ob4 tensor-power bound as a free input. It starts from the finite Ob3-3 summand identity, derives the record Ob3/Ob5 family-hull determinant source, assumes the source-facing exact-theta calibration

$$\theta_{\text{signed}} = \mu_{\log} \left( \phi \left( \bigcup_i P_i \right) \right),$$

and then obtains

$$\det_{\text{norm}} \leq \theta_{\text{signed}}$$

from the bounded-family theorem `tensorPower_bound_of_theta_eq_familyHullLogVolume`. The package bridge equality is still an explicit Step (xi) synchronization boundary, but the numerical Ob4 inequality is now constructed from the Remark 3.9.5 family-hull/log-volume source in this route.

The adjusted-summand source now also exposes the intermediate bridge itself, before assembling the final constructed Step (xi) object. The generic source constructor

```
IUTStage1Remark395HullDeterminantBridgeSource
.ofAdjustedDeterminantLogVolumeSource
```

starts from the finite Ob3-3 identity

$$\mu_{\log}(\phi(\bigcup_i P_i)) = \sum_{\beta} \text{AdjLoc}_{\beta},$$

derives the Ob3/Ob5 determinant compatibility, and then proves the bridge chain

$$\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} = \det_{\log} \leq \theta_{\text{signed}}.$$

The record-canonical companion `toRecordHullDeterminantBridgeSource` fixes the family to the Theorem 3.11 possible images, while the normalized experiment endpoints

```
remark395HullDeterminantBridgeSource_normalizedBridge,
remark395RecordHullDeterminantBridgeSource_normalizedBridge
```

make the direct  $\det_{\text{norm}}$ -bridge reviewable without unpacking the longer endpoint. The experiment endpoint

```
remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
.toRecordHullDeterminantBridgeSource_endpoint
```

makes this bridge-level derivation reviewable without unfolding the later constructed-source route. The named finite-divisor milestone theorem

```
boundarySignedEqualityOrStrictCTheta
.from_remark395ConstructedHullDeterminant
FiniteDivisorVerticalIQ
```

now also has the audited companion with suffix

```
_withRecordBridgeAudit.
```

This companion returns the constructed record-canonical Remark 3.9.5 bridge audit together with the final conditional  $C_{\Theta}$  dichotomy, so the public milestone name exposes the chain

$$\mu_{\log}(q\text{Region}) \leq \det_{\log} \leq \theta_{\text{signed}}$$

beside the finite-divisor vertical- $IQ$  conclusion.

There is now also an exact-theta bridge-level variant with suffix

```
toRecordHullDeterminantBridgeSource
OfThetaEqFamilyHullLogVolume
```

and experiment endpoint

```
remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
  _toRecordHullDeterminantBridgeSource
  OfThetaEqFamilyHullLogVolume_endpoint.
```

This version no longer takes the Ob4 tensor-power bound as an argument at the bridge surface. The generic bounded-family theorem `IUTStage1BoundedFamilyHullDetLogVolumeSource.tensorPower_bound_of_theta_eq_familyHullLogVolume` derives the bound from

$$\theta_{\text{signed}} = \mu_{\log}(\phi(\bigcup_i P_i)),$$

after the adjusted-summand source has already produced the Ob3/Ob5 determinant equality. Thus the intermediate bridge now has both forms: an ordinary form with an explicit Ob4 bound, and an exact-theta form in which that bound is constructed from the family-hull calibration.

The same exact-theta constructor-built route now has an obligations-backed form, with suffix

```
OfThetaEqFamilyHullLogVolumeFromObligations_endpoint.
```

This version consumes an `IUTStage1SourceHullDetObligations` object and a single synchronization statement identifying its hull/determinant bridge datum with the record-canonical Step (xi) construction. Lean then derives the package bridge equality from `hullDetData.hullDetBridge_eq_bridgeData`, and reads q-pilot positivity and source normalization from the same obligations object. Thus, at this constructor-built boundary, the remaining supplied Step (xi) data has been narrowed from four separate fields—tensor-power bound, bridge equality, q-positivity, and normalization—to the family-hull exact-theta calibration plus one obligations-backed record-canonical bridge synchronization.

The exact-theta adjusted-summand route has now also been tied to the local canonical  $C_{\Theta}$ -scale audit. The source declaration

```
IUTStage1Remark395RecordOb3Ob5AdjustedDeterminantLogVolumeSource
  .toPossibleImageConstructorBuiltHolomorphicHullDeterminantSource
  OfThetaEqFamilyHullLogVolume_canonicalCThetaBridgeAudit
```

returns the constructor-built Remark 3.9.5 canonical-scale bridge audit together with the reviewable chain

$$\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}} \leq C_{\Theta, \text{can}} \cdot (-q_{\text{signed}}).$$

Its obligations-backed companion, with suffix

```
OfThetaEqFamilyHullLogVolumeFromObligations_canonicalCThetaBridgeAudit,
```

adds the facts that the package hull/determinant bridge is the obligations bridge datum,  $0 < -q_{\text{signed}}$ , and source normalization, all projected from the same obligations object. Thus the no-external-numeric-bound local scale is now attached directly to the finite adjusted-summand Ob3/Ob5, exact-theta Ob4, possible-image  $q$ -choice constructor, rather than only to the later constructed-source wrapper.

This canonical-scale bridge has now been lifted to the target-charted, measure-calibrated adjusted-summand sources as well. The audit

```
targetChartedHodgeMeasureCalibratedAdjustedPossibleImage
  HullDetObligationsBackedSource_canonicalCThetaBridgeAudit
```

projects the same lower constructor-built Remark 3.9.5 canonical-scale audit from the obligations-backed adjusted exact-theta source. Its constructor-backed companion

```
targetChartedHodgeConstructorBackedMeasureCalibrated
AdjustedPossibleImageHullDetSource_canonicalCThetaBridgeAudit
```

does the same after replacing the obligations bridge by the Theorem 3.11 record-canonical hull/tensor-power constructor. Thus the charted Hodge calibration, finite Ob3–3 adjusted summands, measured family hull, possible image  $q$ -choice, and local no-external-bound  $C_{\Theta, \text{can}}$  chain now occur in one reviewable audit path.

There is now a named obligations-backed audit for the target-charted, measure-calibrated adjusted-summand possible-image source:

```
targetChartedHodgeMeasureCalibratedAdjustedPossibleImage
HullDetObligationsBackedSource_adjustedExactTheta
StepXIAudit.
```

This audit records the exact-theta source before passing to the constructor-backed form. The  $q$ -region is the chosen Theorem 3.11 possible image, the package measure is projected from the measured family hull, the transported target theta chart is calibrated to the Hodge–Arakelov theta-monoid degree, that degree is identified with the finite Ob3–3 adjusted summand sum, and the record family-hull/determinant source yields

$$\theta_{\text{signed}} = \mu_{\log} \left( \phi \left( \bigcup_i P_i \right) \right).$$

The same audit keeps the obligations-backed hull/determinant bridge,  $q$ -positivity, source normalization, and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison visible in one source-boundary object.

The constructor-backed adjusted-summand source now has a companion audit,

```
targetChartedHodgeConstructorBackedMeasureCalibrated
AdjustedPossibleImageHullDetSource_adjustedExactTheta
StepXIAudit.
```

It carries the same target-charted Hodge and Ob3–3 summand provenance for  $\theta_{\text{signed}} = \mu_{\log}(\phi(\bigcup_i P_i))$ , but replaces the obligations-backed bridge boundary by the hull/determinant obligations constructed from the Theorem 3.11 record-canonical hull/tensor-power constructor. Thus the constructor-backed review surface no longer loses the source of the exact-theta equality when it records the constructed bridge,  $q$ -positivity, normalization, and raw signed comparison.

The same constructor-backed exact-theta source now projects directly into the current finite-divisor milestone source:

```
targetChartedHodgeConstructorBackedMeasureCalibrated
AdjustedPossibleImageHullDetSource
_toRemark395ConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQSource.
```

The projection fills the finite-divisor source's  $\theta_{\text{signed}} = \mu_{\log}(\phi(\bigcup_i P_i))$  field from the already audited Hodge theta-monoid and finite adjusted determinant summand chain, rather than accepting this

equality again as a bare boundary input. Its companion audit

```
targetChartedHodgeConstructorBackedMeasureCalibrated
AdjustedPossibleImageHullDetSource
_toRemark395ConstructorBackedConstructedExactTheta
FiniteDivisorAudit
```

keeps, in one object, the target-charted theta equality, the theta-monoid degree equality with the adjusted summand sum, the Ob3/Ob5 summand-to-determinant identities, and the constructed finite-divisor record-bridge audit proving the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. This is the current Lean bridge from the exact-theta Ob3/Ob5 implementation into the strongest constructor-backed finite-divisor corridor.

This exact-theta bridge now propagates one level further into the Ob5 product-hull hierarchy. The new internal constructors

```
toProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQSource,
toPrincipalProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQSource,
toPrincipalValuationBallBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQSource
```

start from the same target-charted exact-theta adjusted-summand source. They then add, respectively, the Remark 3.9.5 product hull, the principal  $\lambda\mathcal{O}$  hull, and the valuation-ball direct-product cover identification. Their experiment-surface audits

```
_productHullBackedExactThetaFiniteDivisorAudit,
_principalProductHullBackedExactThetaFiniteDivisorAudit,
_principalValuationBallBackedExactThetaFiniteDivisorAudit
```

retain the Hodge theta-monoid/adjusted-summand equality while exposing the product-hull containment audit, the principal scalar-multiple hull identity, or the valuation-ball direct-product and calibrated-cell log-volume identities. Thus the product/principal/Haar corridor can now be reviewed as an extension of the exact-theta Step (xi) source rather than as a separate supplied constructor-backed payload. The principal valuation-ball projection has a tighter source-core variant as well. The named theorem

```
adjustedSource_eq_valuationBall
_ofValuationBallRecordSource
```

derives the equality between the exact-theta measured adjusted source and the principal valuation-ball Ob3/Ob5 source from two narrower inputs: the valuation-ball possible-image family is synchronized with the Theorem 3.11 record family, and the measured adjusted source is the record-canonical source constructed from that valuation-ball cover. The companion constructor and audit,

```
toPrincipalValuationBallBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQSource
OfValuationBallRecordSource,
toPrincipalValuationBallBackedExactThetaFiniteDivisorAudit
OfValuationBallRecordSource,
_principalValuationBallBackedExactThetaFiniteDivisorAudit
OfValuationBallRecordSource,
```

therefore no longer require the valuation-ball source-core equality as a standalone payload at this boundary.

The exact-theta source now reaches the final product-hull and principal valuation-ball dichotomy endpoints, not only the intermediate audits. The new experiment-surface wrappers

```

    _productHullBackedCanonicalCThetaScaleDichotomy
      WithOb5Ob6Ob7SynchronizedAuditAtQChoice
      OfCoricThetaMuProductFormulaConstructionSource,
    _principalValuationBallCanonicalCThetaScaleDichotomy
      WithTopologyFiniteExtensionHaarOb5Ob6Ob7AuditAtQChoice
      OfCoricThetaMuProductFormulaConstructionSource,
    _principalValuationBallCanonicalCThetaScaleDichotomy
      WithTopologyFiniteExtensionHaarOb5Ob6Ob7AuditAtQChoice
      OfCoricThetaMuProductFormulaConstructionSource
      OfValuationBallRecordSource

```

take the target-charted exact-theta adjusted-summand source, construct the product-hull-backed or principal valuation-ball-backed finite-divisor source internally, and then invoke the strongest current finite product-formula Ob7 route. Consequently the returned  $C_\Theta$  dichotomy now carries the exact-theta Step (xi) provenance through the Remark 3.9.5 product-hull, principal  $\lambda\mathcal{O}$ , valuation-ball topology/Haar, Ob5 quotient, Ob6 approximant, and Ob7 log-Kummer/product-formula layers. The record-canonical valuation-ball variant derives the principal valuation-ball source-core synchronization from the same possible-image family equality with the Theorem 3.11 record and the equality with the record-canonical valuation-ball adjusted source before invoking this final topology/Haar  $C_\Theta$  endpoint.

The exact-theta route has also been pushed through the projected-factorwise local log-coordinate refinement. The constructor

```

    _toValuationUnitBallNonzeroScalar
      LocalLogCoordinateProjectedFactorwiseTargetTransportSource,
    _toValuationUnitBallNonzeroScalar
      LocalLogCoordinateProjectedFactorwiseTargetTransportSource
      OfValuationBallRecordSource

```

builds the projected-factorwise transport source from the target-charted Step (xi) source by first constructing the principal valuation-ball finite-divisor source and then attaching the literal dependent-product local factor data. The record-canonical variant derives the principal valuation-ball source-core equality from the Theorem 3.11 possible-image synchronization and the record-canonical valuation-ball adjusted source before adding these local coordinate factors. The corresponding final wrappers

```

    _valuationUnitBallNonzeroScalarProjectedFactorwise
      CanonicalCThetaScaleDichotomyWithTopologyFiniteExtensionHaar
      Ob5Ob6Ob7AuditAtQChoice
      OfCoricThetaMuProductFormulaConstructionSource,
    _valuationUnitBallNonzeroScalarProjectedFactorwise
      CanonicalCThetaScaleDichotomyWithTopologyFiniteExtensionHaar
      Ob5Ob6Ob7AuditAtQChoice
      OfCoricThetaMuProductFormulaConstructionSource
      OfValuationBallRecordSource

```

returns the target-point transport audit together with the principal topology/Haar Ob5–Ob7 audit and the canonical-scale dichotomy. Thus the current strongest endpoint carries, simultaneously, exact-theta Step (xi) provenance, explicit product-index/valuation-place transport, local  $\lambda_v O_v$  scalar-image regions, valuation-unit-ball provenance, and finite product-formula Ob7 provenance.

The same exact-theta final route now has a valuation-log-image form. The constructor

```
_toValuationUnitBallNonzeroScalarValuationLogImage
  ProjectedFactorwiseTargetTransportSource,
_toValuationUnitBallNonzeroScalarValuationLogImage
  ProjectedFactorwiseTargetTransportSource
  OfValuationBallRecordSource
```

builds the projected-factorwise source from the target-charted Step (xi) source while defining the local coordinate regions as  $\ell_v(O_v)$  and  $\ell_v(\lambda_v O_v)$ . The record-canonical version derives the principal valuation-ball source-core equality from the Theorem 3.11 possible-image family synchronization and the record-canonical valuation-ball adjusted source. The corresponding final wrappers with suffix

```
_valuationUnitBallNonzeroScalarValuationLogImage
  ProjectedFactorwiseCanonicalCThetaScaleDichotomy
  WithTopologyFiniteExtensionHaarOb5Ob6Ob7AuditAtQChoice
  OfCoricThetaMuProductFormulaConstructionSource,
_valuationUnitBallNonzeroScalarValuationLogImage
  ProjectedFactorwiseCanonicalCThetaScaleDichotomy
  WithTopologyFiniteExtensionHaarOb5Ob6Ob7AuditAtQChoice
  OfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```

returns the same target-point transport audit, principal topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy, but no longer accepts separate per-place image-equality hypotheses for the local coordinate regions. In the record-canonical variant it also no longer accepts the valuation-ball source-core equality as an independent input.

The finite-sum target-point form now has the same record-canonical strengthening. The constructor

```
_toValuationUnitBallNonzeroScalarValuationLog
  FiniteSumTargetPointSource
  OfValuationBallRecordSource
```

uses the actual point map

$$x \mapsto \left\{ \text{coord} = \sum_v \ell_v(x_v) \right\}$$

and asks only for the two transported target-point synchronizations with the principal local-integer and selected-hull regions. The valuation-ball source-core equality is derived from the same record-canonical valuation-ball source used above. The corresponding final endpoint

```
_valuationUnitBallNonzeroScalarValuationLog
  FiniteSumTargetPointCanonicalCThetaScaleDichotomy
  WithTopologyFiniteExtensionHaarOb5Ob6Ob7AuditAtQChoice
  OfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```



returns the target-point transport audit, the principal topology/Haar Ob5–Ob7 audit, and the canonical-scale dichotomy at this lower boundary. Thus the source-facing route has descended from per-place image regions to the finite local valuation/log sum as a point-level transport construction, while keeping the Theorem 3.11 possible-image synchronization as the source of the principal valuation-ball comparison.

This record-canonical finite-sum endpoint has also been pushed through the coordinate-place refinement. The new constructor

```
_toValuationUnitBallNonzeroScalarCoordinatePlace
  ValuationLogFiniteSumTargetPointSource
  OfValuationBallRecordSource
```

uses the valuation cover’s coordinate-place map as an equivalence  $\delta \simeq \gamma_{\text{local}}$  and derives the older local-index compatibility from it. Its final endpoint

```
_valuationUnitBallNonzeroScalarCoordinatePlace
  ValuationLogFiniteSumTargetPointCanonicalCThetaScaleDichotomy
  WithTopologyFiniteExtensionHaarOb5Ob6Ob7AuditAtQChoice
  OfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```

therefore reaches the same target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy from the source-facing coordinate/place synchronization rather than from an arbitrary supplied index/place compatibility.

The same record-canonical route now descends one step further to normalized Haar log-coordinates. The constructor

```
_toValuationUnitBallNonzeroScalarHaarLogCoordinate
  FiniteSumTargetPointSource
  OfValuationBallRecordSource
```

replaces the raw local maps  $\ell_v$  by local Haar-log-coordinate sources: each  $\ell_v(x_v)$  is the normalized Haar log-volume of the source’s local region attached to  $x_v$ . The transported target-point equalities remain the two synchronizations with the principal local-integer and selected-hull regions, and the principal valuation-ball source-core equality is still derived from the record-canonical valuation-ball source. The final endpoint

```
_valuationUnitBallNonzeroScalarHaarLogCoordinate
  FiniteSumTargetPointCanonicalCThetaScaleDichotomy
  WithTopologyFiniteExtensionHaarOb5Ob6Ob7AuditAtQChoice
  OfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```

therefore reaches the target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy from a source boundary that records the Haar-log-volume origin of every local valuation/log coordinate.

The compact-open Haar finite-sum layer has now received the same record-canonical upgrade. The constructor

```
_toValuationUnitBallNonzeroScalarCompactOpen
  HaarLogCoordinateFiniteSumTargetPointSource
  OfValuationBallRecordSource
```

starts from local compact-open Haar-log-coordinate sources, so every local region  $U_{v,x_v}$  carries finite-extension topological Haar provenance before being sent to the target point  $\{\text{coord} = \sum_v \ell_v(x_v)\}$ . As in the preceding Haar layer, the transported target-point equalities are checked against the principal local-integer and selected-hull regions of the constructed valuation-ball source, while the source-core equality is derived from the record-canonical valuation-ball adjusted source. The corresponding final endpoint

```
_valuationUnitBallNonzeroScalarCompactOpen
  HaarLogCoordinateFiniteSumTargetPointCanonicalCThetaScale
  DichotomyWithTopologyFiniteExtensionHaarOb5Ob6Ob7
  AuditAtQChoiceOfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```

therefore reaches the target-point transport audit, the principal topology/Haar Ob5–Ob7 audit, and the canonical-scale dichotomy from the compact-open local Haar boundary, without accepting the valuation-ball source-core equality as an independent hypothesis at this level.

The centered valuation-ball Haar finite-sum layer now has the same record-canonical form. The constructor

```
_toValuationUnitBallNonzeroScalarCenteredValuationBall
  HaarLogCoordinateFiniteSumTargetPointSource
  OfValuationBallRecordSource
```

specializes each compact-open local factor to a centered closed valuation ball  $\overline{B}(x_v, r_v)$  in a proper ultrametric local carrier. The local source supplies the centered-ball Haar log-coordinate and proves the compact-open provenance needed by the preceding layer. The record-canonical constructor still derives the principal valuation-ball source-core equality from the valuation-ball adjusted source, so the two transported target-point equalities are the only remaining local synchronization data at this boundary. The final endpoint

```
_valuationUnitBallNonzeroScalarCenteredValuationBall
  HaarLogCoordinateFiniteSumTargetPointCanonicalCThetaScale
  DichotomyWithTopologyFiniteExtensionHaarOb5Ob6Ob7
  AuditAtQChoiceOfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```

returns the same target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy after projecting through the compact-open Haar finite-sum route.

The valued-field integer centered-ball layer has also been made record-canonical. The constructor

```
_toValuationUnitBallNonzeroScalarValuedFieldInteger
  CenteredValuationBallHaarLogCoordinateFiniteSumTargetPointSource
  OfValuationBallRecordSource
```

replaces the abstract proper-ultrametric local carrier by a nontrivially-normed valued field with its integer-source Haar normalization. Thus the local centered ball and its compact-open Haar provenance are read from valued-field integer data before the source projects to the centered-ball finite-sum corridor. The final endpoint

```
_valuationUnitBallNonzeroScalarValuedFieldInteger
  CenteredValuationBallHaarLogCoordinateFiniteSumTargetPoint
  CanonicalCThetaScaleDichotomyWithTopologyFiniteExtension
  HaarOb5Ob6Ob7AuditAtQChoiceOfCoricThetaMuProductFormula
  ConstructionSourceOfValuationBallRecordSource
```

returns the same target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy after deriving the valuation-ball source-core equality from the record-canonical valuation-ball adjusted source.

The concrete  $p$ -adic centered-ball layer now has the same record-canonical endpoint. The constructor

```
_toValuationUnitBallNonzeroScalarPadicCenteredValuationBall
  HaarLogCoordinateFiniteSumTargetPointSource
  OfValuationBallRecordSource
```

fixes the local factor at a valuation place  $v$  to the actual field  $\mathbb{Q}_{p_v}$ , with the integer ring, residue prime, and Haar normalization supplied by the  $p$ -adic centered valuation-ball source. It still derives the principal valuation-ball source-core equality from the record-canonical valuation-ball adjusted source, and only retains the two transported target-point synchronizations with the constructed principal regions. The final endpoint

```
_valuationUnitBallNonzeroScalarPadicCenteredValuationBall
  HaarLogCoordinateFiniteSumTargetPointCanonicalCThetaScale
  DichotomyWithTopologyFiniteExtensionHaarOb5Ob6Ob7
  AuditAtQChoiceOfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```

then reaches the target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy after projecting through the valued-field integer finite-sum route.

The concrete finite-extension  $p$ -adic centered-ball layer now has the same record-canonical strengthening. The constructor

```
_toValuationUnitBallNonzeroScalarPadicFiniteExtension
  CenteredValuationBallHaarLogCoordinateFiniteSumTargetPointSource
  OfValuationBallRecordSource
```

replaces the base local factor  $\mathbb{Q}_{p_v}$  by an actual finite-dimensional local extension  $K_v/\mathbb{Q}_{p_v}$ . The local Haar coordinate records the finite-extension degree  $\text{finrank}_{\mathbb{Q}_{p_v}} K_v$ , the residue prime  $p_v$ , and the uniformizer scaling map  $x \mapsto p_v x$  through the algebra map into  $K_v$ . As in the base  $p$ -adic endpoint, the principal valuation-ball source-core equality is derived from the record-canonical valuation-ball adjusted source; the endpoint only retains the two target-point synchronizations identifying the transported local integer and selected-scalar images with the constructed principal regions. The final endpoint

```
_valuationUnitBallNonzeroScalarPadicFiniteExtension
  CenteredValuationBallHaarLogCoordinateFiniteSumTargetPoint
  CanonicalCThetaScaleDichotomyWithTopologyFiniteExtension
  HaarOb5Ob6Ob7AuditAtQChoiceOfCoricThetaMuProductFormula
  ConstructionSourceOfValuationBallRecordSource
```

then reaches the same target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy through the finite-extension valued-field integer projection.

The finite-extension  $p$ -adic endpoint has also been strengthened by base-prime dilation topology in record-canonical form. The constructor

```
_toValuationUnitBallNonzeroScalarPadicFiniteExtensionDilation
  CenteredValuationBallHaarLogCoordinateFiniteSumTargetPointSource
  OfValuationBallRecordSource
```

uses the same record-canonical valuation-ball adjusted source to construct the principal hull/determinant source, but each local factor now supplies a homeomorphism-backed Haar source for multiplication by the image of  $p_v$  in  $K_v$ . Thus the local source carries the finite-extension degree and residue-prime data of the previous layer together with the open/compact provenance of the base-prime dilation used by the finite-extension Haar normalization. The final endpoint

```
_valuationUnitBallNonzeroScalarPadicFiniteExtensionDilation
  CenteredValuationBallHaarLogCoordinateFiniteSumTargetPoint
  CanonicalCThetaScaleDichotomyWithTopologyFiniteExtension
  HaarOb5Ob6Ob7AuditAtQChoiceOfCoricThetaMuProductFormula
  ConstructionSourceOfValuationBallRecordSource
```

then projects through the finite-extension layer and returns the same target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy.

The same finite-extension local-field boundary now has a record-canonical constructed dilation-mass refinement. The constructor

```
_toValuationUnitBallNonzeroScalarPadicFiniteExtensionConstructed
  DilationMassCenteredValuationBallHaarLogCoordinateFiniteSum
  TargetPointSourceOfValuationBallRecordSource
```

keeps the valuation-ball record source as the origin of the principal hull/determinant object, while each local factor supplies the constructed nonzero base-prime dilation and the real-valued Haar scaling law

$$\mu_v(p_v S_v)_{\mathbb{R}} = \mu_v(S_v)_{\mathbb{R}} / p_v^{[K_v:\mathbb{Q}_{p_v}]}$$

for all local subsets  $S_v$ . The final endpoint

```
_valuationUnitBallNonzeroScalarPadicFiniteExtensionConstructed
  DilationMassCenteredValuationBallHaarLogCoordinateFiniteSum
  TargetPointCanonicalCThetaScaleDichotomyWithTopology
  FiniteExtensionHaarOb5Ob6Ob7AuditAtQChoiceOfCoricThetaMu
  ProductFormulaConstructionSourceOfValuationBallRecordSource
```

therefore exposes the local nonzero scalar facts, pointwise dilation formula, all-subset Haar mass formula, target-point transport audit, topology/Haar Ob5–Ob7 audit, and canonical-scale dichotomy in one record-canonical route.

The record-canonical finite-extension boundary has now been lowered one step further from real-valued mass scaling to the measure-level Haar modulus. The new constructor

```
_toValuationUnitBallNonzeroScalarPadicFiniteExtensionConstructed
  DilationHaarModulusCenteredValuationBallHaarLogCoordinate
  FiniteSumTargetPointSourceOfValuationBallRecordSource
```

uses the same valuation-ball record source for the principal hull/determinant object, but each local factor now supplies the identity in  $\mathbb{R}_{\geq 0} \cup \{\infty\}$

$$\mu_v(p_v S_v) = \text{ofReal}\left(p_v^{-[K_v:\mathbb{Q}_{p_v}]}\right) \cdot \mu_v(S_v)$$

for every subset  $S_v \subseteq K_v$ . The corresponding endpoint

```
_valuationUnitBallNonzeroScalarPadicFiniteExtensionConstructed
  DilationHaarModulusCenteredValuationBallHaarLogCoordinate
  FiniteSumTargetPointCanonicalCThetaScaleDichotomyWithTopology
  FiniteExtensionHaar0b50b60b7AuditAtQChoiceOfCoricThetaMu
  ProductFormulaConstructionSourceOfValuationBallRecordSource
```

first exposes this all-subset Haar-modulus formula and then projects through the constructed dilation-mass corridor to the canonical-scale dichotomy. Thus the Step (xi) route now distinguishes the genuine measure identity from its `toReal` mass-shadow at the record-canonical experiment surface.

The same record-canonical route now has the next lower Haar-character refinement. The constructor

```
_toValuationUnitBallNonzeroScalarPadicFiniteExtensionConstructed
  DilationHaarCharacterCenteredValuationBallHaarLogCoordinate
  FiniteSumTargetPointSourceOfValuationBallRecordSource
```

keeps the valuation-ball principal hull/determinant source fixed, but replaces the local measure identity by the additive Haar-character scalar for multiplication by  $p_v$ :

$$\text{addEquivAddHaarChar}(x \mapsto p_v x) = p_v^{-[K_v:\mathbb{Q}_{p_v}]}.$$

The final record-canonical endpoint first exposes this scalar, then the derived all-subset Haar-modulus formula, and finally the same canonical-scale dichotomy through the Haar-modulus route. In this layer the analytic source datum is therefore the Haar-character evaluation; the measure-level formula is a derived projection.

The record-canonical local Haar boundary has also been lowered to normalized valuation-unit-ball mass. The new constructor

```
_toValuationUnitBallNonzeroScalarPadicFiniteExtensionUnitBall
  HaarCharacterCenteredValuationBallHaarLogCoordinateFiniteSum
  TargetPointSourceOfValuationBallRecordSource
```

retains the same principal valuation-ball hull/determinant source, while each local factor supplies

$$\mu_v(\mathcal{O}_v) = 1, \quad \mu_v(p_v \mathcal{O}_v) = p_v^{-[K_v:\mathbb{Q}_{p_v}]}.$$

The corresponding endpoint exposes these two local mass facts, derives the additive Haar-character scalar, derives the all-subset Haar-modulus formula, and then reaches the canonical-scale dichotomy through the Haar-character route.

The record-canonical surface now also uses the core specialization theorem that derives the unit-ball Haar-character source from the constructed all-subset Haar-modulus source. The new endpoint

```
_valuationUnitBallNonzeroScalarPadicFiniteExtensionConstructed
  DilationHaarModulusDerivedUnitBallHaarCharacterCentered
  ValuationBallHaarLogCoordinateFiniteSumTargetPointCanonical
  CThetaScaleDichotomyWithTopologyFiniteExtensionHaar0b50b60b7
  AuditAtQChoiceOfCoricThetaMuProductFormulaConstructionSource
  OfValuationBallRecordSource
```

takes the constructed Haar-modulus local source and regularity of the Haar measure, then derives  $\mu_v(\mathcal{O}_v) = 1$ ,  $\mu_v(p_v \mathcal{O}_v) = p_v^{-[K_v:\mathbb{Q}_{p_v}]}$ , the additive Haar-character scalar, the all-subset Haar-modulus formula, and the same canonical-scale dichotomy. Thus the  $p_v \mathcal{O}_v$  mass is no longer a separate record-canonical hypothesis. The remaining local analytic gap below this layer is now the source construction of the valuation ring  $\mathcal{O}_v$ , its normalized Haar mass, Haar regularity, and the all-subset base-prime Haar-modulus identity from the actual p-adic/Frobenioid input data.

The milestone-facing constructed source now also factors its log-volume comparison through the generic record-canonical Remark 3.9.5 bridge source. The projection `toRecordHullDeterminantBridgeSource` packages the same  $\phi$ -hull operator, Theorem 3.11 possible-image family, q-region containment, Ob3/Ob5 determinant compatibility, and Ob4 tensor-power bound as the record bridge source. The new constructed-record bridge audit, exposed on the experiment surface, records that the constructed source's q-to-determinant-to-theta chain is read from this generic Remark 3.9.5 bridge theorem rather than re-proved as an isolated comparison. This audit now also has a leaner proof shape: it stores the coarse record-bridge endpoint and the constructed-source endpoint, while Lean derives the named projection theorems for q-hull containment, determinant-log comparison, normalized determinant comparison, and the final  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. In particular, the normalized determinant chain

$$\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}.$$

is a theorem projected from the record bridge endpoint, not an additional field of the audit object. The experiment surface exposes this two-step normalized form as

`remark395ConstructedHolomorphicHullDeterminantSource_normalizedRecordBridge.`

The public constructor endpoints for the record bridge, the exact-theta bridge, the constructed source, and the possible-image-choice constructor now include the same normalized inequalities directly in their returned conjunctions. Thus the milestone route displays  $\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}$  at the point where the Step (xi) source is built, not only after a later audit projection. The constructor-backed finite-divisor source now exposes the same bridge projection directly. Its experiment-surface audit,

`remark395ConstructorBackedConstructedHullDeterminant  
FiniteDivisorVerticalIQ_recordBridgeAudit,`

starts from the constructor-backed adjusted source, constructs the record Remark 3.9.5 bridge internally, and records

$$\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} = \det_{\log} \leq \theta_{\text{signed}}$$

together with the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison projected from the same Theorem 3.11 hull/determinant constructor. Thus the newest finite-divisor endpoint no longer hides the Step (xi) q-to-normalized-determinant-to-theta comparison behind only the constructed obligations equality; the remaining external input at the  $C_{\Theta}$  endpoint is still the global numeric estimate. The corresponding compact endpoint

`remark395ConstructorBackedConstructedOb3Ob5AdjustedHull  
DeterminantFiniteDivisorVerticalIQ  
_cThetaDichotomyWithRecordBridgeAudit`

returns this constructor-backed record bridge audit together with the finite-divisor vertical- $IQ$   $C_{\Theta}$  dichotomy. Thus the public milestone surface now carries the normalized Step (xi) bridge

and the conditional Corollary 3.12 dichotomy in one theorem. The finite-divisor constructor-backed source now also has a product-hull-backed form. This source records that the measured holomorphic-hull operator used by the constructed Step (xi) source is induced by an `IUTStage1Remark395ProductHullSystemSource`. Its audit identifies

$$\phi(P_{\text{rec}})$$

with the selected product hull obtained as the intersection of all product hulls containing the Theorem 3.11 possible-image union  $P_{\text{rec}}$ , proves  $q \subseteq \phi(P_{\text{rec}})$ , proves minimality among such product hulls, and identifies the hull log-volume with the product-hull log-volume. The endpoint

```
remark395ProductHullBackedConstructorBackedConstructed
Ob30b5AdjustedHullDeterminantFiniteDivisorVerticalIQ
_cThetaDichotomyWithProductHullAudit
```

returns this product-hull audit together with the finite-divisor vertical- $IQ$   $C_\Theta$  dichotomy. Thus the current finite-divisor milestone no longer forgets the source-paper “smallest product hull” formulation when it enters the downstream Corollary 3.12 corridor. The product-hull source now also has a smaller possible-image containment audit,

```
remark395ProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQ
_possibleImageContainmentAudit.
```

This audit separates the Ob1/Ob2 absorption facts from the later Ob5 and determinant payloads. It records that the source-facing possible-image family has union  $P_{\text{rec}}$ , that both  $\phi(P_{\text{rec}})$  and the canonical  $\Phi(P_{\text{rec}})$  approximant are the selected smallest product hull, and that

$$P_{\text{rec}} \subseteq \phi(P_{\text{rec}}), \quad P_i \subseteq \phi(P_{\text{rec}}), \quad q \subseteq P_{\text{rec}} \subseteq \phi(P_{\text{rec}}).$$

These containments are proved from the product-hull intersection law and the constructor-backed q-choice possible image; they are no longer hidden inside the later quotient/determinant audits. The same finite-divisor surface now has a principal-product-hull refinement. The source

```
IUTStage1Remark395PrincipalProductHullBackedConstructorBacked
ConstructedHullDeterminantFiniteDivisorVerticalIQSource
```

uses a principal  $\lambda \cdot O$  hull system instead of a bare product-hull system, then forgets to the existing product-hull-backed source. Its audit records that the selected hull is the scalar image

$$\lambda_{\text{sel}} \cdot O,$$

that  $\lambda_{\text{sel}}$  satisfies the nonzero-parameter predicate, that the Theorem 3.11 possible-image union and q-pilot region lie in this selected principal product hull, and that this selected hull is minimal among principal product hulls containing the possible-image union. The public finite-divisor endpoint

```
remark395PrincipalProductHullBackedConstructorBackedConstructed
Ob30b5AdjustedHullDeterminantFiniteDivisorVerticalIQ
_cThetaDichotomyWithPrincipalProductHullAudit
```

returns this principal-hull audit together with the usual conditional  $C_\Theta$  dichotomy. This pushes the product-hull boundary one step closer to the source-paper formula of Remark 3.9.5(i), where

hulls are smallest regions of the form  $\lambda \cdot O$ . The product-hull-backed source also exposes an Ob5 quotient/determinant audit,

```
remark395ProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQ
_ob5QuotientDeterminantAudit.
```

Given a nonempty q-choice possible image and a nonempty comparison possible image, this audit proves that both images collapse to the distinguished upper-semi quotient point modulo the selected product hull and hence have the same quotient image. It also identifies  $\mu_{\log}(\phi(P_{\text{rec}}))$  with the product-hull log-volume, the normalized determinant, the determinant log-volume, and the normalized tensor-power log-volume, while retaining the q-pilot log-volume bound into the selected product hull and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. This is the first finite-divisor product-hull surface where the source-paper “smallest product hull” formulation and the Remark 3.9.5(Ob5) quotient-compatible determinant formalism are visible in one audit object. The same Ob5 boundary now has a q-pilot-derived variant:

```
productHullBackedOb5QuotientDeterminantAudit
_of_qPilotRegion_nonempty.
```

Here Lean derives nonemptiness of the selected q-choice possible image from nonemptiness of the q-pilot region and the constructor-backed inclusion  $q \subseteq P_{q\text{-choice}}$ . Thus the q-side quotient collapse no longer needs a separate selected-possible-image nonemptiness premise at this product-hull boundary. The same source now also has a  $\Phi/\Xi$ -approximant audit,

```
remark395ProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQ
_phiXiApproximantAudit.
```

It constructs the source-facing possible-image family  $P_B = \{P_\beta\}_{\beta \in B}$  directly from the product-hull system and the Theorem 3.11 possible-image regions. Lean proves that the family union is  $P_{\text{rec}}$ , that the canonical hull  $\phi(P_B)$  is the selected smallest product hull, and that the canonical  $\Phi(P_B)$  approximant is this same hull. If an exact  $\Xi(P_B)$  family is supplied, the audit proves

$$H_{\Xi(P_B)} = \phi(P_B)$$

at the selected product-hull boundary, records the exact  $\Xi$ -member log-volume equality, and proves that  $H_{\Xi(P_B)}$  has the same collapsed upper-semi quotient image as any nonempty comparison possible image. This threads the paper’s  $\Phi(P)$ ,  $\Xi(P)$ , and  $H_{\Xi(P)}$  formalism into the strongest current finite-divisor product-hull route instead of leaving it only at the generic source-core endpoint. The same product-hull source now exposes the Ob6 log-volume version of this audit,

```
remark395ProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQ
_ob6HullApproximantLogVolumeAudit.
```

This audit identifies both  $H_{\Phi(P_B)}$  and  $H_{\Xi(P_B)}$  with the selected product hull, proves

$$\mu_{\log}(P_B) \leq \mu_{\log}(H_{\Phi(P_B)}), \quad \mu_{\log}(P_B) \leq \mu_{\log}(H_{\Xi(P_B)}),$$

and records the corresponding comparison-region and q-pilot inequalities into the  $H_{\Xi(P_B)}$  log-volume. The normalized determinant equality and the raw  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison remain in



the same audit object, so the Ob6 passage is now visible directly on the finite-divisor product-hull route. This Ob6 boundary now has a canonical exact- $\Xi$  specialization: instead of supplying arbitrary  $\Phi(P_B)$  and  $\Xi(P_B)$  families, the route takes the exact source calibration  $\mu_{\log}(\phi(P_B)) = \mu_{\log}(P_B)$ , uses the canonical  $\Phi(P_B)$  approximant, and constructs the exact  $\Xi(P_B)$  family from that calibration. Thus the remaining payload at this point is the source construction of the exact log-volume equality, not a free choice of approximant families. At the concrete Hodge-theater/log-theta boundary, this exact- $\Xi$  route now also has a source-derived  $C_\Theta$  variant,

`concreteHodgeTheaterLogThetaConcreteCalibratedExactXi  
SelectedQRemark395SourceDerivedCThetaAudit.`

Here the global constant is the *IUT IV* estimate's  $C_\Theta$ , and the required domination  $C_{\Theta, \text{can}} \leq C_\Theta$  is projected from the local-to-global arithmetic-gap source. The public concrete exact- $\Xi$  boundary therefore no longer has to expose that domination as a raw scalar hypothesis. The same source-derived form now reaches the closed-family and product-hull exact- $\Xi$  boundaries: closedness constructs the calibration, the product-hull witness constructs closedness, and the local-to-global source supplies the  $C_\Theta$  comparison in both cases. The construction of the arithmetic-gap source itself remains part of the local *IUT IV* payload. This source-derived form now also reaches the principal valuation-ball local boundary, and that boundary has been lowered through realized-region equality to a local log-shell exact statement. Starting from a principal cover whose possible regions are transported theta regions, Lean now accepts the two local identities that a transported theta region is the realized image of its selected log-shell and that this log-shell is the compact-open valuation ball. It can also derive these identities from the pointwise local construction: theta-region points have chosen compact-open valuation-ball representatives, and compact-open valuation-ball points realize back into the transported theta region. This pointwise source is now constructed from compact-open local-chart data, from the compact-open log-Kummer graph source, and from the possible-region log-Kummer map source after rewriting the cover possible region as the transported theta region. The resulting construction builds the exact  $\Xi(P_B)$  family and uses the local-to-global arithmetic source for the global  $C_\Theta$  comparison, without reintroducing a caller-supplied scalar domination after the product-hull lowering. The same specialization now propagates through the synchronized Ob5–Ob7 review object and the canonical-scale audit: the product-hull route can run with canonical  $\Phi(P_B)$  and source-constructed exact  $\Xi(P_B)$  while retaining the Ob7 prime-strip/log-Kummer data. In the strongest product-hull surface, the finite product-formula Ob7 construction feeds the canonical  $C_\Theta$  audit without reintroducing caller-chosen approximant families. The downstream finite-divisor dichotomy has now been lowered to the same boundary: from the exact  $\Xi(P_B)$  calibration and the product-formula Ob7 source, Lean selects the canonical approximant index and derives the canonical-scale  $C_\Theta$  alternative directly. The product-hull boundary also exposes an exact-theta bridge audit,

`remark395ProductHullBackedConstructorBackedConstructed  
HullDeterminantFiniteDivisorVerticalIQ  
_exactThetaBridgeAudit.`

This audit does not add a new comparison possible image. It packages the source-facing identities already needed by the determinant route:

$$\theta_{\text{signed}} = \mu_{\log}(\phi(P_B)), \quad \mu_{\log}(\phi(P_B)) = \det_{\text{norm}} = \det,$$

with  $\phi(P_B)$  the selected smallest product hull. From the exact theta/family-hull equality, Lean derives the normalized tensor-power upper bound into  $\theta_{\text{signed}}$ , and the audit records the chain

$$\mu_{\log}(q) \leq \mu_{\log}(\phi(P_B)) = \det_{\text{norm}} \leq \theta_{\text{signed}}.$$

Thus the strongest current product-hull surface separates the remaining open source task—constructing the actual IUT product-hull/determinant data—from the ordered-real and determinant-log-volume consequences already checked by the kernel. The same surface now has an Ob7 log-Kummer compatibility audit,

```
remark395ProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQ
_ob7LogKummerCompatibilityAudit.
```

Given a finite  $F^{\times\mu}$ -prime-strip lift whose global realified Frobenioid log-volume agrees with the determinant log-volume, this audit identifies the family-hull and normalized determinant log-volumes with that prime-strip global value and proves

$$\mu_{\log}(q) \leq \mu_{\log}(F_{\text{global}}^{\times\mu}).$$

For every environment prime it also returns the corresponding Gaussian prime-to-place equality, equality of local realified log-volumes at the evaluated prime, and equality of Gaussian and environment unit characters. Thus the product-hull route now retains the Ob7 log-Kummer/Frobenioid data at the precise boundary where the determinant comparison enters the 3.12 corridor. The same Ob7 boundary now has a source-object form. The declarations with suffixes

```
Ob7LogKummerCompatibilityAuditOfSource,
Ob5Ob6Ob7SynchronizedAuditAtQChoiceOfQPilotRegionNonemptyOfOb7Source
```

take the typed Remark 3.9.5(Ob7) compatibility source itself, rather than a loose prime-strip lift together with a separate determinant/global-log-volume equality. The only synchronization left at this boundary is the proof that the Ob7 source’s hull/determinant bridge is the constructed product-hull Step (xi) bridge. Thus the determinant-to-prime-strip comparison, local prime/place square, local realified Frobenioid readings, and unit-character transport are reviewed as one source-paper object. There is now a further coric form of the same Ob7 boundary. The core source

```
IUTStage1Remark395Ob7CoricLogKummerCompatibilitySource
```

uses the finite  $F^{+ \times \mu}$  invariant: a common unit character on the valuation set  $V$  whose pullbacks are the environment and Gaussian unit characters. It projects to the ordinary Ob7 source, while the product audit

```
Ob7CoricLogKummerCompatibilityAudit
```

keeps the projected Ob7 determinant comparison together with the coric unit equalities. The q-choice Ob5–Ob7 synchronized and canonical-scale audits now also have `OfCoricOb7Source` forms, so the unit part of Ob7 is no longer represented only by a transported equality between two prime-strip unit characters. This coric boundary has now been lowered one more step toward the source-paper Corollary 4.7(iv) construction. The declaration

```
ProductHullBackedCoricThetaMuOb7ConstructionSource
```

does not take a completed  $F^{+ \times \mu}$  invariant as input. It takes an  $F^{\times\mu}$ -prime-strip lift, a common coric unit character on  $V$ , the environment pullback equality, and the determinant/global log-volume identification. Lean constructs the coric invariant by

```
IUTStage1CoricThetaMuPrimeStripInvariant.
ofLiftAndCoricUnitCharacter,
```

then derives the Gaussian coric pullback equality from the prime-strip evaluation square. The product-hull and principal topology/Haar audit surfaces now have `OfCoricThetaMuConstructionSource` forms, so this finite Corollary 4.7(iv) construction is visible at the same Ob5–Ob7 boundary as the Remark 3.9.5 hull and determinant data. The product-hull final dichotomy now has the corresponding `OfCoricOb7Source` endpoint: the canonical-scale  $C_\Theta$  dichotomy is returned together with the synchronized Ob5–Ob7 audit while consuming the single coric  $F^{+\times\mu}$  Ob7 source and its bridge equality with the constructed Remark 3.9.5 hull/determinant source, rather than a raw prime-strip lift and determinant-global equality. The product-hull boundary now also has a synchronized Ob5–Ob7 review object,

```
remark395ProductHullBackedConstructorBackedConstructed
HullDeterminantFiniteDivisorVerticalIQ
_ob50b60b7SynchronizedAudit.
```

It packages the Ob6  $H_{\Phi(P_B)}/H_{\Xi(P_B)}$  log-volume audit and the Ob7 finite  $F^{\times\mu}$ -prime-strip audit in one source object, while also recording that the Ob7 hull/determinant bridge uses exactly the same Theorem 3.11 possible-image family and the same selected product-hull operator as the Ob6 approximant boundary. Thus a prime-strip log-volume comparison can no longer be reviewed at this surface independently of the product-hull possible-image family whose Ob5 quotient collapse and Ob6 approximant inequalities are being used. This synchronized review object is now threaded through the finite-divisor vertical- $IQ$  boundary as well. The experiment endpoint

```
remark395ProductHullBackedConstructorBackedConstructed
Ob30b5AdjustedHullDeterminantFiniteDivisorVerticalIQ
_cThetaDichotomyWithOb50b60b7SynchronizedAudit
```

returns the synchronized Ob5–Ob7 audit together with the usual conditional  $C_\Theta$  dichotomy. Thus the strongest current product-hull finite-divisor route no longer reviews the final ordered-real conclusion after forgetting the Ob5 quotient, Ob6 hull-approximant, and Ob7 log-Kummer provenance attached to the same Remark 3.9.5 hull. This route now also has

```
_cThetaDichotomyWithOb50b60b7SynchronizedAudit
OfQPilotRegionNonempty,
```

which replaces the direct q-choice possible-image nonemptiness hypothesis by a nonempty q-pilot region. The synchronized audit then obtains the selected possible-image witness internally from  $q \subseteq P_{q\text{-choice}}$ , so the public finite-divisor review target is closer to the source-paper q-pilot-object formulation. There is now a further q-choice-specialized version,

```
_cThetaDichotomyWithOb50b60b7SynchronizedAudit
AtQChoiceOfQPilotRegionNonempty,
```

and its canonical-scale analogue. In this endpoint the Ob5 comparison possible image is not an arbitrary extra choice: it is the constructor-backed q-choice itself. Hence the single nonempty q-pilot region supplies both quotient-collapse nonemptiness witnesses through  $q \subseteq P_{q\text{-choice}}$ . The canonical-scale version therefore has neither an external numeric  $C_\Theta$  estimate nor a separate comparison-choice nonemptiness hypothesis. The constructor-built source-level canonical-scale bridge is now exposed directly as

```
possibleImageConstructorBuiltHullSource_remark395CanonicalCThetaBridgeAudit.
```

It records the chain  $\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}} \leq C_{\Theta, \text{can}} \cdot (-q_{\text{signed}})$  at the Step (xi) source boundary, separate from the downstream finite-divisor wrappers.

The same milestone-facing constructed source now has a possible-image q-choice constructor. In this form the q-pilot region is definitionally the chosen Theorem 3.11 possible image  $P_i$ , so Lean derives  $q \subseteq \bigcup_i P_i$  from the possible-image union rather than accepting that containment as a separate field. The endpoint then exposes containment in the record-canonical holomorphic hull, the Ob3/Ob4 weighted determinant payload, the q-to-determinant log-volume inequality, and the resulting  $q_{\text{signed}} \leq \theta_{\text{signed}}$  comparison. This is a small but important tightening of the current trust boundary: the generic Remark 3.9.5 bridge source can now be instantiated in the source-native possible-image case without an arbitrary q-region containment input.

The constructor-built Step (xi) source now also exposes the Remark 3.9.5(v)–(vi) upper-semi quotient passage as

```
possibleImageConstructorBuiltHullSource
_ob5QuotientIndependenceAudit.
```

Given two nonempty Theorem 3.11 possible images, the audit proves that both images collapse to the same point under the quotient by the bounded-family holomorphic hull  $\phi(\bigcup_i P_i)$ . The same record carries the bounded-family determinant/log-volume equality, the family-union log-volume bound, the normalized tensor-power equality, and the raw Step (xi) signed comparison. Thus Ob5 is now visible on the constructor-built public surface as the paper’s independence-of-possibilities quotient statement, not just as a background containment lemma.

The constructor-built Step (xi) source now has the same record-canonical Ob3/Ob5 projection. A shadow hull/log-volume object is first converted back to a Remark 3.9.5  $\phi$ -operator by `toRemark395Operator`; the constructor-built source then forms the record Ob3/Ob5 determinant-compatibility source and the record hull/determinant bridge source from its own q-region containment, determinant compatibility, and Ob4 tensor-power bound. The public `recordOb3Ob5BridgeAudit` endpoint records that the q-to-determinant and determinant-to-theta inequalities are obtained from the generic record-canonical bridge theorem. This does not construct the analytic determinant compatibility, but it removes another ad hoc audit boundary: the large constructor-built object now factors through the same source object as the milestone-facing constructed source.

The constructor-built Step (xi) source now also has a canonical local  $C_{\Theta}$ -scale audit. From q-pilot positivity it defines

$$C_{\Theta, \text{can}} = \theta_{\text{signed}} / (-q_{\text{signed}})$$

and proves internally that

$$\theta_{\text{signed}} \leq C_{\Theta, \text{can}} \cdot (-q_{\text{signed}}).$$

The canonical-one constructed-IPL finite-divisor route therefore has a no-external-bound endpoint

```
sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQSource
_canonicalOneConstructorBuiltIPLConstruction
CanonicalCThetaScaleDichotomy.
```

The same source now exposes the stronger audit

```
sourceDerivedHodgeSHEIPLHullFiniteDivisorVerticalIQSource
_canonicalOneConstructorBuiltIPLConstruction
Remark395CanonicalCThetaBridgeAudit.
```

This audit keeps the canonical local scale attached to the constructed Remark 3.9.5 bridge chain

$$\mu_{\log}(q\text{Region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}} \leq C_{\Theta, \text{can}} \cdot (-q_{\text{signed}}).$$

Thus the local no-external-bound scale is no longer merely a final ordered-real specialization; it is recorded beside the Ob1–Ob5 holomorphic-hull, determinant, and record Ob3/Ob5 bridge payload that produces the signed comparison. The compact constructed-hull finite-divisor endpoint now has the same audited canonical-scale form,

```
boundarySignedEqualityOrStrictCTheta_from_remark395
  ConstructedHullDeterminantFiniteDivisorVerticalIQ
    _canonicalCThetaScaleWithCanonicalScaleAudit.
```

It returns the constructed Remark 3.9.5 canonical-scale audit together with the finite-divisor vertical-*IQ* dichotomy, so the no-external-bound finite boundary exposes the normalized determinant bridge and the derived  $\theta_{\text{signed}} \leq C_{\Theta, \text{can}}(-q_{\text{signed}})$  estimate instead of only the final ordered-real conclusion. This does not yet identify  $C_{\Theta, \text{can}}$  with the global paper constant  $C_{\Theta}$ . Its purpose is narrower and useful: the theta/log-q upper bound is no longer an opaque route hypothesis for this local scale, and the remaining mathematical task is now isolated as the comparison between this canonical source scale and the IUT constant from the paper. This comparison boundary is now a named Lean object rather than prose. The constructed source theorem

```
IUTStage1Remark395ConstructedHolomorphicHullDeterminantSource
  .constructedGlobalCThetaScaleComparisonAudit
```

assumes only

$$C_{\Theta, \text{can}} \leq C_{\Theta}$$

for the chosen paper/global constant  $C_{\Theta}$ . From this domination and q-pilot positivity, Lean derives

$$\theta_{\text{signed}} \leq C_{\Theta} \cdot (-q_{\text{signed}})$$

and then applies the standard Corollary 3.12 ordered-real dichotomy. The experiment-surface endpoints

```
remark395ConstructedHolomorphicHullDeterminantSource
  _globalCThetaScaleComparisonAudit,
remark395ConstructedHolomorphicHullDeterminantSource
  _globalCThetaScaleChain
```

therefore replace the raw final numeric hypothesis by the sharper remaining source obligation “global  $C_{\Theta}$  dominates the constructed local Remark 3.9.5 scale”. This is still an obligation, but it is now the correct one to attack from the source-paper global estimate. This source-level comparison has now been threaded through the compact finite-divisor vertical-*IQ* boundary as

```
boundarySignedEqualityOrStrictCTheta_from_remark395
  ConstructedHullDeterminantFiniteDivisorVerticalIQ
    _globalCThetaScaleWithGlobalScaleAudit.
```

The endpoint assumes  $C_{\Theta, \text{can}} \leq C_{\Theta}$ , constructs the global-scale Remark 3.9.5 audit, derives the numeric  $\theta_{\text{signed}} \leq C_{\Theta}(-q_{\text{signed}})$  estimate internally, and then returns the finite-divisor dichotomy. Thus the finite Step (x) boundary no longer needs to expose the raw final numeric hypothesis when

the intended local-to-global  $C_\Theta$  comparison is the available source obligation. The paper-side  $C_\Theta$  expression from IUT IV is now connected to this same boundary. The experiment-surface audit

`Remark395ConstructedIUTIVCThetaHandoffAudit`

takes a constructed Remark 3.9.5 Step (xi) source and an `IUTStage1IUTIVCThetaPilotLogVolumeEstimateShadow`. The latter supplies the displayed IUT IV expression

$$C_\Theta = \text{arithmeticUpperTerm} - \text{mainLogTerm} - 1$$

together with the existing IUT IV handoff endpoint. The only new comparison input is again

$$C_{\Theta, \text{can}} \leq C_\Theta.$$

The compact endpoint

`remark395ConstructedHolomorphicHullDeterminantSource`  
`_iutIVCThetaHandoffChain`

then records, in one proposition, the IUT IV expression for  $C_\Theta$ , the constructed Step (xi) chain  $\mu_{\log}(q_{\text{Region}}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}}$ , the derived paper-side bound  $\theta_{\text{signed}} \leq C_\Theta(-q_{\text{signed}})$ , and the final Corollary 3.12 dichotomy. Thus the remaining global comparison is no longer split between the Step (xi) local scale audit and the separate IUT IV constant shadow. This IUT IV handoff has now been lifted to the compact finite-divisor vertical- $IQ$  boundary:

`boundarySignedEqualityOrStrictCTheta_from_remark395`  
`ConstructedHullDeterminantFiniteDivisorVerticalIQ`  
`_iutIVCThetaWithHandoffAudit.`

The endpoint consumes the constructed Remark 3.9.5 Step (xi) source, the IUT IV estimate object, and the single comparison  $C_{\Theta, \text{can}} \leq C_\Theta$ . It returns the IUT IV handoff inequalities, the constructed global-scale Remark 3.9.5 audit at `estimate.cTheta`, and the finite-divisor dichotomy. Thus the paper-side  $C_\Theta$  expression is visible at the same boundary as the Step (x) vertical- $IQ$  data. The first source-facing replacement of this last comparison is now in Lean. The structures

`IUTStage1Theorem311Ind1Action`, `IUTStage1Theorem311Ind2Action`,  
`IUTStage1Theorem311Ind3UpperSemiRelation`, `IUTStage1Theorem311TypedIndeterminacyCore`

replace the earlier name/boolean indeterminacy shadow on the local-to-global critical path by typed relations on a Theorem 3.11 choice space. The formal payload matches the source-paper asymmetry needed in the Corollary 3.12 corridor: (Ind<sub>1</sub>) and (Ind<sub>2</sub>) preserve procession-normalized log-volume, while (Ind<sub>3</sub>) supplies only an upper-semi log-volume inequality. The core constructs the generated quotient and quotient map, and the possible-image compatibility record states that (Ind<sub>1</sub>) and (Ind<sub>2</sub>) identify possible-image regions whereas (Ind<sub>3</sub>) contributes the one-sided estimate. A finite one-point witness `finiteToyCore` checks joint satisfiability of this typed interface; it is deliberately not an IUT model. The quotient layer is now explicit. The declaration

`IUTStage1Theorem311TypedIndeterminacyCore.`  
`EqualityQuotientPossibleImages`

indexes possible images by `Quot(equalityQuotient.relation)` and proves that pulling back along `equalityQuotientMap` recovers the original choice-indexed family. The direct (Ind<sub>1</sub>) and (Ind<sub>2</sub>)

steps are members of this equality orbit, while the equality quotient's  $(\text{Ind}_3)$  generator is empty;  $(\text{Ind}_3)$  remains available only through the upper-semi log-volume theorem. This quotient now feeds the Step (xi) hull side directly: the constructor

```
IUTStage1Theorem311TypedIndeterminacyCore.
  EqualityQuotientPossibleImages.
  toRemark395PossibleImageFamilySource
```

builds a Remark 3.9.5 possible-image family indexed by `Quot(equalityQuotient.relation)`. The checked endpoints

```
remark395Ob5EqualityQuotientEndpoint_of_equalityOrbit,
remark395Ob5Ob6EqualityQuotientEndpoint_of_equalityOrbit
```

prove the Ob5 collapse and Ob6  $\Phi/\Xi$  hull-log-volume inequalities for  $(\text{Ind}_1)/(\text{Ind}_2)$ -orbit choices. They do not identify  $(\text{Ind}_3)$  choices; the  $(\text{Ind}_3)$  contribution is still precisely the separate one-sided log-volume inequality. The finite toy witness has been upgraded accordingly to `finiteToyEqualityQuotientPossibleImages`. The same equality-quotient discipline is now available at the generated full-label Step (xi) boundary: the public generated constructor keeps  $(\text{Ind}_3)$  outside the equality quotient and exposes the selected q-region as both a quotient possible image and the pullback of the corresponding theta-pilot-class image. The current nonvacuity audit is packaged as

```
IUTStage1Theorem311TypedIndeterminacyCore.
  FiniteToyTypedIndeterminacyNonvacuityAudit.
```

It records a nonempty choice space, self-steps for the three typed indeterminacies, preservation of log-volume for  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$ , the one-sided upper-semi estimate for  $(\text{Ind}_3)$ , absence of an  $(\text{Ind}_3)$  generator in the equality quotient, and pullback compatibility for the quotient-indexed possible-image family. This closes only the interface-level satisfiability check: it prevents the typed indeterminacy layer from being vacuous, but it is not yet a construction of Mochizuki's full indeterminacy apparatus. The witness has also been strengthened from the purely reflexive one-point case to a strict two-point audit,

```
IUTStage1Theorem311TypedIndeterminacyCore.
  StrictFiniteToyTypedIndeterminacyNonvacuityAudit.
```

This audit now also carries the generic `actionLawAudit` certificate used by the main corridor. Here the choice space is `Fin 2`,  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  are equality relations, and  $(\text{Ind}_3)$  contains the strict step  $0 \rightarrow 1$ . The Lean theorem

```
IUTStage1Theorem311TypedIndeterminacyCore.
  strictFiniteToyTypedIndeterminacyNonvacuityAudit_
  ind3_strict_not_equalized
```

proves simultaneously that this  $(\text{Ind}_3)$  step is present, that its log-volume inequality is strict, that the target point is not in the  $(\text{Ind}_1)/(\text{Ind}_2)$  equality orbit of the source point, that the two points have distinct `equalityQuotientMap` images, and that  $(\text{Ind}_3)$  is still absent from the equality quotient generators. The quotient-map separation is proved by a finite quotient representative map `Quot(equalityQuotient.relation) → Fin 2`, whose well-definedness follows from the fact that the strict toy equality quotient relation is exactly equality. This is stronger nonvacuity evidence for the

asymmetric typed interface, while retaining the same limitation: it is a finite audit model of the interface, not an IUT source construction. The same strict model now also carries

`IUTStage1Theorem311TypedIndeterminacyCore.`  
`StrictFiniteToyEqualityQuotientHullNonvacuityAudit.`

This audit instantiates the quotient-indexed Remark 3.9.5 hull/log-volume compatibility layer on the strict two-point model. Its endpoint proves pullback to the original finite possible-image family, hull-log-volume invariance along  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$ , the  $(\text{Ind}_3)$  upper-semi core inequality  $0 \leq 1$ , and the same strict non-equalization statement for the  $0 \rightarrow 1$   $(\text{Ind}_3)$  step. Thus the finite audit now reaches through the same quotient-to-hull interface used by the Step (xi) corridor, while still remaining only a nonvacuity check. The one-sided multiradial source now also exposes this information as the structured audit

`IUTStage1Theorem311OneSidedMultiradialConstructionSource.`  
`OneSidedQuotientAudit.`

The audit records that possible images are indexed through the equality quotient, that the equality quotient has no  $(\text{Ind}_3)$  generator, that  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  preserve procession-normalized log-volume, that  $(\text{Ind}_3)$  remains only an upper-semi relation, and that the selected q-region is the quotient-indexed Theorem 3.11 possible image. This audit now also carries

`IUTStage1Theorem311TypedIndeterminacyCore.`  
`ActionLawAudit,`

the compact certificate that the three typed indeterminacy action objects share the same procession-normalized log-volume, that the  $(\text{Ind}_1)/(\text{Ind}_2)$  quotient maps respect their preserving steps, and that  $(\text{Ind}_3)$  is excluded from the equality quotient. The local-global  $C_\Theta$  source and its finite-place version now project this audit directly, so the closed boundary can cite the one-sided quotient facts without unpacking the Step (xi) constructor. The selected q-region now also has a quotient-hull audit,

`IUTStage1Theorem311OneSidedMultiradialConstructionSource.`  
`OneSidedSelectedQHullLogVolumeAudit.`

This audit consumes the equality-quotient `EqualityQuotientHullLogVolumeCompatibility` and the constructed Remark 3.9.5 hull/determinant source. It proves that the selected q-pilot region is the quotient-indexed possible region, lies in the quotient canonical hull, and satisfies the constructed source's q-region log-volume bound by  $\theta$ , while retaining  $(\text{Ind}_1)/(\text{Ind}_2)$  hull-log-volume equalities and the separate  $(\text{Ind}_3)$  upper-semi core inequality.

The local-to-global comparison itself is now isolated as

`ConstructedTheorem311IndeterminacyLocalGlobalCThetaSource.`

This source object ties the typed Theorem 3.11 indeterminacy core to the constructed Remark 3.9.5 Step (xi) source and the IUT IV estimate shadow. It records the remaining paper-mathematical assembly obligations: local place log-volume assembly, finite-divisor valuation-ball Haar normalization, product/sum local-to-global assembly, and compatibility between the Theorem 3.11 indeterminacy construction and the Step (xi) determinant/hull source. Crucially, it no longer assumes the raw comparison  $C_{\Theta, \text{can}} \leq C_\Theta$ . Instead Lean derives it from the paper-shaped arithmetic gap

$$C_{\Theta, \text{can}} + 1 \leq \text{arithmeticUpperTerm} - \text{mainLogTerm}$$



together with the IUT IV identity

$$C_{\Theta} = \text{arithmeticUpperTerm} - \text{mainLogTerm} - 1.$$

The compact finite-divisor endpoint

`boundarySignedEqualityOrStrictCTheta_from_constructed`  
`Theorem311IndeterminacyLocalGlobalCThetaFiniteDivisorVerticalIQ`

therefore consumes this source object and returns both the source-obligation endpoint and the Corollary 3.12 dichotomy. This is progress on the disputed corridor because the last scalar comparison is now a typed Theorem 3.11/IUT IV local-to-global source obligation, not an exposed final numeric hypothesis. It remains an obligation until the local place assembly, Haar normalization, and product/sum comparison are constructed from the corresponding source-paper objects rather than recorded as proof-carrying fields. The Theorem 3.11 multiradial source has also been strengthened below this local-to-global handoff. The source object

`IUTStage1Theorem311QuotientMultiradialSource`

now ties the typed  $(\text{Ind}_1), (\text{Ind}_2), (\text{Ind}_3)$  core to an actual `IUTStage1MultiradialThetaImages` quotient package. It records that the multiradial quotient is the quotient generated by the typed indeterminacy core, that the possible-image family is the one carried by the Theorem 3.11 record, and that the selected q-region is literally one of these possible images. It also carries the finite  $F_l$ -label layer: a  $\Theta\text{NF}$  gluing torsor, the cardinality  $\#F_l = l$ , and procession-label transitions satisfying the zero and addition laws. Lean proves that every such label transition has the same quotient-map class and hence the same multiradial possible-image region.

The source is no longer constructed only by supplying this whole package as a raw payload. The finite procession layer is separated as

`IUTStage1Theorem311FLProcessionAction,`

which records the  $\Theta\text{NF}$  gluing torsor, the  $Z/lZ$ -indexed procession transition on choices, the zero/addition action laws, and the fact that each transition stays inside the quotient generated by the typed indeterminacy core. The constructor

`IUTStage1Theorem311QuotientMultiradialConstructionSource`

then builds the quotient-aware source: the multiradial image object is formed from the typed quotient and the record's Theorem 3.11 theta possible images, the selected q-region is defined to be the possible image at the selected choice, and  $\#F_l = l$  is proved by `ZMod.card`. Thus the remaining paper-side payload at this layer has been narrowed to two mathematical assertions: possible-image invariance along the typed quotient and the actual finite procession action on the source choice space.

The preferred source boundary now uses the one-sided equality quotient. The typed core exposes

`IUTStage1Theorem311TypedIndeterminacyCore.equalityQuotient`

generated by  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  alone. Thus  $(\text{Ind}_3)$  is not a possible-image equality: it remains only the upper-semi log-volume relation. From a `PossibleImageQuotientCompatibility` object, Lean proves

$$i \sim_{\text{Ind}_1, \text{Ind}_2} j \implies \Theta\text{Image}_i = \Theta\text{Image}_j$$

as `PossibleImageQuotientCompatibility.equalityQuotient_image_invariant`, while retaining the separate theorem that an  $(\text{Ind}_3)$ -step gives only the upper-semi log-volume inequality. The Step (xi) source

`IUTStage1Theorem311OneSidedMultiradialConstructionSource`

constructs the multiradial possible-image object from this equality quotient. It now also exposes the quotient-indexed possible-image family itself: pulling back along `equalityQuotientMap` recovers the original choice-indexed family, and the selected q-region is the pullback of the selected quotient class. The local-to-global experiment endpoint reports the same factorization, so this quotient passage is visible at the  $C_\Theta$  boundary instead of remaining a private constructor detail. The finite  $F_l$ -procession action is now threaded through this same hull interface. The endpoint

`IUTStage1Theorem311OneSidedMultiradialConstructionSource.  
flProcessionRemark3950b50b6_endpoint`

states that translating a choice by an  $F_l$ -label leaves its  $(\text{Ind}_1, \text{Ind}_2)$ -equality-quotient class unchanged and therefore gives the Remark 3.9.5 Ob5 collapse together with the Ob6  $\Phi/\Xi$  hull-log-volume inequalities for the original and translated possible images. This is a source-level bridge from procession label transitions to the Step (xi) hull family; it still does not identify  $(\text{Ind}_3)$ -related choices.

The anonymous choice index can now be replaced by a concrete Hodge-theater/log-theta-lattice choice type. A choice carries a Hodge-theater identifier, a history label, an  $(n, m)$  log-theta coordinate, an  $F_l$  label, and the current procession, local tensor, and upper-semi data. The constructor

`IUTStage1Theorem311OneSidedMultiradialConstructionSource.  
ofConcreteHodgeTheaterLogTheta`

builds the one-sided multiradial source from concrete  $(\text{Ind}_1)$ ,  $(\text{Ind}_2)$ , and  $(\text{Ind}_3)$  laws on this choice space. Lean now constructs the finite  $F_l$ -procession action itself: it translates the  $F_l$  label by the canonical  $\mathbb{Z}/l\mathbb{Z}$  action, proves the zero and addition laws, proves  $\#F_l = l$ , and derives equality-quotient compatibility from the concrete  $(\text{Ind}_1)$  step. This has been lowered one step further at the source-choice boundary. The constructor now also has the compact audit `ConcreteHodgeTheaterLogThetaConstructorAudit`, which packages the one-sided quotient audit, the selected q-region endpoint, finite  $F_l$ -cardinality,  $(\text{Ind}_1)/(\text{Ind}_2)$  log-volume preservation, and the no- $(\text{Ind}_3)$ -equality guard as one review object. The new `IUTStage1FLLabelProcessionSource` fixes one forgotten theta-pilot lattice node and constructs the full  $\mathbb{Z}/l\mathbb{Z}$ -indexed family of finite-label representatives over it. Its audit proves  $\#F_l = l$ , that every label occurs, that a coordinate over the same forgotten lattice node has a unique full label, and that label translation agrees with coordinate translation. The choice-level source `FLLabelProcessionChoiceSource` then turns every full-label representative into a concrete  $(\text{Ind}_1)$  step from the base choice; with the Theorem 3.11 indeterminacy law, Lean derives preservation of the procession-normalized log-volume for every such label.

The next transition in Remark 3.11.2 is now explicit as well. The declaration

`IUTStage1AbsoluteFLLabelProcessionSource`

forms the  $|F_l|$  label layer from the full  $F_l$  family by sending  $j \in \mathbb{Z}/l\mathbb{Z}$  to the zero label or to the sign quotient of the corresponding nonzero cusp label. Its audit proves that every  $|F_l|$  label is represented, that nonzero opposite labels  $j$  and  $-j$  have the same absolute label, that this is exactly the quotient identification, and that ordinary  $F_l$ -procession translation is compatible with the induced

$\pm$ -procession label map. The choice-level audit `AbsoluteLabelProcessionChoiceAudit` attaches this passage to concrete Hodge-theater/log-theta choices, and the Step (xi) action audit now records both the all-full-label source and the induced absolute-label compatibility. Thus the formal label layer now follows the source-paper chain

$$F_l\text{-labels} \longrightarrow |F_l|\text{-labels} \longrightarrow \pm\text{-processions}$$

instead of stopping at the ordinary  $F_l$ -procession action.

Remark 3.11.2 also treats the mono-analytic  $\pm$ -procession index sets as naked finite sets, not as further arithmetic holomorphic data. Lean now models the component indexed by  $j$  as  $\text{Fin}(j + 1)$ , proves that any finite type of cardinality  $j + 1$  is equivalent to this chosen model, and packages the family of choices

$$\prod_{j=0}^l \text{Fin}(j + 1).$$

The total cardinality is proved to be  $(l + 1)!$ , matching the paper's  $l^{\pm}!$  count. This audit is attached to the absolute-label procession source, so the formal passage to  $\pm$ -processions now records both the quotient of labels and the naked mono-analytic counting data.

This source is canonical: `ofCoordinate` builds the full-label family from a log-theta coordinate, `ofChoice` attaches it to a concrete Hodge-theater/log-theta choice, and `ConcreteHodgeTheaterLogThetaFullLabelProcessionSource.canonical` assembles the choice-wise family for the whole concrete source space.

The one-sided constructor has both an explicit and a canonical full-label entry point,

```
IUTStage1Theorem3110OneSidedMultiradialConstructionSource.
  ofConcreteHodgeTheaterLogThetaFullLabelSource,
  ofConcreteHodgeTheaterLogThetaCanonicalFullLabelSource.
```

They build the same concrete multiradial source as `ofConcreteHodgeTheaterLogTheta`, but their endpoints also audit that each action translate is backed by the all-label source, is represented by an  $(\text{Ind}_1)$  full-label choice, preserves log-volume, and has the expected  $Z/lZ$  label. Thus the  $F_l$ -procession input consumed by the corridor is now tied to the source-level no-omission statement constructed from the log-theta coordinate itself, rather than merely to an abstract action law.

The quotient-image constructor

```
IUTStage1Theorem3110OneSidedMultiradialConstructionSource.
  ofConcreteHodgeTheaterLogThetaQuotientImages
```

takes the theta-pilot possible images as a family on the  $(\text{Ind}_1, \text{Ind}_2)$ -equality quotient and a pullback theorem identifying the record's choice-indexed images with this quotient family. Lean derives the old possible-image compatibility record from these quotient-indexed data. This has now been bundled as

```
ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.
```

The source object keeps the supplied quotient family visible, proves that it agrees with the internally reconstructed quotient family, selects the q-image, and constructs the corresponding Remark 3.9.5 quotient hull compatibility. The canonical constructor

```
ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.
  ofCompatibility
```

now builds this quotient family by `Quot.lift` from the concrete  $(\text{Ind}_1, \text{Ind}_2)$  possible-image compatibility theorem, with the pullback law definitionally recovered. The remaining mathematical input is therefore sharper: prove that compatibility theorem from the source-paper theta-pilot apparatus, rather than hand-supply a quotient family or direct  $(\text{Ind}_1, \text{Ind}_2)$  image equalities at the Step (xi) boundary. The experiment surface now uses the sharper factorized form at the strongest valuation-ball endpoint. The new constructor

```
concreteHodgeTheaterLogThetaImageFactorizationSource_to
  OneSidedIUTIVTheorem110ValuationBallHaarFormulaGapMatched
  ArithmeticDegreePadicFormulaMatchedStepXILocalTermCThetaSource
```

starts from `ConcreteHodgeTheaterLogThetaThetaPilotImageFactorizationSource`: a theta-class map, its possible-image family, and proofs that  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  preserve the theta class. It constructs the quotient theta-pilot source internally by `ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource`.

`ofImageFactorization`, then enters the existing valuation-ball formula-gap/local-to-global  $C_\Theta$  route. Thus the public endpoint no longer asks for a prebuilt quotient theta-pilot source at this boundary. This has now been refined once more: the theta-class map itself is no longer an arbitrary field. The concrete class

```
IUTStage1ConcreteHodgeTheaterLogThetaChoice.ThetaPilotClass
```

keeps the Hodge-theater history, the log-theta lattice column and row, the log-theta-column, and the coric datum, but forgets the finite  $F_l$  label and the local tensor representative. Lean proves `ind1_thetaPilotClass_eq` and `ind2_thetaPilotClass_eq` from the concrete source steps. Thus the new constructor

```
ConcreteHodgeTheaterLogThetaThetaPilotImageFactorizationSource.
  ofThetaPilotClass
```

only requires a family of possible images on this concrete class and a pullback identification with the record's choice-indexed possible images. The direct one-sided constructor

```
ofConcreteHodgeTheaterLogThetaThetaPilotClassImages
```

then constructs the factorization, derives the  $(\text{Ind}_1, \text{Ind}_2)$  possible-image equalities, builds the  $F_l$ -procession action, and fixes the selected q-region as the chosen Theorem 3.11 possible image. It still produces the quotient theta-pilot source via

```
ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.
  ofImageFactorization.
```

No  $(\text{Ind}_3)$  class equality is part of this constructor; the endpoint explicitly keeps  $(\text{Ind}_3)$  out of the equality quotient and uses only the typed upper-semi log-volume inequality. This boundary has now been lowered again by

```
ConcreteHodgeTheaterLogThetaThetaPilotClassImageLawSource.
```

This source supplies a representative concrete choice for each theta-pilot class and proves that two choices with the same theta-pilot class have the same possible-image region. Lean then constructs the class-indexed family, proves the pullback identity, and feeds the resulting factorization into

ofConcreteHodgeTheaterLogThetaThetaPilotClassImageLaw. The representative part has now been made explicit: ThetaPilotClassRepresentativeData chooses the forgotten  $F_l$ -label, procession representative, local tensor representative, and upper-semi representative for each theta-pilot class, and Lean proves that this choice is a section of the theta-pilot forgetting map. The lower

ConcreteHodgeTheaterLogThetaThetaPilotClassRegionSource

then takes a class-level possible-image formula  $\Theta_{\text{class}} \mapsto P_{\Theta_{\text{class}}}$  and the pointwise pullback law

$$P_{\text{record}}(x) = P_{\Theta_{\text{class}}(x)}.$$

At the quotient boundary this class-region source now feeds

ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.  
ofClassRegionSource.

Thus the equality-quotient family is constructed from the class-region formula itself: Lean derives the same-class image law, the  $(\text{Ind}_1, \text{Ind}_2)$  quotient compatibility, the selected q-region, containment in the Theorem 3.11 possible-image union, and the exclusion of  $(\text{Ind}_3)$  from equality. This is the source-level quotient possible-image construction used before entering Remark 3.9.5. The same construction is now also available at the typed-core level, before the larger endpoint wrappers enter. The source ThetaPilotClassPossibleImageSource takes a possible-image family on the concrete theta-pilot class itself and pulls it back along the forgetting map from concrete Hodge-theater/log-theta choices. Lean derives the  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  region equalities from preservation of this class, constructs the  $(\text{Ind}_1, \text{Ind}_2)$ -equality-quotient possible-image family, and records that  $(\text{Ind}_3)$  remains only the typed upper-semi log-volume inequality. This source now lowers directly to both the Step (xi) theta-pilot factorization and the quotient theta-pilot source: after one record-pullback equality, Lean identifies the selected q-region with the selected equality-quotient image, proves containment in the Theorem 3.11 possible-image union, and again exposes the absence of an  $(\text{Ind}_3)$  equality generator. Thus the class-indexed possible-image family reaches the Remark 3.9.5 boundary without a manually supplied quotient-image package. The same lowering now has two direct endpoints: one returns the selected q-region hull/log-volume audit, and the other continues through the constructed global  $C_\Theta$  comparison to the existing dichotomy. These two endpoints are now also available one layer lower, from the lattice-key image law itself: the Hodge-theater/history/log-theta-lattice invariance reconstructs the possible-image formula before the selected q-region is sent into Remark 3.9.5. The same quotient source now has a direct class-law route,

ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.  
ofClassImageLawSource,

which first converts same-class possible-image invariance into typed fiber-transport invariance via ConcreteHodgeTheaterLogThetaThetaPilotClassImageLawSource.

toFiberTransportSource. This uses the Lean theorem that fiber transport is equivalent to equality of the concrete theta-pilot class, so the class-image law now feeds the quotient construction without a separate lattice-key payload. There is also a lower direct route,

ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.  
ofLatticeImageLawSource,

which starts from the Hodge-theater/history/label-forgotten-lattice/coric same-key image law. The quotient possible-image family is therefore obtained after reconstructing the lattice formula from

representatives, rather than by first exposing an independent class-region formula. The current descent from class formula to quotient source is now organized as a chain of progressively more concrete boundaries. At the top, `ConcreteHodgeTheaterLogThetaThetaPilotClassFormulaRecordSource` identifies the Theorem 3.11 record family with a theta-pilot class formula. The lattice-formula boundary then factors the class through the Hodge-theater id, history label, coric datum, and the label-forgotten `IUTStage1Theorem311ThetaPilotLatticeCoordinate`; the theorem `thetaPilotLatticeCoordinate_flProcessionTranslate` records that the  $F_l$ -procession label is invisible to this theta-pilot coordinate.

Below the formula boundaries, `ConcreteHodgeTheaterLogThetaThetaPilotLatticeImageLawSource` uses representatives and a same-lattice-key image law to reconstruct the lattice formula internally. The typed fiber-transport source replaces this same-key law by a transport relation preserving the Hodge theater, history label, label-forgotten lattice coordinate, and coric datum. The choice-space layer now proves that this transport relation is equivalent to equality of the concrete theta-pilot class: `thetaPilotClass_eq_iff_latticeKey_eq` gives the key-level characterization, while `ConcreteHodgeTheaterLogThetaThetaPilotFiberTransport`. `iff_thetaPilotClass_eq` identifies fiber transport with class equality. Thus the same-key and same-class formulations are no longer parallel payloads. The equality-quotient source lowers the assumption further: it no longer assumes fiber-region equality, but derives it from membership in the  $(\text{Ind}_1, \text{Ind}_2)$  equality orbit and the quotient pullback theorem.

The newest boundary is

`ConcreteHodgeTheaterLogThetaThetaPilotFiberInd12ChainSource`.

It does not supply equality-orbit membership directly. For each typed theta-pilot fiber transport it supplies an explicit chain generated by concrete  $(\text{Ind}_1)$  procession steps, concrete  $(\text{Ind}_2)$  local tensor steps, symmetry, and composition. Lean converts this chain into equality-orbit membership, then into equality of quotient maps and equality of possible-image regions.

This has now been refined once more by

`ConcreteHodgeTheaterLogThetaThetaPilotFiberProcessionTensorSource`.

Here the finite procession part of the chain is no longer supplied. Lean forms the label shift

$$j_2 - j_1 \in \mathbb{Z}/l\mathbb{Z}$$

between the two  $F_l$ -labels, translates the source choice by this shift, and uses `flProcessionTranslate_ind1Step` to obtain the  $(\text{Ind}_1)$  segment. The only remaining chain input is then the concrete  $(\text{Ind}_2)$  local tensor step from this shifted choice to the target choice. The same boundary now exposes `fiberTransport_processionShiftLabelAudit`: the canonical shift is the unique  $F_l$ -translation aligning the two theta-pilot-fiber coordinates, and its label action sends  $j_1$  to  $j_2$ . Thus the preferred boundary has moved from “construct an arbitrary equality chain” to “construct the local tensor symmetry after the canonical procession-label shift”.

This boundary has now been lowered in seven stages. First,

`ConcreteHodgeTheaterLogThetaThetaPilotFiberLocalTensorDataSource`.

It proves the shifted-coordinate equality from the theta-pilot fiber transport and the  $\mathbb{Z}/l\mathbb{Z}$  label shift. The  $(\text{Ind}_2)$  step is then constructed from three local tensor equalities: procession state, direct-summand count, and upper-semi state after the shift. Second,

`ConcreteHodgeTheaterLogThetaThetaPilotFiberDirectSummandSymmetrySource`

replaces the direct-summand-count equality by a finite equivalence between the two summand index sets. Lean derives equality of the two cardinalities and then reuses the local-tensor source. Third,

**ConcreteHodgeTheaterLogThetaThetaPilotFiberProcessionTransportSource**

replaces the procession-state equality by a typed procession transport: equality of the D-prime-strip procession identifier and equality of the chosen representative. The missing column equality is derived from the shifted coordinate and the two procession-column laws, so Lean reconstructs the full procession-state equality. Fourth,

**ConcreteHodgeTheaterLogThetaThetaPilotFiberUpperSemiTransportSource**

replaces the upper-semi-state equality by a typed upper-semi transport. This transport preserves the non-column upper-semi compatibility data; the missing log-theta-column equality is derived from the shifted coordinate and the two upper-semi-column laws. Lean then reconstructs the full upper-semi state. Fifth,

**ConcreteHodgeTheaterLogThetaThetaPilotFiberDirectSummandPacketSource.**

It replaces the direct finite summand equivalence by packet-level data: source and target local tensor packets, identification of their tensor states with the two choices under comparison, and an equivalence of the corresponding capsule index sets. Since each packet records that its direct-summand count is its capsule count, Lean reconstructs the direct-summand symmetry consumed by the  $(\text{Ind}_2)$  local tensor step. Sixth,

**ConcreteHodgeTheaterLogThetaThetaPilotFiberDirectSummandActionPacketSource**

replaces the capsule-index equivalence itself by a direct-summand packet action: the source supplies direct-summand packet states and an action on the source summand family whose induced capsule family is the target packet. The induced capsule action has the same finite index type as the source family, so Lean derives the capsule-index equivalence and then the direct-summand symmetry. Seventh,

**ConcreteHodgeTheaterLogThetaThetaPilotFiberInd2ActionPacketSource**

replaces this arbitrary direct-summand-family action by the two typed Theorem 3.11 local tensor-factor actions: the nonarchimedean  $\text{Ism}$  action and the archimedean order-two action. Lean forgets either typed action to the generic packet-action interface, derives the capsule-index equivalence, and then reconstructs the direct-summand symmetry required by the  $(\text{Ind}_2)$  step. It now also reconstructs the post-procession concrete  $(\text{Ind}_2)$  step itself from the typed packet symmetry, the procession transport, and the upper-semi transport. This reconstruction is now exposed as **PostProcessionInd2ActionPacketAudit**, and the **ofFiberInd2ActionPacketSource** quotient constructor carries the same audit together with the selected quotient  $q$ -region and the no- $(\text{Ind}_3)$  equality guard. At the place-audited boundary, the action-entry steps now project to this typed packet symmetry through explicit local tensor symmetry-label certificates. The matching action, target capsule family, and equality of the two local tensor symmetry labels are no longer separate generic inputs. The certificates have also been lowered one step: they may now be derived from a packet-label compatibility between the tensor label and the direct-summand family's typed symmetry kind. The target kind is now derived from a symmetry-kind transport law between the source and target packets, rather than asserted as an independent target-side certificate. These

source-labelled action-entry steps feed the place-audited possible-image quotient directly, so region invariance and fiber membership can be proved at this stricter  $(\text{Ind}_2)$  boundary. The newest source constructors lower this once more: the nonarchimedean and archimedean label-transport source steps can now be built from the concrete local tensor  $\text{Ism/order-two}$  labels, the matching action's source kind, and a direct-summand kind-transport law. The packet-label and target-kind data have now been combined into one `SymmetryLabelTransportSource`: both tensor labels are read against the source packet's typed summand kind, and the target summand kind is transported from the source. Its checked audit packages the whole projection chain from label transport to transported packet labels, typed  $(\text{Ind}_2)$  packet symmetry, direct-summand symmetry, and summand-count equality. The local Hodge/SHE layer now also exposes the smaller audit `SymmetryLabelTransportSource.TransportAudit`: from the single label-transport source it derives the source and target label certificates, the target-kind transport, and equality of the two local tensor symmetry labels. Thus the place-audited  $(\text{Ind}_2)$  packet audit records the label transport as one source datum, rather than as separate source-label, target-label, and target-kind assumptions. The local tensor layer now retains this same datum in `Ind2ActionPacketSymmetrySource`: a nonarchimedean case consists of two packet states, one `SymmetryLabelTransportSource`, and an  $\text{Ism}$  direct-summand action; the archimedean case is the order-two analogue. Its projection derives the old `Ind2ActionPacketSymmetry`, the generic direct-summand action-packet symmetry, and the summand-count equality. The place-audited action-entry layer now separates proof-only and data-carrying forms: the older label-transport step, whose matching action is stored behind a propositional existential, proves nonemptiness of this source object, while the new nonarchimedean and archimedean label-transport source steps retain the matching action as data and construct the source-level packet/action object directly. Step (xi) uses this stricter source as `ConcreteHodgeTheaterLogThetaThetaPilotFiberInd2ActionPacketTransportSource`, then forgets it to the previous typed action-packet source before entering the selected- $q$  quotient constructor. Its audit now retains the procession transport fields and the non-column upper-semi transport fields that reconstruct the post-procession  $(\text{Ind}_2)$  local tensor comparison, rather than exposing only the projected packet symmetry. The possible-image layer packages the next step as a quotient audit: the same source-labelled transport is a generator of the  $(\text{Ind}_1, \text{Ind}_2)$  equality quotient, so the corresponding theta-pilot possible-image regions agree and the acting place remains in its finite fiber. The concrete choice layer now has matching constructors for the typed transports:  $(\text{Ind}_1)$  is built from `ProcessionTransport`,  $(\text{Ind}_2)$  from procession and upper-semi transports plus the local summand-count equality, and  $(\text{Ind}_3)$  from `UpperSemiTransport` together with the explicit log-theta-column equality. This transport boundary is now checked against the typed Theorem 3.11 core itself: `typedInd1ProcessionTransportAudit` and `typedInd2LocalTransportAudit` produce the corresponding equality generators, normalized-log-volume preservation, and equality-quotient identifications, while `typedInd3UpperSemiTransportAudit` produces only the one-sided upper-semi audit and the no- $(\text{Ind}_3)$ -equality guard. The same boundary now has record-based forms `Ind1ProcessionTransportSource`, `Ind2LocalTensorTransportSource`, and `Ind3UpperSemiTransportSource`. Their checked constructors build the three concrete indeterminacy steps before the typed core derives the equality/equality/upper-semi consequences. Thus this layer no longer exposes a loose list of Hodge-theater, procession, tensor, and upper-semi hypotheses at the audit endpoint. The Step (xi) fiber source now constructs the relevant record sources before composing these checks as `PostProcessionTypedCoreTransportAudit`: the canonical  $F_l$ -shift gives an `Ind1ProcessionTransportSource`, and the post-shift fiber transport gives an `Ind2LocalTensorTransportSource` from procession transport, upper-semi transport, and direct-summand packet symmetry. Thus a theta-pilot fiber transport is first the canonical  $F_l$ -procession  $(\text{Ind}_1)$ -shift and then the post-shift typed  $(\text{Ind}_2)$  local-



tensor equality. The finite label correction is now justified by the  $Z/l\mathbb{Z}$ -torsor law itself: `existsUnique_translateFLabel_eq_of_toThetaPilotLatticeCoordinate_eq` proves that two representatives over the same theta-pilot lattice node are connected by a unique  $F_l$ -translation, and the Step (xi) source exposes this as `fiberTransport_processionShiftLabelAudit`. Thus the whole fiber transport preserves typed-core log-volume and equality-quotient class, with the same evidence visible at the selected- $q$  boundary. That boundary now also exports preservation of the concrete theta-pilot class and the one-sided  $(\text{Ind}_3)$  upper-semi relation audit;  $(\text{Ind}_3)$  is therefore visible at the endpoint as upper-semi data, not as an equality-quotient transport. The remaining source payload is now lower and sharper: construct the paper-side label transports for the  $Z\text{Mod}(\ell)$ -labelled local log-shell representatives, the  $\text{IsM/order-two}$  actions, procession transports, and upper-semi transports from the underlying Hodge-theater arithmetic, log-theta lattice, and Frobenioid packet data.

The experiment surface has been lowered to this boundary as well. The endpoint

```
concreteHodgeTheaterLogThetaThetaPilotClassImages_to
  OneSidedIUTIVTheorem110ValuationBallHaarFormulaGapMatched
  ArithmeticDegreePadicFormulaMatchedStepXILocalTermCThetaSource
```

starts from the concrete class-indexed possible-image family, constructs the factorization source internally, and then reuses the same valuation-ball formula-gap/local-to-global  $C_\Theta$  corridor. Its audit exposes the class pullback, the derived  $(\text{Ind}_1)/(\text{Ind}_2)$  class invariance, the selected  $q$ -region's containment in the Theorem 3.11 possible-image union, the constructed valuation endpoint, and the final Corollary 3.12 dichotomy. Thus the strongest public valuation-ball boundary no longer asks for an arbitrary theta-class map. This experiment boundary has now also been lowered to the class image law:

```
concreteHodgeTheaterLogThetaThetaPilotClassImageLaw_to
  OneSidedIUTIVTheorem110ValuationBallHaarFormulaGapMatched
  ArithmeticDegreePadicFormulaMatchedStepXILocalTermCThetaSource.
```

It consumes `ConcreteHodgeTheaterLogThetaThetaPilotClassImageLawSource`, constructs the class-indexed family internally, and exposes the representative law, same-class image invariance, selected  $q$ -region containment, constructed valuation endpoint, local-to-global  $C_\Theta$  handoff, and final dichotomy. This public valuation boundary now also has a direct class-region endpoint,

```
concreteHodgeTheaterLogThetaThetaPilotClassRegion_to
  OneSidedIUTIVTheorem110ValuationBallHaarFormulaGapMatched
  ArithmeticDegreePadicFormulaMatchedStepXILocalTermCThetaSource
  _endpoint.
```

It consumes `ConcreteHodgeTheaterLogThetaThetaPilotClassRegionSource`, derives the class-image law internally, and exposes the representative section, class-region pullback formula, same-class invariance, selected  $q$ -region containment, valuation endpoint, local-to-global  $C_\Theta$  handoff, and final dichotomy. The lower source layer feeding this boundary now factors the class formula through the label-forgotten log-theta lattice coordinate, so the remaining theorem-side payload is the proof that theta-pilot possible images are invariant on the corresponding same-key fibers. The same concrete quotient source now feeds the constructed Remark 3.9.5 hull/determinant source directly. The constructor

```
ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.
  toRemark395ConstructedHolomorphicHullDeterminantSource
```

takes the q-region to be the selected Theorem 3.11 quotient possible image. Thus the containment  $q \subseteq \bigcup_i \Theta \text{Image}_i$  is derived from the multiradial source, not passed as an independent Remark 3.9.5 hypothesis. The endpoint then identifies this q-region with the quotient theta-pilot image, places it inside the quotient canonical hull, and carries forward the existing determinant-to- $\theta$  log-volume bound. The selected-q handoff is now also exposed as `toRemark395SelectedQHullLogVolumeAudit_endpoint`: it packages the constructed q-region equality, canonical-hull containment, q-region log-volume bound,  $(\text{Ind}_1, \text{Ind}_2)$  hull-log-volume equalities, and the separate  $(\text{Ind}_3)$  upper-semi inequality in one checked statement. Composing once more with the constructed global- $C_\Theta$  audit gives

```
ConcreteHodgeTheaterLogThetaQuotientThetaPilotSource.  
toRemark395ConstructedGlobalCThetaScaleComparisonAudit.
```

This endpoint builds the constructed Remark 3.9.5 source internally, reads the selected q-region and the  $q_{\log} \leq \theta_{\log}$  comparison from that source, and proves the Corollary 3.12 ordered-real dichotomy after the single remaining global comparison  $C_{\Theta, \text{can}} \leq C_\Theta$ . Thus the current boundary is no longer the possible-image or q-containment step; it is the local-to-global comparison of the constructed canonical scale with the paper's global  $C_\Theta$ . The strict typed  $(\text{Ind}_2)$  action-packet source now reaches this same boundary directly. The endpoints

```
ofFiberInd2ActionPacketSource_toRemark395SelectedQHullLogVolumeAudit  
_endpoint,  
ofFiberInd2ActionPacketSource_toRemark395ConstructedGlobalCThetaScale  
ComparisonAudit_endpoint
```

construct the quotient source internally and return the `PostProcessionTypedCoreTransportAudit` together with the selected q-region hull/log-volume audit and the global  $C_\Theta$  dichotomy. This keeps the finite procession shift and post-shift  $(\text{Ind}_2)$  packet symmetry visible at the final handoff, rather than hiding them behind an intermediate quotient-source argument. The stricter source-level packet/action transport source now has the same two handoff endpoints. Its strict fiber endpoint exposes an audit of the retained `Ind2ActionPacketSymmetrySource`, so the packet states, label transport, and typed Ism/order-two action are checked before being forgotten to the projected  $(\text{Ind}_2)$  symmetry. The quotient-constructor endpoint and both Remark 3.9.5 endpoints also return the named payload `LowerTransportPayload`. This payload contains the procession transport, the upper-semi transport, and the field equalities needed to compare the shifted choice with the target choice. The local comparison handoff is now summarized by `FiberTransportQuotientComparisonAudit`. This audit starts with the retained source-level  $(\text{Ind}_2)$  packet/action transport object, checks its packet-source audit, then records the typed post-procession  $(\text{Ind}_1, \text{Ind}_2)$  transport audit, equality-quotient-map preservation, theta-pilot-class preservation, possible-image region invariance, and the induced lattice-image law. It also records explicitly that  $(\text{Ind}_3)$  contributes only the upper-semi relation and no equality-quotient generator. The same handoff still exposes the selected q-region, the global  $C_\Theta$  dichotomy, fiber-transport log-volume preservation, direct-summand-count preservation, and the exclusion of  $(\text{Ind}_3)$  from the equality quotient. The named audit `SourceLevelTransportQuotientAudit` now packages this same lower payload with the one-sided quotient audit before the Remark 3.9.5 hull/determinant source is introduced. The subsequent `SourceLevelTransportRemark395SelectedQAudit` and `SourceLevelTransportRemark395GlobalCThetaAudit` carry this same source-level quotient audit across the selected-q hull/log-volume comparison and the global  $C_\Theta$  dichotomy, so the strict transport data is visible at the actual Corollary 3.12 handoff. The audit

`SourceLevelTransportFLProcessionRemark395Ob5Ob6Audit` connects the same strict source to the concrete  $F_l$ -label translation and the Remark 3.9.5 Ob5–Ob6  $\Phi/\Xi$  hull estimates. At the procession boundary itself, the  $\Phi$ -side can now be the canonical hull family and the  $\Xi$ -side can be built from the exact Remark 3.9.5 log-volume source, instead of being supplied as an arbitrary family. The same canonical/exact family construction is also exposed at the typed indeterminacy Ob5–Ob7 experiment surface, where the Ob7 prime-strip compatibility remains the only additional payload. The full-label-backed version additionally exhibits the translated label in the no-omission  $F_l$  family and records the corresponding  $(\text{Ind}_1)$  log-volume preservation before the hull estimates are used. The selected-q specialization now uses the canonical no-omission full-label source internally and identifies the selected q-region with the equality-quotient possible region before applying the same Ob5–Ob6 estimates. The corresponding global  $C_\Theta$  audit carries this canonical full-label selected-q evidence through to the final dichotomy. An exact- $\Xi$  specialization now constructs the  $\Phi$ -family canonically and obtains  $\Xi$  from the Remark 3.9.5 exact log-volume source, rather than accepting arbitrary approximant families at this boundary. At the strongest current local boundary, the endpoint `ConcreteHodgeTheaterLogThetaCompactOpenLogKummerMapClosedCorollary312Endpoint` starts from compact-open log-Kummer map data over the transported theta-region family. It constructs the log-Kummer graph, pointwise log-shell source, exact- $\Xi(P_B)$  family, Remark 3.9.5 hull/determinant source, and source-derived IUT IV  $C_\Theta$  comparison before exposing the final Corollary 3.12 dichotomy. The endpoint also records the derived signed bound  $\theta_{\text{signed}} \leq C_\Theta(-q_{\text{signed}})$  and the guard that  $(\text{Ind}_3)$  contributes no equality-quotient generator. Its finite-place variant, `ConcreteHodgeTheaterLogThetaCompactOpenLogKummerMapFinitePlaceClosedCorollary312Endpoint`, constructs the local-global source from finite local Step (xi)/Haar summation data, so the compact-open log-Kummer boundary no longer has to receive the generic local-global  $C_\Theta$  source directly. The normalized-Haar variant lowers this once more: the total Haar defect is derived from a finite-place lower-bound source, i.e. placewise nonnegativity plus a distinguished normalized valuation-ball contribution, before the same compact-open Corollary 3.12 boundary is entered. The p-adic unit-ball variant lowers this lower-bound source to local Haar-normalization data over the finite places: the defect is the unit-ball dilation index, and the distinguished-place lower bound is proved from primality and finite-dimensionality. A valuation-ball formula-gap matched variant now enters the same compact-open boundary from the IUT IV Theorem 1.10 source itself: the audit retains the valuation-ball formula-gap source, the p-adic prime-error split, and the Step (xi) arithmetic-degree calibration before projecting to the closed local-global  $C_\Theta$  handoff. The endpoint now also has a checked `RemainingPayloadAudit`; this is a projection, not an additional assumption, and records in one place the closed no-raw-comparison audit, the source-derived signed bound, the final dichotomy, and the exclusion of  $(\text{Ind}_3)$  from equality transport. The valuation-ball source below this endpoint now has its own `ValuationBallFormulaGapSourceDODAudit`. This audit keeps the Theorem 1.10 valuation-ball provenance visible while projecting the finite-place summation audit, the IUT IV arithmetic-gap handoff, the coarse local-global assembly expansion, and the closed no-raw-comparison  $C_\Theta$  dichotomy from the same source object. It now also contains the explicit finite-place  $C_\Theta$  chain: the canonical scale, arithmetic upper term, and main term are identified with finite sums, the summed Step (xi)/Haar inequality and unit Haar defect give the global arithmetic gap, and the IUT IV handoff yields the signed  $C_\Theta$  bound. The same source audit also projects the local formula-gap estimate audit for the distinguished Proposition 1.4 and archimedean Proposition 1.5 comparison objects. The endpoint-level `RemainingPayloadAudit` projects this valuation-ball source audit directly, and its `remainingPayloadAudit_formulaGapLocalEstimateAudit` and `remainingPayloadAudit_finitePlaceCThetaChain` projections now return the local formula-gap audit and the finite-place  $C_\Theta$  calculation at the compact-open endpoint itself. The public

compact-open boundary was first lowered to the calibrated valuation-ball source:

```
ConcreteHodgeTheaterLogThetaCompactOpenLogKummerMap
ValuationBallHaarCalibratedFormulaGapMatchedStepXI
ClosedCorollary312Endpoint.
```

That boundary was then tightened to the derived valuation-ball source, to the unscaled degree-bound source, to the degree-identified unscaled source, through the local-degree formula source, to the object-backed local-degree source, and to the arithmetic-divisor-backed valuation-ball source:

```
ConcreteHodgeTheaterLogThetaCompactOpenLogKummerMap
ValuationBallHaarArithmeticDivisorBackedLocalDegreeStepXI
ClosedCorollary312Endpoint.
```

It consumes a valuation-ball source whose public local payload is the arithmetic-divisor-backed matched local-degree component source. At each distinguished nonarchimedean place the local different and conductor contributions are the local degrees of the Theorem 1.10 arithmetic divisors, with nonnegativity supplied by divisor effectivity and with the Proposition 1.4 tensor components identified explicitly. The archimedean branch is still the constructed metric component. A synchronization proof identifies this additive arithmetic-divisor formula core with the additive projection of the valuation-ball Theorem 1.10 formula source, after which the object, local formula, degree-identified, unscaled, derived, and calibrated valuation-ball sources are constructed internally before the final dichotomy is inherited. The endpoint audit exposes the arithmetic-divisor-backed source endpoint and its local-degree audit alongside the inherited Corollary 3.12 dichotomy. The compact-open boundary has now been lowered one more source step to the Record Ob3/Ob5 determinant/log-volume handoff:

```
ConcreteHodgeTheaterLogThetaCompactOpenLogKummerMap
ValuationBallHaarRecordOb3Ob5ArithmeticDivisorBacked
LocalDegreeStepXIClosedCorollary312Endpoint.
```

This endpoint consumes the record-canonical adjusted determinant source and a valuation-ball Record Ob3/Ob5 source. Lean then derives the Step (xi) valuation-ball determinant equality and the canonical-scale finite-sum equality by projection through `RecordOb3Ob5ValuationBallStepXIDeterminantHandoffAudit`, before entering the arithmetic-divisor-backed compact-open route above. Thus the valuation-ball compact-open endpoint no longer accepts the final determinant and  $C_{\Theta, \text{can}}$ -sum equalities as its public mathematical payload. This boundary has now been pushed one step further down to the valuation-cover source itself:

```
ConcreteHodgeTheaterLogThetaCompactOpenLogKummerMap
ValuationBallHaarValuationCoverRecordOb3Ob5
ArithmeticDivisorBackedLocalDegreeStepXIClosedCorollary312Endpoint.
```

The endpoint consumes a valuation-ball factor-calibrated Haar tensor-packet cover and the single synchronization possibleRegion =  $\Theta$ Image with the Theorem 3.11 record family. The Record Ob3/Ob5 adjusted determinant/log-volume source is then constructed internally from the valuation-ball cover before the Record Ob3/Ob5 valuation-ball handoff and compact-open Corollary 3.12 dichotomy are invoked. This removes `recordAdjustedSource` as a separate endpoint input at this boundary. Thus the strict quotient boundary already shows the full equality/equality/upper-semi pattern: (Ind<sub>1</sub>) and (Ind<sub>2</sub>) provide equality transport, while (Ind<sub>3</sub>) remains only one-sided upper-semi data.

The bridge to the constructed Remark 3.9.5 source is now named as

`IUTStage1Theorem311QuotientMultiradialRemark395Compatibility.`

Its essential field identifies the constructed Step (xi) q-pilot region with the selected Theorem 3.11 possible image. From this, Lean re-derives

$$q\text{Region} \subseteq \bigcup_i \Theta\text{Image}_i$$

through the quotient-aware Theorem 3.11 source, instead of treating the record-union containment as an unrelated payload. The construction-source endpoint also produces this compatibility and the quotient pullback once the constructed Remark 3.9.5 q-pilot region is identified with the selected possible image. The one-sided version is now also a first-class audit:

`IUTStage1Theorem311OneSidedMultiradialConstructionSource.`  
`OneSidedRemark395CompatibilityAudit.`

It packages the constructed q-pilot equality with the  $(\text{Ind}_1, \text{Ind}_2)$ -equality quotient pullback, the selected quotient possible image, containment in the Theorem 3.11 possible-image union, the explicit absence of  $(\text{Ind}_3)$  generators from the equality quotient, and the separate  $(\text{Ind}_3)$  upper-semi log-volume inequality. This is the compatibility object now exported by the preferred local-to-global  $C_\Theta$  audits. The same one-sided constructor now has a packet-normalized concrete entry:

`ofConcreteHodgeTheaterLogThetaVertical`  
`LogKummerPacketAlignment.`

It constructs the public Theorem 3.11 source from theta-pilot class images and the vertical log-Kummer packet-aligned procession source, and its audit exposes the packet-normalized average equality together with the inherited selected q-region endpoint. This is the current preferred bridge from the concrete Hodge-theater/log-theta-lattice layer into the Step (xi) corridor. The next refinement removes the single opaque arithmetic-gap field from the preferred source surface. The Lean structure

`ConstructedTheorem311FinitePlaceLocalGlobalCThetaSource`

introduces a finite set of local places and records four local functions: the local canonical Step (xi) scale, the local IUT IV arithmetic upper contribution, the local main-log contribution, and the local Haar-normalization defect. Its load-bearing local assertion is the pointwise inequality

$$C_{\Theta, \text{can}, v} + \delta_v \leq A_v - M_v.$$

Lean proves

$$C_{\Theta, \text{can}} + 1 \leq \text{arithmeticUpperTerm} - \text{mainLogTerm}$$

by summing these local inequalities with `Finset.sum_le_sum`, using the equalities

$$C_{\Theta, \text{can}} = \sum_v C_{\Theta, \text{can}, v}, \quad \text{arithmeticUpperTerm} = \sum_v A_v, \quad \text{mainLogTerm} = \sum_v M_v,$$

and the finite-divisor/Haar normalization condition

$$1 \leq \sum_v \delta_v.$$

The resulting conversion theorem

```
ConstructedTheorem311FinitePlaceLocalGlobalCThetaSource
.toConstructedTheorem311IndeterminacyLocalGlobalCThetaSource
```

constructs the coarser source object automatically. The public finite-divisor endpoint

```
boundarySignedEqualityOrStrictCTheta_from_constructed
Theorem311FinitePlaceLocalGlobalCThetaFiniteDivisorVerticalIQ
```

therefore derives the Corollary 3.12 dichotomy from a finite local-place assembly source, rather than from a raw numerical bound, a raw  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison, or a single global arithmetic-gap hypothesis. The remaining mathematical work has been pushed down to constructing the local terms  $C_{\Theta, \text{can}, v}$ ,  $A_v$ ,  $M_v$ , and  $\delta_v$  from the actual Theorem 3.11/Step (xi)/IUT IV objects and proving the pointwise local inequalities.

The preferred local-to-global surface has also been tightened to use the one-sided Theorem 3.11 construction directly. The route now passes through localized Step (xi) determinant terms, normalized Haar defects,  $p$ -adic unit-ball Haar indices, IUT IV local arithmetic defects, arithmetic-divisor evaluation, Theorem 1.10 local case formulas, Proposition 1.4/1.5 construction sources, and finally the additive-Haar local analytic construction source. The public theorem

```
boundarySignedEqualityOrStrictCTheta_from_constructed
Theorem311OneSidedIUTIVTheorem110
AdditiveHaarLocalAnalyticArithmeticDivisor
StepXILocalTermCThetaFiniteDivisorVerticalIQ
```

is the current preferred finite-divisor endpoint. The source records carry an `IUTStage1Theorem311OneSidedMultiradialConstructionSource`, identify the constructed Remark 3.9.5  $q$ -pilot region with its selected possible image, and then feed the same finite-place Step (xi)/Haar summation into the  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison. The public endpoint returns the Corollary 3.12 dichotomy while also reporting the equality quotient generated only by  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$ , the separate one-sided  $(\text{Ind}_3)$  log-volume inequality, and the selected  $q$ -region containment in the Theorem 3.11 possible-image union. Thus the current preferred route no longer exposes the raw numeric  $C_{\Theta}$  comparison and no longer uses a bare typed indeterminacy core at the local-to-global boundary. At the one-sided finite-place closed boundary, Lean now also has a realified-packet-source variant: the Step (x) finite-divisor and  $(\text{Ind}_3)$ -source equalities are recovered from the realified Frobenioid log-Kummer packet source while the local-to-global  $C_{\Theta}$  comparison remains closed by the finite-place summation source. The same Step (x) lowering is now available at the preferred additive-Haar local-analytic boundary. The endpoint with suffix `_ofRealifiedFrobenioidPacketSource` keeps the full Theorem 3.11/IUT IV Theorem 1.10 additive-Haar  $C_{\Theta}$  route, but replaces the public packet-local Kummer/forgetting fields and finite-divisor/ $(\text{Ind}_3)$  equalities by a single realified Frobenioid log-Kummer packet source. Thus the currently preferred finite-divisor endpoint exposes the closed local-to-global comparison and the source-recovered Step (x) packet equalities at the same boundary. The first closed local-to-global  $C_{\Theta}$  boundary has now also been tied to the constructed qualitative Hodge/SHE/IPL source. The declaration

```
boundarySignedEqualityOrStrictCTheta_from_constructed
QualitativeHodgeSHEIPLIndeterminacyLocalGlobalCTheta
FiniteDivisorVerticalIQ
```

projects the IPL link from `IUTStage1ConstructedQualitativeFiniteHodgeSHEIPLConstructionSource` and returns `ConstructedQualitativeHodgeSHEIPLIndeterminacyLocalGlobalCThetaAudit`.

That audit records the constructed IPL link source, structured Hodge/SHE/APT evidence, transport guards, the local-to-global  $C_\Theta$  endpoint, the *IUT IV* handoff, the global  $C_\Theta$  comparison audit, and the final dichotomy in one checked proposition. The same constructed qualitative provenance is now also available at the finite-place local-to-global boundary:

```
boundarySignedEqualityOrStrictCTheta_from_constructed
QualitativeHodgeSHEIPLFinitePlaceLocalGlobalCTheta
FiniteDivisorVerticalIQ
```

returns an audit recording the finite local-place sums, placewise Step (xi)/Haar inequality, total Haar defect lower bound, derived  $C_{\Theta, \text{can}} \leq C_\Theta$  comparison, constructed Hodge/SHE/IPL bridge, and final dichotomy. The one-sided finite-place route now has the same constructed qualitative entry point:

```
boundarySignedEqualityOrStrictCTheta_from_constructed
QualitativeHodgeSHEIPLOneSidedFinitePlaceLocalGlobalCTheta
FiniteDivisorVerticalIQ.
```

Its audit adds the Theorem 3.11 one-sided quotient record to the finite-place payload: (Ind<sub>1</sub>) and (Ind<sub>2</sub>) supply the equality quotient for possible images, while (Ind<sub>3</sub>) remains a one-sided upper-semi log-volume relation. The deeper additive-Haar route below now reuses this same one-sided audit rather than returning to a free-standing IPL-link surface.

The newest constructor, **ConstructedTheorem311OneSidedStepXIILocalTermCThetaSource**, removes one more arbitrary layer from the finite-place comparison. Its local canonical terms are the weighted adjusted localization contributions of an **IUTStage1Remark3950b30b4LocalizedVectorBundleDeterminantSource**; the local arithmetic upper contribution is then definitionally this Step (xi) term plus the local Haar defect and local main-log term. Lean derives the pointwise Step (xi)/Haar inequality and constructs the finite-place local-to-global source from these data. The remaining source obligations at this boundary are now explicit: identify  $C_{\Theta, \text{can}}$  with the sum of the localized Step (xi) terms, identify the IUT IV arithmetic and main-log terms with their local sums, and identify the local Haar-defect terms with the precise IUT IV local arithmetic defects. The Haar-defect lower-bound input is no longer consumed as a raw sum inequality: **IUTStage1FinitePlaceHaarDefectLowerBoundSource** records nonnegative local Haar defects and a distinguished normalized valuation-ball place whose defect is at least one, and Lean proves  $\sum_v \delta_v \geq 1$  from those facts. The stricter constructor **ConstructedTheorem311OneSidedNormalizedHaarStepXIILocalTermCThetaSource** threads this derived bound into the Step (xi) local-to-global comparison and now has its own finite-divisor vertical-*IQ* endpoint. The next constructor **IUTStage1FinitePlacePadicUnitBallHaarIndexDefectSource** derives this finite-place lower-bound source from placewise  $p$ -adic unit-ball Haar normalization. For each place  $v$ , the local defect is the dilation index

$$\delta_v = p_v^{[K_v : \mathbb{Q}_{p_v}]};$$

Lean proves  $\delta_v \geq 0$  and  $\delta_{v_0} \geq 1$  for a distinguished normalized place from primality of  $p_v$  and the natural finrank exponent. The wrapper **ConstructedTheorem311OneSidedPadicUnitBallHaarStepXIILocalTermCThetaSource** threads this  $p$ -adic Haar-index source into the normalized Step (xi) local-to-global surface, and the corresponding finite-divisor vertical-*IQ* endpoint projects through the normalized-Haar route to the same Corollary 3.12 dichotomy. The new source **IUTStage1FinitePlaceIUTIVLocalArithmeticDefectSource** names the paper-side local

arithmetic-defect term in the IUT IV  $C_\Theta$  estimate and records its placewise equality with the  $p$ -adic unit-ball Haar index. It therefore derives the same nonnegativity, distinguished-place lower bound, and total  $\sum_v \delta_v \geq 1$  statement for the IUT IV local defects. The corresponding Step (xi) wrapper `ConstructedTheorem311OneSidedIUTIVArithmeticDefectStepXILocalTermCThetaSource` expresses the arithmetic upper sum using these named IUT IV local defects and projects to the  $p$ -adic Haar-index route by the recorded equality. Its finite-divisor vertical- $IQ$  endpoint is now the preferred local-to-global  $C_\Theta$  surface for this part of the corridor. The divisor-evaluation refinement `IUTStage1IUTIVThetaPilotArithmeticDivisorLocalEvaluationSource` now records the local Definition 1.9/Theorem 1.10 arithmetic-divisor degree evaluation: local different degrees, conductor degrees, absorbed prime/error contributions, local main-log terms, and finite-sum identities recovering  $\log \text{Diff}_{F_{\text{tpd}}}$ ,  $\log \text{Cond}_{F_{\text{tpd}}}$ , the absorbed  $10(e_{\text{mod}}^* l + \eta_{\text{prm}})$  term, the global arithmetic upper term, and the global main-log term. The wrapper `ConstructedTheorem311OneSidedIUTIVArithmeticDivisorEvaluationStepXILocalTermCThetaSource` threads this source into Step (xi), leaving the local matching condition that the IUT IV arithmetic upper contribution is the Step (xi) weighted determinant contribution plus the local IUT IV defect plus the local main-log contribution. The next source layer now makes this more faithful to Definition 1.9 itself. `IUTStage1IUTIVArithmeticDivisorSource` formalizes a finite arithmetic divisor as coefficients  $c_v$ , degree weights, a positive normalizing degree, support, effectivity, local normalized degree summands, and the theorem that the global normalized degree is the finite sum of the local summands. `IUTStage1IUTIVTheorem110ArithmeticDivisorSource` packages the three paper divisors  $d_{\text{ADiv}}$ ,  $q_{\text{ADiv}}$ , and  $f_{\text{ADiv}}$ , including effectivity, equality of the conductor and  $q$ -parameter supports, and recovery of  $\log \text{Diff}_{F_{\text{tpd}}}$  and  $\log \text{Cond}_{F_{\text{tpd}}}$  from normalized degrees. `IUTStage1IUTIVTheorem110LocalEstimateGateSource` names the three local cases of Theorem 1.10, Steps (v)–(vii): distinguished nonarchimedean, nondistinguished nonarchimedean with zero upper bound, and archimedean. Its endpoint proves the local upper-semi bound into the arithmetic-minus-main-log gap and supplies the finite-sum identities for the absorbed prime/error and main-log terms. The preferred local boundary now refines this gate through `IUTStage1IUTIVTheorem110LocalCaseFormulaSource`. This source defines the local procession upper bound by the paper’s case split: the distinguished nonarchimedean Step (v) formula, zero for the nondistinguished nonarchimedean Step (vi) branch, and the archimedean Step (vii) formula. Lean constructs the older gate source from this formula-level source, so the Step (vi) zero contribution is a theorem of the constructor rather than a separate payload field. The wrapper `ConstructedTheorem311OneSidedIUTIVTheorem110FormulaArithmeticDivisorStepXILocalTermCThetaSource` threads this stricter typed Theorem 1.10 layer into the Step (xi) route. Thus the preferred public route no longer exposes the raw total Haar-defect sum inequality, an unnamed Haar-defect summand, the global arithmetic/main-log sum identities, bare local degree functions, or a raw nondistinguished local-zero field as separate endpoint hypotheses. The most recent refinement moves one layer further into the local analytic estimates of IUT IV. The Lean source `IUTStage1IUTIVProposition14DistinguishedLocalLogShellEstimate` records the Proposition 1.4(iii) chain from the distinguished nonarchimedean log-shell container through the Proposition 1.7 weighted average to the Step (v) coarse procession-normalized bound. The source `IUTStage1IUTIVProposition14NondistinguishedLocalLogShellEstimate` records the Proposition 1.4(iv) zero log-volume statement for the nondistinguished branch, and Lean derives the corresponding nonnegative local arithmetic gap. The archimedean source `IUTStage1IUTIVProposition15ArchimedeanLocalMetricEstimate` records the Proposition 1.5(iii),(iv) metric container estimate and proves the elementary Step (vii) exact-to-coarse comparison from  $\log(\pi) \leq 2$  and  $l \geq 5$ . These three objects feed `IUTStage1IUTIVTheorem110PropositionLogShellFormulaSource` and then



`IUTStage1IUTIVTheorem110PropositionArithmeticDivisorEvaluationSource`, which now projects to the formula-level Theorem 1.10 route.

The preferred boundary now goes one step lower. The source `IUTStage1IUTIVProposition14DistinguishedLocalLogShellConstructionSource` constructs the distinguished Proposition 1.4 estimate from finite-extension Haar normalized log-volume data, the displayed Proposition 1.4(iii) first and second container bounds, the Proposition 1.7 weighted-average comparison, and the Step (v) coarse procession-normalized bound. The source `IUTStage1IUTIVProposition14NondistinguishedLocalLogShellConstructionSource` constructs the nondistinguished Proposition 1.4(iv) estimate from the same finite-extension Haar normalization, identifying the tensor container with the normalized integral container and deriving its zero log-volume. The source `IUTStage1IUTIVProposition15ArchimedeanMetricConstructionSource` records the finite sets  $I, V$ , the direct-sum cardinality  $2^{|I|-1}|V|^{|I|}$ , primitive-automorphism preservation of the integral structure, and the vector containment used in Proposition 1.5(iv), then projects to the archimedean exact-to-coarse estimate. These construction sources feed `IUTStage1IUTIVTheorem110LocalAnalyticConstructionFormulaSource` and `IUTStage1IUTIVTheorem110LocalAnalyticArithmeticDivisorEvaluationSource`. This finite-extension construction layer is now an intermediate projection. The additive-Haar-backed route is now an intermediate projection in the preferred local-to-global  $C_\Theta$  boundary. The compact-open declarations `IUTStage1IUTIVProposition14DistinguishedCompactOpenHaarLogShellSource` and `IUTStage1IUTIVProposition14NondistinguishedCompactOpenHaarLogShellSource` lower Proposition 1.4 to compact-open topology/Haar normalization data; the additive declarations `IUTStage1IUTIVProposition14DistinguishedAdditiveHaarLogShellSource` and `IUTStage1IUTIVProposition14NondistinguishedAdditiveHaarLogShellSource` lower the same estimates to additive Haar normalization on the local additive carrier. These feed `IUTStage1IUTIVTheorem110AdditiveHaarLocalAnalyticConstructionFormulaSource` and `IUTStage1IUTIVTheorem110AdditiveHaarLocalAnalyticArithmeticDivisorEvaluationSource`. The newest Lean layer lowers this further to valuation-ball additive Haar data. The sources

`IUTStage1IUTIVProposition14DistinguishedValuationBallAdditiveHaarLogShellSource`,  
`IUTStage1IUTIVProposition14NondistinguishedValuationBallAdditiveHaarLogShellSource`

replace the generic additive normalization input by `IUTStage1ValuationBallAdditiveHaarNormalizationSource`, whose audit identifies the ring of integers and chosen compact open subset as valuation balls, proves compact-openness of the unit ball and selected ball, and records the normalized Haar/log-volume uniformizer shift. These proposition-level objects feed `IUTStage1IUTIVTheorem110ValuationBallAdditiveHaarLocalAnalyticConstructionFormulaSource` and `IUTStage1IUTIVTheorem110ValuationBallAdditiveHaarLocalAnalyticArithmeticDivisorEvaluationSource` which project to the additive-Haar, local-analytic, Proposition-level, formula-level, and theta-pilot arithmetic-divisor evaluation records. The valuation-ball layer now also reaches the named formula-to-gap boundary: `IUTStage1IUTIVTheorem110ValuationBallAdditiveHaarFormulaGapMatchedArithmeticDivisorEvaluationSource` retains the distinguished Step (v) and archimedean Step (vii) gap comparison objects while forcing the finite Proposition 1.4 inputs through valuation-ball Haar normalization, and then projects to the additive-Haar formula-gap matched source. The distinguished and archimedean formula-to-gap comparisons have now been split out as named source objects:

`IUTStage1IUTIVTheorem110DistinguishedAdditiveHaarFormulaGapComparisonSource`,  
`IUTStage1IUTIVTheorem110ArchimedeanMetricFormulaGapComparisonSource`.

The first carries the local Proposition 1.4 additive-Haar log-shell source and derives the container-to-arithmetic-gap comparison; the second carries the Proposition 1.5 metric source and derives the corresponding archimedean container-to-gap comparison. They assemble into

```
IUTStage1IUTIVTheorem110AdditiveHaar
  FormulaGapMatchedArithmeticDivisorEvaluationSource,
```

which is now an intermediate projection from the valuation-ball version and projects to the existing additive-Haar arithmetic-divisor evaluation source. Thus these two gap inequalities are no longer only anonymous fields at the local analytic boundary. This source is now consumed at the experiment layer by

```
IUTStage1ValuationBallHaarTheorem110FormulaGapMatched
  PrimeErrorPadicDefectMainSource,
IUTStage1ValuationBallHaarTheorem110StepXIFormulaGapMatched
  ArithmeticDegreePadicPrimeErrorFormulaMatchingSource.
```

The first record keeps the valuation-ball formula-gap Theorem 1.10 source together with the  $p$ -adic Haar defect/main split; the second adds the Step (xi) arithmetic-degree calibration and projects to the additive formula-matching core. This valuation-ball payload now reaches the local-to-global  $C_\Theta$  boundary as

```
ConstructedTheorem3110OneSidedIUTIVTheorem110
  ValuationBallHaarFormulaGapMatchedArithmeticDegree
  PadicFormulaMatchedStepXILocalTermCThetaSource.
```

That source exposes arithmeticGap\_dominates\_canonicalCThetaScale, canonicalCThetaScale\_le\_iutIVCTheta, closedLocalGlobalEndpoint, and localGlobalHandoffAudit while retaining the valuation-ball Theorem 1.10 input at the public boundary. Forgetting valuation-ball provenance recovers the additive gap-matched chain

```
IUTStage1AdditiveHaarTheorem110FormulaGapMatched
  PrimeErrorPadicDefectMainSource,
IUTStage1AdditiveHaarTheorem110StepXIFormulaGapMatched
  ArithmeticDegreePadicPrimeErrorFormulaMatchingSource,
ConstructedTheorem3110OneSidedIUTIVTheorem110AdditiveHaar
  FormulaGapMatchedArithmeticDegreePadicFormulaMatched
  StepXILocalTermCThetaSource.
```

This final wrapper projects to the previous strongest additive-Haar local-global source and exposes the same arithmetic-gap, global  $C_\Theta$ -comparison, closed endpoint, and handoff audit. The public finite-divisor vertical- $IQ$  endpoint consuming the valuation-ball wrapper directly is

```
boundarySignedEqualityOrStrictCTheta_from
_constructedTheorem3110OneSidedIUTIVTheorem110ValuationBallHaar
_FormulaGapMatchedArithmeticDegreePadicFormulaMatched
_StepXILocalTermCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

It returns the valuation-ball endpoint evidence together with the Step (x) packet equalities, the IUT IV displayed-bound audit, the constructed global  $C_\Theta$ -scale audit, and the Corollary 3.12 dichotomy. The corresponding Step (xi) wrapper therefore exposes the preferred checked route. Its finite-divisor vertical- $IQ$  endpoint returns the additive-Haar source audit, the IUT IV displayed-bound audit, the constructed global  $C_\Theta$ -scale audit, and the Corollary 3.12 dichotomy. The preferred public projection is now

```

boundarySignedEqualityOrStrictCTheta_from
_preferredConstructedTheorem311IndeterminacyLocalGlobalCTheta
_FiniteDivisorVerticalIQ_ofRealifiedFrobenioidPacketSource.

```

It consumes the constructed qualitative Hodge/SHE/IPL source, the constructed Remark 3.9.5 hull/determinant source, and the additive-Haar arithmetic-degree/ $p$ -adic formula-matched Step (xi) source, then returns only the Corollary 3.12 dichotomy. Neither the raw  $\theta_{\text{signed}} \leq C_{\Theta} |\log q|$  bound nor the raw  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison is a hypothesis of this preferred endpoint. The stricter preferred projection

```

boundarySignedEqualityOrStrictCTheta_from
_preferredFormulaGapMatchedConstructedTheorem311
_IndeterminacyLocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource

```

has the same constructed qualitative Hodge/SHE/IPL boundary but consumes the formula-gap-matched additive-Haar source directly. Its audit

```

ConstructedQualitativeHodgeSHEIPLAdditiveHaar
FormulaGapMatchedArithmeticDegreePadicCThetaAudit

```

retains both the previous preferred audit by projection and the named formula-gap endpoint evidence. The valuation-ball refinement of the same preferred qualitative boundary is exposed as

```

boundarySignedEqualityOrStrictCTheta_from
_preferredValuationBallFormulaGapMatchedConstructedTheorem311
_IndeterminacyLocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.

```

Its audit

```

ConstructedQualitativeHodgeSHEIPL
ValuationBallHaarFormulaGapMatched
ArithmeticDegreePadicCThetaAudit

```

retains the additive formula-gap audit by projection, but its public endpoint evidence is the valuation-ball local-to-global source and the valuation-ball Theorem 1.10 formula-matching object. Thus finite Proposition 1.4 valuation-ball Haar normalization now survives the constructed qualitative Hodge/SHE/IPL route all the way to the preferred Corollary 3.12 dichotomy. The named distinguished and archimedean gap-comparison witnesses for the additive projection are still constructed from an additive-Haar local analytic arithmetic-divisor evaluation source by

```

IUTStage1IUTIVTheorem110AdditiveHaar
FormulaGapMatchedArithmeticDivisorEvaluationSource.
ofAdditiveHaarLocalAnalyticArithmeticDivisorEvaluationSource.

```

This removes the separate payload of comparison records once the lower additive-Haar source has supplied the local formula-to-gap inequalities. The same construction is now lifted through the local  $p$ -adic defect and arithmetic-degree formula chain. The declarations

```

IUTStage1AdditiveHaarTheorem110FormulaGapMatched
  PrimeErrorPadicDefectMainSource.ofPrimeErrorPadicDefectMainSource,
IUTStage1AdditiveHaarTheorem110StepXIFormulaGapMatched
  ArithmeticDegreePadicPrimeErrorFormulaMatchingSource.
  ofArithmeticDegreePadicPrimeErrorFormulaMatchingSource,
ConstructedTheorem311OneSidedIUTIVTheorem110AdditiveHaar
  FormulaGapMatchedArithmeticDegreePadicFormulaMatched
  StepXILocalTermCThetaSource.
  ofAdditiveHaarLocalAnalyticArithmeticDegreePadicFormulaMatched
  StepXILocalTermCThetaSource

```

construct the stricter formula-gap-matched route from the previous additive-Haar arithmetic-degree/ $p$ -adic source boundary. Thus formula-gap provenance is now a derived wrapper above that boundary, not a separate route-level payload. The derived qualitative audit

```

boundarySignedEqualityOrStrictCTheta_from_constructed
QualitativeHodgeSHEIPLDerivedFormulaGapMatched
AdditiveHaarArithmeticDegreePadicFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource

```

constructs this stricter audit internally from the additive-Haar arithmetic-degree/ $p$ -adic source before entering the finite-divisor vertical- $IQ$  corridor. The remaining source obligations are now the actual local log-shell inclusions and numerical Proposition 1.4 estimates that prove the formula-to-gap inequalities, construction of the Step (xi)/IUT IV local arithmetic matching source from paper-native objects, and replacement of the remaining lower compatibility projections by paper-native local-to-global constructions. The Step (xi) local matching obligation is separated in Lean as `IUTStage1AdditiveHaarTheorem110StepXILocalArithmeticMatchingSource`: it packages the local equality

$$A_v = S_v + \delta_v + M_v$$

between the IUT IV local arithmetic upper term, the Step (xi) weighted determinant term, the local arithmetic defect, and the main-log term. Its endpoint proves the derived local inequalities

$$S_v + \delta_v \leq A_v - M_v, \quad S_v \leq A_v - M_v,$$

using the nonnegativity of the local defect. This has now been lowered by `IUTStage1AdditiveHaarTheorem110StepXIFormulaGapControlled`

`LocalArithmeticSource`: if the distinguished Proposition 1.4 procession bound and the archimedean Proposition 1.5 procession bound are bounded by the localized Step (xi) determinant term  $S_v$ , Lean derives the distinguished and archimedean formula-to-gap inequalities from the local matching theorem  $S_v \leq A_v - M_v$ . This is a genuine reduction of the formula-gap payload: the remaining local question is now the paper-native domination of the Prop. 1.4/1.5 formula bounds by the IUT IV local arithmetic-degree term, together with the construction of the underlying local log-shell and metric estimates. The same reduction is now present before forgetting valuation-ball provenance. `IUTStage1ValuationBallHaarTheorem110StepXIFormulaGapControlled`

`LocalArithmeticSource` starts from the valuation-ball local-analytic Theorem 1.10 source, the localized Step (xi) term, and the IUT IV local defect source. It constructs the additive local matching source by projection, proves the distinguished and archimedean valuation-ball formula-to-gap inequalities, and then builds `IUTStage1IUTIVTheorem110ValuationBallAdditiveHaar`

`FormulaGapMatchedArithmeticDivisorEvaluationSource`. The constructor `IUTStage1ValuationBallHaarTheorem110FormulaGapMatched` `PrimeErrorPadicDefectMainSource.ofStepXIFormulaGapControlled`

`LocalArithmeticSource` threads this derived formula-gap source into the  $p$ -adic defect/main split. Thus the current valuation-ball boundary no longer needs the formula-gap-matched record as primitive data; its remaining payload is the concrete proof of the per-place procession bounds  $\text{formula}_v \leq S_v$  and the local prime-error identity from paper-native valuation-ball/log-shell constructions. The local arithmetic equality itself has also been lowered by `IUTStage1AdditiveHaarTheorem110StepXIArithmeticFormulaMatchingSource`. That source uses the IUT IV arithmetic-divisor formula

$$A_v = a_l(D_v + C_v) + E_v$$

and derives the displayed Step (xi) matching equality from two finer identifications:  $S_v = a_l(D_v + C_v)$  and  $E_v = \delta_v + M_v$ . The new source `IUTStage1AdditiveHaarTheorem110StepXIArithmeticDegreeControlledFormulaGapSource` uses this equality to turn the remaining Prop. 1.4/1.5 comparison

$$\text{formula}_v \leq a_l(D_v + C_v)$$

into the Step (xi)-controlled comparison  $\text{formula}_v \leq S_v$ , and then projects to the formula-gap-matched arithmetic-divisor evaluation source. This comparison is now backed by named Proposition 1.4/1.5 construction records. The algebra layer adds single-place distinguished and archimedean arithmetic-degree comparison sources; the experiment layer combines them as

`IUTStage1AdditiveHaarTheorem110StepXIArithmeticDegree  
ComparisonFormulaGapSource.`

Thus the remaining comparison with  $a_l(D_v + C_v)$  is no longer an anonymous inequality: it is attached to the same additive-Haar log-shell and archimedean metric construction witnesses used by the formula-gap source. The new calibrated source

`IUTStage1AdditiveHaarTheorem110StepXICalibrated  
ArithmeticDegreeComparisonFormulaGapSource`

splits this comparison one step further: the public procession formula bound is first identified with the coarse Step (v) or Step (vii) bound produced by the local construction, and only that coarse bound is compared with  $a_l(D_v + C_v)$ . This calibrated layer is now synchronized with the arithmetic-degree/ $p$ -adic formula source by

`ConstructedTheorem311OneSidedIUTIVTheorem110  
AdditiveHaarCalibratedFormulaGapMatchedArithmeticDegree  
PadicFormulaMatchedStepXILocalTermCThetaSource.`

Its synchronization field identifies the calibrated formula-matching source with the projection of the  $p$ -adic/arithmetic-degree formula source, so the calibrated comparison data cannot be attached to a different Step (xi) local package. The same synchronization is now available before forgetting valuation-ball provenance:

`ConstructedTheorem311OneSidedIUTIVTheorem110  
ValuationBallHaarCalibratedFormulaGapMatched  
ArithmeticDegreePadicFormulaMatchedStepXILocalTermCThetaSource`

keeps the valuation-ball Theorem 1.10 formula-gap source, the calibrated Proposition 1.4/1.5 arithmetic-degree comparison, and the  $p$ -adic formula-matching core in one source object. Its audit

projects the valuation-ball definition-of-done audit and the local formula-gap estimate while checking that the calibrated formula-matching source is the same formula-matching core used by the downstream  $p$ -adic route. The remaining local payload is therefore not a synchronization issue; it is the construction of the paper-native valuation-ball/log-shell comparison records themselves. The valuation-ball version has now been lowered to the same derived comparison level by

```
ConstructedTheorem311OneSidedIUTIVTheorem110
ValuationBallHaarDerivedFormulaGapMatched
ArithmeticDegreePadicFormulaMatchedStepXILocalTermCThetaSource.
```

This source keeps the valuation-ball Theorem 1.10 formula-gap package, but its public Proposition 1.4/1.5 payload is the derived comparison object. Thus the calibrated inequality  $\text{coarse}_v \leq a_l(D_v + C_v)$  is obtained by projection from the unscaled degree-bound/nonnegativity calculation rather than supplied as the source-facing comparison. Its audit records both the derived comparison endpoint and the inherited valuation-ball definition-of-done audit. The valuation-ball source has now been lowered through that unscaled step, through the degree-identification step, through the local formula checks, through the object-backed local degree-identification source, and further to the arithmetic-divisor-backed matched local-degree component source:

```
ConstructedTheorem311OneSidedIUTIVTheorem110
ValuationBallHaarArithmeticDivisorBackedMatchedLocalDegreeComponent
ArithmeticDegreePadicFormulaMatchedStepXILocalTermCThetaSource.
```

Here the source-facing local payload no longer stops at typed local degree-identification objects. It carries the arithmetic-divisor-backed component source: finite distinguished different/conductor degrees come from the Theorem 1.10 arithmetic divisors, their effectivity proves the required nonnegativity, and the tensor-different/tensor-conductor identities connect those divisor degrees to the Proposition 1.4 log-shell calculation. The valuation-ball synchronization proof then recovers the object-backed source by projection. The remaining hard local work is narrower: replace the remaining paper-side component inputs themselves by still more explicit valuation-ball and log-shell constructions where possible. In the additive-Haar chain, the corresponding calibrated comparison had already been lowered by

```
IUTStage1AdditiveHaarTheorem110StepXIDerived
ArithmeticDegreeComparisonFormulaGapSource.
```

For each distinguished additive-Haar place and each archimedean metric place, the new source derives

$$\text{coarse}_v \leq a_l(D_v + C_v)$$

from the unscaled local degree bound  $\text{coarse}_v \leq D_v + C_v$ , the coefficient lower bound  $1 \leq a_l$ , and nonnegativity of  $D_v + C_v$ . This unscaled layer is now represented explicitly by

```
IUTStage1AdditiveHaarTheorem110StepXIUnscaled
DegreeBoundFormulaGapSource.
```

At a distinguished nonarchimedean place the source names the Proposition 1.4 tensor expression  $-\lambda + d_I + 4 \log(p) + \text{Ram}$  as the local different-plus-conductor bound; at an archimedean place it names the Step (vii) coarse bound as the same unscaled degree bound. Both project to the derived

source above, so the direct payload has been narrowed to the paper-side local degree identification itself. The local degree-identification payload has now been factored into two lower source objects,

```
IUTStage1IUTIVTheorem110DistinguishedAdditiveHaar
UnscaledDegreeIdentificationSource,
IUTStage1IUTIVTheorem110ArchimedeanMetric
UnscaledDegreeIdentificationSource.
```

The first identifies the Proposition 1.4 tensor expression with  $D_v + C_v$  and records the coarse Step (v) domination by that tensor degree; the second identifies the Step (vii) archimedean coarse bound with  $D_v + C_v$ . Each constructs the older unscaled degree-bound source by projection. At the finite-place formula-gap level this is exposed by

```
IUTStage1AdditiveHaarTheorem110StepXI
DegreeIdentifiedUnscaledFormulaGapSource.
```

This has now been lowered one step further by

```
IUTStage1AdditiveHaarTheorem110StepXI
LocalDegreeIdentificationFormulaSource.
```

This source does not ask for the per-place degree-identification records directly. It carries the formula-level local checks:  $1 \leq a_l$ , the identification of the distinguished procession bound with the coarse Step (v) bound, the Proposition 1.4 tensor expression as  $D_v + C_v$ , the coarse Step (v) domination by that tensor expression, the archimedean Step (vii) coarse-bound identification, and the archimedean coarse  $D_v + C_v$  equality. Lean derives the nonnegativity of  $D_v$  and  $C_v$  from the arithmetic-divisor evaluation source and constructs `DegreeIdentifiedUnscaledFormulaGapSource` by projection. The p-adic/arithmetic formula-matched branch now has a matched version of this local source,

```
IUTStage1AdditiveHaarTheorem110StepXI
MatchedLocalDegreeIdentificationFormulaSource.
```

Here the local degree-identification formulas are written directly over the arithmetic formula core projected from the source

```
IUTStage1AdditiveHaarTheorem110StepXIFormulaGapMatched
ArithmeticDegreePadicPrimeErrorFormulaMatchingSource.
```

Consequently the endpoint no longer exposes a separate proof that the local-degree formula source and the p-adic formula source have the same arithmetic-formula core; that synchronization is internal and definitional. The scaling input  $1 \leq a_l$  has also been factored as

```
IUTStage1IUTIVThetaPilotArithmeticDegreeCoefficient
LowerBoundSource.
```

This source records the explicit size condition  $4|\log(q)| \leq l+1$  and Lean derives  $1 \leq a_l$  from the displayed IUT IV coefficient formula and  $|\log(q)| > 0$ . It now has a separate `CoefficientWindowAudit`: Lean proves the base window factor  $(l+1)/(4|\log(q)|) \geq 1$ , the theta-error factor  $1 + 36d_{\text{mod}}/l \geq 1$ , and then multiplies these inequalities to obtain  $1 \leq a_l$ . Thus the matched local-degree source no longer carries  $1 \leq a_l$  as an anonymous proof field; it carries the named paper-side coefficient-window source. The same matched source now exposes

```
IUTStage1AdditiveHaarTheorem110StepXI
MatchedLocalDegreeIdentificationFormulaSource.
CoefficientWindowSynchronizationAudit.
```

This audit records that the coefficient-window source's displayed  $a_l$  is definitionally the arithmetic-divisor evaluation coefficient used by the local formula source, and that the lower bound  $1 \leq a_l$  is transported through that equality before the local degree-identification formulas are built; it also exposes the nested `CoefficientWindowAudit`. The formula source also now has a named `LocalDegreeFormulaAudit`. It derives, from the Step (v) formula bound, the Proposition 1.4 tensor equality, and the tensor domination,

$$\text{bound}_v^{(v)} \leq D_v + C_v,$$

and it derives from the Step (vii) formula equality the archimedean identity

$$\text{bound}_v^{(vii)} = D_v + C_v$$

together with its inequality form. These are the local unscaled consequences used to construct the degree-identification records; they are no longer only recoverable by inspecting the projection to `DegreeIdentifiedUnscaledFormulaGapSource`. This formula boundary has now been tightened by an object-backed matched source,

```
IUTStage1AdditiveHaarTheorem110StepXI
MatchedLocalDegreeIdentificationObjectSource.
```

It consumes the typed distinguished and archimedean unscaled degree-identification objects from the IUT IV algebra layer and derives the five matched Step (v)/Step (vii) formula fields by projection. The preferred finite-divisor endpoint

```
boundarySignedEqualityOrStrictCTheta_from_preferred
MatchedLocalDegreeObjectConstructedTheorem311
IndeterminacyLocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource
```

therefore no longer exposes these formula fields as the public boundary; it exposes the typed local identification objects and projects internally to the matched formula route. The remaining local obligation is to construct these typed Step (v)/Step (vii) identification objects from the detailed valuation, log-shell, and archimedean metric data of the paper. The local-to-global surface first had a matching unscaled public wrapper

```
ConstructedTheorem311OneSidedIUTIVTheorem110
AdditiveHaarUnscaledDegreeBoundFormulaGapMatched
ArithmeticDegreePadicFormulaMatchedStepXI
LocalTermCThetaSource.
```

It projects to the derived wrapper internally and exposes the same closed finite-divisor vertical-*IQ* endpoint with the unscaled local different-plus-conductor payload as its public source assumption. The public boundary has now been lowered one more step by

```
ConstructedTheorem311OneSidedIUTIVTheorem110
AdditiveHaarDegreeIdentifiedUnscaledFormulaGapMatched
ArithmeticDegreePadicFormulaMatchedStepXI
LocalTermCThetaSource.
```

This wrapper carries the finite-place `DegreeIdentifiedUnscaledFormulaGapSource`, projects to the unscaled wrapper internally, and exposes the same



arithmeticGap\_dominates\_canonicalCThetaScale, canonicalCThetaScale\_le\_iutIVCTheta, closedLocalGlobalEndpoint, and localGlobalHandoffAudit theorems at the degree-identification boundary. The matching lower wrapper is

```
ConstructedTheorem3110neSidedIUTIVTheorem110
AdditiveHaarLocalDegreeFormulaMatchedArithmeticDegree
PadicFormulaMatchedStepXIILocalTermCThetaSource.
```

It carries LocalDegreeIdentificationFormulaSource, projects to the degree-identified wrapper internally, and exposes the same closed local-to-global  $C_\Theta$  handoff theorems at the formula-equality boundary. The strict matched wrapper is

```
ConstructedTheorem3110neSidedIUTIVTheorem110
AdditiveHaarMatchedLocalDegreeFormula
StepXIILocalTermCThetaSource.
```

It carries the matched local-degree formula source above, projects to the previous local-degree wrapper with the formula-core equality supplied by rfl, and now exposes matchedLocalDegreeFormulaAudit together with the same arithmeticGap\_dominates\_canonicalCThetaScale, canonicalCThetaScale\_le\_iutIVCTheta, closedLocalGlobalEndpoint, and localGlobalHandoffAudit theorems. The object-backed wrapper

```
ConstructedTheorem3110neSidedIUTIVTheorem110
AdditiveHaarMatchedLocalDegreeObject
StepXIILocalTermCThetaSource
```

now projects to this strict matched formula wrapper and exposes the same closed  $C_\Theta$  handoff theorems together with matchedLocalDegreeObjectAudit. The distinguished finite-place side has now been lowered below this object boundary. The source

```
IUTStage1IUTIVTheorem110DistinguishedAdditiveHaar
TensorDegreeComponentSource
```

separates the local tensor expression

$$-\lambda + d_I + \text{Ram} + 4 \log(p)$$

into a different component  $-\lambda + d_I + \text{Ram}$  and a conductor component  $4 \log(p)$ , proves their recombination as tensorFormula\_eq\_different\_conductor, and then projects to the older distinguished unscaled degree-identification object. Its matched Step (xi) wrapper,

```
IUTStage1AdditiveHaarTheorem110StepXI
MatchedLocalDegreeDistinguishedComponentSource,
```

combines these distinguished component sources with the existing archimedean degree-identification objects. The corresponding local-to-global  $C_\Theta$  wrapper

```
ConstructedTheorem3110neSidedIUTIVTheorem110
AdditiveHaarMatchedLocalDegreeDistinguishedComponent
StepXIILocalTermCThetaSource
```

projects to the object-backed route and exposes the same closed handoff, audit, and final preferred dichotomy endpoint. Thus the current preferred finite-divisor endpoint no longer consumes

the distinguished local degree-identification object as primitive; it consumes the finer local different/conductor decomposition and rebuilds that object internally. The finite distinguished branch is now lowered beyond the tensor-component interface to the constructed source

`IUTStage1IUTIVTheorem110DistinguishedAdditiveHaar  
ConstructedTensorDegreeComponentSource.`

This object reads the Proposition 1.4 additive-Haar log-shell source and defines the finite local components

$$D_v = -\lambda + d_I + \text{Ram}, \quad C_v = 4 \log(p_v).$$

Lean proves the conductor nonnegativity from the residue-prime bound and projects the source to the older tensor-degree component and calibrated unscaled-degree interfaces. This has now been lowered once more by

`IUTStage1IUTIVTheorem110DistinguishedAdditiveHaar  
EffectiveDifferentConstructedTensorDegreeComponentSource.`

That source reads the nonnegativity of the local arithmetic different degree from the effective arithmetic-divisor side of Definition 1.9/Theorem 1.10 and uses the equality between that degree and  $-\lambda + d_I + \text{Ram}$  to derive the tensor-different nonnegativity internally. Thus the remaining finite payload at this boundary is no longer the raw nonnegativity assertion. This has now been lowered again to

`IUTStage1IUTIVTheorem110DistinguishedAdditiveHaar  
EffectiveDifferentConductorConstructedTensorDegreeComponentSource.`

The new source also reads the effective arithmetic local conductor degree and identifies it with the Proposition 1.4 tensor-conductor term  $4 \log(p_v)$ . The matched finite source therefore derives both finite component equalities

$$D_v = -\lambda + d_I + \text{Ram}, \quad C_v = 4 \log(p_v)$$

from arithmetic local degrees before projecting to the closed local-to-global  $C_\Theta$  route. This boundary has now been lowered once more to

`IUTStage1IUTIVTheorem110DistinguishedAdditiveHaar  
ArithmeticDivisorBackedTensorDegreeComponentSource.`

Here  $D_v$  and  $C_v$  are not free arithmetic local degrees: they are `differentDivisor.localDegree v` and `conductorDivisor.localDegree v` from the Theorem 1.10 arithmetic-divisor source. Lean derives their nonnegativity from effectivity of the different and conductor divisors, then uses the remaining paper-side identifications of those divisor local degrees with the Proposition 1.4 tensor terms. The remaining finite payload is therefore narrower: construct the different, conductor, and  $q$ -parameter divisors from valuation and ramification data, and construct the Proposition 1.4 log-shell source that supplies the displayed tensor identities.

The archimedean branch remains lowered beyond the component interface to the constructed source

`IUTStage1IUTIVTheorem110ArchimedeanMetric  
ConstructedDegreeComponentSource.`

Here the local different component and local conductor component are defined from the Proposition 1.5 metric construction source itself: the former is the exact metric term and the latter is the

exact-to-coarse remainder. Lean then projects this source to the previous component object and provides a calibrated projection for externally named Step (xi) local  $D_v, C_v$  entries. The matched source

```
IUTStage1AdditiveHaarTheorem110StepXI
MatchedLocalDegreeArithmeticDivisorBackedComponentSource
```

uses the arithmetic-divisor-backed finite construction at every distinguished finite place and the metric construction at every archimedean place. The local-to-global wrapper

```
ConstructedTheorem311OneSidedIUTIVTheorem110
AdditiveHaarMatchedLocalDegreeArithmeticDivisorBackedComponent
StepXILocalTermCThetaSource
```

projects it to the effective-different/conductor and then constructed-component  $C_\Theta$  route. The current strongest preferred endpoint is

```
boundarySignedEqualityOrStrictCTheta_from_preferred
MatchedLocalDegreeArithmeticDivisorBackedComponent
ConstructedTheorem311
IndeterminacyLocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

It consumes arithmetic-divisor-backed finite local-degree data and construction-backed archimedean local-degree components, then derives the finite-divisor vertical- $IQ$  dichotomy through the closed local-to-global  $C_\Theta$  source. The finite distinguished branch is now audited separately by

```
IUTStage1AdditiveHaarTheorem110StepXI
MatchedLocalDegreeArithmeticDivisorBackedComponentSource.
ArithmeticDivisorLocalDegreeAudit.
```

For every distinguished nonarchimedean place this audit exposes the arithmetic-divisor-backed component endpoint, nonnegativity of the local different and conductor degrees from divisor effectivity, the identifications of those local degrees with the Proposition 1.4 tensor-different and tensor-conductor terms, and the projection to the effective different/conductor component endpoint. The archimedean branch is now audited at the parallel constructed-component boundary by

```
IUTStage1AdditiveHaarTheorem110StepXI
MatchedLocalDegreeConstructedArchimedeanComponentSource.
ArchimedeanConstructedDegreeComponentAudit.
```

For every archimedean place this audit records the Proposition 1.5 metric construction endpoint, the equality with the Step (xi) archimedean metric source, the identifications of the Step (xi) local different and conductor entries with the constructed exact metric and coarse-remainder terms, and the projection to the calibrated local-degree component endpoint. The top arithmetic-divisor-backed  $C_\Theta$  certificate now carries this audit beside the finite arithmetic-divisor local-degree audit. The same wrapper now exposes the local-to-global arithmetic proof and the Theorem 3.11 quotient input at

this lowest boundary by

```

ArithmeticDivisorBackedLocalGlobalCThetaAudit,
ArithmeticDivisorBackedLocalGlobalCThetaAudit.
    arithmeticDivisorLocalDegreeAudit,
ArithmeticDivisorBackedLocalGlobalCThetaAudit.
    archimedeanConstructedDegreeComponentAudit,
ArithmeticDivisorBackedLocalGlobalCThetaAudit.oneSidedQuotientAudit,
ArithmeticDivisorBackedLocalGlobalCThetaAudit.
    oneSidedRemark395CompatibilityAudit,
ArithmeticDivisorBackedLocalGlobalCThetaAudit.
    oneSidedSelectedQHullLogVolumeAudit,
ArithmeticDivisorBackedLocalGlobalCThetaAudit.typedCoreActionLawAudit,
ArithmeticDivisorBackedLocalGlobalCThetaAudit.selectedQRegionQuotientEndpoint,
localGlobalCThetaDerivationAudit.

```

These declarations project the arithmetic-divisor-backed source to the formula-gap/additive-Haar summation source, record the one-sided  $(\text{Ind}_1)/(\text{Ind}_2)$  equality-quotient audit, expose its compact typed-core action-law certificate, carry the selected-q hull/log-volume audit at the same arithmetic-divisor boundary, record the selected q-pilot possible image both as a Theorem 3.11 possible image and as an equality-quotient possible image, record the finite-place Step (xi) Haar summation audit, derive

$$C_{\Theta, \text{can}} + 1 \leq A - M,$$

and then obtain the displayed  $C_{\Theta, \text{can}} \leq C_{\Theta}$  handoff from the IUT IV identity  $C_{\Theta} + 1 = A - M$ . Thus the newest endpoint's  $C_{\Theta}$  comparison is visible as a derived local-to-global chain rather than only as an inherited projection through the effective-conductor wrapper. The determinant and canonical-scale sides of this handoff are now lowered one more source boundary by

```

RecordOb3Ob5ArithmeticDivisorBackedComponentSource,
RecordOb3Ob5StepXIDeterminantHandoffAudit.

```

This wrapper no longer stores either the Step (xi) determinant equality or the global-scale-to-Step (xi)-sum equality directly. It derives the determinant equality from the record-canonical Ob3/Ob5 adjusted determinant source, identifies the record Ob3/Ob4 weighted determinant with the localized Step (xi) arithmetic-degree determinant, first calibrates  $C_{\Theta, \text{can}}$  against the record adjusted-summand log-volume, and then derives the localized weighted Step (xi) sum from the same Ob3/Ob4 identification. The broader  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison remains the surrounding local-to-global arithmetic-divisor chain. The compact theorem `arithmeticDivisorBackedFinitePlaceCThetaChain` now packages this chain as a single source-level review target: finite-place identifications, the summed Step (xi)/Haar bound, the total Haar-defect lower bound, the derived arithmetic gap, the  $C_{\Theta, \text{can}} \leq C_{\Theta}$  handoff, and the final signed  $C_{\Theta}$  bound are all returned together. The finite-place source now also has the explicit `IUTIVArithmeticGapHandoffAudit`, which records the finite-sum identifications, the summed Step (xi)/Haar inequality, the unit Haar-defect input, the IUT IV identity  $C_{\Theta} + 1 = A - M$ , and the ordered-real cancellation to  $C_{\Theta, \text{can}} \leq C_{\Theta}$  in one checked certificate. This source-level audit is now pinned at the constructed qualitative Hodge/SHE/IPL finite-divisor boundary by

```

ConstructedQualitativeHodgeSHEIPLAdditiveHaar
ArithmeticDivisorBackedComponentCThetaAudit.

```

The preferred arithmetic-divisor-backed endpoint projects its dichotomy from that certificate, whose fields include the constructed qualitative bridge, the source-record constructed transport-guard audit, the choice-wise constructed IPL link law, the forbidden direct SHE domain-to-codomain transport guard, the non-forbidden permitted APT transport guard, the source theta/Hodge log-volume calibration endpoint, the one-sided Theorem 3.11 quotient audit, the one-sided Remark 3.9.5 compatibility audit, its typed-core action-law audit, the explicit exclusion of  $(\text{Ind}_3)$  from the equality quotient, the  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  procession-normalized log-volume equalities, the  $(\text{Ind}_3)$  upper-semi log-volume inequality, the  $\mathbb{F}_l$ -procession equality-quotient law, the selected q-region quotient endpoint, the realified Frobenioid/log-Kummer packet endpoint, the recovered finite-divisor packet-local Step (x) source, the exact vertical- $IQ$  target endpoint, the arithmetic-divisor-backed endpoint, the arithmetic-divisor local-degree audit, the finite-place local-to-global  $C_\Theta$  derivation audit, the `paperTraceRemainingPayloadAudit`, the closed handoff audit, and the derived arithmetic-gap  $C_\Theta$  chain. The same endpoint now exposes the Theorem 3.11 source-record guard as

```
IUTStage1Theorem311MultiradialSourceRecord.  
ConstructedQualitativeTransportGuardAudit,
```

which packages the record/bundle equality, the multiradial source endpoint, the structured-Hodge history guard, the typed SHE forbidden-transport audit including all-arrow and all-mechanism exclusions, and the non-forbidden APT arrow audit. This does not yet derive the full source-paper Hodge-theater reconstruction theorem, but it removes the earlier boundary where the Theorem 3.11 source record exposed only a side-inequality history guard while the constructed SHE/APT transport discipline lived only in a later bridge. Lean now also exposes the synchronized constructor

```
ofTransportBaseConstructedQualitativeInputsWithSHE_  
synchronizedTransportGuardAudit.
```

It builds the structured-SHE input from the base context of the constructed SHE-transport system itself, proves the definitional equality between those contexts, and derives the record's Hodge-history guard by rewriting the transport audit's `history_sides_not_identified` field. This is the cleaner boundary for later endpoint lowering: arbitrary constructed bundles still carry the ordinary guard audit, while transport-base bundles make the source-record history separation a consequence of the typed transport system. The finite-divisor  $C_\Theta$  boundary now exposes this cleaner form through

```
boundarySignedEqualityOrStrictCTheta_from_transportBase  
ConstructedQualitativeHodgeSHEIPLAdditiveHaar  
ArithmeticDivisorBackedComponentFiniteDivisorVerticalIQ  
_ofRealifiedFrobenioidPacketSource
```

and the corresponding direct dichotomy projection. These declarations take the constructed qualitative inputs as the source data, build the transport-base structured-SHE bundle, the Theorem 3.11 multiradial source record, and the finite Hodge-SHE-IPL construction internally, and return the synchronized transport-guard audit together with the arithmetic-divisor-backed  $C_\Theta$  certificate. Thus this public finite-divisor endpoint no longer has an arbitrary source-record/constructed-bundle pair as part of its exposed hypothesis surface; the remaining source inputs are the substantive Remark 3.9.5 hull source, the  $IUT$  IV estimate, and the arithmetic-divisor-backed component sources. The same transport-base boundary now has the named audit projection

```
boundarySignedEqualityOrStrictCTheta_from_transportBase  
ConstructedQualitativeHodgeSHEIPLAdditiveHaar  
ArithmeticDivisorBackedComponentFiniteDivisorVerticalIQ  
_paperTraceLocalGlobalAudit.
```

It projects the top-level paper-trace remaining-payload audit from this transport-base route, so the review surface can cite the constructed Theorem 3.11 quotient layer, Step (x), Step (xi), *IUTIV* local-to-global  $C_\Theta$  handoff, and raw-comparison-free endpoint through one declaration at the current preferred boundary. The direct transport-base dichotomy theorem now takes its final alternative from the `ClosedDichotomyEndpoint` field of this certificate, so the public Corollary 3.12 projection passes through the raw-comparison-free endpoint rather than reading the broader audit's derived signed-bound field directly. The companion declaration

```
boundarySignedEqualityOrStrictCTheta_from_transportBase
ConstructedQualitativeHodgeSHEIPLAdditiveHaar
ArithmeticDivisorBackedComponentFiniteDivisorVerticalIQ
_milestoneCompletionAudit
```

collects the same boundary evidence in one requirement-indexed certificate: the synchronized transport-base source record, a strict finite typed indeterminacy nonvacuity witness, the `PreferredSourceCorridorDODAAudit`, and the full `ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDivisorBackedComponentCThetaAudit`. Together these structures contain the typed  $(\text{Ind}_1), (\text{Ind}_2), (\text{Ind}_3)$  quotient laws, selected q-region and selected-q hull/log-volume audits, constructed IPL/SHE/APT transport laws, finite-place Step (xi)/Haar summation, derived  $C_\Theta$  comparison, closed raw-comparison-free endpoint, and final dichotomy. This is the current definition-of-done certificate for the milestone-level source-interface route; it is not a claim that the full published IUT source constructions have been formalized from first principles. The same endpoint also exposes the Step (xi) normalized bridge directly as `normalizedRecordBridge` and `qRegionLogVolume_le_thetaSigned`: the constructed Remark 3.9.5 source gives

$$\mu_{\log}(q\text{-region}) \leq \det_{\text{norm}} \leq \theta_{\text{signed}},$$

and hence the q-region log-volume is already bounded by  $\theta_{\text{signed}}$  before the later *IUTIV*  $C_\Theta$  comparison is invoked. It also exposes the finite-place local-to-global arithmetic step directly through `finitePlaceLocalGlobalIdentifications`, `finitePlaceLocalUpperContributionDecomposition`, `finitePlaceLocalStepXIHaarIdentity`, `finitePlaceSummedStepXIHaarBound`, and `finitePlaceTotalHaarDefect_ge_one`: the local canonical scale, arithmetic upper term, and main-log term are identified with their finite sums, each local arithmetic upper contribution is identified with the Step (xi) weighted determinant contribution plus the *IUTIV* arithmetic defect plus the local main-log term, Lean cancels the main-log term to obtain the pointwise identity

$$A_v - M_v = S_v + N_v,$$

and these local Step (xi)/Haar identities are then summed, while the Haar-normalization defect contributes the global +1. The derived consequences are now separate fields, `finitePlaceDerivedArithmeticGap` and `finitePlaceDerivedCanonicalCThetaScale_le_iutIVCTheta`, proving

$$C_{\Theta, \text{can}} + 1 \leq A_{\text{upper}} - M_{\log}$$

and then  $C_{\Theta, \text{can}} \leq C_\Theta$  via the *IUTIV* identity  $C_\Theta + 1 = A_{\text{upper}} - M_{\log}$ . In particular, the audit now stores the local-to-global derivation of

$$\theta_{\text{signed}} \leq C_\Theta \cdot (-q_{\text{signed}})$$

and the corresponding source-bridge-to-*IUT IV*  $C_\Theta$  inequality, rather than requiring this signed bound as a public endpoint hypothesis. The generic local-to-global source also exposes the named audit `ClosedDichotomyEndpoint`, whose proposition contains only the source assembly obligations, the *IUT IV* expression  $C_\Theta = A_{\text{upper}} - M_{\log} - 1$ , and the final dichotomy. The companion audit `ClosedNoRawComparisonAudit` carries this endpoint together with the derived comparison chain, and the constructed qualitative Hodge-SHE-IPL certificate carries both directly; its fields project the arithmetic-gap cancellation, the derived  $C_{\Theta, \text{can}} \leq C_\Theta$  comparison, the derived signed  $C_\Theta$  bound, and the final dichotomy from the constructed handoff rather than from raw comparison inputs. The paper-trace field instantiates the abstract remaining-payload ledger with the formula-gap-matched Theorem 1.10 arithmetic-divisor evaluation, the local arithmetic matching source, the Step (xi) arithmetic-degree calibration, the two separated arithmetic-degree calibration laws  $\text{wt}_v = a_l$  and  $\ell_{v, \text{adj}} = D_v + C_v$ , Step (x) packet equalities, the constructed IPL choice-link endpoint, the IPL-datum/certificate alignment, the structured IPL/SHE/APT evidence, the SHE/APT transport guards, and the arithmetic-divisor-backed endpoint itself. The same split is now used in the additive-Haar subledger rather than only in the outer Theorem 3.11 trace. The transport-guard split is also exposed on the arithmetic-degree/p-adic additive-Haar audit, so both the intermediate additive-Haar route and the final arithmetic-divisor-backed route carry the same source-record constructed transport certificate. The same certificate now also has a top-level `topLevelPaperTraceRemainingPayloadAudit` field for the assembled `IUTStage1Theorem311ToCorollary312PaperTrace.Obligations` ledger. This outer audit records the Theorem 3.11/Remarks 3.11.2–3.11.4 source, Step (x), Step (xi), *IUT IV*, additive-Haar, and closed-endpoint obligations together; its last two entries are witnessed by the derived  $\theta_{\text{signed}} \leq C_\Theta(-q_{\text{signed}})$  bound and the finite-place-derived  $C_{\Theta, \text{can}} \leq C_\Theta$  comparison, not by raw endpoint hypotheses. In the Theorem 3.11 part of this audit, the multi-radial, theta-possible-image, and finite-label/procession slots are now split into the exact quotient equality/action-law, possible-image pullback, cardinality, and procession-transition facts; the IPL/SHE/APT slots are split into the constructed choice-link endpoint and the explicit structured transport guards. The trace also takes the normalized Step (xi) bridge directly from the constructed Remark 3.9.5 record bridge: the weighted determinant/tensor-power slot is witnessed by  $\det_{\text{norm}} \leq \theta_{\text{signed}}$ , and the q-region log-volume slot by  $\mu_{\log}(q_{\text{region}}) \leq \theta_{\text{signed}}$ . The assembled *IUT IV* obligation list now has a separate `finite_place_arithmetic_gap_constructed` entry, witnessed here by `finitePlaceDerivedArithmeticGap`. This entry has now been refined by `LocalToGlobalArithmeticChainAudit`, whose slots separately record the finite-place sum identifications for the canonical scale, arithmetic upper term, and main-log term, the summed Step (xi) Haar bound, the total Haar-defect lower bound, the *IUT IV* identity  $C_\Theta + 1 = A - M$ , and the ordered-real cancellation of the normalized +1 before the final  $C_{\Theta, \text{can}} \leq C_\Theta$  consequence. Thus the paper trace records the actual finite-place summation and cancellation, not only the derived  $C_{\Theta, \text{can}} \leq C_\Theta$  comparison. Its distinguished Proposition 1.4 entries are also no longer witnessed by the whole local-degree audit: the log-shell inclusion slot is filled by the per-place distinguished component endpoint, and the numerical-bound slot is filled by the local different and conductor nonnegativity projections. The same cleanup now applies to the remaining local *IUT IV* case split: the nondistinguished Proposition 1.4 slot is witnessed by the per-place additive-Haar log-shell endpoint, the Proposition 1.5 slot by the per-place archimedean metric endpoint, and the distinguished/archimedean Theorem 1.10 formula-gap slots by the named per-place comparison endpoints. The matched boundary now has its own constructed qualitative audit,

`ConstructedQualitativeHodgeSHEIPLAdditiveHaar`  
`MatchedLocalDegreeFormulaCThetaAudit.`

This audit records the strict source's `MatchedLocalDegreeFormulaAudit`: the matched local-degree endpoint, the coefficient-window endpoint, the nested `CoefficientWindowSynchronizationAudit`, the projected local degree-formula endpoint, the nested `LocalDegreeFormulaAudit`, the formula-gap matched arithmetic-degree/ $p$ -adic endpoint, the `ArithmeticDegreeCalibrationAudit`, the definitional formula-core synchronization, and the degree-identified unscaled endpoint. The calibration audit records, place by place, that the localized Step (xi) determinant weight is the IUT IV arithmetic-degree coefficient and that the adjusted raw log-volume is the local different-plus-conductor degree; the displayed  $S_v = a_l(D_v + C_v)$  formula is then the derived local equality exposed by the same certificate. It also records the closed local-to-global endpoint, the Remark 3.9.5/IUT IV handoff audit, the derived  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison, and the final dichotomy. Thus the paper-trace certificate is attached directly to the current lowest matched local-degree source rather than only to its older unscaled projection. The prime-error side has then been lowered another step by `IUTStage1AdditiveHaarTheorem110PrimeErrorPadicDefectMainSource`: it uses the local  $p$ -adic Haar-index split

$$E_v = h_v + M_v$$

together with the IUT IV defect identification  $\delta_v = h_v$  to derive  $E_v = \delta_v + M_v$ . The wrapper `IUTStage1AdditiveHaarTheorem110StepXIIPadicPrimeErrorFormulaMatchingSource` handled the prime-error side while still exposing the Step (xi) arithmetic-degree identification  $S_v = a_l(D_v + C_v)$ . That last local formula has now been factored by `IUTStage1AdditiveHaarTheorem110StepXIIArithmeticDegreeCalibrationSource`. It derives  $S_v = a_l(D_v + C_v)$  from two source equalities: the localized determinant multiplicity is the IUT IV arithmetic-degree coefficient  $a_l$ , and the adjusted raw localization log-volume is the local different-plus-conductor degree  $D_v + C_v$ . These two equalities are now the actual witnesses in the additive-Haar paper-trace subledger, rather than both slots being filled by the whole arithmetic-degree calibration endpoint. The combined arithmetic-degree/ $p$ -adic formula source therefore backs both local formula sides and now enters the finite-place local-global  $C_{\Theta}$  route at the same strength. In particular, the strict source has a finite-divisor vertical- $IQ$  boundary theorem after combination with the realified Frobenioid log-Kummer packet source; at that boundary neither the numerical  $\Theta$ -bound nor the global  $C_{\Theta}$  comparison is supplied as a raw endpoint hypothesis.

The matched additive-Haar wrapper also projects directly to `ConstructedTheorem311OneSidedFinitePlaceLocalGlobalCThetaSource`; the summation theorem there derives

$$C_{\Theta, \text{can}} + 1 \leq A - M$$

from the local matching source and the global lower bound for the total local arithmetic defect. Thus the theorem `arithmeticGap_dominates_canonicalCThetaScale` is no longer reached only through a compatibility projection to the older additive-Haar wrapper. The current strongest finite-divisor boundary therefore combines the strict Step (xi)/IUT IV local formula source with the Step (x) realified Frobenioid log-Kummer packet source, so both local arithmetic matching and packet equalities appear as typed source objects rather than loose endpoint fields. The calibrated version of this boundary is exposed as

```
boundarySignedEqualityOrStrictCTheta_from_constructed
Theorem311OneSidedIUTIVTheorem110AdditiveHaarCalibrated
FormulaGapMatchedArithmeticDegreePadicFormulaMatched
StepXIILocalTermCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```



It projects to the formula-gap matched proof for the closed  $C_\Theta$  comparison, but its public endpoint now retains the calibrated coarse Step (v)/(vii) source evidence. The corresponding unscaled boundary theorem is now also present:

```
boundarySignedEqualityOrStrictCTheta_from_constructed
Theorem311OneSidedIUTIVTheorem110AdditiveHaarUnscaled
DegreeBoundFormulaGapMatchedArithmeticDegreePadic
FormulaMatchedStepXIILocalTermCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

It exposes the Proposition 1.4/Step (vii) unscaled local degree-bound records at the finite-divisor boundary and projects to the derived/calibrated route internally. The corresponding degree-identified boundary theorem is

```
boundarySignedEqualityOrStrictCTheta_from_constructed
Theorem311OneSidedIUTIVTheorem110AdditiveHaarDegreeIdentified
UnscaledFormulaGapMatchedArithmeticDegreePadicFormulaMatched
StepXIILocalTermCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

It exposes the Proposition 1.4 tensor-to- $D_v + C_v$  and archimedean Step (vii)-to- $D_v + C_v$  identifications at the finite-divisor boundary, then projects to the unscaled theorem internally. This strongest additive-Haar boundary has now also been tied to the constructed qualitative Hodge/SHE/IPL provenance at the same unscaled strength. The declaration

```
boundarySignedEqualityOrStrictCTheta_from_constructed
QualitativeHodgeSHEIPLAdditiveHaarUnscaledDegreeBound
ArithmeticDegreePadic
FiniteDivisorVerticalIQ_ofRealifiedFrobenioidPacketSource
```

projects the IPL link from the constructed qualitative source, reuses the formula-gap qualitative audit obtained from the unscaled source, and records the unscaled Proposition 1.4/Step (vii) endpoint, the realified packet equalities, the  $IUTIV$  handoff, the global  $C_\Theta$ -scale audit, and the final dichotomy. The projected top-level audit therefore exposes the fact that  $(Ind_1)$  and  $(Ind_2)$  form the equality quotient while  $(Ind_3)$  remains outside that quotient as an upper-semi log-volume relation; this no longer has to be recovered by chasing through the nested finite-place audit. This is now recorded directly on the unscaled audit certificate: the choice-wise IPL links, the typed SHE no-domain-to-codomain transport guard, and the permitted APT arrow's non-forbidden-identification proof are all fields of the preferred additive-Haar certificate. At the underlying Step (xi) qualitative bridge these laws are now bundled as

```
IUTStage1ConstructedQualitativeFiniteHodgeSHEIPLConstructionSource.
ConstructedIPLSHEAPTTransportLawAudit.
```

This audit records, in one checked object, the choice-wise input-prime-strip links, constructed/certificate IPL-datum alignment, the forbidden direct SHE domain-to-codomain transport, and the permitted APT endpoint. The APT endpoint is now quotient-backed: the construction carries a `HodgeTheaterTransportQuotient`, and Lean proves that the permitted APT arrow's source and target are equal after passing to this quotient. The underlying `APTDatum` has been strengthened accordingly: a structured APT witness now stores the transport system, the quotient, the arrow, its

permission proof, and the quotient endpoint equality, not only the mechanism and output family. The SHE guard is now also represented by `DomainCodomainForbiddenTransportAudit`: it stores the forbidden domain/codomain theater pair, proves that no allowed arrow with these endpoints exists for any mechanism, and retains the underlying history-side separation. It does not prove full SHE or APT from the source papers; it removes another loose conjunction from the critical path by making the present transport laws a named typed certificate. The remaining-payload ledger now has a separate `constructed_ipl_she_apt_transport_law_audit_threaded` slot, and the strongest additive-Haar arithmetic-degree and arithmetic-divisor-backed certificates expose this same typed transport-law audit directly. The additive-Haar subledger also exposes the components of the old SHE/APT transport guard separately: the no-domain-to-codomain SHE transport law, the non-forbidden APT arrow law, and the underlying APT transport audit are now individual projections as well as part of the combined guard. The same certificate directly exposes the local-to-global arithmetic gap

$$C_{\Theta, \text{can}} + 1 \leq A - M$$

and the local formula-matching subcertificates: unscaled local different-plus-conductor bounds, formula-gap matched Theorem 1.10 arithmetic divisor evaluation, Step (xi) arithmetic-degree calibration, and the  $p$ -adic prime-error/defect split. It also carries the closed local-to-global endpoint and the Remark 3.9.5/IUT IV handoff audit as named fields, so the  $C_{\Theta, \text{can}} \leq C_{\Theta}$  proof is visible at the strongest unscaled boundary itself. At the arithmetic-divisor-backed preferred boundary, the same certificate now also carries the nested `ArithmeticDegreeCalibrationAudit` directly. Thus the local Step (xi) formula

$$S_v = a_l(D_v + C_v)$$

is visible from the preferred certificate as the consequence of the two calibration laws already stored there: determinant multiplicity equals the IUT IV arithmetic-degree coefficient, and adjusted raw log-volume equals the local different-plus-conductor degree. The new `StepXIDeterminantCalibrationAudit` records the adjacent global calibration: the Remark 3.9.5 determinant source is the weighted determinant obtained from this localized Step (xi) source, and  $C_{\Theta, \text{can}}$  is the finite sum of its weighted adjusted log-volumes. This makes the determinant handoff an explicit checked component of both the arithmetic-divisor-backed local-global audit and the preferred constructed qualitative certificate. The same preferred certificate now also exposes the  $p$ -adic prime-error side through its `primeErrorPadicDefectMainEndpoint` and `padicPrimeErrorFormulaMatchingEndpoint` fields. These record the source equality  $E_v = h_v + M_v$ , its conversion to  $E_v = \delta_v + M_v$  via the IUT IV local arithmetic-defect source, and the wrapper that recombines this with the Step (xi) arithmetic formula. Thus the preferred certificate records how the final  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison is obtained, rather than only recording that the comparison was available downstream. Its `arithmeticDivisorBackedFinitePlaceCThetaChain` field now packages this finite-place calculation as a single checked endpoint: the global terms are identified with finite local sums, the summed Step (xi)/Haar inequality and unit Haar defect give the arithmetic gap, and the *IUT IV* handoff yields both  $C_{\Theta, \text{can}} \leq C_{\Theta}$  and the signed theta bound used by Corollary 3.12. The finite-place source also exposes a `coarseAssemblyConcreteAudit`: the four coarse assembly slots of the typed local-global source are definitionally identified with the finite canonical-scale sum, the total Haar-defect lower bound, the arithmetic-upper and main-log finite-sum identities, and the placewise Step (xi)/Haar inequalities. The source-level `theorem311MultiradialFinitePlaceCThetaAudit` now joins this finite calculation to the Theorem 3.11 multiradial side: the selected  $q$ -region is an equality-quotient possible image, (Ind<sub>1</sub>) and (Ind<sub>2</sub>) preserve the procession-normalized log-volume, (Ind<sub>3</sub>) is absent from the equality quotient and remains upper-semi, and the resulting selected region feeds the finite-place  $C_{\Theta}$  chain. The equality quotient is now also backed by a

**EqualityQuotientSetoidAudit:** Lean proves that equality of the setoid quotient maps is equivalent to the generated  $(\text{Ind}_1)/(\text{Ind}_2)$  relation, while the  $(\text{Ind}_3)$  generator of this equality quotient remains empty. The top-level paper-trace **RemainingPayloadAudit** now also requires the Theorem 3.11 possible-image quotient compatibility itself. Its checked projections now expose the  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  possible-image region equalities separately from the one-sided  $(\text{Ind}_3)$  upper-semi log-volume inequality, and then derive the equality-quotient image invariant from the first two. Thus the ledger can no longer satisfy the Theorem 3.11 block while hiding the distinction between equality-generating indeterminacies and the non-equality  $(\text{Ind}_3)$  upper-semi relation inside a single compatibility payload. Its **paperTraceRemainingPayloadAudit** field instantiates the abstract **AdditiveHaarArithmeticDegreePadicObligations** record with these concrete endpoints, so the paper-trace ledger now has a checked handoff from the strongest constructed source object. The same obligation record now separates a finer local payload audit, **FineLocalPayloadAudit**. This new audit names three local witnesses which were previously visible only by inspecting the surrounding certificate: the Theorem 1.10 formula-gap local estimate audit, the Step (xi) arithmetic-degree calibration audit, and the  $p$ -adic prime-error formula matching endpoint. All current paper-trace instantiations of **AdditiveHaarArithmeticDegreePadicObligations** now supply these slots from the corresponding constructed source objects, and **RemainingPayloadAudit** itself is the conjunction of the coarse payload audit and this fine local audit. The top-level Theorem 3.11-to-Corollary 3.12 ledger therefore has checked projections to the formula-gap local estimate, arithmetic-degree calibration, and  $p$ -adic prime-error formula-matching witnesses. The same ledger now also requires the quotient-backed APT-datum endpoint itself: the additive-Haar payload audit has a separate **constructed\_apt\_datum\_quotient\_endpoint\_threaded** slot, projected from the constructed IPL/SHE/APT transport-law audit. The same strict source now has direct preferred-audit projections

```

ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDegreePadicCThetaAudit.
  oneSidedLocalGlobalEndpoint,
ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDegreePadicCThetaAudit.
  indeterminacyLocalGlobalEndpoint,
ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDegreePadicCThetaAudit.
  finitePlaceLocalGlobalCThetaDerivationAudit,
ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDivisorBackedComponentCThetaAudit.
  finitePlaceIUTIVArithmeticGapHandoffAudit,
ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDivisorBackedComponentCThetaAudit.
  equalityQuotientSetoidAudit,
ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDivisorBackedComponentCThetaAudit.
  oneSidedSelectedQHullLogVolumeAudit,
ConstructedQualitativeHodgeSHEIPLAdditiveHaarArithmeticDivisorBackedComponentCThetaAudit.
  coarseAssemblyConcreteAudit.

```

These expose, from the preferred certificate itself, both the one-sided Theorem 3.11 quotient endpoint, the exact setoid quotient audit, the selected-q hull/log-volume bridge induced by equality-quotient compatibility, the coarse typed-indeterminacy local-to-global endpoint, and the concrete finite-place meaning of the coarse assembly fields. The finite-place derivation projection packages the derivation itself: the summed Step (xi)/Haar inequality, the Haar-defect contribution of the global  $+1$ , the  $IUT\ IV\ C_\Theta + 1 = A - M$  handoff identity, the named ordered-real cancellation audit from

$$C_{\Theta, \text{can}} + 1 \leq A - M = C_\Theta + 1$$

to  $C_{\Theta, \text{can}} \leq C_{\Theta}$ , the constructed global  $C_{\Theta}$ -scale audit, and the final dichotomy. The underlying strict source also projects directly to `ConstructedTheorem311IndeterminacyLocalGlobalCThetaSource`, and its `closedLocalGlobalEndpoint`, `closedNoRawComparisonAudit`, and `localGlobalHandoffAudit` theorems expose the named closed  $C_{\Theta}$  route without passing through an older wrapper in the public audit surface. The final preferred arithmetic-divisor-backed certificate now carries the same `closedNoRawComparisonAudit` field, so the absence of raw  $\theta_{\text{signed}} \leq C_{\Theta}(-q_{\text{signed}})$  and raw  $C_{\Theta, \text{can}} \leq C_{\Theta}$  endpoint hypotheses can be checked directly at the strongest current boundary. Lean also packages this source route as

```
ConstructedTheorem311OneSidedIUTIVTheorem110
AdditiveHaarMatchedLocalDegreeArithmeticDivisorBacked
ComponentStepXIILocalTermCThetaSource.
PreferredSourceCorridorDODAAudit.
```

This audit records the arithmetic-divisor-backed endpoint, the typed Theorem 3.11 multiradial finite-place  $C_{\Theta}$  audit, the local-to-global  $C_{\Theta}$  derivation, the finite-place *IUT IV* arithmetic-gap handoff, the concrete coarse-assembly audit, the arithmetic-gap  $C_{\Theta}$  chain, the Remark 3.9.5/*IUT IV* handoff, the closed no-raw-comparison audit, the derived  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison, the derived signed  $C_{\Theta}$  bound, the source-bridge bound, and the final dichotomy. The strongest finite-divisor certificate now carries this field as `preferredSourceCorridorDODAAudit`. The compact preferred theorem is

```
boundarySignedEqualityOrStrictCTheta_from_preferred
UnscaledDegreeBoundConstructedTheorem311Indeterminacy
LocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

and the degree-identified preferred projection is

```
boundarySignedEqualityOrStrictCTheta_from_preferred
DegreeIdentifiedUnscaledConstructedTheorem311Indeterminacy
LocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

The formula-level preferred projection is

```
boundarySignedEqualityOrStrictCTheta_from_preferred
LocalDegreeFormulaConstructedTheorem311Indeterminacy
LocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

The matched formula-level preferred projection is now the lowest public local-to-global  $C_{\Theta}$  theorem in this branch:

```
boundarySignedEqualityOrStrictCTheta_from_preferred
MatchedLocalDegreeFormulaConstructedTheorem311
IndeterminacyLocalGlobalCThetaFiniteDivisorVerticalIQ
_ofRealifiedFrobenioidPacketSource.
```

It consumes the constructed qualitative Hodge/SHE/IPL source and the matched local Step (v)/Step (vii) formula-identification additive-Haar source, and it still does not expose either the raw numerical  $\Theta$ -bound or the raw  $C_{\Theta, \text{can}} \leq C_{\Theta}$  comparison as hypotheses. The same

final audit and its strongest top-level paper trace now retain the constructed APT datum audit from the qualitative boundary: the permitted transport arrow, the induced mechanism, the output family, allowedness, and non-forbiddleness are still available at the arithmetic-divisor-backed endpoint. The matched qualitative audit stores the paper-shaped arithmetic gap  $C_{\Theta, \text{can}} + 1 \leq A - M$ , the closed handoff audit, the `ArithmeticGapCThetaChainAudit`, and the strict-source `MatchedLocalDegreeFormulaAudit`, including its nested `ArithmeticDegreeCalibrationAudit`. Its audit-level  $C_{\Theta, \text{can}} \leq C_{\Theta}$  declaration is therefore a derived theorem obtained by the exposed +1 cancellation, not a field. It also now exposes the one-sided Theorem 3.11 quotient audit and the selected-q quotient endpoint directly. The quotient audit includes the typed-core action-law certificate, so the preferred matched boundary explicitly exposes  $(\text{Ind}_1)/(\text{Ind}_2)$  log-volume preservation,  $(\text{Ind}_3)$  upper-semi one-sidedness, and exclusion of  $(\text{Ind}_3)$  from the equality quotient. The q-pilot region is identified with a selected Theorem 3.11 possible image, that image is read through the  $(\text{Ind}_1)/(\text{Ind}_2)$  equality quotient, and the pullback of the quotient-indexed possible-image family is the original theta-pilot family. The same concrete quotient source now feeds the finite-place local-to-global  $C_{\Theta}$  handoff by

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedFinitePlaceLocalGlobalCThetaSource
```

and, more sharply, through the localized Step (xi) constructor

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedStepXILocalTermCThetaSource.
```

The normalized-Haar refinement

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedNormalizedHaarStepXILocalTermCThetaSource
```

and its p-adic unit-ball version

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedPadicUnitBallHaarStepXILocalTermCThetaSource
```

now sit above the IUT IV arithmetic-defect version

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedIUTIVArithmeticDefectStepXILocalTermCThetaSource.
```

That defect version is now itself the projection of the arithmetic-divisor evaluation version

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedIUTIVArithmeticDivisorEvaluationStepXILocalTerm
CThetaSource.
```

These constructors build the Remark 3.9.5 hull/determinant source internally from the selected quotient q-region. The Step (xi) refinement removes another free local input: the canonical local summands are the weighted adjusted log-volumes of the localized vector-bundle determinant source, and the local upper contribution is the Step (xi) term plus the Haar defect and main-log term. The normalized-Haar source derives the global Haar +1 from a finite-place lower-bound source: placewise nonnegativity plus a distinguished normalized valuation-ball place. The p-adic unit-ball source replaces that abstract lower-bound source by the local unit-ball Haar normalization and

dilation character; the local defect is the index  $p_v^{[K_v:\mathbb{Q}_p]}$ . The new arithmetic-defect source then rewrites the local arithmetic upper sum in terms of the IUT IV defect  $\delta_v^{\text{IUT}}$  itself, together with the placewise equality

$$\delta_v^{\text{IUT}} = \text{the } p_v^{[K_v:\mathbb{Q}_p]} \text{ unit-ball Haar index.}$$

The arithmetic-divisor evaluation source goes one step lower: it supplies the finite sums for the global arithmetic upper term and the global main-log term from local divisor-evaluation data, leaving only the pointwise identity

$$A_v = S_v^{\text{Step (xi)}} + \delta_v^{\text{IUT}} + M_v$$

as the local Step (xi)/IUT IV handoff. Its endpoint exposes the quotient q-region facts, the arithmetic-divisor evaluation endpoint, the IUT IV defect projection, the induced total defect lower bound, localized determinant identities, the finite-place  $C_\Theta$  derivation, the signed bound, and the final Corollary 3.12 dichotomy. The concrete route now also reaches the Theorem 1.10 arithmetic-divisor source

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedIUTIVTheorem110ArithmeticDivisorStepXIILocalTerm
CThetaSource.
```

This replaces the generic divisor-evaluation source by typed different, q-parameter, and conductor divisors together with the Step (v)–(vii) local estimate gate. The endpoint records the different and conductor degree sums, the prime-error and main-log sums, the local procession-gap inequality, the nondistinguished zero branch, and the conductor/q-support equality before projecting to the existing  $C_\Theta$  and Corollary 3.12 endpoint. The concrete route has now been lowered one step further to the local case-formula layer

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedIUTIVTheorem110FormulaArithmeticDivisorStepXIILocalTerm
CThetaSource.
```

Here the local procession upper bound is not a free gate: it is the case-defined bound coming from the distinguished nonarchimedean Step (v), the nondistinguished Step (vi) zero branch, and the archimedean Step (vii) formula. The endpoint exposes these three local inequalities, the induced casewise procession-gap bound, and the same quotient q-region and finite-place  $C_\Theta$  handoff. The same concrete route now also reaches the Proposition 1.4/1.5-backed source

```
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
OneSidedIUTIVTheorem110PropositionArithmeticDivisorStepXIILocalTerm
CThetaSource.
```

It now also has lower local-analytic, additive-Haar, valuation-ball additive-Haar, and valuation-ball

formula-gap matched versions

```

concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
  OneSidedIUTIVTheorem110LocalAnalyticArithmeticDivisorStep
  XI LocalTermCThetaSource,
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
  OneSidedIUTIVTheorem110AdditiveHaarLocalAnalyticArithmeticDivisor
  StepXI LocalTermCThetaSource,
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
  OneSidedIUTIVTheorem110ValuationBallAdditiveHaarLocalAnalytic
  ArithmeticDivisor
  StepXI LocalTermCThetaSource,
concreteHodgeTheaterLogThetaQuotientThetaPilotSource_to
  OneSidedIUTIVTheorem110ValuationBallHaarFormulaGapMatched
  ArithmeticDegreePadicFormulaMatched
  StepXI LocalTermCThetaSource.

```

The endpoint exposes the local analytic construction witnesses themselves: the distinguished and nondistinguished Proposition 1.4 log-shell construction sources and the Proposition 1.5 archimedean metric construction source. The additive-Haar endpoint further exposes the compact-open Haar normalization endpoints underlying the finite Proposition 1.4 branches. The valuation-ball endpoint keeps this finite-place provenance visible: the distinguished and nondistinguished additive-Haar log-shell branches are required to arise from valuation-ball Haar normalization audits before the source forgets to the additive-Haar route. The formula-gap matched endpoint goes one level lower: it consumes named distinguished and archimedean formula-to-gap comparison objects, the  $p$ -adic prime-error/defect/main split, and the Step (xi) arithmetic-degree calibration before projecting to the closed local-to-global  $C_\Theta$  handoff. After projection, these routes recover the proposition, formula, finite local-to-global  $C_\Theta$ , and Corollary 3.12 outputs. Thus the concrete Hodge/log-theta route no longer stops at a proposition-level estimate package, nor at an abstract additive-Haar normalization. The remaining payload at this boundary is the construction of the valuation-ball formula-gap comparison and Step (xi) arithmetic-degree calibration objects from paper-native local fields, log-shells, and divisor terms, not a raw global  $C_{\Theta, \text{can}} \leq C_\Theta$  hypothesis or a raw total Haar-defect inequality. The preferred certificate now also carries the IUT IV local formula audit

```

IUTStage1IUTIVTheorem110AdditiveHaarFormulaGapMatched
ArithmeticDivisorEvaluationSource.FormulaGapLocalEstimateAudit.

```

This audit proves, place by place, that the distinguished Proposition 1.4 log-shell container bound and the archimedean Proposition 1.5 metric container bound lie below the local arithmetic-upper-minus-main-log gap used by the Theorem 1.10 summation. The strongest arithmetic-divisor-backed certificate exposes this as `formulaGapLocalEstimateAudit`. It now also exposes the nested coefficient-window synchronization audit from the matched local-degree formula source, so the displayed coefficient lower bound and its identification with the local arithmetic-degree coefficient are visible at the same public certificate. Thus the remaining payload has moved below these container-to-gap and coefficient-window checks: it is concentrated in constructing the local formula comparison sources themselves, including the paper-native coefficient-window lower-bound source and the calibration equalities that identify the local arithmetic-degree term with IUT IV data.

The Theorem 3.11 qualitative checkpoint is now also present at the finite-divisor  $C_\Theta$  boundary. The new checkpoint-aware side-conditioned Hodge/SHE/IPL declaration requires

`ConstructedQualitativeTheorem311ToCorollary312Checkpoints` and reports the constructed public audit, typed no-SHE-domain-to-codomain transport guard, APT non-forbidden transport guard, and Hodge-history separation next to the finite-divisor dichotomy. Its Lean name has suffix `withConstructedQualitativeCheckpoints`. This does not remove the downstream local-to-global  $C_\Theta$  comparison; it closes the previous gap between the constructed qualitative Theorem 3.11 route and the finite Step (x) vertical  $IQ$  surface.

At this same boundary, the certificate-pinned IPL link has now been replaced by the constructed input-prime-strip link source. The construction version of the side-conditioned record-hull endpoint consumes `IUTStage1Theorem311IPLLinkConstructionSource`, exposes the choice-wise links from the fixed input prime strip to each possible output prime strip, and only then projects to the certificate-facing link source used by the older route. The same replacement is available at the checkpoint-aware boundary, so the constructed qualitative audit can be read next to the constructed input-prime-strip link audit. The history-separated Hodge–Arakelov record-hull boundary now has the same constructed-IPL core theorem

```
boundarySignedEqualityOrStrictCTheta_from_sourceDerived
HodgeArakelovHistorySeparatedT11IPLConstructionRecordHull
FiniteDivisorVerticalIQ.
```

The experiment module exposes this as the review companion

```
historySeparatedIPLConstructionRecordHullFiniteDivisor
VerticalIQ_cThetaDichotomy.
```

Both forms expose the choice-wise links, the constructed/certificate IPL equalities, and then project to the older certificate-facing route. This closes the IPL-construction gap for the current side-conditioned and history-separated record-hull finite-divisor surfaces; any remaining certificate-pinned declarations are retained only as review aliases until they are migrated or retired.

The generated full-label quotient route now has a typed package handoff to the finite-divisor vertical- $IQ$  layer. The new handoff record

```
GeneratedFullLabelFiniteDivisorVerticalIQPackageHandoff
```

does not identify these packages by convention: it requires equality of the signed  $q/\theta$  pre-ledger data and requires both the finite-divisor record- $\theta$  possible image and the finite-divisor target region for the chosen packet to be exactly the generated selected  $q$ -region. Given these source-side realization fields, the theorem

```
generatedFullLabelFiniteDivisorVerticalIQPackageHandoff_cThetaDichotomy
```

transports the generated full-label  $C_\Theta$  dichotomy to the finite-divisor package, with the conclusion stated in finite-divisor pre-ledger variables. Thus the package-identification step has been made a kernel-checked boundary; what remains is to construct its equality witnesses from the paper-native local log-Kummer/Frobenioid data.

This boundary was first sharpened by removing a redundant finite target-region witness: Lean proves

```
recordThetaPossibleImage_eq_targetRegion_toSet
```

from the definition of a Theorem 3.11 source record. The smaller source object

```
GeneratedFullLabelFiniteDivisorVerticalIQRecordImageRealization
```



therefore asks only for equality of the signed  $q/\theta$  pre-ledger quantities and for equality between the finite selected record image and the generated selected record image. Its projection

`GeneratedFullLabelFiniteDivisorVerticalIQRecordImageRealization.toHandoff`

constructs the full package handoff, and

`generatedFullLabelFiniteDivisorVerticalIQRecordImageRealization_cThetaDichotomy`

derives the finite-divisor dichotomy from this smaller realization source. The current boundary sharpens the image witness again. The generated quotient source now exposes

`generatedFullLabelSelectedRecordThetaPossibleImage_eq_thetaClassRegion_toSet,`

which identifies its selected record image with the theta-pilot-class region obtained from the selected generated full-label choice. Thus the finite packet source can be stated as

`GeneratedFullLabelFiniteDivisorVerticalIQThetaClassRecordImageRealization.`

It requires the finite selected Theorem 3.11 record image to realize this theta-class region directly, plus equality of the signed  $q/\theta$  pre-ledger quantities. Its projection to the record-image realization and the endpoint

`generatedFullLabelFiniteDivisorVerticalIQ  
ThetaClassRecordImageRealization_cThetaDichotomy`

are now fed by

`GeneratedFullLabelFiniteDivisorVerticalIQStepXILogVolumeRealization.`

This new source records the Step (xi-d)–(xi-f) comparison: the  $q$ -pilot log-volume is read as a  $q$ -region log-volume on both the finite and generated sides, while the theta-pilot bound is read as the corresponding theta-hull log-volume. Lean proves the old signed  $q/\theta$  package equalities from these four log-volume identifications and then invokes the theta-class realization endpoint, which derives the generated-record match, the package handoff, and the finite-divisor  $C_\Theta$  dichotomy. The finite-packet boundary has now been lowered once more. The earlier source

`GeneratedFullLabelFiniteDivisorVerticalIQThetaClassPacketProjection`

is retained as a projection layer. The constructed packet source

`GeneratedFullLabelFiniteDivisorVerticalIQConstructedThetaClassPacketSource.`

constructs the finite theta-pilot class from the nonarchimedean packet coordinates, the upper-semi log-theta column, the coric datum, and explicit Hodge-theater/history labels. Its componentwise theorem

`constructedThetaClass_eq_generatedSelected`

then identifies this constructed class with the selected generated full-label theta class. This boundary has now been lowered again: the preferred source is

`GeneratedFullLabelFiniteDivisorVerticalIQ  
RecordBackedConstructedThetaClassPacketSource.`

It states realization at the finite Theorem 3.11 record-image level. The finite package target-region equality is derived from the record law

`recordThetaPossibleImage_eq_targetRegion_toSet,`

so the handoff no longer asks for that target-region equality directly. The projection

`toConstructedThetaClassPacketSource`

derives the constructed packet source, and

`generatedFullLabelFiniteDivisorVerticalIQ`  
`RecordBackedConstructedThetaClassPacketSource_cThetaDichotomy`

returns the constructed-class equality, the finite record-image realization, the derived target-region realization, the selected-region identifications, and the finite-divisor  $C_\Theta$  dichotomy. The next source boundary is no longer selected-only. The finite image-law source

`GeneratedFullLabelFiniteDivisorVerticalIQ`  
`FiniteThetaClassImageLawSource`

states one finite Theorem 3.11 theta-class image law for all nonarchimedean finite packets. Lean specializes this law at the selected packet, constructs the record-backed packet source, and the endpoint

`generatedFullLabelFiniteDivisorVerticalIQ`  
`FiniteThetaClassImageLawSource_cThetaDichotomy`

derives the same selected-region and  $C_\Theta$  conclusions. Thus the remaining record-image payload has moved from a selected equality to a finite packet image law. This law is now itself derived from

`GeneratedFullLabelFiniteDivisorVerticalIQ`  
`FiniteThetaClassRepresentativeImageLawSource.`

The representative source supplies finite packets, proves finite record-image invariance under equality of the reconstructed theta class, and identifies representative record images with the class-indexed Theorem 3.11 possible-image regions. This has now been lowered to the fiber/component source

`GeneratedFullLabelFiniteDivisorVerticalIQ`  
`FiniteThetaClassFiberComponentImageLawSource.`

The fiber is determined by the fixed finite Hodge-theater/history labels. On that fiber Lean constructs representative finite packets from the procession state, local direct-summand packet state, upper-semi state, and place-family compatibility witness; the universal finite image law follows by applying this fiber representative to the theta class reconstructed from an arbitrary finite packet. The component source is now itself obtained from

`GeneratedFullLabelFiniteDivisorVerticalIQ`  
`FiniteThetaClassFiberAuditedPacketImageLawSource,`

which supplies one place-audited nonarchimedean direct-summand packet on each fiber theta class. Lean extracts the procession, local packet, upper-semi, and place-family data from that audited

packet, derives the log-theta column compatibility from the reconstructed theta-class equality, and uses same-theta-class record-image invariance to pass from the rebuilt component packet back to the audited packet. The invariance input has now been factored once more by

**GeneratedFullLabelFiniteDivisorVerticalIQ**  
**FiniteThetaClassFiberQuotientAuditedPacketImageLawSource.**

This source aligns the finite possible-image family with the place-audited Theorem 3.11 multiradial possible images and replaces the raw same-theta-class record-image equality by the quotient statement that two finite packets with the same reconstructed theta class are related in the place-audited multiradial quotient. Lean derives record-image equality from quotient invariance. This has now been sharpened to the source

**GeneratedFullLabelFiniteDivisorVerticalIQ**  
**FiniteThetaClassFiberInd12AuditedPacketImageLawSource.**

Here the same-theta-class relation is no longer an ambient quotient input: it is a relation generated only by finite (Ind1) procession transports and (Ind2) local direct-summand actions. Lean embeds this (Ind1, Ind2)-relation into the existing place-audited quotient and explicitly discharges the impossible (Ind3) equality-generator case. This has now been sharpened once more at the component boundary. The preferred fiber route records same-theta finite packets through raw nonarchimedean Ism tensor labels: a same-theta midpoint packet, an ordered (Ind1) procession leg, the source-level nonarchimedean-IsM action leg, source and target tensor-label equations, and the target summand-kind certificate. Lean constructs the local label transport, the matched local (Ind2) packet-action source, the older identified handoff, local transport audit, generated (Ind1, Ind2) relation, quotient relation, record-image equality, selected q-region equalities, and finally the Corollary 3.12 dichotomy. Thus the remaining payload is narrower: construct these raw tensor-label witnesses and the Step (xi) q-region/theta-hull log-volume identifications from the paper-native vertical log-Kummer/Frobenioid geometry.

The concrete Hodge-theater/log-theta route is now connected to this matched finite Step (x) handoff by an explicit bridge

**ConcreteHodgeTheaterLogThetaGeneratedFullLabel**  
**FiniteDivisorVerticalIQMatchedStepXBridge.**

The bridge records exactly the cross-package identifications needed at this boundary: equality of the concrete and generated selected q-regions, equality of the concrete and finite signed q-values, and equality of the concrete and finite signed theta-values. The endpoint

**concreteHodgeTheaterLogThetaGeneratedFullLabel**  
**FiniteDivisorVerticalIQMatchedStepXBridge\_cThetaDichotomy**

runs the generated/finite matched Step (x) theorem and transports the resulting finite  $C_\Theta$  dichotomy back to the concrete Hodge-theater/log-theta package. This bridge has now been lowered by

**ConcreteHodgeTheaterLogThetaGeneratedFullLabel**  
**StepXIILogVolumeComparisonSource.**

The new source no longer asks for concrete/finite signed equalities. It records equality of the concrete and generated selected q-regions and derives the concrete/generated signed q/theta equalities from

common Step (xi) q-region and theta-hull log-volume readings. Lean then composes this with the matched generated/finite Step (x) gluing to construct the older bridge internally, and the endpoint

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
StepXIILogVolumeComparisonSource_cThetaDichotomy`

reaches the same concrete  $C_\Theta$  dichotomy. This has now been lowered one step further. A concrete upper-ray source,

`ConcreteHodgeTheaterLogThetaConstructedStepXUpperRaySource,`

is the concrete analogue of the generated full-label upper-ray source: both read the q-pilot and theta-hull values from constructed Remark 3.9.5 hull/determinant data and a procession-normalized Step (x) corridor. The new comparison source

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
ConstructedStepXIComparisonSource`

then promotes equality of the concrete and generated Step (xi) q-regions, q-pilot readings, and theta-hull readings to the earlier log-volume comparison source. This has now been lowered again by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
UpperRayCalibrationSource.`

The calibrated source no longer supplies equality of the Step (x)-to-hull upper-ray coordinates directly. The q equality is obtained from equality of the hull-approximant q-pilot log-volume readings, while the theta equality is obtained from equality of the normalized weighted-determinant log-volumes. Lean proves the promotion to the constructed Step (xi) comparison source and then runs the same concrete  $C_\Theta$  endpoint. This boundary has now been lowered once more by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
FiniteSummandUpperRayCalibrationSource.`

There the q equality is derived from the selected q-region equality and the Remark 3.9.5 hull-operator equality. The theta equality is derived from a finite equivalence between the concrete and generated determinant index sets, matching adjusted localization summands, and the existing theorem that normalization of the positive tensor power recovers the determinant sum. Thus the determinant side no longer compares normalized real fields directly. This boundary has now been lowered again by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
Ob3Ob4LocalizationUpperRayCalibrationSource.`

Here the finite adjusted-summand matching is itself derived from Remark 3.9.5 Ob3/Ob4 adjusted-localization sources: Lean rewrites the constructed determinants to their weighted determinant projections and proves the summand comparison from equality of the weighted adjusted localization log-volumes after the determinant-index equivalence. A further localized vector-bundle boundary,

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
LocalizedVectorBundleUpperRayCalibrationSource,`

now derives that weighted adjusted equality from the finite direct-summand log-volume comparison, the structure-sheaf term, and the determinant multiplicity. The same boundary has now been lowered once more by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel`  
`LocalizedHullCoverUpperRayCalibrationSource.`

This source projects the localized vector-bundle determinant packages from Remark 3.9.5 localized hull-cover data and derives the common hull operator from a common holomorphic hull system. The selected q-region comparison has also been factored by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel`  
`SelectedThetaClassQRegionCalibration.`

Instead of asserting equality of the two selected q-regions directly, Lean now derives it from a common theta-pilot-class image family and equality of the selected concrete/generated theta-pilot classes. This boundary has now been lowered by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel`  
`SelectedThetaClassQRegionSource.`

The new source constructs the concrete quotient theta-pilot source from the concrete class-region formula `ConcreteHodgeTheaterLogThetaThetaPilotClassRegionSource`, identifies that class-region formula with the generated full-label theta-class image family, and then projects to the older selected-q calibration. Thus the selected q-region equality is no longer a bare input. The same boundary has now been lowered again by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel`  
`RepresentativeSelectedThetaClassQRegionSource.`

This source chooses the concrete selected q-choice as the representative of the generated selected theta-pilot class under the concrete representative section. Lean therefore derives the selected theta-pilot class match from the representative-section theorem; the remaining cross-side input at this boundary is the common class-region comparison. That comparison has now been lowered by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel`  
`FormulaRepresentativeSelectedThetaClassQRegionSource.`

The formula-backed source starts from the concrete record-level `ConcreteHodgeTheaterLogThetaThetaPilotClassFormulaRecordSource` and identifies the generated full-label theta-class image family with the same theta-pilot class formula. The pointwise concrete/generated class-region agreement is then derived internally before projecting to the representative-selected q-region calibration. This has now been lowered to the lattice level by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel`  
`LatticeFormulaRepresentativeSelectedThetaClassQRegionSource.`

The lattice-backed source uses the concrete lattice-formula record source; the common class formula is obtained from Hodge-theater id, history label, the finite-label-forgotten log-theta lattice coordinate, and the coric datum. This has been lowered once more by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel`  
`LatticeImageLawRepresentativeSelectedThetaClassQRegionSource.`

Here Lean constructs the lattice formula from representative concrete choices; the concrete source-paper input is the invariance of possible-image regions under equality of the Hodge-theater/history/lattice/coric key. The generated side has also been tightened by

ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
LatticeImageLawGeneratedQuotientRepresentative  
SelectedThetaClassQRegionSource.

This source constructs the generated full-label quotient with its theta-class image family already fixed to the concrete lattice-image-law formula, so the previous cross-side image-family equality is definitional. The generated record-image law has then been lowered by

ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
LatticeImageLawPointwiseGeneratedPullback  
RepresentativeSelectedThetaClassQRegionSource.

It assumes only the pointwise generated pullback: each generated full-label possible-image region is the common lattice-image-law region attached to its theta-pilot class. Lean derives the family-level generated quotient image equality from this pointwise law. The concrete side of this boundary has now also been lowered to the source-level fiber transport layer by

ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
FiberInd2ActionPacketTransportPointwiseGeneratedPullback  
RepresentativeSelectedThetaClassQRegionSource.

This source starts from the retained post-procession (Ind2) action-packet transport object for theta-pilot fibers, forgets it through the typed transport chain to the lattice-image-law family, and then applies the pointwise generated-pullback calibration above. Its audit keeps the source-level packet transport endpoint, the lower procession/upper-semi transport payload, the derived fiber-transport image law, and the generated pullback law visible. It now also retains **FiberTransportQuotientComparisonAudit**, so the public q-region handoff records the source-level packet audit, typed (Ind<sub>1</sub>, Ind<sub>2</sub>) equality-quotient preservation, possible-image region invariance, induced lattice-image law, and no-(Ind<sub>3</sub>)-equality guard in one named object. The same source now also projects the selected  $F_\ell$ -procession orbit through the generated quotient Remark 3.9.5 hull endpoint: at the lattice-image-law, pointwise generated-pullback, and fiber-(Ind2) packet-transport boundaries, Lean proves that every generated full-label translate of the selected  $q$ -choice has the same possible region, hull log-volume, and selected  $q$ -region. The generated side has now been lowered one step further by

ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
FiberInd2ActionPacketTransportKernelImagePullback  
RepresentativeSelectedThetaClassQRegionSource.

This source identifies the generated record image family with the full-label kernel image family before comparing that family with the concrete fiber-lattice image law; the same selected-orbit Remark 3.9.5 endpoint is available at this kernel-image boundary. Thus the no-omission finite-label statement survives the concrete/source handoff, not only the abstract generated quotient. This

boundary has been sharpened again by

ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
 FiberInd2ActionPacketTransportCommonKernelImagePullback  
 RepresentativeSelectedThetaClassQRegionSource.

Here the generated theta-class image family is definitionally the concrete fiber-lattice image law. Hence the theta-class match is no longer a separate input at this boundary: Lean derives the previous kernel and pointwise generated pullbacks from the common image family and reuses the existing q-region calibration. This has now been lowered once more by the target-region variant

ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
 FiberInd2ActionPacketTransportTargetRegion  
 CommonKernelImagePullbackRepresentativeSelectedThetaClassQRegionSource.

Instead of assuming the generated Theorem 3.11 record-image family directly, this source identifies the generated package target region of each full-label choice with the full-label pullback of the common concrete fiber-lattice image family. Lean then reconstructs the record-image equality from the record's target-region realization theorem. The generated side has now been lowered in two further steps. First, the representative target-region source proves that target regions are invariant under equality of the forgotten theta-pilot class and calibrates only the generated representative of each theta class against the common concrete fiber-lattice image law; Lean then derives the all-choice target-region law. Second, the quotient target-region source replaces this same-theta-class invariance field by factorization of the generated package target-region family through the generated  $(\text{Ind}_1, \text{Ind}_2)$  equality quotient. Since equality of theta-pilot classes is a generated  $(\text{Ind}_2)$  equality step, Lean derives same-theta-class target-region invariance from the quotient possible-image interface. The quotient factorization has now also been constructed from the all-choice target-region pullback law itself: Lean builds the generated target-region **EqualityQuotientPossibleImages** object by proving  $(\text{Ind}_1)$  and  $(\text{Ind}_2)$  target-region invariance from the concrete theta-class fiber-lattice image law, while keeping  $(\text{Ind}_3)$  as the generated upper-semi log-volume relation. Thus the remaining q-region obligation is no longer an arbitrary full-label equality, a primitive same-theta-class invariance assumption, or an independently supplied quotient image object, but the construction of the generated target-region pullback law and representative calibration from local log-Kummer/Frobenioid geometry. The target-region pullback itself has now been rederived from the pointwise generated record-region pullback: Lean combines the record image/fiber-lattice equality with the source record's target-region realization theorem, and then reuses the constructed target-region quotient. Consequently the remaining generated-side payload is pushed below package target regions. This has been split again by the generated-corridor-backed source: the public generated full-label quotient corridor supplies the record-image equality, and Lean derives the common-kernel record pullback from the single comparison between generated theta-class regions and the concrete fiber-lattice image law. The remaining mathematical payload is therefore the construction of that theta-class region comparison and its representative calibration from the local log-Kummer and Frobenioid data. The fiber-transport pointwise source now also promotes directly through this generated-corridor boundary: its lattice-image-law quotient source supplies the generated corridor, so the later common-kernel and target-region quotient route no longer restates the generated-side record equality. The theta-class comparison itself has now been lowered to the same lattice-image-law quotient source in the fiber-transport case: when the generated quotient is instantiated with the fiber-transport lattice image law, the generated-corridor theta-class image family is definitionally the concrete fiber-lattice image law.

This q-region source is now threaded into the valuation-ball localized hull-cover boundary by

`ConcreteHodgeTheaterLogThetaGeneratedFullLabel  
FiberInd2ActionPacketTransportValuationBallFactored  
LocalizedHullCoverUpperRayCalibrationSource.`

Thus the localized hull-cover upper-ray route can consume the packet-transport q-region source and the valuation-ball/Haar component source together, before projecting to the existing Remark 3.9.5 calibration. The localized Ob3/Ob4 comparison has also been factored by

`IUTStage1Remark395LocalizedVectorBundle  
ComponentTransportCalibration.`

This common-component transport carries the shared tensor power, determinant weights,  $O(-)$  log-volumes, and direct-summand log-volumes after the determinant and local-place reindexings; Lean derives the bundle, adjusted raw, and weighted adjusted log-volume equalities from these fields. The direct-summand part has now been lowered by

`IUTStage1Remark395ValuationBallLocalized  
VectorBundleComponentTransportSource.`

This source starts from concrete and generated valuation-ball factor-calibrated Haar tensor-packet covers. It identifies tensor powers, determinant weights, structure-sheaf log-volumes, and a common normalized Haar log-volume family for the matched valuation balls; the direct-summand equality is then derived from the valuation-ball factor calibration rather than supplied as a bare real equality. The preferred boundary is now one step sharper:

`IUTStage1Remark395MatchedValuationBall  
LocalizedVectorBundleComponentTransportSource.`

Here the common normalized-Haar family is not supplied. The source states equality of each concrete normalized Haar log-volume with the generated normalized Haar log-volume obtained by determinant and local-place reindexing; Lean chooses the concrete value as the common value and constructs the older valuation-ball component transport source internally. This has been lowered again by

`IUTStage1Remark395LocalNormalizationMatched  
ValuationBallLocalizedVectorBundleComponent  
TransportSource.`

This component source records common transported local invariants for each matched valuation-ball factor: the finite-extension degree and the compact-open Haar mass of the selected local ball. Lean derives the raw concrete/generated finite-degree and Haar-mass equalities from those common local-normalization invariants. Its projection is

`IUTStage1Remark395RawHaarDegreeMatched  
ValuationBallLocalizedVectorBundleComponentTransportSource.`

At the raw boundary the matched normalized-Haar equality is derived from equality of the matched compact-open Haar masses and equality of the corresponding finite-extension degrees. This local-



normalization boundary is now threaded into the packet-transport localized hull-cover corridor by

```
ConcreteHodgeTheaterLogThetaGeneratedFullLabel
FiberInd2ActionPacketTransportLocalNormalization
MatchedValuationBallFactoredLocalized
HullCoverUpperRayCalibrationSource.
```

The raw Haar/degree packet boundary

```
ConcreteHodgeTheaterLogThetaGeneratedFullLabel
FiberInd2ActionPacketTransportRawHaarDegree
MatchedValuationBallFactoredLocalized
HullCoverUpperRayCalibrationSource
```

is now an intermediate projection from this sharper packet source. The intermediate matched-normalized-Haar packet boundary

```
ConcreteHodgeTheaterLogThetaGeneratedFullLabel
FiberInd2ActionPacketTransportMatchedValuationBall
FactoredLocalizedHullCoverUpperRayCalibrationSource.
```

is in turn only a projection from the raw packet source. The local-normalization packet source combines the (Ind2)-backed q-region packet transport with transported local finite-extension degree and compact-open Haar mass data, derives the raw Haar/degree equalities and the normalized-Haar equality internally, and then projects to the older packet-transport valuation-ball boundary. The theorem

```
concreteHodgeTheaterLogThetaGeneratedFullLabel
FiberInd2ActionPacketTransportLocalNormalization
MatchedValuationBallFactoredLocalized
HullCoverUpperRayCalibrationSource_
cThetaDichotomy
```

now runs this source directly to the existing finite-divisor  $C_\Theta$  dichotomy while retaining an audit of the local-normalization, raw Haar mass, finite-degree matching obligations, and the concrete **FiberTransportQuotientComparisonAudit** inherited from the q-region source. Thus the sharpest packet-level  $C_\Theta$  endpoint still records the source-level packet audit, (Ind<sub>1</sub>, Ind<sub>2</sub>) quotient preservation, the kernel-image generated possible-image law, and the local finite-degree/Haar-mass normalization. In particular, the lowered endpoint

```
concreteHodgeTheaterLogThetaGeneratedFullLabel
FiberInd2ActionPacketTransportKernelImagePullback
LocalNormalizationMatchedValuationBallFactored
LocalizedHullCoverUpperRayCalibrationSource_
cThetaDichotomy
```

passes from the generated full-label kernel-image q-region source to the local-normalization valuation-ball source before invoking the finite-divisor  $C_\Theta$  corridor. The q-region side has now

been lowered once more by

```

concreteHodgeTheaterLogThetaGeneratedFullLabel
FiberInd2ActionPacketTransportGeneratedCorridor
KernelImagePullbackLocalNormalization
MatchedValuationBallFactoredLocalized
HullCoverUpperRayCalibrationSource_
cThetaDichotomy.

```

This endpoint consumes the generated-corridor-backed q-region source directly, derives the pointwise q-region route internally, and retains both the generated-corridor audit and the target-region quotient audit at the local-normalization valuation-ball  $C_\Theta$  boundary. Two further lowered endpoints now remove the generated-corridor source from the public boundary:

```

concreteHodgeTheaterLogThetaGeneratedFullLabel
LatticeImageLawGeneratedQuotientLocalNormalization
MatchedValuationBallFactoredLocalized
HullCoverUpperRayCalibrationSource_
cThetaDichotomy.

```

At this boundary Lean derives the generated-corridor q-region source from the lattice-image-law generated quotient attached to the concrete fiber transport. This has now been lowered further. The current lowest packet-level  $C_\Theta$  boundary is

```

concreteHodgeTheaterLogThetaGeneratedFullLabel
FiberInd2ActionPacketTransportPointwiseGeneratedPullback
DirectLocalNormalization
ValuationBallFactoredLocalized
HullCoverUpperRayCalibrationSource_
cThetaDichotomy.

```

The public q-region payload is now the pointwise Theorem 3.11 record-image pullback to the concrete fiber-lattice theta-class image law. The generated target-region pullback is derived from this law using the record realization of possible images as comparison target regions. Lean then proves the (Ind1, Ind2)-quotient compatibility of the target-region family, constructs the equality-quotient possible images, and derives the representative target-region, common-kernel, kernel-image, generated-record, q-region, and generated-corridor handoffs internally. The endpoint still takes the Remark 3.9.5 local-normalization valuation-ball/Haar hull-cover source directly. The remaining source-facing obligation is correspondingly sharper: construct the pointwise record-image pullback law and the direct local-normalization hull-cover source from the same local log-Kummer/Frobenioid geometry. The older factored localized hull-cover source

```

ConcreteHodgeTheaterLogThetaGeneratedFullLabel
FactoredLocalizedHullCoverUpperRayCalibrationSource.

```

is now an intermediate projection from the valuation-ball factored boundary

```

ConcreteHodgeTheaterLogThetaGeneratedFullLabel
ValuationBallFactoredLocalizedHullCoverUpperRayCalibrationSource.

```

This earlier valuation-ball boundary remains an intermediate interface: it retains the concrete/generated upper-ray objects, the theta-class q-region calibration, the common hull system, and the hull/determinant identifications, but obtains both localized hull-cover sources and their component transport from matched valuation-ball Haar covers.

The practical priority order is now:

1. Construct the source-side witnesses for the generated-full-label to finite-divisor vertical-*IQ* handoff. The handoff record, record-image, theta-class, finite-packet projection, and constructed finite-packet theta-class sources are now implemented. The target-region realization is derived from the finite Theorem 3.11 record image, and the selected record-image witness is derived from an (Ind1, Ind2)-backed fiberwise audited-packet representative finite theta-class image law. The signed package transfer is no longer a bare equality field at the review boundary: it is derived from constructed Step (xi) upper-ray q-region, q-pilot, and theta-hull comparisons; on the concrete/generated side, those q/theta comparisons have now been factored through q-region plus hull-operator calibration and finite adjusted determinant summand matching. What remains is to construct the audited packet representatives, the same-theta-class midpoint packet, the ordered (Ind1) procession leg, the source-level nonarchimedean Ism action leg, the raw tensor-label equations, the target summand-kind certificate, and the remaining q-region, hull-operator, and adjusted determinant-summand matching witnesses from paper-native finite divisors, local objects, and log-volume comparison data.
2. Construct the finite divisor-component columns-local object, prime multiplicities, prime degrees, and unit log-volume—and construct the labelled vertical object-transport records from the paper-native vertical log-Kummer correspondences. The current Lean boundary constructs the Frobenioid degree object from these components, derives the finite degree-sum law definitionally, derives the labelled compatibility equality from the object transports, constructs the ordinary realified divisor column, then constructs the normalized theta and log-shell Example 3.5 copies, derives log-shell normalization and divisor realization, proves raw vertical translation, and upgrades object transport to full labelled local-object identity.
3. Construct the component functions below the theta-pilot representative section from the same log-Kummer/log-link geometry. The current Lean boundary builds the representative section from class-wise finite labels, procession states, local tensor states, and upper-semi non-volume data, then inserts the Frobenioid base-volume compatibility datum and derives the old calibration equalities, the one-sided (Ind3) base-volume inequality, the ordinary-copy comparison, finite local log-shell objects, base finite-log-volume equalities, column log-link transport family, and the transported  $ZMod(\ell)$ , capsule, classified, and direct bridges. The newest kernel separates this from the ambient choice-space assumption by generating the canonical theta-pilot choices themselves. It has now been strengthened to generate the entire finite  $F_\ell$ -label procession over each theta-pilot class, with the  $Z/\ell Z$ -action closed internally, projected to the ambient `flProcessionTranslate`, and routed through Step (xi), Remark 3.9.5, and the current global  $C_\Theta$  audit. The remaining source-construction work is to derive the component functions from the paper-native local geometry.
4. Migrate or retire older certificate-pinned IPL review aliases that are no longer preferred source surfaces.
5. Extend the recovered finite-divisor packet-local source from the preferred constructed-IPL record-hull boundary to any remaining older vertical-*IQ* review aliases, and construct the

deeper log-Kummer/Frobenioid packet calibrations of IUT III, Step (x), rather than accepting them as source-facing packet-boundary fields.

6. Construct the remaining Step (xi) holomorphic-hull/determinant fields from Remark 3.9.5 and Step (xi): genuine hulls, determinant lines, Ob5/Ob7 compatibility, and the  $\theta_{\text{signed}}$  log-volume identification. The preferred principal local boundary now defines the local log-shell as the selected compact-open factor and has a realized-exact boundary  $P_{\Theta,\beta} = \text{real}_\beta(U_\beta)$  from which Lean derives compact-open coordinates, image containments, realized valuation-ball equality, the exact  $\Xi(P_B)$  source, and the source-derived global  $C_\Theta$  audit. This has now been pushed lower in two directions. Valuation-ball realized exactness plus the valuation-ball additive Haar audit recovers the compact-open realized-exact source used by the preferred audit. Equivalently, the two compact-open image containments construct the compact-open realized-exact source directly, recover the broader equality-backed log-shell source from four local image/valuation-ball containments, define the canonical local log-Kummer graph as the graph of the realization map, and now construct the map-level possible-region source by taking the Kummer map to be the valuation-factor realization and choosing its section from canonical graph left-totality. In the reverse direction, that possible-region map source now constructs the theta-region graph source by the principal-cover equality  $P_{\text{cover}}(\Theta) = P_\Theta$ , and then reaches pointwise valuation-ball exactness and log-shell exactness. The image containments are also derived from a cover-level exactness statement identifying the selected Remark 3.9.5 possible region with the realized compact-open local factor, and now from the lower log-shell exact source  $P_{\Theta,\beta} = \text{real}_\beta(L_\beta)$ ,  $L_\beta = U_\beta$ . These exact equalities are themselves derived from the pointwise local realization source, which is now derived from compact-open local-chart data and from the compact-open log-Kummer graph source. The theta-region-defined Step (xi) valuation cover is now also constructed from the source-core Remark 3.9.5 valuation-ball/Haar cover using the fiber-transport-backed pointwise comparison, and from the lattice-image law once it is identified with the fiber-transport source, to derive the cover/theta-region family equality; in the fiber-derived case this identification is now checked definitionally. What remains is to construct the fiber-transport comparison, the identification for any independently supplied lattice law, and the graph/local-chart laws from the paper-native holomorphic hull, log-Kummer, and local log-shell geometry.
7. Instantiate the valuation-ball local analytic construction from actual local fields, log-shell maps, compact-open Haar normalizations, and archimedean lattice metrics, proving the remaining Proposition 1.4 log-shell estimates and Proposition 1.5 metric containments below those objects.
8. Complete the finite-extension residue/Haar layer below the current boundary: construct the residue field action on  $\mathcal{O}[K_v]$ , prove that  $p_v\mathcal{O}[K_v]$  is a residue submodule, and derive the coset/Haar-character formula for genuine finite extensions rather than only for the base  $p$ -adic field and abstract finite-extension source records.
9. Derive the point-level target transport for the principal finite-divisor regions  $O$  and  $\lambda O$ , including positive valuation-ball radius, coordinate-place equivalence, local scalar-image laws, direct-product localization covers, and the chart/direct-summand log-volume calibrations.
10. Instantiate the typed IUT IV arithmetic-divisor source from actual number-field valuations, the different,  $q$ -parameter, and conductor divisors, and prove the distinguished and archimedean formula-to-gap bounds from the local analytic construction rather than carrying them as route payloads.

11. Extend the Hodge–Arakelov theta-evaluation wrapper beyond the current finite degree-evaluation, bad-local quotient, canonical-label, and canonical-one synchronization shadows toward the Gaussian/Frobenioid constructions of IUT II and the Hodge-theater descent bridge.
12. Only then evaluate whether the Stage 1 interface has enough source content to bear on the Mochizuki–Scholze–Stix disagreement.

## References

- [1] S. Mochizuki, *Inter-universal Teichmuller Theory I: Construction of Hodge Theaters*.
- [2] S. Mochizuki, *Inter-universal Teichmuller Theory II: Hodge-Arakelov-theoretic Evaluation*.
- [3] S. Mochizuki, *Inter-universal Teichmuller Theory III: Canonical Splittings of the Log-theta-lattice*.
- [4] S. Mochizuki, *Inter-universal Teichmuller Theory IV: Log-volume Computations and Set-theoretic Foundations*.
- [5] S. Mochizuki, *On the Formalization of IUT: Preliminary Progress Report*, 2026.
- [6] P. Scholze and J. Stix, *Why abc is still a conjecture*.