Signed lead in, one clean MerusCase case out

When a lead reaches “Signed”, the bridge checks the data and finds the client if they already exist. Then it creates the case, adds each injury with its own POST, attaches the employer and records the referral source and signed date. Lost replies are read back, never sent twice.

0 wrong links	0 duplicates	1 POST per injury	29 of 29 fields	47 / 47 tests
300 test leads vs 3,000 synthetic clients; 118/120 returning linked	14 injected failures, 10 lost replies read back	45 injuries on 33 cases	11 published, 15 per your sheet, 3 gaps solved	webhook, mapping, dedupe, failures, setup

How it runs

GOHIGHLEVEL

Pipeline Stage Changed
pipeline Intake → stage Signed

Custom Webhook action
POST, Bearer token, JSON body from the template (50 keys, 3 injury slots)

Told the result
tag + note with the case ID, or the reason it is held

BRIDGE

202 in ~3 ms
stored under an idempotency key; a repeat delivery returns the first result

Checks before any write
CT end date, future dates, unknown body parts, unmapped attorney, over 3 injuries: held, not half-created

Finds the client
local index of MerusCase contacts: link / review / new

MERUSCASE (IN ORDER)

1. **caseFiles/add** — case + contact (or the existing contact ID) + injury 1
2. **contacts/edit** — returning clients: fill blanks only, never overwrite
3. **injuries/edit** — injuries 2 and 3, no Injury ID = add (published)
4. **contacts/add → parties/add** — employer, reused when already on file
5. **activities/add** — referral source; “Retainer signed” dated on the signed date

The three fields with no API field

Employer
`contacts/add (company) → parties/add`

Company contact attached as a party. Before creating one, the bridge checks for it by normalised name, so “North Bay Builders, Inc.” and “NORTH BAY BUILDERS INC” share one contact.

Referral source
`activities/add · “Intake: referral source”`

A firm activity type (created once with activityTypes/add) keeps referral sources filterable in the case activity log. GoHighLevel keeps them for marketing reports.

Signed date
`activities/add · “Retainer signed”, dated`

activities/add takes a date, so the entry sits on the timeline on the day the client signed, not the day the bridge ran. date_opened too, if caseFiles/add accepts it.

All 29 fields (PUBLISHED injuries/edit names · YOUR SHEET caseFiles/add, not in the public docs · GAP)

1	First name	SHEET	11	State	SHEET	21	Where it happened	PUB
2	Last name	SHEET	12	ZIP	SHEET	22	Carrier claim number	PUB
3	Middle name	SHEET	13	Preferred language	SHEET	23	EAMS ADJ number	PUB
4	Date of birth	SHEET	14	Date of injury (CT start)	PUB	24	Treating doctors	PUB
5	Mobile phone	SHEET	15	CT end date	PUB	25	Assigned attorney	SHEET
6	Home phone	SHEET	16	Injury type (Specific / CT)	PUB	26	Case manager	SHEET
7	Email	SHEET	17	Body parts	PUB	27	Employer	GAP
8	Street address	SHEET	18	Injury description	PUB	28	Referral source	GAP
9	Apt / unit	SHEET	19	How it happened	PUB	29	Signed date	GAP
10	City	SHEET	20	Occupation	PUB			

One lead, every request

A synthetic client with a CT injury and a specific injury: `caseFiles/add` (30) → `injuries/edit` (12) → `contacts/add` (2) → `parties/add` (2) → `activities/add` (3) → `activities/add` (4) → GoHighLevel tag + note “MerusCase case 5001 created (contact 1001, 2 injuries).”. Injury dates go out as MM/DD/YYYY, injury_type_id 1 = CT, 2 = Specific, and body parts as IDs with left/right (q1_injury_description_N_id / _lr, up to 10).

Checks that hold a lead before anything is written

- HOLD First name, last name or DOB missing; DOB implausible
- HOLD No phone and no email
- HOLD Injury type not Specific or CT
- HOLD CT injury without an end date, or ending before it starts
- HOLD Specific injury given an end date
- HOLD Date of injury, CT end or signed date in the future
- HOLD Body part the map does not know (“spleen”)
- HOLD More than 10 body parts, or more than 3 injuries
- HOLD The same injury twice (same type and date)
- HOLD Attorney or case manager with no MerusCase user ID

Held leads get a GoHighLevel tag and a note with the reasons; fixed and sent again, they run.

Dedupe: there is no contact search to call

MerusCase's published API reads a contact only by ID, and your endpoint list has no search. The bridge keeps a local index built through published endpoints: caseFiles/index → parties/view → contacts/view. 3,000 cases took 6,016 calls, about 50 minutes once at an assumed 2 requests a second. After that it refreshes nightly with `modified[gte]`, and contacts the bridge creates are indexed immediately.

LINK	DOB + first + last name (nicknames incl. Pepe, Lupe, Chuy; accents; hyphens; swapped names)
LINK	DOB + phone or email + one name
LINK	Both names + phone or email, no DOB on file
REVIEW	Phone or email shared with a different DOB (relatives, Jr./Sr.)
REVIEW	Name only, or more than one match
NEW	Same name, different DOB, nothing shared

Measured on 3,000 synthetic clients and 300 leads with known answers. Returning clients were typed 11 ways; 30 lookalikes share a name or phone with an existing client:



Wrong links: 0. On review, the lead waits and GoHighLevel gets a tag plus a note with the candidate contact IDs. Staff resolve it with one call.

Injuries and failures

Injury 1 rides in caseFiles/add. Injuries 2 and 3 are separate injuries/edit calls without an Injury ID, which MerusCase documents as "add". MerusCase takes no idempotency key, so every write is journalled. When a reply is lost, the bridge reads the record back before sending again:

WRITE	READ-BACK AFTER A LOST REPLY
`caseFiles/add`	caseFiles/index?modified[gte] → injuries/view + parties/view: same first injury and client, on a case no other intake owns
`injuries/edit`	injuries/view: same date and type, not already recorded
`parties/add · activities/add`	parties/view: the employer is on the case · activities/index: the marker [intake … signed] is there
`contacts/add (employer)`	no read-back without a contact search: at worst one unattached duplicate employer, flagged

Test day: 50 deliveries (40 leads, 10 sent twice) against 3,000 existing cases, with 14 injected MerusCase failures (500 after saving, dropped connections, 500 before saving, 429):

33 cases, 5 for existing clients	**45** injuries, one POST each	**10** lost replies read back	**0** duplicate cases, injuries, parties, notes

LEAD	LEADS	DONE	HELD	REVIEW	WHY
new, 1 injury	20	19	0	1	date of birth and part of the name
new, 2 injuries	6	6	0	0	
new, 3 injuries	3	3	0	0	
returning client	5	5	0	0	
held: CT without end date	1	0	1	0	Injury 1: CT injury needs an end date
held: unknown body part	1	0	1	0	Body parts (injury 1): unknown body part: spleen
held: attorney not mapped	1	0	1	0	Assigned attorney "Associate (new hire)" has no MerusCase user ID in config/firm.json
review: shares a phone	2	0	0	2	phone on file for someone with a different date of birth
repeat deliveries	10	first result returned; no second case			

3 held with reasons (CT without end date, unknown body part "spleen", unmapped attorney). 3 sent to review (2 sharing a relative's phone, 1 sharing a DOB and last name). A lead at another stage was ignored. Also tested: a kill right after a save is resumed without re-sending, and a refused step stops with the step named, then Retry resumes.

Firm IDs, checked before go-live

`npm run check-config` checks the user IDs (users/index), the case type (caseTypes/index) and the activity types (activityTypes/index; --create adds missing ones) against your instance. Case status, venue, office and body-part IDs have no published list endpoint, so they are filled from your spreadsheet.

Handoff

1. GoHighLevel: Pipeline Stage Changed → Custom Webhook (Bearer) with the body template; Private Integration token for the tag and note.
2. MerusCase: OAuth app; confirm caseFiles/add, contacts/add and contacts/edit names from your spreadsheet; build the index once.
3. One Node service + one SQLite file; README covers the review queue, retries and re-indexing.

Sources: MerusCase developer guide (endpoints; app setup and authentication), HighLevel help (Custom Webhook and Webhook actions), HighLevel API (Private Integration tokens). Assumed until your spreadsheet: caseFiles/add, contacts/add and contacts/edit field names and the response envelope. Modelled: 2 requests/s for the index estimate.