

prombutter.sql

```
1 ALTER TABLE public.entity_tags
2 DROP CONSTRAINT fk_entity_tags_tag;
3
4 DROP TABLE IF EXISTS public.entity_tags CASCADE;
5
6 CREATE TABLE public.entity_tags
7 (
8     entity_type    TAG_ENTITY_TYPE NOT NULL,
9     entity_id      UUID NOT NULL,
10    tag_id         UUID NOT NULL
11 );
12
13 COMMENT ON COLUMN public.entity_tags.entity_type IS '대상 엔티티 종류';
14
15 COMMENT ON COLUMN public.entity_tags.entity_id IS '대상 엔티티 ID';
16
17 COMMENT ON COLUMN public.entity_tags.tag_id IS '태그 ID';
18
19 COMMENT ON TABLE public.entity_tags IS '엔티티-태그 연결';
20
21 CREATE UNIQUE INDEX pk_entity_tags ON public.entity_tags
22 ( entity_type,entity_id,tag_id );
23
24 ALTER TABLE public.entity_tags
25 ADD CONSTRAINT pk_entity_tags PRIMARY KEY
26 USING INDEX pk_entity_tags;
27
28 ALTER TABLE public.entity_tags
29 ADD CONSTRAINT fk_entity_tags_tag FOREIGN KEY ( tag_id )
30 REFERENCES tags (id );
31
32
33 ALTER TABLE public.events
34 DROP CONSTRAINT fk_events_user;
35
36 ALTER TABLE public.events
37 DROP CONSTRAINT fk_events_workspace;
38
39 DROP TABLE IF EXISTS public.events CASCADE;
40
41 CREATE TABLE public.events
42 (
43     id            bigint NOT NULL,
44     event_name    character varying(80) NOT NULL,
45     user_id       UUID,
46     workspace_id  UUID,
47     session_id    character varying(100),
48     device_type   DEVICE_TYPE,
49     prompt_has_vars boolean,
50     prompt_length integer,
51     error_code    character varying(80),
52     error_message text,
53     properties    jsonb DEFAULT '{} '::jsonb NOT NULL,
54     occurred_at   timestamp with time zone DEFAULT CURRENT_TIMESTAMP
55     entry_point   ENTRY_POINT,
56     target_entity_type EVENT_TARGET_TYPE,
57     target_entity_id UUID
58 );
59
60 COMMENT ON COLUMN public.events.id IS '이벤트 ID';
61
```

```

62 COMMENT ON COLUMN public.events.event_name IS '이벤트명(예: prompt_injec
63
64 COMMENT ON COLUMN public.events.user_id IS '사용자 ID';
65
66 COMMENT ON COLUMN public.events.workspace_id IS '워크스페이스 ID';
67
68 COMMENT ON COLUMN public.events.session_id IS '세션 ID';
69
70 COMMENT ON COLUMN public.events.device_type IS '디바이스 유형(WEB/EXTENS
71
72 COMMENT ON COLUMN public.events.prompt_has_vars IS '변수 포함 여부';
73
74 COMMENT ON COLUMN public.events.prompt_length IS '주입/복사된 텍스트 길이';
75
76 COMMENT ON COLUMN public.events.error_code IS '실패 코드';
77
78 COMMENT ON COLUMN public.events.error_message IS '실패 안내 메시지';
79
80 COMMENT ON COLUMN public.events.properties IS '추가 파라미터(JSONB)';
81
82 COMMENT ON COLUMN public.events.occurred_at IS '발생 시각';
83
84 COMMENT ON COLUMN public.events.entry_point IS '진입점 (WEBAPP/EXT_ENTR
85
86 COMMENT ON COLUMN public.events.target_entity_type IS '대상 엔티티 종류 (
87
88 COMMENT ON COLUMN public.events.target_entity_id IS '대상 엔티티 ID (FK
89
90 COMMENT ON TABLE public.events IS '이벤트 로그';
91
92 CREATE UNIQUE INDEX pk_events ON public.events
93 ( id,occurred_at );
94
95 ALTER TABLE public.events
96 ADD CONSTRAINT pk_events PRIMARY KEY
97 USING INDEX pk_events;
98
99 ALTER TABLE public.events
100 ADD CONSTRAINT fk_events_user FOREIGN KEY ( user_id )
101 REFERENCES users (id );
102
103 ALTER TABLE public.events
104 ADD CONSTRAINT fk_events_workspace FOREIGN KEY ( workspace_id )
105 REFERENCES workspaces (id );
106
107
108 DROP TABLE IF EXISTS public.login_attempts CASCADE;
109
110 CREATE TABLE public.login_attempts
111 (
112     id          bigint DEFAULT nextval('login_attempts_id_seq') NOT NULL,
113     ip_address   INET,
114     success      boolean NOT NULL,
115     attempted_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP
116     email_hash   character varying(64) NOT NULL
117 );
118
119 COMMENT ON COLUMN public.login_attempts.id IS '시도 ID';
120
121 COMMENT ON COLUMN public.login_attempts.ip_address IS 'IP 주소';
122
123 COMMENT ON COLUMN public.login_attempts.success IS '성공 여부';
124
125 COMMENT ON COLUMN public.login_attempts.attempted_at IS '시도 시각';
126
127 COMMENT ON COLUMN public.login_attempts.email_hash IS '이메일 해시 (소문자
128

```

```

129 COMMENT ON TABLE public.login_attempts IS '로그인 시도 기록(CAPTCHA 트리거
130
131 CREATE UNIQUE INDEX pk_login_attempts ON public.login_attempts
132 ( id );
133
134 ALTER TABLE public.login_attempts
135 ADD CONSTRAINT pk_login_attempts PRIMARY KEY
136 USING INDEX pk_login_attempts;
137
138
139 ALTER TABLE public.prompt_blocks
140 DROP CONSTRAINT fk_prompt_blocks_part;
141
142 ALTER TABLE public.parts
143 DROP CONSTRAINT fk_parts_workspace;
144
145 DROP TABLE IF EXISTS public.parts CASCADE;
146
147 CREATE TABLE public.parts
148 (
149     id          UUID DEFAULT gen_random_uuid() NOT NULL,
150     workspace_id  UUID NOT NULL,
151     title        character varying(100) NOT NULL,
152     body         character varying(700) NOT NULL,
153     is_favorite   boolean DEFAULT 'false' NOT NULL,
154     deleted_at    timestamp with time zone,
155     purge_at      timestamp with time zone,
156     created_at    timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL,
157     updated_at    timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL
158 );
159
160 COMMENT ON COLUMN public.parts.id IS '파트 ID';
161
162 COMMENT ON COLUMN public.parts.workspace_id IS '워크스페이스 ID';
163
164 COMMENT ON COLUMN public.parts.title IS '제목(100자, 워크스페이스 내 중복
165
166 COMMENT ON COLUMN public.parts.body IS '본문(700자)';
167
168 COMMENT ON COLUMN public.parts.is_favorite IS '파트 즐겨찾기(, 편집 접근용
169
170 COMMENT ON COLUMN public.parts.deleted_at IS 'Soft Delete 시각';
171
172 COMMENT ON COLUMN public.parts.purge_at IS '영구 삭제 예정 시각(deleted_at
173
174 COMMENT ON COLUMN public.parts.created_at IS '생성 시각';
175
176 COMMENT ON COLUMN public.parts.updated_at IS '수정 시각';
177
178 COMMENT ON TABLE public.parts IS '파트(프롬프트 재료)';
179
180 CREATE UNIQUE INDEX pk_parts ON public.parts
181 ( id );
182
183 ALTER TABLE public.parts
184 ADD CONSTRAINT pk_parts PRIMARY KEY
185 USING INDEX pk_parts;
186
187 ALTER TABLE public.parts
188 ADD CONSTRAINT uq_parts_active_title UNIQUE
189 USING INDEX uq_parts_active_title;
190
191 ALTER TABLE public.parts
192 ADD CONSTRAINT uk_parts_active_title UNIQUE
193 USING INDEX uk_parts_active_title;
194
195 ALTER TABLE public.parts

```

```

196 ADD CONSTRAINT fk_parts_workspace FOREIGN KEY ( workspace_id )
197 REFERENCES workspaces (id );
198
199
200 ALTER TABLE public.prompt_blocks
201 DROP CONSTRAINT fk_prompt_blocks_part;
202
203 ALTER TABLE public.prompt_blocks
204 DROP CONSTRAINT fk_prompt_blocks_prompt;
205
206 DROP TABLE IF EXISTS public.prompt_blocks CASCADE;
207
208 CREATE TABLE public.prompt_blocks
209 (
210     id        UUID DEFAULT gen_random_uuid() NOT NULL,
211     prompt_id  UUID NOT NULL,
212     part_id    UUID,
213     inline_body character_varying(700),
214     created_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL,
215     sort_order integer NOT NULL,
216     block_type BLOCK_TYPE NOT NULL
217 );
218
219 COMMENT ON COLUMN public.prompt_blocks.id IS '블록 ID';
220
221 COMMENT ON COLUMN public.prompt_blocks.prompt_id IS '프롬프트 ID';
222
223 COMMENT ON COLUMN public.prompt_blocks.part_id IS '파츠 ID(kind=PART)';
224
225 COMMENT ON COLUMN public.prompt_blocks.inline_body IS '인라인 본문(kind=INLINE)';
226
227 COMMENT ON COLUMN public.prompt_blocks.created_at IS '생성 시각';
228
229 COMMENT ON COLUMN public.prompt_blocks.sort_order IS '정렬 순서';
230
231 COMMENT ON COLUMN public.prompt_blocks.block_type IS '블록 종류 (PART/INLINE)';
232
233 COMMENT ON TABLE public.prompt_blocks IS '프롬프트 블록(파츠 참조 또는 인라인 참조)';
234
235 CREATE UNIQUE INDEX pk_prompt_blocks ON public.prompt_blocks
236 ( id );
237
238 ALTER TABLE public.prompt_blocks
239 ADD CONSTRAINT pk_prompt_blocks PRIMARY KEY
240 USING INDEX pk_prompt_blocks;
241
242 ALTER TABLE public.prompt_blocks
243 ADD CONSTRAINT uk_prompt_blocks_position UNIQUE
244 USING INDEX uk_prompt_blocks_position;
245
246 ALTER TABLE public.prompt_blocks
247 ADD CONSTRAINT uk_prompt_blocks_sort_order UNIQUE
248 USING INDEX uk_prompt_blocks_sort_order;
249
250 ALTER TABLE public.prompt_blocks
251 ADD CONSTRAINT fk_prompt_blocks_part FOREIGN KEY ( part_id )
252 REFERENCES parts (id );
253
254 ALTER TABLE public.prompt_blocks
255 ADD CONSTRAINT fk_prompt_blocks_prompt FOREIGN KEY ( prompt_id )
256 REFERENCES prompts (id );
257
258
259 ALTER TABLE public.prompt_blocks
260 DROP CONSTRAINT fk_prompt_blocks_prompt;
261
262 ALTER TABLE public.prompts

```

```

263 DROP CONSTRAINT fk_prompts_workspace;
264
265 DROP TABLE IF EXISTS public.prompts CASCADE;
266
267 CREATE TABLE public.prompts
268 (
269     id        UUID DEFAULT gen_random_uuid() NOT NULL,
270     workspace_id  UUID NOT NULL,
271     title      character varying(100) NOT NULL,
272     favorited_at timestamp with time zone,
273     deleted_at  timestamp with time zone,
274     purge_at   timestamp with time zone,
275     created_at  timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL,
276     updated_at  timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL
277 );
278
279 COMMENT ON COLUMN public.prompts.id IS '프롬프트 ID';
280
281 COMMENT ON COLUMN public.prompts.workspace_id IS '워크스페이스 ID';
282
283 COMMENT ON COLUMN public.prompts.title IS '제목(100자, 워크스페이스 내 중복 가능)';
284
285 COMMENT ON COLUMN public.prompts.favorited_at IS '즐거찾기 등록 시각';
286
287 COMMENT ON COLUMN public.prompts.deleted_at IS 'Soft Delete 시각';
288
289 COMMENT ON COLUMN public.prompts.purge_at IS '영구 삭제 예정 시각(deleted_at 이후 30일)';
290
291 COMMENT ON COLUMN public.prompts.created_at IS '생성 시각';
292
293 COMMENT ON COLUMN public.prompts.updated_at IS '수정 시각';
294
295 COMMENT ON TABLE public.prompts IS '프롬프트(실행 단위)';
296
297 CREATE UNIQUE INDEX pk_prompts ON public.prompts
298 ( id );
299
300 ALTER TABLE public.prompts
301 ADD CONSTRAINT pk_prompts PRIMARY KEY
302 USING INDEX pk_prompts;
303
304 ALTER TABLE public.prompts
305 ADD CONSTRAINT uq_prompts_active_title UNIQUE
306 USING INDEX uq_prompts_active_title;
307
308 ALTER TABLE public.prompts
309 ADD CONSTRAINT uk_prompts_active_title UNIQUE
310 USING INDEX uk_prompts_active_title;
311
312 ALTER TABLE public.prompts
313 ADD CONSTRAINT fk_prompts_workspace FOREIGN KEY ( workspace_id )
314 REFERENCES workspaces (id );
315
316
317 ALTER TABLE public.revisions
318 DROP CONSTRAINT fk_revisions_created_by;
319
320 ALTER TABLE public.revisions
321 DROP CONSTRAINT fk_revisions_workspace;
322
323 DROP TABLE IF EXISTS public.revisions CASCADE;
324
325 CREATE TABLE public.revisions
326 (
327     id        UUID DEFAULT gen_random_uuid() NOT NULL,
328     entity_type REVISION_ENTITY_TYPE NOT NULL,
329     entity_id  UUID NOT NULL,

```

```

330     revision_no    integer NOT NULL,
331     workspace_id   UUID NOT NULL,
332     snapshot       jsonb NOT NULL,
333     created_by     UUID,
334     created_at     timestamp with time zone DEFAULT CURRENT_TIMESTAMP N
335 );
336
337 COMMENT ON COLUMN public.revisions.id IS '이력 ID';
338
339 COMMENT ON COLUMN public.revisions.entity_type IS '대상 엔티티 종류 (PROMPT, TAG, CHAT)';
340
341 COMMENT ON COLUMN public.revisions.entity_id IS '대상 엔티티 ID (엔티티 ID)';
342
343 COMMENT ON COLUMN public.revisions.revision_no IS '엔티티별 버전 번호 (1부터 시작)';
344
345 COMMENT ON COLUMN public.revisions.workspace_id IS '워크스페이스 ID (탈퇴한 워크스페이스 제외)';
346
347 COMMENT ON COLUMN public.revisions.snapshot IS '스냅샷 (자식 포함, JSONB)';
348
349 COMMENT ON COLUMN public.revisions.created_by IS '저장 사용자 ID';
350
351 COMMENT ON COLUMN public.revisions.created_at IS '생성 시각';
352
353 COMMENT ON TABLE public.revisions IS '편집 이력 (프롬프트/파츠/태그 통합 스냅샷)';
354
355 CREATE UNIQUE INDEX pk_revisions ON public.revisions
356 ( id );
357
358 ALTER TABLE public.revisions
359 ADD CONSTRAINT pk_revisions PRIMARY KEY
360 USING INDEX pk_revisions;
361
362 ALTER TABLE public.revisions
363 ADD CONSTRAINT uk_revisions_entity_no UNIQUE
364 USING INDEX uk_revisions_entity_no;
365
366 ALTER TABLE public.revisions
367 ADD CONSTRAINT fk_revisions_created_by FOREIGN KEY ( created_by )
368 REFERENCES users ( id );
369
370 ALTER TABLE public.revisions
371 ADD CONSTRAINT fk_revisions_workspace FOREIGN KEY ( workspace_id )
372 REFERENCES workspaces ( id );
373
374
375 ALTER TABLE public.sample_prompts
376 DROP CONSTRAINT fk_sample_prompts_category;
377
378 DROP TABLE IF EXISTS public.sample_categories CASCADE;
379
380 CREATE TABLE public.sample_categories
381 (
382     id          UUID DEFAULT gen_random_uuid() NOT NULL,
383     name        character varying(50) NOT NULL,
384     slug        character varying(50) NOT NULL,
385     sort_order  integer DEFAULT 0 NOT NULL
386 );
387
388 COMMENT ON COLUMN public.sample_categories.id IS '카테고리 ID';
389
390 COMMENT ON COLUMN public.sample_categories.name IS '카테고리명';
391
392 COMMENT ON COLUMN public.sample_categories.slug IS 'URL 슬러그';
393
394 COMMENT ON COLUMN public.sample_categories.sort_order IS '정렬 순서';
395
396 COMMENT ON TABLE public.sample_categories IS '샘플 프롬프트 카테고리';

```

```

397
398 CREATE UNIQUE INDEX pk_sample_categories ON public.sample_categories
399 ( id );
400
401 ALTER TABLE public.sample_categories
402 ADD CONSTRAINT pk_sample_categories PRIMARY KEY
403 USING INDEX pk_sample_categories;
404
405 ALTER TABLE public.sample_categories
406 ADD CONSTRAINT uk_sample_categories_name UNIQUE
407 USING INDEX uk_sample_categories_name;
408
409 ALTER TABLE public.sample_categories
410 ADD CONSTRAINT uk_sample_categories_slug UNIQUE
411 USING INDEX uk_sample_categories_slug;
412
413
414 ALTER TABLE public.sample_prompts
415 DROP CONSTRAINT fk_sample_prompts_category;
416
417 DROP TABLE IF EXISTS public.sample_prompts CASCADE;
418
419 CREATE TABLE public.sample_prompts
420 (
421     id UUID DEFAULT gen_random_uuid() NOT NULL,
422     category_id UUID NOT NULL,
423     title character varying(100) NOT NULL,
424     description text,
425     body character varying(700) NOT NULL,
426     sort_order integer DEFAULT 0 NOT NULL,
427     is_published boolean DEFAULT 'true' NOT NULL,
428     created_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL,
429     updated_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL,
430 );
431
432 COMMENT ON COLUMN public.sample_prompts.id IS '샘플 프롬프트 ID';
433
434 COMMENT ON COLUMN public.sample_prompts.category_id IS '카테고리 ID';
435
436 COMMENT ON COLUMN public.sample_prompts.title IS '제목';
437
438 COMMENT ON COLUMN public.sample_prompts.description IS '설명';
439
440 COMMENT ON COLUMN public.sample_prompts.body IS '본문(복사 시 단일 INLINE)';
441
442 COMMENT ON COLUMN public.sample_prompts.sort_order IS '정렬 순서';
443
444 COMMENT ON COLUMN public.sample_prompts.is_published IS '공개 여부';
445
446 COMMENT ON COLUMN public.sample_prompts.created_at IS '생성 시각';
447
448 COMMENT ON COLUMN public.sample_prompts.updated_at IS '수정 시각';
449
450 COMMENT ON TABLE public.sample_prompts IS '샘플 프롬프트(시딩, 갤러리 탐색용)';
451
452 CREATE UNIQUE INDEX pk_sample_prompts ON public.sample_prompts
453 ( id );
454
455 ALTER TABLE public.sample_prompts
456 ADD CONSTRAINT pk_sample_prompts PRIMARY KEY
457 USING INDEX pk_sample_prompts;
458
459 ALTER TABLE public.sample_prompts
460 ADD CONSTRAINT fk_sample_prompts_category FOREIGN KEY ( category_id )
461 REFERENCES sample_categories (id );
462
463

```

```

464 ALTER TABLE public.entity_tags
465 DROP CONSTRAINT fk_entity_tags_tag;
466
467 ALTER TABLE public.tags
468 DROP CONSTRAINT fk_tags_workspace;
469
470 DROP TABLE IF EXISTS public.tags CASCADE;
471
472 CREATE TABLE public.tags
473 (
474     id        UUID DEFAULT gen_random_uuid() NOT NULL,
475     workspace_id  UUID NOT NULL,
476     name       character varying(50) NOT NULL,
477     created_at   timestamp without time zone DEFAULT CURRENT_TIMESTAMP
478 );
479
480 COMMENT ON COLUMN public.tags.id IS '태그 ID';
481
482 COMMENT ON COLUMN public.tags.workspace_id IS '워크스페이스 ID';
483
484 COMMENT ON COLUMN public.tags.name IS '태그명';
485
486 COMMENT ON COLUMN public.tags.created_at IS '생성 시각';
487
488 COMMENT ON TABLE public.tags IS '태그';
489
490 CREATE UNIQUE INDEX pk_tags ON public.tags
491 ( id );
492
493 ALTER TABLE public.tags
494 ADD CONSTRAINT pk_tags PRIMARY KEY
495 USING INDEX pk_tags;
496
497 ALTER TABLE public.tags
498 ADD CONSTRAINT uk_tags_name UNIQUE
499 USING INDEX uk_tags_name;
500
501 ALTER TABLE public.tags
502 ADD CONSTRAINT fk_tags_workspace FOREIGN KEY ( workspace_id )
503 REFERENCES workspaces (id );
504
505
506 ALTER TABLE public.tokens
507 DROP CONSTRAINT fk_tokens_user;
508
509 DROP TABLE IF EXISTS public.tokens CASCADE;
510
511 CREATE TABLE public.tokens
512 (
513     id        UUID DEFAULT gen_random_uuid() NOT NULL,
514     user_id    UUID NOT NULL,
515     token_hash character varying(255) NOT NULL,
516     expires_at timestamp with time zone NOT NULL,
517     used_at    timestamp with time zone,
518     created_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP
519     token_type TOKEN_TYPE NOT NULL
520 );
521
522 COMMENT ON COLUMN public.tokens.id IS '토큰 ID';
523
524 COMMENT ON COLUMN public.tokens.user_id IS '사용자 ID';
525
526 COMMENT ON COLUMN public.tokens.token_hash IS '토큰 해시 (원본 토큰은 저장
527
528 COMMENT ON COLUMN public.tokens.expires_at IS '만료 시각';
529
530 COMMENT ON COLUMN public.tokens.used_at IS '사용(소비) 시각. NULL이면 미사

```



```

531
532 COMMENT ON COLUMN public.tokens.created_at IS '생성 시각';
533
534 COMMENT ON COLUMN public.tokens.token_type IS '토큰 종류 (EMAIL_VERIFICATION_TOKEN)';
535
536 COMMENT ON TABLE public.tokens IS '단기 인증 토큰 (이메일 인증/비밀번호 재설정)';
537
538 CREATE UNIQUE INDEX pk_tokens ON public.tokens
539 ( id );
540
541 ALTER TABLE public.tokens
542 ADD CONSTRAINT pk_tokens PRIMARY KEY
543 USING INDEX pk_tokens;
544
545 ALTER TABLE public.tokens
546 ADD CONSTRAINT uk_tokens_hash UNIQUE
547 USING INDEX uk_tokens_hash;
548
549 ALTER TABLE public.tokens
550 ADD CONSTRAINT fk_tokens_user FOREIGN KEY ( user_id )
551 REFERENCES users (id );
552
553
554 ALTER TABLE public.user_identities
555 DROP CONSTRAINT fk_user_identities_user;
556
557 DROP TABLE IF EXISTS public.user_identities CASCADE;
558
559 CREATE TABLE public.user_identities
560 (
561     id UUID DEFAULT gen_random_uuid() NOT NULL,
562     user_id UUID NOT NULL,
563     provider AUTH_PROVIDER NOT NULL,
564     provider_user_id character varying(255) NOT NULL,
565     access_token bytea,
566     refresh_token bytea,
567     created_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP NOT NULL
568 );
569
570 COMMENT ON COLUMN public.user_identities.id IS '연결 ID';
571
572 COMMENT ON COLUMN public.user_identities.user_id IS '사용자 ID';
573
574 COMMENT ON COLUMN public.user_identities.provider IS '인증 제공자(EMAIL_PROVIDER)';
575
576 COMMENT ON COLUMN public.user_identities.provider_user_id IS '제공자 측 ID';
577
578 COMMENT ON COLUMN public.user_identities.access_token IS '액세스 토큰(RefreshToken)';
579
580 COMMENT ON COLUMN public.user_identities.refresh_token IS '리프레시 토큰';
581
582 COMMENT ON COLUMN public.user_identities.created_at IS '생성 시각';
583
584 COMMENT ON TABLE public.user_identities IS '사용자 인증 제공자 연결';
585
586 CREATE UNIQUE INDEX pk_user_identities ON public.user_identities
587 ( id );
588
589 ALTER TABLE public.user_identities
590 ADD CONSTRAINT pk_user_identities PRIMARY KEY
591 USING INDEX pk_user_identities;
592
593 ALTER TABLE public.user_identities
594 ADD CONSTRAINT uk_user_identities_provider UNIQUE
595 USING INDEX uk_user_identities_provider;
596
597 ALTER TABLE public.user_identities

```

```

598 ADD CONSTRAINT fk_user_identities_user FOREIGN KEY ( user_id )
599 REFERENCES users (id );
600
601
602 ALTER TABLE public.user_sessions
603 DROP CONSTRAINT fk_user_sessions_user;
604
605 DROP TABLE IF EXISTS public.user_sessions CASCADE;
606
607 CREATE TABLE public.user_sessions
608 (
609     id        UUID DEFAULT gen_random_uuid() NOT NULL,
610     user_id    UUID NOT NULL,
611     refresh_token_hash character_varying(255) NOT NULL,
612     device_info text,
613     expires_at timestamp with time zone NOT NULL,
614     revoked_at timestamp with time zone,
615     created_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP N
616 );
617
618 COMMENT ON COLUMN public.user_sessions.id IS '세션 ID';
619
620 COMMENT ON COLUMN public.user_sessions.user_id IS '사용자 ID';
621
622 COMMENT ON COLUMN public.user_sessions.refresh_token_hash IS '리프레시 토큰';
623
624 COMMENT ON COLUMN public.user_sessions.device_info IS '디바이스 정보';
625
626 COMMENT ON COLUMN public.user_sessions.expires_at IS '만료 시각';
627
628 COMMENT ON COLUMN public.user_sessions.revoked_at IS '폐기 시각(비밀번호 변경 시)';
629
630 COMMENT ON COLUMN public.user_sessions.created_at IS '생성 시각';
631
632 COMMENT ON TABLE public.user_sessions IS '사용자 세션';
633
634 CREATE UNIQUE INDEX pk_user_sessions ON public.user_sessions
635 ( id );
636
637 ALTER TABLE public.user_sessions
638 ADD CONSTRAINT pk_user_sessions PRIMARY KEY
639 USING INDEX pk_user_sessions;
640
641 ALTER TABLE public.user_sessions
642 ADD CONSTRAINT uk_user_sessions_refresh_hash UNIQUE
643 USING INDEX uk_user_sessions_refresh_hash;
644
645 ALTER TABLE public.user_sessions
646 ADD CONSTRAINT fk_user_sessions_user FOREIGN KEY ( user_id )
647 REFERENCES users (id );
648
649
650 ALTER TABLE public.events
651 DROP CONSTRAINT fk_events_user;
652
653 ALTER TABLE public.user_identities
654 DROP CONSTRAINT fk_user_identities_user;
655
656 ALTER TABLE public.user_sessions
657 DROP CONSTRAINT fk_user_sessions_user;
658
659 ALTER TABLE public.workspaces
660 DROP CONSTRAINT fk_workspaces_owner;
661
662 ALTER TABLE public.tokens
663 DROP CONSTRAINT fk_tokens_user;
664

```

```

665 ALTER TABLE public.revisions
666 DROP CONSTRAINT fk_revisions_created_by;
667
668 DROP TABLE IF EXISTS public.users CASCADE;
669
670 CREATE TABLE public.users
671 (
672     id        UUID DEFAULT gen_random_uuid() NOT NULL,
673     email     CITEXT NOT NULL,
674     name      character varying(100) NOT NULL,
675     password_hash character varying(255),
676     role      USER_ROLE DEFAULT 'USER'::user_role NOT NULL,
677     email_verified_at timestamp with time zone,
678     onboarding_completed_at timestamp with time zone,
679     failed_login_count integer DEFAULT 0 NOT NULL,
680     last_failed_login_at timestamp with time zone,
681     created_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP N
682     updated_at timestamp with time zone DEFAULT CURRENT_TIMESTAMP N
683     extension_first_detected_at timestamp with time zone,
684     extension_last_detected_at timestamp with time zone
685 );
686
687 COMMENT ON COLUMN public.users.id IS '사용자 ID';
688
689 COMMENT ON COLUMN public.users.email IS '이메일';
690
691 COMMENT ON COLUMN public.users.name IS '이름';
692
693 COMMENT ON COLUMN public.users.password_hash IS '비밀번호 해시(이메일 가입
694
695 COMMENT ON COLUMN public.users.role IS '권한(USER/SUPER_ADMIN)';
696
697 COMMENT ON COLUMN public.users.email_verified_at IS '이메일 인증 시각';
698
699 COMMENT ON COLUMN public.users.onboarding_completed_at IS '온보딩 완료 시
700
701 COMMENT ON COLUMN public.users.failed_login_count IS '연속 로그인 실패 횟
702
703 COMMENT ON COLUMN public.users.last_failed_login_at IS '마지막 로그인 실패
704
705 COMMENT ON COLUMN public.users.created_at IS '생성 시각';
706
707 COMMENT ON COLUMN public.users.updated_at IS '수정 시각';
708
709 COMMENT ON COLUMN public.users.extension_first_detected_at IS '최초 감지
710
711 COMMENT ON COLUMN public.users.extension_last_detected_at IS '최근 감지
712
713 COMMENT ON TABLE public.users IS '사용자';
714
715 CREATE UNIQUE INDEX pk_users ON public.users
716 ( id );
717
718 ALTER TABLE public.users
719 ADD CONSTRAINT pk_users PRIMARY KEY
720 USING INDEX pk_users;
721
722 ALTER TABLE public.users
723 ADD CONSTRAINT uk_users_email UNIQUE
724 USING INDEX uk_users_email;
725
726
727 DROP TABLE IF EXISTS public.variables CASCADE;
728
729 CREATE TABLE public.variables
730 (
731     entity_type    VARIABLE_ENTITY_TYPE NOT NULL,

```

```

732     entity_id    UUID NOT NULL,
733     name         character varying(100) NOT NULL,
734     has_conflict boolean DEFAULT 'false' NOT NULL
735 );
736
737 COMMENT ON COLUMN public.variables.entity_type IS '대상 엔티티 종류';
738
739 COMMENT ON COLUMN public.variables.entity_id IS '대상 엔티티 ID';
740
741 COMMENT ON COLUMN public.variables.name IS '변수명';
742
743 COMMENT ON COLUMN public.variables.has_conflict IS '변수명 충돌 여부';
744
745 COMMENT ON TABLE public.variables IS '변수';
746
747 CREATE UNIQUE INDEX pk_variables ON public.variables
748 ( entity_type,entity_id,name );
749
750 ALTER TABLE public.variables
751 ADD CONSTRAINT pk_variables PRIMARY KEY
752 USING INDEX pk_variables;
753
754
755 ALTER TABLE public.events
756 DROP CONSTRAINT fk_events_workspace;
757
758 ALTER TABLE public.parts
759 DROP CONSTRAINT fk_parts_workspace;
760
761 ALTER TABLE public.prompts
762 DROP CONSTRAINT fk_prompts_workspace;
763
764 ALTER TABLE public.tags
765 DROP CONSTRAINT fk_tags_workspace;
766
767 ALTER TABLE public.revisions
768 DROP CONSTRAINT fk_revisions_workspace;
769
770 ALTER TABLE public.workspaces
771 DROP CONSTRAINT fk_workspaces_owner;
772
773 DROP TABLE IF EXISTS public.workspaces CASCADE;
774
775 CREATE TABLE public.workspaces
776 (
777     id          UUID DEFAULT gen_random_uuid() NOT NULL,
778     owner_id    UUID NOT NULL,
779     name        character varying(100) DEFAULT '내 워크스페이스' NOT NULL,
780     created_at  timestamp with time zone DEFAULT CURRENT_TIMESTAMP N
781     updated_at  timestamp with time zone DEFAULT CURRENT_TIMESTAMP N
782 );
783
784 COMMENT ON COLUMN public.workspaces.id IS '워크스페이스 ID';
785
786 COMMENT ON COLUMN public.workspaces.owner_id IS '소유자 사용자 ID(1:1)';
787
788 COMMENT ON COLUMN public.workspaces.name IS '워크스페이스명';
789
790 COMMENT ON COLUMN public.workspaces.created_at IS '생성 시각';
791
792 COMMENT ON COLUMN public.workspaces.updated_at IS '수정 시각';
793
794 COMMENT ON TABLE public.workspaces IS '워크스페이스';
795
796 CREATE UNIQUE INDEX pk_workspaces ON public.workspaces
797 ( id );
798

```

```
799 ALTER TABLE public.workspaces
800   ADD CONSTRAINT pk_workspaces PRIMARY KEY
801   USING INDEX pk_workspaces;
802
803 ALTER TABLE public.workspaces
804   ADD CONSTRAINT uk_workspaces_owner UNIQUE
805   USING INDEX uk_workspaces_owner;
806
807 ALTER TABLE public.workspaces
808   ADD CONSTRAINT fk_workspaces_owner FOREIGN KEY ( owner_id )
809   REFERENCES users (id );
```