

CREATIVE DIST


QUICK GUIDE

A creative saturator for your DAW: four interchangeable modules, a 5-band EQ, and an output stage that never lets you break the signal.

HOW IT'S BUILT

What's inside the plugin

Creative Dist is built around **four interchangeable modules** — Saturation, Noise, Bode, and Flux — that you choose, reorder, and combine freely across three drag-and-drop slots (any slot can hold any of the four). The signal then passes through an always-on **5-band EQ**, and finally through an **output** stage that keeps the level in check before it leaves the plugin.



Any slot can hold any of the four modules — or stay empty. You can use the same module twice, drag it to reorder the chain, and listen to any module **in isolation** (parallel to whatever comes after it) with that module's PAR button. A small × in the corner of an empty slot's picker lets you back out without choosing anything.

ALWAYS ON, BEHIND THE SCENES

You won't find a knob for these — they work on their own, so you can experiment without risking a broken signal: **Auto Gain** (compensates level as you push Drive), **DC blocking**, a **Silence Gate** at −120dB, **BassProtect** (shields the low end from heavy saturation), and **HarshnessGuard** (tames the harshest highs). And right at the end of the chain, an asymptotic **Soft Clip** always keeps you under 0dBFS.

THE TOP BAR

Presets, undo, bypass

Preset ▶ ◀	Step through presets with the arrows, or open the full searchable list from the dropdown — grouped into Factory and Your Presets, each organized into Vox / Bass / Synth / Sound Design categories.	Dice	Randomize every active module at once — a great way to find a starting point.
Save / Load	Save the current preset into a category (with an overwrite prompt), or import one from a file.	Undo	Step back one action on knobs or EQ if a change doesn't work out.
Folder	Choose where your presets are saved, or reset to the default folder next to the plugin.	Bypass	Turn off the whole plugin (passthrough), screen dimmed, to compare against the original signal.

MODULE 1 OF 4

Saturation

DISTORTION

The heart of the saturation: pushes the signal through a distortion curve, with 18 different characters to choose from.

Drive	How hard the signal is pushed into the curve — higher means more saturation.
Mix	How much saturated signal you hear blended with the clean signal.
Dyn Resp	Makes Drive react in real time to the input signal's envelope.
Asymmetry	Makes the curve asymmetric between the positive and negative half-cycles: more even harmonics, a more organic color.

THE 18 MODES (WAVE TYPE)

- | | |
|---|--|
| 01 Tube — warm, smooth valve-style saturation | 02 Soft Clip — gentle, musical peak compression |
| 03 Asym — asymmetric curve, lively color | 04 Diode — biting, diode-style edge |
| 05 Overdrive — smooth, guitar-style overdrive | 06 Hard Clip — sharp, direct clipping |
| 07 Linear — no distortion, clean reference | 08 Digital — jagged clip, deliberately lo-fi |
| 09 Foldback — the signal folds back on itself | 10 Sine — sinusoidal waveshaping |
| 11 Bitcrush — reduces bit depth, retro | 12 Downsample — reduces sample rate, retro |
| 13 X-Shaper — pure cubic curve, predictable color | 14 Dual Shaper — Tube + Soft Clip in series |
| 15 Tape — soft magnetic-tape saturation | 16 Wavefolder — folds peaks back instead of clipping them |
| 17 Rectifier — diode-rectifier style, octave-up flavor | 18 Exciter — adds harmonic sizzle to the top end |

MODULE 2 OF 4

Noise

TEXTURE

Adds a bed of noise to the signal: from a thin veil to a texture in the foreground.

- Amount** Amount of noise blended into the signal.
- HP / LP** High-pass and low-pass filters that shape the noise's color.
- Pitch** Transposes the noise up to ± 32 semitones.
- Loop / 1-Shot** Loop: the noise runs continuously. 1-Shot: it restarts on every incoming transient, like a small burst synced to the sound.
- **White** — full spectrum, even across all frequencies
- **Brown** — even darker, deep and muffled
- **Digital** — colder, more "computerized"
- **Pink** — more low-end energy, soft and natural
- **Vinyl Crackle** — record-style, analog imperfections

MODULE 3 OF 4

Bode

FREQUENCY

Not a pitch shifter: shifts the entire spectrum by a fixed amount in Hz, creating metallic, inharmonic tones — with a built-in feedback delay.

- Frequency** How far (in Hz) the spectrum is shifted — the Range setting (six values, 200Hz–5000Hz) sets the knob's scale.
- Key Follow** The shift frequency tracks the pitch of the incoming note instead of staying at a fixed Hz value.
- Delay Time** The feedback loop's delay time; the BPM button syncs it to the DAW's tempo in musical values.
- Feedback** How much shifted/delayed signal feeds back into the loop — higher means more cascades and movement.
- Mix** Dry/wet between the original and the frequency-shifted signal.

Every module also has a **PAR** (Parallel) button: it isolates that module from the rest of the chain, so you hear it "clean" instead of reprocessed by whatever comes after it.

MODULE 4 OF 4

Flux

MORPH

Blends between two independently chosen algorithms — Algo A and Algo B — instead of picking just one, so you can morph continuously between two completely different textures.

Mix Crossfades between Algo A (0%) and Algo B (100%) — draggable directly on the display too.

Rate Tempo/speed control shared by whichever algorithm uses it (e.g. Tremolo) — syncs to the DAW's tempo.

Algo A / Algo B Pick any of the nine algorithms below independently for each side of the blend.

THE 9 ALGORITHMS

Sweep — auto-wah style filter motion

Tremolo — rhythmic amplitude pulsing

Resonator — tuned resonant ringing

Ring — ring modulation, metallic tones

Cloud — granular texture clouds

Doubler — thickens with a detuned voice

Flanger — classic sweeping comb filter

Shimmer — pitched-up reverb-like tail

Formant — vocal-like formant shifting

14 BUILT-IN PRESETS

A curated dropdown of Algo A/B combinations to start exploring from, each shown with its own accent color: Wah Pulse, Jet Sweep, Bell Swarm, Broken Radio, Grain Pad, Resonant Growl, Deep Cloud, Bell Resonance, Filter Choir, Slow Swirl, Ghost Pad, Halo Pad, Crystal Veil, Vocal Double.

ALWAYS ON

5-band EQ

The EQ never switches off — it's always active, which is why it has no on/off switch. Five bands: Low Cut and High Cut (with adjustable slope) plus three bells (frequency, gain, Q) — all draggable directly on the curve, with a live spectrum reference behind it and clearly readable frequency markers.

Pre / Post	The EQ works before or after the four modules — two independent settings, switch with one click.
Linear Phase	Switches the engine from a classic IIR filter to a linear-phase (FIR) one: more transparent, at the cost of some latency — with a built-in safety limiter that keeps sharp transients from ever overshooting.
Mix	Dry/wet for the whole EQ section — same neon indicator as Linear Phase when active.
Oversampling	Off / 2X / 4X — turn it up if you hear aliasing on the more aggressive saturation modes.

FINAL STAGE

Output

Input Gain	Sets the level before it enters the chain — useful for pushing the saturation modules harder (or softer).
Level	The plugin's output volume, shown against a segmented LED-style meter with peak-hold.
Soft Clip	Not a button — a light. It lights up when the safety limiter is working to keep the output under 0dBFS.

GETTING STARTED

Five practical tips

- 01 Start with **Mix at 100%** and Drive low: it's easier to judge a saturation's character when it isn't blended with the clean signal. Lower the Mix only after you've picked a mode.
- 02 Use **PAR (Parallel)** on a module to A/B the processed and original signal without leaving the plugin.
- 03 If an aggressive mode — Digital, Bitcrush, Hard Clip — sounds unpleasantly harsh, turn **Oversampling** up to 2X or 4X in the EQ before switching modes.
- 04 Module order matters: drag Noise before Saturation to have it distort along with the signal, or leave it after — with PAR on — to keep it clean and separate. Flux works the same way anywhere in the chain.
- 05 The red **SOFT CLIP** light isn't an error: it's the safety net that keeps you under 0dBFS on the way out, no matter what you do upstream.

IN ONE SENTENCE

Four modules to combine, an EQ that's always ready, an output that has your back: **explore without fear of breaking the signal.**