

# Comprehensive Data Science Documentation

**Prosenjit Mondol**

Data Scientist

[prosenjit1156@email.com](mailto:prosenjit1156@email.com)

August 13, 2025

## Contents

<b>1</b>	<b>Data Preprocessing</b>	<b>2</b>
<b>2</b>	<b>Handle Categorical Data</b>	<b>2</b>
2.1	Different Encoding Methods for Categorical Data . . . . .	2
2.2	Looking at null or missing values . . . . .	3
<b>3</b>	<b>Checking imbalanced in target variable</b>	<b>3</b>
<b>4</b>	<b>Outlier Detection</b>	<b>4</b>
<b>5</b>	<b>Let's see how it fared in prediction using Logistic Regression</b>	<b>5</b>
<b>6</b>	<b>Algorithms</b>	<b>6</b>
6.1	Simple Linear Regression . . . . .	6
<b>7</b>	<b>Models</b>	<b>6</b>
7.1	Ensemble Model . . . . .	6
7.2	SOTA Model . . . . .	6

## 1 Data Preprocessing

- [Sampling](#)  
Sampling techniques are used to select a representative subset of data from a large population to reduce the computational complexity and improve the efficiency of the analysis.
- [Transformation](#)  
Transformation techniques involve manipulating raw data to create a single input, such as scaling, normalization, or encoding categorical data.
- [Denoising](#)  
Denoising techniques remove unwanted noise from the data that can lead to inaccurate results.
- [Imputation](#)  
Imputation techniques are used to fill in missing values in the data using statistical methods.
- [Feature extraction](#)  
Feature extraction techniques help to identify and extract relevant features from the data that are significant in a particular context.
- [Normalization](#)  
Normalization techniques are used to organize data for more efficient access and processing.

## 2 Handle Categorical Data

Categorical data is a type of data that represents qualitative or nominal characteristics, such as gender, occupation, Categorical data cannot be measured or compared using mathematical operations like addition or subtraction.

### 2.1 Different Encoding Methods for Categorical Data

- [One-Hot Encoding](#)  
One-Hot Encoding creates a new binary column for each category.

Listing 1: Logistic Regression Example

```
X = pd.get_dummies(X)
print(X)
```

- [Label Encoding](#)  
Label Encoding assigns a numerical value to each category.

```
from sklearn.preprocessing import LabelEncoder

encoders = {}

for col in data[features].columns:
    encoders[col] = LabelEncoder()
    data[col] = encoders[col].fit_transform(data[col])

data[features].nunique()
```

- [Binary Encoding](#)  
Binary Encoding creates new columns representing each category.

## 2.2 Looking at null or missing values

- [Mean Imputation](#)  
Mean imputation is a simple and widely used method for filling in missing values.
- [Mode Imputation](#)  
Mode imputation is a method for filling in missing values that is similar to mean imputation, but instead of using the mean, it uses the mode of the available values in a column.
- [K-Nearest Neighbor \(KNN\) Imputation](#)  
KNN imputation is a method for filling in missing values that is based on the distance between data points.

Listing 2: Logistic Regression Example

```
# Multiple Imputation by Chained Equations
from sklearn.experimental import
    enable_iterative_imputer
from sklearn.impute import IterativeImputer

#mputed_data = df[numerical_columns].copy(deep=
    True)
mice_imputer = IterativeImputer()
data[numerical_columns] = mice_imputer.
    fit_transform(data[numerical_columns])
```

## 3 Checking imbalanced in target variable

- [Handling imbalanced data using oversampling](#)  
oversampling is a method for handling imbalanced data by increasing the size of the minority class.

Listing 3: Logistic Regression Example

```

from sklearn.utils import resample

no = normalized_data[normalized_data.RainTomorrow ==
0]
yes = normalized_data[normalized_data.RainTomorrow ==
1]
yes_oversampled = resample(yes, replace=True,
n_samples=len(no), random_state=123)
oversampled_data = pd.concat([no, yes_oversampled])

fig = plt.figure(figsize = (8,5))
sns.countplot(x='RainTomorrow', data =
oversampled_data, palette = "Set1").set(title='
RainTomorrow_Indicator_No(0)_and_Yes(1)_after_
Oversampling_(Balanced_Dataset)')

```

- [How multicollinearity affects decision trees](#)  
Multicollinearity affects decision trees by reducing the importance and accuracy of the input features.

Listing 4: Logistic Regression Example

```

#the heat map of the correlation
plt.figure(figsize=(16,10))
sns.heatmap(X.corr(), annot=True, cmap='RdYlGn')

```

## 4 Outliner Detection

- [Boxplot Method](#)  
One of the simplest and most popular methods for detecting outliers is the box-plot.

Listing 5: Logistic Regression Example

```

plt.figure(figsize=(50,25))
sns.boxplot(data=scaled_data[
numerical_features])

```

- [Z-Score Method](#)  
The Z-Score method is a simple and widely used method for detecting outliers.

Listing 6: Logistic Regression Example

```
from scipy import stats
import numpy as np

# Calculate Z-scores for each value in the numerical
# features
z_scores = np.abs(stats.zscore(scaled_data[
    numerical_features]))

# Identify outliers (e.g., Z-score > 3)
outliers = (z_scores > 3)

# Print rows with outliers
print(scaled_data[outliers.any(axis=1)])
```

- **Transformation**  
Transformation involves transforming the data to a different scale to reduce the impact of the outliers.

Listing 7: Logistic Regression Example

```
from sklearn.preprocessing import
    PowerTransformer
# Apply Power Transformation to the numerical
# features
power_transformer = PowerTransformer()
scaled_data[numerical_features] =
    power_transformer.fit_transform(
        scaled_data[numerical_features])
```

## 5 Let's see how it fared in prediction using Logistic Regression

Listing 8: Logistic Regression Example

```
# Train a logistic regression model on the training set
from sklearn.metrics import accuracy_score
from sklearn.linear_model import LogisticRegression

# Instantiate the model
logreg = LogisticRegression(solver='liblinear',
    random_state=0)
```

```
# Fit the model
logreg.fit(X_train, y_train)

# Predict on the test set
y_pred_test = logreg.predict(X_test)

print('Model accuracy score: {0:0.4f}'.format(
    accuracy_score(y_test, y_pred_test)))
```

## 6 Algorithms

### 6.1 Simple Linear Regression

## 7 Models

### 7.1 Ensemble Model

**Definition:**

An ensemble model in machine learning combines the predictions of multiple individual models (base estimators) to produce a more accurate and robust prediction than any single model alone.

### 7.2 SOTA Model

**Definition:**

In deep learning, SOTA model means State-of-the-Art model — basically, the best-performing architecture or method for a given task at a given time, according to benchmarks or competitions.