



ANDROID STATIC ANALYSIS REPORT



 X360 Mobile (0.5 public)

File Name:

X360_0.5_public.apk

Package Name:

emu.x360.mobile

Scan Date:

May 30, 2026, 8:33 p.m.

App Security Score:

60/100 (LOW RISK)

Grade:



 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
0	6	3	1	1

FILE INFORMATION

File Name: X360_0.5_public.apk
Size: 14.32MB
MD5: 3f36e2e501966aceafbde96896d0187d
SHA1: 64b61d4c5d4bc1c996984458f5e486214ebcc1b2
SHA256: 80fafc94e0be599fbc9065a694f2ce0c3bc92d140962870fdac26987f9838731

APP INFORMATION

App Name: X360 Mobile
Package Name: emu.x360.mobile
Main Activity: emu.x360.mobile.X360MobileDashboardActivity
Target SDK: 36
Min SDK: 30
Max SDK:
Android Version Name: 0.5 public
Android Version Code: 6

APP COMPONENTS

Activities: 4
Services: 0
Receivers: 0
Providers: 2
Exported Activities: 1
Exported Services: 0

Exported Receivers: 0
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=IT, O=X360Mobile, CN=Ashnar2602
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-05-20 20:58:49+00:00
Valid To: 2056-05-12 20:58:49+00:00
Issuer: C=IT, O=X360Mobile, CN=Ashnar2602
Serial Number: 0xca2455c8e4bd67f5
Hash Algorithm: sha256
md5: 906c6d11cffd3fe3e8ec7dfb237558c5
sha1: 698db904ef59d4f9f20ee26a561de2c70ffd9d8f
sha256: fa52f2df2c7002b55299e96583a1cc464cbf6e68b7788e018e220cb59fa34995
sha512: a089425dfc0f9ea01ccb1f2de22a94b05e163ca8a25be242b6087d30b261b6b2d753a640511f2e7e2346ed15280d3ebe7be46a6226eb8392c83af975c78db270
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 9dba38993c896872b2e5d510ec4d094172b1ff05a48bf123eb2276e828902d14
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.READ_EXTERNAL_STORAGE	dangerous	read external storage contents	Allows an application to read from external storage.
android.permission.WRITE_EXTERNAL_STORAGE	dangerous	read/modify/delete external storage contents	Allows an application to write to external storage.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.MANAGE_EXTERNAL_STORAGE	dangerous	Allows an application a broad access to external storage in scoped storage	Allows an application a broad access to external storage in scoped storage. Intended to be used by few apps that need to manage files on behalf of the users.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
emu.x360.mobile.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

 APKID ANALYSIS

FILE	DETAILS	
3f36e2e501966aceafbde96896d0187d.apk	FINDINGS	DETAILS
	Manipulator Found	Resources Confusion
classes.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check Build.BOARD check
	Compiler	unknown (please file detection issue!)

 BROWSABLE ACTIVITIES

ACTIVITY	INTENT
emu.x360.mobile.X360MobileGameLaunchActivity	Schemes: file://, content://, Hosts: *, Mime Types: */*, Path Patterns: .*\\.iso, .*\\.\\.iso, .*\\.\\.\\.iso, .*\\.xex, .*\\.\\.xex, .*\\.\\.\\.xex, .*\\.zar, .*\\.\\.zar, .*\\.\\.\\.zar, .*\\.xbla, .*\\.\\.xbla, .*\\.\\.\\.xbla,

 NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

 CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

 MANIFEST ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	Activity (emu.x360.mobile.X360MobileGameLaunchActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

</> CODE ANALYSIS

HIGH: 0 | WARNING: 4 | INFO: 3 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	B/AbstractActivityC0260m.java B/I.java B/J.java I/D0.java M1/e.java R1/AbstractC0797c9.java R1/AbstractC1004x.java R1/AbstractC1007x2.java R1/C0803d4.java R1/C0836g4.java R1/C0862i8.java R1/D5.java R1/E3.java R1/E8.java R1/H8.java R1/I9.java R1/L7.java R1/L8.java R1/N7.java R1/RunnableC0983u8.java R1/U8.java R1/X8.java T0/F.java b0/A.java b1/AbstractC0320a.java d1/AbstractC0368j.java d1/v.java emu/x360/mobile/X360MobileActivity.java emu/x360/mobile/X360MobileDashboardActivity.java emu/x360/mobile/X360MobileFileDialog.java emu/x360/mobile/X360MobileGameActivity.java h0/C0431a.java h0/v.java h1/i.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				h1/l.java org/libSDL/app/HIDDeviceBLESteamController.java
				org/libSDL/app/HIDDeviceManager.java org/libSDL/app/HIDDeviceUSB.java org/libSDL/app/SDLActivity.java org/libSDL/app/SDLAudioManager.java t1/AbstractC1212x.java
2	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	J1/a.java J1/b.java J1/c.java k1/a.java w/a.java
3	This app listens to Clipboard changes. Some malware also listen to Clipboard changes.	info	OWASP MASVS: MSTG-PLATFORM-4	org/libSDL/app/SDLClipboardHandler.java
4	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	T0/C1150h.java org/libSDL/app/SDLClipboardHandler.java
5	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	I/C0135h0.java R1/C0878k3.java
6	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	R1/C0862i8.java R1/I9.java R1/U1.java
7	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	R1/I9.java

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libhook_impl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libmain.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__fwrite_chk', '__fread_chk', '__vsprintf_chk', '__write_chk', '__read_chk', '__strlen_chk', '__pread_chk', '__pwrite_chk', '__strncpy_chk', '__strncpy_chk', '__vsprintf_chk', '__memmove_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__recvfrom_chk', '__sendto_chk', '__strchr_chk', '__strrchr_chk', '__strcpy_chk', '__strcat_chk', '__strncat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libmain_hook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libSDL2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', ['__strlen_chk', ['__strcpy_chk', ['__strcat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libhook_impl.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__read_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libmain.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memcpy_chk', '__memset_chk', '__fwrite_chk', '__fread_chk', '__vsprintf_chk', '__write_chk', '__read_chk', '__strlen_chk', '__pread_chk', '__pwrite_chk', '__strncpy_chk', '__strncpy_chk', '__vsprintf_chk', '__memmove_chk', '__FD_SET_chk', '__FD_ISSET_chk', '__recvfrom_chk', '__sendto_chk', '__strchr_chk', '__strrchr_chk', '__strcpy_chk', '__strcat_chk', '__strncat_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libmain_hook.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	arm64-v8a/libSDL2.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__memset_chk', '__strlen_chk', '__strcpy_chk', '__strcat_chk']	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00004	Get filename and put it to JSON object	file collection	R1/D6.java R1/I9.java R1/T0.java
00013	Read file and put it into a stream	file	A/AbstractC0226a.java M1/AbstractC0562d.java M1/C0559a.java M1/e.java M1/i.java R1/AbstractC0908n3.java R1/AbstractC1004x.java R1/C0971t6.java R1/H8.java R1/I9.java R1/J2.java R1/L8.java R1/S0.java R1/T0.java R1/T2.java d1/m.java
00072	Write HTTP input stream into a file	command network file	R1/E9.java R1/I9.java R1/L8.java h1/l.java
00089	Connect to a URL and receive input stream from the server	command network	R1/AbstractC0797c9.java R1/E9.java R1/H9.java R1/I9.java R1/L8.java h1/l.java
00030	Connect to the remote server through the given URL	network	R1/AbstractC0797c9.java R1/E9.java R1/H9.java h1/l.java

RULE ID	BEHAVIOUR	LABEL	FILES
00109	Connect to a URL and get the response code	network command	R1/AbstractC0797c9.java R1/E9.java R1/H9.java R1/I9.java R1/L8.java h1/I.java
00022	Open a file from given absolute path of the file	file	C0/p.java F/C0081k.java R0/h.java R1/AbstractC1004x.java R1/C0862i8.java R1/C0970t5.java R1/C0975u0.java R1/C0994w.java R1/C1000w5.java R1/D8.java R1/E3.java R1/I9.java R1/N7.java R1/P4.java R1/Q1.java R1/R1.java R1/R4.java R1/RunnableC0997w2.java R1/S0.java R1/S1.java R1/S3.java R1/T0.java R1/U1.java R1/U4.java R1/W7.java R1/y9.java d/O.java emu/x360/mobile/X360MobileActivity.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	emu/x360/mobile/X360MobileActivity.java emu/x360/mobile/X360MobileGameActivity.java emu/x360/mobile/X360MobileGameLaunchActivity.java org/libSDL/app/SDLActivity.java

RULE ID	BEHAVIOUR	LABEL	FILES
00191	Get messages in the SMS inbox	sms	emu/x360/mobile/X360MobileContentResolverBridge.java emu/x360/mobile/X360MobileGameLaunchActivity.java
00014	Read file into a stream and put it into a JSON object	file	R1/C0971t6.java R1/I9.java R1/T0.java
00121	Create a directory	file command	emu/x360/mobile/X360MobileActivity.java
00036	Get resource file from res/raw directory	reflection	emu/x360/mobile/X360MobileActivity.java org/libSDL/app/SDLActivity.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	org/libSDL/app/SDLActivity.java
00012	Read data and put it into a buffer stream	file	R1/H8.java R1/I9.java
00005	Get absolute path of file and put it to JSON object	file	R1/I9.java R1/T0.java
00015	Put buffer stream (data) to JSON object	file	R1/I9.java
00096	Connect to a URL and set request method	command network	R1/I9.java
00094	Connect to a URL and read data from it	command network	R1/I9.java R1/L8.java
00108	Read the input stream from given URL	network command	R1/I9.java R1/L8.java
00189	Get the content of a SMS message	sms	emu/x360/mobile/X360MobileContentResolverBridge.java
00188	Get the address of a SMS message	sms	emu/x360/mobile/X360MobileContentResolverBridge.java
00011	Query data from URI (SMS, CALLLOGS)	sms calllog collection	emu/x360/mobile/X360MobileContentResolverBridge.java

RULE ID	BEHAVIOUR	LABEL	FILES
00200	Query data from the contact list	collection contact	emu/x360/mobile/X360MobileContentResolverBridge.java
00187	Query a URI and check the result	collection sms callog calendar	emu/x360/mobile/X360MobileContentResolverBridge.java
00201	Query data from the call log	collection callog	emu/x360/mobile/X360MobileContentResolverBridge.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms callog calendar	emu/x360/mobile/X360MobileContentResolverBridge.java

🚫 ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	3/25	android.permission.READ_EXTERNAL_STORAGE, android.permission.WRITE_EXTERNAL_STORAGE, android.permission.INTERNET
Other Common Permissions	0/44	

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.121.4 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
issuetracker.google.com	ok	IP: 142.251.27.102 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
api.thegamesdb.net	ok	IP: 65.109.25.83 Country: United States of America Region: Massachusetts City: Andover Latitude: 42.648373 Longitude: -71.161453 View: Google Map
android.googlesource.com	ok	IP: 142.251.127.82 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
goo.gle	ok	IP: 67.199.248.12 Country: United States of America Region: New York City: New York City Latitude: 40.739288 Longitude: -73.984955 View: Google Map
api.github.com	ok	IP: 140.82.121.6 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
schemas.android.com	ok	No Geolocation information available.
x360-log-relay.vercel.app	ok	IP: 64.29.17.67 Country: Canada Region: Ontario City: Etobicoke Latitude: 43.623768 Longitude: -79.559723 View: Google Map
xenia.jp	ok	IP: 185.199.110.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map



EMAIL	FILE
+d@a-.dm	apktool_out/lib/arm64-v8a/libmain.so
+d@a-.dm	lib/arm64-v8a/libmain.so

HARDCODED SECRETS

POSSIBLE SECRETS
100F6C34-1735-4313-B402-38567131E5F3
5246dd1c14c2fce7a1c85ad77d3aa348ca350fe62337abddf7f2c6f758004626
100F6C32-1735-4313-B402-38567131E5F3
100F6C33-1735-4313-B402-38567131E5F3

SCAN LOGS

Timestamp	Event	Error
2026-05-30 20:33:47	Generating Hashes	OK
2026-05-30 20:33:47	Extracting APK	OK
2026-05-30 20:33:47	Unzipping	OK

2026-05-30 20:33:47	Parsing APK with androguard	OK
2026-05-30 20:33:48	Extracting APK features using aapt/aapt2	OK
2026-05-30 20:33:49	Getting Hardcoded Certificates/Keystores	OK
2026-05-30 20:33:50	Parsing AndroidManifest.xml	OK
2026-05-30 20:33:50	Extracting Manifest Data	OK
2026-05-30 20:33:50	Manifest Analysis Started	OK
2026-05-30 20:33:50	Performing Static Analysis on: X360 Mobile (emu.x360.mobile)	OK
2026-05-30 20:33:52	Fetching Details from Play Store: emu.x360.mobile	OK
2026-05-30 20:33:52	Checking for Malware Permissions	OK
2026-05-30 20:33:52	Fetching icon path	OK
2026-05-30 20:33:52	Library Binary Analysis Started	OK
2026-05-30 20:33:52	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK

2026-05-30 20:33:52	Analyzing apktool_out/lib/arm64-v8a/libhook_impl.so	OK
2026-05-30 20:33:52	Analyzing apktool_out/lib/arm64-v8a/libmain.so	OK
2026-05-30 20:33:52	Analyzing apktool_out/lib/arm64-v8a/libmain_hook.so	OK
2026-05-30 20:33:52	Analyzing apktool_out/lib/arm64-v8a/libSDL2.so	OK
2026-05-30 20:33:52	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-05-30 20:33:52	Analyzing lib/arm64-v8a/libhook_impl.so	OK
2026-05-30 20:33:52	Analyzing lib/arm64-v8a/libmain.so	OK
2026-05-30 20:33:53	Analyzing lib/arm64-v8a/libmain_hook.so	OK
2026-05-30 20:33:53	Analyzing lib/arm64-v8a/libSDL2.so	OK
2026-05-30 20:33:53	Reading Code Signing Certificate	OK
2026-05-30 20:33:53	Running APKiD 3.1.0	OK
2026-05-30 20:33:55	Detecting Trackers	OK

2026-05-30 20:33:56	Decompiling APK to Java with JADX	OK
2026-05-30 20:34:02	Converting DEX to Smali	OK
2026-05-30 20:34:02	Code Analysis Started on - java_source	OK
2026-05-30 20:34:03	Android SBOM Analysis Completed	OK
2026-05-30 20:34:05	Android SAST Completed	OK
2026-05-30 20:34:05	Android API Analysis Started	OK
2026-05-30 20:34:07	Android API Analysis Completed	OK
2026-05-30 20:34:07	Android Permission Mapping Started	OK
2026-05-30 20:34:08	Android Permission Mapping Completed	OK
2026-05-30 20:34:09	Android Behaviour Analysis Started	OK
2026-05-30 20:34:11	Android Behaviour Analysis Completed	OK
2026-05-30 20:34:11	Extracting Emails and URLs from Source Code	OK

2026-05-30 20:34:13	Email and URL Extraction Completed	OK
2026-05-30 20:34:13	Extracting String data from APK	OK
2026-05-30 20:34:13	Extracting String data from SO	OK
2026-05-30 20:34:13	Extracting String data from Code	OK
2026-05-30 20:34:13	Extracting String values and entropies from Code	OK
2026-05-30 20:34:14	Performing Malware check on extracted domains	OK
2026-05-30 20:34:17	Saving to Database	OK

Report Generated by - MobSF v4.4.5

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).