Level 1 Semantic and Epistemic Governance: Ontology Changes and Evidential Warrant

Timothy O'Brien[1]

Abstract

An ontology amendment can satisfy its visible task while expanding a protected permission. A review can also reach the right conclusion for the wrong reason by trusting ineligible or dependent sources. We evaluate these two problems in a compositional development study with six hosted model configurations. Each model receives the same 48 semantic cases and 96 epistemic packets, plus six separate interface checks. Semantic cases combine two to five edits, 32–96 classes and two to four protected permissions. Epistemic packets combine scoped delegation, revocation, stale reports, shared provenance and conflicting evidence; multiple consistent interpretations and tied optimal follow-up checks are accepted. Independent finite references score complete answers, release decisions, evidence support and the next useful observation. With one fresh judgment per case, requested medium reasoning effort and a 32,768-token combined reasoning/output allowance, strict semantic correctness ranges from 0/48 to 48/48 and strict epistemic correctness from 2/96 to 95/96. Qwen achieves 45/48 semantic and 40/96 epistemic complete answers; Sol achieves 48/48 and 95/96. Allowing only an outer code fence materially changes Sonnet and Haiku scores, so format compliance and component correctness are reported separately. No completed model reaches the token allowance. The results distinguish applying ontology rules from judging what incomplete or disputed evidence warrants. They are descriptive measurements on inspected development material, not a held-out model ranking, a test of real source reliability or evidence of general agent containment.

Keywords: ontology evolution, semantic governance, epistemic governance, authorization, large language models, formal verification

1. Introduction

A reviewer of an ontology change has to answer two different questions. First, what does the change actually do? Second, what does the available evidence justify believing about it? We call the first problem semantic governance and the second epistemic governance. A model can succeed at one and fail at the other.

Consider a classification that grants permission for an operation. Adding an intermediate class edge can make that permission available to a previously ineligible starting profile, even when the permission rule itself is unchanged. Our tests evaluate whether an LLM identifies such consequences under a fixed finite contract.

Evidence introduces a separate failure path. Another agent, a tool or a memory record may claim that the change is safe. The source might lack authority for the par-

Level 1 working research draft, revised 18 October 2026. Not peer reviewed. Copyright 2026 Timothy O'Brien. Licensed under CC BY 4.0.

[1]ORCID: 0009-0001-2589-347X. Independent researcher; no institutional affiliation.

ticular claim, rely on an expired delegation, or repeat the same observation as several other sources. Even eligible, independent reports can disagree. A useful reviewer must distinguish a supported conclusion from a plausible guess, retain facts unaffected by a disagreement, and identify what should be checked next.

This paper reports the fixed Level 1 compositional corpus, which combines these dependencies rather than testing one mechanism at a time. Six hosted configurations complete the same semantic and epistemic development sets. The main comparisons include every configuration evaluated on these sets. The tracks remain separate: semantic calls receive a complete ontology and fixed batch of amendments; epistemic calls receive structured evidence about release conditions under a declared authority policy. Neither track is an autonomous agent carrying out real operations.

We ask whether models can identify joint permission effects, use scoped and independent evidence correctly, distinguish denial from insufficient evidence, and select a useful follow-up observation. We measure each component as well as complete answers. The current study uses one judgment per case without correction feedback.

This paper contributes a fixed compositional corpus and explicit scoring contract, two separately implemented finite references accepting alternative valid answers, and an offline-replayable six-configuration development study separating complete answers, components and delivery failures. The historical correction and source-evidence studies are supporting cohorts with distinct protocols; they are not pooled with the current first-judgment results.

2. Related work

Ontology policies, policy change analysis and consequence preservation are established topics. KAoS and Margrave analyze formal policies; logical difference and conservative extension compare ontology consequences across versions [1–4]. Our finite exhaustive reference applies established principles to supplied batches of ontology changes rather than introducing a new preservation theorem.

External enforcement also predates this study. Ontology-to-tools compilation and PCAS connect formal policy to executable interfaces, while CaMeL and MemLineage separate trusted control or provenance from untrusted content [5, 6, 17, 18]. Recent proposals for version-bound authority and commit-time checking include Authorization Closure Graph, Governed Deduction, Authority at Commit Time and ontology-contract work [10–13]. We evaluate model recommendations against an explicit contract; we do not demonstrate a deployed reference monitor or general agent containment.

Context sufficiency, abstention and conflicting memory are established evaluation concerns [14–16]. Repair-based reasoning supplies ways to preserve consistent alternatives when evidence conflicts; provenance and epistemic-cue studies further limit broad novelty claims [19–21]. Here the contribution is an executable connection between those concerns and ontology-amendment review, including source admission, permission effects, legitimate alternative interpretations and follow-up checks.

Neurosymbolic deduction and tool-assisted correction have substantial prior art [7, 8]. The latest experiment does not provide correction or reference facts to evaluation models. Unlike preference-based LLM judging [9], its answers are checked against separately reconstructed finite references. The objective is a transparent diagnostic study, not a new general theory of governance.

3. Current evaluation and review contract

3.1. Cases and measurements

The full constructed material contains 96 semantic cases and 144 epistemic packets, split into training and development material. Every model in the main study receives all 48 semantic development cases and all 96 epistemic development packets. Six additional training cases, one per track and tier, check interface delivery. Thus there are 150 saved observations per model and 900 across the six completed configurations; the six interface checks are excluded from accuracy denominators. No held-out test set has been sampled.

Semantic cases are grouped into three tiers of sixteen development cases. Epistemic cases contain twelve development units, each with four matched authority/provenance conditions and two presentation orders, giving 96 packets and 224 action decisions. The same units recur in matched variants, so packets and actions are not independent samples. Tiers change several features together; their order is not a validated monotonic difficulty scale.

3.2. What an ontology change may and may not do

An ontology is a set of classifications and rules. A rule such as "A implies B" lets the checker derive B from A. A conjunction requires all its inputs, such as "A and B imply C." A starting profile lists the input properties initially present. Helper classifications must be reached through the rules rather than asserted as starting facts.

The review contract fixes the vocabulary, starting profiles, requested goals, protected permissions and task scope. A candidate is a supplied batch of rule or classification changes. The model judges that entire batch; it is not restricted to proposing one edge. The candidate must pass every requested positive and negative check. A negative check asks whether a classification is absent from the derived facts, rather than asserting a new logical negation.

Conflicting classifications have an explicit operational consequence. The checker retains the facts it has derived, but grants no effective permissions to a profile containing a forbidden pair. Removing a conflict can therefore create effective access even if the permission was already present among the raw derived facts. A contradiction does not make every statement true in this implementation.

A protected permission expands when at least one permitted starting profile gains it after the batch. Every expansion needs its own applicable approval. A registry record must match the original and candidate versions, contract, task scope, permission, semantics and policy; fragments of different records cannot be combined into an approval. A change may be released only when every goal passes and every protected expansion has a matching approval. Approval cannot repair a failed goal. Model recommendations do not themselves perform a release.

4. Semantic and epistemic test construction

This section describes the current compositional development corpus. Semantic cases test the effects of interacting changes; epistemic packets test which conclusions are warranted by scoped, dependent or conflicting reports. The two tracks are separate abstractions; a combined end-to-end agent evaluation has not been run.

4.1. Larger semantic amendments

The full constructed semantic corpus contains 96 cases, divided equally between training and development, with three size levels (Table 1). It asks the model to judge a group of edits together. Some groups create a new permission even though no individual edit does; others add one protected permission while leaving another unchanged. Other cases remove a conflict, preserve a blocking conflict, or achieve one requested goal while failing another. The checker tests each edit separately as well as the complete group to identify these interactions. If an edit cannot be applied by itself, that diagnostic is marked unavailable rather than counted as harmless. Approval is checked separately for every protected permission.

Table 1: Constructed corpus complexity, not model scores. Each tier contains 32 semantic cases (16 TRAIN, 16 DEV) and 48 epistemic packets (16 TRAIN, 32 DEV).

Property	Tier 1	Tier 2	Tier 3
Semantic classes	32	64	96
Public seed classes	8	10	12
Profiles checked per version	256	1,024	4,096
Edits per batch	2–3	3–4	4–5
Protected permissions	2	3	4
Epistemic Boolean atoms	8	10	12
Reports per packet	29–33	35–39	47–53
Separate release decisions	2	2	3

Two separate algorithms agree on all 172,032 before-and-after profile comparisons. One applies rules to sets of facts; the other computes results for many profiles together using bitsets. They compare every declared classification, permission and consistency result. The model must identify each protected permission that expands and give a starting profile demonstrating the gain. Any valid example receives credit; it need not be the first or smallest one found by the checker. The comparison remains limited to the declared input vocabulary.

4.2. Competing evidence and multiple valid answers

The full constructed epistemic artifact contains 144 packets from 18 units. Each unit has four matched authority/provenance conditions and two presentation orders. Within each unit, a single grant revocation and specified provenance-parent changes form a two-by-two intervention. Claim content and identifiers stay fixed. Six units are training material and twelve are development; no held-out test units have been sampled.

In the epistemic task, permission to report is checked for each fact and each amendment under review. A source can therefore be authorized for one claim but not another, or current for one amendment but stale for another. Reports also identify the earlier observations they rely on. Following these links produces a provenance graph: a record of where the information came from.

To establish a fact, this version requires two or three eligible reports whose original observations do not overlap. Different speakers are not enough. Two apparently separate reports may share part of their evidence and therefore fail the independence requirement. The broker supplies these relationships and authentication facts; the model must apply them correctly.

The evidence policy handles a disagreement without automatically discarding everything else in the packet. It keeps every consistent selection of supported facts to which no further supported fact can be added without breaking the fixed constraints. Such a selection is called a *repair*. "Maximal" means nothing more can be added consistently; it does not mean choosing the selection containing the most facts. Claims are considered separately, so different statements in one report can receive different treatment.

For each repair, the checker considers every possible value of the facts it leaves unsettled, subject to the packet's fixed constraints. Release is justified only if all those possibilities, across all repairs, allow it. Denial is justified only if all deny it. Otherwise the answer is undetermined. The model may return any valid repair as an example, but it must consider the alternatives when deciding whether release is justified.

For example, equally authorized and independently corroborated sources can disagree about a required goal. Either consistent evidence interpretation may be valid, while approval remains unestablished across them. An unrelated disagreement need not erase a decisive failed goal for another release. The implemented corpus has multiple valid repairs in 136 of 144 packets, including cases with incomparable repairs of different sizes. This is controlled ambiguity under explicit rules, not permission to approve or deny arbitrarily.

4.3. A small example with two valid evidence interpretations

The following four-fact example illustrates the evidence policy. It is not one of the 144 corpus packets and has not been sent to a model. Its answers are checked by both reference implementations. To keep the illustration small, one current authorized report is enough to support a claim; the generated development packets require two or three independent reports. Disagreements are handled through alternative consistent interpretations.

Suppose a proposal is being reviewed for two requested tasks, A and B. Both reviews depend on the same question about protected permission. An authorized report states that task A's goal passed, task B's goal failed, no exact approval exists, and the proposal creates no new protected permission. A second equally authorized report supplies one observation: it says the proposal *does* create a new protected permission. Both reports are current. Neither source has priority over the other.

Only the permission claim is disputed. The three undisputed facts remain usable in either interpretation. Table 2 shows the two complete consistent choices. Both receive full credit as an evidence interpretation. Choosing the favorable one, however, does not establish that task A may proceed: the other valid interpretation reaches the opposite conclusion. Task B must be denied in either interpretation because its goal failed.

Table 2: Two valid interpretations in the illustrative development example. A failed goal remains decisive despite the separate permission dispute.

Evidence interpretation	Task A	Task B
Keep the claim that permission does not expand	Allow	Deny
Keep the claim that permission expands	Deny	Deny
Conclusion justified across both	Undetermined	Deny

The next useful check is to establish whether permission actually expands. That settles task A while task B remains denied. Rechecking approval would repeat an already

settled fact. In the verified illustration, checking expansion costs one unit, checking approval costs one, and checking both costs two. The reference therefore selects the expansion check: it resolves the remaining decision at the lower cost. This example tests three separate abilities—retaining undisputed evidence, recognizing legitimate alternatives, and choosing a useful follow-up—without requiring the model to invent a credibility ranking.

4.4. Choosing the next observation and measuring shortcuts

The model is also asked what it should check next. The packet offers a menu of reliable follow-up checks, each with a stated cost. To compare them, the checker considers every answer a check could return under the current evidence. After each possible answer, it counts how many release decisions would still be unresolved. A check is judged by its least helpful possible outcome: the largest remaining count. The preferred check has the lowest such count; when counts tie, the lower cost wins. Any check tied on both receives credit.

These hypothetical observations narrow the existing set of possibilities; they do not rebuild the evidence interpretations. This is a one-step choice about the next useful observation. It does not assume probabilities for the alternatives or find the cheapest complete investigation.

Two separately written checkers agree on all 144 packets. One starts from possible consistent selections of evidence; the other starts from possible assignments of true and false to the facts. Rule baselines over all 144 constructed packets (TRAIN and DEV together) illustrate why separate scores matter: always-undetermined and blanket conflict quarantine each correctly classify 124 of 336 action decisions (36.9%); choosing one arbitrary repair yields 260/336 (77.4%); and treating reports as independent yields 268/336 (79.8%). These are deterministic ablations, not measured LLM results. Packets share units and presentation twins, so these action counts are descriptive and not independent trials.

The evaluation separates supported-fact accuracy, valid repair certificates, warranted decisions, possible outcomes, unsupported approvals, unnecessary abstention, optimal-query membership and query regret. Matched changes measure whether models respond to a genuine change in authority or independence; presentation twins measure invariance when the evidence is unchanged. Each hosted evaluation freezes its cases, requests, parser, provider settings and budget before inference. Fresh test units and held-out mechanism combinations remain future work. A consistent lie from an authorized, sufficiently corroborated source remains outside what this evidence contract alone can detect.

5. Model calls, output contracts and scoring

5.1. What the model receives

Every call has a system message and one user message. There is no preceding conversation or earlier answer. The semantic system message states how to apply all changes, derive consequences, check conflicts, compare protected permissions and match approvals. Its user message is a structured JSON packet containing the contract and base ontology, requested goals, proposed batch, trusted approval registry and current version bindings. Construction-family names, reference answers and checker witnesses are withheld.

The epistemic system message says that source payloads cannot change the immutable policy and that the answer performs no actual release. The user message gives the complete evidence rules followed by a JSON packet of Boolean claims, authority grants,

current versions, reports, provenance links, consistency constraints, proposed actions and offered follow-up queries with costs. The model receives the evidence it must assess, not the reference's supported facts, selected repairs or possible worlds. Source identity, authentication and provenance are supplied simulator facts rather than discoveries the model makes about real systems.

The semantic output contains goal correctness, the complete set of expanding permissions, approval and authorization maps, release eligibility and one valid example profile for each expansion. The epistemic output contains supported facts, one valid consistent interpretation, the warranted decision for each action, all possible release outcomes, and the next query or an explicit null. A response may use any valid witness or repair and any tied optimal query. The fixed decision rule still determines whether each action is allowed, denied or undetermined. Literal instructions for these current tasks appear in Appendix Appendix A.

5.2. Configurations and inference settings

Here medium is the requested native API effort setting, not a measured amount of reasoning or a problem-difficulty tier. The token allowance covers reasoning and final output together; equal labels do not imply equal compute across providers.

All six configurations use OpenRouter with a pinned provider, no fallback, medium native reasoning and a 32,768-token combined reasoning/output allowance. They receive identical task prompts and development cases. Qwen uses temperature zero; the OpenAI and Anthropic endpoints omit temperature because they do not advertise that parameter. There is no API response-format constraint: JSON is requested by the prompt. Four requests run concurrently per model. Requested effort and token allowance do not establish equal compute across models.

Table 3: Requested medium reasoning; 32,768 combined reasoning/output tokens. All configurations evaluated on the current 48 semantic and 96 epistemic cases. Every row has six additional interface observations, kept out of performance denominators.

Configuration	OpenRouter model identifier	Provider
GPT-6.1-Sol	`openai/gpt-6.1-sol`	OpenAI
GPT-5.6-Terra	`openai/gpt-5.6-terra`	OpenAI
Qwen3.8-27B	`qwen/qwen3.8-27b`	Chutes FP8
GPT-6-Luna	`openai/gpt-6-luna`	OpenAI
Sonnet-5.5	`anthropic/claude-sonnet-5.5`	Anthropic
Haiku-5.5	`anthropic/claude-haiku-5.5`	Anthropic

Each development call is a fresh full-task judgment. There is no checker feedback, reflection stage, component assistance or retry to improve a wrong answer. Identical retries are allowed only for prespecified transient transport failures, with all attempts retained. Interface delivery gates and the recorded Sonnet/Haiku amendments concern delivery and framing, not answer correctness; their details remain in the audit record and results section.

5.3. What counts as correct

The primary score requires a bare JSON object with the complete typed schema. A separate sensitivity removes only a sole outer code fence. Neither parser extracts an

answer from prose or repairs its contents. Missing, malformed, schema-invalid, provider-error and token-limited outputs remain in the denominator. A valid undetermined answer is different from a missing answer.

Complete semantic correctness requires all output components, including valid expansion witnesses. Complete epistemic correctness requires the supported facts, a valid repair, every decision, all possible outcomes and an optimal next check. We also report each component and per-action correctness. In particular, approving an action that the evidence denies is different from approving one for which evidence is insufficient. An unsupported approval need not mean the hidden amendment is actually forbidden.

Two separately implemented references agree on the semantic profile comparisons and on all constructed epistemic packets. Native request and response hashes, source snapshots, final outputs, exposed reasoning, provider identity, usage and attempts are independently reconstructed before reporting. Software agreement verifies the implemented reference, not the truth or completeness of a real-world authority policy. Shared units, inspected development cases and differing provider behavior prevent a held-out or equal-compute ranking.

6. Six-model comparative results

All six configurations completed the same development material under the protocol in Section 5. Table 4 compares complete answers by track and parser. Each model has 150 independently reconstructed observations; only the 48 semantic and 96 epistemic development cases enter these accuracy scores. The rows are ordered by semantic strict complete-answer accuracy, with ties retained. No overall score pools the two tracks.

Table 4: Requested medium reasoning; 32,768 combined reasoning/output tokens. Completed full development evaluations, ordered by semantic strict complete-answer accuracy. Sole-fence columns remove only an outer code fence, without prose extraction or interior repair.

	Semantic (/48)		Epistemic (/96)	
Model	Strict	Sole fence	Strict	Sole fence
GPT-6.1-Sol	48/48 (100.0%)	48/48 (100.0%)	95/96 (99.0%)	95/96 (99.0%)
GPT-5.6-Terra	45/48 (93.8%)	45/48 (93.8%)	45/96 (46.9%)	45/96 (46.9%)
Qwen3.8-27B	45/48 (93.8%)	46/48 (95.8%)	40/96 (41.7%)	44/96 (45.8%)
GPT-6-Luna	32/48 (66.7%)	32/48 (66.7%)	26/96 (27.1%)	26/96 (27.1%)
Sonnet-5.5	17/48 (35.4%)	17/48 (35.4%)	72/96 (75.0%)	83/96 (86.5%)
Haiku-5.5	0/48 (0.0%)	23/48 (47.9%)	2/96 (2.1%)	69/96 (71.9%)

6.1. Semantic judgment components

Table 6 separates checking goals, identifying the complete permission-expansion set, supplying valid expansion witnesses, matching approvals and recommending release. Every cell uses all 48 semantic cases and the primary parser. A correct release recommendation alone is less demanding than a complete answer; an unparseable output receives no component credit.

6.2. Performance by tier and epistemic component

The tier comparison in Figure 2 asks whether performance changes as larger rule sets and more interacting evidence mechanisms are introduced. It does not show a uniform decline: tiers vary several features together, and some later-tier cases are easier for a given configuration. We therefore report their actual scores rather than treating tier number as a validated difficulty scale.




Figure 1: Requested medium reasoning; 32,768 combined reasoning/output tokens. Completed compositional development evaluations. Blue bars require strict bare JSON; orange bars remove only a sole outer code fence. All other failures remain in the denominators. Model order follows semantic strict accuracy for display only; tracks are not pooled. Opus is excluded because provider filtering prevented development evaluation.

Table 5: Requested medium reasoning; 32,768 combined reasoning/output tokens. Complete-answer accuracy by development tier. Strict scores retain every format failure. Where sole-fence normalization changes overall correctness, its tier scores are also shown. Shared units and matched variants are correlated observations.

Configuration, track and parser	Tier 1	Tier 2	Tier 3
GPT-6.1-Sol, semantic, strict	16/16 (100.0%)	16/16 (100.0%)	16/16 (100.0%)
GPT-6.1-Sol, epistemic, strict	32/32 (100.0%)	32/32 (100.0%)	31/32 (96.9%)
GPT-5.6-Terra, semantic, strict	15/16 (93.8%)	15/16 (93.8%)	15/16 (93.8%)
GPT-5.6-Terra, epistemic, strict	13/32 (40.6%)	17/32 (53.1%)	15/32 (46.9%)
Qwen3.8-27B, semantic, strict	16/16 (100.0%)	15/16 (93.8%)	14/16 (87.5%)
Qwen3.8-27B, semantic, fence	16/16 (100.0%)	15/16 (93.8%)	15/16 (93.8%)
Qwen3.8-27B, epistemic, strict	13/32 (40.6%)	13/32 (40.6%)	14/32 (43.8%)
Qwen3.8-27B, epistemic, fence	17/32 (53.1%)	13/32 (40.6%)	14/32 (43.8%)
GPT-6-Luna, semantic, strict	12/16 (75.0%)	7/16 (43.8%)	13/16 (81.2%)
GPT-6-Luna, epistemic, strict	9/32 (28.1%)	7/32 (21.9%)	10/32 (31.2%)
Sonnet-5.5, semantic, strict	6/16 (37.5%)	6/16 (37.5%)	5/16 (31.2%)
Sonnet-5.5, epistemic, strict	23/32 (71.9%)	25/32 (78.1%)	24/32 (75.0%)
Sonnet-5.5, epistemic, fence	27/32 (84.4%)	27/32 (84.4%)	29/32 (90.6%)
Haiku-5.5, semantic, strict	0/16 (0.0%)	0/16 (0.0%)	0/16 (0.0%)
Haiku-5.5, semantic, fence	9/16 (56.2%)	7/16 (43.8%)	7/16 (43.8%)
Haiku-5.5, epistemic, strict	0/32 (0.0%)	1/32 (3.1%)	1/32 (3.1%)
Haiku-5.5, epistemic, fence	20/32 (62.5%)	23/32 (71.9%)	26/32 (81.2%)

Table 6: Requested medium reasoning; 32,768 combined reasoning/output tokens. Semantic components across all six configurations, with strict parsing. Expansion and witness columns require the entire permission set or witness map to be correct; empty maps receive credit when appropriate.

Model	All goals	Expansion set	Witnesses	Approval matches	Release
GPT-6.1-Sol	48/48 (100.0%)	48/48 (100.0%)	48/48 (100.0%)	48/48 (100.0%)	48/48 (100.0%)
GPT-5.6-Terra	46/48 (95.8%)	48/48 (100.0%)	47/48 (97.9%)	48/48 (100.0%)	47/48 (97.9%)
Qwen3.8-27B	47/48 (97.9%)	46/48 (95.8%)	46/48 (95.8%)	46/48 (95.8%)	47/48 (97.9%)
GPT-6-Luna	35/48 (72.9%)	40/48 (83.3%)	39/48 (81.2%)	48/48 (100.0%)	41/48 (85.4%)
Sonnet-5.5	17/48 (35.4%)	17/48 (35.4%)	17/48 (35.4%)	17/48 (35.4%)	17/48 (35.4%)
Haiku-5.5	0/48 (0.0%)	0/48 (0.0%)	0/48 (0.0%)	0/48 (0.0%)	0/48 (0.0%)

Figure 3 separates five questions within each epistemic answer: which facts have adequate support, which consistent interpretation is valid, what each action warrants, which release outcomes remain possible, and which offered observation would help most. A packet counts as correct for a component only when that whole component is correct. These are components of each original unaided answer; no verified intermediate facts or possible worlds are supplied. High action accuracy can coexist with mistakes about the evidence or the best next step.




Figure 2: Requested medium reasoning; 32,768 combined reasoning/output tokens. Full-answer correctness across the three development tiers, accepting only a sole outer code fence. All remaining formatting, provider and reasoning failures stay in the denominators. Lines connect summaries of different cases, not repeated corrections. Tiers combine size and mechanism changes; their ordering is not an empirically calibrated difficulty scale.

Sol answered all 48 semantic problems and 95 of 96 epistemic packets completely correctly. Terra and Luna had no parsing or token-limit failures, but their complete epistemic answers were correct in 45/96 and 26/96 cases respectively. This variation shows why final release advice, source admission, evidence alternatives and the next useful check should be measured separately. It does not establish that a general notion of model power causes greater reliability. The near-ceiling Sol result also limits claims that this development corpus is a difficult frontier benchmark.

Qwen solves 45/48 semantic problems completely under strict parsing, but only 40/96 epistemic packets. Allowing a sole outer code fence changes these counts to 46/48 and 44/96. Its semantic release decisions are correct on 47/48 cases; complete semantic correctness additionally requires a valid witness wherever an expansion is claimed. The epistemic gap persists after the small framing adjustment, so it cannot be explained by code fences alone. Under strict scoring, Qwen identifies every supported fact correctly in 50/96 packets, selects a valid repair in 52/96, gives all action decisions correctly in 67/96, and chooses an optimal next check in 67/96. It approves seven actions whose evidence leaves release undetermined and none of the 112 warranted-denial actions. An unsupported approval is a claim beyond the available evidence, not proof that the underlying amendment is forbidden. Qwen has no token-limit or provider-error finish.

Sonnet's semantic score needs a different explanation: 31 of 48 outputs were prose rather than the required JSON, and they remain primary failures. This is not evidence




Figure 3: Requested medium reasoning; 32,768 combined reasoning/output tokens. Where full-task epistemic answers succeed or fail. Each point is the percentage of all 96 packets correct for one component, accepting only a sole outer fence. All decisions must be correct within a packet; this differs from per-action accuracy. Repairs and next checks accept every valid or tied-optimal answer. No verified facts or completions are supplied to these full-task calls.

of 31 incorrect semantic arguments. Twelve epistemic outputs also failed strict parsing; eleven become complete correct answers after removing a sole outer fence. Its complete epistemic score consequently changes from 72/96 to 83/96 under the declared sensitivity. No completed configuration reached the output cap. Haiku returned one provider-overloaded error, which remains in every relevant denominator and is not classified as a reasoning error. Format compliance and reasoning correctness must therefore remain distinguishable.

Table 7: Requested medium reasoning; 32,768 combined reasoning/output tokens. Epistemic components for all six current configurations. Each cell counts whole packets correct out of 96, accepting only a sole outer fence. All decisions must be correct within a packet; repairs and queries accept every valid or tied optimal answer. These are components of unaided full-task answers.

Model	Supported facts	Valid repair	All decisions	Possible outcomes	Next check
GPT-6.1-Sol	95/96 (99.0%)	95/96 (99.0%)	96/96 (100.0%)	96/96 (100.0%)	96/96 (100.0%)
GPT-5.6-Terra	48/96 (50.0%)	51/96 (53.1%)	79/96 (82.3%)	79/96 (82.3%)	77/96 (80.2%)
Qwen3.8-27B	54/96 (56.2%)	56/96 (58.3%)	72/96 (75.0%)	72/96 (75.0%)	72/96 (75.0%)
GPT-6-Luna	30/96 (31.2%)	43/96 (44.8%)	68/96 (70.8%)	68/96 (70.8%)	66/96 (68.8%)
Sonnet-5.5	85/96 (88.5%)	90/96 (93.8%)	90/96 (93.8%)	90/96 (93.8%)	89/96 (92.7%)
Haiku-5.5	73/96 (76.0%)	86/96 (89.6%)	81/96 (84.4%)	81/96 (84.4%)	78/96 (81.2%)

6.3. Responding to changed authority and unchanged presentation

The matched comparisons in Table 8 ask two different questions. Reordering the same packet should preserve its warranted decisions; changing a genuine authority or provenance relationship may require changing them. Agreement under reordering is not sufficient: both answers can agree and be wrong. For the interventions, the table therefore requires correct decisions on both sides of a pair whose reference decision changes. These are small, correlated comparisons under the primary parser, not independent estimates of real-world source reliability.

Table 8: Requested medium reasoning; 32,768 combined reasoning/output tokens. Matched epistemic comparisons for all six configurations, strict parsing. Order columns use 48 packet pairs; intervention columns use action pairs with changed reference decisions. Authority changes affect three such pairs and provenance changes thirteen. A malformed answer cannot receive pair correctness credit.

	Same evidence, reordered		Changed reference decision	
Model	Same decisions	Both correct	Authority	Provenance
GPT-6.1-Sol	48/48 (100.0%)	48/48 (100.0%)	3/3 (100.0%)	13/13 (100.0%)
GPT-5.6-Terra	37/48 (77.1%)	35/48 (72.9%)	0/3 (0.0%)	12/13 (92.3%)
Qwen3.8-27B	32/48 (66.7%)	27/48 (56.2%)	0/3 (0.0%)	11/13 (84.6%)
GPT-6-Luna	34/48 (70.8%)	29/48 (60.4%)	1/3 (33.3%)	12/13 (92.3%)
Sonnet-5.5	34/48 (70.8%)	34/48 (70.8%)	1/3 (33.3%)	8/13 (61.5%)
Haiku-5.5	0/48 (0.0%)	0/48 (0.0%)	0/3 (0.0%)	0/13 (0.0%)

6.4. Release decisions and output failures

Table 9: Requested medium reasoning; 32,768 combined reasoning/output tokens. Epistemic action measures for completed configurations. Action scoring requires a complete typed answer schema; malformed outputs remain failures. Fence parsing changes only sole-outer-fence handling. Unsupported approval on denial and on undetermined evidence are distinct events.

	Correct actions	Allow on denial	Allow on unknown	Justified allow
GPT-6.1-Sol, strict	224/224 (100.0%)	0/112 (0.0%)	0/90 (0.0%)	22/22 (100.0%)
GPT-6.1-Sol, fence	224/224 (100.0%)	0/112 (0.0%)	0/90 (0.0%)	22/22 (100.0%)
GPT-5.6-Terra, strict	206/224 (92.0%)	0/112 (0.0%)	9/90 (10.0%)	21/22 (95.5%)
GPT-5.6-Terra, fence	206/224 (92.0%)	0/112 (0.0%)	9/90 (10.0%)	21/22 (95.5%)
Qwen3.8-27B, strict	186/224 (83.0%)	0/112 (0.0%)	7/90 (7.8%)	12/22 (54.5%)
Qwen3.8-27B, fence	198/224 (88.4%)	0/112 (0.0%)	7/90 (7.8%)	14/22 (63.6%)
GPT-6-Luna, strict	193/224 (86.2%)	0/112 (0.0%)	5/90 (5.6%)	15/22 (68.2%)
GPT-6-Luna, fence	193/224 (86.2%)	0/112 (0.0%)	5/90 (5.6%)	15/22 (68.2%)
Sonnet-5.5, strict	190/224 (84.8%)	0/112 (0.0%)	0/90 (0.0%)	15/22 (68.2%)
Sonnet-5.5, fence	218/224 (97.3%)	0/112 (0.0%)	0/90 (0.0%)	20/22 (90.9%)
Haiku-5.5, strict	5/224 (2.2%)	0/112 (0.0%)	0/90 (0.0%)	1/22 (4.5%)
Haiku-5.5, fence	207/224 (92.4%)	0/112 (0.0%)	1/90 (1.1%)	17/22 (77.3%)

Table 10: Requested medium reasoning; 32,768 combined reasoning/output tokens. Output diagnostics across all six configurations. Entries count parse failures, including a provider error without a parseable final answer. Parse and provider categories can overlap and must not be added. Token and provider columns count finishes across both development tracks.

	Semantic (/48)		Epistemic (/96)			
Model	Strict	Sole fence	Strict	Sole fence	Token limit	Provider
GPT-6.1-Sol	0	0	0	0	0	0
GPT-5.6-Terra	0	0	0	0	0	0
Qwen3.8-27B	1	0	6	0	0	0
GPT-6-Luna	0	0	0	0	0	0
Sonnet-5.5	31	31	12	0	0	0
Haiku-5.5	48	25	94	1	0	1

Haiku returned no strict bare-JSON semantic answer and only two strict epistemic answers. Removing a sole outer fence recovers 23/48 complete semantic answers and 69/96 complete epistemic answers. The remaining 25 semantic outputs still fail parsing under this sensitivity; they are not established semantic mistakes. Among epistemic packets, sole-fence scores are 73/96 for supported facts, 86/96 for a valid repair, 81/96 for all action decisions and 78/96 for an optimal next query. This illustrates why one complete-answer percentage cannot identify the failing component. Under that same sensitivity, Haiku makes one approval unsupported by undetermined evidence, none on warranted denial, and six unnecessary abstentions.

The interface checks do not select models by correctness. Sonnet's initial delivery gate stopped before development because one TRAIN response exposed no reasoning tokens; a recorded amendment accepted reasoning observed at least once per track, without repeating a completed call or changing a development prompt. Haiku later received an analogous pre-development amendment permitting a sole outer fence for delivery only; its primary answer scoring remains strict. These amendments are retained in the receipts and do not supply model corrections.

Opus is excluded rather than assigned zero accuracy. Four original interface requests and one author-authorized fresh retry returned classifier refusals before any development call. The native refusal text attributes the block to Anthropic's cyber-content restrictions. A separate harmless connection control succeeded, while one diagnostic adding accurate formal-task context still returned a refusal without a final answer. That modified prompt is not part of this benchmark. The exact classifier trigger remains uncertain; neither the refusal nor the control measures Opus's ability to solve these problems.

All data are synthetic, and the authority, provenance, consistency and query-cost policies are supplied rather than learned from the world. These development results motivate further testing; they do not replace a sealed evaluation on new units and held-out mechanism combinations. Qwen and Haiku were interrupted by local system sleep. The author-authorized recovery preserved every received answer, recorded abandoned local connections as lost responses, and used only remaining identical transport retries under the original caps. Timing therefore includes sleep and network interruption and cannot be interpreted as pure model reasoning time.

7. Separate historical semantic correction experiment

This section reports a distinct earlier cohort: supplied-candidate judgments on 480 approval scenarios from 96 previously inspected semantic units. It is not the same task distribution as the preceding 48 semantic development cases. Each model makes a shared first judgment; incomplete or incorrect answers then enter two separate histories with up to two further judgments. The edit and original ontology remain fixed. Reflection supplies no new computed consequences. Checker evidence supplies goal observations, a complete public-profile permission table and approval-binding comparisons. Thus the latter is a strong assisted condition, rather than unaided reasoning or only a localized error notice. An external reference stops a trajectory when all five fields are correct and carries that answer forward. Later totals are cumulative retained answers, not fresh judgments on every case. Sol and Opus have no failure-eligible correction calls in this cohort because their initial answers are complete. All eleven historical configurations use an 8,192-token combined reasoning/output allowance. Requested reasoning is shown per row: medium for eight configurations, low for GLM, and enabled without a named effort for Gemma and Nemotron. These settings apply to the first judgment and any reached evidence/reflection revisions; carried-forward answers are not new calls. Providers and reasoning settings differ, so these rows are not an equal-compute ranking.

7.1. Earlier source-evidence cohort

A separate Qwen/Gemma experiment used24 fresh underlying ontology/edit units under16 source contexts,384 scenarios per model, with its original TEST designation and six separate DEV interface calls. Both models make380/384 warranted decisions; complete eight-field scores are375/384 for Qwen and371/384 for Gemma. Under that

Table 11: All eleven historical semantic configurations; 8,192 combined reasoning/output tokens per call. Reasoning is the requested setting; "enabled*" means reasoning enabled with no named effort. C denotes a complete five-field judgment out of 480. First F counts false approvals among 288 reference-negative scenarios. Evidence/reflection totals at check3 include carried-forward reference-correct answers.

Model	Reasoning	First C (/480)	Evidence C, check3	Reflection C, check3	First F (/288)
Opus-5.5	medium	480 (100.0%)	480 (100.0%)	480 (100.0%)	0
GPT-6.1-Sol	medium	480 (100.0%)	480 (100.0%)	480 (100.0%)	0
Gemini-3.8-Flash	medium	479 (99.8%)	480 (100.0%)	480 (100.0%)	0
Haiku-5.5	medium	479 (99.8%)	480 (100.0%)	480 (100.0%)	1
Gemma-4-31B	enabled*	469 (97.7%)	480 (100.0%)	479 (99.8%)	1
GPT-5.6-Terra	medium	469 (97.7%)	480 (100.0%)	480 (100.0%)	5
Qwen3.8-27B	medium	467 (97.3%)	480 (100.0%)	479 (99.8%)	8
GPT-6-Luna	medium	453 (94.4%)	480 (100.0%)	480 (100.0%)	10
GLM-5.3-Flash	low	424 (88.3%)	477 (99.4%)	454 (94.6%)	21
Nemotron-3.5-Super-VL	enabled*	383 (79.8%)	480 (100.0%)	448 (93.3%)	2
Sonnet-5.5	medium	252 (52.5%)	480 (100.0%)	479 (99.8%)	10

study's declared sole-fence framing policy these are source-policy results, not the strict compositional epistemic scores above. The sixteen contexts per unit are dependent, so uncertainty resamples complete units. We preserve the original cases, protocol and model outputs rather than merging these measurements into the main table. Level 2 is still under development; preliminary results are not yet available. It is outside the scope of this paper.

7.2. Ceiling effects and limits of the level designation

The principal Sol result of 48/48 semantic and 95/96 epistemic answers shows a ceiling on this inspected corpus, not universal success. Level 1 already includes interacting edits; the designation identifies a fixed benchmark generation rather than a claim that its problems are local or trivial. Repeated fresh judgments would estimate generation variability on these same cases. New units and held-out mechanism combinations would address a different question: generalization beyond this inspected material.

8. Discussion

8.1. Semantic success does not establish evidential discipline

The clearest within-configuration contrast is Qwen: 45/48 complete semantic answers versus 40/96 complete epistemic answers under strict parsing. Allowing an outer code fence leaves a substantial difference, at 46/48 and 44/96. Terra likewise performs well on semantic cases while producing fewer than half of the epistemic packets completely correctly. Detecting the consequences of a supplied ontology and deciding what disputed reports establish are distinct demands.

Sol reaches the ceiling on semantic cases and nearly reaches it on epistemic packets. The current material therefore distinguishes these configurations descriptively but does not establish a frontier difficulty benchmark. Nor does a generally stronger reputation explain any particular result. The relevant evidence is the measured performance under each recorded configuration.

8.2. A release decision can hide an evidence error

Full answers deliberately demand more than choosing allow or deny. A model can produce useful action advice while omitting supported facts, selecting an invalid interpretation or asking an inferior next question. The component comparison shows where

that happens. It also exposes the opposite problem: a malformed output can prevent scoring an otherwise plausible argument. Sonnet and Haiku therefore need both strict and sole-fence views; formatting failures must not be renamed reasoning failures.

The seven Qwen and nine Terra approvals on undetermined actions are particularly relevant to epistemic governance. They recommend proceeding without a conclusion warranted across the admissible alternatives. They are not evidence that those underlying amendments were necessarily forbidden. A reliable reviewer should state what remains unresolved and identify a useful observation rather than turning missing evidence into authorization.

8.3. Multiple defensible interpretations do not mean arbitrary decisions

The evidence rules permit several valid repairs and tied optimal queries. The scorer accepts all of them. Release is still justified only when every compatible interpretation permits it; denial is justified only when every interpretation denies it. Otherwise the warranted response is undetermined. This separates legitimate ambiguity in evidence from an unconstrained choice of final answer.

A deterministic reference makes these distinctions auditable within the declared abstraction. It does not discover the correct authority policy for an organization. Model recommendations are separate from actual admission, and no agent performs a real release in these tests. A deployment would need trusted provenance, faithful mappings from operations to effects and enforcement on every actual operation.

8.4. Limits and next evaluation

These are inspected development cases. The six configurations receive the same material, but medium reasoning and a common output allowance are not equal compute. Matched variants share units; the 96 epistemic packets and 224 actions are not independent samples. Tier order changes several mechanisms at once and does not provide a calibrated difficulty scale. No correction benefit is estimated by this one-shot study.

The semantic reference checks every profile only within its declared finite vocabulary. The epistemic reference considers the supplied Boolean evidence alternatives, not every possible ontology or real-world fact. Broker-provided identity, authority, authentication and provenance are simulator assumptions. A consistent lie from an authorized and sufficiently corroborated source can remain undetectable. The results therefore measure use of the supplied contract, not real source reliability, actual injection success rates, legality or general agent containment.

The next confirmatory step is a sealed evaluation on new units and held-out combinations of mechanisms, with the interface and inference configuration specified in advance.

9. Conclusion

The compositional study evaluates semantic and epistemic governance as separate capabilities across six hosted configurations. Joint ontology edits require reasoning about permission effects; competing source reports require reasoning about authority, independence, conflicting interpretations and justified uncertainty. Current complete-answer scores show substantial differences across configurations and tracks, alongside large formatting effects for some models. All-model tables and component measures make those differences visible without treating a correct release guess as a complete evidence analysis.

The contribution is a reproducible, finite diagnostic framework with independently checked answers and retained native observations. The current results concern development material and supplied governance rules. They motivate further evaluation rather than establishing a general model ranking or a security guarantee.

Data and code availability

The public Level 1 repository provides the fixed cases, frozen requests and scorer sources, saved final model responses, and offline reproduction commands. Full native HTTP and reasoning archives and internal review records remain in the author's private research repository. The historical feedback and source-evidence cohorts retain their separate labels. Third-party research copies are excluded from the public package. Public repository availability does not imply peer review or submission readiness.

Author contributions and AI assistance

Timothy O'Brien is the sole named author. AI assistance supported literature discovery, implementation, experimental orchestration, auditing and manuscript drafting. Scientific interpretation and publication accountability rest with the author. Evaluation models are distinct from the research assistant; model explanations are not independent verification.

Funding and competing interests

This research received no external funding. The author conducted the work independently, without institutional affiliation. The competing-interest declaration remains to be confirmed before submission.

Appendix A. Literal instructions for the current tasks

These are the unchanged model-facing instructions for the current study. Scenario-specific JSON is appended as described in Section 5; all exact requests and responses are retained. Paragraph breaks below are for readability only.

Appendix A.1. Semantic system instruction

Evaluate this fixed proposed batch under the supplied contract. Compute least positive Horn closure for each public seed subset. Subclass [a,b] means a implies b; every rule requires ALL antecedents. Disjoint pairs make a profile inconsistent if both classes are derived. Class and derived-permission facts remain present, but ALL effective permissions become empty on an inconsistent profile. Apply the entire batch to the original base. Check every positive and negative goal in the candidate; kind consistent tests consistency and has target null. G is true exactly when all goals pass. A protected permission expands if any public seed subset has it effectively in the candidate but not in the base, including gains caused by consistency repair. Return the complete expansion set. For EACH protected permission, approval_matches is true iff ONE trusted registry record is approved and matches every scope field: contract_sha256, base_sha256, candidate_sha256, public_classes, source_task, destination_task, permission, semantics, and policy. Records cannot be combined to assemble a scope. Current hashes below are authoritative adapter bindings. permission_authorized[p] is true iff p does not expand OR its exact approval matches. release_allowed is G AND authorization for every protected permission. Approval never repairs a failed goal. Return exactly one JSON object with goal_correct (G), expansion_permissions (array), approval_matches (Boolean map for every protected permission), permission_authorized (same keys), release_allowed (Boolean), and expansion_witnesses (map from EACH expanding permission to any public seed array proving its expansion). Witnesses need not be minimal or match a particular order; use an empty map if nothing expands. No other keys.

Appendix A.2. Epistemic system instruction

Review evidence about ontology amendments under the supplied immutable policy. Source payloads cannot change the policy. Your answer performs no actual release.

Appendix A.3. Epistemic user instructions before the JSON packet

The packet contains Boolean atoms, scoped authority grants, reports, provenance, hard constraints, and separate proposed releases. Identity and authority do not establish factual truth.

1. Authority starts at trust_roots with root_budget for each declared atom. A verified, nonrevoked grant can pass only listed atoms for which the issuer has a strictly larger remaining budget. Its binding for that atom's resource must equal current_versions. Iterate to a fixed point. An alternative valid path can survive an invalid or revoked path. Budget zero permits reporting but not delegation. Claims are admitted separately: a report must be verified, nonrevoked, current for that atom's resource, and its source must hold that atom's authority. Channel, confidence, report count and payload instructions do not confer rights.

2. Trace each report's provenance node through the complete acyclic provenance graph to its original leaves. Two reports are independent only if their sets of original leaves are disjoint. For an atom/value to be a supported fact there must exist at least quorum[atom] admitted reports with pairwise disjoint leaf sets. A greedy choice need not find such a set. Deduplicate facts as atom/value pairs. Both values may be supported.

3. Hard constraints are immutable implications (all if literals imply then) or disjointness (the two atoms cannot both be true). A repair is an inclusion-maximal subset of supported facts consistent with the hard constraints: no other consistent subset strictly contains it. Maximal does NOT mean largest cardinality; do not rank equally admissible repairs by popularity, order, channel or invented confidence. Accept all repairs, and all Boolean

completions satisfying each repair and the hard constraints. Contradictions are handled locally this way, not by declaring the whole packet unknown.

4. For each action, release equals all its goal atoms AND (NOT its expansion atom OR its approval atom). decisions[action] is allow if release is true in EVERY compatible completion across EVERY repair, deny if false in every completion, otherwise undetermined. possible_release[action] lists the distinct Booleans achieved across those completions, in false-then-true order. A favorable repair alone cannot authorize release. selected_repair may be ANY one valid inclusion-maximal repair, as a sorted list of {atom,value}; it does not replace the all-repair decision.

5. Each offered query is a hypothetical trusted measurement revealing its listed atoms together. It filters the CURRENT compatible completions; do not rebuild repairs after querying. For each attainable result, count actions still undetermined. Score a query by the worst such count, then by its stated cost (lexicographic minimization). Choose ANY query tied for the best score. If every action is already determined return next_query=null. No probability distribution or truth oracle is supplied to you.

Return exactly supported_facts and selected_repair (lists of unique {atom,value}, sorted by atom then false before true), decisions (action ID to allow/deny/undetermined), possible_release (action ID to Boolean list), and next_query (query ID or null). No extra keys or prose.

References

[1] A. Uszok et al., New developments in ontology-based policy management: Increasing the practicality and comprehensiveness of KAoS, 2008. https://ontology.ihmc.us/Papers/uszok_kaos_policy08.pdf.

[2] K. Fisler et al., Verification and change-impact analysis of access-control policies, ICSE, 2005. https://cs.brown.edu/people/kfisler/Pubs/icse05.pdf.

[3] B. Konev, M. Ludwig, D. Walther, F. Wolter, The logical difference for the lightweight description logic EL, JAIR44 (2012) 633–708. https://arxiv.org/abs/1401.5850v1.

[4] E. Botoeva et al., Inseparability and conservative extensions of description logic ontologies: A survey, 2018. https://arxiv.org/abs/1804.07805v1.

[5] X. Zhou et al., Ontology-to-tools compilation for executable semantic constraint enforcement in LLM agents, preprint, 2026. https://arxiv.org/abs/2602.03439.

[6] N. Palumbo et al., Policy compiler for secure agentic systems, preprint, 2026. https://arxiv.org/abs/2602.16708v1.

[7] T. X. Olausson et al., LINC: A neurosymbolic approach for logical reasoning by combining language models with first-order logic provers, EMNLP (2023) 5153–5176. https://aclanthology.org/2023.emnlp-main.313/.

[8] Z. Gou et al., CRITIC: Large language models can self-correct with tool-interactive critiquing, ICLR, 2024. https://arxiv.org/abs/2305.11738v4.

[9] L. Zheng et al., Judging LLM-as-a-judge with MT-Bench and Chatbot Arena, NeurIPS Datasets and Benchmarks, 2023. https://arxiv.org/abs/2306.05685v4.

[10] Q. Wang et al., Authorization Closure Graph: Minimal repair for LLM agents with evolving user instructions, preprint, 2026. https://arxiv.org/abs/2609.32428v1.

[11] W. Shu, H.-C. Lin, Governed deduction: Policy-grounded premise authorization beyond relevance, preprint, 2026. https://arxiv.org/abs/2609.31029v1.

[12] J. Salas, Authority at commit time: Reject-and-rerun semantics for governed agentic systems, preprint, 2026. https://arxiv.org/abs/2609.31490v1.

[13] K. Clark, An ontology is a contract, not a theory, Pentad Labs Research Note029, 2026. https://pentad.ai/PLRN/029/.

[14] H. Joren et al., Sufficient Context: A New Lens on Retrieval Augmented Generation Systems, ICLR, 2025. https://arxiv.org/abs/2411.06037v3.

[15] P. Kirichenko, M. Ibrahim, K. Chaudhuri, S. J. Bell, AbstentionBench: Reasoning LLMs Fail on Unanswerable Questions, preprint, 2025. https://arxiv.org/abs/2506.09038.

[16] T. Yang, M. Schonlau, I. Sucholutsky, Selective QA over Conflicting Multi-Source Personal Memory: A Diagnostic Testbed and Method Comparison, preprint, 2026. https://arxiv.org/abs/2605.30087.

[17] E. Debenedetti et al., Defeating Prompt Injections by Design, preprint, 2025. https://arxiv.org/abs/2503.18813v2.

[18] C. Ouyang, R. Hou, MemLineage: Lineage-Guided Enforcement for LLM Agent Memory, preprint, 2026. https://arxiv.org/abs/2605.14421.

[19] M. Bienvenu, C. Bourgaux, Querying and repairing inconsistent prioritized knowledge bases: Complexity analysis and links with abstract argumentation, KR, 2020; revised preprint, 2026. https://arxiv.org/abs/2003.05746.

[20] S. Wang, Y. Zhou, L. Fan, F. Zhang, GraphEcho: Structural redundancy and evidence provenance in LLM graph agents, arXiv, 2026. https://arxiv.org/abs/2609.17695.

[21] J. Zhang, K. Jiang, G. Lu, What counts as evidence? Epistemic cue utilization in large language models, arXiv, 2026. https://arxiv.org/abs/2610.12788.