

RMCAT WG  
Internet-Draft  
Intended status: Informational  
Expires: April 25, 2013

V. Singh  
J. Ott  
Aalto University  
October 22, 2012

Evaluating Congestion Control for Interactive Real-time Media.  
draft-singh-rmcattcc-eval-01.txt

## Abstract

The Real-time Transport Protocol (RTP) is used to transmit media in telephony and video conferencing applications. This document describes the guidelines to evaluate new congestion control algorithms for interactive point-to-point real-time media.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 25, 2013.

## Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	3
2. Terminology . . . . .	3
3. Metrics . . . . .	3
4. Guidelines . . . . .	4
4.1. Avoiding Congestion Collapse . . . . .	4
4.2. Stability . . . . .	4
4.3. Audio and Video . . . . .	4
4.4. Diverse Environments . . . . .	5
4.5. Varying Path Characteristics . . . . .	5
4.6. Reacting to Transient Events or Interruptions . . . . .	5
4.7. Fairness With Similar Cross-Traffic . . . . .	5
4.8. Impact on Cross-Traffic . . . . .	6
4.9. Extensions to RTP/RTCP . . . . .	6
5. Minimum Requirements for Evaluation . . . . .	6
6. Example Evaluation Scenarios . . . . .	6
7. Status of Proposals . . . . .	7
8. Security Considerations . . . . .	7
9. IANA Considerations . . . . .	7
10. Acknowledgements . . . . .	7
11. References . . . . .	8
11.1. Normative References . . . . .	8
11.2. Informative References . . . . .	8
Appendix A. Change Log . . . . .	9
A.1. Changes in draft-singh-rmcat-cc-eval-01 . . . . .	9
Authors' Addresses . . . . .	9

## 1. Introduction

This memo describes the guidelines to help with evaluating new congestion control algorithms for interactive point-to-point real time media. The requirements for the congestion control algorithm are outlined in [I-D.jesup-rtp-congestion-reqs]). This document builds upon previous work at the IETF: Specifying New Congestion Control Algorithms [RFC5033] and Metrics for the Evaluation of Congestion Control Algorithms [RFC5166].

The guidelines proposed in the document are intended to prevent a congestion collapse, promote fair capacity usage and optimize the media flow's throughput, delay, loss and quality. Furthermore, the proposed algorithms are expected to operate within the envelope of the circuit breakers defined in [I-D.ietf-avtcore-rtp-circuit-breakers].

This document only provides broad-level criteria for evaluating a new congestion control algorithm and the working group should expect a thorough scientific study to make its decision. The results of the evaluation are not expected to be included within the internet-draft but should be cited in the document.

## 2. Terminology

The terminology defined in RTP [RFC3550], RTP Profile for Audio and Video Conferences with Minimal Control [RFC3551], RTCP Extended Report (XR) [RFC3611], Extended RTP Profile for RTCP-based Feedback (RTP/AVPF) [RFC4585] and Support for Reduced-Size RTCP [RFC5506] apply.

## 3. Metrics

[RFC5166] describes the basic metrics for congestion control. Metrics that are important to interactive multimedia are:

- \* Delay
- \* Throughput
- \* Minimizing oscillations in encoding rate (stability)
- \* Reactivity to transient events
- \* Packet loss and discard rate
- \* Users' quality of experience

[Editor's Note: measurement interval and statistical measures (min, max, mean, median) are yet to be specified.]

Section 2.1 of [RFC5166] discusses the tradeoff between throughput, delay and loss.

- (i) Bandwidth Utilization: is the ratio of the encoding rate to the (available) end-to-end path capacity.
- \* Under-utilization: is the period of time when the endpoint's encoding rate is lower than the end-to-end capacity, i.e., the bandwidth utilization is less than 1.
- \* Overuse: is the period of time when the endpoint's encoding rate is higher than the end-to-end capacity, i.e., the bandwidth utilization is greater than 1.
- \* Steady-state: is the period of time when the endpoint's encoding rate is relatively stable, i.e., the bandwidth utilization is constant.

(ii) Packet Loss and Discard Rate.

(iii) Fair Share.

[Editor's Note: This metric should match the one defined in the RMCAT requirements [I-D.jesup-rtp-congestion-reqs] document.]

#### 4. Guidelines

A congestion control algorithm should be tested in simulation or a testbed environment, and the experiments should be repeated multiple times to infer statistical significance. The following guidelines are considered for evaluation:

##### 4.1. Avoiding Congestion Collapse

Does the congestion control propose any changes to (or diverge from) the circuit breaker conditions defined in [I-D.ietf-avtcore-rtp-circuit-breakers].

##### 4.2. Stability

The congestion control should be assessed for its stability when the path characteristics do not change over time. Changing the media encoding rate too often or by too much may adversely affect the users' quality of experience.

##### 4.3. Audio and Video

The congestion control algorithm should be assessed with different types of media behavior, i.e., the media should contain idle and

data-limited periods. For example, periods of silence or low motion.

#### 4.4. Diverse Environments

The congestion control algorithm should be assessed in heterogeneous environments, containing both wired and wireless paths. Examples of wireless access technologies are: 802.11x, HSPA, WCDMA, or GPRS. One of the main challenges of the wireless environments is the inability to distinguish congestion induced loss from transmission (bit-error) loss. Congestion control algorithms may incorrectly identify transmission loss as congestion loss and reduce the media encoding rate too much, which may cause oscillatory behavior and deteriorate the users' quality of experience. Furthermore, packet loss may induce additional delay in networks with wireless paths due to link-layer retransmissions.

#### 4.5. Varying Path Characteristics

The congestion control algorithm should be evaluated for a range of path characteristics such as, different end-to-end capacity and latency, varying amount of cross traffic on a bottle-neck link and a router's queue length. The main motivation for the previous and current criteria is to determine under which circumstances will the proposed congestion control algorithm break down and also determine the operational range of the algorithm.

[Editor's Note: Different types of queueing mechanisms? Random Early Detection or only DropTail?].

#### 4.6. Reacting to Transient Events or Interruptions

The congestion control algorithm should be able to handle changes in end-to-end capacity and latency. Latency may change due to route updates, link failures, handovers etc. In mobile environment the end-to-end capacity may vary due to the interference, fading, handovers, etc. In wired networks the end-to-end capacity may vary due to changes in resource reservation.

#### 4.7. Fairness With Similar Cross-Traffic

The congestion control algorithm should be evaluated when competing with other RTP flows using the same congestion control algorithm. The proposal should highlight the bottleneck capacity share of each RTP flow.

#### 4.8. Impact on Cross-Traffic

The congestion control algorithm should be evaluated when competing with standard TCP. Short TCP flows may be considered as transient events and the RTP flow may give way to the short TCP flow to complete quickly. However, long-lived TCP flows may starve out the RTP flow depending on router queue length. In the latter case the proposed congestion control for RTP should be as aggressive as standard TCP [RFC5681].

The proposal should also measure the impact on varied number of cross-traffic sources, i.e., few and many competing flows.

#### 4.9. Extensions to RTP/RTCP

The congestion control algorithm should indicate if any protocol extensions are required to implement it and should carefully describe the impact of the extension.

### 5. Minimum Requirements for Evaluation

[Editor's Note: If needed, a minimum evaluation criteria can be based on the above guidelines]

### 6. Example Evaluation Scenarios

In the scenarios listed below, all RTP flows are bi-directional and point-to-point.

[S1] RTP flow on a fixed link: This scenario evaluates the ramp-up to the bottleneck capacity and the stability of the proposed congestion control algorithm.

[S2] RTP flow on a variable capacity link: This scenario evaluates the reactivity of the proposed congestion control algorithm to transient network events due to interference and handovers in mobile environments. Sample 3G bandwidth traces are available at [3GPP.R1.081955].

[S3] Fairness to RTP flows running the same congestion control algorithm: This scenario shows if the proposed algorithm can share the bottleneck link equitably, irrespective of number of flows.

[S4] Competing with long-lived TCP flows: In this scenario the proposed algorithm is expected to be TCP-friendly, i.e., it should neither starve out the competing TCP flows (causing a congestion

collapse) nor should it be starved out by TCP.

[S5] Competing with short TCP flows: Depending on the level of statistical multiplexing on the bottleneck link, the proposed algorithm may behave differently. If there are a few short TCP flows then the proposed algorithm may observe these flows as transient events and let them complete quickly. Alternatively, if there are many short flows then the proposed algorithm may have to compete with the flows as if they were long lived TCP flows.

[Editor's Note: definition of many and few short TCP flows may depend on the bottleneck link capacity.]

## 7. Status of Proposals

Congestion control algorithms are expected to be published as "Experimental" documents until they are shown to be safe to deploy. An algorithm published as a draft should be experimented in simulation, or a controlled environment (testbed) to show its applicability. Every congestion control algorithm should include a note describing the environments in which the algorithm is tested and safe to deploy. It is possible that an algorithm is not recommended for certain environments or perform sub-optimally for the user.

[Editor's Note: Should there be a distinction between "Informational" and "Experimental" drafts for congestion control algorithms in RMCAT. [RFC5033] describes Informational proposals as algorithms that are not safe for deployment but are proposals to experiment with in simulation/testbeds. While Experimental algorithms are ones that are deemed safe in some environments but require a more thorough evaluation (from the community).]

## 8. Security Considerations

Security issues have not been discussed in this memo.

## 9. IANA Considerations

There are no IANA impacts in this memo.

## 10. Acknowledgements

Much of this document is derived from previous work on congestion control at the IETF.

The authors would like to thank Harald Alvestrand, Luca De Cicco, Wesley Eddy, Stefan Holmer, Randell Jesup Piers O'Hanlon, Timothy B. Terriberry, Michael Welzl for providing valuable feedback on earlier versions of this draft.

## 11. References

### 11.1. Normative References

- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, RFC 3550, July 2003.
- [RFC3551] Schulzrinne, H. and S. Casner, "RTP Profile for Audio and Video Conferences with Minimal Control", STD 65, RFC 3551, July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", RFC 3611, November 2003.
- [RFC4585] Ott, J., Wenger, S., Sato, N., Burmeister, C., and J. Rey, "Extended RTP Profile for Real-time Transport Control Protocol (RTCP)-Based Feedback (RTP/AVPF)", RFC 4585, July 2006.
- [RFC5506] Johansson, I. and M. Westerlund, "Support for Reduced-Size Real-Time Transport Control Protocol (RTCP): Opportunities and Consequences", RFC 5506, April 2009.
- [I-D.jesup-rtp-congestion-reqs]  
Jesup, R. and H. Alvestrand, "Congestion Control Requirements For Real Time Media",  
draft-jesup-rtp-congestion-reqs-00 (work in progress),  
March 2012.
- [I-D.ietf-avtcore-rtp-circuit-breakers]  
Perkins, C. and V. Singh, "RTP Congestion Control: Circuit Breakers for Unicast Sessions",  
draft-ietf-avtcore-rtp-circuit-breakers-00 (work in progress), October 2012.

### 11.2. Informative References

- [RFC5033] Floyd, S. and M. Allman, "Specifying New Congestion Control Algorithms", BCP 133, RFC 5033, August 2007.



- [RFC5166]   Floyd, S., "Metrics for the Evaluation of Congestion Control Mechanisms", RFC 5166, March 2008.
- [RFC5681]   Allman, M., Paxson, V., and E. Blanton, "TCP Congestion Control", RFC 5681, September 2009.
- [3GPP.R1.081955]  
R1-081955, 3GPP., "LTE Link Level Throughput Data for SA4 Evaluation Framework", 3GPP R1-081955, 5 2008.

## Appendix A.   Change Log

Note to the RFC-Editor: please remove this section prior to publication as an RFC.

### A.1.   Changes in draft-singh-rmcat-cc-eval-01

- o   Removed QoE metrics.
- o   Changed stability to steady-state.
- o   Added measuring impact against few and many flows.
- o   Added guideline for idle and data-limited periods.

## Authors' Addresses

Varun Singh  
Aalto University  
School of Electrical Engineering  
Otakaari 5 A  
Espoo, FIN 02150  
Finland

Email: [varun@comnet.tkk.fi](mailto:varun@comnet.tkk.fi)

Joerg Ott  
Aalto University  
School of Electrical Engineering  
Otakaari 5 A  
Espoo, FIN 02150  
Finland

Email: [jo@comnet.tkk.fi](mailto:jo@comnet.tkk.fi)

