



Sep 21, 2020

nf-vcf-novel-dataset-builder

Israel Aguilar Ordoñez¹¹Instituto Nacional de Medicina Genómica (INMEGEN)**1** Works for me dx.doi.org/10.17504/protocols.io.bkh7kt9n

Whole genome variation in 27 Mexican indigenous populations, demographic and biomedical insights



Judith Ballesteros Villascán

Centro de Investigación y de Estudios Avanzados del IPN (Cin...

ABSTRACT

Nextflow pipeline used to build the novel variants dataset for the 100GMX project.

'nf-vcf-novel-dataset-builder' is a pipeline tool that builds a VCF file compiling only novel variants according to dbSNP and VEP, from a VEPextended annotated VCF file. This novel selection does not include singletons and private variants. The main output is in VCF format. Additional outputs include the dataset in TSV format, and a sequence coverage from gnomAD in these sites.

Important note: input file must be previously annotated by <https://github.com/laguilaror/nf-VEPextended>

All steps described are mk modules of code that will be done automatically through Nextflow pipeline.

EXTERNAL LINK

<https://github.com/laguilaror/nf-vcf-novel-dataset-builder.git>

DOI

dx.doi.org/10.17504/protocols.io.bkh7kt9n

PROTOCOL CITATION

Israel Aguilar Ordoñez 2020. nf-vcf-novel-dataset-builder. **protocols.io**
<https://dx.doi.org/10.17504/protocols.io.bkh7kt9n>



EXTERNAL LINK

<https://github.com/laguilaror/nf-vcf-novel-dataset-builder.git>

LICENSE

————— This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

CREATED

Aug 30, 2020

LAST MODIFIED

Sep 21, 2020

PROTOCOL INTEGER ID

41247

GUIDELINES

Installation

Download nf-vcf-novel-dataset-builder from Github repository:

```
git clone https://github.com/Iaguilaror/nf-vcf-novel-dataset-builder.git
```

Compatible OS*:

- [Ubuntu 18.04.03 LTS](#)

*nf-vcf-novel-dataset-builder may run in other UNIX based OS and versions, but testing is required.

Software Requirements:

 **bcftools 1.9** [↗](#)

 **htslib 1.9** [↗](#)

 **Nextflow 19.04** [↗](#)

 **Plan9**
[source](#)

 **R 3.4.4** [↗](#)

MATERIALS TEXT

Pipeline Inputs

- A compressed vcf file with extension '.vcf.gz'; the VCF must be previously annotated with <https://github.com/Iaguilaror/nf-VEPextended>

Example line(s):

```
##fileformat=VCFv4.2 #CHROM POS ID REF ALT QUAL FILTER INFO chr21
5101724 . G A . PASS
AC=1;AF=0.00641;AN=152;DP=903;ANN=A|intron_variant|MODIFIER|GATD3B|ENSG00000280071|Tran
script|ENST00000624810.3|protein_coding||4/5|ENST00000624810.3:c.357+19987C>T|||||1|
1|cds_start_NF&cds_end_NF|SNV|HGNC|HGNC:53816||5|||ENSP00000485439|A0A096LP73|UPI0004F
23660|||||chr21:g.5101724G>A|||||||||||||||||||||2.079|0.034663|||||||||
|||||||||||||||||chr21 5102165
rs1373489291 G T . PASS
AC=1;AF=0.00641;AN=140;DP=853;ANN=T|intron_variant|MODIFIER|GATD3B|ENSG00000280071|Tran
script|ENST00000624810.3|protein_coding||4/5|ENST00000624810.3:c.357+19546C>A|||||rs1
373489291||-
```

```
1|cds_start_NF&cds_end_NF|SNV|HGNC|HGNC:53816||5|||ENSP00000485439||A0A096LP73|UPI0004F
23660|||||chr21:g.5102165G>T|||||||||||||||||||||||||||||5.009|0.275409|||||||||||||
|||||||||||||||||||||||||||||||||||||||||||||||||||||||||
```

BEFORE STARTING

Test

To test nf-vcf-novel-dataset-builder execution using test data, run:

```
./runtest.sh
```

Your console should print the Nextflow log for the run, once every process has been submitted, the following message will appear:

```
=====
nf-vcf-novel-dataset-builder: Basic pipeline TEST SUCCESSFUL
=====
```

nf-vcf-novel-dataset-builder results for test data should be in the following file:

```
nf-vcf-novel-dataset-builder/test/results/VCFnovelbuilder-results
```

Usage

To run nf-vcf-novel-dataset-builder go to the pipeline directory and execute:

```
nextflow run vcf-novel-finder.nf --vcffile <path to input 1> [--output_dir path to
results ]o results ] [-resume]
```

For information about options and parameters, run:

```
nextflow run vcf-novel-finder.nf --help
```

Pre-processing

1 Remove singletons and private

Remove singletons and private variants.



- a) Filter positions where AC >= '3' to eliminate singletons and private.
- * AC could be modified.

Dependencies:



bcftools 1.9 [↗](#)

Core-processing

2 Select novel

Select novel SNPs, indels variants and concatenate both type variants.



- a) Filter novel SNPs.
- b) Filter novel indels.
- c) Concatenate novel SNPs and indels.
- d) Sort VCF.

Dependencies:



bcftools 1.9 [↗](#)

Pos-processing

3 Count per sample

List and count samples to present block data in a column format.

- final-counter.R is a tool for transforming wide to long format.



- a) List all samples.
- b) Extract block of counted data only.
- c) Transform to column format.

Dependencies:



bcftools 1.9 [↗](#)

- final-counter.R

4 Simplify VCF for dbSNP upload

Remove genotypes, remove FORMAT and all INFO field except INFO/AF and FORMAT, also changes AF to AF_natmx.



- a) Remove genotypes.
- b) Remove fields except for INFO/AF and FILTER.
- c) Rename local AF to AF_natmx, also in the header.

Dependencies:



bcftools 1.9 [↗](#)

Final Output:



A compressed and simplified VCF file format.

Example line(s):

```
#CHROM POS ID REF ALT QUAL FILTER INFO chr21 5227536 . C
CTCTCCTCTCT . . AF_natmx=0.019 ...
```

5 VCF2TSV

Convert vcf to tsv format.

Dependencies:



bcftools 1.9 [↗](#)

Final Output:



A compressed TSV file format.

Example line(s):

CHROM	POS	REF	ALT	AF_natmx	Allele	Consequence	IMPACT	SYMBOL
Gene	Feature_type	Feature	BIOTYPE	EXON	INTRON	HGVSc	HGVSp	cDNA_position
CDS_position	Protein_posi	chr21	5227536	C	CTCTCCTCTCT	0.019	TCTCCTCTCT	
intergenic_variant	MODIFIER
.

6 Consequence cataloguer

Catalogue consequences for each type of variant.

- cataloguer.R is a tool for cataloging the consequences of novel variants.

Dependencies:

- cataloguer.R

Final Output:



A compressed TSV file format by each category of variant and a SVG file.

Example line(s) of TSV:

Consequence	number_of_variants	Type	General_category	UTR	3 prime
First_specific_consequence	3_prime_UTR_variant	2	noncoding	UTR	3 prime
UTR	3_prime_UTR_variant&NMD_transcript_variant	NA	noncoding	UTR	3 prime
UTR	...				

7 Coverage gnomAD

Plot gnomAD coverages.

- coverage-analyzer.R is a tool for plotting coverage of the gnomAD project.

Dependencies:

- coverage-analyzer.R

Final Output:



.tif file format by each variant category.