

Jul 15, 2024

Imaging- Bright field

DOI

dx.doi.org/10.17504/protocols.io.rm7vzjj9rlx1/v1

daniel.dautan daniel^{1,2}, Per Svenningsson^{1,2}

¹Department of Clinical Neuroscience, Karolinska Institutet, 171 76 Stockholm, Sweden;

²Aligning Science Across Parkinson's (ASAP) Collaborative Research Network, Chevy Chase, MD 20815, USA

ASAP Collaborative Rese...



Eileen Ruth Torres

Weill Cornell Medicine

OPEN  ACCESS



DOI: dx.doi.org/10.17504/protocols.io.rm7vzjj9rlx1/v1

Protocol Citation: daniel.dautan daniel, Per Svenningsson 2024. Imaging- Bright field. **protocols.io**

<https://dx.doi.org/10.17504/protocols.io.rm7vzjj9rlx1/v1>

License: This is an open access protocol distributed under the terms of the **Creative Commons Attribution License**, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

We use this protocol and it's working

Created: June 04, 2024

Last Modified: July 15, 2024

Protocol Integer ID: 101202

Keywords: ASAPCRN

Funders Acknowledgement:

Aligning Science Across

Parkinson's

Grant ID: 020608

Abstract

Protocol for imaging using Hamamatsu NanoZoomer slide scanner. Sections for analysis should be mounted on slides, stained for appropriate markers, and coverslipped. This protocol is using a Carl Zeiss LSM 880 confocal microscope.



- 1 Image slides at 40x magnification.
- 2 Extract individual sections using the NDP.view software (<https://www.hamamatsu.com/eu/en/product/life-science-and-medical-systems/digital-slide-scanner/U12388-01.html>).
- 3 Save images as tiff files.
- 4 Open images from same structures as one single stack using the merge function.
- 5 Using the crop, rotate, and move functions align all images from the same stack as best as possible. Note: Using 2-3 specific anatomy points to align the structures make the process easier.
- 6 Crop the entire stack at the same dimensions.
- 7 Save each image as a new tiff file (it is recommended to save it in a new folder).
- 8 Open the imageJ macro provided on Zenodo: <https://doi.org/10.5281/zenodo.10822458>.
Note: A README is provided at the beginning of the macro in order to convert all images in a 0-255 bit image.
- 9 Save the images as a new tiff file (it is recommended to save it in a new folder).
- 10 Open matlab and run for each structure the protocol provided on the Zenodo: <https://doi.org/10.5281/zenodo.10822458>.
Note: Follow the information provided on the code to align images.