



Nov 02, 2021

# Spike Detection

Bryan Yoo<sup>1</sup>, [Jessica Griffiths](#)<sup>1</sup>, Sarkis Mazmanian<sup>1</sup>

<sup>1</sup>California Institute of Technology

1



[dx.doi.org/10.17504/protocols.io.bzp9p5r6](https://dx.doi.org/10.17504/protocols.io.bzp9p5r6)

**Mazmanian Lab**

 Jessica Griffiths

Protocol for spike detection of GCaMP6F imaging data used in Yoo et al 2021

DOI

[dx.doi.org/10.17504/protocols.io.bzp9p5r6](https://dx.doi.org/10.17504/protocols.io.bzp9p5r6)

Bryan Yoo, Jessica Griffiths, Sarkis Mazmanian 2021. Spike Detection .

**protocols.io**

<https://dx.doi.org/10.17504/protocols.io.bzp9p5r6>



Center for Environmental and Microbial Interactions (CEMI)

Grant ID: n/a

Emerald Foundation

Grant ID: n/a

Heritage Medical Research Institute

Grant ID: n/a

National Institutes of Health

Grant ID: GM007616 and DK078938

Department of Defense

Grant ID: PD160030

Aligning Science Across Parkinson's

Grant ID: ASAP-00037

protocol ,

Nov 02, 2021

Nov 02, 2021

- 1 Data sets of fluorescent values recorded at a rate of 0.206 s from GCaMP6F-expressing unstimulated neurons in the myenteric plexus of the proximal large intestine and analyzed with the MLspike software for Matlab downloaded from GitHub (<https://github.com/MLspike/spikes>) ([Deneux et al., 2016](#)).
- 2 MLspike determines a new baseline to subtract from the raw fluorescence data to allow accurate modelling. The software uses a version of the Viterbi algorithm to obtain the most probable spike train. From the model, fluctuating baseline, model-estimated spike train, and most probable spike times were extracted. Polynomial coefficients ( $p_2$ ) were changed from 0.5 to 0.55 and ( $p_3$ ) from 0.01 to 0.03 for GCaMP6F fluorescence as recommended ([Deneux et al., 2016](#)). The minimum range for baseline ( $b_{\min}$ ) was changed from 0.7 to 0.5 as determined by observed fluorescence values.