





Jul 27, 2022

🌐 Structural prediction of VPS13C with AlphaFold2

Shujun Cai¹, Pietro De Camilli¹

¹Departments of Neuroscience and of Cell Biology, Howard Hughes Medical Institute, Program in Cellular Neuroscience, Neurodegeneration and Repair, Yale University School of Medicine, New Haven, Connecticut 06510, USA

1 Works for me

 Sharedx.doi.org/10.17504/protocols.io.6qpvr6rjbvmk/v1 Shujun Cai

ABSTRACT

This protocol describes the procedure of structural prediction of full-length human VPS13C and its truncation mutant with AlphaFold2 and the procedure to combine each segments into one structure.

ATTACHMENTS

[442-930.docx](#)

DOI

dx.doi.org/10.17504/protocols.io.6qpvr6rjbvmk/v1

PROTOCOL CITATION

Shujun Cai, Pietro De Camilli 2022. Structural prediction of VPS13C with AlphaFold2. **protocols.io**
<https://dx.doi.org/10.17504/protocols.io.6qpvr6rjbvmk/v1>



KEYWORDS

UCSF ChimeraX, VPS13C, ASAPCRN, AlphaFold

LICENSE

————— This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

CREATED

May 17, 2022

LAST MODIFIED

Jun 03, 2022

OWNERSHIP HISTORY

May 17, 2022  maria.s

May 23, 2022  Shujun Cai

PROTOCOL INTEGER ID

62734

Structure prediction

1

Separate Full-length VPS13C and truncation mutant into three pieces and two pieces, respectively, i.e., a.a. 1-1860, 1201-2340, 1801-3753 for full-length VPS13C and a.a. 1-1762, 1277-3240 for VPS13C Δ 1235-1748.

Note: prediction of the entire VPS13C sequence does not work because of sequence-length limitation of AlphaFold 2.0.

2

Install AlphaFold 2.0 on the Yale Farnam high performance computer cluster, used for structural prediction of each segment.

Note: Use 5 pTM models to generate five structures. For subsequent analysis use the one with highest confidence score, shown in rankings.json file.

Combination of segments

3


Open UCSF ChimeraX software and import pdb files of segments.

4

Align the fragments with overlapping regions with “mmaker” command.

5

Delete the overlapping regions from adjacent fragments with “delete” command.

- 
- 6 At the connection point, form a carbon–nitrogen bond with “build join peptide” command to connect two amino acid residues from two fragments.