



Jul 12, 2024

Imaging- Confocal

DOI

dx.doi.org/10.17504/protocols.io.j8nlk88y1l5r/v1

daniel.dautan daniel^{1,2}, Per Svenningsson^{1,2}

¹Department of Clinical Neuroscience, Karolinska Institutet, 171 76 Stockholm, Sweden;

²Aligning Science Across Parkinson's (ASAP) Collaborative Research Network, Chevy Chase, MD 20815, USA

ASAP Collaborative Rese...

Kaplitt Protocols



Eileen Ruth Torres

Weill Cornell Medicine

OPEN  ACCESS



DOI: **dx.doi.org/10.17504/protocols.io.j8nlk88y1l5r/v1**

Protocol Citation: daniel.dautan daniel, Per Svenningsson 2024. Imaging- Confocal. **protocols.io**

<https://dx.doi.org/10.17504/protocols.io.j8nlk88y1l5r/v1>

License: This is an open access protocol distributed under the terms of the **[Creative Commons Attribution License](#)**, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working

We use this protocol and it's working

Created: June 04, 2024

Last Modified: July 12, 2024

Protocol Integer ID: 101201

Keywords: ASAPCRN, imaging, mouse brain

Funders Acknowledgement:

Aligning Science Across

Parkinson's

Grant ID: 020608



Abstract

Protocol for imaging using confocal microscope. Sections for analysis should be mounted on slides, stained for appropriate markers, and coverslipped. This protocol is using a Carl Zeiss LSM 880 confocal microscope.



- 1 Using the confocal microscope, capture images at 10x magnification using a resolution of either 1024x1024 or 2048x2048.
- 2 If needed for larger area of the brain, use tile-scanning with a 0.6 zoom factor and 10% overlap for automated reconstruction.
- 3 If acquiring z-stack images use 1-4um spacing. Use stack projection in ImageJ and exclude approximately 10% of the section's surface.
- 4 Making sure to use the same settings across all images for the same experiment, use ImageJ to process the images.