

VERSION 4
NOV 14, 2023

OPEN ACCESS



DOI:
dx.doi.org/10.17504/protocols.io.rm7vzy7k8lx1/v4

Protocol Citation: Christian Macdonald, David Nedrud, Patrick Rockefeller Grimes, Donovan Trinidad, Catherine Shin, James Fraser, Willow Coyote-Maestas 2023. Dimple library generation and assembly protocol . **protocols.io** <https://dx.doi.org/10.17504/protocols.io.rm7vzy7k8lx1/v4> Version created by Christian Macdonald

License: This is an open access protocol distributed under the terms of the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited

Protocol status: Working
We use this protocol and it's working.

Created: Nov 14, 2023

Last Modified: Nov 14, 2023

PROTOCOL integer ID: 90928

Dimple library generation and assembly protocol V.4

Patrick Rockefeller

Christian Macdonald¹, David Nedrud², Grimes¹, Willow Coyote-Maestas¹

Donovan Trinidad¹, Catherine Shin¹, James Fraser¹,

¹University of California, San Francisco; ²Bio-Techne



Christian Macdonald
University of California, San Francisco

DISCLAIMER

DISCLAIMER – FOR INFORMATIONAL PURPOSES ONLY; USE AT YOUR OWN RISK

The protocol content here is for informational purposes only and does not constitute legal, medical, clinical, or safety advice, or otherwise; content added to [protocols.io](#) is not peer reviewed and may not have undergone a formal approval of any kind. Information presented in this protocol should not substitute for independent professional judgment, advice, diagnosis, or treatment. Any action you take or refrain from taking using or relying upon the information presented here is strictly at your own risk. You agree that neither the Company nor any of the authors, contributors, administrators, or anyone else associated with [protocols.io](#), can be held responsible for your use of the information contained in or linked to this protocol or any of our Sites/Apps and Services.

ABSTRACT

This is a protocol for generating and QCing mutagenic libraries using the Dimple protocol. This version is updated to include expanded descriptions of QC and to clarify certain steps.

MATERIALS

Enzymes and cells

- ☒ PrimeSTAR GXL DNA Polymerase Contributed by users Catalog #R050A
- ☒ MegaX DH10B T1R Electrocompetent Cells Life Technologies Catalog #C6400-03
- ☒ NEB Golden Gate Assembly Mix New England Biolabs Catalog # E1601S (Bsal)

Kits (NEB kits given only as examples - any comparable kit should work)

- ☒ Monarch PCR and DNA Cleanup Kit - 50 preps New England Biolabs Catalog #T1030S
- ☒ Monarch® DNA Gel Extraction Kit New England Biolabs Catalog #T1020
- ☒ Monarch Plasmid Miniprep Kit - 250 preps New England Biolabs Catalog #T1010L

Media and chemicals

- ☒ SOC Outgrowth Medium - 100 ml New England Biolabs Catalog #B9020S
- ☒ PCR Water (nuclease free) Contributed by users Catalog #PCPW

Equipment and consumables

- Thermocycler
- Electroporator
- Shaker
- Horizontal electrophoresis system
- Benchtop centrifuge
- OD meter
- Electroporation cuvettes (0.1 cm)
- Cuvettes for OD measurement
- Selection agar plates
- Agarose
- Optional: large BioAssay plates for plasmid purification

Preparation

1 Use DIMPLE to generate mutagenic oligos and primers.

The screenshot shows the DIMPLE Deep Indel Missense Programmable Library Engineering interface. The settings are as follows:

- Working Directory: (empty)
- Target Gene File: (empty)
- Oligo Length: 230
- Fragment Length: auto
- Fragment Overlap (This will change if deletions are selected): 0
- Barcode Start position: 0
- Type IIS restriction sequence: CGTCTC
- Sequences to avoid: CGTCTC, GGTCTC
- Include Stop Codons: ☐
- Codon Usage: ☐ E. coli, ☒ Human
- Custom Codon Usage: ☐
- Select Mutations: ☐ List of Deletions, ☐ List of Insertions
- Include Substitutions: ☐
- Run DIMPLE: (button)

Snapshot of the default DIMPLE GUI

2 Important notes: DIMPLE breaks a gene up into sub-library fragments and generates mutagenic insert oligo pools, where each oligo contains barcodes, Type IIS restriction cutsites, and a sub-region of the gene. Be sure to review your library generation vector and gene sequences and look for pre-existing Type IIS restriction sites. Use site-directed mutagenesis to remove unwanted off-target sites. Also note that, by default, DIMPLE expects restriction enzymes with 6 bp recognition sites and 4 bp overhang lengths (as with BsaI and BsmBI).

3 Input wild type gene sequence: Input your gene sequence, including backbone, in fasta format. Place all genes to be mutagenized in the same fasta file. You can define which positions your genes start and end in the fasta header. Note that this uses 0 indexing: for example, if your first nucleotide is 884 on snapgene, use 883 in the fasta header).

■ For example: >geneA start:35 end:250

The screenshot shows a Notepad++ window with a FASTA file. The header line is: >geneA start:35 end:250. The sequence is a long string of nucleotides (A, T, C, G) representing the gene sequence.

*If you do not define your start & end position, the software will analyze different ORFs and ask you to define these positions.

```
Analyzing Gene: pMV306_mOP_EccD3
ORF#1 MSNTVMPVIRVAVLAAGDDGRLT...VGLFSLVLR - length 475, strand 1, frame 2
ORF#2 MGLAEDSAQRDPISLIQAPGRCEV...RGAPHLPGAR - length 102, strand 1, frame 2
ORF#3 MPRSEESHKSCRPLERKMARGRKH...PESCTGVATR - length 89, strand 1, frame 3
ORF#4 MDAEAWLAGEKRLIEWTPPDQRAK...EAMSKLAKTS - length 330, strand 1, frame 3
ORF#5 MSHIQRETSRPLRLNSMDADLYG...QFHLNLEFF - length 271, strand 1, frame 3
ORF#6 MLLAAAGLVPTHRRAVLALARRGS...WRHLNDRHFT - length 311, strand -1, frame 1
ORF#7 MVRGINSVSQSLTISVSTSLATL...SGAWGFPYKR - length 43, strand -1, frame 2
ORF#8 MMVVMFKSPVEAEQADQQRHHRD...LLNSAAGSEL - length 497, strand -1, frame 2
ORF#9 MPRGPCSSVGPSCALGSSPRRAE...THAPELASSL - length 166, strand -1, frame 3
ORF#10 MYQAHGEAFELTRATEPATPNST...VFSDLKLDL - length 367, strand -1, frame 3
which ORF are you targeting? (number):1
MSNTVMPV
Is this the beginning of your gene?(position 883) (y/n):y
VGLFSLVLR
Is the size of your gene 1425bp? (y/n):n
Enter nucleotide length of your gene:1428
GLFSLVLR*
Is this end correct? (y/n):y
```

It is important to include the plasmid backbone so that the software can avoid making primers that nonspecifically recognize a region outside of your gene.

```
Non specific Fragment:8
[162, 159, 159, 159, 156, 156, 159, 159, 159]
Creating Gene:pMW306_mOP_Ecd3 --- Fragment:2-54
no thermodynamic data for neighbors 'AT/GT' available. Please check position manually:352 reverse
Primer:ATAGGTCTCgcccgatccggccgc
Match: ggcgcgcagccgcacccggccgc
Found non-specific match at 790bp:
match:cgaccacgcggcgacacccggccgc
primer:ATAGGTCTCgcccgatccggccgc Tm:35.03620585066153
----- Fragment size swapped due to non-specific primers -----
```

4 Using the DIMPLE GUI

- 4.1 *Working Directory:* When you open the DIMPLE GUI, first designate your working directory. This is the folder you wish your mutagenic oligo & primer outputs to be saved in.
- 4.2 *Target Gene File:* Upload your gene fasta text file with the Target Gene File button.
- 4.3 *Oligo length:* Designate the length of your oligo. This will include the barcodes, Type IIS restriction cutsite, and a region of your target gene that will be mutagenized. So, target gene +50bp.
- 4.4 *Fragment length:* You can adjust the length of your fragments, we recommend leaving the fragment length set to auto.
 - DIMPLE will automatically break up your gene into roughly the same fragment sizes, and will determine which lengths work best to avoid matching overhangs.
- 4.5 *Fragment overlap:* The number of base pairs shared between sub-regions. We have seen that setting overlap to 0 base pairs leads to errors. The overlap is set to 4 base pairs by default.
- 4.6 *Barcode start position:* The software selects from a set pool of barcodes when designing oligos. You can define which number barcode in the list this starts from.
- 4.7 *Type IIS restriction sequence:* You can select which Type IIS restriction cutsite you'd like to append to your inserts and backbone. You can choose between the BsmBI (CGTCTC) or BsaI (GGTCTC) sequences.
- 4.8 *Sequences to avoid:* This will allow the code to design fragments without the cutsite you selected in the *Type IIS restriction sequence* section. If there is an error when running, this implies you have a cutsite in your gene or vector that needs to be removed.

```
Exception in Tkinter callback
Traceback (most recent call last):
  File "C:\Program Files\WindowsApps\PythonSoftwareFoundation.Python.3.10_3.10.1520.0_x64_qbz5n2kfra8p0\lib\tkinter\__init__.py", line 188, in __call__
    return self.func(*args)
  File "C:\Users\ASUS\Desktop\Fraser_CoyoteMaestas_Lab\DMS\DIMPLE-master\run_dimple_gui.py", line 45, in run
    OLS = addgene(app.geneFile)
  File "C:\Users\ASUS\Desktop\Fraser_CoyoteMaestas_Lab\DMS\DIMPLE-master\DIMPLE\DIMPLE.py", line 41, in addgene
    tmpOLS.append(DIMPLE(gene, start, end))
  File "C:\Users\ASUS\Desktop\Fraser_CoyoteMaestas_Lab\DMS\DIMPLE-master\DIMPLE\DIMPLE.py", line 142, in __init__
    raise ValueError('Unwanted Restriction cut sites found. Please input plasmids with these removed.' + str(DIMPLE.avoid_sequences))
ValueError: Unwanted Restriction cut sites found. Please input plasmids with these removed.[Seq('GGTCTC')]
```

4.9 *Codon usage:* Your oligos can be codon optimized to your organism of choice. The default options are *E. coli* or *Human*, but you can also upload a codon usage table for any organism by pressing "Custom codon usage."

4.10 *Select mutations:*

Deletions: If you'd like to generate a library with deletions across your gene, select "List of deletions". Enter how many base pairs you'd like to be deleted across your library.

- **For example**, if you'd like deletions that are one codon long, enter "3" for 3 nucleotides.
- **For example**, If you'd like to include both deletions that are one codon long AND two codons long in the same pool, enter "3,6" for both 3, and 6 nucleotide long deletions.

Insertions: If you'd like to generate a library with different amino acids inserted across your gene, select "List of Insertions".

- **For example**, if you'd like to insert glycines across your gene, include "GGG" in the box.
- **For example**, If you'd like to insert glycine-serine across your gene, include "GGGTGC" in the box.
- **For example**, if you'd like to insert glycine AND glycine-serine across your gene, include "GGG,GGGTGC" in the box.

Substitutions: If you'd like to generate a library where an amino acid at each position is swapped with every other possible amino acid, select "Include Substitutions."

4.11 *Run DIMPLE:* Hit "Run DIMPLE" when you are ready to generate your pool.

5 Examples of what the running code and outputs look like:

The code will first iterate the ideal fragment length sizes across each gene of interest.

```
----- Analyzing Gene:pMV306_mOP_EccD3 -----
----- Fragment size swapped due to matching overhangs -----
Non specific Fragment:1
[162, 156, 159, 159, 159, 159, 159, 159, 156]
----- Fragment size swapped due to matching overhangs -----
Non specific Fragment:2
[162, 159, 156, 159, 159, 159, 159, 159, 156]
----- Fragment size swapped due to matching overhangs -----
Non specific Fragment:3
[162, 159, 159, 156, 159, 159, 159, 159, 156]
----- Fragment size swapped due to matching overhangs -----
Non specific Fragment:4
[162, 159, 159, 159, 156, 159, 159, 159, 156]
----- Fragment size swapped due to matching overhangs -----
Non specific Fragment:6
[162, 159, 159, 159, 156, 156, 162, 159, 156]
----- Fragment size swapped due to matching overhangs -----
Non specific Fragment:7
[162, 159, 159, 159, 156, 156, 159, 162, 156]
----- Fragment size swapped due to matching overhangs -----
Non specific Fragment:8
[162, 159, 159, 159, 156, 156, 159, 159, 159]
```

5.1 Next, barcodes are assigned to each fragment. The code will update how many barcodes it attempted to use to generate each fragment pool, and will remove these from the remaining barcode pool.

This will continue for each gene included in your fasta file.

```
Creating Gene:Hikeshi --- Fragment:43-81
Barcodes used:9
Barcodes Remaining:1066
Creating Gene:Hikeshi --- Fragment:83-119
Barcodes used:3
Barcodes Remaining:1063
Creating Gene:Hikeshi --- Fragment:121-158
Barcodes used:6
Barcodes Remaining:1057
Creating Gene:Hikeshi --- Fragment:160-198
no thermodynamic data for neighbors 'GT/AG' available. Please check position manually:258 forward
Primer:ATAGGTCTCAGACAGCAAATGATGAAGCAAAATTGTAG
Match: CACGAATGGGAAGCCAAGTGCCATCTTCAAAATTTAG
Barcodes used:9
Barcodes Remaining:1048
```

5.2 There is a final QC check for each primer set generated.

```

Running QC for barcode primer specificity
Checking primer set:TSHR_oligoP_DMS-1
Checking primer set:TSHR_oligoP_DMS-2
Checking primer set:TSHR_oligoP_DMS-3
Checking primer set:TSHR_oligoP_DMS-4
Checking primer set:TSHR_oligoP_DMS-5
Checking primer set:TSHR_oligoP_DMS-6
Checking primer set:TSHR_oligoP_DMS-7
Checking primer set:TSHR_oligoP_DMS-8
Checking primer set:TSHR_oligoP_DMS-9
Checking primer set:TSHR_oligoP_DMS-10
Checking primer set:TSHR_oligoP_DMS-11
Checking primer set:TSHR_oligoP_DMS-12
Checking primer set:TSHR_oligoP_DMS-13
Checking primer set:TSHR_oligoP_DMS-14
Checking primer set:TSHR_oligoP_DMS-15
Checking primer set:TSHR_oligoP_DMS-16
Checking primer set:ABCG2_oligoP_DMS-1
Checking primer set:ABCG2_oligoP_DMS-2
Checking primer set:ABCG2_oligoP_DMS-3
Checking primer set:ABCG2_oligoP_DMS-4
Checking primer set:ABCG2_oligoP_DMS-5
Checking primer set:ABCG2_oligoP_DMS-6
Checking primer set:ABCG2_oligoP_DMS-7
Checking primer set:ABCG2_oligoP_DMS-8
Checking primer set:ABCG2_oligoP_DMS-9
Checking primer set:ABCG2_oligoP_DMS-10
Checking primer set:ABCG2_oligoP_DMS-11

```

5.3 All outputs are saved in your working directory.

If you are using DIMPLE to mutagenize several genes, there will be separate files for the primers and mutagenic inserts for each gene, as well as a master list of **all** oligos and primers.

All_Oligos	FASTA File	16,745 KB
All_Primer	FASTA File	19 KB
GPR161_DMS_Gene_Primer	FASTA File	2 KB
GPR161_DMS_Oligo_Primer	FASTA File	2 KB
GPR161_DMS_Oligos	FASTA File	2,655 KB
GPR161_mutations	Microsoft Excel Co...	20 KB
Hikeshi_DMS_Gene_Primer	FASTA File	1 KB
Hikeshi_DMS_Oligo_Primer	FASTA File	1 KB
Hikeshi_DMS_Oligos	FASTA File	996 KB
Hikeshi_mutations	Microsoft Excel Co...	21 KB

For each gene, DIMPLE generates a list of:

- **EXAMPLE_DMS_Oligos.** This is the list of sub-library oligo pools, where each oligo contains barcodes, Type IIS restriction cutsites, and a sub-region of the gene.

```

GPR161_DMS_Oligos - Notepad
File Edit Format View Help
>GPR161_DMS-1_Ser2Cys
GAATAGGTGGCAAAACGCTGAGATAGATGCGGTCTCCgatatGTGcctgaactcaagtc
tgtcctgcgaaaagaactcttaacctcacagaggagaggggagagggcggtga
taattacgcagttcattgccatcatcgtgataacattctgtatgtttggaaacctcg
tcattgtgtgagGAGACCACTAAACGTGACGGGTGCGCTAAAGTGAGC
>GPR161_DMS-1_Ser2Asp
GAATAGGTGGCAAAACGCTGAGATAGATGCGGTCTCCgatatGACctgaactcaagtc
tgtcctgcgaaaagaactcttaacctcacagaggagaggggagagggcggtga
taattacgcagttcattgccatcatcgtgataacattctgtatgtttggaaacctcg
tcattgtgtgagGAGACCACTAAACGTGACGGGTGCGCTAAAGTGAGC
>GPR161_DMS-1_Ser2Ser
GAATAGGTGGCAAAACGCTGAGATAGATGCGGTCTCCgatatTCCctgaactcaagtc
tgtcctgcgaaaagaactcttaacctcacagaggagaggggagagggcggtga
taattacgcagttcattgccatcatcgtgataacattctgtatgtttggaaacctcg
tcattgtgtgagGAGACCACTAAACGTGACGGGTGCGCTAAAGTGAGC

```

Screenshot of mutagenic inserts generated by DIMPLE

- **EXAMPLE_DMS_Gene_Primer.** These are primers used to add cutsites to and amplify the backbone each mutagenic insert will be ligated into.


GPR161_DMS_Gene_Primer - Notepad

```

File Edit Format View Help
>GPR161_geneP_Mut-1_R Frag2-46 59.4C
ATAGGTCtctatcgatgctggcgctcatc
>GPR161_geneP_Mut-1_F Frag2-46 53.5C
ATAGGTCcggtagccctgtataaaatcata
>GPR161_geneP_Mut-2_R Frag48-90 57.6C
ATAGGTCcagaggtttccaaacatacga
>GPR161_geneP_Mut-2_F Frag48-90 60.3C
ATAGGTCgatctttggagtcgtgtgtgc
>GPR161_geneP_Mut-3_R Frag92-134 61.2C
ATAGGTCtcttgattgaactagtcacgacaaaagg
>GPR161_geneP_Mut-3_F Frag92-134 61.1C
ATAGGTCGaaaataacaggcaatcgcgcc
>GPR161_geneP_Mut-4_R Frag136-178 57.2C
ATAGGTCcaccatagggtacagaacgg
>GPR161_geneP_Mut-4_F Frag136-178 56.3C
ATAGGTCtcttgccaccgggaaccc

```

Screenshot of backbone primers generated by DIMPLE. Each primer name also lists its melting temperature.



Each primer pair linearizes the backbone

- **EXAMPLE_DMS_Oligo_Primer**s. These are primers used to amplify the mutagenic inserts from your oligo pool.


GPR161_DMS_Oligo_Primer - Notepad

```

File Edit Format View Help
>GPR161_oligoP_DMS-1_F Frag2-46_57.9C
GAATAGGTGGCAAAACGCTGA
>GPR161_oligoP_DMS-1_R Frag2-46_58.3C
GCTCACTTTACGCGCACC
>GPR161_oligoP_DMS-2_F Frag48-90_58.6C
AGTTTGGGATCTCGTACACG
>GPR161_oligoP_DMS-2_R Frag48-90_57.8C
TGAGGACTTTTGGCTTCGAC
>GPR161_oligoP_DMS-3_F Frag92-134_55.9C
ATCCATAGCGTCCCTATTGC
>GPR161_oligoP_DMS-3_R Frag92-134_58.7C
TCCCCGTGATGCTTAGGGA
>GPR161_oligoP_DMS-4_F Frag136-178_58.6C
CTTAACGGCGTGACACTTAG
>GPR161_oligoP_DMS-4_R Frag136-178_58.5C
TTGGCTAATAGTGGGAGGCG

```

- **EXAMPLE_mutations**. This is the list of mutations that will be present in your final library.



Library assembly

3d

6 Prepare oligo pool stock

Follow any recommendations for oligo pool resuspension: typically, this results in a 10 ng/μL solution, which the following steps assume. Lower or higher concentrations may require alterations.

7 PCR amplification of oligos, backbone

Thaw all components beforehand and follow general directions provided by manufacturer.


Amplification of mutagenic inserts and backbones should ideally be performed in parallel, assuming one has two thermocyclers. Alternatively, the backbone amplification can be performed first, then the the insert amplification can be done during the gel purification of the backbone.

8 PCR amplification of backbone.

Prepare a master mix with PrimeSTAR GXL polymerase:

A	B	C	D	E
Component	Total amount in master mix (μL)	Amount/react ion (μL)	Comment	Number of regions
dNTP	20	4		5
5X buffer	50	10		
Template (vector)	5	1	~10 ng	
Enzyme	5	1		
Nuclease-free H ₂ O	160	32		
Primers		2	Fwd & reverse combined at 20 μM (each)	
Total	240	50		

Mix by vortexing and spin down.

8.1 Transfer  48 μL of master mix into separate tubes for each reaction.

8.2 Add reaction-specific primers to each tube:  2 μL (paired at 20 μM, each) . Mix and spin down.

8.3 Place on thermocycler and amplify:

A	B	C
Step	T (° C)	Time (sec)
1	98	10
2	55	15
3	68	60 per kb
4	Repeat 1-3 15-24 times	See note
5	10	Hold

Note: the number of cycles should be optimized to minimize PCR cycles. Increasing cycles introduces the possibility of error. An initial comparison of 16, 18, and 22 total cycles can be used to find a minimum number of cycles which yields sufficient DNA for the assembly reaction (see **step 11** below) and no more. Increasing the template concentration (to 50 or 100 ng) could be preferable to increasing PCR cycles if large numbers are required for amplification.


8.4 Purify amplified product by gel extraction.

Prepare an agarose gel for gel purification (0.5% - 0.75%). Ideally, it should be of sufficient size to load all samples.

8.5 Load and run backbone products.

8.6 Use a scalpel or razor blade to (carefully!) cut out each product. Using a gel extraction kit, purify the product and elute in 10 µL elution buffer.

8.7 Important QC step - evaluate the quality of the amplification with the gel. Each lane should have a single, crisp band at the expected size. Multiple bands, or no bands, might indicate improper annealing and may require T_m or extension time optimization. Blurry and smeary bands might indicate problems with the electrophoresis or amplification conditions. It is essential to get specific, clean amplification of the backbone, and libraries should not be generated with messy reactions.



Example visualization of expected backbone amplification reactions on SYBR Safe-stained agarose gel. Each lane has a single, crisp band at the expected position that is well-separated from other lanes.


9 PCR amplification of mutagenic inserts.

Prepare a master mix with PrimeSTAR GXL polymerase:

A	B	C	D	E
Component	Total amount in master mix (µL)	Amount/react ion (µL)	Comment	Regions
5X buffer	50	10		5
dNTP	20	4		

A	B	C	D	E
Oligo pool	5	1	10 ng pool per reaction, assuming a stock at 10 ng/μL	
Enzyme (PrimeSTAR GXL)	5	1		
Primers		2	Fwd & rev combined, 20 μM (each)	
Nuclease-free H ₂ O	160	32		
Total	240	50		

Mix by vortexing.


9.1 Transfer  48 μL insert master mix into separate tubes for each reaction.

9.2 Add reaction-specific primers to each tube:  2 μL (paired at 20 μM, each) . Mix and spin down.

9.3 Place on thermocycler and amplify:

A	B	C
Step	T (° C)	Time (sec)
1	98	10
2	55	15
3	68	60
4	Repeat 1-3 15-24 times	See note
5	10	Hold

Note: the number of cycles should be optimized to minimize PCR cycles. Increasing cycles introduces both PCR bias and error. An initial comparison of 16, 18, and 22 total cycles can be used to find a minimum number of cycles which yields sufficient DNA for assembly step and no more. For the example libraries here, this is ~100 ng per oligo pool, and

9.4 Use a PCR cleanup kit to purify each product. Elute in  10 μL elution buffer .

10 **Important QC step** - run a gel with each PCR product and visualize it. Ideally, each reaction should ideally give a single strong band at the expected size. Failure to do so may require changing PCR conditions.

11 Golden gate assembly

Prepare a master mix for the assembly. Use the table below to calculate: adjust number of regions and amount of necessary backbone and insert for desired amounts per reaction. We have found 3 μL backbone and 1 μL oligo (insert) are usually good.

A	B	C	D	E
Component	Total amount (μL)	Amount/reaction (μL)	Notes	Number of regions
10X buffer	20	4		5
Enzyme	10	2		
Backbone		3	300 ng	
Insert		1	2:1 molar ratio: for example libraries here, ~30-40 ng	

A	B	C	D	E
Nuclease-free H ₂ O	150	30		
Total	200	40		

Vortex to mix.

- 11.1 Transfer appropriate master mix into separate tubes for each reaction.

Example: if each reaction has 3 μ L backbone and 1 μ L insert, then transfer **36 μ L** to each tube.

- 11.2 To each tube, add the appropriate vector/insert pair:

For this example:

 3 μ L backbone (purified)


 1 μ L insert (purified)

Mix well and spin down.

- 11.3 Place on thermocycler and run the following program:

A	B	C
Step	T (° C)	Time (min)
1	37	5
2	16	10
3	Repeat 1-2 34 times (35 total cycles)	
4	60	5
5	10	Hold

Important: This assumes the assembly is performed with BsaI. If using a different enzyme (such as BsmBI), check the recommended temperatures from the vendor.



- 11.4 Use a PCR cleanup kit to purify each product. Elute in  10 μ L nuclease-free H₂O.

Important: using elution buffer or TE may cause electroporation to fail!




- 11.5 **Important QC step:** before electroporating libraries, transform 1 μ L of each library into chemically competent cells and plate. If no or very few colonies are observed the next day, this could suggest a failure during assembly. Further check the assembly by running a small portion on a gel.


Transformation and recovery of sublibraries

2d

- 12 Using a high-efficiency electrocompetent strain of *E. coli*, such as MegaX DH10B, prepare a transformation for each assembly:  3 μ L assembly product with  20 μ L electrocompetent cells in a 0.1 cm cuvette. Follow the specific instructions for voltage and outgrowth media corresponding to your cells and electroporator. Outgrow cells for 1 hour before proceeding.

- 13 **Essential QC step:** Count total number of transformants to ensure adequate coverage.

Prepare 5 10-fold serial dilutions: for each reaction, add  900 μ L H₂O to six 1.5 mL microcentrifuge tubes. Add  100 μ L of the outgrowth mixture to the first, then mix well and add  100 μ L of this to the second tube. Repeat for the rest of the tubes.

- 13.1 Plate  100 μ L of the last three dilutions (1:1000, 1:10000, 1:100000) on LB-agar with appropriate antibiotic. Grow overnight and count colonies the next day. Calculate the total number of transformants and determine the variant coverage per reaction. At least 50-fold coverage is **essential**. Note: the relevant measurement here is not transformation *efficiency* (i.e., cfu/ng), but simply *total transformants*!

- 13.2 **Example calculations**

Let's say you are working with oligos with fragments of 50 codons from the protein of interest. For each residue, you generated 20 substitutions (including 1 synonymous), 3

insertions, and 3 deletions, for a total of 26 different variants at each position. Then this subpool will have a total of **1300** possible variants.

In order to have 50-fold coverage of these subpool, you would need to obtain $50 \times 1300 = 65000$ total transformed bacteria. In order to get 200-fold coverage, you would need $200 \times 1300 = 2.6 \times 10^5$ total transformed bacteria.

Now suppose for two subpool transformations with 1300 variants in each, dilutions were performed as directed. The minimum number of colonies one would need to see for 50-fold coverage would be:

A	B	C
Dilution factor of plate	Minimum number of colonies	Rounded
1:10 ⁴	104	104
1:10 ⁵	10.4	11
1:10 ⁶	1.04	2

We normally average the results of each dilution in order to get a better sense of our coverage. With good transformations, we often see very dense plates at lower dilutions. To be conservative, we typically just note that there are a much larger number than necessary and leave them out of the average. On the flip side, sometimes we observe no colonies at very high dilutions. These should be included during averaging.

Suppose two subpools were cloned and the following colony counts were obtained for the dilution plates:

A	B	C	D
Reaction	Colonies (1:10 ³ plate)	Colonies (1:10 ⁴ plate)	Colonies (1:10 ⁵ plate)
Subpool 1	36	5	0
Subpool 2	Many	18	2

The total number of implied transformants in the starting outgrowth media was calculated with the following formula:

$$N = C_n \times 10^n \times 100$$

where C_n is the total number of colonies on a particular plate, 10^n accounts for the serial dilutions, and 100 accounts for the fact that only 100 μ L out of the 1 mL outgrowth media is being sampled, and only 1/10 of each dilution is being plated. If a large number of colonies are seen on a lower dilution, we typically ignore that one, but a lack of colonies is counted as a zero. Here, we would calculate the following implied transformants:


A	B	C	D	E
Reaction	Transformants	Transformants	Transformants	Average
Subpool 1	3.6e6	5e6	0	1e6
Subpool 2		2e7	2e7	2e7

Next, the total transformants per variants in each pool is calculated, using the average number of transformants.


A	B	C
Reaction	Variants in pool	Coverage
Subpool 1	10000	300
Subpool 2	1300	14000





Both these subpools would be good to proceed with.

- 13.3 Important QC step:** pick single colonies from the QC plates and use clonal sequencing to check for mutations (e.g., Sanger sequencing or whole-plasmid sequencing). We typically pick 5 colonies per subpool and expect the majority to contain a desired mutation. Too much WT could indicate problems during the backbone amplification, and too many off-target mutations could suggest a failure to amplify or purify properly. In both cases, these would be extremely deleterious to the quality of the final library.

- 14** Add the remaining outgrowth culture to  30 mL LB supplemented with appropriate antibiotic for further outgrowth in either a Falcon tube or glass culture tube. Shake until the culture reaches OD 0.6-0.7.

Note: it is important to harvest the cells in the exponential phase. This takes 4-6 hours in our experience, but may vary (including between samples in the same day).

- 15** Harvest DNA from cultures using a miniprep kit, splitting each reaction across 3 columns. Elute each column in  40 μ L elution buffer and combine elutions corresponding to a single sublibrary.

- 16 Measure each sublibrary concentration with a fluorometric method, such as Qubit. With the lowest concentration as the target concentration, prepare a dilution of each sublibrary in H₂O. Mix  2 µL of this dilution from each sublibrary to create an equimolar library pool.
- 17 Subclone library to transfer from library vector to selection vector. Depending on construct design, this may require digestion/ligation or a Golden Gate reaction.
- 18 Use PCR cleanup kit to purify reaction, and elute in  10 µL H₂O.
- 19 Using a high-efficiency electrocompetent strain of *E. coli*, such as MegaX DH10B, transform  3 µL subcloned product with  50 µL electrocompetent cells cells in a 0.1 cm cuvette. Follow the specific instructions for voltage and outgrowth media corresponding to your cells and electroporator. Outgrow cells for 1 hour before proceeding.
- 20 Repeat transformation and isolation following steps for subpool cloning and quantification as above, except perform 6 serial dilutions and plate samples at 1:10000, 1:100000, and 1:1000000 dilutions and use variant counts for the total library. Again, at least 200-fold coverage is **essential** for maintaining unbiased libraries. Pick colonies and submit for clonal sequencing as well: we typically submit ~10 samples for our final pooled library.